

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: LUMIERE

Report Number: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)

Luminaire Tested: **1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29476)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: LUMIERE
Catalog Number: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV
Description: LUMIERE LANTERRA 1003 LED ACCENT/SIGN LUMINAIRE, FLUSH LENS, SPOT
OPTIC, WHITE HOUSING.
Light Source: (1) 4000K CCT, 80 CRI LED
Ballast/Driver: ELECTRONIC DRIVER


Summary

Lumens per Lamp:	N/A	NEMA Type:	3H x 3V
Luminaire Lumens:	920.4 lumens	Max Intensity:	6989.4 candela
Efficiency:	N/A	Max Intensity Angle:	0°H x 0°V
Efficacy:	93.9 lumens/watt		
Luminous Opening:	Circular (Dia: 0.25' x H: 0')		
Beam Angle (50%):	16°H x 16°V	Field Angle (10%):	36.1°H x 36.1°V
Beam Lumens:	300.5 lumens	Field Lumens:	648.1 lumens
Beam Efficiency:	32.7%	Field Efficiency:	70.4%
Input Watts (W):	9.8		
Input Voltage (V):	120		
Input Current (A _{in}):	NR		
Voltage Rise (V):	NR		
Power Factor:	NR		
Total Harmonic Distortion (THDi):	NR		
Frequency (hertz):	60		
Stabilization Time:	NR		
Operation Time:	NR		
Ambient Temperature (°C):	NR		
Test Distance:	25 FT		

REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

Iso-Candela Plot






REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

Lumen Table

90	0.0	0.0	0.0	0.1	0.1	0.1	0.0	0.0	0.0									
80	0.0	0.0	0.0	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
70	0.0	0.0	0.0	0.0	0.0	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
60		0.0	0.0	0.0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.0	0.0				
50	0.0	0.0	0.0	0.1	0.1	0.1	0.1	0.2	0.2	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0
40		0.0	0.0	0.1	0.1	0.2	0.6	1.2	1.2	0.6	0.2	0.1	0.1	0.0				
30	0.0	0.0	0.0	0.1	0.2	1.3	6.7	11.8	11.8	6.7	1.3	0.2	0.1	0.0	0.0	0.0	0.0	0.0
20		0.0	0.0	0.1	0.5	6.4	17.1	28.9	28.9	17.1	6.4	0.5	0.1	0.0				
10	0.0	0.0	0.1	0.1	1.0	10.8	28.1	113.3	113.3	28.1	10.8	1.0	0.1	0.1	0.0	0.0	0.0	0.0
0		0.0	0.1	0.1	1.0	10.8	28.1	113.3	113.3	28.1	10.8	1.0	0.1	0.1				
-10	0.0	0.0	0.0	0.1	0.5	6.4	17.1	28.9	28.9	17.1	6.4	0.5	0.1	0.0	0.0	0.0	0.0	0.0
-20		0.0	0.0	0.1	0.2	1.3	6.7	11.8	11.8	6.7	1.3	0.2	0.1	0.0				
-30	0.0	0.0	0.0	0.1	0.1	0.2	0.6	1.2	1.2	0.6	0.2	0.1	0.1	0.0	0.0	0.0	0.0	0.0
-40		0.0	0.0	0.1	0.1	0.1	0.1	0.2	0.2	0.1	0.1	0.1	0.1	0.0				
-50	0.0	0.0	0.0	0.0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0
-60		0.0	0.0	0.0	0.0	0.0	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0				
-70	0.0	0.0	0.0	0.0	0.0	0.0	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
-80		0.0	0.0	0.0	0.0	0.0	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.0				
-90	0.0	0.0	0.0	0.1	0.1	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0


REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

Luminous Intensity Polar Plot



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

Luminous Intensity Plot



Beam:
H Angle: 16°
V Angle: 16°
Lumens: 300.5
Efficiency: 32.7%

Field:
H Angle: 36.1°
V Angle: 36.1°
Lumens: 648.1
Efficiency: 70.4%

Spill:
Lumens: 272.3
Efficiency: 29.6%

— Vertical Distribution through 0-Deg
- - Horizontal Distribution through 0-Deg



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

FIELD
 BEAM

CANDELA DISTRIBUTION:

	-90°	-88.75°	-87.5°	-86.25°	-85°	-83.75°	-82.5°	-81.25°	-80°	-78.75°	-77.5°
90°	0	0	0	0	0	0	0	0	0	0	0
88.75°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
86.25°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
83.75°	0	0	0	0	0	0	0	0	0	0	0
82.5°	0	0	0	0	0	0	0	0	0	0	0
81.25°	0	0	0	0	0	0	0	0	0	0	0
80°	0	0	0	0	0	0	0	0	0	0	0
78.75°	0	0	0	0	0	0	0	0	0	0	0
77.5°	0	0	0	0	0	0	0	0	0	0	0
76.25°	0	0	0	0	0	0	0	0	0	0	0
75°	0	0	0	0	0	0	0	0	0	0	0
73.75°	0	0	0	0	0	0	0	0	0	0	0
72.5°	0	0	0	0	0	0	0	0	0	0	0
71.25°	0	0	0	0	0	0	0	0	0	0	0
70°	0	0	0	0	0	0	0	0	0	0	0
68.75°	0	0	0	0	0	0	0	0	0	0	0
67.5°	0	0	0	0	0	0	0	0	0	0	0
66.25°	0	0	0	0	0	0	0	0	0	0	1
65°	0	0	0	0	0	0	0	0	0	0	1
63.75°	0	0	0	0	0	0	0	0	0	0	1
62.5°	0	0	0	0	0	0	0	0	0	1	1
61.25°	0	0	0	0	0	0	0	0	0	1	1
60°	0	0	0	0	0	0	0	0	0	1	1
58.75°	0	0	0	0	0	0	0	0	1	1	1
57.5°	0	0	0	0	0	0	0	0	1	1	1
56.25°	0	0	0	0	0	0	0	0	1	1	1
55°	0	0	0	0	0	0	0	1	1	1	1
53.75°	0	0	0	0	0	0	0	1	1	1	1
52.5°	0	0	0	0	0	0	0	1	1	1	1
51.25°	0	0	0	0	0	0	0	1	1	1	1
50°	0	0	0	0	0	0	0	1	1	1	1
48.75°	0	0	0	0	0	0	0	1	1	1	1
47.5°	0	0	0	0	0	0	1	1	1	1	1
46.25°	0	0	0	0	0	0	1	1	1	1	1
45°	0	0	0	0	0	0	1	1	1	1	1
43.75°	0	0	0	0	0	0	1	1	1	1	1
42.5°	0	0	0	0	0	0	1	1	1	1	1
41.25°	0	0	0	0	0	0	1	1	1	1	1
40°	0	0	0	0	0	0	1	1	1	1	1
38.75°	0	0	0	0	0	0	1	1	1	1	1
37.5°	0	0	0	0	0	0	1	1	1	1	1
36.25°	0	0	0	0	0	1	1	1	1	1	1
35°	0	0	0	0	0	1	1	1	1	1	1



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-90°	-88.75°	-87.5°	-86.25°	-85°	-83.75°	-82.5°	-81.25°	-80°	-78.75°	-77.5°
33.75°	0	0	0	0	0	1	1	1	1	1	1
32.5°	0	0	0	0	0	1	1	1	1	1	1
31.25°	0	0	0	0	0	1	1	1	1	1	1
30°	0	0	0	0	0	1	1	1	1	1	1
28.75°	0	0	0	0	0	1	1	1	1	1	1
27.5°	0	0	0	0	0	1	1	1	1	1	1
26.25°	0	0	0	0	0	1	1	1	1	1	1
25°	0	0	0	0	0	1	1	1	1	1	1
23.75°	0	0	0	0	0	1	1	1	1	1	1
22.5°	0	0	0	0	0	1	1	1	1	1	1
21.25°	0	0	0	0	0	1	1	1	1	1	1
20°	0	0	0	0	0	1	1	1	1	1	1
18.75°	0	0	0	0	0	1	1	1	1	1	1
17.5°	0	0	0	0	0	1	1	1	1	1	1
16.25°	0	0	0	0	0	1	1	1	1	1	1
15°	0	0	0	0	0	1	1	1	1	1	1
13.75°	0	0	0	0	0	1	1	1	1	1	1
12.5°	0	0	0	0	0	1	1	1	1	1	1
11.25°	0	0	0	0	0	1	1	1	1	1	1
10°	0	0	0	0	0	1	1	1	1	1	1
8.75°	0	0	0	0	0	1	1	1	1	1	1
7.5°	0	0	0	0	0	1	1	1	1	1	1
6.25°	0	0	0	0	0	1	1	1	1	1	1
5°	0	0	0	0	0	1	1	1	1	1	1
3.75°	0	0	0	0	0	1	1	1	1	1	1
2.5°	0	0	0	0	0	1	1	1	1	1	1
1.25°	0	0	0	0	0	1	1	1	1	1	1
0°	0	0	0	0	1	1	1	1	1	1	1
-1.25°	0	0	0	0	0	1	1	1	1	1	1
-2.5°	0	0	0	0	0	1	1	1	1	1	1
-3.75°	0	0	0	0	0	1	1	1	1	1	1
-5°	0	0	0	0	0	1	1	1	1	1	1
-6.25°	0	0	0	0	0	1	1	1	1	1	1
-7.5°	0	0	0	0	0	1	1	1	1	1	1
-8.75°	0	0	0	0	0	1	1	1	1	1	1
-10°	0	0	0	0	0	1	1	1	1	1	1
-11.25°	0	0	0	0	0	1	1	1	1	1	1
-12.5°	0	0	0	0	0	1	1	1	1	1	1
-13.75°	0	0	0	0	0	1	1	1	1	1	1
-15°	0	0	0	0	0	1	1	1	1	1	1
-16.25°	0	0	0	0	0	1	1	1	1	1	1
-17.5°	0	0	0	0	0	1	1	1	1	1	1
-18.75°	0	0	0	0	0	1	1	1	1	1	1
-20°	0	0	0	0	0	1	1	1	1	1	1
-21.25°	0	0	0	0	0	1	1	1	1	1	1



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-90°	-88.75°	-87.5°	-86.25°	-85°	-83.75°	-82.5°	-81.25°	-80°	-78.75°	-77.5°
-22.5°	0	0	0	0	0	1	1	1	1	1	1
-23.75°	0	0	0	0	0	1	1	1	1	1	1
-25°	0	0	0	0	0	1	1	1	1	1	1
-26.25°	0	0	0	0	0	1	1	1	1	1	1
-27.5°	0	0	0	0	0	1	1	1	1	1	1
-28.75°	0	0	0	0	0	1	1	1	1	1	1
-30°	0	0	0	0	0	1	1	1	1	1	1
-31.25°	0	0	0	0	0	1	1	1	1	1	1
-32.5°	0	0	0	0	0	1	1	1	1	1	1
-33.75°	0	0	0	0	0	1	1	1	1	1	1
-35°	0	0	0	0	0	1	1	1	1	1	1
-36.25°	0	0	0	0	0	1	1	1	1	1	1
-37.5°	0	0	0	0	0	0	1	1	1	1	1
-38.75°	0	0	0	0	0	0	1	1	1	1	1
-40°	0	0	0	0	0	0	1	1	1	1	1
-41.25°	0	0	0	0	0	0	1	1	1	1	1
-42.5°	0	0	0	0	0	0	1	1	1	1	1
-43.75°	0	0	0	0	0	0	1	1	1	1	1
-45°	0	0	0	0	0	0	1	1	1	1	1
-46.25°	0	0	0	0	0	0	1	1	1	1	1
-47.5°	0	0	0	0	0	0	1	1	1	1	1
-48.75°	0	0	0	0	0	0	0	1	1	1	1
-50°	0	0	0	0	0	0	0	1	1	1	1
-51.25°	0	0	0	0	0	0	0	1	1	1	1
-52.5°	0	0	0	0	0	0	0	1	1	1	1
-53.75°	0	0	0	0	0	0	0	1	1	1	1
-55°	0	0	0	0	0	0	0	1	1	1	1
-56.25°	0	0	0	0	0	0	0	0	1	1	1
-57.5°	0	0	0	0	0	0	0	0	1	1	1
-58.75°	0	0	0	0	0	0	0	0	1	1	1
-60°	0	0	0	0	0	0	0	0	0	1	1
-61.25°	0	0	0	0	0	0	0	0	0	1	1
-62.5°	0	0	0	0	0	0	0	0	0	1	1
-63.75°	0	0	0	0	0	0	0	0	0	0	1
-65°	0	0	0	0	0	0	0	0	0	0	1
-66.25°	0	0	0	0	0	0	0	0	0	0	1
-67.5°	0	0	0	0	0	0	0	0	0	0	0
-68.75°	0	0	0	0	0	0	0	0	0	0	0
-70°	0	0	0	0	0	0	0	0	0	0	0
-71.25°	0	0	0	0	0	0	0	0	0	0	0
-72.5°	0	0	0	0	0	0	0	0	0	0	0
-73.75°	0	0	0	0	0	0	0	0	0	0	0
-75°	0	0	0	0	0	0	0	0	0	0	0
-76.25°	0	0	0	0	0	0	0	0	0	0	0
-77.5°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-90°	-88.75°	-87.5°	-86.25°	-85°	-83.75°	-82.5°	-81.25°	-80°	-78.75°	-77.5°
-78.75°	0	0	0	0	0	0	0	0	0	0	0
-80°	0	0	0	0	0	0	0	0	0	0	0
-81.25°	0	0	0	0	0	0	0	0	0	0	0
-82.5°	0	0	0	0	0	0	0	0	0	0	0
-83.75°	0	0	0	0	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0	0	0	0	0
-86.25°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-88.75°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-76.25°	-75°	-73.75°	-72.5°	-71.25°	-70°	-68.75°	-67.5°	-66.25°	-65°	-63.75°
90°	0	0	0	0	0	0	0	0	0	0	0
88.75°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
86.25°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
83.75°	0	0	0	0	0	0	0	0	0	0	0
82.5°	0	0	0	0	0	0	0	0	0	0	0
81.25°	0	0	0	0	0	0	0	0	0	0	0
80°	0	0	0	0	0	0	0	0	0	0	0
78.75°	0	0	0	0	0	0	0	0	0	0	0
77.5°	0	0	0	0	0	0	0	0	1	1	1
76.25°	0	0	0	0	0	0	0	1	1	1	1
75°	0	0	0	0	0	1	1	1	1	1	1
73.75°	0	0	0	0	1	1	1	1	1	1	1
72.5°	0	0	0	1	1	1	1	1	1	1	1
71.25°	0	0	1	1	1	1	1	1	1	1	1
70°	0	1	1	1	1	1	1	1	1	1	1
68.75°	0	1	1	1	1	1	1	1	1	1	1
67.5°	1	1	1	1	1	1	1	1	1	1	1
66.25°	1	1	1	1	1	1	1	1	1	1	1
65°	1	1	1	1	1	1	1	1	1	1	1
63.75°	1	1	1	1	1	1	1	1	1	1	1
62.5°	1	1	1	1	1	1	1	1	1	1	1
61.25°	1	1	1	1	1	1	1	1	1	1	1
60°	1	1	1	1	1	1	1	1	1	1	1
58.75°	1	1	1	1	1	1	1	1	1	1	1
57.5°	1	1	1	1	1	1	1	1	1	1	1
56.25°	1	1	1	1	1	1	1	1	1	1	1
55°	1	1	1	1	1	1	1	1	1	1	1
53.75°	1	1	1	1	1	1	1	1	1	1	1
52.5°	1	1	1	1	1	1	1	1	1	1	1
51.25°	1	1	1	1	1	1	1	1	1	1	1
50°	1	1	1	1	1	1	1	1	1	1	1
48.75°	1	1	1	1	1	1	1	1	1	1	1
47.5°	1	1	1	1	1	1	1	1	1	1	1
46.25°	1	1	1	1	1	1	1	1	1	1	1
45°	1	1	1	1	1	1	1	1	1	1	1
43.75°	1	1	1	1	1	1	1	1	1	1	1
42.5°	1	1	1	1	1	1	1	1	1	1	1
41.25°	1	1	1	1	1	1	1	1	1	1	1
40°	1	1	1	1	1	1	1	1	1	1	2
38.75°	1	1	1	1	1	1	1	1	1	1	2
37.5°	1	1	1	1	1	1	1	1	1	2	2
36.25°	1	1	1	1	1	1	1	1	1	2	2
35°	1	1	1	1	1	1	1	1	1	2	2



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-76.25°	-75°	-73.75°	-72.5°	-71.25°	-70°	-68.75°	-67.5°	-66.25°	-65°	-63.75°
33.75°	1	1	1	1	1	1	1	1	2	2	2
32.5°	1	1	1	1	1	1	1	1	2	2	2
31.25°	1	1	1	1	1	1	1	1	2	2	2
30°	1	1	1	1	1	1	1	1	2	2	2
28.75°	1	1	1	1	1	1	1	2	2	2	2
27.5°	1	1	1	1	1	1	1	2	2	2	2
26.25°	1	1	1	1	1	1	1	2	2	2	2
25°	1	1	1	1	1	1	1	2	2	2	2
23.75°	1	1	1	1	1	1	1	2	2	2	2
22.5°	1	1	1	1	1	1	2	2	2	2	2
21.25°	1	1	1	1	1	1	2	2	2	2	2
20°	1	1	1	1	1	1	2	2	2	2	2
18.75°	1	1	1	1	1	1	2	2	2	2	2
17.5°	1	1	1	1	1	1	2	2	2	2	2
16.25°	1	1	1	1	1	1	2	2	2	2	2
15°	1	1	1	1	1	1	2	2	2	2	2
13.75°	1	1	1	1	1	1	2	2	2	2	2
12.5°	1	1	1	1	1	2	2	2	2	2	2
11.25°	1	1	1	1	1	2	2	2	2	2	2
10°	1	1	1	1	1	2	2	2	2	2	2
8.75°	1	1	1	1	1	2	2	2	2	2	2
7.5°	1	1	1	1	1	2	2	2	2	2	2
6.25°	1	1	1	1	1	2	2	2	2	2	2
5°	1	1	1	1	1	2	2	2	2	2	2
3.75°	1	1	1	1	1	2	2	2	2	2	2
2.5°	1	1	1	1	1	2	2	2	2	2	2
1.25°	1	1	1	1	1	2	2	2	2	2	2
0°	1	1	1	1	1	2	2	2	2	2	2
-1.25°	1	1	1	1	1	2	2	2	2	2	2
-2.5°	1	1	1	1	1	2	2	2	2	2	2
-3.75°	1	1	1	1	1	2	2	2	2	2	2
-5°	1	1	1	1	1	2	2	2	2	2	2
-6.25°	1	1	1	1	1	2	2	2	2	2	2
-7.5°	1	1	1	1	1	2	2	2	2	2	2
-8.75°	1	1	1	1	1	2	2	2	2	2	2
-10°	1	1	1	1	1	2	2	2	2	2	2
-11.25°	1	1	1	1	1	2	2	2	2	2	2
-12.5°	1	1	1	1	1	2	2	2	2	2	2
-13.75°	1	1	1	1	1	1	2	2	2	2	2
-15°	1	1	1	1	1	1	2	2	2	2	2
-16.25°	1	1	1	1	1	1	2	2	2	2	2
-17.5°	1	1	1	1	1	1	2	2	2	2	2
-18.75°	1	1	1	1	1	1	2	2	2	2	2
-20°	1	1	1	1	1	1	2	2	2	2	2
-21.25°	1	1	1	1	1	1	2	2	2	2	2



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-76.25°	-75°	-73.75°	-72.5°	-71.25°	-70°	-68.75°	-67.5°	-66.25°	-65°	-63.75°
-22.5°	1	1	1	1	1	1	2	2	2	2	2
-23.75°	1	1	1	1	1	1	1	2	2	2	2
-25°	1	1	1	1	1	1	1	2	2	2	2
-26.25°	1	1	1	1	1	1	1	2	2	2	2
-27.5°	1	1	1	1	1	1	1	2	2	2	2
-28.75°	1	1	1	1	1	1	1	2	2	2	2
-30°	1	1	1	1	1	1	1	1	2	2	2
-31.25°	1	1	1	1	1	1	1	1	2	2	2
-32.5°	1	1	1	1	1	1	1	1	2	2	2
-33.75°	1	1	1	1	1	1	1	1	2	2	2
-35°	1	1	1	1	1	1	1	1	1	2	2
-36.25°	1	1	1	1	1	1	1	1	1	2	2
-37.5°	1	1	1	1	1	1	1	1	1	2	2
-38.75°	1	1	1	1	1	1	1	1	1	1	2
-40°	1	1	1	1	1	1	1	1	1	1	2
-41.25°	1	1	1	1	1	1	1	1	1	1	1
-42.5°	1	1	1	1	1	1	1	1	1	1	1
-43.75°	1	1	1	1	1	1	1	1	1	1	1
-45°	1	1	1	1	1	1	1	1	1	1	1
-46.25°	1	1	1	1	1	1	1	1	1	1	1
-47.5°	1	1	1	1	1	1	1	1	1	1	1
-48.75°	1	1	1	1	1	1	1	1	1	1	1
-50°	1	1	1	1	1	1	1	1	1	1	1
-51.25°	1	1	1	1	1	1	1	1	1	1	1
-52.5°	1	1	1	1	1	1	1	1	1	1	1
-53.75°	1	1	1	1	1	1	1	1	1	1	1
-55°	1	1	1	1	1	1	1	1	1	1	1
-56.25°	1	1	1	1	1	1	1	1	1	1	1
-57.5°	1	1	1	1	1	1	1	1	1	1	1
-58.75°	1	1	1	1	1	1	1	1	1	1	1
-60°	1	1	1	1	1	1	1	1	1	1	1
-61.25°	1	1	1	1	1	1	1	1	1	1	1
-62.5°	1	1	1	1	1	1	1	1	1	1	1
-63.75°	1	1	1	1	1	1	1	1	1	1	1
-65°	1	1	1	1	1	1	1	1	1	1	1
-66.25°	1	1	1	1	1	1	1	1	1	1	1
-67.5°	1	1	1	1	1	1	1	1	1	1	1
-68.75°	0	1	1	1	1	1	1	1	1	1	1
-70°	0	1	1	1	1	1	1	1	1	1	1
-71.25°	0	0	1	1	1	1	1	1	1	1	1
-72.5°	0	0	0	1	1	1	1	1	1	1	1
-73.75°	0	0	0	0	1	1	1	1	1	1	1
-75°	0	0	0	0	0	1	1	1	1	1	1
-76.25°	0	0	0	0	0	0	0	1	1	1	1
-77.5°	0	0	0	0	0	0	0	0	1	1	1



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-76.25°	-75°	-73.75°	-72.5°	-71.25°	-70°	-68.75°	-67.5°	-66.25°	-65°	-63.75°
-78.75°	0	0	0	0	0	0	0	0	0	0	0
-80°	0	0	0	0	0	0	0	0	0	0	0
-81.25°	0	0	0	0	0	0	0	0	0	0	0
-82.5°	0	0	0	0	0	0	0	0	0	0	0
-83.75°	0	0	0	0	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0	0	0	0	0
-86.25°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-88.75°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-62.5°	-61.25°	-60°	-58.75°	-57.5°	-56.25°	-55°	-53.75°	-52.5°	-51.25°	-50°
90°	0	0	0	0	0	0	0	0	0	0	0
88.75°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
86.25°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
83.75°	0	0	0	0	0	0	0	0	0	0	0
82.5°	0	0	0	0	0	0	0	0	0	0	0
81.25°	0	0	0	0	0	0	1	1	1	1	1
80°	0	0	0	1	1	1	1	1	1	1	1
78.75°	1	1	1	1	1	1	1	1	1	1	1
77.5°	1	1	1	1	1	1	1	1	1	1	1
76.25°	1	1	1	1	1	1	1	1	1	1	1
75°	1	1	1	1	1	1	1	1	1	1	1
73.75°	1	1	1	1	1	1	1	1	1	1	1
72.5°	1	1	1	1	1	1	1	1	1	1	1
71.25°	1	1	1	1	1	1	1	1	1	1	1
70°	1	1	1	1	1	1	1	1	1	1	1
68.75°	1	1	1	1	1	1	1	1	1	1	1
67.5°	1	1	1	1	1	1	1	1	1	1	1
66.25°	1	1	1	1	1	1	1	1	1	1	1
65°	1	1	1	1	1	1	1	1	1	1	1
63.75°	1	1	1	1	1	1	1	1	1	1	1
62.5°	1	1	1	1	1	1	1	1	1	1	1
61.25°	1	1	1	1	1	1	1	1	1	1	1
60°	1	1	1	1	1	1	1	1	1	1	1
58.75°	1	1	1	1	1	1	1	1	1	1	1
57.5°	1	1	1	1	1	1	1	1	1	2	2
56.25°	1	1	1	1	1	1	1	1	2	2	2
55°	1	1	1	1	1	1	1	2	2	2	2
53.75°	1	1	1	1	1	1	2	2	2	2	2
52.5°	1	1	1	1	1	2	2	2	2	2	2
51.25°	1	1	1	1	2	2	2	2	2	2	2
50°	1	1	1	1	2	2	2	2	2	2	2
48.75°	1	1	1	2	2	2	2	2	2	2	2
47.5°	1	1	2	2	2	2	2	2	2	2	2
46.25°	1	1	2	2	2	2	2	2	2	2	2
45°	1	2	2	2	2	2	2	2	2	2	2
43.75°	1	2	2	2	2	2	2	2	2	2	2
42.5°	2	2	2	2	2	2	2	2	2	2	2
41.25°	2	2	2	2	2	2	2	2	2	2	2
40°	2	2	2	2	2	2	2	2	2	2	3
38.75°	2	2	2	2	2	2	2	2	2	3	3
37.5°	2	2	2	2	2	2	2	2	2	3	3
36.25°	2	2	2	2	2	2	2	2	3	3	3
35°	2	2	2	2	2	2	2	2	3	3	3



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-62.5°	-61.25°	-60°	-58.75°	-57.5°	-56.25°	-55°	-53.75°	-52.5°	-51.25°	-50°
33.75°	2	2	2	2	2	2	2	3	3	3	3
32.5°	2	2	2	2	2	2	2	3	3	3	3
31.25°	2	2	2	2	2	2	3	3	3	3	3
30°	2	2	2	2	2	2	3	3	3	3	3
28.75°	2	2	2	2	2	3	3	3	3	3	3
27.5°	2	2	2	2	2	3	3	3	3	3	3
26.25°	2	2	2	2	2	3	3	3	3	3	3
25°	2	2	2	2	3	3	3	3	3	3	3
23.75°	2	2	2	2	3	3	3	3	3	3	3
22.5°	2	2	2	2	3	3	3	3	3	3	3
21.25°	2	2	2	2	3	3	3	3	3	3	3
20°	2	2	2	3	3	3	3	3	3	3	3
18.75°	2	2	2	3	3	3	3	3	3	3	3
17.5°	2	2	2	3	3	3	3	3	3	3	3
16.25°	2	2	2	3	3	3	3	3	3	3	3
15°	2	2	2	3	3	3	3	3	3	3	3
13.75°	2	2	3	3	3	3	3	3	3	3	3
12.5°	2	2	3	3	3	3	3	3	3	3	3
11.25°	2	2	3	3	3	3	3	3	3	3	3
10°	2	2	3	3	3	3	3	3	3	3	3
8.75°	2	2	3	3	3	3	3	3	3	3	3
7.5°	2	2	3	3	3	3	3	3	3	3	3
6.25°	2	2	3	3	3	3	3	3	3	3	3
5°	2	2	3	3	3	3	3	3	3	3	3
3.75°	2	2	3	3	3	3	3	3	3	3	3
2.5°	2	2	3	3	3	3	3	3	3	3	3
1.25°	2	2	3	3	3	3	3	3	3	3	3
0°	2	2	3	3	3	3	3	3	3	3	3
-1.25°	2	2	3	3	3	3	3	3	3	3	3
-2.5°	2	2	3	3	3	3	3	3	3	3	3
-3.75°	2	2	3	3	3	3	3	3	3	3	3
-5°	2	2	3	3	3	3	3	3	3	3	3
-6.25°	2	2	3	3	3	3	3	3	3	3	3
-7.5°	2	2	3	3	3	3	3	3	3	3	3
-8.75°	2	2	3	3	3	3	3	3	3	3	3
-10°	2	2	3	3	3	3	3	3	3	3	3
-11.25°	2	2	3	3	3	3	3	3	3	3	3
-12.5°	2	2	3	3	3	3	3	3	3	3	3
-13.75°	2	2	3	3	3	3	3	3	3	3	3
-15°	2	2	2	3	3	3	3	3	3	3	3
-16.25°	2	2	2	3	3	3	3	3	3	3	3
-17.5°	2	2	2	3	3	3	3	3	3	3	3
-18.75°	2	2	2	3	3	3	3	3	3	3	3
-20°	2	2	2	3	3	3	3	3	3	3	3
-21.25°	2	2	2	2	3	3	3	3	3	3	3



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-62.5°	-61.25°	-60°	-58.75°	-57.5°	-56.25°	-55°	-53.75°	-52.5°	-51.25°	-50°
-22.5°	2	2	2	2	3	3	3	3	3	3	3
-23.75°	2	2	2	2	3	3	3	3	3	3	3
-25°	2	2	2	2	3	3	3	3	3	3	3
-26.25°	2	2	2	2	2	3	3	3	3	3	3
-27.5°	2	2	2	2	2	3	3	3	3	3	3
-28.75°	2	2	2	2	2	3	3	3	3	3	3
-30°	2	2	2	2	2	2	3	3	3	3	3
-31.25°	2	2	2	2	2	2	3	3	3	3	3
-32.5°	2	2	2	2	2	2	2	3	3	3	3
-33.75°	2	2	2	2	2	2	2	3	3	3	3
-35°	2	2	2	2	2	2	2	2	3	3	3
-36.25°	2	2	2	2	2	2	2	2	3	3	3
-37.5°	2	2	2	2	2	2	2	2	2	3	3
-38.75°	2	2	2	2	2	2	2	2	2	3	3
-40°	2	2	2	2	2	2	2	2	2	2	3
-41.25°	2	2	2	2	2	2	2	2	2	2	2
-42.5°	2	2	2	2	2	2	2	2	2	2	2
-43.75°	1	2	2	2	2	2	2	2	2	2	2
-45°	1	2	2	2	2	2	2	2	2	2	2
-46.25°	1	1	2	2	2	2	2	2	2	2	2
-47.5°	1	1	2	2	2	2	2	2	2	2	2
-48.75°	1	1	1	2	2	2	2	2	2	2	2
-50°	1	1	1	1	2	2	2	2	2	2	2
-51.25°	1	1	1	1	2	2	2	2	2	2	2
-52.5°	1	1	1	1	1	2	2	2	2	2	2
-53.75°	1	1	1	1	1	1	2	2	2	2	2
-55°	1	1	1	1	1	1	1	2	2	2	2
-56.25°	1	1	1	1	1	1	1	1	2	2	2
-57.5°	1	1	1	1	1	1	1	1	1	2	2
-58.75°	1	1	1	1	1	1	1	1	1	1	1
-60°	1	1	1	1	1	1	1	1	1	1	1
-61.25°	1	1	1	1	1	1	1	1	1	1	1
-62.5°	1	1	1	1	1	1	1	1	1	1	1
-63.75°	1	1	1	1	1	1	1	1	1	1	1
-65°	1	1	1	1	1	1	1	1	1	1	1
-66.25°	1	1	1	1	1	1	1	1	1	1	1
-67.5°	1	1	1	1	1	1	1	1	1	1	1
-68.75°	1	1	1	1	1	1	1	1	1	1	1
-70°	1	1	1	1	1	1	1	1	1	1	1
-71.25°	1	1	1	1	1	1	1	1	1	1	1
-72.5°	1	1	1	1	1	1	1	1	1	1	1
-73.75°	1	1	1	1	1	1	1	1	1	1	1
-75°	1	1	1	1	1	1	1	1	1	1	1
-76.25°	1	1	1	1	1	1	1	1	1	1	1
-77.5°	1	1	1	1	1	1	1	1	1	1	1



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-62.5°	-61.25°	-60°	-58.75°	-57.5°	-56.25°	-55°	-53.75°	-52.5°	-51.25°	-50°
-78.75°	1	1	1	1	1	1	1	1	1	1	1
-80°	0	0	0	1	1	1	1	1	1	1	1
-81.25°	0	0	0	0	0	0	1	1	1	1	1
-82.5°	0	0	0	0	0	0	0	0	0	0	0
-83.75°	0	0	0	0	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0	0	0	0	0
-86.25°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-88.75°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-48.75°	-47.5°	-46.25°	-45°	-43.75°	-42.5°	-41.25°	-40°	-38.75°	-37.5°	-36.25°
90°	0	0	0	0	0	0	0	0	0	0	0
88.75°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
86.25°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
83.75°	0	0	0	0	0	0	0	0	0	0	1
82.5°	0	1	1	1	1	1	1	1	1	1	1
81.25°	1	1	1	1	1	1	1	1	1	1	1
80°	1	1	1	1	1	1	1	1	1	1	1
78.75°	1	1	1	1	1	1	1	1	1	1	1
77.5°	1	1	1	1	1	1	1	1	1	1	1
76.25°	1	1	1	1	1	1	1	1	1	1	1
75°	1	1	1	1	1	1	1	1	1	1	1
73.75°	1	1	1	1	1	1	1	1	1	1	1
72.5°	1	1	1	1	1	1	1	1	1	1	1
71.25°	1	1	1	1	1	1	1	1	1	1	1
70°	1	1	1	1	1	1	1	1	1	1	1
68.75°	1	1	1	1	1	1	1	1	1	1	1
67.5°	1	1	1	1	1	1	1	1	1	1	1
66.25°	1	1	1	1	1	1	1	1	1	1	1
65°	1	1	1	1	1	1	1	1	1	2	2
63.75°	1	1	1	1	1	1	1	2	2	2	2
62.5°	1	1	1	1	1	2	2	2	2	2	2
61.25°	1	1	1	2	2	2	2	2	2	2	2
60°	1	2	2	2	2	2	2	2	2	2	2
58.75°	2	2	2	2	2	2	2	2	2	2	2
57.5°	2	2	2	2	2	2	2	2	2	2	2
56.25°	2	2	2	2	2	2	2	2	2	2	2
55°	2	2	2	2	2	2	2	2	2	2	2
53.75°	2	2	2	2	2	2	2	2	2	2	2
52.5°	2	2	2	2	2	2	2	2	2	2	3
51.25°	2	2	2	2	2	2	2	2	3	3	3
50°	2	2	2	2	2	2	2	3	3	3	3
48.75°	2	2	2	2	2	3	3	3	3	3	3
47.5°	2	2	2	2	3	3	3	3	3	3	3
46.25°	2	2	2	3	3	3	3	3	3	3	3
45°	2	2	3	3	3	3	3	3	3	3	3
43.75°	2	3	3	3	3	3	3	3	3	3	3
42.5°	3	3	3	3	3	3	3	3	3	3	3
41.25°	3	3	3	3	3	3	3	3	3	3	3
40°	3	3	3	3	3	3	3	3	3	3	3
38.75°	3	3	3	3	3	3	3	3	3	3	3
37.5°	3	3	3	3	3	3	3	3	3	3	3
36.25°	3	3	3	3	3	3	3	3	3	3	3
35°	3	3	3	3	3	3	3	3	3	3	4



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-48.75°	-47.5°	-46.25°	-45°	-43.75°	-42.5°	-41.25°	-40°	-38.75°	-37.5°	-36.25°
33.75°	3	3	3	3	3	3	3	3	3	4	4
32.5°	3	3	3	3	3	3	3	3	4	4	4
31.25°	3	3	3	3	3	3	3	3	4	4	4
30°	3	3	3	3	3	3	3	4	4	4	5
28.75°	3	3	3	3	3	3	4	4	4	4	5
27.5°	3	3	3	3	3	3	4	4	4	5	5
26.25°	3	3	3	3	3	4	4	4	5	5	5
25°	3	3	3	3	3	4	4	4	5	5	6
23.75°	3	3	3	3	4	4	4	5	5	6	6
22.5°	3	3	3	3	4	4	4	5	5	6	8
21.25°	3	3	3	4	4	4	5	5	6	6	9
20°	3	3	3	4	4	4	5	5	6	8	10
18.75°	3	3	3	4	4	5	5	6	6	9	11
17.5°	3	3	4	4	4	5	5	6	7	10	12
16.25°	3	3	4	4	4	5	5	6	8	11	13
15°	3	3	4	4	5	5	6	7	9	12	14
13.75°	3	4	4	4	5	5	6	7	10	13	15
12.5°	3	4	4	4	5	5	6	8	11	13	16
11.25°	3	4	4	4	5	5	6	9	12	14	16
10°	3	4	4	5	5	6	7	9	12	15	17
8.75°	3	4	4	5	5	6	7	10	13	15	18
7.5°	3	4	4	5	5	6	8	11	13	16	18
6.25°	3	4	4	5	5	6	8	11	14	16	19
5°	4	4	4	5	5	6	8	11	14	16	19
3.75°	4	4	4	5	5	6	9	12	14	16	20
2.5°	4	4	4	5	5	6	9	12	14	17	20
1.25°	4	4	4	5	5	6	9	12	14	17	20
0°	4	4	4	5	5	6	9	12	14	17	20
-1.25°	4	4	4	5	5	6	9	12	14	17	20
-2.5°	4	4	4	5	5	6	9	12	14	17	20
-3.75°	4	4	4	5	5	6	9	12	14	16	20
-5°	4	4	4	5	5	6	8	11	14	16	19
-6.25°	3	4	4	5	5	6	8	11	14	16	19
-7.5°	3	4	4	5	5	6	8	11	13	16	18
-8.75°	3	4	4	5	5	6	7	10	13	15	18
-10°	3	4	4	5	5	6	7	9	12	15	17
-11.25°	3	4	4	4	5	5	6	9	12	14	16
-12.5°	3	4	4	4	5	5	6	8	11	13	16
-13.75°	3	4	4	4	5	5	6	7	10	13	15
-15°	3	3	4	4	5	5	6	7	9	12	14
-16.25°	3	3	4	4	4	5	5	6	8	11	13
-17.5°	3	3	4	4	4	5	5	6	7	10	12
-18.75°	3	3	3	4	4	5	5	6	6	9	11
-20°	3	3	3	4	4	4	5	5	6	8	10
-21.25°	3	3	3	4	4	4	5	5	6	6	9



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-48.75°	-47.5°	-46.25°	-45°	-43.75°	-42.5°	-41.25°	-40°	-38.75°	-37.5°	-36.25°
-22.5°	3	3	3	3	4	4	4	5	5	6	8
-23.75°	3	3	3	3	4	4	4	5	5	6	6
-25°	3	3	3	3	3	4	4	4	5	5	6
-26.25°	3	3	3	3	3	4	4	4	5	5	5
-27.5°	3	3	3	3	3	3	4	4	4	5	5
-28.75°	3	3	3	3	3	3	4	4	4	4	5
-30°	3	3	3	3	3	3	3	4	4	4	5
-31.25°	3	3	3	3	3	3	3	3	4	4	4
-32.5°	3	3	3	3	3	3	3	3	4	4	4
-33.75°	3	3	3	3	3	3	3	3	3	4	4
-35°	3	3	3	3	3	3	3	3	3	3	4
-36.25°	3	3	3	3	3	3	3	3	3	3	3
-37.5°	3	3	3	3	3	3	3	3	3	3	3
-38.75°	3	3	3	3	3	3	3	3	3	3	3
-40°	3	3	3	3	3	3	3	3	3	3	3
-41.25°	3	3	3	3	3	3	3	3	3	3	3
-42.5°	3	3	3	3	3	3	3	3	3	3	3
-43.75°	2	3	3	3	3	3	3	3	3	3	3
-45°	2	2	3	3	3	3	3	3	3	3	3
-46.25°	2	2	2	3	3	3	3	3	3	3	3
-47.5°	2	2	2	2	3	3	3	3	3	3	3
-48.75°	2	2	2	2	2	3	3	3	3	3	3
-50°	2	2	2	2	2	2	2	3	3	3	3
-51.25°	2	2	2	2	2	2	2	2	3	3	3
-52.5°	2	2	2	2	2	2	2	2	2	2	3
-53.75°	2	2	2	2	2	2	2	2	2	2	2
-55°	2	2	2	2	2	2	2	2	2	2	2
-56.25°	2	2	2	2	2	2	2	2	2	2	2
-57.5°	2	2	2	2	2	2	2	2	2	2	2
-58.75°	2	2	2	2	2	2	2	2	2	2	2
-60°	1	2	2	2	2	2	2	2	2	2	2
-61.25°	1	1	1	2	2	2	2	2	2	2	2
-62.5°	1	1	1	1	1	2	2	2	2	2	2
-63.75°	1	1	1	1	1	1	1	2	2	2	2
-65°	1	1	1	1	1	1	1	1	1	2	2
-66.25°	1	1	1	1	1	1	1	1	1	1	1
-67.5°	1	1	1	1	1	1	1	1	1	1	1
-68.75°	1	1	1	1	1	1	1	1	1	1	1
-70°	1	1	1	1	1	1	1	1	1	1	1
-71.25°	1	1	1	1	1	1	1	1	1	1	1
-72.5°	1	1	1	1	1	1	1	1	1	1	1
-73.75°	1	1	1	1	1	1	1	1	1	1	1
-75°	1	1	1	1	1	1	1	1	1	1	1
-76.25°	1	1	1	1	1	1	1	1	1	1	1
-77.5°	1	1	1	1	1	1	1	1	1	1	1



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-48.75°	-47.5°	-46.25°	-45°	-43.75°	-42.5°	-41.25°	-40°	-38.75°	-37.5°	-36.25°
-78.75°	1	1	1	1	1	1	1	1	1	1	1
-80°	1	1	1	1	1	1	1	1	1	1	1
-81.25°	1	1	1	1	1	1	1	1	1	1	1
-82.5°	0	1	1	1	1	1	1	1	1	1	1
-83.75°	0	0	0	0	0	0	0	0	0	0	1
-85°	0	0	0	0	0	0	0	0	0	0	0
-86.25°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-88.75°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-35°	-33.75°	-32.5°	-31.25°	-30°	-28.75°	-27.5°	-26.25°	-25°	-23.75°	-22.5°
90°	0	0	0	0	0	0	0	0	0	0	0
88.75°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
86.25°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
83.75°	1	1	1	1	1	1	1	1	1	1	1
82.5°	1	1	1	1	1	1	1	1	1	1	1
81.25°	1	1	1	1	1	1	1	1	1	1	1
80°	1	1	1	1	1	1	1	1	1	1	1
78.75°	1	1	1	1	1	1	1	1	1	1	1
77.5°	1	1	1	1	1	1	1	1	1	1	1
76.25°	1	1	1	1	1	1	1	1	1	1	1
75°	1	1	1	1	1	1	1	1	1	1	1
73.75°	1	1	1	1	1	1	1	1	1	1	1
72.5°	1	1	1	1	1	1	1	1	1	1	1
71.25°	1	1	1	1	1	1	1	1	1	1	1
70°	1	1	1	1	1	1	1	1	1	1	1
68.75°	1	1	1	1	1	1	1	1	1	1	2
67.5°	1	1	1	1	1	2	2	2	2	2	2
66.25°	1	2	2	2	2	2	2	2	2	2	2
65°	2	2	2	2	2	2	2	2	2	2	2
63.75°	2	2	2	2	2	2	2	2	2	2	2
62.5°	2	2	2	2	2	2	2	2	2	2	2
61.25°	2	2	2	2	2	2	2	2	2	2	2
60°	2	2	2	2	2	2	2	2	2	2	2
58.75°	2	2	2	2	2	2	2	2	2	2	2
57.5°	2	2	2	2	2	2	2	2	3	3	3
56.25°	2	2	2	2	2	3	3	3	3	3	3
55°	2	2	2	3	3	3	3	3	3	3	3
53.75°	2	3	3	3	3	3	3	3	3	3	3
52.5°	3	3	3	3	3	3	3	3	3	3	3
51.25°	3	3	3	3	3	3	3	3	3	3	3
50°	3	3	3	3	3	3	3	3	3	3	3
48.75°	3	3	3	3	3	3	3	3	3	3	3
47.5°	3	3	3	3	3	3	3	3	3	3	3
46.25°	3	3	3	3	3	3	3	3	3	3	3
45°	3	3	3	3	3	3	3	3	3	3	3
43.75°	3	3	3	3	3	3	3	3	3	4	4
42.5°	3	3	3	3	3	3	3	4	4	4	4
41.25°	3	3	3	3	3	4	4	4	4	4	4
40°	3	3	3	3	4	4	4	4	4	5	5
38.75°	3	3	4	4	4	4	4	5	5	5	5
37.5°	3	4	4	4	4	4	5	5	5	6	6
36.25°	4	4	4	4	5	5	5	5	6	6	8
35°	4	4	4	5	5	5	6	6	7	9	10



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-35°	-33.75°	-32.5°	-31.25°	-30°	-28.75°	-27.5°	-26.25°	-25°	-23.75°	-22.5°
33.75°	4	4	5	5	5	6	6	8	9	11	12
32.5°	4	5	5	5	6	6	8	10	12	13	14
31.25°	5	5	5	6	7	8	10	12	13	15	16
30°	5	5	6	7	9	10	12	14	15	17	18
28.75°	5	6	6	8	10	12	14	16	17	19	21
27.5°	6	6	8	10	12	14	16	17	19	21	24
26.25°	6	8	10	12	14	16	17	20	22	25	35
25°	7	9	12	13	15	17	19	22	26	36	46
23.75°	9	11	13	15	17	19	21	25	36	47	64
22.5°	10	12	14	16	18	21	24	35	46	64	101
21.25°	11	13	15	18	20	23	33	44	60	99	137
20°	13	15	17	19	22	29	41	53	92	133	175
18.75°	14	16	18	21	24	37	49	81	123	166	219
17.5°	15	17	20	22	32	44	66	110	153	206	263
16.25°	16	18	21	25	38	52	92	137	188	246	306
15°	16	19	22	31	45	70	117	163	223	285	345
13.75°	17	20	23	37	51	92	140	194	257	321	380
12.5°	18	21	28	43	63	113	161	224	290	354	412
11.25°	19	22	33	47	82	132	187	252	320	383	440
10°	20	23	37	52	98	149	210	278	346	408	462
8.75°	21	27	41	61	113	165	231	302	369	430	482
7.5°	21	30	44	73	125	182	251	322	389	448	496
6.25°	22	32	47	84	136	197	267	339	405	463	507
5°	22	35	50	92	145	209	281	353	418	474	517
3.75°	23	36	51	99	152	219	292	363	428	484	523
2.5°	23	38	53	104	158	226	300	371	435	489	528
1.25°	23	38	53	107	161	230	304	375	440	492	530
0°	23	39	54	108	162	232	306	377	441	493	531
-1.25°	23	38	53	107	161	230	304	375	440	492	530
-2.5°	23	38	53	104	158	226	300	371	435	489	528
-3.75°	23	36	51	99	152	219	292	363	428	484	523
-5°	22	35	50	92	145	209	281	353	418	474	517
-6.25°	22	32	47	84	136	197	267	339	405	463	507
-7.5°	21	30	44	73	125	182	251	322	389	448	496
-8.75°	21	27	41	61	113	165	231	302	369	430	482
-10°	20	23	37	52	98	149	210	278	346	408	462
-11.25°	19	22	33	47	82	132	187	252	320	383	440
-12.5°	18	21	28	43	63	113	161	224	290	354	412
-13.75°	17	20	23	37	51	92	140	194	257	321	380
-15°	16	19	22	31	45	70	117	163	223	285	345
-16.25°	16	18	21	25	38	52	92	137	188	246	306
-17.5°	15	17	20	22	32	44	66	110	153	206	263
-18.75°	14	16	18	21	24	37	49	81	123	166	219
-20°	13	15	17	19	22	29	41	53	92	133	175
-21.25°	11	13	15	18	20	23	33	44	60	99	137



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-35°	-33.75°	-32.5°	-31.25°	-30°	-28.75°	-27.5°	-26.25°	-25°	-23.75°	-22.5°
-22.5°	10	12	14	16	18	21	24	35	46	64	101
-23.75°	9	11	13	15	17	19	21	25	36	47	64
-25°	7	9	12	13	15	17	19	22	26	36	46
-26.25°	6	8	10	12	14	16	17	20	22	25	35
-27.5°	6	6	8	10	12	14	16	17	19	21	24
-28.75°	5	6	6	8	10	12	14	16	17	19	21
-30°	5	5	6	7	9	10	12	14	15	17	18
-31.25°	5	5	5	6	7	8	10	12	13	15	16
-32.5°	4	5	5	5	6	6	8	10	12	13	14
-33.75°	4	4	5	5	5	6	6	8	9	11	12
-35°	4	4	4	5	5	5	6	6	7	9	10
-36.25°	4	4	4	4	5	5	5	5	6	6	8
-37.5°	3	4	4	4	4	4	5	5	5	6	6
-38.75°	3	3	4	4	4	4	4	5	5	5	5
-40°	3	3	3	3	4	4	4	4	4	5	5
-41.25°	3	3	3	3	3	4	4	4	4	4	4
-42.5°	3	3	3	3	3	3	3	4	4	4	4
-43.75°	3	3	3	3	3	3	3	3	3	4	4
-45°	3	3	3	3	3	3	3	3	3	3	3
-46.25°	3	3	3	3	3	3	3	3	3	3	3
-47.5°	3	3	3	3	3	3	3	3	3	3	3
-48.75°	3	3	3	3	3	3	3	3	3	3	3
-50°	3	3	3	3	3	3	3	3	3	3	3
-51.25°	3	3	3	3	3	3	3	3	3	3	3
-52.5°	3	3	3	3	3	3	3	3	3	3	3
-53.75°	2	3	3	3	3	3	3	3	3	3	3
-55°	2	2	2	3	3	3	3	3	3	3	3
-56.25°	2	2	2	2	2	3	3	3	3	3	3
-57.5°	2	2	2	2	2	2	2	2	3	3	3
-58.75°	2	2	2	2	2	2	2	2	2	2	2
-60°	2	2	2	2	2	2	2	2	2	2	2
-61.25°	2	2	2	2	2	2	2	2	2	2	2
-62.5°	2	2	2	2	2	2	2	2	2	2	2
-63.75°	2	2	2	2	2	2	2	2	2	2	2
-65°	2	2	2	2	2	2	2	2	2	2	2
-66.25°	1	2	2	2	2	2	2	2	2	2	2
-67.5°	1	1	1	1	1	2	2	2	2	2	2
-68.75°	1	1	1	1	1	1	1	1	1	1	2
-70°	1	1	1	1	1	1	1	1	1	1	1
-71.25°	1	1	1	1	1	1	1	1	1	1	1
-72.5°	1	1	1	1	1	1	1	1	1	1	1
-73.75°	1	1	1	1	1	1	1	1	1	1	1
-75°	1	1	1	1	1	1	1	1	1	1	1
-76.25°	1	1	1	1	1	1	1	1	1	1	1
-77.5°	1	1	1	1	1	1	1	1	1	1	1



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-35°	-33.75°	-32.5°	-31.25°	-30°	-28.75°	-27.5°	-26.25°	-25°	-23.75°	-22.5°
-78.75°	1	1	1	1	1	1	1	1	1	1	1
-80°	1	1	1	1	1	1	1	1	1	1	1
-81.25°	1	1	1	1	1	1	1	1	1	1	1
-82.5°	1	1	1	1	1	1	1	1	1	1	1
-83.75°	1	1	1	1	1	1	1	1	1	1	1
-85°	0	0	0	0	0	0	0	0	0	0	0
-86.25°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-88.75°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-21.25°	-20°	-18.75°	-17.5°	-16.25°	-15°	-13.75°	-12.5°	-11.25°	-10°	-8.75°
90°	0	0	0	0	0	0	0	0	0	0	0
88.75°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
86.25°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
83.75°	1	1	1	1	1	1	1	1	1	1	1
82.5°	1	1	1	1	1	1	1	1	1	1	1
81.25°	1	1	1	1	1	1	1	1	1	1	1
80°	1	1	1	1	1	1	1	1	1	1	1
78.75°	1	1	1	1	1	1	1	1	1	1	1
77.5°	1	1	1	1	1	1	1	1	1	1	1
76.25°	1	1	1	1	1	1	1	1	1	1	1
75°	1	1	1	1	1	1	1	1	1	1	1
73.75°	1	1	1	1	1	1	1	1	1	1	1
72.5°	1	1	1	1	1	1	1	1	1	1	1
71.25°	1	1	1	1	1	1	1	1	1	1	1
70°	1	1	1	1	1	1	1	2	2	2	2
68.75°	2	2	2	2	2	2	2	2	2	2	2
67.5°	2	2	2	2	2	2	2	2	2	2	2
66.25°	2	2	2	2	2	2	2	2	2	2	2
65°	2	2	2	2	2	2	2	2	2	2	2
63.75°	2	2	2	2	2	2	2	2	2	2	2
62.5°	2	2	2	2	2	2	2	2	2	2	2
61.25°	2	2	2	2	2	2	2	2	2	2	2
60°	2	2	2	2	2	2	3	3	3	3	3
58.75°	2	3	3	3	3	3	3	3	3	3	3
57.5°	3	3	3	3	3	3	3	3	3	3	3
56.25°	3	3	3	3	3	3	3	3	3	3	3
55°	3	3	3	3	3	3	3	3	3	3	3
53.75°	3	3	3	3	3	3	3	3	3	3	3
52.5°	3	3	3	3	3	3	3	3	3	3	3
51.25°	3	3	3	3	3	3	3	3	3	3	3
50°	3	3	3	3	3	3	3	3	3	3	3
48.75°	3	3	3	3	3	3	3	3	3	3	3
47.5°	3	3	3	3	3	3	4	4	4	4	4
46.25°	3	3	3	4	4	4	4	4	4	4	4
45°	4	4	4	4	4	4	4	4	4	5	5
43.75°	4	4	4	4	4	5	5	5	5	5	5
42.5°	4	4	5	5	5	5	5	5	5	6	6
41.25°	5	5	5	5	5	6	6	6	6	7	7
40°	5	5	6	6	6	7	7	8	9	9	10
38.75°	6	6	6	7	8	9	10	11	12	12	13
37.5°	6	8	9	10	11	12	13	13	14	15	15
36.25°	9	10	11	12	13	14	15	16	16	17	18
35°	11	13	14	15	16	16	17	18	19	20	21



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-21.25°	-20°	-18.75°	-17.5°	-16.25°	-15°	-13.75°	-12.5°	-11.25°	-10°	-8.75°
33.75°	13	15	16	17	18	19	20	21	22	23	27
32.5°	15	17	18	20	21	22	23	28	33	37	41
31.25°	18	19	21	22	25	31	37	43	47	52	61
30°	20	22	24	32	38	45	51	63	82	98	113
28.75°	23	29	37	44	52	70	92	113	132	149	165
27.5°	33	41	49	66	92	117	140	161	187	210	231
26.25°	44	53	81	110	137	163	194	224	252	278	302
25°	60	92	123	153	188	223	257	290	320	346	369
23.75°	99	133	166	206	246	285	321	354	383	408	430
22.5°	137	175	219	263	306	345	380	412	440	462	482
21.25°	178	225	273	320	362	400	434	463	487	505	520
20°	225	277	327	372	413	449	480	503	522	538	553
18.75°	273	327	375	419	458	490	514	534	553	571	589
17.5°	320	372	419	461	494	520	542	564	586	608	630
16.25°	362	413	458	494	522	546	571	597	624	650	681
15°	400	449	490	520	546	573	602	633	667	703	740
13.75°	434	480	514	542	571	602	637	676	718	762	817
12.5°	463	503	534	564	597	633	676	723	777	842	923
11.25°	487	522	553	586	624	667	718	777	853	946	1051
10°	505	538	571	608	650	703	762	842	946	1066	1212
8.75°	520	553	589	630	681	740	817	923	1051	1212	1414
7.5°	532	567	606	651	709	779	878	1007	1170	1384	1661
6.25°	542	579	621	673	736	820	938	1088	1294	1572	1946
5°	551	590	635	692	759	860	998	1178	1427	1771	2252
3.75°	559	599	646	707	784	897	1047	1251	1547	1976	2554
2.5°	564	605	655	719	803	925	1085	1320	1656	2144	2787
1.25°	567	609	661	727	814	941	1114	1363	1722	2248	2945
0°	568	611	663	729	817	947	1124	1378	1745	2283	3001
-1.25°	567	609	661	727	814	941	1114	1363	1722	2248	2945
-2.5°	564	605	655	719	803	925	1085	1320	1656	2144	2787
-3.75°	559	599	646	707	784	897	1047	1251	1547	1976	2554
-5°	551	590	635	692	759	860	998	1178	1427	1771	2252
-6.25°	542	579	621	673	736	820	938	1088	1294	1572	1946
-7.5°	532	567	606	651	709	779	878	1007	1170	1384	1661
-8.75°	520	553	589	630	681	740	817	923	1051	1212	1414
-10°	505	538	571	608	650	703	762	842	946	1066	1212
-11.25°	487	522	553	586	624	667	718	777	853	946	1051
-12.5°	463	503	534	564	597	633	676	723	777	842	923
-13.75°	434	480	514	542	571	602	637	676	718	762	817
-15°	400	449	490	520	546	573	602	633	667	703	740
-16.25°	362	413	458	494	522	546	571	597	624	650	681
-17.5°	320	372	419	461	494	520	542	564	586	608	630
-18.75°	273	327	375	419	458	490	514	534	553	571	589
-20°	225	277	327	372	413	449	480	503	522	538	553
-21.25°	178	225	273	320	362	400	434	463	487	505	520



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-21.25°	-20°	-18.75°	-17.5°	-16.25°	-15°	-13.75°	-12.5°	-11.25°	-10°	-8.75°
-22.5°	137	175	219	263	306	345	380	412	440	462	482
-23.75°	99	133	166	206	246	285	321	354	383	408	430
-25°	60	92	123	153	188	223	257	290	320	346	369
-26.25°	44	53	81	110	137	163	194	224	252	278	302
-27.5°	33	41	49	66	92	117	140	161	187	210	231
-28.75°	23	29	37	44	52	70	92	113	132	149	165
-30°	20	22	24	32	38	45	51	63	82	98	113
-31.25°	18	19	21	22	25	31	37	43	47	52	61
-32.5°	15	17	18	20	21	22	23	28	33	37	41
-33.75°	13	15	16	17	18	19	20	21	22	23	27
-35°	11	13	14	15	16	16	17	18	19	20	21
-36.25°	9	10	11	12	13	14	15	16	16	17	18
-37.5°	6	8	9	10	11	12	13	13	14	15	15
-38.75°	6	6	6	7	8	9	10	11	12	12	13
-40°	5	5	6	6	6	7	7	8	9	9	10
-41.25°	5	5	5	5	5	6	6	6	6	7	7
-42.5°	4	4	5	5	5	5	5	5	5	6	6
-43.75°	4	4	4	4	4	5	5	5	5	5	5
-45°	4	4	4	4	4	4	4	4	4	5	5
-46.25°	3	3	3	4	4	4	4	4	4	4	4
-47.5°	3	3	3	3	3	3	4	4	4	4	4
-48.75°	3	3	3	3	3	3	3	3	3	3	3
-50°	3	3	3	3	3	3	3	3	3	3	3
-51.25°	3	3	3	3	3	3	3	3	3	3	3
-52.5°	3	3	3	3	3	3	3	3	3	3	3
-53.75°	3	3	3	3	3	3	3	3	3	3	3
-55°	3	3	3	3	3	3	3	3	3	3	3
-56.25°	3	3	3	3	3	3	3	3	3	3	3
-57.5°	3	3	3	3	3	3	3	3	3	3	3
-58.75°	2	3	3	3	3	3	3	3	3	3	3
-60°	2	2	2	2	2	2	3	3	3	3	3
-61.25°	2	2	2	2	2	2	2	2	2	2	2
-62.5°	2	2	2	2	2	2	2	2	2	2	2
-63.75°	2	2	2	2	2	2	2	2	2	2	2
-65°	2	2	2	2	2	2	2	2	2	2	2
-66.25°	2	2	2	2	2	2	2	2	2	2	2
-67.5°	2	2	2	2	2	2	2	2	2	2	2
-68.75°	2	2	2	2	2	2	2	2	2	2	2
-70°	1	1	1	1	1	1	1	2	2	2	2
-71.25°	1	1	1	1	1	1	1	1	1	1	1
-72.5°	1	1	1	1	1	1	1	1	1	1	1
-73.75°	1	1	1	1	1	1	1	1	1	1	1
-75°	1	1	1	1	1	1	1	1	1	1	1
-76.25°	1	1	1	1	1	1	1	1	1	1	1
-77.5°	1	1	1	1	1	1	1	1	1	1	1



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-21.25°	-20°	-18.75°	-17.5°	-16.25°	-15°	-13.75°	-12.5°	-11.25°	-10°	-8.75°
-78.75°	1	1	1	1	1	1	1	1	1	1	1
-80°	1	1	1	1	1	1	1	1	1	1	1
-81.25°	1	1	1	1	1	1	1	1	1	1	1
-82.5°	1	1	1	1	1	1	1	1	1	1	1
-83.75°	1	1	1	1	1	1	1	1	1	1	1
-85°	0	0	0	0	0	0	0	0	0	0	0
-86.25°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-88.75°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-7.5°	-6.25°	-5°	-3.75°	-2.5°	-1.25°	0°	1.25°	2.5°	3.75°	5°
90°	0	0	0	0	0	0	0	0	0	0	0
88.75°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
86.25°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	1	0	0	0	0
83.75°	1	1	1	1	1	1	1	1	1	1	1
82.5°	1	1	1	1	1	1	1	1	1	1	1
81.25°	1	1	1	1	1	1	1	1	1	1	1
80°	1	1	1	1	1	1	1	1	1	1	1
78.75°	1	1	1	1	1	1	1	1	1	1	1
77.5°	1	1	1	1	1	1	1	1	1	1	1
76.25°	1	1	1	1	1	1	1	1	1	1	1
75°	1	1	1	1	1	1	1	1	1	1	1
73.75°	1	1	1	1	1	1	1	1	1	1	1
72.5°	1	1	1	1	1	1	1	1	1	1	1
71.25°	1	1	1	1	1	1	1	1	1	1	1
70°	2	2	2	2	2	2	2	2	2	2	2
68.75°	2	2	2	2	2	2	2	2	2	2	2
67.5°	2	2	2	2	2	2	2	2	2	2	2
66.25°	2	2	2	2	2	2	2	2	2	2	2
65°	2	2	2	2	2	2	2	2	2	2	2
63.75°	2	2	2	2	2	2	2	2	2	2	2
62.5°	2	2	2	2	2	2	2	2	2	2	2
61.25°	2	2	2	2	2	2	2	2	2	2	2
60°	3	3	3	3	3	3	3	3	3	3	3
58.75°	3	3	3	3	3	3	3	3	3	3	3
57.5°	3	3	3	3	3	3	3	3	3	3	3
56.25°	3	3	3	3	3	3	3	3	3	3	3
55°	3	3	3	3	3	3	3	3	3	3	3
53.75°	3	3	3	3	3	3	3	3	3	3	3
52.5°	3	3	3	3	3	3	3	3	3	3	3
51.25°	3	3	3	3	3	3	3	3	3	3	3
50°	3	3	3	3	3	3	3	3	3	3	3
48.75°	3	3	4	4	4	4	4	4	4	4	4
47.5°	4	4	4	4	4	4	4	4	4	4	4
46.25°	4	4	4	4	4	4	4	4	4	4	4
45°	5	5	5	5	5	5	5	5	5	5	5
43.75°	5	5	5	5	5	5	5	5	5	5	5
42.5°	6	6	6	6	6	6	6	6	6	6	6
41.25°	8	8	8	9	9	9	9	9	9	9	8
40°	11	11	11	12	12	12	12	12	12	12	11
38.75°	13	14	14	14	14	14	14	14	14	14	14
37.5°	16	16	16	16	17	17	17	17	17	16	16
36.25°	18	19	19	20	20	20	20	20	20	20	19
35°	21	22	22	23	23	23	23	23	23	23	22



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-7.5°	-6.25°	-5°	-3.75°	-2.5°	-1.25°	0°	1.25°	2.5°	3.75°	5°
33.75°	30	32	35	36	38	38	39	38	38	36	35
32.5°	44	47	50	51	53	53	54	53	53	51	50
31.25°	73	84	92	99	104	107	108	107	104	99	92
30°	125	136	145	152	158	161	162	161	158	152	145
28.75°	182	197	209	219	226	230	232	230	226	219	209
27.5°	251	267	281	292	300	304	306	304	300	292	281
26.25°	322	339	353	363	371	375	377	375	371	363	353
25°	389	405	418	428	435	440	441	440	435	428	418
23.75°	448	463	474	484	489	492	493	492	489	484	474
22.5°	496	507	517	523	528	530	531	530	528	523	517
21.25°	532	542	551	559	564	567	568	567	564	559	551
20°	567	579	590	599	605	609	611	609	605	599	590
18.75°	606	621	635	646	655	661	663	661	655	646	635
17.5°	651	673	692	707	719	727	729	727	719	707	692
16.25°	709	736	759	784	803	814	817	814	803	784	759
15°	779	820	860	897	925	941	947	941	925	897	860
13.75°	878	938	998	1047	1085	1114	1124	1114	1085	1047	998
12.5°	1007	1088	1178	1251	1320	1363	1378	1363	1320	1251	1178
11.25°	1170	1294	1427	1547	1656	1722	1745	1722	1656	1547	1427
10°	1384	1572	1771	1976	2144	2248	2283	2248	2144	1976	1771
8.75°	1661	1946	2252	2554	2787	2945	3001	2945	2787	2554	2252
7.5°	2013	2422	2838	3237	3543	3737	3804	3737	3543	3237	2838
6.25°	2422	2950	3482	3943	4303	4536	4617	4536	4303	3943	3482
5°	2838	3482	4084	4619	5037	5310	5406	5310	5037	4619	4084
3.75°	3237	3943	4619	5217	5675	5971	6061	5971	5675	5217	4619
2.5°	3543	4303	5037	5675	6156	6457	6550	6457	6156	5675	5037
1.25°	3737	4536	5310	5971	6457	6754	6854	6754	6457	5971	5310
0°	3804	4617	5406	6061	6550	6854	6989	6854	6550	6061	5406
-1.25°	3737	4536	5310	5971	6457	6754	6854	6754	6457	5971	5310
-2.5°	3543	4303	5037	5675	6156	6457	6550	6457	6156	5675	5037
-3.75°	3237	3943	4619	5217	5675	5971	6061	5971	5675	5217	4619
-5°	2838	3482	4084	4619	5037	5310	5406	5310	5037	4619	4084
-6.25°	2422	2950	3482	3943	4303	4536	4617	4536	4303	3943	3482
-7.5°	2013	2422	2838	3237	3543	3737	3804	3737	3543	3237	2838
-8.75°	1661	1946	2252	2554	2787	2945	3001	2945	2787	2554	2252
-10°	1384	1572	1771	1976	2144	2248	2283	2248	2144	1976	1771
-11.25°	1170	1294	1427	1547	1656	1722	1745	1722	1656	1547	1427
-12.5°	1007	1088	1178	1251	1320	1363	1378	1363	1320	1251	1178
-13.75°	878	938	998	1047	1085	1114	1124	1114	1085	1047	998
-15°	779	820	860	897	925	941	947	941	925	897	860
-16.25°	709	736	759	784	803	814	817	814	803	784	759
-17.5°	651	673	692	707	719	727	729	727	719	707	692
-18.75°	606	621	635	646	655	661	663	661	655	646	635
-20°	567	579	590	599	605	609	611	609	605	599	590
-21.25°	532	542	551	559	564	567	568	567	564	559	551



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-7.5°	-6.25°	-5°	-3.75°	-2.5°	-1.25°	0°	1.25°	2.5°	3.75°	5°
-22.5°	496	507	517	523	528	530	531	530	528	523	517
-23.75°	448	463	474	484	489	492	493	492	489	484	474
-25°	389	405	418	428	435	440	441	440	435	428	418
-26.25°	322	339	353	363	371	375	377	375	371	363	353
-27.5°	251	267	281	292	300	304	306	304	300	292	281
-28.75°	182	197	209	219	226	230	232	230	226	219	209
-30°	125	136	145	152	158	161	162	161	158	152	145
-31.25°	73	84	92	99	104	107	108	107	104	99	92
-32.5°	44	47	50	51	53	53	54	53	53	51	50
-33.75°	30	32	35	36	38	38	39	38	38	36	35
-35°	21	22	22	23	23	23	23	23	23	23	22
-36.25°	18	19	19	20	20	20	20	20	20	20	19
-37.5°	16	16	16	16	17	17	17	17	17	16	16
-38.75°	13	14	14	14	14	14	14	14	14	14	14
-40°	11	11	11	12	12	12	12	12	12	12	11
-41.25°	8	8	8	9	9	9	9	9	9	9	8
-42.5°	6	6	6	6	6	6	6	6	6	6	6
-43.75°	5	5	5	5	5	5	5	5	5	5	5
-45°	5	5	5	5	5	5	5	5	5	5	5
-46.25°	4	4	4	4	4	4	4	4	4	4	4
-47.5°	4	4	4	4	4	4	4	4	4	4	4
-48.75°	3	3	4	4	4	4	4	4	4	4	4
-50°	3	3	3	3	3	3	3	3	3	3	3
-51.25°	3	3	3	3	3	3	3	3	3	3	3
-52.5°	3	3	3	3	3	3	3	3	3	3	3
-53.75°	3	3	3	3	3	3	3	3	3	3	3
-55°	3	3	3	3	3	3	3	3	3	3	3
-56.25°	3	3	3	3	3	3	3	3	3	3	3
-57.5°	3	3	3	3	3	3	3	3	3	3	3
-58.75°	3	3	3	3	3	3	3	3	3	3	3
-60°	3	3	3	3	3	3	3	3	3	3	3
-61.25°	2	2	2	2	2	2	2	2	2	2	2
-62.5°	2	2	2	2	2	2	2	2	2	2	2
-63.75°	2	2	2	2	2	2	2	2	2	2	2
-65°	2	2	2	2	2	2	2	2	2	2	2
-66.25°	2	2	2	2	2	2	2	2	2	2	2
-67.5°	2	2	2	2	2	2	2	2	2	2	2
-68.75°	2	2	2	2	2	2	2	2	2	2	2
-70°	2	2	2	2	2	2	2	2	2	2	2
-71.25°	1	1	1	1	1	1	1	1	1	1	1
-72.5°	1	1	1	1	1	1	1	1	1	1	1
-73.75°	1	1	1	1	1	1	1	1	1	1	1
-75°	1	1	1	1	1	1	1	1	1	1	1
-76.25°	1	1	1	1	1	1	1	1	1	1	1
-77.5°	1	1	1	1	1	1	1	1	1	1	1



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	-7.5°	-6.25°	-5°	-3.75°	-2.5°	-1.25°	0°	1.25°	2.5°	3.75°	5°
-78.75°	1	1	1	1	1	1	1	1	1	1	1
-80°	1	1	1	1	1	1	1	1	1	1	1
-81.25°	1	1	1	1	1	1	1	1	1	1	1
-82.5°	1	1	1	1	1	1	1	1	1	1	1
-83.75°	1	1	1	1	1	1	1	1	1	1	1
-85°	0	0	0	0	0	0	1	0	0	0	0
-86.25°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-88.75°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	6.25°	7.5°	8.75°	10°	11.25°	12.5°	13.75°	15°	16.25°	17.5°	18.75°
90°	0	0	0	0	0	0	0	0	0	0	0
88.75°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
86.25°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
83.75°	1	1	1	1	1	1	1	1	1	1	1
82.5°	1	1	1	1	1	1	1	1	1	1	1
81.25°	1	1	1	1	1	1	1	1	1	1	1
80°	1	1	1	1	1	1	1	1	1	1	1
78.75°	1	1	1	1	1	1	1	1	1	1	1
77.5°	1	1	1	1	1	1	1	1	1	1	1
76.25°	1	1	1	1	1	1	1	1	1	1	1
75°	1	1	1	1	1	1	1	1	1	1	1
73.75°	1	1	1	1	1	1	1	1	1	1	1
72.5°	1	1	1	1	1	1	1	1	1	1	1
71.25°	1	1	1	1	1	1	1	1	1	1	1
70°	2	2	2	2	2	2	1	1	1	1	1
68.75°	2	2	2	2	2	2	2	2	2	2	2
67.5°	2	2	2	2	2	2	2	2	2	2	2
66.25°	2	2	2	2	2	2	2	2	2	2	2
65°	2	2	2	2	2	2	2	2	2	2	2
63.75°	2	2	2	2	2	2	2	2	2	2	2
62.5°	2	2	2	2	2	2	2	2	2	2	2
61.25°	2	2	2	2	2	2	2	2	2	2	2
60°	3	3	3	3	3	3	3	2	2	2	2
58.75°	3	3	3	3	3	3	3	3	3	3	3
57.5°	3	3	3	3	3	3	3	3	3	3	3
56.25°	3	3	3	3	3	3	3	3	3	3	3
55°	3	3	3	3	3	3	3	3	3	3	3
53.75°	3	3	3	3	3	3	3	3	3	3	3
52.5°	3	3	3	3	3	3	3	3	3	3	3
51.25°	3	3	3	3	3	3	3	3	3	3	3
50°	3	3	3	3	3	3	3	3	3	3	3
48.75°	3	3	3	3	3	3	3	3	3	3	3
47.5°	4	4	4	4	4	4	4	3	3	3	3
46.25°	4	4	4	4	4	4	4	4	4	4	3
45°	5	5	5	5	4	4	4	4	4	4	4
43.75°	5	5	5	5	5	5	5	5	4	4	4
42.5°	6	6	6	6	5	5	5	5	5	5	5
41.25°	8	8	7	7	6	6	6	6	5	5	5
40°	11	11	10	9	9	8	7	7	6	6	6
38.75°	14	13	13	12	12	11	10	9	8	7	6
37.5°	16	16	15	15	14	13	13	12	11	10	9
36.25°	19	18	18	17	16	16	15	14	13	12	11
35°	22	21	21	20	19	18	17	16	16	15	14



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	6.25°	7.5°	8.75°	10°	11.25°	12.5°	13.75°	15°	16.25°	17.5°	18.75°
33.75°	32	30	27	23	22	21	20	19	18	17	16
32.5°	47	44	41	37	33	28	23	22	21	20	18
31.25°	84	73	61	52	47	43	37	31	25	22	21
30°	136	125	113	98	82	63	51	45	38	32	24
28.75°	197	182	165	149	132	113	92	70	52	44	37
27.5°	267	251	231	210	187	161	140	117	92	66	49
26.25°	339	322	302	278	252	224	194	163	137	110	81
25°	405	389	369	346	320	290	257	223	188	153	123
23.75°	463	448	430	408	383	354	321	285	246	206	166
22.5°	507	496	482	462	440	412	380	345	306	263	219
21.25°	542	532	520	505	487	463	434	400	362	320	273
20°	579	567	553	538	522	503	480	449	413	372	327
18.75°	621	606	589	571	553	534	514	490	458	419	375
17.5°	673	651	630	608	586	564	542	520	494	461	419
16.25°	736	709	681	650	624	597	571	546	522	494	458
15°	820	779	740	703	667	633	602	573	546	520	490
13.75°	938	878	817	762	718	676	637	602	571	542	514
12.5°	1088	1007	923	842	777	723	676	633	597	564	534
11.25°	1294	1170	1051	946	853	777	718	667	624	586	553
10°	1572	1384	1212	1066	946	842	762	703	650	608	571
8.75°	1946	1661	1414	1212	1051	923	817	740	681	630	589
7.5°	2422	2013	1661	1384	1170	1007	878	779	709	651	606
6.25°	2950	2422	1946	1572	1294	1088	938	820	736	673	621
5°	3482	2838	2252	1771	1427	1178	998	860	759	692	635
3.75°	3943	3237	2554	1976	1547	1251	1047	897	784	707	646
2.5°	4303	3543	2787	2144	1656	1320	1085	925	803	719	655
1.25°	4536	3737	2945	2248	1722	1363	1114	941	814	727	661
0°	4617	3804	3001	2283	1745	1378	1124	947	817	729	663
-1.25°	4536	3737	2945	2248	1722	1363	1114	941	814	727	661
-2.5°	4303	3543	2787	2144	1656	1320	1085	925	803	719	655
-3.75°	3943	3237	2554	1976	1547	1251	1047	897	784	707	646
-5°	3482	2838	2252	1771	1427	1178	998	860	759	692	635
-6.25°	2950	2422	1946	1572	1294	1088	938	820	736	673	621
-7.5°	2422	2013	1661	1384	1170	1007	878	779	709	651	606
-8.75°	1946	1661	1414	1212	1051	923	817	740	681	630	589
-10°	1572	1384	1212	1066	946	842	762	703	650	608	571
-11.25°	1294	1170	1051	946	853	777	718	667	624	586	553
-12.5°	1088	1007	923	842	777	723	676	633	597	564	534
-13.75°	938	878	817	762	718	676	637	602	571	542	514
-15°	820	779	740	703	667	633	602	573	546	520	490
-16.25°	736	709	681	650	624	597	571	546	522	494	458
-17.5°	673	651	630	608	586	564	542	520	494	461	419
-18.75°	621	606	589	571	553	534	514	490	458	419	375
-20°	579	567	553	538	522	503	480	449	413	372	327
-21.25°	542	532	520	505	487	463	434	400	362	320	273



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	6.25°	7.5°	8.75°	10°	11.25°	12.5°	13.75°	15°	16.25°	17.5°	18.75°
-22.5°	507	496	482	462	440	412	380	345	306	263	219
-23.75°	463	448	430	408	383	354	321	285	246	206	166
-25°	405	389	369	346	320	290	257	223	188	153	123
-26.25°	339	322	302	278	252	224	194	163	137	110	81
-27.5°	267	251	231	210	187	161	140	117	92	66	49
-28.75°	197	182	165	149	132	113	92	70	52	44	37
-30°	136	125	113	98	82	63	51	45	38	32	24
-31.25°	84	73	61	52	47	43	37	31	25	22	21
-32.5°	47	44	41	37	33	28	23	22	21	20	18
-33.75°	32	30	27	23	22	21	20	19	18	17	16
-35°	22	21	21	20	19	18	17	16	16	15	14
-36.25°	19	18	18	17	16	16	15	14	13	12	11
-37.5°	16	16	15	15	14	13	13	12	11	10	9
-38.75°	14	13	13	12	12	11	10	9	8	7	6
-40°	11	11	10	9	9	8	7	7	6	6	6
-41.25°	8	8	7	7	6	6	6	6	5	5	5
-42.5°	6	6	6	6	5	5	5	5	5	5	5
-43.75°	5	5	5	5	5	5	5	5	4	4	4
-45°	5	5	5	5	4	4	4	4	4	4	4
-46.25°	4	4	4	4	4	4	4	4	4	4	3
-47.5°	4	4	4	4	4	4	4	3	3	3	3
-48.75°	3	3	3	3	3	3	3	3	3	3	3
-50°	3	3	3	3	3	3	3	3	3	3	3
-51.25°	3	3	3	3	3	3	3	3	3	3	3
-52.5°	3	3	3	3	3	3	3	3	3	3	3
-53.75°	3	3	3	3	3	3	3	3	3	3	3
-55°	3	3	3	3	3	3	3	3	3	3	3
-56.25°	3	3	3	3	3	3	3	3	3	3	3
-57.5°	3	3	3	3	3	3	3	3	3	3	3
-58.75°	3	3	3	3	3	3	3	3	3	3	3
-60°	3	3	3	3	3	3	3	2	2	2	2
-61.25°	2	2	2	2	2	2	2	2	2	2	2
-62.5°	2	2	2	2	2	2	2	2	2	2	2
-63.75°	2	2	2	2	2	2	2	2	2	2	2
-65°	2	2	2	2	2	2	2	2	2	2	2
-66.25°	2	2	2	2	2	2	2	2	2	2	2
-67.5°	2	2	2	2	2	2	2	2	2	2	2
-68.75°	2	2	2	2	2	2	2	2	2	2	2
-70°	2	2	2	2	2	2	1	1	1	1	1
-71.25°	1	1	1	1	1	1	1	1	1	1	1
-72.5°	1	1	1	1	1	1	1	1	1	1	1
-73.75°	1	1	1	1	1	1	1	1	1	1	1
-75°	1	1	1	1	1	1	1	1	1	1	1
-76.25°	1	1	1	1	1	1	1	1	1	1	1
-77.5°	1	1	1	1	1	1	1	1	1	1	1



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	6.25°	7.5°	8.75°	10°	11.25°	12.5°	13.75°	15°	16.25°	17.5°	18.75°
-78.75°	1	1	1	1	1	1	1	1	1	1	1
-80°	1	1	1	1	1	1	1	1	1	1	1
-81.25°	1	1	1	1	1	1	1	1	1	1	1
-82.5°	1	1	1	1	1	1	1	1	1	1	1
-83.75°	1	1	1	1	1	1	1	1	1	1	1
-85°	0	0	0	0	0	0	0	0	0	0	0
-86.25°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-88.75°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	20°	21.25°	22.5°	23.75°	25°	26.25°	27.5°	28.75°	30°	31.25°	32.5°
90°	0	0	0	0	0	0	0	0	0	0	0
88.75°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
86.25°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
83.75°	1	1	1	1	1	1	1	1	1	1	1
82.5°	1	1	1	1	1	1	1	1	1	1	1
81.25°	1	1	1	1	1	1	1	1	1	1	1
80°	1	1	1	1	1	1	1	1	1	1	1
78.75°	1	1	1	1	1	1	1	1	1	1	1
77.5°	1	1	1	1	1	1	1	1	1	1	1
76.25°	1	1	1	1	1	1	1	1	1	1	1
75°	1	1	1	1	1	1	1	1	1	1	1
73.75°	1	1	1	1	1	1	1	1	1	1	1
72.5°	1	1	1	1	1	1	1	1	1	1	1
71.25°	1	1	1	1	1	1	1	1	1	1	1
70°	1	1	1	1	1	1	1	1	1	1	1
68.75°	2	2	2	1	1	1	1	1	1	1	1
67.5°	2	2	2	2	2	2	2	2	1	1	1
66.25°	2	2	2	2	2	2	2	2	2	2	2
65°	2	2	2	2	2	2	2	2	2	2	2
63.75°	2	2	2	2	2	2	2	2	2	2	2
62.5°	2	2	2	2	2	2	2	2	2	2	2
61.25°	2	2	2	2	2	2	2	2	2	2	2
60°	2	2	2	2	2	2	2	2	2	2	2
58.75°	3	2	2	2	2	2	2	2	2	2	2
57.5°	3	3	3	3	3	2	2	2	2	2	2
56.25°	3	3	3	3	3	3	3	3	2	2	2
55°	3	3	3	3	3	3	3	3	3	3	2
53.75°	3	3	3	3	3	3	3	3	3	3	3
52.5°	3	3	3	3	3	3	3	3	3	3	3
51.25°	3	3	3	3	3	3	3	3	3	3	3
50°	3	3	3	3	3	3	3	3	3	3	3
48.75°	3	3	3	3	3	3	3	3	3	3	3
47.5°	3	3	3	3	3	3	3	3	3	3	3
46.25°	3	3	3	3	3	3	3	3	3	3	3
45°	4	4	3	3	3	3	3	3	3	3	3
43.75°	4	4	4	4	3	3	3	3	3	3	3
42.5°	4	4	4	4	4	4	3	3	3	3	3
41.25°	5	5	4	4	4	4	4	4	3	3	3
40°	5	5	5	5	4	4	4	4	4	3	3
38.75°	6	6	5	5	5	5	4	4	4	4	4
37.5°	8	6	6	6	5	5	5	4	4	4	4
36.25°	10	9	8	6	6	5	5	5	5	4	4
35°	13	11	10	9	7	6	6	5	5	5	4



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	20°	21.25°	22.5°	23.75°	25°	26.25°	27.5°	28.75°	30°	31.25°	32.5°
33.75°	15	13	12	11	9	8	6	6	5	5	5
32.5°	17	15	14	13	12	10	8	6	6	5	5
31.25°	19	18	16	15	13	12	10	8	7	6	5
30°	22	20	18	17	15	14	12	10	9	7	6
28.75°	29	23	21	19	17	16	14	12	10	8	6
27.5°	41	33	24	21	19	17	16	14	12	10	8
26.25°	53	44	35	25	22	20	17	16	14	12	10
25°	92	60	46	36	26	22	19	17	15	13	12
23.75°	133	99	64	47	36	25	21	19	17	15	13
22.5°	175	137	101	64	46	35	24	21	18	16	14
21.25°	225	178	137	99	60	44	33	23	20	18	15
20°	277	225	175	133	92	53	41	29	22	19	17
18.75°	327	273	219	166	123	81	49	37	24	21	18
17.5°	372	320	263	206	153	110	66	44	32	22	20
16.25°	413	362	306	246	188	137	92	52	38	25	21
15°	449	400	345	285	223	163	117	70	45	31	22
13.75°	480	434	380	321	257	194	140	92	51	37	23
12.5°	503	463	412	354	290	224	161	113	63	43	28
11.25°	522	487	440	383	320	252	187	132	82	47	33
10°	538	505	462	408	346	278	210	149	98	52	37
8.75°	553	520	482	430	369	302	231	165	113	61	41
7.5°	567	532	496	448	389	322	251	182	125	73	44
6.25°	579	542	507	463	405	339	267	197	136	84	47
5°	590	551	517	474	418	353	281	209	145	92	50
3.75°	599	559	523	484	428	363	292	219	152	99	51
2.5°	605	564	528	489	435	371	300	226	158	104	53
1.25°	609	567	530	492	440	375	304	230	161	107	53
0°	611	568	531	493	441	377	306	232	162	108	54
-1.25°	609	567	530	492	440	375	304	230	161	107	53
-2.5°	605	564	528	489	435	371	300	226	158	104	53
-3.75°	599	559	523	484	428	363	292	219	152	99	51
-5°	590	551	517	474	418	353	281	209	145	92	50
-6.25°	579	542	507	463	405	339	267	197	136	84	47
-7.5°	567	532	496	448	389	322	251	182	125	73	44
-8.75°	553	520	482	430	369	302	231	165	113	61	41
-10°	538	505	462	408	346	278	210	149	98	52	37
-11.25°	522	487	440	383	320	252	187	132	82	47	33
-12.5°	503	463	412	354	290	224	161	113	63	43	28
-13.75°	480	434	380	321	257	194	140	92	51	37	23
-15°	449	400	345	285	223	163	117	70	45	31	22
-16.25°	413	362	306	246	188	137	92	52	38	25	21
-17.5°	372	320	263	206	153	110	66	44	32	22	20
-18.75°	327	273	219	166	123	81	49	37	24	21	18
-20°	277	225	175	133	92	53	41	29	22	19	17
-21.25°	225	178	137	99	60	44	33	23	20	18	15



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	20°	21.25°	22.5°	23.75°	25°	26.25°	27.5°	28.75°	30°	31.25°	32.5°
-22.5°	175	137	101	64	46	35	24	21	18	16	14
-23.75°	133	99	64	47	36	25	21	19	17	15	13
-25°	92	60	46	36	26	22	19	17	15	13	12
-26.25°	53	44	35	25	22	20	17	16	14	12	10
-27.5°	41	33	24	21	19	17	16	14	12	10	8
-28.75°	29	23	21	19	17	16	14	12	10	8	6
-30°	22	20	18	17	15	14	12	10	9	7	6
-31.25°	19	18	16	15	13	12	10	8	7	6	5
-32.5°	17	15	14	13	12	10	8	6	6	5	5
-33.75°	15	13	12	11	9	8	6	6	5	5	5
-35°	13	11	10	9	7	6	6	5	5	5	4
-36.25°	10	9	8	6	6	5	5	5	5	4	4
-37.5°	8	6	6	6	5	5	5	4	4	4	4
-38.75°	6	6	5	5	5	5	4	4	4	4	4
-40°	5	5	5	5	4	4	4	4	4	3	3
-41.25°	5	5	4	4	4	4	4	4	3	3	3
-42.5°	4	4	4	4	4	4	3	3	3	3	3
-43.75°	4	4	4	4	3	3	3	3	3	3	3
-45°	4	4	3	3	3	3	3	3	3	3	3
-46.25°	3	3	3	3	3	3	3	3	3	3	3
-47.5°	3	3	3	3	3	3	3	3	3	3	3
-48.75°	3	3	3	3	3	3	3	3	3	3	3
-50°	3	3	3	3	3	3	3	3	3	3	3
-51.25°	3	3	3	3	3	3	3	3	3	3	3
-52.5°	3	3	3	3	3	3	3	3	3	3	3
-53.75°	3	3	3	3	3	3	3	3	3	3	3
-55°	3	3	3	3	3	3	3	3	3	3	2
-56.25°	3	3	3	3	3	3	3	3	2	2	2
-57.5°	3	3	3	3	3	2	2	2	2	2	2
-58.75°	3	2	2	2	2	2	2	2	2	2	2
-60°	2	2	2	2	2	2	2	2	2	2	2
-61.25°	2	2	2	2	2	2	2	2	2	2	2
-62.5°	2	2	2	2	2	2	2	2	2	2	2
-63.75°	2	2	2	2	2	2	2	2	2	2	2
-65°	2	2	2	2	2	2	2	2	2	2	2
-66.25°	2	2	2	2	2	2	2	2	2	2	2
-67.5°	2	2	2	2	2	2	2	2	1	1	1
-68.75°	2	2	2	1	1	1	1	1	1	1	1
-70°	1	1	1	1	1	1	1	1	1	1	1
-71.25°	1	1	1	1	1	1	1	1	1	1	1
-72.5°	1	1	1	1	1	1	1	1	1	1	1
-73.75°	1	1	1	1	1	1	1	1	1	1	1
-75°	1	1	1	1	1	1	1	1	1	1	1
-76.25°	1	1	1	1	1	1	1	1	1	1	1
-77.5°	1	1	1	1	1	1	1	1	1	1	1



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	20°	21.25°	22.5°	23.75°	25°	26.25°	27.5°	28.75°	30°	31.25°	32.5°
-78.75°	1	1	1	1	1	1	1	1	1	1	1
-80°	1	1	1	1	1	1	1	1	1	1	1
-81.25°	1	1	1	1	1	1	1	1	1	1	1
-82.5°	1	1	1	1	1	1	1	1	1	1	1
-83.75°	1	1	1	1	1	1	1	1	1	1	1
-85°	0	0	0	0	0	0	0	0	0	0	0
-86.25°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-88.75°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	33.75°	35°	36.25°	37.5°	38.75°	40°	41.25°	42.5°	43.75°	45°	46.25°
90°	0	0	0	0	0	0	0	0	0	0	0
88.75°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
86.25°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
83.75°	1	1	1	0	0	0	0	0	0	0	0
82.5°	1	1	1	1	1	1	1	1	1	1	1
81.25°	1	1	1	1	1	1	1	1	1	1	1
80°	1	1	1	1	1	1	1	1	1	1	1
78.75°	1	1	1	1	1	1	1	1	1	1	1
77.5°	1	1	1	1	1	1	1	1	1	1	1
76.25°	1	1	1	1	1	1	1	1	1	1	1
75°	1	1	1	1	1	1	1	1	1	1	1
73.75°	1	1	1	1	1	1	1	1	1	1	1
72.5°	1	1	1	1	1	1	1	1	1	1	1
71.25°	1	1	1	1	1	1	1	1	1	1	1
70°	1	1	1	1	1	1	1	1	1	1	1
68.75°	1	1	1	1	1	1	1	1	1	1	1
67.5°	1	1	1	1	1	1	1	1	1	1	1
66.25°	2	1	1	1	1	1	1	1	1	1	1
65°	2	2	2	2	1	1	1	1	1	1	1
63.75°	2	2	2	2	2	2	1	1	1	1	1
62.5°	2	2	2	2	2	2	2	2	1	1	1
61.25°	2	2	2	2	2	2	2	2	2	2	1
60°	2	2	2	2	2	2	2	2	2	2	2
58.75°	2	2	2	2	2	2	2	2	2	2	2
57.5°	2	2	2	2	2	2	2	2	2	2	2
56.25°	2	2	2	2	2	2	2	2	2	2	2
55°	2	2	2	2	2	2	2	2	2	2	2
53.75°	3	2	2	2	2	2	2	2	2	2	2
52.5°	3	3	3	2	2	2	2	2	2	2	2
51.25°	3	3	3	3	3	2	2	2	2	2	2
50°	3	3	3	3	3	3	2	2	2	2	2
48.75°	3	3	3	3	3	3	3	3	2	2	2
47.5°	3	3	3	3	3	3	3	3	3	2	2
46.25°	3	3	3	3	3	3	3	3	3	3	2
45°	3	3	3	3	3	3	3	3	3	3	3
43.75°	3	3	3	3	3	3	3	3	3	3	3
42.5°	3	3	3	3	3	3	3	3	3	3	3
41.25°	3	3	3	3	3	3	3	3	3	3	3
40°	3	3	3	3	3	3	3	3	3	3	3
38.75°	3	3	3	3	3	3	3	3	3	3	3
37.5°	4	3	3	3	3	3	3	3	3	3	3
36.25°	4	4	3	3	3	3	3	3	3	3	3
35°	4	4	4	3	3	3	3	3	3	3	3



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	33.75°	35°	36.25°	37.5°	38.75°	40°	41.25°	42.5°	43.75°	45°	46.25°
33.75°	4	4	4	4	3	3	3	3	3	3	3
32.5°	5	4	4	4	4	3	3	3	3	3	3
31.25°	5	5	4	4	4	3	3	3	3	3	3
30°	5	5	5	4	4	4	3	3	3	3	3
28.75°	6	5	5	4	4	4	4	3	3	3	3
27.5°	6	6	5	5	4	4	4	3	3	3	3
26.25°	8	6	5	5	5	4	4	4	3	3	3
25°	9	7	6	5	5	4	4	4	3	3	3
23.75°	11	9	6	6	5	5	4	4	4	3	3
22.5°	12	10	8	6	5	5	4	4	4	3	3
21.25°	13	11	9	6	6	5	5	4	4	4	3
20°	15	13	10	8	6	5	5	4	4	4	3
18.75°	16	14	11	9	6	6	5	5	4	4	3
17.5°	17	15	12	10	7	6	5	5	4	4	4
16.25°	18	16	13	11	8	6	5	5	4	4	4
15°	19	16	14	12	9	7	6	5	5	4	4
13.75°	20	17	15	13	10	7	6	5	5	4	4
12.5°	21	18	16	13	11	8	6	5	5	4	4
11.25°	22	19	16	14	12	9	6	5	5	4	4
10°	23	20	17	15	12	9	7	6	5	5	4
8.75°	27	21	18	15	13	10	7	6	5	5	4
7.5°	30	21	18	16	13	11	8	6	5	5	4
6.25°	32	22	19	16	14	11	8	6	5	5	4
5°	35	22	19	16	14	11	8	6	5	5	4
3.75°	36	23	20	16	14	12	9	6	5	5	4
2.5°	38	23	20	17	14	12	9	6	5	5	4
1.25°	38	23	20	17	14	12	9	6	5	5	4
0°	39	23	20	17	14	12	9	6	5	5	4
-1.25°	38	23	20	17	14	12	9	6	5	5	4
-2.5°	38	23	20	17	14	12	9	6	5	5	4
-3.75°	36	23	20	16	14	12	9	6	5	5	4
-5°	35	22	19	16	14	11	8	6	5	5	4
-6.25°	32	22	19	16	14	11	8	6	5	5	4
-7.5°	30	21	18	16	13	11	8	6	5	5	4
-8.75°	27	21	18	15	13	10	7	6	5	5	4
-10°	23	20	17	15	12	9	7	6	5	5	4
-11.25°	22	19	16	14	12	9	6	5	5	4	4
-12.5°	21	18	16	13	11	8	6	5	5	4	4
-13.75°	20	17	15	13	10	7	6	5	5	4	4
-15°	19	16	14	12	9	7	6	5	5	4	4
-16.25°	18	16	13	11	8	6	5	5	4	4	4
-17.5°	17	15	12	10	7	6	5	5	4	4	4
-18.75°	16	14	11	9	6	6	5	5	4	4	3
-20°	15	13	10	8	6	5	5	4	4	4	3
-21.25°	13	11	9	6	6	5	5	4	4	4	3



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	33.75°	35°	36.25°	37.5°	38.75°	40°	41.25°	42.5°	43.75°	45°	46.25°
-22.5°	12	10	8	6	5	5	4	4	4	3	3
-23.75°	11	9	6	6	5	5	4	4	4	3	3
-25°	9	7	6	5	5	4	4	4	3	3	3
-26.25°	8	6	5	5	5	4	4	4	3	3	3
-27.5°	6	6	5	5	4	4	4	3	3	3	3
-28.75°	6	5	5	4	4	4	4	3	3	3	3
-30°	5	5	5	4	4	4	3	3	3	3	3
-31.25°	5	5	4	4	4	3	3	3	3	3	3
-32.5°	5	4	4	4	4	3	3	3	3	3	3
-33.75°	4	4	4	4	3	3	3	3	3	3	3
-35°	4	4	4	3	3	3	3	3	3	3	3
-36.25°	4	4	3	3	3	3	3	3	3	3	3
-37.5°	4	3	3	3	3	3	3	3	3	3	3
-38.75°	3	3	3	3	3	3	3	3	3	3	3
-40°	3	3	3	3	3	3	3	3	3	3	3
-41.25°	3	3	3	3	3	3	3	3	3	3	3
-42.5°	3	3	3	3	3	3	3	3	3	3	3
-43.75°	3	3	3	3	3	3	3	3	3	3	3
-45°	3	3	3	3	3	3	3	3	3	3	3
-46.25°	3	3	3	3	3	3	3	3	3	3	2
-47.5°	3	3	3	3	3	3	3	3	3	2	2
-48.75°	3	3	3	3	3	3	3	3	2	2	2
-50°	3	3	3	3	3	3	2	2	2	2	2
-51.25°	3	3	3	3	3	2	2	2	2	2	2
-52.5°	3	3	3	2	2	2	2	2	2	2	2
-53.75°	3	2	2	2	2	2	2	2	2	2	2
-55°	2	2	2	2	2	2	2	2	2	2	2
-56.25°	2	2	2	2	2	2	2	2	2	2	2
-57.5°	2	2	2	2	2	2	2	2	2	2	2
-58.75°	2	2	2	2	2	2	2	2	2	2	2
-60°	2	2	2	2	2	2	2	2	2	2	2
-61.25°	2	2	2	2	2	2	2	2	2	2	1
-62.5°	2	2	2	2	2	2	2	2	1	1	1
-63.75°	2	2	2	2	2	2	1	1	1	1	1
-65°	2	2	2	2	1	1	1	1	1	1	1
-66.25°	2	1	1	1	1	1	1	1	1	1	1
-67.5°	1	1	1	1	1	1	1	1	1	1	1
-68.75°	1	1	1	1	1	1	1	1	1	1	1
-70°	1	1	1	1	1	1	1	1	1	1	1
-71.25°	1	1	1	1	1	1	1	1	1	1	1
-72.5°	1	1	1	1	1	1	1	1	1	1	1
-73.75°	1	1	1	1	1	1	1	1	1	1	1
-75°	1	1	1	1	1	1	1	1	1	1	1
-76.25°	1	1	1	1	1	1	1	1	1	1	1
-77.5°	1	1	1	1	1	1	1	1	1	1	1



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	33.75°	35°	36.25°	37.5°	38.75°	40°	41.25°	42.5°	43.75°	45°	46.25°
-78.75°	1	1	1	1	1	1	1	1	1	1	1
-80°	1	1	1	1	1	1	1	1	1	1	1
-81.25°	1	1	1	1	1	1	1	1	1	1	1
-82.5°	1	1	1	1	1	1	1	1	1	1	1
-83.75°	1	1	1	0	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0	0	0	0	0
-86.25°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-88.75°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	47.5°	48.75°	50°	51.25°	52.5°	53.75°	55°	56.25°	57.5°	58.75°	60°
90°	0	0	0	0	0	0	0	0	0	0	0
88.75°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
86.25°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
83.75°	0	0	0	0	0	0	0	0	0	0	0
82.5°	1	0	0	0	0	0	0	0	0	0	0
81.25°	1	1	1	1	1	1	1	0	0	0	0
80°	1	1	1	1	1	1	1	1	1	1	0
78.75°	1	1	1	1	1	1	1	1	1	1	1
77.5°	1	1	1	1	1	1	1	1	1	1	1
76.25°	1	1	1	1	1	1	1	1	1	1	1
75°	1	1	1	1	1	1	1	1	1	1	1
73.75°	1	1	1	1	1	1	1	1	1	1	1
72.5°	1	1	1	1	1	1	1	1	1	1	1
71.25°	1	1	1	1	1	1	1	1	1	1	1
70°	1	1	1	1	1	1	1	1	1	1	1
68.75°	1	1	1	1	1	1	1	1	1	1	1
67.5°	1	1	1	1	1	1	1	1	1	1	1
66.25°	1	1	1	1	1	1	1	1	1	1	1
65°	1	1	1	1	1	1	1	1	1	1	1
63.75°	1	1	1	1	1	1	1	1	1	1	1
62.5°	1	1	1	1	1	1	1	1	1	1	1
61.25°	1	1	1	1	1	1	1	1	1	1	1
60°	2	1	1	1	1	1	1	1	1	1	1
58.75°	2	2	1	1	1	1	1	1	1	1	1
57.5°	2	2	2	2	1	1	1	1	1	1	1
56.25°	2	2	2	2	2	1	1	1	1	1	1
55°	2	2	2	2	2	2	1	1	1	1	1
53.75°	2	2	2	2	2	2	2	1	1	1	1
52.5°	2	2	2	2	2	2	2	2	1	1	1
51.25°	2	2	2	2	2	2	2	2	2	1	1
50°	2	2	2	2	2	2	2	2	2	1	1
48.75°	2	2	2	2	2	2	2	2	2	2	1
47.5°	2	2	2	2	2	2	2	2	2	2	2
46.25°	2	2	2	2	2	2	2	2	2	2	2
45°	2	2	2	2	2	2	2	2	2	2	2
43.75°	3	2	2	2	2	2	2	2	2	2	2
42.5°	3	3	2	2	2	2	2	2	2	2	2
41.25°	3	3	2	2	2	2	2	2	2	2	2
40°	3	3	3	2	2	2	2	2	2	2	2
38.75°	3	3	3	3	2	2	2	2	2	2	2
37.5°	3	3	3	3	2	2	2	2	2	2	2
36.25°	3	3	3	3	3	2	2	2	2	2	2
35°	3	3	3	3	3	2	2	2	2	2	2



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	47.5°	48.75°	50°	51.25°	52.5°	53.75°	55°	56.25°	57.5°	58.75°	60°
33.75°	3	3	3	3	3	3	2	2	2	2	2
32.5°	3	3	3	3	3	3	2	2	2	2	2
31.25°	3	3	3	3	3	3	3	2	2	2	2
30°	3	3	3	3	3	3	3	2	2	2	2
28.75°	3	3	3	3	3	3	3	3	2	2	2
27.5°	3	3	3	3	3	3	3	3	2	2	2
26.25°	3	3	3	3	3	3	3	3	2	2	2
25°	3	3	3	3	3	3	3	3	3	2	2
23.75°	3	3	3	3	3	3	3	3	3	2	2
22.5°	3	3	3	3	3	3	3	3	3	2	2
21.25°	3	3	3	3	3	3	3	3	3	2	2
20°	3	3	3	3	3	3	3	3	3	3	2
18.75°	3	3	3	3	3	3	3	3	3	3	2
17.5°	3	3	3	3	3	3	3	3	3	3	2
16.25°	3	3	3	3	3	3	3	3	3	3	2
15°	3	3	3	3	3	3	3	3	3	3	2
13.75°	4	3	3	3	3	3	3	3	3	3	3
12.5°	4	3	3	3	3	3	3	3	3	3	3
11.25°	4	3	3	3	3	3	3	3	3	3	3
10°	4	3	3	3	3	3	3	3	3	3	3
8.75°	4	3	3	3	3	3	3	3	3	3	3
7.5°	4	3	3	3	3	3	3	3	3	3	3
6.25°	4	3	3	3	3	3	3	3	3	3	3
5°	4	4	3	3	3	3	3	3	3	3	3
3.75°	4	4	3	3	3	3	3	3	3	3	3
2.5°	4	4	3	3	3	3	3	3	3	3	3
1.25°	4	4	3	3	3	3	3	3	3	3	3
0°	4	4	3	3	3	3	3	3	3	3	3
-1.25°	4	4	3	3	3	3	3	3	3	3	3
-2.5°	4	4	3	3	3	3	3	3	3	3	3
-3.75°	4	4	3	3	3	3	3	3	3	3	3
-5°	4	4	3	3	3	3	3	3	3	3	3
-6.25°	4	3	3	3	3	3	3	3	3	3	3
-7.5°	4	3	3	3	3	3	3	3	3	3	3
-8.75°	4	3	3	3	3	3	3	3	3	3	3
-10°	4	3	3	3	3	3	3	3	3	3	3
-11.25°	4	3	3	3	3	3	3	3	3	3	3
-12.5°	4	3	3	3	3	3	3	3	3	3	3
-13.75°	4	3	3	3	3	3	3	3	3	3	3
-15°	3	3	3	3	3	3	3	3	3	3	2
-16.25°	3	3	3	3	3	3	3	3	3	3	2
-17.5°	3	3	3	3	3	3	3	3	3	3	2
-18.75°	3	3	3	3	3	3	3	3	3	3	2
-20°	3	3	3	3	3	3	3	3	3	3	2
-21.25°	3	3	3	3	3	3	3	3	3	2	2



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	47.5°	48.75°	50°	51.25°	52.5°	53.75°	55°	56.25°	57.5°	58.75°	60°
-22.5°	3	3	3	3	3	3	3	3	3	2	2
-23.75°	3	3	3	3	3	3	3	3	3	2	2
-25°	3	3	3	3	3	3	3	3	3	2	2
-26.25°	3	3	3	3	3	3	3	3	2	2	2
-27.5°	3	3	3	3	3	3	3	3	2	2	2
-28.75°	3	3	3	3	3	3	3	3	2	2	2
-30°	3	3	3	3	3	3	3	2	2	2	2
-31.25°	3	3	3	3	3	3	3	2	2	2	2
-32.5°	3	3	3	3	3	3	2	2	2	2	2
-33.75°	3	3	3	3	3	3	2	2	2	2	2
-35°	3	3	3	3	3	2	2	2	2	2	2
-36.25°	3	3	3	3	3	2	2	2	2	2	2
-37.5°	3	3	3	3	2	2	2	2	2	2	2
-38.75°	3	3	3	3	2	2	2	2	2	2	2
-40°	3	3	3	2	2	2	2	2	2	2	2
-41.25°	3	3	2	2	2	2	2	2	2	2	2
-42.5°	3	3	2	2	2	2	2	2	2	2	2
-43.75°	3	2	2	2	2	2	2	2	2	2	2
-45°	2	2	2	2	2	2	2	2	2	2	2
-46.25°	2	2	2	2	2	2	2	2	2	2	2
-47.5°	2	2	2	2	2	2	2	2	2	2	2
-48.75°	2	2	2	2	2	2	2	2	2	2	1
-50°	2	2	2	2	2	2	2	2	2	1	1
-51.25°	2	2	2	2	2	2	2	2	2	1	1
-52.5°	2	2	2	2	2	2	2	2	1	1	1
-53.75°	2	2	2	2	2	2	2	1	1	1	1
-55°	2	2	2	2	2	2	1	1	1	1	1
-56.25°	2	2	2	2	2	1	1	1	1	1	1
-57.5°	2	2	2	2	1	1	1	1	1	1	1
-58.75°	2	2	1	1	1	1	1	1	1	1	1
-60°	2	1	1	1	1	1	1	1	1	1	1
-61.25°	1	1	1	1	1	1	1	1	1	1	1
-62.5°	1	1	1	1	1	1	1	1	1	1	1
-63.75°	1	1	1	1	1	1	1	1	1	1	1
-65°	1	1	1	1	1	1	1	1	1	1	1
-66.25°	1	1	1	1	1	1	1	1	1	1	1
-67.5°	1	1	1	1	1	1	1	1	1	1	1
-68.75°	1	1	1	1	1	1	1	1	1	1	1
-70°	1	1	1	1	1	1	1	1	1	1	1
-71.25°	1	1	1	1	1	1	1	1	1	1	1
-72.5°	1	1	1	1	1	1	1	1	1	1	1
-73.75°	1	1	1	1	1	1	1	1	1	1	1
-75°	1	1	1	1	1	1	1	1	1	1	1
-76.25°	1	1	1	1	1	1	1	1	1	1	1
-77.5°	1	1	1	1	1	1	1	1	1	1	1



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	47.5°	48.75°	50°	51.25°	52.5°	53.75°	55°	56.25°	57.5°	58.75°	60°
-78.75°	1	1	1	1	1	1	1	1	1	1	1
-80°	1	1	1	1	1	1	1	1	1	1	0
-81.25°	1	1	1	1	1	1	1	0	0	0	0
-82.5°	1	0	0	0	0	0	0	0	0	0	0
-83.75°	0	0	0	0	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0	0	0	0	0
-86.25°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-88.75°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	61.25°	62.5°	63.75°	65°	66.25°	67.5°	68.75°	70°	71.25°	72.5°	73.75°
90°	0	0	0	0	0	0	0	0	0	0	0
88.75°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
86.25°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
83.75°	0	0	0	0	0	0	0	0	0	0	0
82.5°	0	0	0	0	0	0	0	0	0	0	0
81.25°	0	0	0	0	0	0	0	0	0	0	0
80°	0	0	0	0	0	0	0	0	0	0	0
78.75°	1	1	0	0	0	0	0	0	0	0	0
77.5°	1	1	1	1	1	0	0	0	0	0	0
76.25°	1	1	1	1	1	1	0	0	0	0	0
75°	1	1	1	1	1	1	1	1	0	0	0
73.75°	1	1	1	1	1	1	1	1	1	0	0
72.5°	1	1	1	1	1	1	1	1	1	1	0
71.25°	1	1	1	1	1	1	1	1	1	1	1
70°	1	1	1	1	1	1	1	1	1	1	1
68.75°	1	1	1	1	1	1	1	1	1	1	1
67.5°	1	1	1	1	1	1	1	1	1	1	1
66.25°	1	1	1	1	1	1	1	1	1	1	1
65°	1	1	1	1	1	1	1	1	1	1	1
63.75°	1	1	1	1	1	1	1	1	1	1	1
62.5°	1	1	1	1	1	1	1	1	1	1	1
61.25°	1	1	1	1	1	1	1	1	1	1	1
60°	1	1	1	1	1	1	1	1	1	1	1
58.75°	1	1	1	1	1	1	1	1	1	1	1
57.5°	1	1	1	1	1	1	1	1	1	1	1
56.25°	1	1	1	1	1	1	1	1	1	1	1
55°	1	1	1	1	1	1	1	1	1	1	1
53.75°	1	1	1	1	1	1	1	1	1	1	1
52.5°	1	1	1	1	1	1	1	1	1	1	1
51.25°	1	1	1	1	1	1	1	1	1	1	1
50°	1	1	1	1	1	1	1	1	1	1	1
48.75°	1	1	1	1	1	1	1	1	1	1	1
47.5°	1	1	1	1	1	1	1	1	1	1	1
46.25°	1	1	1	1	1	1	1	1	1	1	1
45°	2	1	1	1	1	1	1	1	1	1	1
43.75°	2	1	1	1	1	1	1	1	1	1	1
42.5°	2	2	1	1	1	1	1	1	1	1	1
41.25°	2	2	1	1	1	1	1	1	1	1	1
40°	2	2	2	1	1	1	1	1	1	1	1
38.75°	2	2	2	1	1	1	1	1	1	1	1
37.5°	2	2	2	2	1	1	1	1	1	1	1
36.25°	2	2	2	2	1	1	1	1	1	1	1
35°	2	2	2	2	1	1	1	1	1	1	1



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	61.25°	62.5°	63.75°	65°	66.25°	67.5°	68.75°	70°	71.25°	72.5°	73.75°
33.75°	2	2	2	2	2	1	1	1	1	1	1
32.5°	2	2	2	2	2	1	1	1	1	1	1
31.25°	2	2	2	2	2	1	1	1	1	1	1
30°	2	2	2	2	2	1	1	1	1	1	1
28.75°	2	2	2	2	2	2	1	1	1	1	1
27.5°	2	2	2	2	2	2	1	1	1	1	1
26.25°	2	2	2	2	2	2	1	1	1	1	1
25°	2	2	2	2	2	2	1	1	1	1	1
23.75°	2	2	2	2	2	2	1	1	1	1	1
22.5°	2	2	2	2	2	2	2	1	1	1	1
21.25°	2	2	2	2	2	2	2	1	1	1	1
20°	2	2	2	2	2	2	2	1	1	1	1
18.75°	2	2	2	2	2	2	2	1	1	1	1
17.5°	2	2	2	2	2	2	2	1	1	1	1
16.25°	2	2	2	2	2	2	2	1	1	1	1
15°	2	2	2	2	2	2	2	1	1	1	1
13.75°	2	2	2	2	2	2	2	1	1	1	1
12.5°	2	2	2	2	2	2	2	2	1	1	1
11.25°	2	2	2	2	2	2	2	2	1	1	1
10°	2	2	2	2	2	2	2	2	1	1	1
8.75°	2	2	2	2	2	2	2	2	1	1	1
7.5°	2	2	2	2	2	2	2	2	1	1	1
6.25°	2	2	2	2	2	2	2	2	1	1	1
5°	2	2	2	2	2	2	2	2	1	1	1
3.75°	2	2	2	2	2	2	2	2	1	1	1
2.5°	2	2	2	2	2	2	2	2	1	1	1
1.25°	2	2	2	2	2	2	2	2	1	1	1
0°	2	2	2	2	2	2	2	2	1	1	1
-1.25°	2	2	2	2	2	2	2	2	1	1	1
-2.5°	2	2	2	2	2	2	2	2	1	1	1
-3.75°	2	2	2	2	2	2	2	2	1	1	1
-5°	2	2	2	2	2	2	2	2	1	1	1
-6.25°	2	2	2	2	2	2	2	2	1	1	1
-7.5°	2	2	2	2	2	2	2	2	1	1	1
-8.75°	2	2	2	2	2	2	2	2	1	1	1
-10°	2	2	2	2	2	2	2	2	1	1	1
-11.25°	2	2	2	2	2	2	2	2	1	1	1
-12.5°	2	2	2	2	2	2	2	2	1	1	1
-13.75°	2	2	2	2	2	2	2	1	1	1	1
-15°	2	2	2	2	2	2	2	1	1	1	1
-16.25°	2	2	2	2	2	2	2	1	1	1	1
-17.5°	2	2	2	2	2	2	2	1	1	1	1
-18.75°	2	2	2	2	2	2	2	1	1	1	1
-20°	2	2	2	2	2	2	2	1	1	1	1
-21.25°	2	2	2	2	2	2	2	1	1	1	1



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	61.25°	62.5°	63.75°	65°	66.25°	67.5°	68.75°	70°	71.25°	72.5°	73.75°
-22.5°	2	2	2	2	2	2	2	1	1	1	1
-23.75°	2	2	2	2	2	2	1	1	1	1	1
-25°	2	2	2	2	2	2	1	1	1	1	1
-26.25°	2	2	2	2	2	2	1	1	1	1	1
-27.5°	2	2	2	2	2	2	1	1	1	1	1
-28.75°	2	2	2	2	2	2	1	1	1	1	1
-30°	2	2	2	2	2	1	1	1	1	1	1
-31.25°	2	2	2	2	2	1	1	1	1	1	1
-32.5°	2	2	2	2	2	1	1	1	1	1	1
-33.75°	2	2	2	2	2	1	1	1	1	1	1
-35°	2	2	2	2	1	1	1	1	1	1	1
-36.25°	2	2	2	2	1	1	1	1	1	1	1
-37.5°	2	2	2	2	1	1	1	1	1	1	1
-38.75°	2	2	2	1	1	1	1	1	1	1	1
-40°	2	2	2	1	1	1	1	1	1	1	1
-41.25°	2	2	1	1	1	1	1	1	1	1	1
-42.5°	2	2	1	1	1	1	1	1	1	1	1
-43.75°	2	1	1	1	1	1	1	1	1	1	1
-45°	2	1	1	1	1	1	1	1	1	1	1
-46.25°	1	1	1	1	1	1	1	1	1	1	1
-47.5°	1	1	1	1	1	1	1	1	1	1	1
-48.75°	1	1	1	1	1	1	1	1	1	1	1
-50°	1	1	1	1	1	1	1	1	1	1	1
-51.25°	1	1	1	1	1	1	1	1	1	1	1
-52.5°	1	1	1	1	1	1	1	1	1	1	1
-53.75°	1	1	1	1	1	1	1	1	1	1	1
-55°	1	1	1	1	1	1	1	1	1	1	1
-56.25°	1	1	1	1	1	1	1	1	1	1	1
-57.5°	1	1	1	1	1	1	1	1	1	1	1
-58.75°	1	1	1	1	1	1	1	1	1	1	1
-60°	1	1	1	1	1	1	1	1	1	1	1
-61.25°	1	1	1	1	1	1	1	1	1	1	1
-62.5°	1	1	1	1	1	1	1	1	1	1	1
-63.75°	1	1	1	1	1	1	1	1	1	1	1
-65°	1	1	1	1	1	1	1	1	1	1	1
-66.25°	1	1	1	1	1	1	1	1	1	1	1
-67.5°	1	1	1	1	1	1	1	1	1	1	1
-68.75°	1	1	1	1	1	1	1	1	1	1	1
-70°	1	1	1	1	1	1	1	1	1	1	1
-71.25°	1	1	1	1	1	1	1	1	1	1	1
-72.5°	1	1	1	1	1	1	1	1	1	1	0
-73.75°	1	1	1	1	1	1	1	1	1	0	0
-75°	1	1	1	1	1	1	1	0	0	0	0
-76.25°	1	1	1	1	1	1	0	0	0	0	0
-77.5°	1	1	1	1	1	0	0	0	0	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	61.25°	62.5°	63.75°	65°	66.25°	67.5°	68.75°	70°	71.25°	72.5°	73.75°
-78.75°	1	1	0	0	0	0	0	0	0	0	0
-80°	0	0	0	0	0	0	0	0	0	0	0
-81.25°	0	0	0	0	0	0	0	0	0	0	0
-82.5°	0	0	0	0	0	0	0	0	0	0	0
-83.75°	0	0	0	0	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0	0	0	0	0
-86.25°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-88.75°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	75°	76.25°	77.5°	78.75°	80°	81.25°	82.5°	83.75°	85°	86.25°	87.5°
90°	0	0	0	0	0	0	0	0	0	0	0
88.75°	0	0	0	0	0	0	0	0	0	0	0
87.5°	0	0	0	0	0	0	0	0	0	0	0
86.25°	0	0	0	0	0	0	0	0	0	0	0
85°	0	0	0	0	0	0	0	0	0	0	0
83.75°	0	0	0	0	0	0	0	0	0	0	0
82.5°	0	0	0	0	0	0	0	0	0	0	0
81.25°	0	0	0	0	0	0	0	0	0	0	0
80°	0	0	0	0	0	0	0	0	0	0	0
78.75°	0	0	0	0	0	0	0	0	0	0	0
77.5°	0	0	0	0	0	0	0	0	0	0	0
76.25°	0	0	0	0	0	0	0	0	0	0	0
75°	0	0	0	0	0	0	0	0	0	0	0
73.75°	0	0	0	0	0	0	0	0	0	0	0
72.5°	0	0	0	0	0	0	0	0	0	0	0
71.25°	0	0	0	0	0	0	0	0	0	0	0
70°	1	0	0	0	0	0	0	0	0	0	0
68.75°	1	0	0	0	0	0	0	0	0	0	0
67.5°	1	1	0	0	0	0	0	0	0	0	0
66.25°	1	1	1	0	0	0	0	0	0	0	0
65°	1	1	1	0	0	0	0	0	0	0	0
63.75°	1	1	1	0	0	0	0	0	0	0	0
62.5°	1	1	1	1	0	0	0	0	0	0	0
61.25°	1	1	1	1	0	0	0	0	0	0	0
60°	1	1	1	1	0	0	0	0	0	0	0
58.75°	1	1	1	1	1	0	0	0	0	0	0
57.5°	1	1	1	1	1	0	0	0	0	0	0
56.25°	1	1	1	1	1	0	0	0	0	0	0
55°	1	1	1	1	1	1	0	0	0	0	0
53.75°	1	1	1	1	1	1	0	0	0	0	0
52.5°	1	1	1	1	1	1	0	0	0	0	0
51.25°	1	1	1	1	1	1	0	0	0	0	0
50°	1	1	1	1	1	1	0	0	0	0	0
48.75°	1	1	1	1	1	1	0	0	0	0	0
47.5°	1	1	1	1	1	1	1	0	0	0	0
46.25°	1	1	1	1	1	1	1	0	0	0	0
45°	1	1	1	1	1	1	1	0	0	0	0
43.75°	1	1	1	1	1	1	1	0	0	0	0
42.5°	1	1	1	1	1	1	1	0	0	0	0
41.25°	1	1	1	1	1	1	1	0	0	0	0
40°	1	1	1	1	1	1	1	0	0	0	0
38.75°	1	1	1	1	1	1	1	0	0	0	0
37.5°	1	1	1	1	1	1	1	0	0	0	0
36.25°	1	1	1	1	1	1	1	1	0	0	0
35°	1	1	1	1	1	1	1	1	0	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	75°	76.25°	77.5°	78.75°	80°	81.25°	82.5°	83.75°	85°	86.25°	87.5°
33.75°	1	1	1	1	1	1	1	1	0	0	0
32.5°	1	1	1	1	1	1	1	1	0	0	0
31.25°	1	1	1	1	1	1	1	1	0	0	0
30°	1	1	1	1	1	1	1	1	0	0	0
28.75°	1	1	1	1	1	1	1	1	0	0	0
27.5°	1	1	1	1	1	1	1	1	0	0	0
26.25°	1	1	1	1	1	1	1	1	0	0	0
25°	1	1	1	1	1	1	1	1	0	0	0
23.75°	1	1	1	1	1	1	1	1	0	0	0
22.5°	1	1	1	1	1	1	1	1	0	0	0
21.25°	1	1	1	1	1	1	1	1	0	0	0
20°	1	1	1	1	1	1	1	1	0	0	0
18.75°	1	1	1	1	1	1	1	1	0	0	0
17.5°	1	1	1	1	1	1	1	1	0	0	0
16.25°	1	1	1	1	1	1	1	1	0	0	0
15°	1	1	1	1	1	1	1	1	0	0	0
13.75°	1	1	1	1	1	1	1	1	0	0	0
12.5°	1	1	1	1	1	1	1	1	0	0	0
11.25°	1	1	1	1	1	1	1	1	0	0	0
10°	1	1	1	1	1	1	1	1	0	0	0
8.75°	1	1	1	1	1	1	1	1	0	0	0
7.5°	1	1	1	1	1	1	1	1	0	0	0
6.25°	1	1	1	1	1	1	1	1	0	0	0
5°	1	1	1	1	1	1	1	1	0	0	0
3.75°	1	1	1	1	1	1	1	1	0	0	0
2.5°	1	1	1	1	1	1	1	1	0	0	0
1.25°	1	1	1	1	1	1	1	1	0	0	0
0°	1	1	1	1	1	1	1	1	1	0	0
-1.25°	1	1	1	1	1	1	1	1	0	0	0
-2.5°	1	1	1	1	1	1	1	1	0	0	0
-3.75°	1	1	1	1	1	1	1	1	0	0	0
-5°	1	1	1	1	1	1	1	1	0	0	0
-6.25°	1	1	1	1	1	1	1	1	0	0	0
-7.5°	1	1	1	1	1	1	1	1	0	0	0
-8.75°	1	1	1	1	1	1	1	1	0	0	0
-10°	1	1	1	1	1	1	1	1	0	0	0
-11.25°	1	1	1	1	1	1	1	1	0	0	0
-12.5°	1	1	1	1	1	1	1	1	0	0	0
-13.75°	1	1	1	1	1	1	1	1	0	0	0
-15°	1	1	1	1	1	1	1	1	0	0	0
-16.25°	1	1	1	1	1	1	1	1	0	0	0
-17.5°	1	1	1	1	1	1	1	1	0	0	0
-18.75°	1	1	1	1	1	1	1	1	0	0	0
-20°	1	1	1	1	1	1	1	1	0	0	0
-21.25°	1	1	1	1	1	1	1	1	0	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	75°	76.25°	77.5°	78.75°	80°	81.25°	82.5°	83.75°	85°	86.25°	87.5°
-22.5°	1	1	1	1	1	1	1	1	0	0	0
-23.75°	1	1	1	1	1	1	1	1	0	0	0
-25°	1	1	1	1	1	1	1	1	0	0	0
-26.25°	1	1	1	1	1	1	1	1	0	0	0
-27.5°	1	1	1	1	1	1	1	1	0	0	0
-28.75°	1	1	1	1	1	1	1	1	0	0	0
-30°	1	1	1	1	1	1	1	1	0	0	0
-31.25°	1	1	1	1	1	1	1	1	0	0	0
-32.5°	1	1	1	1	1	1	1	1	0	0	0
-33.75°	1	1	1	1	1	1	1	1	0	0	0
-35°	1	1	1	1	1	1	1	1	0	0	0
-36.25°	1	1	1	1	1	1	1	1	0	0	0
-37.5°	1	1	1	1	1	1	1	0	0	0	0
-38.75°	1	1	1	1	1	1	1	0	0	0	0
-40°	1	1	1	1	1	1	1	0	0	0	0
-41.25°	1	1	1	1	1	1	1	0	0	0	0
-42.5°	1	1	1	1	1	1	1	0	0	0	0
-43.75°	1	1	1	1	1	1	1	0	0	0	0
-45°	1	1	1	1	1	1	1	0	0	0	0
-46.25°	1	1	1	1	1	1	1	0	0	0	0
-47.5°	1	1	1	1	1	1	1	0	0	0	0
-48.75°	1	1	1	1	1	1	0	0	0	0	0
-50°	1	1	1	1	1	1	0	0	0	0	0
-51.25°	1	1	1	1	1	1	0	0	0	0	0
-52.5°	1	1	1	1	1	1	0	0	0	0	0
-53.75°	1	1	1	1	1	1	0	0	0	0	0
-55°	1	1	1	1	1	1	0	0	0	0	0
-56.25°	1	1	1	1	1	0	0	0	0	0	0
-57.5°	1	1	1	1	1	0	0	0	0	0	0
-58.75°	1	1	1	1	1	0	0	0	0	0	0
-60°	1	1	1	1	0	0	0	0	0	0	0
-61.25°	1	1	1	1	0	0	0	0	0	0	0
-62.5°	1	1	1	1	0	0	0	0	0	0	0
-63.75°	1	1	1	0	0	0	0	0	0	0	0
-65°	1	1	1	0	0	0	0	0	0	0	0
-66.25°	1	1	1	0	0	0	0	0	0	0	0
-67.5°	1	1	0	0	0	0	0	0	0	0	0
-68.75°	1	0	0	0	0	0	0	0	0	0	0
-70°	1	0	0	0	0	0	0	0	0	0	0
-71.25°	0	0	0	0	0	0	0	0	0	0	0
-72.5°	0	0	0	0	0	0	0	0	0	0	0
-73.75°	0	0	0	0	0	0	0	0	0	0	0
-75°	0	0	0	0	0	0	0	0	0	0	0
-76.25°	0	0	0	0	0	0	0	0	0	0	0
-77.5°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	75°	76.25°	77.5°	78.75°	80°	81.25°	82.5°	83.75°	85°	86.25°	87.5°
-78.75°	0	0	0	0	0	0	0	0	0	0	0
-80°	0	0	0	0	0	0	0	0	0	0	0
-81.25°	0	0	0	0	0	0	0	0	0	0	0
-82.5°	0	0	0	0	0	0	0	0	0	0	0
-83.75°	0	0	0	0	0	0	0	0	0	0	0
-85°	0	0	0	0	0	0	0	0	0	0	0
-86.25°	0	0	0	0	0	0	0	0	0	0	0
-87.5°	0	0	0	0	0	0	0	0	0	0	0
-88.75°	0	0	0	0	0	0	0	0	0	0	0
-90°	0	0	0	0	0	0	0	0	0	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	88.75°	90°
90°	0	0
88.75°	0	0
87.5°	0	0
86.25°	0	0
85°	0	0
83.75°	0	0
82.5°	0	0
81.25°	0	0
80°	0	0
78.75°	0	0
77.5°	0	0
76.25°	0	0
75°	0	0
73.75°	0	0
72.5°	0	0
71.25°	0	0
70°	0	0
68.75°	0	0
67.5°	0	0
66.25°	0	0
65°	0	0
63.75°	0	0
62.5°	0	0
61.25°	0	0
60°	0	0
58.75°	0	0
57.5°	0	0
56.25°	0	0
55°	0	0
53.75°	0	0
52.5°	0	0
51.25°	0	0
50°	0	0
48.75°	0	0
47.5°	0	0
46.25°	0	0
45°	0	0
43.75°	0	0
42.5°	0	0
41.25°	0	0
40°	0	0
38.75°	0	0
37.5°	0	0
36.25°	0	0
35°	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)
 CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	88.75°	90°
33.75°	0	0
32.5°	0	0
31.25°	0	0
30°	0	0
28.75°	0	0
27.5°	0	0
26.25°	0	0
25°	0	0
23.75°	0	0
22.5°	0	0
21.25°	0	0
20°	0	0
18.75°	0	0
17.5°	0	0
16.25°	0	0
15°	0	0
13.75°	0	0
12.5°	0	0
11.25°	0	0
10°	0	0
8.75°	0	0
7.5°	0	0
6.25°	0	0
5°	0	0
3.75°	0	0
2.5°	0	0
1.25°	0	0
0°	0	0
-1.25°	0	0
-2.5°	0	0
-3.75°	0	0
-5°	0	0
-6.25°	0	0
-7.5°	0	0
-8.75°	0	0
-10°	0	0
-11.25°	0	0
-12.5°	0	0
-13.75°	0	0
-15°	0	0
-16.25°	0	0
-17.5°	0	0
-18.75°	0	0
-20°	0	0
-21.25°	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	88.75°	90°
-22.5°	0	0
-23.75°	0	0
-25°	0	0
-26.25°	0	0
-27.5°	0	0
-28.75°	0	0
-30°	0	0
-31.25°	0	0
-32.5°	0	0
-33.75°	0	0
-35°	0	0
-36.25°	0	0
-37.5°	0	0
-38.75°	0	0
-40°	0	0
-41.25°	0	0
-42.5°	0	0
-43.75°	0	0
-45°	0	0
-46.25°	0	0
-47.5°	0	0
-48.75°	0	0
-50°	0	0
-51.25°	0	0
-52.5°	0	0
-53.75°	0	0
-55°	0	0
-56.25°	0	0
-57.5°	0	0
-58.75°	0	0
-60°	0	0
-61.25°	0	0
-62.5°	0	0
-63.75°	0	0
-65°	0	0
-66.25°	0	0
-67.5°	0	0
-68.75°	0	0
-70°	0	0
-71.25°	0	0
-72.5°	0	0
-73.75°	0	0
-75°	0	0
-76.25°	0	0
-77.5°	0	0



REPORT NUMBER: P220572 (CONVERTED FROM TYPE C PHOTOMETRY)

CATALOG NUMBER: 1003-[A1, S1, SU1]-FL-LED4080-S-WT-L1-UNV

CANDELA DISTRIBUTION (continued):

	88.75°	90°
-78.75°	0	0
-80°	0	0
-81.25°	0	0
-82.5°	0	0
-83.75°	0	0
-85°	0	0
-86.25°	0	0
-87.5°	0	0
-88.75°	0	0
-90°	0	0

(END OF REPORT)