

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: METALUX

Report Number: P1444465

Luminaire Tested: EHBR1-36-UNV-TA-L830

Issue Date: 5/1/2026

Test Information

Test Method: LM-79-2019
Report Number: P1444465
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (C80-8019A)
Test Lab: INNOVATION CENTER
Issue Date: 5/1/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: METALUX
Catalog Number: EHBR1-36-UNV-TA-L830
Description: Elevate Round Highbay at, 36000 lumens, 3000K 80CRI LEDs with TA lens
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 33724.4 lumens
Efficiency: N/A
Efficacy: 176.2 lumens/watt
Spacing Criteria (0/90/45): 1.13 / 0.77 / 0.88
Luminous Opening: Circular (Dia: 1.71' x H: 0')
CIE Type: Direct

Input Watts (W): 191.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1444465
CATALOG NUMBER: EHBR1-36-UNV-TA-L830

Luminous Intensity Polar Plot



— 0°-180° - - 45°-225° - - - 90°-270° - · - 135°-315°



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	101	101	101	99			
1	112	108	105	103	109	106	103	101	102	100	98	98	96	95	94	93	92	90			
2	105	99	94	90	103	97	93	89	94	90	87	91	88	85	88	85	83	81			
3	99	91	85	81	97	90	84	80	87	82	79	84	81	77	82	79	76	74			
4	93	84	78	73	91	83	77	73	81	76	72	79	74	71	77	73	70	68			
5	88	78	72	67	86	77	71	66	75	70	66	73	69	65	72	68	64	63			
6	83	73	66	61	81	72	66	61	70	65	60	69	64	60	67	63	60	58			
7	78	68	61	57	77	67	61	56	66	60	56	65	59	56	63	59	55	54			
8	74	64	57	53	73	63	57	52	62	56	52	61	56	52	60	55	52	50			
9	70	60	53	49	69	59	53	49	58	53	49	57	52	48	56	52	48	47			
10	67	56	50	46	66	56	50	46	55	49	46	54	49	45	53	49	45	44			

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	136793	136793	136793	136793
5°	138352	142385	136415	144251
10°	140424	150477	137057	149482
15°	142064	137326	137739	131797
20°	141582	103021	136948	95319
25°	135008	65639	130546	59555
30°	118883	39760	114278	36336
35°	92296	25168	86987	22295
40°	58960	15943	53943	14981
45°	30732	12561	30223	12354
50°	18257	11321	17698	11144
55°	14213	10884	13688	10786
60°	12273	11346	11751	11198
65°	11841	12171	11389	11756
70°	12017	13239	11418	12740
75°	13630	14895	12895	14236
80°	15702	18357	14236	16756
85°	19252	23061	15556	19742

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 25°
 Vertical Angle: 45°
 Luminance: 47032 cd/sqm



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	2870.7	8.5
10°-20°	8075.7	23.9
20°-30°	9197.6	27.3
30°-40°	6610.8	19.6
40°-50°	3048.9	9.0
50°-60°	1459.0	4.3
60°-70°	1064.6	3.2
70°-80°	808.8	2.4
80°-90°	367.9	1.1
90°-100°	11.9	0.0
100°-110°	8.6	0.0
110°-120°	14.7	0.0
120°-130°	24.6	0.1
130°-140°	36.2	0.1
140°-150°	43.1	0.1
150°-160°	40.5	0.1
160°-170°	29.6	0.1
170°-180°	11.2	0.0
0°-30°	20144.0	59.7
0°-40°	26754.8	79.3
0°-60°	31262.7	92.7
0°-90°	33503.9	99.3
90°-120°	35.3	0.1
90°-150°	139.2	0.4
90°-180°	220.0	0.7
0°-180°	33724.4	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	29129	29129	29129	29129	29129	
5°	29349	30205	28938	30600	29349	2805
15°	29221	28246	28331	27109	29221	8233
25°	26056	12668	25194	11494	26056	11812
35°	16100	4390	15173	3889	16100	9881
45°	4627	1891	4551	1860	4627	3936
55°	1736	1329	1672	1317	1736	1602
65°	1066	1095	1025	1058	1066	1064
75°	751	821	711	785	751	781
85°	357	428	289	366	357	336
90°	81	107	12	18	81	53
95°	5	5	5	5	5	4
105°	9	7	9	7	9	10
115°	19	10	20	10	19	19
125°	37	16	38	18	37	33
135°	59	32	61	35	59	45
145°	78	58	80	62	78	49
155°	92	82	94	86	92	42
165°	107	101	109	104	107	30
175°	119	118	120	119	119	11
180°	121	121	121	121	121	



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1
2.5°	29240.4	29238.0	29237.6	29235.5	29235.0	29235.0	29234.0	29231.6	29230.1	29226.8	29223.0
5°	29348.9	29347.6	29348.3	29348.6	29346.5	29341.9	29334.8	29326.1	29315.1	29304.7	29295.5
7.5°	29432.8	29434.8	29437.4	29436.8	29430.5	29419.8	29405.3	29397.0	29401.9	29417.7	29454.1
10°	29448.1	29460.6	29465.5	29464.0	29451.3	29442.1	29445.6	29476.4	29537.9	29619.9	29731.9
12.5°	29388.4	29403.8	29403.2	29398.1	29385.8	29398.3	29443.0	29534.9	29666.6	29828.2	30017.8
15°	29220.7	29240.6	29235.0	29228.4	29220.2	29261.3	29350.6	29510.2	29713.5	29941.4	30174.8
17.5°	28895.2	28919.2	28907.6	28900.1	28893.2	28970.3	29123.7	29357.3	29613.5	29871.3	30092.3
20°	28330.7	28346.7	28319.0	28305.9	28316.9	28468.0	28693.9	28992.3	29262.3	29506.0	29657.2
22.5°	27409.2	27429.2	27377.1	27371.0	27435.4	27667.4	27953.3	28286.8	28540.5	28733.7	28791.9
25°	26055.5	26075.1	26013.2	26050.2	26159.7	26475.6	26816.1	27172.9	27389.4	27532.5	27493.0
27.5°	24228.2	24246.1	24187.4	24263.0	24436.0	24851.3	25252.0	25638.9	25831.9	25932.2	25805.1
30°	21923.7	21961.0	21891.5	21997.0	22261.2	22800.1	23259.3	23693.3	23885.7	23961.9	23764.2
32.5°	19186.5	19239.5	19163.0	19320.0	19688.6	20336.0	20857.6	21342.5	21555.4	21642.5	21419.1
35°	16099.5	16175.5	16087.7	16323.3	16777.9	17498.8	18076.4	18617.8	18869.8	18993.4	18768.3
37.5°	12828.8	12901.3	12853.8	13168.1	13667.2	14414.5	15004.1	15588.1	15872.7	16058.1	15880.6
40°	9617.8	9684.1	9720.0	10079.4	10548.9	11253.3	11819.6	12397.4	12715.8	12948.4	12839.0
42.5°	6788.2	6855.1	6977.3	7324.0	7715.6	8298.7	8783.7	9302.5	9606.7	9854.8	9812.7
45°	4627.4	4705.0	4858.1	5142.1	5425.2	5843.6	6199.7	6603.2	6851.7	7079.0	7081.7
47.5°	3242.7	3297.2	3434.0	3627.9	3812.5	4336.1	4357.7	4556.0	4723.0	4892.9	4914.9
50°	2499.0	2531.9	2604.4	2712.5	2817.2	2953.1	3077.5	3221.2	3324.0	3417.1	3439.4
52.5°	2054.1	2074.9	2111.8	2170.4	2231.1	2305.0	2371.6	2450.5	2506.4	2556.3	2566.8
55°	1736.0	1753.3	1808.2	1819.4	1888.8	1902.2	1931.8	1979.8	2012.3	2042.2	2049.6
57.5°	1496.0	1508.6	1520.3	1545.2	1566.6	1597.7	1622.7	1657.1	1677.6	1699.2	1701.1
60°	1306.7	1315.8	1324.0	1341.4	1355.9	1377.5	1394.8	1418.2	1432.9	1449.1	1451.0
62.5°	1165.8	1172.3	1177.8	1189.2	1199.6	1216.2	1229.9	1249.5	1263.2	1275.7	1278.5
65°	1065.6	1070.4	1073.9	1082.6	1091.6	1105.8	1118.2	1134.2	1144.2	1153.8	1155.9
67.5°	976.9	981.4	985.1	993.0	999.3	1009.8	1018.1	1030.1	1037.7	1045.4	1045.6
70°	875.2	879.4	882.2	889.6	894.7	903.7	910.4	921.2	928.9	937.5	939.6
72.5°	804.8	807.3	811.1	817.7	824.8	834.5	843.4	854.7	864.1	872.9	876.7
75°	751.2	754.1	756.7	762.4	767.3	775.4	782.2	792.4	800.6	810.1	814.7
77.5°	674.0	677.3	679.5	685.2	689.4	697.3	702.3	711.4	718.1	726.8	731.0
80°	580.6	583.8	585.3	590.6	594.0	601.2	606.1	614.9	620.6	629.2	634.2
82.5°	477.1	480.1	480.9	486.1	487.8	493.8	497.4	506.4	513.3	524.6	532.3
85°	357.3	358.3	360.1	358.8	366.0	366.4	374.6	376.1	387.0	389.8	402.0
87.5°	218.4	221.6	223.2	228.2	230.3	235.3	236.9	242.1	245.0	251.1	253.9
90°	80.8	85.1	85.9	91.0	91.8	96.2	96.6	101.7	102.6	107.8	108.8
92.5°	4.9	4.9	4.8	5.1	5.1	5.7	6.1	6.3	6.4	6.9	7.0
95°	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	4.9
97.5°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.5	5.5
100°	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.3
102.5°	7.6	7.6	7.6	7.6	7.6	7.5	7.6	7.5	7.5	7.5	7.2
105°	9.0	8.9	9.0	8.9	8.9	8.9	8.9	8.6	8.6	8.5	8.5
107.5°	10.7	10.6	10.6	10.6	10.6	10.5	10.5	10.4	10.2	10.0	10.0
110°	13.0	12.8	12.8	12.7	12.6	12.6	12.6	12.2	12.2	12.0	11.9



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	15.8	15.6	15.5	15.5	15.4	15.0	14.9	14.7	14.6	14.2	14.1
115°	19.1	18.9	18.8	18.5	18.4	18.0	17.8	17.5	17.2	16.9	16.6
117.5°	22.9	22.7	22.5	22.2	21.8	21.5	21.2	20.7	20.3	19.9	19.6
120°	27.4	26.9	26.7	26.1	25.8	25.3	24.9	24.4	23.9	23.2	22.9
122.5°	31.9	31.6	31.3	30.6	30.3	29.6	29.1	28.3	27.8	27.2	26.6
125°	37.0	36.5	36.3	35.6	34.9	34.3	33.7	33.0	32.3	31.4	30.7
127.5°	42.3	41.9	41.5	40.7	40.1	39.3	38.5	37.7	37.0	36.0	35.3
130°	47.9	47.4	46.8	46.1	45.4	44.6	43.7	42.7	42.0	40.9	40.1
132.5°	53.4	53.0	52.5	51.7	51.0	49.8	49.1	48.0	47.0	46.1	45.1
135°	59.0	58.5	58.0	57.2	56.5	55.4	54.4	53.3	52.4	51.1	50.3
137.5°	64.4	63.8	63.2	62.4	61.6	60.4	59.6	58.5	57.4	56.2	55.3
140°	69.4	68.8	68.2	67.3	66.6	65.7	64.5	63.5	62.4	61.2	60.3
142.5°	74.2	73.5	73.0	72.1	71.4	70.3	69.3	68.1	67.2	65.9	65.1
145°	78.3	77.7	77.2	76.4	75.6	74.5	73.6	72.4	71.6	70.5	69.5
147.5°	82.1	81.5	81.1	80.3	79.7	78.6	77.7	76.6	75.8	74.8	74.1
150°	85.4	85.0	84.5	83.8	83.1	82.2	81.4	80.6	79.7	78.7	77.9
152.5°	88.2	87.7	87.3	86.6	86.1	85.1	84.5	83.6	82.8	82.0	81.2
155°	91.5	91.0	90.5	89.9	89.3	88.5	87.8	87.0	86.4	85.5	84.9
157.5°	95.3	94.6	94.1	93.4	92.9	92.2	91.5	90.8	90.1	89.5	88.9
160°	99.2	98.6	98.2	97.5	96.9	96.1	95.5	94.8	94.3	93.6	93.0
162.5°	103.4	102.8	102.2	101.6	101.1	100.3	99.8	99.2	98.6	97.9	97.4
165°	107.4	107.0	106.4	105.9	105.4	104.8	104.3	103.6	103.1	102.5	102.0
167.5°	111.4	110.9	110.5	110.0	109.5	109.0	108.5	108.0	107.6	107.0	106.6
170°	114.7	114.1	113.8	113.4	113.1	112.6	112.3	111.8	111.4	111.0	110.6
172.5°	117.0	116.6	116.3	116.2	115.7	115.5	115.2	114.8	114.7	114.2	114.1
175°	118.9	118.5	118.4	118.2	118.0	117.7	117.7	117.5	117.5	117.1	116.9
177.5°	120.1	119.9	119.9	119.8	119.8	119.7	119.6	119.4	119.3	119.3	119.1
180°	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1
2.5°	29220.2	29216.6	29211.7	29205.6	29200.3	29194.2	29179.6	29175.3	29180.2	29183.4	29190.1
5°	29289.6	29291.6	29292.4	29305.7	29317.1	29345.8	29569.8	29658.9	29727.8	29771.5	29837.9
7.5°	29498.9	29566.3	29632.9	29722.5	29799.8	29904.2	30296.3	30463.2	30581.9	30667.1	30772.1
10°	29853.7	30000.7	30138.6	30300.1	30438.9	30598.0	30962.9	31125.5	31228.2	31302.8	31372.6
12.5°	30211.0	30414.9	30599.2	30778.9	30929.3	31067.1	31195.5	31252.4	31257.2	31259.6	31222.6
15°	30397.1	30592.1	30754.5	30873.4	30961.6	31000.8	30779.7	30663.8	30517.3	30396.6	30198.1
17.5°	30279.7	30396.6	30466.7	30459.8	30423.4	30301.1	29675.2	29331.0	28989.2	28681.2	28277.3
20°	29757.5	29748.6	29687.5	29514.7	29306.4	28982.6	27909.5	27290.4	26691.8	26166.0	25528.2
22.5°	28786.0	28633.1	28420.0	28047.4	27633.4	27067.5	25529.7	24619.1	23785.7	23049.5	22224.8
25°	27378.3	27063.9	26670.8	26079.2	25435.8	24610.6	22715.2	21582.4	20581.9	19714.2	18762.7
27.5°	25576.9	25103.1	24527.2	23708.3	22836.7	21779.4	19678.1	18428.0	17353.9	16423.5	15410.8
30°	23444.1	22828.1	22084.2	21067.9	20016.5	18817.5	16686.2	15420.0	14332.9	13375.7	12362.2
32.5°	21033.9	20312.3	19440.6	18300.0	17163.0	15930.1	13871.9	12646.2	11607.7	10687.0	9769.7
35°	18375.6	17601.8	16679.6	15516.2	14386.0	13187.4	11298.8	10193.6	9276.5	8462.7	7721.9
37.5°	15524.1	14764.2	13887.7	12791.2	11743.2	10657.0	9027.4	8101.4	7331.8	6656.3	6084.4
40°	12559.3	11894.3	11136.0	10188.0	9293.6	8389.1	7051.4	6316.3	5709.0	5193.8	4765.1
42.5°	9630.8	9115.5	8533.9	7784.8	7100.3	6411.6	5382.0	4837.4	4387.5	4016.7	3713.7
45°	6987.5	6642.8	6252.7	5731.9	5258.3	4777.9	4045.1	3662.4	3369.4	3130.3	2928.1
47.5°	4884.6	4684.7	4672.4	4191.2	3843.9	3550.1	3078.0	2836.4	2656.8	2511.9	2383.9
50°	3430.3	3333.6	3213.4	3041.7	2880.5	2714.4	2426.8	2280.7	2175.5	2087.7	2006.8
52.5°	2564.4	2514.2	2450.1	2359.0	2271.7	2178.3	1996.3	1903.3	1870.2	1788.5	1724.4
55°	2048.2	2019.5	1983.0	1929.5	1876.4	1855.2	1699.1	1630.1	1586.3	1554.0	1519.6
57.5°	1701.3	1679.9	1658.3	1622.0	1591.3	1554.0	1471.2	1435.8	1409.8	1390.8	1366.9
60°	1451.2	1438.4	1426.3	1405.1	1388.4	1368.3	1315.8	1295.7	1282.2	1270.7	1255.6
62.5°	1280.9	1274.3	1268.0	1256.7	1248.3	1237.4	1201.4	1191.9	1185.0	1179.3	1170.0
65°	1158.0	1153.2	1149.7	1142.1	1138.0	1131.6	1100.7	1094.3	1090.0	1088.0	1082.6
67.5°	1046.2	1041.2	1039.0	1033.6	1031.9	1027.9	1002.6	999.0	997.6	998.3	996.3
70°	941.7	939.6	940.7	939.9	942.2	943.0	927.6	927.5	929.2	932.4	932.8
72.5°	879.1	879.1	880.2	880.8	883.0	884.2	871.4	870.8	871.5	873.9	874.0
75°	819.5	820.5	823.7	824.8	827.5	828.1	811.2	809.2	809.3	811.7	810.8
77.5°	737.0	740.6	746.7	749.9	755.2	756.1	737.2	734.9	735.0	737.4	735.4
80°	643.4	650.3	660.0	666.8	674.8	678.1	658.6	654.0	649.7	649.0	645.1
82.5°	543.9	552.3	564.1	570.3	578.8	580.7	548.2	542.1	538.4	538.7	535.1
85°	415.3	421.6	432.3	435.7	441.0	440.5	403.4	387.5	391.7	385.2	390.3
87.5°	260.5	264.2	270.9	271.7	274.2	273.7	236.3	228.9	226.8	227.0	224.2
90°	113.7	115.1	119.8	118.9	121.7	120.1	88.7	84.2	82.5	84.9	82.1
92.5°	7.5	7.5	7.8	7.9	8.2	8.4	5.2	4.3	4.7	4.4	4.9
95°	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.8	4.8
97.5°	5.5	5.5	5.4	5.4	5.4	5.4	5.4	5.4	5.4	5.2	5.2
100°	6.3	6.3	6.2	6.2	6.1	6.1	6.1	6.1	6.1	5.8	5.8
102.5°	7.1	7.1	7.0	6.9	6.8	6.8	6.9	6.9	6.8	6.6	6.5
105°	8.4	8.3	8.2	7.9	7.8	7.7	7.9	7.8	7.7	7.6	7.5
107.5°	9.8	9.7	9.4	9.2	9.1	8.9	9.2	9.1	8.9	8.5	8.4
110°	11.6	11.3	11.1	10.8	10.5	10.2	10.7	10.5	10.2	9.9	9.7



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	13.6	13.4	13.0	12.6	12.2	11.9	12.6	12.5	12.0	11.4	11.2
115°	16.1	15.8	15.4	14.9	14.4	14.0	14.7	14.6	14.1	13.5	13.0
117.5°	19.0	18.5	18.0	17.5	16.9	16.3	17.4	17.0	16.4	15.8	15.4
120°	22.2	21.7	21.1	20.5	19.8	19.1	20.3	20.0	19.4	18.6	18.0
122.5°	25.9	25.3	24.5	23.9	23.1	22.4	23.8	23.5	22.7	21.9	21.2
125°	30.0	29.2	28.5	27.7	26.8	26.0	27.7	27.4	26.6	25.7	24.9
127.5°	34.5	33.7	32.8	32.0	31.0	30.3	31.9	31.7	30.7	29.9	28.9
130°	39.2	38.3	37.4	36.5	35.6	34.8	36.6	36.3	35.5	34.5	33.5
132.5°	44.1	43.3	42.2	41.5	40.5	39.5	41.6	41.3	40.6	39.5	38.7
135°	49.3	48.3	47.4	46.5	45.4	44.7	46.9	46.7	46.0	44.9	44.0
137.5°	54.2	53.3	52.4	51.6	50.7	49.7	52.5	52.4	51.6	50.5	49.7
140°	59.4	58.5	57.5	56.8	55.8	55.2	58.0	58.0	57.3	56.5	55.6
142.5°	64.0	63.2	62.4	61.7	60.9	60.2	63.5	63.6	62.9	62.1	61.4
145°	68.6	67.9	67.1	66.4	65.7	65.1	68.8	69.1	68.6	67.8	67.2
147.5°	73.0	72.3	71.6	70.9	70.3	70.0	74.1	74.5	74.1	73.4	72.9
150°	77.1	76.4	75.7	75.1	74.7	74.3	79.2	79.9	79.4	79.1	78.5
152.5°	80.5	79.8	79.2	78.6	78.0	77.7	84.0	85.1	84.8	84.2	83.8
155°	84.2	83.6	82.9	82.5	82.0	81.7	88.9	90.1	89.8	89.5	89.1
157.5°	88.2	87.6	86.9	86.5	86.1	85.6	93.4	95.1	94.7	94.3	94.0
160°	92.5	91.9	91.2	90.8	90.2	89.8	98.0	99.7	99.4	99.0	98.6
162.5°	96.8	96.4	95.7	95.3	94.7	94.3	102.5	104.3	103.9	103.5	103.2
165°	101.4	101.0	100.4	100.0	99.6	99.2	107.0	108.6	108.4	108.0	107.6
167.5°	106.0	105.7	105.2	104.8	104.3	104.2	111.4	113.0	112.7	112.3	112.0
170°	110.3	110.0	109.6	109.3	109.1	109.0	115.1	116.3	116.2	115.9	115.6
172.5°	113.8	113.7	113.4	113.2	113.1	113.0	118.0	119.1	119.1	118.9	118.5
175°	116.8	116.6	116.5	116.5	116.3	116.2	120.3	121.1	121.0	120.8	120.6
177.5°	119.1	119.1	119.1	119.1	119.1	119.1	121.5	122.0	121.9	121.9	121.8
180°	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1
2.5°	29191.6	29201.8	29203.4	29215.3	29214.4	29228.6	29226.3	29238.0	29231.2	29240.8	29232.7
5°	29877.2	29939.4	29971.9	30032.6	30051.8	30106.1	30121.4	30170.9	30173.0	30212.3	30203.3
7.5°	30846.6	30938.2	30992.6	31067.6	31105.7	31168.1	31195.7	31241.9	31256.8	31293.5	31296.3
10°	31425.4	31469.9	31501.0	31521.9	31541.0	31549.9	31560.4	31557.6	31560.4	31556.3	31565.3
12.5°	31197.7	31132.7	31089.7	31008.3	30961.2	30871.3	30827.1	30740.6	30709.3	30635.0	30624.3
15°	30044.7	29818.2	29658.2	29425.4	29279.2	29050.2	28916.2	28709.7	28615.3	28451.1	28408.0
17.5°	27943.0	27522.6	27197.2	26779.9	26490.2	26100.2	25854.9	25532.0	25355.1	25094.8	25004.6
20°	24996.5	24374.5	23886.5	23305.0	22889.0	22370.6	22038.8	21620.2	21377.2	21057.4	20927.8
22.5°	21537.3	20762.8	20153.3	19466.5	18964.5	18386.8	17989.2	17536.3	17272.0	16924.5	16770.7
25°	17971.9	17117.8	16440.2	15716.6	15186.1	14607.0	14209.4	13764.5	13490.9	13161.1	13008.3
27.5°	14561.8	13697.3	13042.5	12369.7	11883.1	11360.6	11001.7	10613.4	10370.6	10089.0	9945.2
30°	11552.5	10790.0	10232.8	9674.4	9269.8	8845.3	8547.2	8225.2	8012.2	7771.2	7634.2
32.5°	9100.9	8512.2	8075.8	7632.8	7301.6	6946.9	6689.2	6405.2	6213.0	5997.7	5873.6
35°	7207.8	6750.4	6402.3	6037.7	5753.1	5451.0	5224.0	4978.8	4806.3	4621.0	4513.8
37.5°	5694.9	5331.2	5044.7	4741.8	4508.1	4257.9	4173.6	3892.2	3713.5	3565.6	3463.1
40°	4469.4	4180.2	3943.2	3711.5	3520.9	3331.1	3178.7	3028.5	2913.1	2807.3	2734.1
42.5°	3490.2	3280.6	3107.6	2937.9	2798.9	2660.5	2550.3	2446.7	2368.9	2299.8	2252.6
45°	2774.5	2630.5	2510.2	2390.7	2292.6	2200.2	2126.0	2059.9	2009.7	1968.1	1938.7
47.5°	2279.4	2180.8	2095.9	2015.2	1948.6	1888.1	1838.4	1822.2	1768.2	1731.8	1718.0
50°	1937.1	1877.5	1813.1	1753.6	1709.1	1664.9	1632.6	1601.0	1580.8	1564.0	1559.0
52.5°	1681.8	1636.1	1600.4	1562.6	1533.3	1501.7	1479.5	1458.5	1447.4	1438.6	1437.6
55°	1491.8	1460.0	1436.3	1411.0	1393.4	1374.9	1363.4	1352.2	1347.4	1343.0	1343.3
57.5°	1348.1	1326.8	1311.5	1295.0	1285.5	1276.6	1273.7	1270.9	1272.5	1273.1	1275.6
60°	1243.5	1229.6	1219.9	1210.5	1206.5	1203.7	1205.8	1208.4	1213.4	1217.5	1221.2
62.5°	1163.2	1155.3	1150.6	1145.5	1145.1	1145.3	1149.6	1153.8	1160.2	1165.0	1168.5
65°	1080.7	1076.1	1074.6	1071.3	1073.0	1073.9	1079.1	1082.4	1088.7	1092.5	1097.1
67.5°	997.2	996.1	997.1	997.1	1000.0	1002.5	1007.4	1011.1	1016.5	1020.0	1023.6
70°	935.6	936.0	938.2	938.7	941.8	943.5	947.9	950.2	955.1	958.0	962.5
72.5°	875.6	874.7	875.2	873.8	874.9	874.4	876.9	878.0	882.1	884.3	889.8
75°	811.8	809.1	808.5	805.6	805.7	803.6	804.6	804.4	807.2	808.3	812.1
77.5°	734.8	730.3	728.0	723.2	723.0	721.3	723.2	724.4	729.1	731.4	735.8
80°	642.6	635.5	632.2	626.6	627.5	627.2	632.0	635.6	641.4	642.5	648.0
82.5°	534.0	526.8	523.3	517.9	519.1	519.3	523.6	524.4	529.4	531.6	538.0
85°	382.4	385.2	377.5	378.1	376.5	379.5	382.4	386.0	390.2	397.3	402.7
87.5°	225.2	224.2	227.0	227.2	231.2	233.1	239.4	243.0	250.0	255.5	265.5
90°	83.1	80.5	83.5	83.1	87.8	87.6	91.6	90.6	95.5	96.5	102.6
92.5°	4.4	4.8	4.4	4.7	4.4	4.9	4.4	4.8	4.4	4.9	4.4
95°	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8
97.5°	5.2	5.2	5.2	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1
100°	5.7	5.7	5.7	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
102.5°	6.5	6.4	6.4	6.3	6.3	6.2	6.2	6.2	6.2	6.2	6.2
105°	7.2	7.1	7.0	6.9	6.9	6.8	6.8	6.6	6.6	6.6	6.6
107.5°	8.2	8.0	7.9	7.8	7.7	7.6	7.5	7.5	7.2	7.2	7.2
110°	9.3	9.1	9.0	8.6	8.5	8.4	8.2	8.2	8.0	7.9	7.9



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	10.8	10.5	10.0	9.8	9.6	9.3	9.2	9.1	9.0	8.9	8.6
115°	12.6	12.1	11.6	11.3	11.1	10.6	10.4	10.2	9.9	9.8	9.7
117.5°	14.7	14.1	13.5	13.0	12.6	12.2	11.9	11.4	11.2	11.1	11.1
120°	17.2	16.6	15.8	15.4	14.7	14.1	13.6	13.3	12.8	12.7	12.6
122.5°	20.3	19.6	18.6	18.0	17.2	16.6	16.0	15.5	15.0	14.7	14.4
125°	23.9	22.9	22.1	21.2	20.3	19.7	18.9	18.3	17.7	17.4	16.9
127.5°	27.9	26.9	25.9	25.0	24.0	23.2	22.4	21.7	21.0	20.4	19.9
130°	32.5	31.6	30.3	29.5	28.3	27.4	26.6	25.8	25.0	24.4	23.8
132.5°	37.6	36.6	35.5	34.5	33.3	32.4	31.4	30.5	29.6	28.9	28.3
135°	43.0	42.1	40.9	39.9	38.8	37.9	36.9	36.0	35.1	34.3	33.5
137.5°	48.8	47.9	46.8	46.0	44.8	43.9	42.7	42.0	40.9	40.4	39.5
140°	54.6	53.9	52.8	51.9	51.0	50.2	49.1	48.3	47.4	46.7	46.0
142.5°	60.4	59.7	58.8	58.1	57.2	56.5	55.5	54.7	53.9	53.2	52.5
145°	66.4	65.8	65.0	64.3	63.5	62.9	61.8	61.2	60.4	59.8	59.3
147.5°	72.2	71.6	70.9	70.3	69.5	68.8	68.1	67.7	66.8	66.4	65.8
150°	77.8	77.3	76.6	76.2	75.5	74.9	74.3	73.7	73.1	72.8	72.1
152.5°	83.3	82.8	82.2	81.9	81.2	80.7	80.1	79.7	79.2	78.7	78.0
155°	88.5	88.1	87.6	87.1	86.5	86.2	85.6	85.1	84.7	84.2	83.6
157.5°	93.6	93.2	92.6	92.3	91.6	91.2	90.8	90.4	89.8	89.5	89.0
160°	98.3	97.9	97.4	96.9	96.5	96.1	95.5	95.3	94.7	94.3	93.9
162.5°	102.8	102.4	102.0	101.6	101.1	100.7	100.2	99.8	99.3	98.9	98.4
165°	107.2	106.8	106.3	105.9	105.6	105.2	104.6	104.3	103.8	103.4	102.9
167.5°	111.7	111.3	110.9	110.5	110.0	109.6	109.2	108.8	108.4	108.0	107.4
170°	115.4	114.9	114.7	114.3	114.0	113.5	113.2	112.8	112.4	112.1	111.7
172.5°	118.3	118.2	117.9	117.7	117.3	117.0	116.8	116.5	116.2	115.9	115.6
175°	120.5	120.4	120.3	119.9	119.8	119.6	119.4	119.3	119.1	119.0	118.7
177.5°	121.8	121.7	121.7	121.5	121.3	121.3	121.2	121.2	121.1	121.0	121.0
180°	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1
2.5°	29241.1	29233.7	29237.2	29223.5	29226.8	29210.2	29208.7	29190.1	29188.2	29170.6	29164.1
5°	30231.2	30214.9	30233.2	30204.6	30210.3	30173.0	30169.9	30121.7	30105.1	30044.8	30018.9
7.5°	31319.3	31313.1	31324.4	31300.4	31299.7	31266.4	31252.6	31209.5	31182.8	31119.4	31079.1
10°	31557.6	31563.2	31554.1	31556.3	31543.4	31539.8	31526.5	31518.1	31496.5	31480.1	31455.8
12.5°	30567.8	30573.7	30536.0	30559.9	30541.0	30585.2	30581.6	30633.7	30641.6	30707.5	30732.5
15°	28280.1	28273.0	28200.6	28246.2	28221.7	28318.7	28340.3	28470.8	28540.5	28708.0	28810.8
17.5°	24824.2	24805.5	24703.5	24759.1	24730.9	24873.7	24921.7	25130.3	25260.4	25530.2	25722.4
20°	20704.6	20668.9	20549.5	20614.6	20585.5	20747.8	20816.3	21068.4	21236.1	21593.5	21847.7
22.5°	16533.8	16477.4	16360.5	16421.3	16393.7	16561.9	16651.0	16903.9	17096.1	17463.0	17759.7
25°	12788.5	12738.2	12625.2	12667.8	12657.5	12799.8	12879.0	13118.2	13307.1	13656.6	13939.8
27.5°	9754.1	9701.8	9599.7	9629.7	9619.4	9740.6	9815.3	10015.2	10177.6	10471.8	10720.5
30°	7465.4	7402.2	7315.6	7332.3	7325.2	7423.3	7493.1	7661.4	7800.6	8049.3	8263.6
32.5°	5722.2	5658.8	5579.1	5586.9	5576.4	5653.5	5710.9	5857.3	5978.7	6190.1	6376.6
35°	4378.3	4452.5	4282.5	4390.2	4278.0	4442.6	4383.4	4474.8	4579.3	4757.4	4912.9
37.5°	3365.9	3314.2	3270.4	3265.7	3265.6	3303.7	3348.6	3436.8	3528.8	3661.4	3798.5
40°	2667.3	2631.0	2602.7	2600.7	2602.7	2629.8	2663.1	2723.9	2791.3	2886.7	2987.4
42.5°	2212.2	2188.2	2171.1	2169.9	2175.3	2194.5	2217.7	2253.8	2297.7	2359.4	2428.5
45°	1914.7	1901.3	1891.8	1891.3	1893.7	1903.8	1917.1	1939.6	1967.4	2006.0	2049.6
47.5°	1705.9	1702.7	1696.8	1696.9	1694.2	1698.3	1699.8	1712.5	1727.3	1756.3	1813.5
50°	1553.9	1553.9	1549.8	1549.6	1545.8	1545.5	1542.3	1547.3	1554.1	1572.2	1590.4
52.5°	1433.7	1433.4	1428.9	1428.0	1423.9	1423.7	1420.9	1422.9	1423.8	1432.9	1443.8
55°	1339.9	1337.1	1331.2	1329.4	1327.8	1330.1	1329.0	1329.2	1328.0	1331.7	1335.0
57.5°	1272.5	1268.8	1263.3	1261.7	1261.3	1264.1	1264.2	1263.2	1258.1	1254.6	1249.9
60°	1219.1	1215.5	1209.6	1208.0	1208.9	1212.8	1212.6	1209.3	1201.8	1195.1	1187.6
62.5°	1166.8	1165.3	1162.3	1161.8	1161.1	1161.7	1159.0	1155.5	1148.1	1141.1	1132.8
65°	1096.5	1097.3	1095.0	1095.3	1092.6	1092.2	1088.1	1084.7	1077.2	1070.8	1062.3
67.5°	1023.5	1024.1	1022.2	1022.2	1020.8	1021.0	1018.6	1015.4	1009.0	1003.9	997.3
70°	963.4	964.9	963.9	964.2	962.5	961.8	957.9	954.9	948.3	943.9	938.0
72.5°	891.4	894.7	894.6	895.3	892.7	891.4	886.8	882.9	877.0	873.6	868.8
75°	813.6	817.8	819.1	820.9	817.2	815.3	810.3	807.2	802.3	800.2	797.1
77.5°	737.8	742.4	746.8	751.0	745.0	739.7	733.3	728.5	721.5	718.9	714.1
80°	652.6	660.8	670.6	678.8	668.2	657.4	646.9	639.1	629.9	626.2	620.1
82.5°	541.4	549.8	555.5	560.7	553.3	545.4	535.2	528.4	518.5	514.8	507.8
85°	411.3	421.8	425.2	428.0	423.2	419.0	409.4	396.6	390.3	380.6	375.4
87.5°	270.5	276.8	278.0	279.0	276.0	274.0	267.8	261.8	251.1	243.4	233.8
90°	102.6	107.0	104.8	106.7	102.8	102.9	96.6	94.4	85.5	82.1	74.1
92.5°	4.7	4.3	4.4	4.3	4.9	4.4	4.9	4.4	4.8	4.4	4.8
95°	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8
97.5°	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.2
100°	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
102.5°	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.3
105°	6.6	6.6	6.6	6.6	6.6	6.6	6.6	6.6	6.6	6.8	6.8
107.5°	7.1	7.1	7.1	7.1	7.2	7.2	7.2	7.2	7.2	7.2	7.5
110°	7.9	7.9	7.9	7.9	7.9	7.9	7.9	7.9	8.0	8.0	8.2



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.9	8.9	9.0	9.0
115°	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.7	9.8	9.8	10.0
117.5°	10.8	10.7	10.7	10.7	10.7	10.7	10.8	10.8	11.1	11.1	11.3
120°	12.5	12.1	12.1	12.1	12.1	12.1	12.2	12.2	12.6	12.6	13.0
122.5°	14.2	14.1	14.1	14.0	14.0	14.0	14.1	14.1	14.4	14.7	15.0
125°	16.8	16.4	16.3	16.2	16.2	16.2	16.3	16.6	16.9	17.0	17.6
127.5°	19.7	19.4	19.1	19.0	19.0	19.0	19.3	19.4	19.8	20.2	20.7
130°	23.3	22.9	22.9	22.6	22.6	22.6	22.9	23.1	23.5	23.9	24.5
132.5°	27.9	27.4	27.2	26.9	26.9	26.9	27.2	27.4	27.9	28.3	29.1
135°	33.2	32.7	32.4	32.1	32.1	32.0	32.3	32.5	33.1	33.5	34.2
137.5°	39.1	38.5	38.3	37.9	37.9	37.9	38.1	38.3	38.8	39.3	40.1
140°	45.4	44.9	44.7	44.3	44.3	44.1	44.4	44.6	45.1	45.5	46.2
142.5°	52.1	51.4	51.1	51.0	50.8	50.8	51.1	51.1	51.6	51.9	52.5
145°	58.7	58.2	58.0	57.6	57.5	57.5	57.6	57.9	58.2	58.5	59.0
147.5°	65.3	64.9	64.6	64.4	64.4	64.3	64.4	64.4	64.6	64.9	65.3
150°	71.9	71.4	71.0	70.8	70.7	70.6	70.7	70.6	70.8	70.9	71.4
152.5°	77.8	77.3	77.2	76.9	76.6	76.5	76.5	76.4	76.5	76.5	76.9
155°	83.5	83.1	82.8	82.5	82.2	82.1	82.1	81.9	82.0	81.9	82.0
157.5°	88.7	88.3	88.1	87.7	87.5	87.1	87.0	86.8	86.8	86.5	86.5
160°	93.6	93.0	92.7	92.5	92.2	91.8	91.6	91.2	91.1	90.9	90.8
162.5°	98.0	97.6	97.2	96.9	96.6	96.2	96.0	95.5	95.4	95.1	95.0
165°	102.5	102.0	101.7	101.2	101.0	100.6	100.3	99.9	99.8	99.4	99.3
167.5°	107.2	106.7	106.3	105.9	105.7	105.3	105.2	104.8	104.6	104.3	104.3
170°	111.4	111.0	110.7	110.4	110.3	109.9	109.8	109.5	109.3	109.2	109.2
172.5°	115.4	115.1	114.8	114.7	114.5	114.2	114.1	114.0	113.8	113.8	113.7
175°	118.5	118.3	118.2	118.0	117.9	117.9	117.7	117.7	117.7	117.7	117.7
177.5°	120.8	120.6	120.6	120.6	120.6	120.6	120.6	120.6	120.6	120.5	120.4
180°	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1
2.5°	29145.1	29137.5	29117.3	29107.4	29088.7	29079.3	29064.8	29055.3	29043.6	29034.8	29030.3
5°	29952.7	29915.4	29840.7	29794.7	29714.1	29661.0	29580.9	29522.2	29439.4	29378.5	29300.3
7.5°	31003.3	30946.1	30850.4	30777.9	30665.0	30578.9	30452.2	30351.0	30211.0	30094.9	29951.9
10°	31431.0	31397.6	31354.7	31308.1	31245.5	31184.3	31097.8	31009.7	30892.2	30775.4	30622.8
12.5°	30798.8	30830.3	30892.2	30921.1	30968.5	30984.6	31006.3	30996.2	30977.0	30929.3	30860.1
15°	29008.4	29139.5	29346.8	29490.2	29691.1	29832.2	30018.9	30139.0	30277.4	30360.1	30438.7
17.5°	26063.2	26316.8	26682.6	26974.4	27366.1	27684.6	28074.9	28381.5	28735.5	29007.1	29296.2
20°	22290.8	22646.0	23150.9	23579.7	24147.3	24628.7	25245.3	25761.9	26364.5	26866.9	27409.0
22.5°	18230.6	18648.5	19227.1	19744.2	20422.1	21027.5	21800.2	22483.2	23297.8	24027.6	24835.0
25°	14400.3	14809.9	15399.2	15934.8	16666.6	17333.5	18177.6	18961.1	19906.6	20788.1	21800.2
27.5°	11115.6	11479.5	11997.6	12479.6	13149.8	13804.6	14661.2	15496.7	16505.5	17452.9	18543.6
30°	8584.5	8879.6	9294.7	9682.5	10220.5	10755.9	11519.0	12291.8	13295.6	14277.2	15395.5
32.5°	6652.7	6904.3	7250.9	7565.6	7980.2	8383.9	8945.9	9563.4	10443.8	11384.3	12465.4
35°	5149.9	5365.2	5660.2	5931.3	6272.2	6592.7	7012.0	7452.8	8124.7	8915.8	9883.4
37.5°	4105.8	4193.6	4404.0	4626.2	4909.4	5172.8	5500.8	5826.7	6307.4	6931.6	7721.9
40°	3122.4	3261.8	3433.1	3608.1	3822.5	4033.7	4393.6	4566.8	4883.3	5331.4	5944.9
42.5°	2519.4	2617.4	2738.0	2859.7	3009.1	3156.2	3338.2	3523.5	3760.2	4063.6	4500.0
45°	2108.3	2172.1	2249.9	2331.0	2429.1	2529.5	2651.4	2778.7	2939.0	3125.5	3390.6
47.5°	1833.6	1868.9	1919.7	1975.1	2042.3	2111.8	2191.1	2272.2	2371.7	2482.5	2633.4
50°	1619.2	1648.7	1688.1	1725.1	1771.6	1842.8	1874.3	1919.0	1979.0	2044.0	2128.5
52.5°	1464.1	1483.7	1508.5	1529.7	1559.1	1585.8	1620.8	1651.6	1693.1	1732.2	1786.7
55°	1343.3	1350.5	1364.4	1378.2	1398.5	1416.7	1440.7	1460.9	1487.3	1510.7	1545.1
57.5°	1250.0	1250.7	1257.2	1264.3	1277.3	1288.8	1305.3	1318.6	1337.0	1351.9	1372.5
60°	1183.0	1179.4	1180.7	1183.2	1190.6	1198.0	1208.5	1217.2	1228.8	1237.2	1248.7
62.5°	1127.1	1121.5	1120.3	1119.6	1123.3	1126.0	1131.7	1135.9	1142.5	1146.2	1152.3
65°	1056.7	1050.1	1047.5	1044.4	1045.6	1044.7	1046.9	1047.0	1050.3	1051.1	1054.6
67.5°	992.7	987.3	983.9	979.8	978.0	975.0	973.8	971.0	970.5	968.2	967.6
70°	934.5	929.0	926.2	922.5	920.5	916.7	914.3	909.5	906.7	902.3	899.8
72.5°	867.0	863.9	863.1	860.6	859.9	857.7	856.7	853.4	851.5	847.6	845.5
75°	796.5	794.0	793.8	791.2	791.0	788.4	787.8	784.2	782.3	778.6	777.0
77.5°	712.6	708.8	707.8	704.8	705.5	704.2	705.2	702.5	701.4	697.6	696.4
80°	617.9	613.2	611.2	607.3	608.3	606.5	608.3	608.1	609.5	606.5	606.0
82.5°	505.9	500.7	499.7	496.9	498.8	499.0	503.0	500.8	501.7	498.9	500.0
85°	368.1	364.3	358.9	358.1	354.6	358.2	353.5	356.7	351.6	355.2	350.4
87.5°	228.2	220.2	216.0	210.3	208.1	202.6	200.4	196.3	197.6	195.7	196.8
90°	72.1	65.0	62.9	56.6	55.4	49.8	49.7	45.7	46.1	41.9	42.6
92.5°	4.4	4.4	4.3	4.7	4.4	4.4	4.3	4.7	4.4	4.7	4.4
95°	4.8	4.8	4.8	4.8	4.8	4.8	4.9	4.9	4.9	4.9	4.9
97.5°	5.2	5.2	5.2	5.2	5.2	5.2	5.2	5.4	5.4	5.4	5.4
100°	5.6	5.7	5.7	5.7	5.7	5.8	5.8	5.8	6.1	6.1	6.1
102.5°	6.3	6.3	6.3	6.4	6.4	6.4	6.5	6.6	6.6	6.8	6.9
105°	6.8	6.9	6.9	7.0	7.0	7.1	7.2	7.5	7.6	7.7	7.8
107.5°	7.5	7.6	7.7	7.8	7.8	8.0	8.2	8.3	8.4	8.6	9.0
110°	8.2	8.3	8.4	8.6	8.9	9.0	9.2	9.4	9.7	9.9	10.4



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	9.1	9.3	9.4	9.7	9.9	10.2	10.5	10.8	11.2	11.6	12.0
115°	10.2	10.5	10.6	11.1	11.2	11.6	12.0	12.6	13.0	13.5	14.1
117.5°	11.4	11.9	12.1	12.6	12.8	13.5	14.0	14.6	15.3	15.8	16.3
120°	13.3	13.6	14.1	14.6	15.0	15.6	16.3	17.0	17.7	18.5	19.1
122.5°	15.4	15.8	16.3	17.0	17.6	18.4	19.1	20.0	20.8	21.7	22.5
125°	18.0	18.6	19.3	20.0	20.8	21.7	22.5	23.5	24.4	25.4	26.3
127.5°	21.2	21.9	22.7	23.5	24.4	25.4	26.3	27.4	28.3	29.5	30.3
130°	25.2	25.9	26.7	27.7	28.6	29.7	30.7	31.9	32.8	33.9	34.8
132.5°	29.7	30.6	31.4	32.5	33.4	34.6	35.6	36.7	37.7	39.0	39.8
135°	34.9	35.9	36.7	37.7	38.8	39.9	40.9	42.1	43.0	44.1	45.1
137.5°	40.7	41.6	42.5	43.5	44.4	45.5	46.6	47.6	48.4	49.6	50.4
140°	46.8	47.7	48.4	49.6	50.4	51.4	52.2	53.2	54.0	55.1	55.8
142.5°	53.1	54.0	54.5	55.4	56.1	57.2	58.0	58.8	59.5	60.2	60.9
145°	59.5	60.2	60.8	61.5	62.2	62.9	63.5	64.3	64.6	65.3	65.9
147.5°	65.8	66.3	66.6	67.3	67.8	68.2	68.8	69.3	69.6	70.2	70.6
150°	71.6	72.0	72.2	72.8	73.0	73.4	73.6	74.1	74.3	74.7	74.9
152.5°	77.0	77.2	77.2	77.7	77.7	77.9	78.0	78.4	78.5	78.7	79.1
155°	81.9	82.0	82.0	82.1	82.1	82.1	82.1	82.5	82.6	82.7	82.9
157.5°	86.4	86.3	86.3	86.3	86.2	86.3	86.3	86.4	86.5	86.8	87.0
160°	90.5	90.4	90.2	90.2	90.2	90.2	90.2	90.5	90.6	91.0	91.2
162.5°	94.7	94.6	94.4	94.4	94.4	94.6	94.7	95.0	95.1	95.5	95.7
165°	99.2	99.2	99.0	99.2	99.2	99.3	99.4	99.7	99.9	100.3	100.6
167.5°	104.3	104.3	104.3	104.3	104.3	104.5	104.6	105.0	105.2	105.6	105.7
170°	109.1	109.2	109.1	109.2	109.2	109.3	109.5	109.6	109.8	110.0	110.2
172.5°	113.7	113.7	113.7	113.7	113.7	113.8	113.8	114.0	114.0	114.1	114.1
175°	117.6	117.6	117.6	117.6	117.6	117.5	117.5	117.3	117.3	117.3	117.3
177.5°	120.3	120.1	119.9	119.9	119.8	119.7	119.7	119.6	119.6	119.6	119.4
180°	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1
2.5°	29024.5	29024.1	29021.3	29022.6	29023.2	29025.2	29027.7	29030.3	29030.9	29032.9	29033.3
5°	29241.7	29169.9	29116.8	29058.4	29014.5	28974.9	28948.6	28927.6	28919.6	28921.5	28926.4
7.5°	29830.7	29682.4	29560.2	29421.1	29305.1	29182.4	29080.6	28983.8	28913.4	28860.8	28831.4
10°	30477.0	30296.5	30123.8	29922.5	29731.7	29528.0	29343.4	29157.7	29002.8	28868.2	28769.5
12.5°	30763.9	30636.3	30487.0	30297.0	30092.8	29857.8	29620.4	29365.9	29129.3	28909.6	28732.4
15°	30460.2	30460.4	30405.9	30314.9	30173.0	29985.2	29759.0	29493.8	29214.5	28929.7	28669.4
17.5°	29496.1	29678.0	29779.2	29843.2	29823.6	29754.4	29610.5	29406.8	29146.4	28843.0	28525.4
20°	27840.6	28269.7	28575.5	28850.5	29004.7	29107.2	29096.9	29014.0	28828.6	28570.7	28239.8
22.5°	25521.5	26241.6	26809.7	27339.6	27711.2	28013.5	28157.2	28218.2	28134.1	27954.4	27643.8
25°	22704.7	23683.7	24519.3	25330.1	25938.3	26461.1	26775.2	26996.5	27014.1	26920.2	26643.1
27.5°	19574.8	20730.4	21787.8	22865.4	23720.8	24472.3	24965.4	25326.3	25440.9	25425.7	25174.1
30°	16448.8	17662.0	18827.6	20084.3	21142.6	22102.7	22754.0	23242.0	23430.1	23466.1	23224.1
32.5°	13496.7	14693.0	15855.4	17169.1	18333.8	19434.1	20203.6	20783.3	21002.0	21053.6	20788.1
35°	10817.4	11921.1	13025.8	14299.0	15457.0	16596.4	17407.2	18014.1	18218.4	18252.9	17945.5
37.5°	8494.0	9434.3	10396.9	11539.3	12602.8	13672.9	14443.2	15013.7	15162.4	15153.2	14805.4
40°	6537.7	7268.8	8042.2	8982.7	9866.8	10771.4	11421.9	11893.5	11971.7	11913.8	11548.4
42.5°	4915.9	5444.0	6004.7	6706.7	7362.8	8039.8	8513.1	8863.1	8874.3	8782.8	8454.7
45°	3662.4	4177.5	4412.7	4837.2	5259.7	5709.9	5998.9	6215.2	6181.6	6101.2	5851.8
47.5°	2792.0	2990.0	3199.9	3463.1	3709.3	4220.1	4182.2	4529.5	4279.4	4449.9	4074.5
50°	2217.1	2327.7	2440.9	2580.5	2709.1	2842.7	2926.2	2988.5	2980.3	2953.5	2881.7
52.5°	1886.3	1920.4	1976.2	2055.6	2127.4	2199.6	2247.1	2285.8	2286.5	2275.7	2239.3
55°	1576.5	1619.9	1659.9	1711.8	1800.3	1813.8	1882.0	1868.2	1873.6	1854.7	1874.0
57.5°	1389.9	1415.2	1437.8	1468.7	1494.2	1524.0	1541.6	1558.6	1556.9	1553.3	1534.7
60°	1257.8	1271.7	1284.2	1302.3	1316.3	1333.1	1341.3	1349.9	1347.1	1340.8	1324.3
62.5°	1155.9	1164.6	1171.7	1183.4	1192.0	1202.5	1206.7	1210.3	1206.7	1200.7	1186.2
65°	1055.4	1061.0	1065.5	1074.3	1080.3	1089.3	1092.9	1096.3	1093.0	1088.3	1077.2
67.5°	964.7	965.3	964.8	968.4	970.2	975.6	977.2	979.7	975.8	971.8	962.5
70°	896.0	894.6	892.8	894.2	894.6	897.1	897.6	897.1	892.5	885.6	875.3
72.5°	842.2	841.4	840.1	841.3	841.3	843.7	842.9	841.7	836.0	829.4	819.2
75°	773.1	772.5	770.0	770.1	767.9	768.7	765.9	764.3	757.9	752.3	743.2
77.5°	692.2	690.9	687.2	685.8	681.6	679.9	674.6	672.0	665.5	661.0	653.3
80°	601.9	600.5	595.7	593.0	586.6	582.4	574.7	570.3	562.8	558.4	550.8
82.5°	497.6	498.1	493.3	489.9	480.6	473.5	463.1	457.5	449.3	445.0	437.3
85°	353.9	348.8	351.5	351.3	345.5	339.3	330.8	324.9	318.0	313.9	308.5
87.5°	194.1	195.3	193.9	192.7	188.6	185.5	178.9	175.4	170.4	167.9	163.7
90°	38.4	39.2	35.3	36.2	32.4	31.6	26.9	26.8	22.7	22.2	19.0
92.5°	4.4	4.4	4.7	4.4	4.7	4.7	4.7	4.7	4.7	4.4	4.7
95°	4.9	5.0	5.0	5.0	5.0	5.0	5.1	5.1	5.1	5.1	5.1
97.5°	5.5	5.5	5.5	5.6	5.6	5.6	5.7	5.7	5.7	5.7	5.7
100°	6.2	6.3	6.3	6.3	6.4	6.4	6.5	6.5	6.6	6.6	6.6
102.5°	6.9	7.0	7.1	7.2	7.5	7.5	7.6	7.6	7.7	7.7	7.7
105°	7.9	8.0	8.3	8.4	8.5	8.6	8.9	8.9	9.0	9.1	9.1
107.5°	9.2	9.3	9.6	9.8	9.9	10.2	10.4	10.5	10.6	10.7	10.8
110°	10.6	10.8	11.2	11.4	11.8	12.0	12.2	12.5	12.6	12.7	13.0



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	12.5	12.7	13.3	13.5	14.0	14.1	14.6	14.8	15.0	15.4	15.5
115°	14.6	15.0	15.5	16.0	16.4	16.9	17.2	17.5	17.8	18.2	18.5
117.5°	17.0	17.6	18.3	18.8	19.3	19.8	20.3	20.7	21.2	21.6	21.9
120°	20.0	20.7	21.3	21.9	22.6	23.2	23.8	24.3	24.7	25.3	25.8
122.5°	23.3	24.1	24.9	25.5	26.3	26.9	27.7	28.2	28.9	29.5	30.2
125°	27.2	27.9	28.9	29.6	30.3	31.1	31.9	32.5	33.3	33.9	34.8
127.5°	31.4	32.1	33.2	33.9	34.8	35.6	36.5	37.1	38.0	38.8	39.7
130°	36.0	36.7	37.7	38.5	39.5	40.4	41.2	42.1	43.0	43.9	44.9
132.5°	40.8	41.8	42.7	43.5	44.6	45.3	46.3	47.2	48.2	49.1	50.2
135°	46.1	46.8	47.9	48.6	49.6	50.4	51.4	52.4	53.4	54.4	55.5
137.5°	51.2	52.1	53.0	53.8	54.7	55.5	56.6	57.4	58.6	59.5	60.8
140°	56.6	57.3	58.1	58.8	59.7	60.4	61.5	62.4	63.5	64.4	65.7
142.5°	61.6	62.2	62.9	63.6	64.4	65.1	66.0	67.1	68.0	69.1	70.2
145°	66.5	67.1	67.7	68.2	68.8	69.6	70.6	71.5	72.4	73.4	74.5
147.5°	71.0	71.5	72.1	72.7	73.3	73.8	74.8	75.6	76.5	77.5	78.5
150°	75.5	75.8	76.2	76.6	77.3	77.9	78.7	79.4	80.6	81.4	82.2
152.5°	79.3	79.7	80.1	80.7	81.2	81.9	82.6	83.4	84.2	85.0	85.9
155°	83.4	83.6	84.1	84.7	85.2	85.7	86.5	87.1	87.9	88.7	89.5
157.5°	87.5	87.7	88.2	88.7	89.3	89.8	90.6	91.1	91.9	92.5	93.2
160°	91.6	92.0	92.5	93.0	93.6	94.1	94.8	95.4	96.0	96.6	97.2
162.5°	96.2	96.6	97.1	97.5	98.2	98.6	99.3	99.8	100.4	101.0	101.6
165°	101.1	101.4	102.0	102.4	102.9	103.2	103.9	104.3	104.9	105.3	105.9
167.5°	106.2	106.4	106.8	107.1	107.6	108.0	108.5	108.8	109.3	109.8	110.3
170°	110.4	110.6	110.9	111.2	111.6	111.8	112.1	112.4	113.0	113.2	113.7
172.5°	114.3	114.3	114.7	114.7	114.9	115.1	115.4	115.6	115.9	116.2	116.3
175°	117.5	117.5	117.6	117.6	117.7	117.7	118.0	118.2	118.3	118.4	118.5
177.5°	119.4	119.4	119.4	119.4	119.6	119.6	119.7	119.7	119.8	119.8	119.9
180°	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1
2.5°	29032.4	29032.0	29031.0	29029.7	29028.4	29029.3	29030.5	29033.9	29039.7	29048.1	29059.1
5°	28930.4	28936.3	28939.7	28940.2	28937.1	28935.3	28938.1	28946.1	28962.2	28989.2	29025.6
7.5°	28823.6	28830.9	28842.1	28850.5	28852.1	28850.2	28850.5	28863.1	28892.8	28945.3	29019.1
10°	28709.5	28687.7	28699.2	28720.1	28736.7	28739.8	28741.9	28756.6	28800.1	28879.5	28997.9
12.5°	28604.1	28535.4	28522.1	28541.1	28566.3	28574.4	28572.1	28578.5	28629.4	28734.5	28899.5
15°	28465.5	28336.3	28292.1	28296.9	28328.1	28339.4	28331.1	28318.7	28368.2	28496.6	28710.2
17.5°	28241.1	28032.8	27951.6	27948.0	27984.6	27994.2	27974.2	27935.3	27984.1	28144.3	28409.5
20°	27900.2	27592.5	27439.7	27415.4	27455.0	27443.4	27403.4	27344.7	27408.8	27603.6	27919.0
22.5°	27287.0	26897.3	26636.2	26551.9	26599.3	26567.7	26509.3	26434.3	26519.4	26740.8	27092.1
25°	26285.2	25834.9	25477.4	25276.8	25314.6	25257.9	25194.3	25103.4	25205.0	25459.0	25845.7
27.5°	24812.7	24292.5	23849.5	23517.4	23529.7	23455.4	23382.1	23264.5	23391.3	23692.0	24128.1
30°	22854.6	22252.7	21713.2	21261.9	21221.5	21149.5	21074.5	20920.1	21078.9	21438.7	21948.4
32.5°	20395.5	19727.3	19103.9	18533.3	18425.7	18355.4	18288.6	18110.9	18318.7	18738.3	19323.8
35°	17519.8	16807.9	16132.1	15480.4	15302.1	15231.8	15173.4	15003.2	15262.5	15719.1	16351.6
37.5°	14363.3	13636.1	12965.1	12296.8	12044.9	11949.5	11907.1	11795.6	12094.7	12546.4	13181.4
40°	11122.8	10446.6	9845.0	9254.9	8967.6	8821.7	8799.4	8779.2	9068.4	9460.3	10036.6
42.5°	8091.4	7545.9	7082.0	6630.9	6370.6	6171.4	6171.3	6231.7	6492.1	6785.7	7230.1
45°	5597.1	5231.0	4935.4	4634.0	4714.5	4317.5	4550.8	4431.0	4559.7	4749.0	5038.0
47.5°	3847.4	3647.6	3485.2	3316.8	3194.1	3076.8	3087.1	3162.7	3283.9	3396.2	3546.6
50°	2804.1	2702.3	2619.7	2532.2	2471.1	2419.4	2422.4	2455.1	2518.8	2578.0	2656.7
52.5°	2197.2	2141.1	2096.2	2047.8	2015.8	1990.0	1991.4	2007.4	2041.7	2075.6	2120.7
55°	1811.0	1804.3	1745.8	1702.5	1686.0	1668.7	1671.8	1678.0	1701.5	1721.2	1751.2
57.5°	1517.7	1491.4	1473.9	1451.1	1440.6	1428.5	1431.2	1433.5	1449.2	1462.5	1483.9
60°	1310.5	1291.9	1279.5	1263.9	1257.1	1249.4	1251.1	1252.5	1262.6	1271.2	1286.7
62.5°	1172.9	1156.2	1145.4	1133.4	1128.5	1123.4	1124.6	1125.0	1131.3	1137.6	1149.3
65°	1067.3	1054.1	1045.1	1034.8	1029.7	1024.3	1024.9	1024.9	1030.1	1034.8	1043.5
67.5°	955.6	945.7	939.9	931.7	928.2	922.7	922.6	920.9	924.3	926.1	932.1
70°	866.0	856.0	848.6	840.7	836.3	831.5	831.6	831.7	835.7	839.9	847.5
72.5°	810.6	801.1	794.4	787.5	783.5	779.3	778.6	778.1	781.0	783.4	788.4
75°	737.4	729.7	725.8	719.3	716.1	711.4	710.7	708.5	709.9	710.3	714.1
77.5°	648.4	641.2	638.0	631.4	628.7	623.5	623.0	620.7	621.7	620.9	623.8
80°	547.0	540.4	538.7	533.3	532.1	527.2	526.4	523.4	524.4	522.0	523.2
82.5°	433.9	427.8	426.6	421.6	421.6	417.1	416.9	412.5	412.5	408.7	402.7
85°	305.6	301.2	299.4	295.3	294.0	290.5	288.7	284.5	283.0	280.3	279.4
87.5°	161.3	158.5	156.0	154.1	150.5	144.2	143.6	139.2	139.5	136.4	136.6
90°	19.0	16.1	16.2	13.6	13.5	11.9	12.0	11.2	11.1	10.4	10.2
92.5°	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7
95°	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.2	5.2
97.5°	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.8	5.8	5.8	5.8
100°	6.6	6.6	6.6	6.6	6.6	6.6	6.6	6.8	6.8	6.8	6.8
102.5°	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.9	7.9
105°	9.1	9.2	9.2	9.2	9.2	9.2	9.2	9.3	9.3	9.3	9.4
107.5°	10.8	11.1	11.1	11.1	11.1	11.1	11.1	11.2	11.2	11.2	11.2
110°	13.0	13.2	13.3	13.4	13.4	13.5	13.5	13.6	13.6	13.6	13.6



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	15.6	15.8	16.0	16.2	16.2	16.4	16.4	16.6	16.6	16.8	16.6
115°	18.8	19.0	19.3	19.6	19.7	19.9	19.9	20.2	20.2	20.2	20.2
117.5°	22.2	22.7	22.9	23.3	23.5	23.9	24.0	24.1	24.1	24.3	24.1
120°	26.1	26.8	27.2	27.5	27.9	28.3	28.5	28.8	28.8	28.8	28.6
122.5°	30.6	31.3	31.8	32.3	32.7	33.2	33.3	33.5	33.5	33.7	33.4
125°	35.3	36.2	36.7	37.4	37.7	38.4	38.5	39.0	39.0	39.0	38.8
127.5°	40.5	41.2	41.9	42.7	43.2	43.7	44.0	44.4	44.4	44.4	44.1
130°	45.7	46.7	47.4	48.2	48.8	49.4	49.6	50.0	50.0	50.2	49.8
132.5°	51.1	52.2	53.0	53.9	54.4	55.2	55.4	55.8	55.8	55.9	55.6
135°	56.6	57.5	58.5	59.5	60.1	60.8	61.1	61.5	61.5	61.5	61.2
137.5°	61.7	62.9	63.8	64.6	65.4	66.0	66.5	66.8	66.8	67.1	66.7
140°	66.6	67.8	68.8	69.6	70.5	71.3	71.6	72.0	72.0	72.0	71.7
142.5°	71.3	72.3	73.3	74.3	74.9	75.7	76.2	76.4	76.4	76.4	76.2
145°	75.6	76.5	77.5	78.5	79.2	79.8	80.1	80.6	80.6	80.6	80.5
147.5°	79.4	80.6	81.3	82.1	82.8	83.5	83.8	84.1	84.2	84.2	84.1
150°	83.3	84.1	84.9	85.6	86.3	86.8	87.0	87.5	87.6	87.7	87.6
152.5°	86.6	87.5	88.2	88.9	89.5	89.9	90.2	90.6	90.9	91.1	91.1
155°	90.1	90.9	91.5	92.2	92.6	93.2	93.6	94.0	94.3	94.6	94.8
157.5°	93.9	94.6	95.1	95.7	96.2	96.9	97.2	97.8	98.2	98.5	98.8
160°	97.8	98.5	99.0	99.7	100.2	100.7	101.2	101.7	102.1	102.5	102.9
162.5°	102.1	102.8	103.1	103.8	104.3	104.8	105.3	105.8	106.2	106.7	107.0
165°	106.4	107.0	107.4	108.0	108.5	109.0	109.3	109.9	110.3	110.6	111.0
167.5°	110.6	111.2	111.6	112.0	112.4	113.0	113.3	113.8	114.1	114.5	114.7
170°	114.0	114.5	114.8	115.2	115.6	116.1	116.2	116.6	116.9	117.3	117.6
172.5°	116.6	117.0	117.3	117.7	117.9	118.2	118.4	118.9	119.1	119.3	119.4
175°	118.7	119.0	119.1	119.3	119.4	119.6	119.8	119.9	120.3	120.4	120.6
177.5°	120.1	120.3	120.4	120.4	120.5	120.5	120.6	120.6	120.6	120.8	120.8
180°	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1
2.5°	29074.7	29089.2	29111.5	29131.6	29162.0	29186.0	29221.9	29249.2	29289.9	29316.2	29360.3
5°	29077.2	29134.2	29208.9	29282.0	29369.8	29449.4	29548.4	29632.7	29732.3	29813.4	29915.2
7.5°	29118.3	29228.0	29359.5	29492.0	29641.9	29782.0	29939.9	30082.9	30239.1	30371.3	30515.7
10°	29148.7	29317.9	29511.7	29706.6	29911.8	30102.5	30295.0	30461.4	30616.8	30744.8	30857.8
12.5°	29107.6	29340.6	29589.3	29829.4	30057.6	30254.9	30420.6	30548.5	30636.7	30696.7	30710.7
15°	28967.8	29248.3	29518.6	29757.7	29947.1	30093.1	30168.7	30204.1	30166.1	30103.0	29964.5
17.5°	28706.7	29002.5	29244.1	29432.8	29532.8	29572.5	29509.8	29400.9	29188.0	28951.7	28610.5
20°	28227.8	28503.5	28678.7	28781.7	28754.9	28655.9	28419.5	28132.1	27707.1	27254.1	26656.4
22.5°	27388.1	27629.1	27722.4	27730.0	27566.8	27318.8	26892.4	26399.5	25729.1	25032.0	24174.7
25°	26127.4	26338.6	26353.3	26270.4	25971.5	25569.8	24943.6	24246.3	23335.2	22406.4	21332.0
27.5°	24417.8	24620.3	24570.7	24416.1	24001.1	23463.5	22661.9	21761.1	20637.9	19540.8	18352.4
30°	22268.8	22485.2	22427.1	22228.7	21735.1	21099.7	20156.5	19109.9	17862.9	16691.0	15486.8
32.5°	19697.0	19970.6	19930.4	19741.9	19226.8	18546.9	17523.4	16413.4	15137.5	13982.7	12811.4
35°	16773.7	17106.0	17123.2	17000.0	16521.8	15849.8	14839.1	13764.7	12542.5	11453.0	10370.9
37.5°	13624.3	14009.5	14088.7	14055.4	13659.1	13065.9	12145.0	11181.2	10098.5	9143.7	8218.1
40°	10457.5	10847.4	10982.6	11022.8	10730.4	10270.9	9515.1	8737.2	7854.6	7080.9	6345.9
42.5°	7569.5	7915.1	8045.9	8128.1	7945.5	7639.1	7087.8	6522.9	5876.3	5318.3	4783.2
45°	5257.1	5501.7	5601.1	5683.9	5584.5	5411.6	5063.5	4710.1	4283.3	3918.6	3573.4
47.5°	3675.6	3810.4	3876.0	3916.2	3877.7	3787.5	3598.1	3393.4	3152.4	2939.3	2734.4
50°	2724.4	2796.2	2830.5	2853.7	2825.7	2775.6	2673.0	2561.6	2429.3	2308.5	2190.5
52.5°	2159.0	2200.1	2220.6	2233.0	2217.0	2186.3	2126.6	2060.6	1981.2	1906.6	1867.4
55°	1818.8	1816.7	1863.9	1841.1	1863.9	1813.0	1802.3	1729.6	1663.8	1617.4	1567.2
57.5°	1500.0	1521.3	1530.4	1540.5	1534.0	1524.7	1499.3	1473.3	1438.5	1409.5	1378.5
60°	1298.4	1316.0	1325.9	1335.9	1335.3	1331.8	1317.2	1301.7	1279.9	1262.6	1243.8
62.5°	1159.6	1174.8	1184.6	1194.2	1195.1	1193.6	1182.6	1171.7	1156.9	1146.1	1133.1
65°	1050.3	1061.0	1067.7	1075.3	1074.9	1072.9	1062.8	1053.9	1041.6	1034.1	1024.6
67.5°	936.0	944.1	949.3	956.5	957.9	958.3	952.8	948.6	942.7	940.5	937.3
70°	854.7	864.5	872.8	882.0	887.0	889.3	887.0	884.8	881.3	879.9	877.3
72.5°	793.1	801.4	807.9	816.2	820.9	824.2	822.4	821.2	818.2	817.7	816.1
75°	716.7	722.5	726.1	732.4	734.8	738.0	736.6	737.4	736.3	738.8	738.6
77.5°	624.9	629.1	630.8	635.3	635.7	639.5	640.4	644.8	647.9	654.9	658.5
80°	521.5	524.1	524.1	528.8	530.8	537.2	540.2	547.4	550.8	557.0	557.5
82.5°	405.0	401.9	405.0	403.1	409.1	416.2	417.1	423.3	424.7	428.5	425.5
85°	276.9	276.7	274.2	274.6	272.8	273.7	272.6	273.8	272.7	272.8	270.0
87.5°	132.6	133.9	131.0	131.9	129.1	130.4	128.0	129.8	126.9	127.4	123.1
90°	9.8	9.6	9.2	9.1	9.3	9.0	8.9	8.6	8.9	8.5	8.5
92.5°	4.7	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.9	4.8	4.8
95°	5.2	5.2	5.2	5.4	5.4	5.4	5.4	5.4	5.4	5.4	5.4
97.5°	6.1	6.1	6.1	6.1	6.2	6.2	6.2	6.2	6.2	6.2	6.1
100°	6.9	6.9	6.9	7.0	7.0	7.0	7.0	7.0	7.0	6.9	6.9
102.5°	8.0	8.0	8.0	8.2	8.2	8.2	8.2	8.2	8.0	8.0	7.9
105°	9.4	9.4	9.6	9.6	9.6	9.6	9.6	9.6	9.4	9.3	9.3
107.5°	11.3	11.3	11.4	11.4	11.4	11.4	11.3	11.2	11.2	11.1	10.8
110°	13.9	13.6	13.9	13.9	13.9	13.6	13.6	13.4	13.3	13.0	12.8



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	16.8	16.6	16.6	16.4	16.4	16.2	16.2	16.0	15.8	15.5	15.3
115°	20.2	19.9	19.9	19.7	19.7	19.4	19.1	18.9	18.6	18.3	18.0
117.5°	24.0	23.9	23.8	23.3	23.2	22.9	22.6	22.2	21.9	21.6	21.2
120°	28.5	28.2	27.9	27.5	27.4	26.8	26.6	26.0	25.7	25.2	24.6
122.5°	33.3	33.0	32.7	32.3	31.9	31.3	30.9	30.3	29.9	29.2	28.8
125°	38.5	38.1	37.7	37.3	36.7	36.2	35.6	34.9	34.3	33.7	33.1
127.5°	44.0	43.5	43.2	42.5	42.0	41.2	40.6	39.8	39.3	38.4	37.7
130°	49.6	49.1	48.8	48.0	47.5	46.6	46.0	45.1	44.4	43.7	42.9
132.5°	55.4	54.8	54.4	53.6	53.0	52.2	51.6	50.7	49.8	49.0	48.3
135°	61.0	60.4	60.0	59.3	58.6	57.6	57.0	56.1	55.4	54.6	53.9
137.5°	66.5	65.9	65.3	64.6	64.0	63.1	62.5	61.6	61.0	60.1	59.5
140°	71.5	70.9	70.5	69.9	69.2	68.5	67.8	67.1	66.4	65.7	65.0
142.5°	75.9	75.5	75.0	74.4	73.8	73.1	72.7	72.0	71.4	70.7	70.2
145°	80.1	79.7	79.3	78.7	78.4	77.7	77.3	76.6	76.3	75.7	75.2
147.5°	84.0	83.6	83.4	82.9	82.7	82.1	82.0	81.4	81.2	80.7	80.5
150°	87.6	87.5	87.3	87.0	86.8	86.5	86.4	86.1	85.9	85.5	85.4
152.5°	91.1	91.1	91.1	91.0	91.0	90.9	90.8	90.6	90.5	90.2	90.1
155°	95.0	95.1	95.3	95.3	95.3	95.3	95.3	95.1	95.1	95.0	95.0
157.5°	99.0	99.2	99.4	99.6	99.7	99.7	99.7	99.7	99.7	99.6	99.6
160°	103.1	103.4	103.6	103.8	104.0	104.0	104.2	104.0	104.2	104.0	103.9
162.5°	107.3	107.6	107.8	108.0	108.2	108.2	108.4	108.4	108.4	108.2	108.2
165°	111.4	111.6	111.8	111.9	112.1	112.1	112.3	112.3	112.3	112.1	112.1
167.5°	115.1	115.2	115.5	115.6	115.9	115.9	116.2	116.1	116.1	116.1	116.1
170°	117.7	118.0	118.2	118.3	118.5	118.5	118.7	118.7	118.9	118.7	118.7
172.5°	119.7	119.8	120.1	120.3	120.4	120.4	120.5	120.5	120.6	120.6	120.6
175°	120.6	120.8	121.0	121.1	121.2	121.3	121.3	121.5	121.5	121.5	121.5
177.5°	121.0	121.1	121.1	121.2	121.3	121.3	121.5	121.5	121.7	121.7	121.7
180°	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1
2.5°	29387.6	29206.1	29182.2	29195.0	29225.2	29236.5	29269.2	29278.1	29311.1	29319.2	29350.8
5°	29994.0	29754.2	29766.1	29823.8	29911.1	29963.2	30049.0	30093.8	30175.8	30213.1	30287.1
7.5°	30633.5	30445.1	30503.8	30601.1	30720.5	30803.1	30906.2	30973.4	31062.2	31117.4	31188.6
10°	30947.4	30895.7	30960.5	31037.0	31105.1	31158.4	31202.1	31237.1	31260.0	31281.5	31290.9
12.5°	30708.5	30788.4	30799.4	30792.0	30746.8	30712.3	30635.0	30582.4	30489.0	30432.1	30321.0
15°	29822.8	29998.5	29901.2	29753.9	29538.5	29358.8	29105.1	28916.2	28652.1	28472.9	28207.7
17.5°	28268.5	28490.2	28236.7	27896.0	27462.5	27091.8	26630.0	26263.5	25804.4	25470.4	25042.0
20°	26080.3	26287.4	25835.5	25270.6	24600.1	24035.9	23370.4	22839.5	22221.1	21761.1	21206.0
22.5°	23355.8	23503.4	22866.6	22105.1	21250.9	20546.0	19750.3	19113.8	18408.1	17882.2	17290.3
25°	20341.7	20381.6	19617.6	18740.4	17788.3	16996.0	16146.6	15477.4	14757.7	14224.7	13643.8
27.5°	17299.5	17241.1	16415.4	15485.3	14483.8	13660.3	12831.9	12204.8	11574.3	11094.3	10593.8
30°	14428.1	14286.7	13429.4	12473.3	11501.2	10763.1	10075.3	9571.7	9070.2	8689.4	8287.6
32.5°	11794.9	11595.4	10760.9	9865.2	9046.1	8476.5	7966.5	7585.4	7180.4	6858.8	6521.6
35°	9462.6	9250.1	8510.8	7751.5	7131.4	6711.6	6310.8	5998.1	5654.3	5382.9	5090.1
37.5°	7461.1	7286.8	6667.6	6070.1	5601.1	5275.7	4947.3	4691.8	4407.6	4288.3	3975.4
40°	5759.9	5638.1	5154.0	4713.4	4361.3	4208.4	3875.1	3636.4	3424.0	3249.0	3079.3
42.5°	4492.8	4449.7	3978.5	3635.0	3387.0	3194.5	3008.6	2857.8	2711.0	2590.3	2476.3
45°	3297.1	3262.9	3053.8	2855.5	2686.5	2551.9	2426.3	2322.6	2226.6	2147.0	2074.7
47.5°	2567.4	2556.5	2436.0	2313.0	2206.6	2120.1	2038.7	1969.8	1906.1	1853.0	1835.7
50°	2088.2	2086.8	2016.1	1940.2	1864.4	1814.4	1762.4	1721.7	1680.7	1648.9	1615.3
52.5°	1774.2	1766.6	1718.9	1672.0	1627.0	1594.2	1560.9	1534.9	1507.8	1488.1	1467.3
55°	1527.5	1535.5	1507.9	1480.0	1451.8	1431.4	1408.1	1390.9	1372.4	1359.9	1347.3
57.5°	1356.1	1366.8	1352.2	1336.4	1319.3	1305.9	1289.8	1277.9	1265.5	1257.5	1250.2
60°	1231.3	1243.0	1237.2	1229.1	1218.6	1210.6	1200.4	1193.7	1185.8	1181.4	1177.3
62.5°	1125.5	1140.2	1138.1	1134.3	1127.5	1123.0	1117.5	1114.5	1109.3	1107.3	1105.3
65°	1020.0	1036.4	1036.1	1034.2	1030.5	1029.2	1025.7	1025.0	1022.3	1023.4	1023.2
67.5°	937.0	951.2	954.3	956.6	956.5	957.3	957.0	958.4	958.4	960.5	961.8
70°	877.0	887.0	889.3	891.7	892.4	894.3	894.3	895.5	895.2	896.9	897.1
72.5°	816.4	829.5	831.9	833.9	833.9	835.7	834.7	834.4	831.8	831.2	829.5
75°	741.1	757.9	761.5	763.9	764.3	765.9	763.6	762.2	757.9	756.1	753.1
77.5°	662.4	679.8	682.4	683.2	681.8	682.2	677.4	674.1	668.7	666.4	663.5
80°	560.0	585.5	587.6	586.0	582.0	581.3	576.7	573.6	567.1	564.8	562.3
82.5°	426.1	456.1	460.3	462.2	458.9	459.6	455.2	453.6	447.5	446.4	442.4
85°	269.0	299.0	304.0	303.2	300.0	299.3	296.7	297.5	297.0	298.6	299.5
87.5°	123.6	152.7	159.7	157.4	157.1	155.0	150.3	152.1	154.9	156.7	156.9
90°	8.4	17.0	16.8	17.7	15.8	16.4	14.8	15.8	14.7	15.6	14.6
92.5°	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.7	4.8	4.7	4.8
95°	5.4	5.2	5.2	5.2	5.1	5.1	5.1	5.1	5.1	5.1	5.1
97.5°	6.1	5.8	5.7	5.7	5.7	5.6	5.6	5.6	5.6	5.5	5.5
100°	6.9	6.5	6.4	6.4	6.3	6.3	6.3	6.2	6.2	6.2	6.1
102.5°	7.8	7.5	7.2	7.1	7.0	6.9	6.9	6.8	6.8	6.6	6.6
105°	9.1	8.5	8.3	8.0	7.9	7.8	7.7	7.6	7.5	7.2	7.2
107.5°	10.7	9.8	9.4	9.2	9.0	8.9	8.5	8.4	8.2	8.0	7.9
110°	12.6	11.4	11.1	10.6	10.4	9.9	9.7	9.4	9.2	9.1	8.9



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	14.9	13.4	12.7	12.2	11.9	11.4	11.1	10.7	10.5	10.0	9.9
115°	17.5	15.6	14.9	14.2	13.9	13.3	12.7	12.5	11.9	11.4	11.2
117.5°	20.7	18.5	17.5	16.8	16.2	15.5	14.9	14.2	13.9	13.3	12.8
120°	24.1	21.6	20.5	19.7	19.0	18.2	17.5	16.8	16.1	15.5	14.9
122.5°	28.1	25.3	24.0	23.1	22.2	21.3	20.5	19.7	18.9	18.2	17.5
125°	32.4	29.2	27.8	26.9	26.0	25.0	24.1	23.1	22.4	21.5	20.7
127.5°	37.0	33.7	32.3	31.3	30.3	29.2	28.3	27.2	26.3	25.3	24.5
130°	42.1	38.5	37.0	36.0	35.1	33.9	33.1	31.9	30.9	29.9	28.9
132.5°	47.5	43.7	42.2	41.2	40.4	39.2	38.3	37.1	36.2	34.9	34.1
135°	53.0	49.1	47.6	46.6	45.8	44.7	43.7	42.6	41.8	40.6	39.8
137.5°	58.6	54.5	53.1	52.2	51.4	50.4	49.6	48.6	47.7	46.6	45.8
140°	64.3	60.0	58.6	57.9	57.2	56.2	55.5	54.6	53.9	53.0	52.2
142.5°	69.5	65.2	63.8	63.1	62.6	61.8	61.4	60.7	60.0	59.0	58.5
145°	74.8	70.2	68.8	68.2	67.9	67.3	66.8	66.3	65.8	65.1	64.5
147.5°	79.9	75.0	73.6	73.3	73.0	72.4	72.2	71.7	71.5	70.9	70.6
150°	85.0	79.4	77.8	77.7	77.3	77.1	76.9	76.5	76.4	76.2	75.9
152.5°	89.8	83.3	81.4	81.2	81.2	80.8	80.7	80.7	80.7	80.6	80.5
155°	94.7	87.5	85.4	85.1	85.0	84.9	84.8	84.8	84.8	84.8	84.9
157.5°	99.3	91.5	89.5	89.1	89.0	88.9	88.7	88.7	88.7	88.7	89.0
160°	103.8	95.8	93.7	93.3	93.2	92.9	92.7	92.6	92.6	92.6	92.7
162.5°	108.0	100.3	98.3	97.8	97.5	97.2	97.1	96.9	96.9	96.8	96.9
165°	111.9	105.0	102.9	102.6	102.4	102.0	101.8	101.6	101.4	101.4	101.4
167.5°	115.9	109.6	108.0	107.6	107.3	107.0	107.0	106.6	106.6	106.3	106.3
170°	118.5	113.7	112.3	112.0	112.0	111.8	111.7	111.6	111.4	111.2	111.2
172.5°	120.5	116.9	115.9	115.7	115.7	115.6	115.6	115.5	115.5	115.5	115.5
175°	121.5	119.3	118.9	118.7	118.7	118.7	118.7	118.7	118.7	118.7	118.9
177.5°	121.8	121.2	121.0	121.0	121.0	121.0	121.0	121.0	121.0	121.1	121.1
180°	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1
2.5°	29356.7	29391.0	29388.4	29420.3	29418.7	29448.8	29442.8	29468.9	29462.9	29485.2	29472.0
5°	30319.8	30384.8	30406.3	30465.1	30477.2	30529.8	30530.9	30572.7	30567.6	30600.3	30582.9
7.5°	31230.6	31291.4	31320.3	31365.9	31388.7	31426.5	31441.3	31472.4	31479.8	31498.1	31497.6
10°	31307.5	31307.3	31321.6	31315.2	31327.9	31320.5	31336.1	31330.5	31353.5	31347.5	31364.9
12.5°	30273.1	30170.5	30133.0	30040.7	30020.6	29941.4	29947.1	29896.3	29920.8	29889.6	29942.7
15°	28049.9	27811.8	27694.2	27487.1	27422.1	27258.4	27245.1	27136.5	27165.8	27108.9	27192.0
17.5°	24764.7	24389.8	24184.0	23881.7	23761.6	23530.1	23483.8	23343.8	23365.5	23295.0	23395.4
20°	20847.9	20394.8	20135.3	19785.6	19629.6	19353.7	19280.5	19123.9	19143.6	19073.5	19187.0
22.5°	16886.3	16412.1	16119.1	15752.6	15553.4	15293.9	15216.1	15058.7	15067.7	15001.9	15111.1
25°	13245.8	12791.1	12506.7	12173.8	12001.0	11763.1	11681.2	11540.1	11548.0	11493.7	11591.8
27.5°	10246.7	9873.6	9635.6	9356.5	9201.6	9006.0	8926.2	8807.5	8807.1	8767.3	8849.3
30°	8007.2	7695.8	7482.2	7239.2	7093.7	6917.1	6840.0	6733.8	6729.2	6700.9	6766.0
32.5°	6269.4	5992.5	5797.7	5583.8	5453.1	5301.7	5228.7	5143.4	5135.6	5110.0	5163.4
35°	4873.7	4640.5	4473.0	4292.8	4306.1	4082.6	4119.8	3946.3	3899.1	3888.9	3928.7
37.5°	3766.8	3586.2	3450.1	3315.2	3223.9	3129.5	3078.6	3032.9	3027.7	3023.3	3051.1
40°	2948.4	2821.9	2723.0	2630.5	2567.6	2510.0	2478.2	2453.1	2447.2	2443.8	2460.6
42.5°	2386.3	2300.9	2237.1	2180.8	2142.5	2111.2	2093.7	2079.8	2075.1	2075.3	2085.2
45°	2016.1	1964.4	1923.3	1888.1	1863.8	1874.4	1842.9	1859.5	1837.6	1860.2	1845.3
47.5°	1775.4	1731.4	1705.9	1681.1	1666.3	1654.4	1654.9	1655.1	1659.8	1660.5	1665.3
50°	1589.8	1564.3	1546.6	1530.7	1523.0	1516.8	1519.0	1520.6	1525.1	1525.4	1529.0
52.5°	1452.4	1435.6	1424.9	1415.1	1411.6	1408.1	1409.6	1408.9	1411.0	1409.9	1412.8
55°	1340.5	1332.6	1329.3	1325.6	1326.1	1325.2	1325.8	1322.3	1320.1	1317.4	1319.8
57.5°	1248.7	1247.6	1249.9	1251.4	1255.7	1257.2	1258.1	1254.0	1250.1	1246.6	1248.6
60°	1178.0	1179.8	1185.3	1189.9	1195.9	1198.7	1200.5	1198.1	1195.2	1192.3	1194.1
62.5°	1108.3	1110.9	1117.7	1122.7	1130.0	1133.9	1138.1	1138.3	1139.4	1138.3	1139.5
65°	1027.3	1030.7	1036.7	1040.9	1047.7	1051.1	1055.4	1056.1	1058.5	1058.0	1060.0
67.5°	965.7	968.8	973.9	977.8	983.9	987.4	991.1	991.3	992.3	992.0	993.9
70°	900.2	901.7	906.2	909.5	915.5	919.1	923.4	924.7	927.4	927.9	930.1
72.5°	830.2	829.5	832.3	833.8	838.3	841.1	846.6	849.6	854.2	855.3	857.0
75°	754.0	753.3	756.6	757.9	761.7	764.5	770.7	774.7	781.7	784.6	783.8
77.5°	665.7	667.3	673.3	676.7	681.8	685.4	693.4	699.8	712.6	718.3	712.6
80°	567.1	568.7	575.0	578.1	584.9	589.2	598.2	605.7	617.2	619.6	616.4
82.5°	445.9	446.2	451.9	454.3	463.1	469.5	480.8	486.8	493.9	492.8	492.0
85°	304.0	308.1	315.1	322.1	332.9	343.3	354.0	362.9	356.6	366.4	355.4
87.5°	162.5	162.1	171.5	170.0	185.2	193.9	203.2	207.6	212.5	211.6	211.7
90°	16.0	14.9	16.2	14.9	17.0	15.5	18.3	17.0	20.3	18.4	21.9
92.5°	4.7	4.8	4.7	4.8	4.7	4.8	4.7	4.7	4.7	4.7	4.7
95°	5.1	5.1	5.1	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
97.5°	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.4	5.4	5.4
100°	6.1	6.1	6.1	6.1	5.8	5.8	5.8	5.8	5.8	5.8	5.8
102.5°	6.5	6.5	6.5	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4
105°	7.1	7.1	7.0	7.0	6.9	6.9	6.9	6.9	6.9	6.9	6.9
107.5°	7.9	7.8	7.7	7.7	7.6	7.6	7.6	7.6	7.6	7.6	7.6
110°	8.6	8.5	8.4	8.4	8.3	8.2	8.2	8.2	8.2	8.2	8.2



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	9.7	9.4	9.3	9.2	9.1	9.1	9.0	9.0	9.0	9.0	9.0
115°	10.8	10.7	10.5	10.4	10.2	10.0	9.9	9.9	9.9	9.9	9.9
117.5°	12.5	12.1	11.9	11.6	11.4	11.3	11.2	11.2	11.1	11.2	11.2
120°	14.4	14.1	13.6	13.4	13.2	13.0	12.7	12.7	12.7	12.7	12.7
122.5°	16.9	16.3	15.8	15.5	15.3	15.0	14.8	14.8	14.8	14.8	14.8
125°	19.9	19.3	18.8	18.4	17.8	17.7	17.5	17.5	17.4	17.5	17.5
127.5°	23.6	22.9	22.2	21.8	21.3	21.1	20.8	20.7	20.7	20.8	20.8
130°	27.9	27.4	26.6	26.0	25.4	25.2	24.9	24.7	24.6	24.7	24.9
132.5°	33.1	32.3	31.6	30.9	30.3	30.0	29.6	29.6	29.5	29.6	29.7
135°	38.7	37.9	37.1	36.5	35.9	35.6	35.2	35.2	35.1	35.2	35.5
137.5°	44.8	44.1	43.3	42.7	42.1	41.9	41.5	41.3	41.3	41.5	41.8
140°	51.2	50.5	49.7	49.3	48.8	48.4	48.1	48.1	48.0	48.2	48.3
142.5°	57.6	57.2	56.5	56.0	55.5	55.3	55.1	55.1	54.8	55.2	55.4
145°	63.9	63.5	62.9	62.5	62.2	62.1	61.6	61.7	61.7	62.1	62.2
147.5°	70.1	69.9	69.3	69.1	68.7	68.7	68.5	68.6	68.6	68.8	68.8
150°	75.6	75.5	75.1	75.0	74.8	74.8	74.7	74.8	74.8	75.0	75.1
152.5°	80.3	80.3	80.1	80.1	80.0	80.1	80.1	80.3	80.5	80.7	80.7
155°	84.9	84.9	84.9	85.0	85.0	85.2	85.2	85.6	85.7	86.1	86.2
157.5°	89.0	89.2	89.2	89.5	89.6	89.8	89.9	90.4	90.5	90.9	91.1
160°	92.9	93.2	93.3	93.6	93.9	94.0	94.3	94.7	95.0	95.4	95.5
162.5°	96.9	97.1	97.2	97.5	97.8	98.0	98.4	98.8	99.0	99.4	99.8
165°	101.4	101.4	101.6	101.7	102.0	102.2	102.5	102.9	103.1	103.5	103.9
167.5°	106.2	106.3	106.2	106.3	106.4	106.7	106.8	107.1	107.3	107.7	108.0
170°	111.0	111.0	111.0	111.0	111.0	111.2	111.3	111.4	111.6	111.8	111.9
172.5°	115.4	115.4	115.2	115.4	115.2	115.4	115.4	115.5	115.5	115.6	115.6
175°	118.7	118.9	118.9	119.0	118.9	118.9	118.9	118.9	118.9	119.0	119.0
177.5°	121.1	121.2	121.2	121.2	121.2	121.3	121.3	121.3	121.3	121.2	121.2
180°	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1
2.5°	29493.8	29479.0	29494.1	29478.8	29494.1	29475.7	29488.2	29468.3	29473.4	29452.7	29458.0
5°	30608.9	30585.4	30598.0	30567.3	30570.6	30529.8	30529.0	30481.5	30469.0	30414.9	30391.1
7.5°	31510.7	31503.0	31507.3	31487.7	31485.4	31457.6	31444.3	31405.0	31380.3	31330.5	31296.5
10°	31367.9	31391.0	31396.9	31420.3	31425.2	31448.4	31453.3	31476.5	31481.3	31498.5	31498.7
12.5°	29940.2	30018.3	30037.0	30133.4	30174.0	30284.4	30343.5	30465.1	30537.3	30658.5	30732.9
15°	27189.8	27324.8	27378.7	27567.0	27671.1	27891.0	28029.0	28281.4	28459.6	28727.5	28918.8
17.5°	23404.3	23593.0	23678.1	23933.5	24100.0	24424.5	24658.3	25043.2	25337.8	25765.5	26104.5
20°	19206.5	19416.2	19531.8	19823.1	20019.6	20398.7	20690.6	21163.5	21557.9	22099.9	22563.3
22.5°	15145.4	15345.0	15473.3	15769.7	15990.9	16386.3	16712.6	17211.7	17653.6	18264.3	18820.0
25°	11628.8	11811.7	11927.7	12195.8	12403.6	12766.9	13078.4	13558.5	13990.9	14603.4	15173.2
27.5°	8890.0	9043.3	9155.1	9383.7	9567.0	9875.1	10142.7	10539.4	10912.0	11441.9	11949.3
30°	6806.0	6941.9	7050.7	7249.8	7419.7	7686.8	7922.1	8255.4	8563.7	8985.4	9389.0
32.5°	5201.0	5317.9	5414.8	5589.1	5743.2	5983.8	6195.8	6487.9	6752.5	7110.2	7442.2
35°	3965.6	4195.6	4179.3	4419.6	4458.3	4630.9	4820.0	5075.5	5309.8	5613.9	5896.6
37.5°	3077.9	3142.6	3211.9	3318.1	3429.8	3586.8	3746.6	4058.7	4173.1	4403.0	4636.9
40°	2482.0	2525.7	2571.5	2643.3	2721.4	2832.1	2948.5	3097.3	3249.9	3436.2	3626.6
42.5°	2098.3	2123.1	2152.2	2194.4	2242.6	2312.7	2390.6	2491.6	2597.6	2728.8	2862.7
45°	1874.7	1863.0	1871.6	1894.3	1923.3	1966.0	2015.1	2077.6	2146.7	2231.7	2322.1
47.5°	1666.3	1671.1	1673.6	1686.0	1701.5	1730.1	1759.9	1802.3	1884.3	1909.2	1958.6
50°	1528.6	1531.0	1530.2	1536.4	1544.4	1562.9	1582.2	1611.0	1639.6	1677.6	1713.9
52.5°	1413.2	1416.5	1416.0	1420.1	1424.4	1436.2	1448.3	1468.7	1487.4	1511.6	1532.5
55°	1322.2	1326.6	1328.3	1331.7	1333.8	1340.0	1344.8	1354.5	1362.5	1376.2	1388.9
57.5°	1252.1	1258.1	1260.9	1262.1	1259.6	1259.3	1257.7	1259.8	1261.4	1268.7	1275.8
60°	1196.9	1201.8	1202.5	1201.8	1197.2	1194.0	1188.8	1187.2	1186.3	1189.9	1193.7
62.5°	1139.1	1140.9	1139.7	1138.3	1133.1	1130.0	1124.6	1122.6	1120.8	1123.3	1125.4
65°	1059.2	1060.7	1059.2	1058.4	1053.8	1051.3	1046.8	1045.3	1042.7	1043.3	1042.8
67.5°	994.4	995.9	994.7	993.5	990.3	988.8	985.4	983.3	980.2	979.0	976.8
70°	929.7	930.9	929.0	927.9	924.3	922.8	919.7	919.0	916.6	916.0	913.5
72.5°	855.3	855.4	852.9	852.1	849.4	849.3	848.0	849.2	849.0	850.3	849.8
75°	779.2	778.1	774.9	774.4	772.3	773.3	771.8	773.7	773.9	776.7	777.1
77.5°	703.0	699.0	692.9	690.0	685.9	685.3	683.0	684.5	684.0	687.3	688.6
80°	606.7	601.8	594.0	590.2	585.3	584.6	582.4	584.6	583.5	587.3	589.9
82.5°	484.4	480.2	472.0	468.9	463.4	463.9	461.5	463.9	463.6	469.2	472.4
85°	358.3	355.5	347.1	339.7	331.3	326.4	321.7	320.8	319.4	321.7	323.6
87.5°	206.9	204.4	197.7	193.4	178.9	179.6	173.9	173.5	172.1	170.8	173.9
90°	19.9	22.7	20.8	23.3	21.9	24.9	23.9	26.7	24.7	27.1	25.8
92.5°	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.4	4.7
95°	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
97.5°	5.5	5.4	5.4	5.4	5.4	5.4	5.4	5.4	5.5	5.5	5.5
100°	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	6.1	6.1	6.1
102.5°	6.4	6.4	6.4	6.4	6.5	6.5	6.5	6.5	6.6	6.6	6.6
105°	6.9	6.9	7.0	7.0	7.0	7.0	7.1	7.1	7.2	7.2	7.5
107.5°	7.6	7.6	7.6	7.7	7.7	7.8	7.8	7.9	8.0	8.2	8.3
110°	8.2	8.3	8.3	8.4	8.4	8.5	8.6	8.9	9.1	9.2	9.4



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	9.1	9.1	9.2	9.3	9.4	9.6	9.7	9.9	10.2	10.5	10.8
115°	10.0	10.0	10.2	10.4	10.6	10.7	11.1	11.3	11.8	12.1	12.6
117.5°	11.3	11.4	11.6	11.8	12.0	12.5	12.7	13.2	13.6	14.1	14.7
120°	13.0	13.2	13.4	13.5	14.0	14.2	14.8	15.4	16.0	16.6	17.4
122.5°	15.0	15.3	15.5	15.8	16.3	16.9	17.5	18.2	18.9	19.7	20.5
125°	17.7	18.0	18.4	18.8	19.4	20.0	20.8	21.6	22.5	23.2	24.3
127.5°	21.2	21.5	21.9	22.5	23.2	23.9	24.7	25.5	26.6	27.5	28.6
130°	25.3	25.7	26.3	26.8	27.7	28.5	29.3	30.3	31.4	32.3	33.4
132.5°	30.3	30.6	31.3	31.9	32.8	33.7	34.8	35.6	36.7	37.7	38.8
135°	35.9	36.3	37.0	37.7	38.7	39.4	40.5	41.3	42.5	43.4	44.6
137.5°	42.2	42.6	43.3	43.9	44.9	45.7	46.7	47.6	48.6	49.6	50.5
140°	48.9	49.3	50.0	50.7	51.4	52.2	53.2	54.0	55.1	55.8	56.7
142.5°	55.9	56.1	56.8	57.4	58.2	58.8	59.7	60.3	61.2	61.8	62.9
145°	62.6	62.9	63.6	64.0	64.6	65.3	66.0	66.7	67.4	68.0	68.8
147.5°	69.3	69.6	70.2	70.7	71.4	71.9	72.4	73.0	73.7	74.3	74.9
150°	75.6	75.9	76.3	76.6	77.3	77.8	78.5	78.9	79.4	79.9	80.6
152.5°	81.3	81.5	82.0	82.2	82.8	83.3	83.6	84.2	84.8	85.1	85.6
155°	86.5	86.9	87.3	87.7	88.2	88.4	89.0	89.3	89.8	90.2	90.8
157.5°	91.5	91.8	92.3	92.5	93.0	93.4	93.9	94.1	94.7	95.0	95.5
160°	96.0	96.4	96.8	97.1	97.6	97.9	98.4	98.8	99.2	99.6	99.9
162.5°	100.2	100.6	101.1	101.4	101.8	102.2	102.6	102.9	103.5	103.8	104.3
165°	104.3	104.6	105.2	105.4	105.9	106.3	106.7	107.1	107.4	107.8	108.2
167.5°	108.4	108.6	109.1	109.5	109.9	110.3	110.6	111.0	111.4	111.7	112.0
170°	112.3	112.6	113.0	113.2	113.5	113.8	114.2	114.5	114.8	115.1	115.5
172.5°	115.9	116.1	116.2	116.3	116.6	116.9	117.1	117.3	117.6	117.7	118.0
175°	119.0	119.0	119.1	119.1	119.3	119.3	119.4	119.6	119.7	119.8	119.9
177.5°	121.2	121.2	121.2	121.2	121.2	121.2	121.2	121.2	121.2	121.2	121.2
180°	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1
2.5°	29437.4	29438.7	29414.9	29413.7	29391.4	29388.6	29366.9	29360.3	29342.7	29336.3	29318.4
5°	30330.5	30301.6	30234.8	30195.5	30129.4	30085.7	30014.2	29967.6	29898.6	29846.5	29777.1
7.5°	31233.8	31188.8	31113.8	31053.0	30961.4	30888.3	30781.0	30693.1	30577.0	30476.5	30354.5
10°	31498.7	31491.8	31472.7	31444.8	31402.2	31354.3	31281.3	31205.1	31103.4	30992.8	30857.3
12.5°	30846.9	30917.3	31013.2	31070.2	31139.3	31169.6	31198.0	31190.9	31172.3	31116.3	31037.9
15°	29195.7	29393.5	29655.4	29858.3	30091.9	30261.5	30448.9	30565.7	30682.3	30736.0	30768.9
17.5°	26569.0	26943.5	27413.2	27802.3	28251.3	28612.0	29007.3	29304.9	29611.0	29830.2	30028.5
20°	23195.1	23737.7	24401.8	24988.6	25670.8	26263.7	26913.4	27446.8	27996.8	28427.0	28834.1
22.5°	19535.4	20179.9	20982.8	21726.7	22606.2	23396.6	24288.5	25064.6	25875.1	26552.1	27206.8
25°	15936.9	16643.5	17521.5	18351.4	19347.5	20267.0	21324.6	22292.0	23339.5	24249.0	25147.4
27.5°	12650.8	13344.6	14241.0	15124.4	16177.7	17157.4	18290.6	19356.5	20549.1	21649.0	22774.1
30°	9950.0	10538.4	11342.1	12197.8	13236.7	14233.7	15379.2	16475.4	17716.1	18917.0	20184.3
32.5°	7883.1	8331.4	8963.3	9686.8	10645.3	11594.4	12685.1	13743.3	14965.1	16178.3	17496.3
35°	6260.6	6610.3	7092.0	7656.7	8468.4	9286.4	10251.2	11213.6	12353.5	13504.6	14785.8
37.5°	4936.8	5220.6	5597.9	6022.0	6673.1	7344.5	8135.6	8933.4	9923.9	10944.2	12105.3
40°	3855.1	4084.8	4378.6	4694.9	5186.6	5703.8	6315.7	6934.4	7730.1	8564.0	9524.9
42.5°	3028.5	3198.0	3405.5	3636.6	4095.3	4369.9	4784.8	5232.3	5817.3	6422.7	7145.1
45°	2432.2	2547.8	2691.6	2846.7	3059.6	3292.5	3576.7	3874.6	4430.4	4703.0	5142.3
47.5°	2031.1	2108.7	2200.2	2297.9	2423.5	2559.0	2727.5	2899.8	3122.6	3353.5	3624.3
50°	1761.0	1839.9	1871.3	1921.9	1994.6	2072.0	2167.0	2262.0	2381.5	2502.6	2642.0
52.5°	1560.5	1586.2	1620.4	1652.5	1697.6	1785.7	1814.2	1863.9	1930.9	1996.4	2069.7
55°	1407.4	1424.2	1446.4	1465.9	1493.0	1519.1	1556.6	1589.7	1634.4	1673.9	1722.4
57.5°	1288.3	1298.9	1314.4	1327.1	1344.7	1359.4	1381.4	1399.3	1425.0	1447.4	1476.8
60°	1201.6	1208.8	1219.1	1227.5	1238.7	1246.4	1257.3	1265.7	1279.3	1290.6	1307.0
62.5°	1131.0	1134.6	1141.4	1146.3	1153.4	1157.3	1163.1	1166.8	1174.3	1180.0	1189.2
65°	1046.1	1047.0	1051.5	1053.5	1059.1	1061.2	1066.0	1067.7	1073.8	1078.1	1086.1
67.5°	976.6	974.6	974.7	973.1	973.9	972.2	972.7	971.0	973.4	974.7	980.9
70°	913.1	910.4	909.5	906.6	905.7	902.7	901.9	899.1	898.9	898.0	900.2
72.5°	851.2	850.4	850.7	848.7	848.5	846.4	846.5	845.2	846.6	847.3	850.1
75°	780.1	780.3	781.7	779.9	780.4	778.7	779.3	777.7	778.6	778.2	781.0
77.5°	693.5	695.6	699.3	698.6	699.8	697.8	698.7	696.4	697.1	695.6	696.6
80°	596.1	600.4	605.5	605.3	607.5	606.1	608.0	605.9	606.7	604.1	603.4
82.5°	480.5	484.2	489.6	489.8	494.6	495.4	500.7	500.5	503.9	501.7	500.2
85°	328.5	331.0	335.7	338.3	343.2	346.2	351.3	353.3	349.7	356.3	351.1
87.5°	171.5	177.9	174.3	182.7	180.7	189.1	187.3	195.1	193.5	200.3	199.4
90°	29.3	28.5	32.3	31.8	36.6	36.7	41.8	41.5	46.3	46.2	51.1
92.5°	4.4	4.7	4.7	4.7	4.7	4.8	4.7	4.7	4.7	4.8	4.7
95°	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.1	5.1	5.1	5.1
97.5°	5.5	5.5	5.5	5.5	5.6	5.6	5.6	5.6	5.6	5.7	5.7
100°	6.1	6.2	6.2	6.2	6.3	6.3	6.4	6.4	6.5	6.5	6.5
102.5°	6.8	6.8	6.9	7.0	7.0	7.1	7.2	7.5	7.5	7.6	7.6
105°	7.6	7.7	7.8	7.9	8.0	8.3	8.4	8.5	8.6	8.9	8.9
107.5°	8.5	8.6	9.0	9.1	9.3	9.6	9.8	9.9	10.2	10.4	10.5
110°	9.7	9.9	10.2	10.6	10.8	11.2	11.4	11.8	12.0	12.2	12.5



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	11.1	11.6	11.9	12.5	12.7	13.2	13.5	14.0	14.1	14.6	14.8
115°	13.0	13.5	14.1	14.6	15.0	15.5	16.0	16.4	16.9	17.2	17.5
117.5°	15.3	16.0	16.4	17.2	17.7	18.4	18.9	19.4	19.9	20.3	20.7
120°	18.0	18.8	19.6	20.3	21.0	21.6	22.2	22.9	23.3	23.9	24.3
122.5°	21.3	22.2	22.9	23.9	24.5	25.3	25.9	26.7	27.2	27.8	28.3
125°	25.2	26.0	26.9	27.8	28.6	29.5	30.2	30.9	31.6	32.3	32.8
127.5°	29.5	30.5	31.4	32.4	33.2	34.1	34.8	35.6	36.3	37.0	37.7
130°	34.3	35.5	36.3	37.3	38.0	39.1	39.7	40.6	41.3	42.1	42.9
132.5°	39.7	40.7	41.6	42.6	43.4	44.3	45.1	46.0	46.6	47.5	48.2
135°	45.4	46.5	47.2	48.2	48.9	49.7	50.5	51.4	52.1	53.0	53.8
137.5°	51.2	52.4	53.1	54.0	54.6	55.5	56.1	57.0	57.6	58.6	59.3
140°	57.4	58.3	58.9	59.8	60.4	61.2	61.8	62.6	63.2	64.0	64.5
142.5°	63.6	64.4	64.9	65.8	66.3	67.1	67.4	68.1	68.8	69.4	70.0
145°	69.4	70.2	70.7	71.4	71.7	72.4	72.9	73.5	73.8	74.5	74.9
147.5°	75.5	76.2	76.4	77.1	77.3	77.9	78.3	78.7	79.2	79.4	79.8
150°	80.8	81.5	81.9	82.2	82.6	83.1	83.4	83.6	83.8	84.2	84.5
152.5°	86.1	86.5	86.8	87.1	87.5	87.8	87.9	88.3	88.4	88.5	88.7
155°	91.0	91.5	91.8	92.2	92.3	92.6	92.6	92.9	93.0	93.2	93.2
157.5°	95.7	96.2	96.5	96.8	96.9	97.2	97.4	97.6	97.6	97.8	97.8
160°	100.3	100.6	101.0	101.2	101.4	101.6	101.7	102.0	102.1	102.1	102.1
162.5°	104.5	104.9	105.2	105.4	105.7	105.9	106.0	106.2	106.3	106.4	106.4
165°	108.5	108.8	109.1	109.5	109.6	109.9	110.0	110.3	110.3	110.4	110.4
167.5°	112.3	112.7	113.0	113.2	113.3	113.5	113.7	114.0	114.0	114.1	114.1
170°	115.6	115.9	116.2	116.3	116.5	116.6	116.8	116.9	116.9	117.0	117.0
172.5°	118.2	118.4	118.4	118.7	118.7	118.9	119.0	119.0	119.1	119.1	119.1
175°	119.9	120.1	120.3	120.3	120.3	120.4	120.4	120.4	120.4	120.4	120.4
177.5°	121.2	121.2	121.2	121.1	121.1	121.1	121.1	121.1	121.1	121.1	121.0
180°	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1	29129.1
2.5°	29312.1	29299.3	29291.1	29280.7	29274.3	29266.2	29260.3	29255.2	29251.1	29247.3	29244.5
5°	29724.2	29658.7	29607.9	29552.8	29507.5	29462.5	29427.6	29398.9	29379.0	29364.1	29355.2
7.5°	30249.0	30129.1	30022.5	29910.1	29809.5	29710.5	29625.2	29551.8	29496.6	29460.8	29439.2
10°	30717.7	30557.1	30398.4	30231.2	30072.8	29918.9	29777.1	29652.4	29553.5	29487.9	29449.6
12.5°	30927.7	30790.9	30628.8	30447.3	30253.1	30056.6	29865.1	29692.4	29547.5	29450.1	29394.0
15°	30742.7	30686.6	30576.5	30435.6	30251.4	30048.2	29823.3	29612.0	29417.5	29291.4	29218.4
17.5°	30140.9	30219.3	30210.8	30157.0	30024.4	29853.5	29624.3	29386.9	29143.6	28975.1	28883.0
20°	29125.2	29371.5	29496.6	29560.7	29508.7	29397.8	29190.3	28949.4	28665.8	28445.8	28311.6
22.5°	27697.9	28132.8	28403.9	28602.2	28644.4	28606.5	28423.4	28194.2	27878.2	27613.7	27415.4
25°	25860.5	26497.8	26926.2	27262.0	27392.4	27426.1	27270.2	27042.3	26690.0	26381.9	26109.5
27.5°	23696.3	24524.3	25096.3	25547.5	25751.3	25839.6	25696.1	25463.6	25046.8	24679.0	24323.2
30°	21259.8	22242.2	22930.9	23472.0	23720.3	23837.0	23684.5	23425.0	22940.1	22497.5	22049.2
32.5°	18652.0	19727.1	20477.5	21065.1	21311.2	21420.9	21221.5	20930.0	20369.6	19848.1	19325.4
35°	15921.8	17006.8	17763.6	18335.5	18541.8	18607.9	18352.9	18016.0	17395.1	16822.7	16252.7
37.5°	13135.8	14145.3	14833.2	15346.5	15474.1	15485.5	15178.2	14806.2	14153.5	13589.1	13021.8
40°	10374.1	11225.3	11780.7	12191.5	12235.9	12196.3	11862.3	11487.8	10877.2	10371.6	9873.6
42.5°	7772.5	8415.1	8811.3	9092.9	9076.1	8998.1	8691.8	8370.0	7866.2	7481.1	7089.1
45°	5543.7	5967.5	6199.1	6363.9	6311.0	6236.6	5998.2	5772.7	5430.3	5181.6	4918.2
47.5°	3851.3	4357.3	4269.2	4591.4	4313.8	4497.1	4115.4	3905.0	3723.3	3591.2	3442.3
50°	2757.2	2873.2	2929.2	2967.4	2947.1	2918.9	2850.3	2789.1	2706.1	2645.5	2575.1
52.5°	2129.3	2187.3	2219.1	2242.0	2237.5	2227.2	2197.3	2170.0	2131.2	2105.5	2074.7
55°	1803.6	1804.5	1862.9	1837.8	1874.8	1831.5	1848.5	1800.4	1808.2	1767.0	1739.3
57.5°	1498.7	1522.5	1533.2	1543.5	1540.6	1538.8	1527.2	1521.4	1508.4	1504.4	1495.1
60°	1318.3	1330.8	1333.4	1338.1	1334.2	1332.6	1323.6	1320.3	1311.6	1309.9	1303.8
62.5°	1194.7	1201.0	1201.0	1201.0	1195.8	1190.8	1180.8	1175.6	1168.1	1166.5	1162.9
65°	1091.5	1098.0	1099.1	1100.5	1096.7	1092.9	1084.0	1078.2	1070.6	1067.7	1063.5
67.5°	984.9	991.9	994.3	997.9	995.7	994.9	988.9	986.6	981.6	980.4	976.6
70°	901.2	904.1	903.9	903.8	899.1	894.8	887.8	884.4	879.2	878.1	874.7
72.5°	851.5	853.5	852.2	850.3	844.3	838.0	829.7	823.7	816.8	812.5	807.6
75°	781.4	784.1	782.3	781.2	775.7	771.6	765.0	761.6	756.8	755.4	752.0
77.5°	695.3	696.6	693.8	693.5	689.3	686.7	681.7	680.9	677.3	677.4	674.1
80°	599.6	598.8	594.3	593.4	589.2	588.2	584.2	584.5	581.7	582.8	580.6
82.5°	493.4	490.6	484.7	483.0	478.1	477.7	475.1	477.3	475.6	478.1	476.6
85°	353.5	354.4	351.7	351.7	350.3	350.7	350.5	352.1	352.4	354.7	354.6
87.5°	197.1	199.9	199.4	202.0	201.9	204.8	205.8	210.1	210.7	214.6	214.6
90°	51.0	56.2	56.0	61.4	61.6	66.8	67.8	73.0	73.4	77.9	77.5
92.5°	4.7	4.7	4.8	4.7	4.7	4.4	4.9	4.4	4.7	4.4	4.4
95°	5.1	5.1	5.1	5.1	5.1	5.0	5.0	5.0	5.0	5.0	5.0
97.5°	5.7	5.7	5.7	5.7	5.7	5.7	5.6	5.6	5.6	5.6	5.6
100°	6.5	6.5	6.6	6.5	6.5	6.5	6.5	6.5	6.5	6.4	6.4
102.5°	7.7	7.7	7.7	7.7	7.7	7.7	7.7	7.6	7.6	7.6	7.6
105°	9.0	9.0	9.1	9.1	9.1	9.1	9.1	9.0	9.0	9.0	9.0
107.5°	10.6	10.6	10.7	10.7	10.8	10.8	10.8	10.7	10.8	10.7	10.7
110°	12.6	12.7	12.8	12.8	13.0	13.0	13.0	13.0	13.2	13.0	13.0



TEST NUMBER: P1444465
 CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	15.0	15.3	15.5	15.5	15.6	15.6	15.8	15.8	16.0	15.8	16.0
115°	17.8	18.2	18.4	18.5	18.8	18.9	19.1	19.1	19.3	19.3	19.3
117.5°	21.2	21.5	21.8	22.1	22.4	22.6	22.9	22.9	23.1	23.1	23.2
120°	24.7	25.2	25.7	26.0	26.4	26.7	27.1	27.2	27.4	27.4	27.5
122.5°	28.9	29.3	30.0	30.3	30.9	31.3	31.7	31.9	32.1	32.1	32.3
125°	33.5	34.1	34.8	35.2	35.9	36.3	36.7	36.9	37.3	37.3	37.4
127.5°	38.4	39.1	39.8	40.4	41.1	41.5	42.0	42.2	42.6	42.6	42.7
130°	43.7	44.3	45.1	45.8	46.5	46.9	47.6	47.9	48.2	48.2	48.3
132.5°	49.1	49.7	50.7	51.2	52.1	52.5	53.2	53.4	53.9	53.9	54.0
135°	54.6	55.3	56.1	56.8	57.5	58.2	58.7	59.0	59.5	59.5	59.6
137.5°	60.1	60.8	61.5	62.2	62.9	63.5	64.0	64.4	64.6	64.9	64.9
140°	65.4	65.9	66.8	67.3	68.0	68.6	69.1	69.4	69.9	69.9	70.0
142.5°	70.6	71.0	71.9	72.3	72.9	73.3	73.7	74.1	74.4	74.5	74.5
145°	75.5	75.8	76.4	76.9	77.3	77.7	78.0	78.4	78.5	78.5	78.6
147.5°	80.3	80.6	80.8	81.2	81.7	82.0	82.1	82.2	82.6	82.6	82.6
150°	84.8	84.9	85.1	85.2	85.5	85.6	85.7	85.9	86.1	85.9	85.9
152.5°	88.9	89.0	89.1	89.1	89.2	89.2	89.2	89.1	89.1	89.0	88.9
155°	93.3	93.3	93.3	93.2	93.3	93.2	93.0	92.9	92.7	92.5	92.3
157.5°	97.8	97.6	97.8	97.6	97.5	97.4	97.2	96.9	96.8	96.4	96.1
160°	102.2	102.1	102.1	102.0	101.8	101.6	101.4	101.1	100.8	100.4	100.0
162.5°	106.4	106.4	106.3	106.2	106.0	105.9	105.7	105.3	105.0	104.6	104.3
165°	110.5	110.4	110.4	110.3	110.2	109.9	109.8	109.3	109.1	108.8	108.4
167.5°	114.1	114.1	114.0	113.8	113.7	113.5	113.3	113.1	112.8	112.4	112.1
170°	117.0	116.9	116.9	116.8	116.6	116.5	116.2	116.1	115.7	115.5	115.2
172.5°	119.0	119.0	118.9	118.7	118.7	118.5	118.3	118.2	117.9	117.7	117.6
175°	120.3	120.3	120.1	120.1	119.9	119.8	119.7	119.6	119.4	119.3	119.1
177.5°	121.0	121.0	120.8	120.8	120.6	120.6	120.6	120.5	120.5	120.4	120.3
180°	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8	120.8



TEST NUMBER: P1444465
CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	29129.1	29129.1
2.5°	29241.9	29240.4
5°	29350.6	29348.9
7.5°	29433.3	29432.8
10°	29443.0	29448.1
12.5°	29384.3	29388.4
15°	29212.8	29220.7
17.5°	28884.7	28895.2
20°	28319.7	28330.7
22.5°	27404.7	27409.2
25°	26074.3	26055.5
27.5°	24260.7	24228.2
30°	21955.1	21923.7
32.5°	19206.2	19186.5
35°	16111.9	16099.5
37.5°	12854.1	12828.8
40°	9691.4	9617.8
42.5°	6917.5	6788.2
45°	4780.6	4627.4
47.5°	3337.3	3242.7
50°	2529.6	2499.0
52.5°	2061.2	2054.1
55°	1739.2	1736.0
57.5°	1497.1	1496.0
60°	1307.0	1306.7
62.5°	1165.3	1165.8
65°	1065.4	1065.6
67.5°	977.5	976.9
70°	875.9	875.2
72.5°	806.0	804.8
75°	752.0	751.2
77.5°	675.2	674.0
80°	582.1	580.6
82.5°	478.8	477.1
85°	357.1	357.3
87.5°	218.5	218.4
90°	81.9	80.8
92.5°	4.7	4.9
95°	5.0	5.0
97.5°	5.6	5.6
100°	6.4	6.4
102.5°	7.6	7.6
105°	9.0	9.0
107.5°	10.7	10.7
110°	13.0	13.0



TEST NUMBER: P1444465
CATALOG NUMBER: EHBR1-36-UNV-TA-L830

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	15.8	15.8
115°	19.1	19.1
117.5°	23.1	22.9
120°	27.4	27.4
122.5°	32.0	31.9
125°	37.1	37.0
127.5°	42.5	42.3
130°	48.0	47.9
132.5°	53.8	53.4
135°	59.3	59.0
137.5°	64.5	64.4
140°	69.6	69.4
142.5°	74.4	74.2
145°	78.5	78.3
147.5°	82.1	82.1
150°	85.6	85.4
152.5°	88.4	88.2
155°	91.9	91.5
157.5°	95.5	95.3
160°	99.6	99.2
162.5°	103.8	103.4
165°	107.8	107.4
167.5°	111.7	111.4
170°	114.8	114.7
172.5°	117.3	117.0
175°	119.0	118.9
177.5°	120.3	120.1
180°	120.8	120.8

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Report Prepared for

Cooper Lighting Solutions

Metalux

Report Number: SP1-2506-472-2

Test Date: 07/31/2025

Luminaire Tested: EHBR-60-L830-N

Data in this report applies to families of products including EHBR-60-L830-N

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2506-472-2
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 08/05/2025
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: Metalux
 Catalog Number: **EHBR-60-L830-N**
 Description: Elevate Round Highbay at, 60000 lumens, 3000K 80CRI LEDs with N lens

Spectral Parameters

CCT (K): 2983
 CIE u': 0.2516
 CIE v': 0.5201
 Duv: -0.0012
 CIE x: 0.4364
 CIE y: 0.4010
 CIE z: 0.1626
 Peak Wavelength (nm): 630
 Dominant Wavelength (nm): 583
 Purity: 51.34918
 Rf: 81.2
 Rg: 101.5

CRI (Ra):	83.4		
R1:	84.0	R9:	29.4
R2:	87.5	R10:	68.6
R3:	88.9	R11:	82.2
R4:	83.8	R12:	61.6
R5:	81.9	R13:	83.9
R6:	83.1	R14:	92.5
R7:	87.1	R15:	79.8
R8:	70.9		



Test Conditions

Stabilization Time: 38M
 Operation Time: 1H 38M
 Sphere Temperature (°C): 25.0

REPORT NUMBER: SP1-2506-472-2

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	76INCH SPHERE IN0058	6/16/2025	12/16/2025
Power Meter	XITRON INXT2011004	1/21/2025	1/21/2026
AC Power Source	CHROMA 61603 IN0063	10/22/2024	10/22/2025
DC Power Source	AGILENT E3634A IN0208	10/22/2024	10/22/2025
Sphere Thermometer	ONSET IN0085	10/22/2024	10/22/2025
Room Thermometer	ONSET IN0046	10/22/2024	10/22/2025

REPORT NUMBER: SP1-2506-472-2

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3000K 4-step quadrangle

REPORT NUMBER: SP1-2506-472-2

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	43	NR	620	294	NR	750	6	NR	880	0	NR
365	0	NR	495	59	NR	625	294	NR	755	5	NR	885	0	NR
370	0	NR	500	81	NR	630	1000	NR	760	4	NR	890	0	NR
375	0	NR	505	109	NR	635	637	NR	765	4	NR	895	0	NR
380	0	NR	510	135	NR	640	175	NR	770	3	NR	900	0	NR
385	0	NR	515	160	NR	645	171	NR	775	3	NR	905	0	NR
390	1	NR	520	180	NR	650	146	NR	780	2	NR	910	0	NR
395	1	NR	525	195	NR	655	119	NR	785	2	NR	915	0	NR
400	2	NR	530	207	NR	660	99	NR	790	2	NR	920	0	NR
405	3	NR	535	218	NR	665	82	NR	795	2	NR	925	0	NR
410	5	NR	540	227	NR	670	76	NR	800	1	NR	930	0	NR
415	10	NR	545	237	NR	675	61	NR	805	1	NR	935	0	NR
420	20	NR	550	247	NR	680	52	NR	810	1	NR	940	0	NR
425	35	NR	555	259	NR	685	44	NR	815	1	NR	945	0	NR
430	58	NR	560	271	NR	690	38	NR	820	1	NR	950	0	NR
435	90	NR	565	283	NR	695	33	NR	825	1	NR	955	0	NR
440	135	NR	570	293	NR	700	27	NR	830	1	NR	960	0	NR
445	204	NR	575	303	NR	705	24	NR	835	1	NR	965	0	NR
450	233	NR	580	310	NR	710	20	NR	840	0	NR	970	0	NR
455	153	NR	585	313	NR	715	17	NR	845	0	NR	975	0	NR
460	98	NR	590	314	NR	720	15	NR	850	0	NR	980	0	NR
465	76	NR	595	310	NR	725	13	NR	855	0	NR	985	0	NR
470	53	NR	600	307	NR	730	11	NR	860	0	NR	990	0	NR
475	39	NR	605	303	NR	735	9	NR	865	0	NR	995	0	NR
480	35	NR	610	331	NR	740	8	NR	870	0	NR	1000	0	NR
485	36	NR	615	353	NR	745	7	NR	875	0	NR			

REPORT NUMBER: SP1-2506-472-2

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR

S/P: 1.27

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	43	NR	620	294	NR	750	6	NR	880	0	NR
365	0	NR	495	59	NR	625	294	NR	755	5	NR	885	0	NR
370	0	NR	500	81	NR	630	1000	NR	760	4	NR	890	0	NR
375	0	NR	505	109	NR	635	637	NR	765	4	NR	895	0	NR
380	0	NR	510	135	NR	640	175	NR	770	3	NR	900	0	NR
385	0	NR	515	160	NR	645	171	NR	775	3	NR	905	0	NR
390	1	NR	520	180	NR	650	146	NR	780	2	NR	910	0	NR
395	1	NR	525	195	NR	655	119	NR	785	2	NR	915	0	NR
400	2	NR	530	207	NR	660	99	NR	790	2	NR	920	0	NR
405	3	NR	535	218	NR	665	82	NR	795	2	NR	925	0	NR
410	5	NR	540	227	NR	670	76	NR	800	1	NR	930	0	NR
415	10	NR	545	237	NR	675	61	NR	805	1	NR	935	0	NR
420	20	NR	550	247	NR	680	52	NR	810	1	NR	940	0	NR
425	35	NR	555	259	NR	685	44	NR	815	1	NR	945	0	NR
430	58	NR	560	271	NR	690	38	NR	820	1	NR	950	0	NR
435	90	NR	565	283	NR	695	33	NR	825	1	NR	955	0	NR
440	135	NR	570	293	NR	700	27	NR	830	1	NR	960	0	NR
445	204	NR	575	303	NR	705	24	NR	835	1	NR	965	0	NR
450	233	NR	580	310	NR	710	20	NR	840	0	NR	970	0	NR
455	153	NR	585	313	NR	715	17	NR	845	0	NR	975	0	NR
460	98	NR	590	314	NR	720	15	NR	850	0	NR	980	0	NR
465	76	NR	595	310	NR	725	13	NR	855	0	NR	985	0	NR
470	53	NR	600	307	NR	730	11	NR	860	0	NR	990	0	NR
475	39	NR	605	303	NR	735	9	NR	865	0	NR	995	0	NR
480	35	NR	610	331	NR	740	8	NR	870	0	NR	1000	0	NR
485	36	NR	615	353	NR	745	7	NR	875	0	NR			

REPORT NUMBER: SP1-2506-472-2

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 2.34

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	43	NR	620	294	NR	750	6	NR	880	0	NR
365	0	NR	495	59	NR	625	294	NR	755	5	NR	885	0	NR
370	0	NR	500	81	NR	630	1000	NR	760	4	NR	890	0	NR
375	0	NR	505	109	NR	635	637	NR	765	4	NR	895	0	NR
380	0	NR	510	135	NR	640	175	NR	770	3	NR	900	0	NR
385	0	NR	515	160	NR	645	171	NR	775	3	NR	905	0	NR
390	1	NR	520	180	NR	650	146	NR	780	2	NR	910	0	NR
395	1	NR	525	195	NR	655	119	NR	785	2	NR	915	0	NR
400	2	NR	530	207	NR	660	99	NR	790	2	NR	920	0	NR
405	3	NR	535	218	NR	665	82	NR	795	2	NR	925	0	NR
410	5	NR	540	227	NR	670	76	NR	800	1	NR	930	0	NR
415	10	NR	545	237	NR	675	61	NR	805	1	NR	935	0	NR
420	20	NR	550	247	NR	680	52	NR	810	1	NR	940	0	NR
425	35	NR	555	259	NR	685	44	NR	815	1	NR	945	0	NR
430	58	NR	560	271	NR	690	38	NR	820	1	NR	950	0	NR
435	90	NR	565	283	NR	695	33	NR	825	1	NR	955	0	NR
440	135	NR	570	293	NR	700	27	NR	830	1	NR	960	0	NR
445	204	NR	575	303	NR	705	24	NR	835	1	NR	965	0	NR
450	233	NR	580	310	NR	710	20	NR	840	0	NR	970	0	NR
455	153	NR	585	313	NR	715	17	NR	845	0	NR	975	0	NR
460	98	NR	590	314	NR	720	15	NR	850	0	NR	980	0	NR
465	76	NR	595	310	NR	725	13	NR	855	0	NR	985	0	NR
470	53	NR	600	307	NR	730	11	NR	860	0	NR	990	0	NR
475	39	NR	605	303	NR	735	9	NR	865	0	NR	995	0	NR
480	35	NR	610	331	NR	740	8	NR	870	0	NR	1000	0	NR
485	36	NR	615	353	NR	745	7	NR	875	0	NR			

Summary

$R_f = 81.2$
 $R_g = 101.5$
 CIE $R_a = 83.4$
 $R_9 = 29.4$



Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 86	CES26 = 71	CES51 = 89	CES76 = 65
CES02 = 63	CES27 = 89	CES52 = 89	CES77 = 82
CES03 = 31	CES28 = 86	CES53 = 80	CES78 = 67
CES04 = 70	CES29 = 68	CES54 = 92	CES79 = 89
CES05 = 50	CES30 = 77	CES55 = 90	CES80 = 85
CES06 = 51	CES31 = 70	CES56 = 81	CES81 = 75
CES07 = 43	CES32 = 64	CES57 = 79	CES82 = 93
CES08 = 41	CES33 = 74	CES58 = 81	CES83 = 89
CES09 = 29	CES34 = 76	CES59 = 92	CES84 = 91
CES10 = 76	CES35 = 87	CES60 = 96	CES85 = 81
CES11 = 59	CES36 = 99	CES61 = 91	CES86 = 74
CES12 = 65	CES37 = 81	CES62 = 93	CES87 = 83
CES13 = 44	CES38 = 83	CES63 = 79	CES88 = 86
CES14 = 74	CES39 = 94	CES64 = 81	CES89 = 74
CES15 = 72	CES40 = 89	CES65 = 78	CES90 = 85
CES16 = 48	CES41 = 88	CES66 = 76	CES91 = 87
CES17 = 50	CES42 = 80	CES67 = 74	CES92 = 73
CES18 = 57	CES43 = 75	CES68 = 79	CES93 = 84
CES19 = 72	CES44 = 99	CES69 = 83	CES94 = 64
CES20 = 67	CES45 = 83	CES70 = 72	CES95 = 80
CES21 = 87	CES46 = 82	CES71 = 70	CES96 = 86
CES22 = 79	CES47 = 79	CES72 = 90	CES97 = 85
CES23 = 92	CES48 = 78	CES73 = 65	CES98 = 83
CES24 = 91	CES49 = 79	CES74 = 94	CES99 = 82
CES25 = 72	CES50 = 88	CES75 = 70	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)