

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: METALUX

Report Number: P1444472

Luminaire Tested: EHBR1-42-UNV-TA-L830-UPL40

Issue Date: 5/1/2026

Test Information

Test Method: LM-79-2019
Report Number: P1444472
REPORT IS A COMBINATION OF REPORTS P1444359 AND P1431635
Test Lab: INNOVATION CENTER
Issue Date: 5/1/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: METALUX
Catalog Number: EHBR1-42-UNV-TA-L830-UPL40
Description: Elevate Round Highbay at, 42000 lumens, 3000K 80CRI LEDs with TA lens
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 42405.7 lumens
Efficiency: N/A
Efficacy: 166.3 lumens/watt
Spacing Criteria (0/90/45): 1.13 / 0.77 / 0.88
Luminous Opening: Vertical Cylinder (Dia: 1.71' x H: 0.1')
CIE Type: Direct

Input Watts (W): 255
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1444472
CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

Luminous Intensity Polar Plot



— 0°-180° - - 45°-225° - · - · 90°-270° - · - · 135°-315°



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	117	117	117	117	113	113	113	113	106	106	106	100	100	100	94	94	94	94	94	94	91
1	110	106	103	100	106	103	100	98	97	95	93	92	90	89	87	86	85	85	85	85	82
2	103	97	92	88	100	94	90	86	90	86	83	85	82	80	81	79	77	77	77	77	74
3	97	89	83	78	94	87	81	77	83	78	75	79	75	72	76	73	70	70	70	70	68
4	91	82	75	70	88	80	74	70	77	72	68	73	69	66	71	67	64	64	64	64	62
5	85	76	69	64	83	74	68	63	71	66	62	69	64	61	66	62	59	59	59	59	57
6	80	70	64	59	78	69	63	58	67	61	57	64	59	56	62	58	55	55	55	55	53
7	76	66	59	54	74	64	58	54	62	57	53	60	55	52	58	54	51	51	51	51	49
8	72	61	55	50	70	60	54	50	58	53	49	57	52	48	55	51	47	47	47	47	46
9	68	57	51	47	66	57	50	46	55	49	46	53	48	45	52	47	44	44	44	44	43
10	65	54	48	43	63	53	47	43	52	46	43	50	46	42	49	45	42	42	42	42	40

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	157268	157268	157268	157268
5°	158030	162638	155818	164768
10°	159349	170758	155528	169628
15°	160131	154790	155256	148558
20°	158475	115313	153288	106692
25°	150003	72929	145046	66171
30°	131039	43825	125963	40052
35°	100848	27500	95047	24360
40°	63796	17250	58368	16210
45°	32881	13439	32336	13218
50°	19279	11954	18687	11767
55°	14768	11309	14222	11208
60°	12497	11553	11965	11404
65°	11737	12065	11288	11653
70°	11467	12633	10896	12157
75°	12261	13396	11599	12806
80°	12688	14836	11504	13544
85°	11949	14315	9657	12255

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 25°
 Vertical Angle: 45°
 Luminance: 50321 cd/sqm



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	3300.4	7.8
10°-20°	9284.5	21.9
20°-30°	10574.3	24.9
30°-40°	7600.3	17.9
40°-50°	3505.3	8.3
50°-60°	1677.4	4.0
60°-70°	1223.9	2.9
70°-80°	929.8	2.2
80°-90°	429.4	1.0
90°-100°	109.3	0.3
100°-110°	643.3	1.5
110°-120°	1188.7	2.8
120°-130°	723.4	1.7
130°-140°	460.0	1.1
140°-150°	337.2	0.8
150°-160°	232.4	0.5
160°-170°	138.9	0.3
170°-180°	47.3	0.1
0°-30°	23159.2	54.6
0°-40°	30759.5	72.5
0°-60°	35942.1	84.8
0°-90°	38525.3	90.8
90°-120°	1941.3	4.6
90°-150°	3461.9	8.2
90°-180°	3880.0	9.1
0°-180°	42405.7	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	33489	33489	33489	33489	33489	
5°	33742	34726	33270	35181	33742	3224
15°	33595	32474	32572	31167	33595	9465
25°	29956	14564	28966	13214	29956	13579
35°	18509	5047	17445	4471	18509	11360
45°	5320	2174	5232	2139	5320	4525
55°	1996	1528	1922	1515	1996	1842
65°	1225	1259	1178	1216	1225	1224
75°	864	944	817	902	864	898
85°	411	492	332	421	411	386
90°	119	149	40	47	119	73
95°	50	56	50	56	50	48
105°	230	298	154	299	230	306
115°	1035	1258	1084	1259	1035	956
125°	773	816	876	818	773	704
135°	601	538	648	541	601	469
145°	528	516	562	522	528	334
155°	489	492	521	496	489	227
165°	483	484	501	486	483	137
175°	492	497	501	498	492	47
180°	498	498	498	498	498	



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (FULL):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
0°	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2
2.5°	33617.2	33614.5	33613.9	33611.5	33610.9	33610.9	33609.8	33607.1	33605.4	33601.5	33597.1
5°	33741.8	33740.3	33741.3	33741.5	33739.1	33733.9	33725.7	33715.7	33703.1	33691.1	33680.4
7.5°	33838.3	33840.7	33843.7	33843.0	33835.7	33823.4	33806.7	33797.2	33802.8	33821.1	33862.8
10°	33855.9	33870.4	33875.9	33874.2	33859.5	33849.0	33853.1	33888.5	33959.2	34053.4	34182.2
12.5°	33787.3	33804.9	33804.3	33798.4	33784.3	33798.7	33850.1	33955.7	34107.2	34292.9	34510.9
15°	33594.6	33617.4	33610.9	33603.4	33593.9	33641.2	33743.8	33927.3	34161.1	34423.1	34691.4
17.5°	33220.4	33247.9	33234.5	33225.9	33217.9	33306.6	33482.9	33751.6	34046.1	34342.5	34596.7
20°	32571.2	32589.7	32557.8	32542.8	32555.5	32729.1	32988.8	33331.9	33642.4	33922.6	34096.4
22.5°	31511.9	31534.9	31474.9	31468.0	31541.9	31808.7	32137.4	32520.8	32812.5	33034.6	33101.6
25°	29955.5	29978.1	29906.9	29949.4	30075.3	30438.5	30830.0	31240.2	31489.1	31653.6	31608.2
27.5°	27854.7	27875.3	27807.8	27894.7	28093.7	28571.0	29031.7	29476.6	29698.4	29813.8	29667.7
30°	25205.2	25248.1	25168.2	25289.5	25593.2	26213.0	26740.8	27239.8	27460.9	27548.7	27321.3
32.5°	22058.5	22119.3	22031.4	22211.8	22635.6	23380.0	23979.7	24537.2	24781.8	24881.9	24625.1
35°	18509.3	18596.7	18495.7	18766.6	19289.2	20118.2	20782.2	21404.6	21694.3	21836.3	21577.5
37.5°	14749.0	14832.3	14777.7	15139.0	15712.9	16572.2	17250.0	17921.5	18248.6	18461.7	18257.7
40°	11057.4	11133.6	11174.9	11588.1	12127.9	12937.7	13588.7	14253.1	14619.1	14886.6	14760.8
42.5°	7804.4	7881.2	8021.7	8420.4	8870.4	9540.8	10098.5	10695.0	11044.6	11330.0	11281.4
45°	5320.0	5409.3	5585.3	5911.8	6237.3	6718.2	7127.7	7591.7	7877.2	8138.6	8141.7
47.5°	3728.0	3790.7	3947.9	4170.9	4383.1	4985.2	5009.9	5237.9	5429.9	5625.2	5650.6
50°	2873.2	2910.8	2994.3	3118.5	3238.8	3395.0	3538.1	3703.4	3821.5	3928.7	3954.2
52.5°	2361.5	2385.5	2427.9	2495.2	2565.0	2649.9	2726.6	2817.2	2881.6	2938.9	2950.9
55°	1995.8	2015.7	2078.9	2091.7	2171.5	2186.9	2220.9	2276.1	2313.5	2347.9	2356.5
57.5°	1720.0	1734.4	1747.8	1776.5	1801.0	1836.8	1865.5	1905.2	1928.8	1953.6	1955.7
60°	1502.3	1512.7	1522.2	1542.1	1558.9	1583.7	1603.6	1630.5	1647.4	1666.0	1668.1
62.5°	1340.3	1347.7	1354.1	1367.2	1379.2	1398.3	1414.1	1436.5	1452.3	1466.7	1469.9
65°	1225.1	1230.6	1234.7	1244.6	1255.1	1271.3	1285.5	1304.0	1315.5	1326.6	1328.9
67.5°	1123.1	1128.4	1132.6	1141.6	1148.8	1161.0	1170.5	1184.3	1193.0	1201.8	1202.1
70°	1006.2	1011.1	1014.3	1022.7	1028.5	1039.0	1046.7	1059.0	1068.0	1077.8	1080.3
72.5°	925.3	928.1	932.5	940.2	948.2	959.4	969.7	982.6	993.4	1003.6	1007.9
75°	863.7	867.1	869.9	876.5	882.1	891.6	899.2	911.0	920.4	931.4	936.7
77.5°	774.8	778.7	781.2	787.8	792.6	801.6	807.3	817.9	825.6	835.5	840.4
80°	667.5	671.1	672.8	679.0	682.9	691.2	696.8	706.9	713.4	723.3	729.1
82.5°	548.4	551.9	552.9	558.7	560.9	567.7	571.8	582.3	590.1	603.1	612.0
85°	410.7	412.0	413.9	412.4	420.8	421.2	430.7	432.4	444.8	448.0	462.2
87.5°	251.0	254.8	256.7	262.4	264.9	270.6	272.3	278.4	281.8	288.7	291.9
90°	119.1	125.8	128.6	136.3	138.9	145.8	148.1	155.8	158.6	166.5	170.8
92.5°	43.9	46.8	49.6	52.9	55.8	59.5	62.8	66.0	69.0	72.6	78.5
95°	50.1	53.5	56.9	60.2	63.6	66.9	70.3	73.6	77.0	80.4	90.1
97.5°	62.9	65.9	68.8	71.7	74.6	77.6	80.5	83.4	86.3	89.1	100.8
100°	82.0	84.4	86.9	89.4	91.8	94.3	96.8	99.2	101.7	104.2	125.8
102.5°	135.9	144.6	153.4	162.1	170.9	179.5	188.4	196.9	205.7	214.4	260.4
105°	230.3	254.0	277.9	301.5	325.3	349.1	372.9	396.3	420.1	443.8	518.7
107.5°	393.8	437.6	481.6	525.6	569.5	613.4	657.3	701.1	745.0	788.6	864.7
110°	727.5	762.8	798.2	833.5	868.8	904.2	939.5	974.6	1010.1	1045.2	1100.7



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	0°	2.5°	5°	7.5°	10°	12.5°	15°	17.5°	20°	22.5°	25°
112.5°	981.1	996.9	1013.1	1029.0	1045.0	1060.8	1076.8	1092.7	1108.8	1124.5	1164.1
115°	1035.3	1040.8	1046.6	1052.0	1057.6	1063.2	1068.8	1074.2	1079.8	1085.2	1112.1
117.5°	1005.4	1004.3	1003.5	1002.5	1001.3	1000.3	999.3	998.0	996.8	995.7	1010.8
120°	937.6	932.7	927.9	922.8	918.0	912.9	908.0	902.9	897.8	892.6	899.1
122.5°	852.2	846.3	840.7	834.5	828.7	822.5	816.7	810.3	804.4	798.3	800.7
125°	773.2	767.3	761.5	755.5	749.3	743.2	737.0	730.8	724.6	718.4	719.7
127.5°	704.6	700.6	696.4	692.0	687.7	683.1	678.7	674.1	669.7	665.0	665.3
130°	660.6	656.9	653.2	649.1	645.3	641.1	637.1	632.7	628.7	624.3	625.0
132.5°	624.6	622.1	619.4	616.5	613.6	610.4	607.5	604.1	601.2	598.0	598.7
135°	600.8	598.3	596.0	593.2	590.6	587.6	584.7	581.6	578.7	575.5	576.5
137.5°	580.7	578.4	576.2	573.7	571.3	568.3	565.7	562.9	560.2	557.2	558.1
140°	562.2	560.2	558.1	555.8	553.7	551.2	548.5	546.0	543.4	540.7	542.0
142.5°	541.4	539.7	538.3	536.4	534.7	532.5	530.6	528.2	526.2	524.0	525.7
145°	528.0	526.7	525.4	523.8	522.2	520.2	518.7	516.5	514.8	512.9	514.7
147.5°	516.2	515.1	514.2	512.9	511.7	510.0	508.5	506.9	505.4	503.9	505.7
150°	505.9	505.0	503.9	502.9	501.5	500.1	498.6	497.2	495.8	494.2	496.1
152.5°	495.1	493.9	493.1	492.0	490.7	489.1	488.0	486.6	485.2	483.8	485.3
155°	488.8	487.7	486.5	485.6	484.4	483.1	481.7	480.4	479.2	477.7	479.0
157.5°	484.9	484.0	483.2	482.1	481.4	480.3	479.3	478.2	477.2	476.2	477.1
160°	483.4	482.6	481.7	480.7	479.9	478.7	477.9	476.8	476.0	475.0	475.7
162.5°	482.2	481.3	480.4	479.5	478.6	477.5	476.6	475.8	474.9	473.9	474.8
165°	482.8	482.3	481.7	481.1	480.4	479.9	479.2	478.5	477.8	477.1	477.7
167.5°	487.4	486.6	486.0	485.1	484.3	483.5	482.7	481.8	481.2	480.3	480.9
170°	489.1	488.5	488.1	487.7	487.2	486.7	486.3	485.9	485.3	484.8	485.4
172.5°	491.8	491.3	491.0	490.8	490.3	490.1	489.7	489.3	489.1	488.6	489.4
175°	492.0	491.6	491.5	491.2	490.9	490.7	490.6	490.4	490.4	490.0	490.4
177.5°	495.2	495.1	495.1	495.1	495.1	494.9	494.8	494.5	494.4	494.4	494.8
180°	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
0°	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2
2.5°	33593.9	33589.8	33584.3	33577.2	33571.1	33564.1	33547.3	33542.3	33547.9	33551.6	33559.3
5°	33673.7	33676.1	33676.9	33692.2	33705.4	33738.3	33996.0	34098.4	34177.5	34227.8	34304.2
7.5°	33914.4	33991.9	34068.4	34171.4	34260.3	34380.3	34831.1	35023.0	35159.4	35257.4	35378.1
10°	34322.2	34491.3	34649.8	34835.5	34995.1	35177.9	35597.6	35784.4	35902.5	35988.4	36068.5
12.5°	34733.1	34967.5	35179.4	35386.1	35558.8	35717.3	35864.9	35930.3	35935.8	35938.6	35896.0
15°	34947.0	35171.2	35357.9	35494.5	35596.1	35640.9	35386.9	35253.6	35085.2	34946.5	34718.2
17.5°	34812.0	34946.5	35027.1	35019.1	34977.2	34836.7	34117.1	33721.2	33328.3	32974.2	32509.9
20°	34211.6	34201.3	34131.2	33932.6	33693.1	33320.8	32087.1	31375.3	30687.1	30082.6	29349.3
22.5°	33094.8	32918.9	32674.0	32245.5	31769.6	31119.1	29351.0	28304.1	27346.0	26499.7	25551.5
25°	31476.4	31114.8	30663.0	29982.8	29243.1	28294.3	26115.3	24812.9	23662.7	22665.0	21571.0
27.5°	29405.3	28860.7	28198.4	27257.0	26254.9	25039.4	22623.6	21186.3	19951.4	18881.8	17717.6
30°	26953.3	26245.0	25389.8	24221.4	23012.6	21634.1	19183.8	17728.1	16478.2	15377.9	14212.7
32.5°	24182.3	23352.7	22350.6	21039.2	19732.1	18314.6	15948.3	14539.2	13345.2	12286.6	11232.0
35°	21126.1	20236.5	19176.2	17838.7	16539.3	15161.3	12990.0	11719.4	10665.1	9729.4	8877.8
37.5°	17847.7	16974.2	15966.5	14705.9	13501.0	12252.2	10378.7	9314.1	8429.3	7652.6	6995.2
40°	14439.2	13674.7	12802.8	11713.0	10684.7	9644.7	8106.8	7261.7	6563.4	5971.1	5478.4
42.5°	11072.3	10479.9	9811.3	8950.1	8163.1	7371.3	6187.6	5561.4	5044.3	4618.0	4269.5
45°	8033.3	7637.1	7188.6	6589.8	6045.4	5493.0	4650.6	4210.6	3873.8	3598.8	3366.3
47.5°	5615.7	5385.8	5371.8	4818.5	4419.2	4081.5	3538.8	3260.9	3054.5	2887.9	2740.7
50°	3943.7	3832.5	3694.4	3496.9	3311.6	3120.7	2790.1	2622.0	2501.2	2400.2	2307.2
52.5°	2948.2	2890.5	2816.9	2712.1	2611.7	2504.4	2295.1	2188.2	2150.1	2056.2	1982.5
55°	2354.8	2321.7	2279.9	2218.3	2157.2	2132.8	1953.4	1874.0	1823.8	1786.7	1747.1
57.5°	1956.0	1931.3	1906.5	1864.8	1829.5	1786.7	1691.4	1650.8	1620.8	1599.0	1571.5
60°	1668.5	1653.7	1639.8	1615.4	1596.2	1573.2	1512.7	1489.7	1474.1	1461.0	1443.5
62.5°	1472.6	1465.0	1457.9	1444.8	1435.1	1422.6	1381.3	1370.2	1362.4	1355.8	1345.1
65°	1331.3	1325.8	1321.8	1313.2	1308.3	1301.0	1265.5	1258.0	1253.2	1250.8	1244.6
67.5°	1202.8	1197.1	1194.5	1188.3	1186.2	1181.7	1152.6	1148.6	1146.9	1147.7	1145.5
70°	1082.6	1080.3	1081.5	1080.6	1083.3	1084.1	1066.5	1066.3	1068.2	1072.0	1072.3
72.5°	1010.7	1010.7	1012.0	1012.7	1015.3	1016.5	1001.8	1001.2	1002.0	1004.7	1004.8
75°	942.1	943.3	947.0	948.2	951.3	952.0	932.6	930.3	930.5	933.1	932.2
77.5°	847.3	851.5	858.5	862.2	868.1	869.3	847.5	845.0	845.1	847.7	845.5
80°	739.7	747.6	758.8	766.7	775.9	779.5	757.2	751.9	746.9	746.2	741.7
82.5°	625.4	635.0	648.5	655.6	665.3	667.6	630.2	623.2	619.0	619.4	615.2
85°	477.4	484.7	496.9	501.0	507.0	506.5	463.9	445.6	450.4	442.9	448.8
87.5°	299.5	303.7	311.4	312.4	315.3	314.6	271.6	263.2	260.8	260.9	257.8
90°	179.8	184.8	193.7	195.9	202.4	203.9	171.3	169.5	164.6	164.4	158.3
92.5°	84.8	90.7	96.9	102.9	109.0	115.1	117.3	122.1	116.2	109.6	103.9
95°	100.0	109.9	119.7	129.6	139.5	149.3	159.2	169.1	159.9	150.5	141.3
97.5°	112.4	124.1	135.5	147.3	158.9	170.6	182.2	193.9	184.1	173.9	164.1
100°	147.6	169.4	191.0	212.8	234.4	256.1	277.9	299.7	280.5	261.3	242.2
102.5°	306.4	352.7	398.8	444.8	490.8	537.1	583.5	629.7	585.7	541.8	498.0
105°	593.4	668.2	743.1	817.6	892.3	967.2	1042.3	1117.0	1047.0	976.9	906.7
107.5°	940.5	1016.3	1092.0	1167.8	1243.7	1319.5	1395.9	1471.8	1403.4	1334.8	1266.4
110°	1156.1	1211.3	1266.6	1322.0	1377.2	1432.5	1488.6	1544.1	1502.9	1461.7	1420.7



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	27.5°	30°	32.5°	35°	37.5°	40°	42.5°	45°	47.5°	50°	52.5°
112.5°	1203.6	1243.3	1282.8	1322.3	1361.7	1401.3	1442.0	1481.7	1461.0	1440.2	1419.8
115°	1138.5	1165.5	1192.0	1218.6	1245.3	1271.8	1299.7	1326.8	1320.0	1313.5	1306.8
117.5°	1025.6	1040.6	1055.5	1070.4	1085.1	1100.0	1116.7	1131.7	1132.8	1134.0	1135.2
120°	905.3	911.7	917.9	924.3	930.2	936.6	944.9	951.5	957.1	962.5	968.0
122.5°	803.0	805.5	807.7	810.2	812.4	814.7	819.4	822.3	826.0	829.9	833.8
125°	720.7	721.9	723.0	724.3	725.1	726.2	730.3	731.8	732.0	732.1	732.4
127.5°	665.5	665.7	665.9	666.2	666.0	666.3	669.4	670.1	667.9	665.4	663.0
130°	625.5	626.0	626.5	627.1	627.7	628.3	631.9	633.3	629.1	624.8	620.6
132.5°	599.3	600.1	600.6	601.6	602.3	603.0	607.1	608.6	603.9	598.9	594.1
135°	577.3	578.4	579.3	580.2	581.0	582.3	586.8	588.6	584.1	579.4	574.8
137.5°	558.8	560.0	560.8	561.9	562.8	563.9	569.0	570.9	567.3	563.3	559.9
140°	543.1	544.2	545.4	546.8	547.9	549.4	554.9	557.2	554.3	551.3	548.3
142.5°	527.1	528.9	530.6	532.5	534.2	536.2	542.5	545.4	543.3	540.9	538.9
145°	516.5	518.7	520.6	522.9	524.9	527.2	534.3	537.6	536.3	534.8	533.4
147.5°	507.1	509.1	510.9	512.8	514.8	517.2	524.5	527.6	527.0	526.0	525.1
150°	497.7	499.6	501.5	503.5	505.7	508.0	516.1	519.8	519.0	518.3	517.4
152.5°	487.0	488.7	490.4	492.3	494.1	496.2	505.9	509.6	509.0	508.2	507.6
155°	480.3	481.7	482.9	484.4	485.8	487.6	497.7	501.2	500.9	500.5	500.0
157.5°	478.0	478.8	479.6	480.6	481.7	482.8	493.3	496.8	496.4	496.0	495.6
160°	476.3	477.1	477.6	478.5	479.2	480.0	490.8	494.0	493.7	493.3	492.9
162.5°	475.7	476.8	477.6	478.7	479.6	480.7	491.6	495.3	494.7	494.0	493.5
165°	478.3	478.8	479.2	479.9	480.4	481.2	491.2	494.2	493.9	493.5	493.1
167.5°	481.4	482.1	482.7	483.4	484.0	484.9	494.3	497.2	496.9	496.5	496.2
170°	485.8	486.4	486.8	487.5	488.1	488.9	496.6	499.1	498.8	498.0	497.6
172.5°	489.9	490.6	491.3	492.0	492.5	493.4	500.0	502.4	502.0	501.5	501.0
175°	490.9	491.3	491.9	492.6	493.1	493.6	498.9	500.6	500.4	500.2	499.9
177.5°	495.2	495.4	495.9	496.4	496.8	497.2	500.5	501.5	501.4	501.4	501.3
180°	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
0°	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2
2.5°	33561.1	33572.9	33574.5	33588.3	33587.2	33603.6	33601.0	33614.5	33606.6	33617.6	33608.4
5°	34349.3	34420.8	34458.1	34527.9	34549.9	34612.4	34630.0	34687.0	34689.3	34734.6	34724.3
7.5°	35463.7	35569.1	35631.7	35717.9	35761.6	35833.4	35865.1	35918.2	35935.3	35977.6	35980.8
10°	36129.2	36180.4	36216.1	36240.1	36262.2	36272.5	36284.4	36281.3	36284.4	36279.8	36290.1
12.5°	35867.4	35792.8	35743.3	35649.7	35595.5	35492.2	35441.4	35341.9	35305.9	35220.4	35208.2
15°	34541.8	34281.4	34097.4	33829.9	33661.7	33398.4	33244.5	33007.0	32898.5	32709.8	32660.2
17.5°	32125.6	31642.2	31268.2	30788.3	30455.3	30006.9	29724.9	29353.6	29150.4	28851.0	28747.4
20°	28738.0	28022.9	27461.8	26793.4	26315.1	25719.1	25337.6	24856.3	24577.0	24209.3	24060.3
22.5°	24761.1	23870.6	23169.9	22380.3	21803.1	21139.0	20681.9	20161.3	19857.3	19457.9	19281.0
25°	20661.9	19680.1	18901.0	18069.0	17459.2	16793.5	16336.3	15824.8	15510.3	15131.1	14955.3
27.5°	16741.5	15747.6	14994.6	14221.2	13661.8	13061.1	12648.6	12201.9	11922.8	11599.2	11433.8
30°	13281.8	12405.1	11764.5	11122.6	10657.2	10169.4	9826.5	9456.5	9211.6	8934.4	8776.9
32.5°	10463.1	9786.4	9284.7	8775.3	8394.5	7986.8	7690.6	7364.0	7143.0	6895.5	6752.8
35°	8286.7	7760.8	7360.7	6941.4	6614.2	6267.0	6005.9	5724.0	5525.7	5312.6	5189.5
37.5°	6547.3	6129.2	5799.9	5451.6	5182.9	4895.2	4798.3	4474.8	4269.3	4099.2	3981.5
40°	5138.3	4805.9	4533.4	4267.1	4047.9	3829.7	3654.6	3481.8	3349.1	3227.5	3143.3
42.5°	4012.7	3771.8	3572.8	3377.7	3217.8	3058.8	2932.0	2812.9	2723.6	2644.0	2589.8
45°	3189.9	3024.2	2885.9	2748.5	2635.7	2529.6	2444.2	2368.3	2310.5	2262.7	2228.9
47.5°	2620.5	2507.1	2409.6	2316.9	2240.2	2170.7	2113.6	2094.9	2032.8	1991.1	1975.1
50°	2227.1	2158.6	2084.6	2016.1	1965.0	1914.1	1877.0	1840.6	1817.4	1798.2	1792.3
52.5°	1933.5	1881.1	1839.9	1796.6	1762.8	1726.5	1701.0	1676.8	1664.0	1653.9	1652.7
55°	1715.1	1678.5	1651.2	1622.2	1602.0	1580.7	1567.5	1554.7	1549.0	1544.0	1544.4
57.5°	1550.0	1525.5	1507.7	1488.9	1477.9	1467.8	1464.5	1461.2	1463.0	1463.7	1466.5
60°	1429.5	1413.7	1402.5	1391.7	1387.1	1383.9	1386.3	1389.2	1395.0	1399.7	1404.0
62.5°	1337.3	1328.3	1322.8	1317.0	1316.5	1316.7	1321.7	1326.6	1333.9	1339.3	1343.4
65°	1242.4	1237.2	1235.4	1231.7	1233.6	1234.7	1240.7	1244.4	1251.7	1256.0	1261.3
67.5°	1146.4	1145.2	1146.3	1146.3	1149.7	1152.5	1158.2	1162.5	1168.6	1172.7	1176.9
70°	1075.6	1076.1	1078.7	1079.2	1082.7	1084.8	1089.8	1092.5	1098.0	1101.4	1106.4
72.5°	1006.7	1005.6	1006.2	1004.6	1005.8	1005.4	1008.1	1009.4	1014.2	1016.7	1023.0
75°	933.3	930.2	929.5	926.1	926.3	923.9	925.0	924.9	928.0	929.2	933.7
77.5°	844.7	839.5	837.0	831.4	831.3	829.2	831.4	832.8	838.3	840.9	845.9
80°	738.7	730.5	726.8	720.3	721.5	721.1	726.6	730.6	737.4	738.6	745.1
82.5°	614.0	605.7	601.7	595.4	596.9	597.0	601.9	602.9	608.7	611.1	618.6
85°	439.6	442.9	434.1	434.6	432.8	436.2	439.6	443.8	448.7	456.7	462.9
87.5°	258.9	257.8	260.9	261.2	265.7	268.1	275.3	279.4	287.5	293.8	305.2
90°	156.6	150.5	151.1	147.8	150.2	147.2	149.6	146.1	149.4	148.5	153.2
92.5°	97.0	91.0	84.4	78.4	71.8	66.1	62.7	60.1	56.9	54.5	51.0
95°	132.2	122.9	113.7	104.5	95.4	86.2	82.8	79.4	76.1	72.7	69.4
97.5°	154.3	144.3	134.5	124.5	114.6	104.7	102.5	100.2	98.0	95.7	93.5
100°	223.0	203.9	184.9	165.7	146.7	127.6	125.8	124.0	122.2	120.5	118.6
102.5°	454.2	410.4	366.6	322.8	279.0	235.2	227.6	219.9	212.4	204.7	197.1
105°	836.6	766.4	696.3	626.3	556.3	486.2	465.3	444.3	423.4	402.5	381.7
107.5°	1198.1	1129.7	1061.4	993.0	924.7	856.4	823.3	790.3	757.1	724.2	691.3
110°	1379.4	1338.3	1297.3	1256.2	1215.3	1174.3	1142.7	1111.3	1079.7	1048.2	1016.7



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77.5°	80°
112.5°	1399.2	1378.6	1357.9	1337.4	1317.0	1296.4	1281.0	1265.6	1250.3	1235.0	1219.4
115°	1300.2	1293.6	1287.0	1280.6	1274.2	1267.6	1266.4	1265.5	1264.2	1263.2	1262.1
117.5°	1136.2	1137.4	1138.5	1139.8	1141.1	1142.4	1150.6	1158.5	1166.9	1175.2	1183.5
120°	973.4	979.0	984.5	990.1	995.6	1001.3	1012.1	1023.2	1034.1	1045.4	1056.7
122.5°	837.4	841.4	845.0	848.9	852.9	856.8	867.5	878.4	889.2	900.3	911.6
125°	732.3	732.4	732.6	732.6	732.7	733.1	741.9	750.8	759.8	769.0	778.1
127.5°	660.6	657.9	655.5	653.2	650.5	648.4	653.4	658.7	663.9	669.4	674.8
130°	616.3	612.0	607.5	603.3	598.8	594.7	596.6	598.7	600.6	602.8	605.1
132.5°	589.0	584.1	579.1	574.0	569.0	564.1	563.9	563.7	563.5	563.6	563.8
135°	569.9	565.4	560.4	555.7	550.8	546.2	544.9	543.5	542.4	541.1	540.1
137.5°	556.0	552.2	548.3	544.7	540.7	536.9	535.0	533.4	531.5	530.3	528.5
140°	545.2	542.3	539.1	536.0	532.9	530.0	528.3	527.0	525.5	524.3	522.9
142.5°	536.5	534.2	531.9	529.7	527.3	525.1	523.5	522.2	520.8	519.6	518.3
145°	531.9	530.4	528.9	527.3	525.8	524.4	523.1	522.0	521.0	520.0	519.1
147.5°	524.2	523.2	522.3	521.4	520.2	519.2	518.4	517.9	516.9	516.4	515.7
150°	516.5	515.7	514.7	514.0	512.8	512.1	511.5	511.2	510.6	510.4	509.9
152.5°	506.6	505.8	505.0	504.2	503.2	502.5	502.0	501.8	501.3	501.1	500.6
155°	499.5	498.9	498.3	497.8	497.0	496.6	496.1	495.4	495.0	494.5	493.8
157.5°	495.1	494.6	494.0	493.6	492.9	492.4	491.9	491.4	490.7	490.4	489.8
160°	492.4	492.1	491.4	490.9	490.5	489.9	489.1	488.5	487.7	487.1	486.2
162.5°	492.6	492.0	491.3	490.6	489.7	489.1	488.6	488.0	487.6	487.1	486.4
165°	492.6	492.1	491.6	491.1	490.7	490.3	489.4	488.8	487.9	487.4	486.5
167.5°	495.7	495.3	494.9	494.5	493.8	493.4	492.8	492.1	491.3	490.6	489.7
170°	497.1	496.4	495.9	495.2	494.6	493.9	493.4	492.6	491.9	491.4	490.6
172.5°	500.5	500.1	499.5	499.1	498.3	497.9	497.5	496.8	496.3	495.6	495.1
175°	499.8	499.6	499.5	499.2	499.1	498.8	498.5	498.4	498.1	498.0	497.7
177.5°	501.3	501.1	501.1	501.0	500.8	500.8	500.5	500.2	499.9	499.5	499.3
180°	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
0°	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2
2.5°	33618.0	33609.5	33613.5	33597.8	33601.5	33582.5	33580.7	33559.3	33557.2	33537.0	33529.4
5°	34756.3	34737.6	34758.6	34725.8	34732.2	34689.3	34685.8	34630.4	34611.3	34542.1	34512.1
7.5°	36007.2	36000.2	36013.1	35985.5	35984.6	35946.4	35930.7	35881.0	35850.2	35777.5	35731.0
10°	36281.3	36287.7	36277.1	36279.8	36264.9	36260.7	36245.5	36235.8	36210.9	36192.0	36164.3
12.5°	35143.3	35150.1	35106.6	35134.2	35112.4	35163.2	35159.2	35218.9	35228.1	35303.9	35332.6
15°	32513.2	32504.9	32421.6	32474.2	32446.0	32557.5	32582.4	32732.4	32812.5	33005.0	33123.2
17.5°	28539.9	28518.5	28401.2	28465.1	28432.6	28597.0	28652.1	28891.8	29041.4	29351.6	29572.6
20°	23803.7	23762.6	23625.4	23700.2	23666.7	23853.4	23932.1	24221.9	24414.8	24825.6	25117.8
22.5°	19008.7	18943.8	18809.4	18879.3	18847.6	19040.9	19143.3	19434.2	19655.1	20076.9	20418.0
25°	14702.8	14645.0	14515.0	14563.9	14552.1	14715.7	14806.7	15081.9	15298.9	15700.6	16026.3
27.5°	11214.2	11154.0	11036.6	11071.1	11059.3	11198.6	11284.5	11514.3	11701.1	12039.2	12325.2
30°	8582.8	8510.2	8410.6	8429.7	8421.6	8534.5	8614.7	8808.2	8968.3	9254.1	9500.5
32.5°	6578.7	6505.7	6414.3	6423.2	6411.1	6499.7	6565.8	6734.1	6873.6	7116.6	7331.1
35°	5033.6	5118.8	4923.5	5047.3	4918.5	5107.6	5039.6	5144.7	5264.7	5469.5	5648.4
37.5°	3869.6	3810.2	3759.9	3754.6	3754.3	3798.2	3849.9	3951.2	4057.0	4209.5	4367.1
40°	3066.5	3024.8	2992.3	2989.9	2992.3	3023.4	3061.6	3131.7	3209.1	3318.7	3434.5
42.5°	2543.4	2515.7	2496.0	2494.7	2500.9	2523.0	2549.5	2591.1	2641.5	2712.5	2792.0
45°	2201.3	2185.9	2174.9	2174.4	2177.2	2188.8	2204.1	2229.9	2261.9	2306.2	2356.5
47.5°	1961.3	1957.5	1950.7	1951.0	1947.9	1952.6	1954.3	1968.9	1985.8	2019.3	2084.9
50°	1786.5	1786.5	1781.8	1781.5	1777.0	1776.8	1773.1	1778.8	1786.8	1807.5	1828.5
52.5°	1648.3	1647.9	1642.8	1641.8	1637.1	1636.8	1633.6	1635.9	1637.0	1647.4	1659.9
55°	1540.4	1537.1	1530.5	1528.3	1526.5	1529.2	1528.0	1528.1	1526.7	1531.1	1534.8
57.5°	1463.0	1458.7	1452.4	1450.5	1450.0	1453.3	1453.4	1452.3	1446.5	1442.4	1436.9
60°	1401.6	1397.4	1390.5	1388.9	1389.8	1394.3	1394.1	1390.4	1381.6	1374.1	1365.3
62.5°	1341.5	1339.7	1336.2	1335.7	1334.8	1335.6	1332.5	1328.5	1319.9	1311.9	1302.3
65°	1260.6	1261.5	1258.9	1259.3	1256.1	1255.7	1251.0	1247.1	1238.4	1231.1	1221.3
67.5°	1176.7	1177.3	1175.3	1175.3	1173.6	1173.9	1171.0	1167.4	1160.1	1154.1	1146.5
70°	1107.6	1109.3	1108.1	1108.5	1106.4	1105.8	1101.3	1097.8	1090.2	1085.3	1078.4
72.5°	1024.9	1028.5	1028.4	1029.3	1026.4	1024.9	1019.5	1015.1	1008.3	1004.3	998.9
75°	935.5	940.3	941.7	943.7	939.5	937.3	931.5	928.0	922.4	920.0	916.5
77.5°	848.2	853.5	858.6	863.4	856.5	850.4	843.1	837.5	829.5	826.5	820.9
80°	750.3	759.7	771.0	780.5	768.1	755.7	743.7	734.8	724.2	719.9	712.9
82.5°	622.4	632.1	638.6	644.6	636.1	627.0	615.3	607.5	596.1	591.9	583.9
85°	472.9	484.9	488.8	492.0	486.5	481.7	470.8	456.0	448.8	437.5	431.6
87.5°	311.0	318.2	319.6	320.7	317.4	315.0	307.9	301.0	288.7	279.8	268.8
90°	150.9	153.7	149.0	148.8	146.4	148.7	143.4	142.8	134.6	132.6	125.5
92.5°	48.3	45.1	42.2	39.2	42.8	45.1	48.6	51.0	54.3	56.9	60.1
95°	66.0	62.7	59.3	55.9	58.6	61.3	64.0	66.7	69.3	72.0	74.7
97.5°	91.2	89.0	86.7	84.5	86.1	87.7	89.2	90.8	92.4	94.0	95.6
100°	116.8	115.0	113.2	111.5	111.5	111.5	111.5	111.5	111.5	111.5	111.5
102.5°	189.4	181.8	174.1	166.5	171.7	176.9	182.0	187.2	192.4	197.6	202.8
105°	360.8	339.9	319.1	298.2	318.4	338.6	358.8	379.0	399.1	419.6	439.7
107.5°	658.1	625.2	592.2	559.2	596.2	632.9	669.7	706.6	743.3	780.1	817.1
110°	985.3	953.9	922.6	891.2	930.2	969.2	1008.3	1047.2	1086.4	1125.4	1164.7



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	82.5°	85°	87.5°	90°	92.5°	95°	97.5°	100°	102.5°	105°	107.5°
112.5°	1204.1	1189.0	1173.7	1158.4	1183.5	1208.6	1233.7	1259.1	1284.3	1309.5	1334.6
115°	1261.2	1260.2	1259.4	1258.5	1270.4	1282.3	1294.2	1306.1	1318.1	1330.0	1342.1
117.5°	1191.9	1200.2	1208.7	1217.3	1221.1	1224.9	1228.9	1232.7	1236.7	1240.7	1244.7
120°	1067.9	1079.0	1090.4	1101.9	1100.3	1098.7	1097.4	1095.8	1094.5	1093.0	1092.0
122.5°	922.8	933.9	945.3	956.7	953.3	949.9	946.6	943.5	940.5	937.3	934.3
125°	787.6	796.9	806.4	816.0	812.6	809.2	805.9	802.9	799.9	796.7	794.0
127.5°	680.6	686.5	692.1	698.0	696.4	694.9	693.7	692.3	691.0	690.0	689.0
130°	607.5	610.0	612.8	615.3	615.8	616.3	617.0	617.8	618.7	619.5	620.7
132.5°	564.3	564.6	565.2	565.8	567.6	569.3	571.6	573.6	576.0	578.1	581.0
135°	539.4	538.6	538.0	537.6	540.3	542.9	545.7	548.7	552.0	555.4	558.7
137.5°	527.4	526.1	525.1	524.0	526.7	529.3	532.3	535.2	538.4	541.7	545.4
140°	521.8	520.8	520.2	519.1	521.8	524.5	527.4	530.3	533.5	536.8	540.2
142.5°	517.3	516.2	515.5	514.7	517.0	519.5	522.3	524.8	527.8	530.6	533.8
145°	518.3	517.4	517.0	516.4	518.0	519.8	521.8	523.8	526.0	528.0	530.6
147.5°	515.2	514.6	514.4	514.1	515.4	516.6	518.1	519.4	521.2	522.7	524.6
150°	509.9	509.5	509.4	509.3	510.1	510.9	511.9	512.7	513.8	514.8	516.2
152.5°	500.6	500.2	500.3	500.1	500.9	501.5	502.5	503.2	504.2	505.1	506.4
155°	493.6	493.2	492.8	492.4	492.7	492.9	493.3	493.5	494.1	494.4	495.0
157.5°	489.5	489.1	488.8	488.3	488.2	488.1	488.2	488.2	488.4	488.3	488.5
160°	485.8	484.9	484.3	483.7	484.0	483.9	484.2	484.2	484.5	484.7	484.9
162.5°	486.1	485.6	485.2	484.7	484.5	484.0	483.7	483.2	483.0	482.7	482.6
165°	485.8	485.1	484.5	483.7	483.6	483.5	483.3	483.2	483.2	483.0	483.1
167.5°	489.2	488.4	487.7	487.1	486.6	485.9	485.6	485.0	484.5	484.0	483.8
170°	490.0	489.3	488.8	488.2	488.0	487.7	487.6	487.2	487.0	486.9	486.9
172.5°	494.6	494.0	493.6	493.1	492.9	492.6	492.5	492.3	492.1	492.1	492.0
175°	497.6	497.3	497.2	496.9	496.6	496.4	496.1	495.9	495.6	495.2	495.1
177.5°	498.9	498.5	498.2	498.0	498.0	498.0	498.0	498.0	498.0	497.9	497.7
180°	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
0°	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2
2.5°	33507.7	33498.9	33475.6	33464.2	33442.8	33432.0	33415.2	33404.4	33390.9	33380.8	33375.6
5°	34436.0	34393.2	34307.3	34254.5	34161.8	34100.7	34008.6	33941.1	33846.0	33775.8	33686.0
7.5°	35643.9	35578.2	35468.2	35384.7	35255.1	35155.9	35010.3	34893.9	34733.1	34599.5	34435.2
10°	36135.7	36097.3	36047.9	35994.3	35922.4	35852.0	35752.5	35651.2	35516.3	35381.9	35206.4
12.5°	35408.9	35445.0	35516.3	35549.5	35603.9	35622.5	35647.4	35635.8	35613.7	35558.8	35479.3
15°	33350.4	33501.2	33739.5	33904.4	34135.4	34297.5	34512.1	34650.3	34809.4	34904.5	34994.8
17.5°	29964.3	30256.0	30676.5	31012.0	31462.4	31828.5	32277.2	32629.7	33036.7	33348.9	33681.3
20°	25627.2	26035.7	26616.2	27109.2	27761.8	28315.2	29024.1	29618.1	30310.9	30888.3	31511.6
22.5°	20959.4	21439.9	22105.0	22699.6	23479.0	24175.0	25063.2	25848.6	26785.1	27624.1	28552.3
25°	16555.8	17026.7	17704.3	18320.0	19161.2	19928.0	20898.4	21799.3	22886.1	23899.7	25063.2
27.5°	12779.5	13197.8	13793.4	14347.6	15118.1	15870.8	16855.7	17816.3	18976.0	20065.2	21319.2
30°	9869.4	10208.7	10685.9	11131.8	11750.4	12366.0	13243.2	14131.6	15285.6	16414.3	17699.9
32.5°	7648.4	7937.8	8336.1	8698.1	9174.7	9638.9	10284.9	10994.8	12007.1	13088.3	14331.3
35°	5920.7	6168.2	6507.3	6819.1	7211.1	7579.6	8061.6	8568.4	9340.9	10250.3	11362.7
37.5°	4720.4	4821.2	5063.3	5318.7	5644.2	5947.1	6324.2	6698.9	7251.5	7969.1	8877.8
40°	3589.7	3750.0	3947.0	4148.1	4394.7	4637.6	5051.2	5250.4	5614.4	6129.4	6834.8
42.5°	2896.5	3009.2	3147.8	3287.7	3459.5	3628.6	3837.9	4051.0	4323.0	4671.9	5173.6
45°	2423.8	2497.4	2586.7	2679.9	2792.7	2908.1	3048.2	3194.6	3378.9	3593.4	3898.1
47.5°	2108.1	2148.7	2207.0	2270.7	2348.0	2427.9	2519.0	2612.2	2726.8	2854.1	3027.5
50°	1861.6	1895.5	1940.8	1983.4	2036.7	2118.6	2154.8	2206.2	2275.2	2350.0	2447.1
52.5°	1683.3	1705.8	1734.2	1758.7	1792.5	1823.1	1863.3	1898.8	1946.5	1991.4	2054.1
55°	1544.4	1552.6	1568.7	1584.4	1607.8	1628.7	1656.3	1679.5	1710.0	1736.8	1776.4
57.5°	1437.1	1437.8	1445.3	1453.5	1468.6	1481.7	1500.7	1516.0	1537.0	1554.2	1577.9
60°	1360.0	1356.0	1357.5	1360.3	1368.7	1377.3	1389.4	1399.3	1412.7	1422.4	1435.6
62.5°	1295.8	1289.5	1288.0	1287.2	1291.4	1294.5	1301.1	1306.0	1313.5	1317.8	1324.8
65°	1214.8	1207.2	1204.3	1200.8	1202.1	1201.0	1203.6	1203.7	1207.5	1208.4	1212.5
67.5°	1141.4	1135.0	1131.2	1126.5	1124.3	1121.0	1119.6	1116.3	1115.8	1113.1	1112.4
70°	1074.3	1068.1	1064.9	1060.5	1058.3	1053.9	1051.2	1045.6	1042.5	1037.3	1034.5
72.5°	996.8	993.3	992.3	989.4	988.6	986.1	984.9	981.1	978.9	974.6	972.0
75°	915.7	912.8	912.6	909.6	909.4	906.5	905.7	901.6	899.4	895.1	893.2
77.5°	819.2	814.9	813.7	810.3	811.1	809.6	810.8	807.7	806.4	802.0	800.7
80°	710.4	705.0	702.7	698.1	699.3	697.3	699.3	699.2	700.8	697.3	696.6
82.5°	581.6	575.6	574.5	571.3	573.5	573.6	578.2	575.8	576.7	573.5	574.9
85°	423.2	418.8	412.5	411.7	407.7	411.8	406.4	410.1	404.3	408.3	402.9
87.5°	262.4	253.2	248.3	241.8	239.3	233.0	230.3	225.7	227.2	225.0	226.2
90°	125.2	119.1	120.2	116.6	118.9	116.1	119.6	118.4	122.5	121.3	125.7
92.5°	62.7	65.6	70.9	76.6	81.8	87.1	92.5	98.2	103.3	108.9	114.1
95°	77.4	80.1	87.3	94.4	101.6	108.8	116.2	123.4	130.6	137.7	144.9
97.5°	97.2	98.8	106.0	113.2	120.4	127.6	134.7	142.1	149.3	156.4	163.6
100°	111.5	111.6	132.0	152.4	172.7	193.3	213.8	234.2	254.7	275.1	295.5
102.5°	207.9	213.1	264.7	316.3	367.9	419.6	471.3	523.0	574.6	626.3	678.1
105°	459.9	480.3	558.9	637.8	716.5	795.4	874.2	953.2	1032.1	1110.9	1189.7
107.5°	853.8	890.8	962.0	1033.2	1104.3	1175.7	1246.9	1318.1	1389.3	1460.7	1532.2
110°	1203.7	1242.8	1290.5	1338.3	1386.1	1433.7	1481.6	1529.3	1577.2	1625.0	1673.1



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	132.5°	135°
112.5°	1359.8	1385.2	1412.9	1440.8	1468.8	1496.7	1524.6	1552.5	1580.6	1608.6	1636.6
115°	1354.3	1366.5	1377.1	1388.1	1399.0	1409.9	1420.9	1432.0	1443.2	1454.2	1465.4
117.5°	1248.6	1253.0	1254.5	1256.5	1258.2	1260.2	1262.1	1264.2	1266.2	1268.4	1270.2
120°	1090.7	1089.5	1087.7	1086.1	1084.3	1082.8	1081.3	1079.8	1078.4	1077.1	1075.6
122.5°	931.3	928.6	926.8	925.3	923.8	922.4	921.2	919.9	918.6	917.3	916.0
125°	791.1	788.4	790.1	791.8	793.7	795.5	797.3	799.5	801.4	803.3	805.4
127.5°	688.0	687.3	691.5	695.9	700.2	704.7	709.1	713.8	718.1	722.9	727.2
130°	621.9	623.2	628.5	634.3	639.8	645.5	651.2	657.0	662.5	668.2	673.9
132.5°	583.4	586.3	591.4	597.0	602.3	607.8	613.3	618.9	624.3	629.9	635.2
135°	562.3	566.1	570.9	575.9	580.9	586.0	590.9	596.1	600.9	606.1	610.9
137.5°	548.7	552.4	556.4	560.4	564.4	568.6	572.7	576.8	580.8	584.9	588.8
140°	543.7	547.4	549.6	552.2	554.5	557.0	559.2	561.7	564.0	566.6	568.8
142.5°	537.0	540.5	541.7	543.4	545.0	546.9	548.4	550.0	551.5	553.0	554.4
145°	532.9	535.5	535.7	536.1	536.5	536.8	537.0	537.4	537.6	537.9	538.0
147.5°	526.4	528.4	528.1	528.1	528.0	527.8	527.8	527.8	527.5	527.4	527.3
150°	517.3	518.7	518.0	517.8	517.2	516.8	516.1	515.8	515.1	514.7	514.1
152.5°	507.4	508.5	507.6	507.3	506.5	505.9	505.1	504.6	503.8	503.2	502.6
155°	495.2	495.9	495.4	495.1	494.7	494.3	493.8	493.7	493.6	493.2	493.0
157.5°	488.7	488.8	488.6	488.3	487.9	487.8	487.7	487.5	487.4	487.5	487.6
160°	485.0	485.4	485.1	484.8	484.7	484.4	484.2	484.1	484.1	484.3	484.4
162.5°	482.2	482.1	481.7	481.5	481.3	481.3	481.1	481.3	481.2	481.3	481.5
165°	483.2	483.4	482.7	482.5	482.1	481.7	481.4	481.2	481.2	481.1	481.0
167.5°	483.4	483.2	483.2	483.3	483.3	483.5	483.6	484.1	484.3	484.7	484.8
170°	486.8	486.9	486.6	486.4	486.2	486.2	486.1	486.0	486.1	486.0	486.0
172.5°	492.0	492.0	491.5	491.0	490.6	490.4	489.9	489.6	489.2	489.0	488.5
175°	494.7	494.5	494.3	494.0	493.8	493.5	493.3	492.7	492.5	492.2	492.1
177.5°	497.6	497.3	497.2	497.2	497.1	496.9	496.9	496.8	496.8	496.8	496.5
180°	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
0°	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2
2.5°	33368.9	33368.6	33365.3	33366.8	33367.4	33369.8	33372.6	33375.6	33376.2	33378.6	33379.1
5°	33618.7	33536.1	33475.1	33407.9	33357.3	33311.9	33281.6	33257.6	33248.3	33250.6	33256.3
7.5°	34295.8	34125.4	33984.7	33824.9	33691.6	33550.5	33433.5	33322.2	33241.2	33180.8	33147.0
10°	35038.9	34831.3	34632.7	34401.4	34182.0	33947.7	33735.7	33522.1	33343.9	33189.3	33075.8
12.5°	35368.6	35221.9	35050.3	34832.0	34597.2	34326.9	34054.1	33761.5	33489.4	33236.9	33033.1
15°	35019.5	35019.8	34957.2	34852.4	34689.3	34473.4	34213.4	33908.4	33587.5	33259.9	32960.7
17.5°	33911.2	34120.3	34236.6	34310.2	34287.6	34208.0	34042.6	33808.4	33509.2	33160.2	32795.1
20°	32007.9	32501.1	32852.7	33169.0	33346.2	33464.0	33452.2	33356.9	33143.8	32847.1	32466.8
22.5°	29341.7	30169.5	30822.7	31431.8	31859.1	32206.6	32371.8	32441.9	32345.3	32138.7	31781.6
25°	26103.3	27228.8	28189.3	29121.5	29820.9	30421.8	30783.0	31037.4	31057.6	30949.7	30631.0
27.5°	22504.8	23833.4	25049.1	26288.0	27271.4	28135.4	28702.2	29117.1	29248.9	29231.5	28942.2
30°	18910.9	20305.7	21645.7	23090.4	24307.3	25411.0	26159.8	26720.9	26937.1	26978.6	26700.3
32.5°	15516.9	16892.3	18228.6	19739.0	21078.1	22343.0	23227.8	23894.2	24145.6	24204.9	23899.7
35°	12436.6	13705.5	14975.4	16439.2	17770.7	19080.6	20012.8	20710.5	20945.4	20985.0	20631.6
37.5°	9765.4	10846.5	11953.2	13266.5	14489.2	15719.4	16605.0	17260.9	17432.0	17421.4	17021.5
40°	7516.2	8356.8	9246.0	10327.2	11343.7	12383.7	13131.6	13673.7	13763.6	13697.0	13276.9
42.5°	5651.8	6258.9	6903.5	7710.6	8464.9	9243.2	9787.3	10189.8	10202.6	10097.3	9720.3
45°	4210.6	4802.9	5073.2	5561.2	6047.0	6564.5	6896.8	7145.4	7106.9	7014.4	6727.8
47.5°	3209.8	3437.4	3678.9	3981.5	4264.5	4851.8	4808.2	5207.4	4919.9	5116.0	4684.4
50°	2549.0	2676.2	2806.2	2966.8	3114.7	3268.2	3364.1	3435.8	3426.5	3395.7	3313.0
52.5°	2168.6	2207.9	2271.9	2363.3	2445.8	2528.8	2583.4	2627.8	2628.8	2616.3	2574.5
55°	1812.4	1862.4	1908.4	1968.1	2069.8	2085.4	2163.7	2147.8	2154.1	2132.3	2154.5
57.5°	1598.0	1627.1	1652.9	1688.4	1717.8	1752.1	1772.3	1791.8	1790.0	1785.7	1764.4
60°	1446.1	1462.1	1476.4	1497.2	1513.3	1532.7	1542.0	1551.9	1548.7	1541.5	1522.5
62.5°	1328.9	1338.9	1347.2	1360.6	1370.3	1382.4	1387.3	1391.5	1387.3	1380.4	1363.7
65°	1213.3	1219.8	1225.0	1235.1	1242.0	1252.3	1256.4	1260.3	1256.5	1251.2	1238.4
67.5°	1109.1	1109.7	1109.3	1113.3	1115.4	1121.6	1123.5	1126.3	1121.9	1117.3	1106.4
70°	1030.0	1028.4	1026.4	1028.0	1028.4	1031.4	1031.9	1031.4	1026.1	1018.1	1006.3
72.5°	968.2	967.3	965.8	967.2	967.2	970.0	969.1	967.7	961.2	953.5	941.8
75°	888.7	888.2	885.2	885.3	882.8	883.7	880.5	878.6	871.3	864.9	854.4
77.5°	795.8	794.3	790.0	788.3	783.7	781.7	775.6	772.6	765.2	760.0	751.1
80°	692.0	690.4	684.8	681.7	674.3	669.6	660.7	655.6	647.0	641.9	633.2
82.5°	572.0	572.7	567.1	563.2	552.6	544.3	532.4	526.0	516.6	511.6	502.6
85°	406.8	401.0	404.1	403.9	397.2	390.1	380.4	373.6	365.6	360.9	354.6
87.5°	223.1	224.5	222.9	221.5	216.8	213.2	205.7	201.7	195.9	193.0	188.3
90°	116.9	113.7	105.2	102.2	93.8	88.7	79.3	75.2	66.4	64.4	59.0
92.5°	108.0	102.0	96.2	89.8	84.1	78.0	71.9	65.9	59.9	57.5	55.8
95°	136.2	127.5	118.8	110.0	101.3	92.5	83.8	75.0	66.3	64.5	62.8
97.5°	153.5	143.2	132.9	122.7	112.3	102.0	91.8	81.5	71.2	70.1	68.9
100°	271.9	248.2	224.5	200.7	177.0	153.2	129.7	105.9	82.2	80.9	79.5
102.5°	620.5	562.9	505.4	447.9	390.4	332.8	275.4	217.7	160.2	151.8	143.6
105°	1102.7	1015.5	928.7	841.4	754.4	667.2	580.3	493.0	405.9	378.0	350.0
107.5°	1450.4	1368.4	1286.7	1204.9	1122.9	1041.2	959.2	877.3	795.4	746.1	696.9
110°	1608.0	1543.1	1478.3	1413.2	1348.4	1283.4	1218.4	1153.4	1088.4	1045.8	1003.6



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	137.5°	140°	142.5°	145°	147.5°	150°	152.5°	155°	157.5°	160°	162.5°
112.5°	1589.1	1541.4	1494.1	1446.5	1398.9	1351.2	1303.7	1255.9	1208.2	1182.5	1156.7
115°	1436.9	1408.2	1379.7	1351.0	1322.3	1293.7	1265.0	1236.1	1207.3	1193.8	1180.3
117.5°	1255.8	1241.1	1226.7	1212.1	1197.4	1182.6	1168.1	1153.3	1138.6	1133.9	1129.1
120°	1071.5	1067.1	1062.6	1058.2	1053.8	1049.4	1044.9	1040.3	1035.6	1036.3	1036.9
122.5°	917.9	919.6	921.5	923.0	924.9	926.4	928.4	929.7	931.4	935.0	938.7
125°	809.8	814.0	818.4	822.6	826.7	831.0	835.4	839.4	843.7	847.3	851.2
127.5°	732.3	736.9	741.9	746.6	751.4	756.1	761.0	765.5	770.3	773.6	777.3
130°	678.3	682.3	686.7	690.6	694.9	699.1	703.2	707.3	711.4	714.1	716.9
132.5°	639.0	642.9	646.6	650.2	654.1	657.8	661.4	665.2	669.1	671.1	673.1
135°	613.9	616.5	619.4	622.1	625.3	627.9	630.8	633.7	636.7	638.0	639.5
137.5°	591.1	593.4	595.8	598.1	600.5	602.8	605.3	607.7	610.4	610.9	612.0
140°	571.2	573.7	576.1	578.5	581.1	583.6	586.3	588.9	591.7	592.4	593.3
142.5°	556.5	558.2	560.2	562.0	564.1	566.0	568.2	570.5	572.7	573.5	574.2
145°	540.3	542.4	544.8	546.9	549.2	551.7	554.4	556.9	559.6	560.1	560.6
147.5°	529.1	530.9	533.0	535.0	537.1	539.0	541.4	543.8	546.1	546.6	547.0
150°	516.2	518.2	520.2	522.3	524.7	527.0	529.3	531.8	534.6	535.4	536.2
152.5°	504.8	506.9	509.2	511.6	514.1	516.6	519.3	521.9	524.7	525.4	526.2
155°	495.2	497.3	499.6	502.1	504.7	506.9	509.6	512.1	514.8	515.8	516.6
157.5°	489.6	491.5	493.6	495.8	498.0	500.2	502.6	504.8	507.3	508.1	508.7
160°	486.2	487.9	489.9	491.8	493.8	495.7	497.8	499.8	501.9	502.6	503.4
162.5°	483.3	485.2	487.2	488.8	490.9	492.9	495.0	496.8	498.9	499.5	500.3
165°	482.4	483.8	485.3	486.5	488.1	489.3	491.0	492.3	494.0	494.6	495.6
167.5°	486.2	487.0	488.0	489.1	490.5	491.5	492.8	493.8	495.1	495.8	496.5
170°	486.9	487.8	488.8	489.8	490.9	492.0	493.0	493.8	495.1	495.7	496.5
172.5°	489.1	489.6	490.4	490.9	491.7	492.2	493.0	493.7	494.5	495.3	496.0
175°	492.5	492.8	493.1	493.4	493.6	494.1	494.5	495.1	495.3	496.0	496.5
177.5°	496.7	497.0	497.2	497.4	498.0	498.1	498.4	498.7	499.1	499.7	500.5
180°	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
0°	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2
2.5°	33377.9	33377.6	33376.4	33375.0	33373.5	33374.4	33375.9	33379.7	33386.4	33396.1	33408.8
5°	33260.8	33267.6	33271.5	33272.0	33268.5	33266.4	33269.7	33278.8	33297.3	33328.3	33370.3
7.5°	33137.9	33146.4	33159.3	33169.0	33170.8	33168.5	33169.0	33183.4	33217.5	33277.9	33362.7
10°	33006.7	32981.8	32994.9	33019.0	33038.1	33041.7	33044.0	33061.0	33110.9	33202.2	33338.4
12.5°	32885.6	32806.6	32791.4	32813.1	32842.1	32851.5	32848.9	32856.2	32914.6	33035.6	33225.3
15°	32726.3	32577.7	32526.9	32532.5	32568.3	32581.3	32571.8	32557.5	32614.4	32762.0	33007.7
17.5°	32468.3	32228.8	32135.5	32131.4	32173.3	32184.5	32161.4	32116.7	32172.9	32357.0	32661.9
20°	32076.3	31722.7	31546.9	31518.9	31564.6	31551.3	31505.2	31437.6	31511.4	31735.3	32098.0
22.5°	31371.4	30923.4	30623.1	30526.3	30580.8	30544.4	30477.3	30391.1	30488.9	30743.3	31147.3
25°	30219.6	29701.9	29290.9	29060.3	29103.7	29038.5	28965.5	28860.9	28977.7	29269.8	29714.4
27.5°	28526.7	27928.7	27419.3	27037.5	27051.6	26966.2	26882.0	26746.8	26892.6	27238.3	27739.7
30°	26275.5	25583.6	24963.2	24444.4	24398.0	24315.2	24229.0	24051.5	24234.0	24647.7	25233.7
32.5°	23448.4	22680.2	21963.4	21307.4	21183.7	21102.9	21026.0	20821.7	21060.7	21543.1	22216.3
35°	20142.2	19323.8	18546.7	17797.6	17592.5	17511.8	17444.6	17248.8	17547.0	18072.0	18799.1
37.5°	16513.2	15677.2	14905.7	14137.5	13847.7	13738.1	13689.3	13561.2	13905.1	14424.4	15154.5
40°	12787.7	12010.4	11318.6	10640.1	10309.9	10142.2	10116.6	10093.2	10425.8	10876.3	11538.9
42.5°	9302.5	8675.4	8142.1	7623.4	7324.1	7095.2	7095.0	7164.5	7463.9	7801.4	8312.4
45°	6434.8	6014.0	5674.1	5327.6	5420.3	4963.7	5231.9	5094.3	5242.2	5459.8	5792.0
47.5°	4423.3	4193.6	4007.0	3813.3	3672.2	3537.4	3549.2	3636.1	3775.4	3904.5	4077.4
50°	3223.9	3106.9	3011.8	2911.2	2840.9	2781.6	2785.0	2822.6	2895.8	2963.8	3054.3
52.5°	2526.1	2461.6	2410.0	2354.3	2317.5	2287.9	2289.5	2307.8	2347.4	2386.3	2438.2
55°	2082.1	2074.3	2007.2	1957.3	1938.3	1918.5	1922.0	1929.2	1956.1	1978.9	2013.3
57.5°	1744.8	1714.6	1694.5	1668.2	1656.2	1642.3	1645.4	1648.1	1666.1	1681.4	1706.1
60°	1506.6	1485.2	1471.0	1453.1	1445.2	1436.3	1438.4	1440.0	1451.5	1461.5	1479.2
62.5°	1348.4	1329.3	1316.8	1303.1	1297.5	1291.5	1292.9	1293.4	1300.6	1307.9	1321.3
65°	1227.0	1211.8	1201.5	1189.6	1183.8	1177.6	1178.2	1178.2	1184.3	1189.6	1199.7
67.5°	1098.7	1087.2	1080.6	1071.1	1067.1	1060.8	1060.7	1058.7	1062.7	1064.8	1071.6
70°	995.6	984.1	975.6	966.5	961.5	955.9	956.1	956.2	960.8	965.7	974.5
72.5°	932.0	921.0	913.4	905.4	900.7	896.0	895.1	894.7	897.9	900.6	906.5
75°	847.7	838.9	834.4	827.0	823.3	817.9	817.1	814.6	816.2	816.7	821.0
77.5°	745.4	737.1	733.5	725.9	722.9	716.8	716.3	713.5	714.8	713.9	717.2
80°	628.9	621.3	619.4	613.2	611.7	606.1	605.2	601.8	602.9	600.2	601.5
82.5°	498.8	491.9	490.4	484.7	484.7	479.6	479.3	474.3	474.3	469.9	462.9
85°	351.4	346.3	344.1	339.5	338.1	334.0	331.9	327.0	325.3	322.2	321.2
87.5°	185.5	182.2	179.4	177.1	173.0	165.7	165.0	160.0	160.4	156.7	157.0
90°	57.5	52.5	51.1	46.6	45.0	41.5	40.0	40.7	42.1	42.8	44.3
92.5°	53.8	51.8	49.7	47.8	45.7	43.7	41.7	43.7	45.7	47.8	49.7
95°	61.0	59.2	57.3	55.5	53.8	52.0	50.2	52.0	53.8	55.7	57.5
97.5°	67.8	66.7	65.6	64.4	63.3	62.2	61.1	62.4	63.5	64.6	65.8
100°	78.2	76.9	75.5	74.2	72.9	71.5	70.2	71.7	73.1	74.4	75.7
102.5°	135.4	127.1	118.8	110.5	102.2	94.0	85.6	94.0	102.2	110.7	119.0
105°	321.9	294.0	266.0	238.0	209.9	181.9	153.9	182.0	210.0	238.1	266.2
107.5°	647.6	598.5	549.1	499.8	450.5	401.2	351.8	401.4	450.7	500.0	549.4
110°	961.0	918.5	876.1	833.6	791.0	748.5	705.9	748.6	791.2	833.9	876.5



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	165°	167.5°	170°	172.5°	175°	177.5°	180°	182.5°	185°	187.5°	190°
112.5°	1130.9	1105.1	1079.2	1053.4	1027.5	1001.6	975.6	1001.9	1027.9	1054.0	1079.9
115°	1166.8	1153.0	1139.5	1125.8	1112.1	1098.4	1084.5	1098.8	1112.7	1126.6	1140.5
117.5°	1124.3	1119.6	1114.8	1110.0	1105.1	1100.4	1095.3	1100.5	1105.7	1111.1	1116.0
120°	1037.3	1038.1	1038.5	1038.9	1039.4	1039.7	1040.0	1040.2	1040.2	1040.2	1040.1
122.5°	942.1	945.8	949.4	952.8	956.2	959.7	962.7	960.1	957.2	954.4	951.3
125°	854.7	858.6	862.2	865.8	869.3	872.9	875.9	873.5	870.6	867.7	864.6
127.5°	780.6	783.8	787.1	790.6	793.5	796.7	799.5	797.4	794.9	792.5	789.7
130°	719.2	722.1	724.5	727.0	729.1	731.4	733.3	732.0	730.4	729.2	727.3
132.5°	675.1	677.1	679.1	680.9	682.5	684.2	685.4	684.9	684.1	683.2	682.0
135°	640.9	642.3	643.5	645.0	646.0	647.0	647.5	647.8	647.5	647.4	646.7
137.5°	612.6	613.5	614.1	614.7	615.0	615.3	615.3	616.2	616.6	617.4	617.5
140°	594.1	594.9	595.6	596.1	596.7	597.2	597.0	598.0	598.5	598.8	598.9
142.5°	575.1	575.9	576.5	577.2	577.6	577.9	577.9	578.8	579.3	579.6	579.8
145°	561.3	561.7	562.0	562.5	562.6	562.7	562.4	563.5	564.2	564.8	565.4
147.5°	547.5	548.1	548.3	548.5	548.6	548.7	548.6	549.5	550.3	551.0	551.4
150°	537.1	537.9	538.4	539.2	539.7	540.0	540.1	540.8	541.2	541.5	541.6
152.5°	526.9	527.6	528.2	528.7	529.2	529.5	529.7	530.3	530.9	531.3	531.5
155°	517.3	518.3	519.0	519.8	520.2	520.8	521.4	521.8	522.2	522.5	522.7
157.5°	509.5	510.4	511.0	511.7	512.3	513.0	513.5	514.1	514.4	515.0	515.2
160°	503.9	504.9	505.4	506.1	506.8	507.3	507.9	508.4	508.9	509.3	509.9
162.5°	500.9	501.6	502.0	502.7	503.4	504.0	504.5	505.2	505.6	506.1	506.5
165°	496.4	497.3	498.0	498.9	499.7	500.6	501.1	501.6	501.7	502.0	502.1
167.5°	497.2	498.1	498.7	499.5	500.1	501.0	501.7	502.1	502.2	502.4	502.4
170°	497.0	497.9	498.5	499.2	499.8	500.6	501.0	501.2	501.3	501.5	501.6
172.5°	496.6	497.6	498.3	499.3	499.9	500.8	501.5	501.5	501.2	501.1	500.8
175°	497.0	497.9	498.4	499.2	499.6	500.4	501.1	500.8	500.7	500.4	500.2
177.5°	501.3	502.3	503.0	503.7	504.6	505.3	506.0	505.4	504.8	504.2	503.6
180°	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
0°	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2
2.5°	33426.6	33443.4	33469.0	33492.1	33527.1	33554.6	33595.9	33627.3	33674.0	33704.3	33755.1
5°	33429.6	33495.0	33581.0	33664.9	33765.8	33857.4	33971.2	34068.2	34182.6	34276.0	34393.0
7.5°	33476.9	33603.0	33754.1	33906.4	34078.7	34239.8	34421.4	34585.7	34765.3	34917.3	35083.4
10°	33511.8	33706.3	33929.0	34153.2	34389.1	34608.3	34829.6	35020.9	35199.6	35346.7	35476.6
12.5°	33464.5	33732.5	34018.3	34294.3	34556.7	34783.6	34974.0	35121.1	35222.6	35291.4	35307.6
15°	33303.7	33626.2	33937.0	34211.9	34429.6	34597.5	34684.4	34725.1	34681.5	34609.0	34449.6
17.5°	33003.5	33343.6	33621.5	33838.3	33953.4	33998.9	33926.9	33801.7	33556.9	33285.3	32892.9
20°	32453.0	32769.9	32971.5	33089.8	33059.0	32945.2	32673.3	32343.0	31854.4	31333.6	30646.3
22.5°	31487.6	31764.6	31872.0	31880.8	31693.0	31408.0	30917.8	30351.1	29580.1	28778.8	27793.2
25°	30038.3	30280.9	30297.9	30202.6	29858.9	29397.1	28677.2	27875.6	26828.1	25760.1	24525.1
27.5°	28072.8	28305.6	28248.5	28070.7	27593.6	26975.6	26054.0	25018.4	23726.9	22465.7	21099.4
30°	25602.0	25850.9	25784.0	25555.9	24988.4	24258.0	23173.5	21970.3	20536.5	19189.4	17804.9
32.5°	22645.2	22959.9	22913.7	22696.9	22104.7	21323.1	20146.4	18870.2	17403.3	16075.7	14729.0
35°	19284.5	19666.5	19686.2	19544.5	18994.8	18222.2	17060.2	15825.0	14419.9	13167.3	11923.2
37.5°	15663.6	16106.5	16197.5	16159.3	15703.6	15021.6	13963.0	12854.8	11610.0	10512.3	9448.2
40°	12022.8	12471.1	12626.6	12672.7	12336.5	11808.2	10939.4	10045.0	9030.2	8140.7	7295.8
42.5°	8702.4	9099.8	9250.2	9344.7	9134.9	8782.6	8148.8	7499.3	6755.8	6114.3	5499.1
45°	6044.0	6325.1	6439.5	6534.7	6420.3	6221.6	5821.4	5415.1	4924.4	4505.1	4108.2
47.5°	4225.8	4380.8	4456.2	4502.4	4458.1	4354.5	4136.6	3901.3	3624.3	3379.3	3143.7
50°	3132.2	3214.7	3254.1	3280.8	3248.6	3191.0	3073.1	2945.0	2792.8	2654.1	2518.4
52.5°	2482.2	2529.5	2552.9	2567.3	2548.8	2513.6	2444.9	2368.9	2277.8	2192.0	2146.9
55°	2091.1	2088.6	2142.8	2116.7	2142.8	2084.4	2072.1	1988.5	1912.9	1859.5	1801.8
57.5°	1724.5	1749.0	1759.4	1771.1	1763.5	1752.9	1723.7	1693.8	1653.9	1620.4	1584.8
60°	1492.7	1513.0	1524.4	1535.9	1535.2	1531.2	1514.3	1496.5	1471.5	1451.5	1429.9
62.5°	1333.1	1350.6	1361.9	1372.9	1374.0	1372.4	1359.5	1347.2	1330.1	1317.6	1302.7
65°	1207.5	1219.8	1227.5	1236.3	1235.8	1233.5	1221.9	1211.6	1197.6	1188.9	1178.0
67.5°	1076.1	1085.4	1091.4	1099.7	1101.3	1101.8	1095.5	1090.6	1083.8	1081.2	1077.6
70°	982.6	993.9	1003.5	1014.0	1019.7	1022.4	1019.7	1017.3	1013.2	1011.6	1008.6
72.5°	911.9	921.4	928.8	938.4	943.7	947.6	945.5	944.1	940.6	940.2	938.2
75°	824.0	830.6	834.8	842.0	844.8	848.5	846.9	847.7	846.6	849.3	849.2
77.5°	718.4	723.2	725.2	730.4	730.9	735.2	736.3	741.3	745.0	752.9	757.1
80°	599.5	602.6	602.6	607.9	610.3	617.6	621.0	629.4	633.2	640.3	640.9
82.5°	465.6	462.1	465.6	463.5	470.2	478.5	479.6	486.6	488.3	492.7	489.2
85°	318.4	318.1	315.3	315.8	313.6	314.6	313.4	314.7	313.5	313.6	310.4
87.5°	152.5	153.9	150.5	151.7	148.5	150.0	147.1	149.3	145.9	146.5	141.5
90°	45.4	46.7	47.8	49.2	51.1	54.7	58.6	62.4	66.7	70.4	74.5
92.5°	51.8	53.9	55.9	57.9	59.9	66.0	72.0	78.1	84.4	90.2	96.3
95°	59.4	61.2	62.9	64.9	66.7	75.4	84.2	92.9	101.7	110.4	119.2
97.5°	67.1	68.2	69.3	70.4	71.8	82.1	92.4	102.7	113.0	123.4	133.5
100°	77.3	78.6	79.9	81.4	82.7	106.5	130.3	154.0	177.8	201.5	225.3
102.5°	127.4	135.6	144.0	152.5	160.8	218.4	276.1	333.7	391.1	448.8	506.3
105°	294.2	322.2	350.6	378.6	406.6	493.8	581.1	668.3	755.4	842.5	929.8
107.5°	598.8	648.2	697.6	746.9	796.3	878.4	960.3	1042.4	1124.4	1206.3	1288.1
110°	919.3	961.6	1004.5	1047.1	1089.8	1154.8	1220.0	1285.0	1350.2	1415.1	1480.2



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	192.5°	195°	197.5°	200°	202.5°	205°	207.5°	210°	212.5°	215°	217.5°
112.5°	1106.1	1132.0	1158.0	1183.7	1209.8	1257.5	1305.6	1353.3	1401.1	1448.6	1496.4
115°	1154.4	1168.0	1181.8	1195.5	1209.4	1238.3	1267.2	1296.0	1324.9	1353.6	1382.5
117.5°	1121.1	1126.2	1131.3	1135.9	1140.9	1155.8	1170.7	1185.5	1200.4	1215.3	1230.1
120°	1040.0	1039.7	1039.4	1038.9	1038.6	1043.2	1048.1	1052.6	1057.4	1061.9	1066.4
122.5°	948.1	944.8	941.6	938.2	934.9	933.2	931.9	930.2	929.0	927.3	925.8
125°	861.3	857.9	854.7	851.1	847.6	843.6	839.6	835.5	831.3	827.3	823.2
127.5°	787.1	784.0	781.2	777.9	774.8	770.2	765.7	761.0	756.5	751.8	747.2
130°	725.5	723.2	721.4	718.7	716.7	712.4	708.6	704.5	700.6	696.4	692.5
132.5°	680.9	679.4	678.0	676.1	674.6	670.9	667.5	663.8	660.2	656.5	653.1
135°	646.3	645.4	644.7	643.5	642.6	639.8	637.2	634.4	631.8	629.0	626.4
137.5°	617.6	617.3	617.2	616.9	616.6	614.3	612.1	609.9	607.7	605.4	603.2
140°	599.1	599.0	598.8	598.6	598.3	595.8	593.5	591.2	588.8	586.4	584.0
142.5°	579.9	579.9	579.8	579.5	579.4	577.4	575.8	573.9	572.0	570.3	568.5
145°	565.8	566.0	566.2	566.1	566.4	564.1	562.1	559.8	557.8	555.6	553.5
147.5°	552.1	552.3	552.7	552.8	553.2	551.3	549.7	547.7	546.1	544.1	542.5
150°	541.9	541.9	542.0	541.9	541.8	539.8	538.1	536.3	534.6	532.4	530.7
152.5°	531.8	532.0	532.1	532.3	532.5	530.6	528.7	526.7	524.7	522.7	520.7
155°	523.0	523.1	523.2	523.2	523.2	521.5	519.7	517.7	515.9	514.0	512.2
157.5°	515.5	515.8	515.9	516.1	516.2	514.6	513.0	511.5	509.9	508.3	506.7
160°	510.0	510.4	510.7	510.8	511.1	509.8	508.6	507.0	506.0	504.3	502.9
162.5°	506.9	507.2	507.5	507.6	507.9	506.6	505.4	504.0	502.7	501.1	499.8
165°	502.4	502.3	502.5	502.3	502.4	501.4	500.7	499.7	498.9	497.9	497.0
167.5°	502.5	502.5	502.6	502.5	502.5	501.9	501.6	500.8	500.1	499.4	498.7
170°	501.7	501.6	501.7	501.5	501.6	501.0	500.4	499.7	499.4	498.3	497.7
172.5°	500.7	500.4	500.2	500.0	499.6	499.2	498.9	498.5	498.1	497.7	497.2
175°	499.8	499.5	499.4	499.1	498.7	498.6	498.3	498.3	498.0	497.9	497.6
177.5°	503.1	502.6	501.9	501.3	500.8	500.6	500.5	500.3	500.3	500.0	499.8
180°	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
0°	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2
2.5°	33786.4	33577.8	33550.2	33564.9	33599.7	33612.7	33650.2	33660.5	33698.5	33707.7	33744.1
5°	34483.6	34207.8	34221.5	34287.9	34388.3	34448.1	34546.8	34598.4	34692.6	34735.4	34820.6
7.5°	35218.8	35002.1	35069.6	35181.5	35318.8	35413.9	35532.4	35609.5	35711.7	35775.2	35856.9
10°	35579.7	35520.3	35594.7	35682.6	35761.0	35822.3	35872.6	35912.8	35939.1	35963.8	35974.6
12.5°	35304.9	35396.8	35409.5	35400.9	35349.1	35309.4	35220.4	35160.0	35052.7	34987.2	34859.5
15°	34286.7	34488.7	34376.8	34207.6	33959.8	33753.3	33461.6	33244.5	32940.7	32734.7	32429.9
17.5°	32499.8	32754.6	32463.2	32071.5	31573.2	31146.9	30616.0	30194.6	29666.8	29282.9	28790.3
20°	29984.1	30222.3	29702.6	29053.1	28282.3	27633.6	26868.6	26258.1	25547.1	25018.4	24380.1
22.5°	26851.8	27021.4	26289.3	25413.8	24431.8	23621.3	22706.6	21974.8	21163.4	20558.9	19878.4
25°	23386.4	23432.2	22554.1	21545.5	20450.9	19540.0	18563.5	17794.1	16966.6	16353.9	15686.0
27.5°	19889.0	19821.8	18872.5	17803.2	16651.8	15705.0	14752.5	14031.5	13306.9	12754.9	12179.6
30°	16587.7	16425.1	15439.5	14340.4	13222.7	12374.1	11583.4	11004.4	10427.9	9990.0	9528.2
32.5°	13560.5	13331.1	12371.7	11341.9	10400.1	9745.2	9159.0	8720.9	8255.2	7885.4	7497.8
35°	10879.0	10634.6	9784.8	8911.7	8198.9	7716.2	7255.4	6896.0	6500.7	6188.6	5852.0
37.5°	8577.8	8377.5	7665.6	6978.6	6439.5	6065.4	5687.8	5394.0	5067.4	4930.1	4570.4
40°	6622.1	6482.0	5925.3	5419.0	5014.1	4838.4	4455.1	4180.7	3936.5	3735.2	3540.3
42.5°	5165.3	5115.7	4574.0	4179.0	3894.0	3672.6	3459.0	3285.6	3116.8	2978.0	2846.9
45°	3790.6	3751.3	3510.9	3282.9	3088.6	2933.9	2789.5	2670.2	2559.8	2468.4	2385.2
47.5°	2951.7	2939.2	2800.7	2659.3	2536.9	2437.5	2343.7	2264.6	2191.3	2130.3	2110.4
50°	2400.8	2399.1	2317.9	2230.6	2143.5	2086.0	2026.2	1979.4	1932.3	1895.7	1857.0
52.5°	2039.9	2031.0	1976.2	1922.3	1870.5	1832.8	1794.5	1764.7	1733.5	1710.9	1686.8
55°	1756.1	1765.4	1733.7	1701.5	1669.1	1645.6	1618.8	1599.1	1577.8	1563.5	1548.9
57.5°	1559.0	1571.3	1554.7	1536.4	1516.7	1501.3	1482.8	1469.1	1454.9	1445.8	1437.4
60°	1415.6	1429.0	1422.4	1413.2	1401.0	1391.9	1380.1	1372.5	1363.3	1358.2	1353.5
62.5°	1294.1	1310.7	1308.4	1304.1	1296.2	1291.2	1284.7	1281.3	1275.2	1273.1	1270.8
65°	1172.7	1191.5	1191.1	1189.1	1184.7	1183.2	1179.2	1178.5	1175.4	1176.6	1176.3
67.5°	1077.2	1093.6	1097.2	1099.8	1099.7	1100.6	1100.3	1101.9	1101.9	1104.3	1105.8
70°	1008.3	1019.7	1022.4	1025.2	1026.0	1028.1	1028.1	1029.5	1029.2	1031.1	1031.4
72.5°	938.7	953.7	956.5	958.6	958.6	960.8	959.7	959.3	956.3	955.7	953.6
75°	852.0	871.3	875.5	878.3	878.6	880.5	877.9	876.3	871.3	869.3	865.8
77.5°	761.5	781.6	784.5	785.5	783.9	784.3	778.8	775.1	768.8	766.1	762.9
80°	643.8	673.2	675.6	673.7	669.1	668.3	663.0	659.5	651.9	649.3	646.5
82.5°	489.9	524.4	529.2	531.3	527.6	528.5	523.4	521.4	514.4	513.2	508.6
85°	309.3	343.8	349.5	348.6	344.9	344.1	341.1	342.1	341.4	343.3	344.3
87.5°	142.1	175.5	183.6	181.0	180.6	178.3	172.9	174.9	178.1	180.2	180.3
90°	78.3	92.3	95.9	93.5	87.8	84.8	79.4	77.0	72.0	69.6	64.7
92.5°	102.4	108.4	114.5	109.0	103.7	98.3	92.9	87.4	82.1	76.6	71.4
95°	128.0	136.6	145.3	138.1	130.8	123.6	116.3	109.2	102.0	94.8	87.7
97.5°	143.8	153.9	164.0	156.8	149.7	142.4	135.2	128.0	120.8	113.5	106.4
100°	249.0	272.3	295.9	275.5	255.0	234.6	214.2	193.7	173.3	153.0	132.4
102.5°	563.7	621.0	678.5	626.7	575.0	523.3	471.7	420.0	368.4	316.6	265.1
105°	1016.7	1103.4	1190.4	1111.3	1032.4	953.6	874.7	795.9	717.0	638.1	559.3
107.5°	1370.0	1451.1	1532.6	1461.4	1390.0	1318.8	1247.3	1176.1	1104.8	1033.5	962.3
110°	1545.2	1609.0	1673.8	1625.8	1578.0	1529.9	1482.2	1434.2	1386.5	1338.7	1291.1



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	220°	222.5°	225°	227.5°	230°	232.5°	235°	237.5°	240°	242.5°	245°
112.5°	1544.0	1590.3	1637.5	1609.3	1581.4	1553.2	1525.2	1497.1	1469.4	1441.2	1413.6
115°	1411.1	1438.1	1466.4	1455.1	1444.1	1432.9	1421.7	1410.8	1399.7	1388.6	1377.9
117.5°	1244.7	1257.4	1271.6	1269.3	1267.4	1265.1	1263.2	1261.1	1259.3	1257.3	1255.5
120°	1070.9	1073.3	1077.2	1078.4	1079.9	1081.2	1082.7	1084.1	1085.6	1087.1	1088.7
122.5°	924.3	920.1	917.7	919.0	920.2	921.3	922.8	923.9	925.3	926.7	928.2
125°	819.2	812.1	807.2	805.1	803.2	801.2	799.1	797.2	795.4	793.5	791.7
127.5°	742.4	734.8	729.4	724.9	720.4	715.8	711.3	706.8	702.4	697.8	693.6
130°	688.5	681.3	676.3	670.6	665.2	659.3	653.7	648.1	642.4	636.8	631.2
132.5°	649.4	642.4	637.9	632.6	627.3	621.7	616.4	610.8	605.4	599.8	594.5
135°	623.7	617.4	613.8	608.8	604.2	599.1	594.2	589.1	584.3	579.1	574.5
137.5°	600.9	594.8	591.9	587.9	584.1	580.1	576.4	572.0	568.2	563.9	560.2
140°	581.6	575.2	572.0	569.8	567.6	565.2	563.1	560.6	558.5	556.2	553.8
142.5°	566.6	560.5	557.8	556.4	555.2	553.5	552.4	550.9	549.5	547.6	546.2
145°	551.3	544.5	541.4	541.1	541.2	541.0	540.9	540.8	540.6	540.2	540.0
147.5°	540.7	533.6	530.7	531.0	531.3	531.4	531.8	531.9	532.2	532.4	532.7
150°	528.8	520.8	517.3	518.1	518.6	519.2	519.8	520.3	521.1	521.7	522.2
152.5°	518.6	509.3	505.4	506.0	506.9	507.4	508.2	509.0	509.9	510.6	511.3
155°	510.0	499.9	495.8	495.9	496.3	496.5	496.8	497.3	497.8	498.1	498.7
157.5°	504.9	494.4	490.4	490.1	490.3	490.3	490.5	490.6	490.9	491.1	491.7
160°	501.4	491.0	487.2	486.9	487.0	487.0	487.0	487.1	487.4	487.6	487.9
162.5°	498.2	488.0	484.4	484.0	483.9	483.9	484.0	483.9	484.1	484.1	484.6
165°	495.8	487.0	483.7	483.7	483.9	483.9	484.1	484.4	484.7	484.9	485.4
167.5°	497.9	490.0	487.5	487.1	486.7	486.3	486.3	485.9	485.9	485.6	485.6
170°	496.9	490.6	488.4	488.3	488.6	488.6	488.5	488.7	488.7	488.7	489.0
172.5°	496.7	492.1	490.5	490.7	491.2	491.5	492.0	492.3	492.8	493.2	493.6
175°	497.4	494.6	493.9	493.8	494.1	494.3	494.6	494.8	495.1	495.2	495.8
177.5°	499.8	498.9	498.4	498.4	498.4	498.4	498.4	498.4	498.4	498.6	498.6
180°	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
0°	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2
2.5°	33750.9	33790.3	33787.3	33824.0	33822.2	33856.8	33849.8	33879.7	33873.0	33898.5	33883.5
5°	34858.0	34932.9	34957.6	35025.1	35039.1	35099.6	35100.8	35148.9	35143.0	35180.6	35160.6
7.5°	35905.4	35975.2	36008.3	36060.9	36087.0	36130.5	36147.5	36183.2	36191.8	36212.9	36212.2
10°	35993.7	35993.4	36009.8	36002.5	36017.1	36008.7	36026.6	36020.1	36046.5	36039.8	36059.7
12.5°	34804.4	34686.4	34643.3	34537.3	34514.2	34423.1	34429.6	34371.2	34399.4	34363.5	34424.6
15°	32248.5	31974.7	31839.5	31601.4	31526.7	31338.5	31323.3	31198.3	31232.0	31166.6	31262.2
17.5°	28471.5	28040.6	27804.0	27456.3	27318.3	27052.2	26998.9	26838.0	26862.9	26781.9	26897.3
20°	23968.4	23447.5	23149.2	22747.1	22567.8	22250.6	22166.5	21986.4	22009.0	21928.4	22058.9
22.5°	19413.9	18868.7	18531.8	18110.5	17881.5	17583.1	17493.6	17312.8	17323.1	17247.3	17373.0
25°	15228.5	14705.8	14378.9	13996.0	13797.3	13523.8	13429.7	13267.4	13276.5	13214.2	13326.8
27.5°	11780.3	11351.4	11077.9	10757.1	10578.9	10354.0	10262.3	10125.8	10125.4	10079.6	10173.8
30°	9205.7	8847.8	8602.2	8322.8	8155.5	7952.6	7864.0	7741.8	7736.5	7704.0	7778.8
32.5°	7207.9	6889.5	6665.4	6419.6	6269.4	6095.3	6011.4	5913.2	5904.3	5874.9	5936.3
35°	5603.2	5335.1	5142.4	4935.4	4950.7	4693.8	4736.5	4536.9	4482.8	4471.0	4516.6
37.5°	4330.6	4123.0	3966.5	3811.5	3706.5	3597.8	3539.4	3486.9	3480.9	3475.8	3507.9
40°	3389.7	3244.4	3130.6	3024.2	2951.9	2885.6	2849.1	2820.2	2813.4	2809.6	2829.0
42.5°	2743.4	2645.4	2572.0	2507.1	2463.2	2427.2	2407.1	2391.0	2385.7	2385.9	2397.3
45°	2317.9	2258.4	2211.1	2170.7	2142.7	2155.0	2118.7	2137.8	2112.7	2138.6	2121.5
47.5°	2041.2	1990.6	1961.3	1932.7	1915.8	1902.1	1902.5	1902.8	1908.2	1909.0	1914.6
50°	1827.7	1798.4	1778.1	1759.8	1751.0	1743.8	1746.3	1748.2	1753.3	1753.7	1757.8
52.5°	1669.7	1650.5	1638.2	1626.9	1622.9	1618.8	1620.6	1619.9	1622.2	1621.0	1624.3
55°	1541.2	1532.1	1528.2	1524.0	1524.6	1523.6	1524.2	1520.2	1517.7	1514.6	1517.5
57.5°	1435.6	1434.4	1437.0	1438.8	1443.6	1445.3	1446.5	1441.7	1437.3	1433.2	1435.5
60°	1354.4	1356.4	1362.8	1368.0	1374.9	1378.2	1380.1	1377.4	1374.2	1370.9	1372.8
62.5°	1274.2	1277.3	1285.0	1290.8	1299.2	1303.6	1308.4	1308.7	1309.9	1308.7	1310.0
65°	1181.1	1184.9	1191.9	1196.7	1204.5	1208.4	1213.3	1214.3	1217.0	1216.3	1218.7
67.5°	1110.4	1113.8	1119.6	1124.2	1131.2	1135.2	1139.5	1139.8	1140.7	1140.5	1142.7
70°	1034.9	1036.6	1041.8	1045.6	1052.6	1056.7	1061.7	1063.2	1066.3	1066.7	1069.3
72.5°	954.4	953.7	956.8	958.5	963.8	967.0	973.3	976.8	982.0	983.4	985.2
75°	866.8	866.1	869.8	871.3	875.7	879.0	886.0	890.6	898.7	902.1	901.2
77.5°	765.4	767.2	774.1	777.9	783.9	788.0	797.2	804.5	819.2	825.7	819.2
80°	651.9	653.8	661.0	664.6	672.5	677.4	687.7	696.3	709.6	712.5	708.7
82.5°	512.6	513.1	519.5	522.3	532.4	539.7	552.8	559.6	567.8	566.6	565.6
85°	349.5	354.3	362.3	370.4	382.7	394.7	407.0	417.1	410.0	421.2	408.6
87.5°	186.8	186.3	197.2	195.5	212.8	222.9	233.6	238.7	244.4	243.3	243.4
90°	62.8	59.5	59.0	55.5	55.8	52.0	53.3	49.7	51.6	47.3	53.7
92.5°	65.9	63.0	60.0	57.2	54.2	51.3	48.3	45.4	42.5	39.6	42.5
95°	80.5	77.7	75.1	72.3	69.6	67.0	64.3	61.5	58.9	56.2	59.6
97.5°	99.2	97.6	96.0	94.5	92.9	91.3	89.7	88.2	86.5	84.9	87.1
100°	111.9	111.9	111.9	111.9	111.7	111.7	111.7	111.7	111.7	111.7	113.5
102.5°	213.4	208.2	203.1	197.7	192.6	187.3	182.2	177.0	171.9	166.7	174.3
105°	480.4	460.3	440.0	419.8	399.5	379.4	359.1	339.0	318.8	298.6	319.5
107.5°	891.2	854.2	817.4	780.6	743.7	706.9	670.1	633.3	596.6	559.8	592.7
110°	1243.2	1204.0	1164.9	1125.8	1086.8	1047.6	1008.6	969.6	930.6	891.6	922.9



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	247.5°	250°	252.5°	255°	257.5°	260°	262.5°	265°	267.5°	270°	272.5°
112.5°	1385.7	1360.2	1335.0	1309.8	1284.5	1259.3	1234.1	1209.0	1183.9	1158.8	1174.1
115°	1366.8	1354.8	1342.7	1330.6	1318.6	1306.5	1294.5	1282.6	1270.7	1258.8	1259.8
117.5°	1253.6	1249.4	1245.4	1241.3	1237.2	1233.3	1229.3	1225.6	1221.6	1217.9	1209.4
120°	1090.5	1091.5	1092.7	1093.9	1095.3	1096.7	1097.9	1099.4	1101.0	1102.6	1091.2
122.5°	929.7	932.4	935.3	938.3	941.3	944.4	947.6	950.9	954.3	957.7	946.3
125°	789.8	792.5	795.4	798.2	801.0	804.2	807.3	810.7	813.9	817.5	807.8
127.5°	689.2	690.1	690.8	691.9	692.8	694.1	695.5	696.8	698.4	700.2	694.1
130°	625.5	624.3	623.0	622.0	620.8	620.1	619.4	618.7	618.1	617.8	615.1
132.5°	589.0	586.4	583.8	581.1	578.7	576.5	574.3	572.4	570.5	568.9	568.0
135°	569.2	565.7	562.1	558.7	555.3	552.3	549.1	546.5	543.7	541.0	541.6
137.5°	556.1	552.7	549.0	545.7	542.3	539.4	536.2	533.3	530.6	528.1	529.1
140°	551.4	547.9	544.3	541.0	537.9	534.8	531.7	529.1	526.1	523.7	524.4
142.5°	544.7	541.7	538.3	535.4	532.3	529.5	526.9	524.5	521.7	519.6	520.3
145°	539.7	537.5	535.0	532.7	530.6	528.7	526.4	524.7	522.9	521.5	521.7
147.5°	532.7	531.1	529.1	527.6	525.8	524.4	522.8	521.6	520.2	519.1	519.2
150°	522.9	521.7	520.5	519.5	518.4	517.4	516.5	515.7	514.8	514.2	514.1
152.5°	512.2	511.3	510.1	509.2	508.3	507.4	506.6	505.9	505.2	504.5	504.4
155°	499.2	498.7	498.2	498.0	497.6	497.5	497.0	497.0	496.6	496.5	496.6
157.5°	491.9	491.9	491.6	491.8	491.7	491.7	491.6	491.9	491.7	492.1	492.2
160°	488.4	488.1	487.8	487.8	487.6	487.4	487.3	487.3	487.2	487.1	487.6
162.5°	484.7	485.1	485.2	485.4	485.8	486.1	486.4	486.9	487.2	487.7	488.0
165°	485.9	485.9	485.7	485.6	485.8	485.8	485.8	486.2	486.1	486.4	487.0
167.5°	485.5	485.8	486.0	486.2	486.5	487.1	487.4	487.9	488.5	489.1	489.6
170°	488.9	488.9	488.9	488.9	488.9	489.1	489.2	489.3	489.5	489.9	490.2
172.5°	493.9	493.9	493.7	493.9	493.7	493.9	493.9	494.1	494.1	494.2	494.4
175°	495.7	496.2	496.5	496.7	496.8	497.1	497.3	497.5	497.8	498.0	498.0
177.5°	498.6	498.7	498.7	498.7	498.7	498.8	498.8	498.8	498.8	498.7	498.9
180°	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
0°	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2
2.5°	33908.4	33891.4	33908.8	33891.2	33908.8	33887.7	33902.0	33879.2	33885.0	33861.3	33867.4
5°	35190.6	35163.5	35177.9	35142.8	35146.4	35099.6	35098.7	35044.1	35029.7	34967.5	34940.2
7.5°	36227.3	36218.5	36223.5	36200.8	36198.3	36166.2	36151.0	36105.7	36077.3	36020.1	35981.0
10°	36063.2	36089.6	36096.5	36123.4	36129.0	36155.7	36161.3	36188.0	36193.5	36213.3	36213.5
12.5°	34421.8	34511.5	34533.0	34643.8	34690.5	34817.4	34885.4	35025.1	35108.1	35247.5	35333.1
15°	31259.6	31414.9	31476.8	31693.3	31813.0	32065.7	32224.5	32514.7	32719.4	33027.6	33247.4
17.5°	26907.5	27124.5	27222.4	27515.9	27707.4	28080.4	28349.2	28791.7	29130.4	29622.1	30011.9
20°	22081.3	22322.4	22455.3	22790.2	23016.2	23452.0	23787.6	24331.4	24784.8	25407.9	25940.7
22.5°	17412.3	17641.8	17789.4	18130.1	18384.5	18839.0	19214.1	19788.0	20296.0	20998.1	21636.9
25°	13369.4	13579.7	13713.0	14021.2	14260.2	14677.9	15036.1	15588.0	16085.1	16789.3	17444.3
27.5°	10220.7	10396.8	10525.4	10788.2	10998.9	11353.2	11660.8	12117.0	12545.2	13154.6	13737.9
30°	7824.8	7980.9	8106.1	8334.9	8530.3	8837.4	9107.9	9491.1	9845.6	10330.3	10794.4
32.5°	5979.5	6113.9	6225.4	6425.6	6603.0	6879.5	7123.2	7459.0	7763.3	8174.5	8556.3
35°	4559.1	4823.6	4804.8	5081.2	5125.6	5324.1	5541.5	5835.1	6104.6	6454.2	6779.1
37.5°	3538.6	3613.0	3692.7	3814.8	3943.2	4123.7	4307.4	4666.2	4797.8	5062.1	5331.0
40°	2853.5	2903.8	2956.4	3039.0	3128.8	3256.0	3389.9	3561.0	3736.3	3950.6	4169.4
42.5°	2412.4	2440.9	2474.3	2522.8	2578.2	2658.9	2748.4	2864.5	2986.4	3137.2	3291.1
45°	2155.4	2141.9	2151.8	2177.8	2211.2	2260.3	2316.8	2388.6	2468.0	2565.7	2669.7
47.5°	1915.8	1921.2	1924.2	1938.3	1956.1	1989.1	2023.3	2072.1	2166.3	2195.0	2251.7
50°	1757.5	1760.1	1759.2	1766.4	1775.4	1796.8	1819.0	1852.1	1885.0	1928.8	1970.5
52.5°	1624.8	1628.5	1628.0	1632.8	1637.6	1651.1	1665.1	1688.4	1710.1	1737.9	1761.9
55°	1520.0	1525.1	1527.1	1531.1	1533.5	1540.5	1546.1	1557.3	1566.5	1582.2	1596.7
57.5°	1439.4	1446.5	1449.7	1451.1	1448.2	1447.8	1445.9	1448.3	1450.1	1458.6	1466.8
60°	1376.0	1381.6	1382.5	1381.6	1376.4	1372.7	1366.8	1364.9	1363.9	1368.0	1372.5
62.5°	1309.7	1311.7	1310.3	1308.7	1302.7	1299.1	1292.9	1290.7	1288.5	1291.4	1293.8
65°	1217.8	1219.6	1217.8	1216.8	1211.4	1208.6	1203.4	1201.7	1198.7	1199.5	1199.0
67.5°	1143.3	1144.9	1143.6	1142.2	1138.5	1136.8	1132.9	1130.4	1126.9	1125.5	1123.0
70°	1068.9	1070.3	1068.1	1066.7	1062.5	1060.9	1057.4	1056.6	1053.7	1053.1	1050.2
72.5°	983.4	983.5	980.5	979.6	976.5	976.4	974.9	976.3	976.1	977.6	977.0
75°	895.9	894.7	890.9	890.2	887.9	889.0	887.4	889.5	889.8	893.0	893.3
77.5°	808.2	803.6	796.6	793.2	788.5	787.9	785.1	787.0	786.4	790.1	791.6
80°	697.6	691.9	682.9	678.6	672.9	672.1	669.6	672.1	670.9	675.2	678.3
82.5°	556.9	552.1	542.6	539.2	532.7	533.4	530.6	533.4	533.0	539.4	543.1
85°	412.0	408.7	399.0	390.4	380.9	375.3	369.9	368.9	367.3	369.9	372.1
87.5°	237.9	234.9	227.3	222.4	205.7	206.4	199.8	199.4	197.8	196.3	199.8
90°	53.6	59.0	59.2	64.3	64.9	70.6	71.7	77.1	77.7	83.5	84.9
92.5°	45.4	48.3	51.2	54.2	57.1	60.0	62.9	65.9	72.1	78.1	84.7
95°	62.9	66.3	69.7	73.0	76.3	79.7	83.1	86.5	95.6	104.8	114.0
97.5°	89.5	91.6	93.9	96.1	98.4	100.6	102.9	105.1	115.1	125.1	134.9
100°	115.3	117.1	118.9	120.7	122.5	124.3	126.1	127.9	147.2	166.2	185.3
102.5°	182.0	189.6	197.3	204.9	212.7	220.3	228.0	235.6	279.4	323.2	366.9
105°	340.3	361.2	382.2	403.0	423.9	444.7	465.6	486.5	556.7	626.7	696.8
107.5°	625.7	658.7	691.7	724.6	757.6	790.7	823.6	856.8	925.1	993.6	1061.9
110°	954.3	985.8	1017.2	1048.7	1080.1	1111.7	1143.2	1174.8	1215.8	1256.9	1297.8



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	275°	277.5°	280°	282.5°	285°	287.5°	290°	292.5°	295°	297.5°	300°
112.5°	1189.4	1204.6	1220.1	1235.4	1250.8	1266.2	1281.6	1297.2	1317.8	1338.2	1358.8
115°	1260.7	1261.7	1262.8	1263.8	1264.9	1266.0	1267.3	1268.5	1275.0	1281.4	1288.1
117.5°	1201.0	1192.5	1184.3	1175.9	1167.7	1159.6	1151.5	1143.5	1142.2	1140.9	1139.8
120°	1080.1	1068.9	1057.6	1046.3	1035.3	1024.3	1013.5	1002.7	997.1	991.6	986.2
122.5°	935.0	923.9	912.8	901.7	890.7	879.9	869.3	858.6	854.7	850.8	847.2
125°	798.4	789.1	779.8	770.7	761.8	752.8	744.1	735.3	735.2	734.9	735.0
127.5°	688.5	682.8	677.1	671.8	666.6	661.2	656.2	651.0	653.5	656.1	658.6
130°	612.6	610.2	608.0	605.6	603.8	601.7	599.8	597.9	602.5	606.5	611.1
132.5°	567.8	567.4	567.3	567.1	567.3	567.3	567.7	567.7	572.9	577.7	582.8
135°	542.3	542.9	544.0	545.0	546.4	547.5	549.0	550.1	555.1	559.7	564.6
137.5°	530.3	531.4	532.8	534.3	536.1	537.6	539.5	541.1	545.0	548.8	552.6
140°	525.4	526.1	527.5	528.7	530.1	531.3	533.0	534.4	537.7	540.5	543.6
142.5°	521.4	522.0	523.2	524.5	525.8	526.9	528.4	529.6	531.9	534.0	536.5
145°	522.6	523.1	524.1	524.8	525.9	526.8	527.9	528.9	530.4	531.7	533.2
147.5°	519.8	520.2	520.7	521.4	522.1	522.7	523.3	524.0	525.0	526.0	526.9
150°	514.3	514.4	514.8	514.9	515.5	515.8	516.3	516.7	517.4	518.3	519.1
152.5°	504.8	504.8	505.1	505.3	505.5	505.9	506.1	506.6	507.3	508.0	508.8
155°	497.0	497.6	498.0	498.4	499.1	499.3	499.9	500.3	500.9	501.4	502.0
157.5°	492.8	493.0	493.6	493.9	494.5	494.9	495.3	495.7	496.4	496.7	497.2
160°	488.3	489.0	489.5	490.4	491.0	491.6	492.3	493.0	493.6	493.9	494.4
162.5°	488.6	489.1	489.5	489.9	490.4	490.9	491.3	491.8	492.6	493.1	493.9
165°	487.7	488.3	489.1	489.6	490.5	491.1	491.8	492.4	492.8	493.4	493.7
167.5°	490.4	490.8	491.8	492.3	493.1	493.6	494.4	495.0	495.4	495.7	496.2
170°	490.8	491.4	492.1	492.6	493.3	493.7	494.5	495.0	495.6	496.1	496.8
172.5°	495.0	495.3	495.9	496.2	496.7	497.3	497.9	498.1	498.7	499.3	499.6
175°	498.0	498.0	498.1	498.3	498.4	498.4	498.5	498.8	498.9	499.1	499.2
177.5°	499.2	499.4	499.5	499.8	500.0	500.2	500.5	500.7	500.7	500.7	500.7
180°	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
0°	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2
2.5°	33843.7	33845.2	33817.8	33816.3	33790.7	33787.6	33762.6	33755.1	33734.8	33727.5	33706.9
5°	34870.5	34837.2	34760.3	34715.2	34639.2	34588.9	34506.8	34453.2	34373.8	34314.1	34234.3
7.5°	35908.9	35857.3	35771.0	35701.2	35595.8	35511.7	35388.4	35287.3	35153.8	35038.3	34898.0
10°	36213.5	36205.6	36183.6	36151.5	36102.5	36047.5	35963.5	35876.0	35759.0	35631.9	35476.0
12.5°	35464.1	35545.0	35655.4	35720.7	35800.4	35835.2	35867.8	35859.7	35838.2	35773.8	35683.7
15°	33565.7	33793.2	34094.2	34327.6	34596.0	34791.1	35006.6	35140.9	35274.8	35336.6	35374.4
17.5°	30545.9	30976.5	31516.4	31963.8	32480.0	32894.7	33349.2	33691.4	34043.2	34295.3	34523.3
20°	26667.0	27290.7	28054.3	28728.9	29513.3	30194.9	30941.8	31555.1	32187.5	32682.0	33149.9
22.5°	22459.6	23200.4	24123.6	24978.7	25989.9	26898.7	27923.9	28816.3	29748.1	30526.6	31279.1
25°	18322.3	19134.8	20144.2	21098.2	22243.5	23300.5	24516.6	25628.7	26833.1	27878.5	28911.4
27.5°	14544.4	15342.1	16372.6	17388.2	18599.2	19725.6	21028.5	22253.8	23625.0	24889.5	26183.1
30°	11439.3	12115.9	13039.9	14023.7	15218.0	16364.2	17681.1	18941.4	20367.9	21748.5	23205.6
32.5°	9063.0	9578.4	10304.9	11136.7	12238.8	13329.8	14583.9	15800.4	17205.2	18599.9	20115.2
35°	7197.7	7599.7	8153.6	8802.7	9736.0	10676.5	11785.7	12892.0	14202.6	15526.0	16998.9
37.5°	5675.8	6002.0	6435.8	6923.4	7671.9	8443.8	9353.3	10270.5	11409.3	12582.4	13917.2
40°	4432.1	4696.3	5034.0	5397.6	5962.8	6557.6	7261.0	7972.2	8887.1	9845.9	10950.7
42.5°	3481.8	3676.7	3915.2	4180.9	4708.3	5024.0	5501.0	6015.5	6688.1	7384.1	8214.7
45°	2796.2	2929.1	3094.5	3272.8	3517.5	3785.3	4112.1	4454.6	5093.5	5407.0	5912.1
47.5°	2335.1	2424.3	2529.6	2641.9	2786.2	2942.0	3135.7	3333.8	3590.0	3855.5	4166.8
50°	2024.6	2115.3	2151.4	2209.6	2293.2	2382.1	2491.4	2600.6	2738.0	2877.2	3037.5
52.5°	1794.1	1823.6	1862.9	1899.9	1951.7	2053.0	2085.8	2142.8	2219.9	2295.2	2379.4
55°	1618.1	1637.4	1662.8	1685.2	1716.5	1746.4	1789.6	1827.6	1878.9	1924.4	1980.3
57.5°	1481.0	1493.4	1511.1	1525.7	1545.9	1562.9	1588.2	1608.8	1638.3	1664.0	1697.9
60°	1381.6	1389.7	1401.6	1411.2	1424.1	1432.9	1445.4	1455.1	1470.7	1483.7	1502.7
62.5°	1300.2	1304.5	1312.2	1317.9	1326.0	1330.5	1337.2	1341.5	1350.0	1356.5	1367.1
65°	1202.6	1203.7	1208.9	1211.3	1217.7	1220.1	1225.5	1227.5	1234.6	1239.5	1248.7
67.5°	1122.7	1120.5	1120.7	1118.8	1119.6	1117.8	1118.2	1116.3	1119.2	1120.7	1127.7
70°	1049.8	1046.7	1045.6	1042.3	1041.3	1037.9	1036.8	1033.8	1033.4	1032.3	1034.9
72.5°	978.7	977.7	978.0	975.7	975.4	973.1	973.1	971.7	973.3	974.1	977.3
75°	896.9	897.1	898.7	896.6	897.2	895.2	896.0	894.1	895.1	894.7	897.9
77.5°	797.3	799.7	804.0	803.1	804.5	802.3	803.2	800.7	801.4	799.7	800.9
80°	685.4	690.4	696.2	695.9	698.4	696.8	699.0	696.5	697.6	694.6	693.8
82.5°	552.5	556.7	562.9	563.1	568.6	569.5	575.6	575.4	579.3	576.7	575.0
85°	377.7	380.5	386.0	389.0	394.5	398.0	403.9	406.3	402.0	409.7	403.6
87.5°	197.2	204.6	200.5	210.0	207.8	217.4	215.3	224.2	222.6	230.2	229.2
90°	91.8	93.9	101.1	103.4	111.8	114.9	117.4	113.6	115.8	112.3	114.7
92.5°	90.7	97.3	103.6	109.9	116.2	122.5	116.6	110.8	104.9	99.2	93.3
95°	123.2	132.5	141.6	150.8	160.0	169.2	159.3	149.5	139.7	129.8	119.9
97.5°	144.7	154.7	164.5	174.3	184.3	194.2	182.5	170.9	159.1	147.6	135.9
100°	204.3	223.6	242.6	261.7	280.8	299.9	278.3	256.5	234.9	213.2	191.4
102.5°	410.8	454.5	498.4	542.3	586.0	629.8	583.9	537.9	491.6	445.6	399.4
105°	767.0	837.0	907.1	977.3	1047.3	1117.7	1042.8	968.2	893.3	818.7	743.8
107.5°	1130.3	1198.5	1267.1	1335.4	1403.8	1472.4	1396.6	1320.8	1245.1	1169.1	1093.3
110°	1339.0	1380.1	1421.4	1462.5	1503.6	1544.9	1489.5	1434.2	1378.9	1323.6	1268.1



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	302.5°	305°	307.5°	310°	312.5°	315°	317.5°	320°	322.5°	325°	327.5°
112.5°	1379.2	1400.1	1420.5	1441.3	1461.8	1482.6	1443.1	1403.7	1363.9	1324.5	1284.9
115°	1294.7	1301.3	1307.9	1314.7	1321.1	1327.9	1301.2	1274.6	1248.0	1221.3	1194.5
117.5°	1138.7	1137.7	1136.4	1135.6	1134.3	1133.2	1118.4	1103.6	1088.5	1073.6	1058.6
120°	980.6	975.2	969.8	964.3	958.8	953.3	947.1	940.9	934.4	928.1	921.6
122.5°	843.3	839.7	835.8	832.2	828.1	824.3	821.9	819.6	817.1	814.7	812.0
125°	734.9	734.8	734.7	734.7	734.4	734.3	733.0	731.9	730.5	729.4	728.0
127.5°	660.9	663.6	665.9	668.3	670.6	673.0	672.7	672.5	672.1	671.8	671.4
130°	615.1	619.7	623.8	628.0	631.9	636.4	635.6	634.9	634.2	633.6	632.8
132.5°	587.8	592.7	597.4	602.5	607.2	612.0	611.1	610.4	609.2	608.6	607.5
135°	569.2	573.9	578.3	583.2	587.5	592.1	590.9	589.9	588.6	587.8	586.6
137.5°	556.1	560.2	563.7	567.4	570.7	574.5	573.2	572.2	570.9	570.0	568.7
140°	546.4	549.5	552.1	555.2	557.9	560.8	559.3	558.0	556.4	555.1	553.5
142.5°	538.6	540.9	542.8	545.2	547.2	549.4	547.1	545.3	543.3	541.3	539.4
145°	534.6	536.2	537.5	538.9	539.9	541.4	539.0	536.8	534.3	532.1	529.7
147.5°	527.6	528.7	529.2	530.2	530.7	531.7	529.3	527.2	524.9	522.6	520.3
150°	519.7	520.7	521.3	522.0	522.7	523.4	521.0	518.7	516.3	514.0	511.6
152.5°	509.6	510.2	510.9	511.4	512.1	512.7	510.4	508.4	506.0	503.8	501.4
155°	502.3	502.9	503.1	503.7	503.8	504.1	502.1	500.5	498.5	496.6	494.6
157.5°	497.6	498.1	498.5	498.7	499.0	499.4	497.9	496.5	495.1	493.6	492.1
160°	494.8	495.1	495.5	495.8	496.2	496.3	495.1	494.0	492.8	491.5	490.1
162.5°	494.5	495.1	495.7	496.1	496.7	497.2	495.7	494.4	493.0	491.5	489.9
165°	494.1	494.5	494.9	495.2	495.3	495.7	494.7	493.8	492.7	491.8	490.7
167.5°	496.5	496.9	497.2	497.6	497.7	498.0	496.9	496.2	495.1	494.1	493.0
170°	497.1	497.7	498.2	498.6	499.1	499.4	498.7	498.0	497.0	496.3	495.3
172.5°	500.1	500.7	500.9	501.2	501.5	502.0	501.1	500.3	499.5	498.6	497.7
175°	499.2	499.3	499.5	499.5	499.5	499.6	499.0	498.3	497.7	497.0	496.3
177.5°	500.7	500.7	500.7	500.6	500.6	500.6	500.1	499.6	499.3	498.8	498.1
180°	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
0°	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2	33489.2
2.5°	33699.5	33684.9	33675.4	33663.4	33656.1	33646.8	33639.9	33634.1	33629.4	33625.0	33621.9
5°	34173.4	34098.1	34039.6	33976.3	33924.3	33872.4	33832.5	33799.4	33776.5	33759.4	33749.2
7.5°	34776.7	34638.8	34516.2	34387.1	34271.5	34157.7	34059.6	33975.1	33911.7	33870.5	33845.6
10°	35315.5	35131.0	34948.4	34756.3	34574.0	34397.4	34234.3	34090.8	33977.2	33901.7	33857.7
12.5°	35557.1	35399.8	35213.4	35004.7	34781.5	34555.6	34335.3	34136.8	33970.1	33858.3	33793.7
15°	35344.4	35279.7	35153.3	34991.3	34779.4	34545.9	34287.4	34044.3	33820.8	33675.8	33591.8
17.5°	34652.4	34742.5	34732.8	34670.9	34518.6	34321.9	34058.5	33785.6	33505.9	33312.2	33206.3
20°	33484.7	33768.0	33911.7	33985.4	33925.5	33798.1	33559.6	33282.5	32956.6	32703.7	32549.2
22.5°	31843.8	32343.8	32655.5	32883.5	32931.9	32888.5	32677.8	32414.3	32051.1	31746.9	31518.9
25°	29731.3	30464.0	30956.4	31342.7	31492.5	31531.3	31352.0	31090.0	30685.1	30330.8	30017.7
27.5°	27243.2	28195.2	28852.7	29371.5	29605.7	29707.3	29542.3	29275.0	28795.9	28373.0	27963.9
30°	24442.1	25571.5	26363.2	26985.3	27270.8	27404.9	27229.7	26931.3	26373.8	25865.0	25349.6
32.5°	21444.0	22679.9	23542.6	24218.1	24501.0	24627.3	24398.0	24062.9	23418.5	22819.0	22218.1
35°	18305.0	19552.4	20422.5	21080.1	21317.1	21393.2	21100.0	20712.7	19998.7	19340.8	18685.5
37.5°	15102.1	16262.7	17053.3	17643.6	17790.3	17803.4	17450.1	17022.3	16271.9	15623.2	14970.9
40°	11926.8	12905.6	13544.1	14016.4	14067.3	14021.9	13637.8	13207.3	12505.3	11924.1	11351.4
42.5°	8935.9	9674.8	10130.2	10454.0	10434.7	10345.0	9992.9	9622.7	9043.6	8601.0	8150.2
45°	6373.6	6860.7	7127.0	7316.4	7255.7	7170.1	6896.1	6636.7	6243.1	5957.2	5654.3
47.5°	4427.8	5009.5	4908.3	5278.6	4959.5	5170.3	4731.4	4489.5	4280.6	4128.6	3957.5
50°	3169.9	3303.2	3367.7	3411.6	3388.2	3355.9	3277.0	3206.5	3111.1	3041.6	2960.5
52.5°	2448.1	2514.7	2551.2	2577.6	2572.4	2560.6	2526.2	2494.8	2450.1	2420.7	2385.2
55°	2073.6	2074.6	2141.7	2112.9	2155.5	2105.6	2125.2	2070.0	2078.9	2031.5	1999.6
57.5°	1723.1	1750.4	1762.7	1774.6	1771.2	1769.2	1755.9	1749.1	1734.1	1729.5	1718.9
60°	1515.7	1529.9	1532.9	1538.5	1533.8	1532.1	1521.7	1517.9	1507.9	1506.0	1498.9
62.5°	1373.5	1380.8	1380.8	1380.8	1374.8	1369.1	1357.6	1351.5	1343.0	1341.1	1337.0
65°	1254.8	1262.4	1263.6	1265.2	1260.9	1256.4	1246.2	1239.6	1230.8	1227.5	1222.8
67.5°	1132.3	1140.3	1143.1	1147.2	1144.8	1143.8	1136.9	1134.3	1128.5	1127.0	1122.7
70°	1036.1	1039.5	1039.2	1039.1	1033.7	1028.8	1020.7	1016.9	1010.8	1009.6	1005.6
72.5°	978.9	981.3	979.8	977.6	970.6	963.4	953.9	947.0	939.1	934.1	928.5
75°	898.3	901.5	899.4	898.1	891.7	887.1	879.5	875.6	870.0	868.4	864.6
77.5°	799.4	800.9	797.7	797.3	792.5	789.5	783.7	782.8	778.7	778.8	775.1
80°	689.3	688.5	683.2	682.3	677.4	676.2	671.7	672.0	668.7	670.1	667.5
82.5°	567.2	564.1	557.2	555.3	549.7	549.2	546.2	548.7	546.8	549.7	548.0
85°	406.4	407.4	404.4	404.4	402.8	403.3	403.0	404.8	405.1	407.8	407.7
87.5°	226.6	229.9	229.2	232.2	232.1	235.5	236.5	241.5	242.1	246.7	246.7
90°	111.1	113.8	110.3	113.1	111.6	115.7	114.9	119.1	117.8	121.3	118.9
92.5°	87.5	81.6	75.9	70.0	67.1	63.9	61.4	58.0	55.4	52.2	49.2
95°	110.1	100.2	90.3	80.5	77.1	73.6	70.3	66.9	63.6	60.2	56.9
97.5°	124.3	112.6	101.0	89.3	86.4	83.5	80.5	77.6	74.6	71.7	68.8
100°	169.6	147.9	126.2	104.3	101.9	99.4	96.9	94.5	92.0	89.4	86.9
102.5°	353.3	307.1	260.9	214.7	206.0	197.2	188.5	179.7	170.9	162.1	153.4
105°	669.0	594.1	519.3	444.4	420.6	396.8	373.1	349.2	325.4	301.6	277.9
107.5°	1017.4	941.3	865.4	789.4	745.6	701.7	657.7	613.5	569.8	525.7	481.7
110°	1212.8	1157.3	1101.9	1046.2	1011.0	975.6	940.1	904.7	869.5	833.9	798.4



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	330°	332.5°	335°	337.5°	340°	342.5°	345°	347.5°	350°	352.5°	355°
112.5°	1245.2	1205.5	1165.7	1125.8	1110.0	1093.8	1078.0	1061.9	1045.7	1029.5	1013.5
115°	1167.7	1140.9	1114.0	1087.1	1081.6	1075.8	1070.3	1064.5	1058.8	1053.0	1047.1
117.5°	1043.7	1028.5	1013.4	998.3	999.2	1000.1	1001.2	1002.0	1002.8	1003.5	1004.3
120°	915.2	908.7	902.3	895.8	900.8	905.5	910.6	915.2	919.8	924.3	928.9
122.5°	809.7	807.0	804.6	801.8	807.9	813.7	819.5	825.2	831.0	836.3	841.8
125°	726.9	725.5	724.3	722.7	728.8	734.7	740.6	746.2	751.9	757.3	762.8
127.5°	671.2	670.9	670.6	670.1	674.5	678.6	682.7	686.5	690.6	694.2	697.9
130°	632.1	631.3	630.8	629.9	633.9	637.5	641.5	644.8	648.5	651.6	654.9
132.5°	606.8	605.8	604.9	603.9	606.9	609.4	612.2	614.5	617.0	619.0	621.2
135°	585.5	584.2	583.3	582.0	584.6	587.1	589.7	591.8	594.1	595.8	597.8
137.5°	567.7	566.4	565.3	564.0	566.4	568.7	570.8	572.8	574.8	576.5	578.0
140°	552.3	550.7	549.4	547.8	549.8	551.8	553.8	555.5	557.3	558.7	560.2
142.5°	537.4	535.1	533.5	531.3	532.8	534.2	535.6	536.8	538.1	539.1	540.0
145°	527.4	524.8	522.7	520.2	521.5	522.5	523.7	524.7	525.5	526.1	527.1
147.5°	518.3	515.8	513.5	511.2	512.3	513.0	513.6	514.3	515.1	515.6	515.9
150°	509.2	506.6	504.2	501.8	502.5	503.1	503.6	504.3	504.9	505.3	505.6
152.5°	499.1	496.8	494.4	492.0	492.5	493.0	493.4	493.7	494.2	494.6	494.8
155°	492.8	490.7	488.8	486.5	487.2	487.5	487.7	488.1	488.3	488.6	488.7
157.5°	490.5	488.8	487.4	485.6	485.6	485.8	485.9	485.7	485.7	485.6	485.4
160°	489.0	487.5	486.1	484.7	484.6	484.7	484.7	484.4	484.5	484.1	483.9
162.5°	488.3	486.8	485.1	483.4	483.3	483.5	483.4	483.2	483.2	483.0	482.8
165°	489.8	488.5	487.4	486.1	486.0	485.7	485.6	485.0	484.8	484.3	483.9
167.5°	491.9	490.7	489.4	488.1	488.1	488.3	488.2	488.1	488.1	487.8	487.8
170°	494.5	493.5	492.6	491.6	491.3	491.2	490.9	490.6	490.3	490.1	489.7
172.5°	496.7	495.8	494.9	493.6	493.6	493.6	493.3	493.2	492.8	492.5	492.4
175°	495.5	494.9	493.9	493.3	493.2	493.1	492.9	492.8	492.5	492.4	492.1
177.5°	497.7	497.3	496.6	496.2	496.0	496.0	495.9	495.8	495.8	495.6	495.5
180°	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2	498.2



TEST NUMBER: P1444472
 CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	357.5°	360°
0°	33489.2	33489.2
2.5°	33618.9	33617.2
5°	33743.8	33741.8
7.5°	33838.9	33838.3
10°	33850.1	33855.9
12.5°	33782.6	33787.3
15°	33585.3	33594.6
17.5°	33208.3	33220.4
20°	32558.7	32571.2
22.5°	31506.7	31511.9
25°	29977.2	29955.5
27.5°	27892.1	27854.7
30°	25241.4	25205.2
32.5°	22081.0	22058.5
35°	18523.5	18509.3
37.5°	14778.1	14749.0
40°	11142.1	11057.4
42.5°	7952.9	7804.4
45°	5496.1	5320.0
47.5°	3836.9	3728.0
50°	2908.3	2873.2
52.5°	2369.7	2361.5
55°	1999.5	1995.8
57.5°	1721.2	1720.0
60°	1502.7	1502.3
62.5°	1339.7	1340.3
65°	1224.9	1225.1
67.5°	1123.9	1123.1
70°	1007.1	1006.2
72.5°	926.7	925.3
75°	864.6	863.7
77.5°	776.3	774.8
80°	669.2	667.5
82.5°	550.4	548.4
85°	410.6	410.7
87.5°	251.2	251.0
90°	122.1	119.1
92.5°	46.6	43.9
95°	53.5	50.1
97.5°	65.9	62.9
100°	84.4	82.0
102.5°	144.6	135.9
105°	254.1	230.3
107.5°	437.7	393.8
110°	762.9	727.5



TEST NUMBER: P1444472
CATALOG NUMBER: EHBR1-42-UNV-TA-L830-UPL40

CANDELA DISTRIBUTION (continued):

	357.5°	360°
112.5°	997.2	981.1
115°	1041.1	1035.3
117.5°	1004.9	1005.4
120°	933.1	937.6
122.5°	847.0	852.2
125°	768.0	773.2
127.5°	701.3	704.6
130°	657.5	660.6
132.5°	622.9	624.6
135°	599.2	600.8
137.5°	579.3	580.7
140°	561.2	562.2
142.5°	540.8	541.4
145°	527.6	528.0
147.5°	515.8	516.2
150°	505.7	505.9
152.5°	494.8	495.1
155°	488.7	488.8
157.5°	485.1	484.9
160°	483.6	483.4
162.5°	482.4	482.2
165°	483.3	482.8
167.5°	487.5	487.4
170°	489.3	489.1
172.5°	492.1	491.8
175°	492.1	492.0
177.5°	495.5	495.2
180°	498.2	498.2

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Report Prepared for

Cooper Lighting Solutions

Metalux

Report Number: SP1-2506-472-2

Test Date: 07/31/2025

Luminaire Tested: EHBR-60-L830-N

Data in this report applies to families of products including EHBR-60-L830-N


Test Information

Test Method: LM-79-2019
 Report Number: SP1-2506-472-2
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 08/05/2025
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: Metalux
 Catalog Number: **EHBR-60-L830-N**
 Description: Elevate Round Highbay at, 60000 lumens, 3000K 80CRI LEDs with N lens

Spectral Parameters

CCT (K): 2983
 CIE u': 0.2516
 CIE v': 0.5201
 Duv: -0.0012
 CIE x: 0.4364
 CIE y: 0.4010
 CIE z: 0.1626
 Peak Wavelength (nm): 630
 Dominant Wavelength (nm): 583
 Purity: 51.34918
 Rf: 81.2
 Rg: 101.5

CRI (Ra):	83.4		
R1:	84.0	R9:	29.4
R2:	87.5	R10:	68.6
R3:	88.9	R11:	82.2
R4:	83.8	R12:	61.6
R5:	81.9	R13:	83.9
R6:	83.1	R14:	92.5
R7:	87.1	R15:	79.8
R8:	70.9		



Test Conditions

Stabilization Time: 38M
 Operation Time: 1H 38M
 Sphere Temperature (°C): 25.0

REPORT NUMBER: SP1-2506-472-2


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	76INCH SPHERE IN0058	6/16/2025	12/16/2025
Power Meter	XITRON INXT2011004	1/21/2025	1/21/2026
AC Power Source	CHROMA 61603 IN0063	10/22/2024	10/22/2025
DC Power Source	AGILENT E3634A IN0208	10/22/2024	10/22/2025
Sphere Thermometer	ONSET IN0085	10/22/2024	10/22/2025
Room Thermometer	ONSET IN0046	10/22/2024	10/22/2025

REPORT NUMBER: SP1-2506-472-2

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles




CCT = 2983K
 CIE x = 0.4364
 CIE y = 0.4010
 Duv = -0.0012

Point lies inside the ANSI 3000K 4-step quadrangle

REPORT NUMBER: SP1-2506-472-2

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	43	NR	620	294	NR	750	6	NR	880	0	NR
365	0	NR	495	59	NR	625	294	NR	755	5	NR	885	0	NR
370	0	NR	500	81	NR	630	1000	NR	760	4	NR	890	0	NR
375	0	NR	505	109	NR	635	637	NR	765	4	NR	895	0	NR
380	0	NR	510	135	NR	640	175	NR	770	3	NR	900	0	NR
385	0	NR	515	160	NR	645	171	NR	775	3	NR	905	0	NR
390	1	NR	520	180	NR	650	146	NR	780	2	NR	910	0	NR
395	1	NR	525	195	NR	655	119	NR	785	2	NR	915	0	NR
400	2	NR	530	207	NR	660	99	NR	790	2	NR	920	0	NR
405	3	NR	535	218	NR	665	82	NR	795	2	NR	925	0	NR
410	5	NR	540	227	NR	670	76	NR	800	1	NR	930	0	NR
415	10	NR	545	237	NR	675	61	NR	805	1	NR	935	0	NR
420	20	NR	550	247	NR	680	52	NR	810	1	NR	940	0	NR
425	35	NR	555	259	NR	685	44	NR	815	1	NR	945	0	NR
430	58	NR	560	271	NR	690	38	NR	820	1	NR	950	0	NR
435	90	NR	565	283	NR	695	33	NR	825	1	NR	955	0	NR
440	135	NR	570	293	NR	700	27	NR	830	1	NR	960	0	NR
445	204	NR	575	303	NR	705	24	NR	835	1	NR	965	0	NR
450	233	NR	580	310	NR	710	20	NR	840	0	NR	970	0	NR
455	153	NR	585	313	NR	715	17	NR	845	0	NR	975	0	NR
460	98	NR	590	314	NR	720	15	NR	850	0	NR	980	0	NR
465	76	NR	595	310	NR	725	13	NR	855	0	NR	985	0	NR
470	53	NR	600	307	NR	730	11	NR	860	0	NR	990	0	NR
475	39	NR	605	303	NR	735	9	NR	865	0	NR	995	0	NR
480	35	NR	610	331	NR	740	8	NR	870	0	NR	1000	0	NR
485	36	NR	615	353	NR	745	7	NR	875	0	NR			

REPORT NUMBER: SP1-2506-472-2

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR

S/P: 1.27

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	43	NR	620	294	NR	750	6	NR	880	0	NR
365	0	NR	495	59	NR	625	294	NR	755	5	NR	885	0	NR
370	0	NR	500	81	NR	630	1000	NR	760	4	NR	890	0	NR
375	0	NR	505	109	NR	635	637	NR	765	4	NR	895	0	NR
380	0	NR	510	135	NR	640	175	NR	770	3	NR	900	0	NR
385	0	NR	515	160	NR	645	171	NR	775	3	NR	905	0	NR
390	1	NR	520	180	NR	650	146	NR	780	2	NR	910	0	NR
395	1	NR	525	195	NR	655	119	NR	785	2	NR	915	0	NR
400	2	NR	530	207	NR	660	99	NR	790	2	NR	920	0	NR
405	3	NR	535	218	NR	665	82	NR	795	2	NR	925	0	NR
410	5	NR	540	227	NR	670	76	NR	800	1	NR	930	0	NR
415	10	NR	545	237	NR	675	61	NR	805	1	NR	935	0	NR
420	20	NR	550	247	NR	680	52	NR	810	1	NR	940	0	NR
425	35	NR	555	259	NR	685	44	NR	815	1	NR	945	0	NR
430	58	NR	560	271	NR	690	38	NR	820	1	NR	950	0	NR
435	90	NR	565	283	NR	695	33	NR	825	1	NR	955	0	NR
440	135	NR	570	293	NR	700	27	NR	830	1	NR	960	0	NR
445	204	NR	575	303	NR	705	24	NR	835	1	NR	965	0	NR
450	233	NR	580	310	NR	710	20	NR	840	0	NR	970	0	NR
455	153	NR	585	313	NR	715	17	NR	845	0	NR	975	0	NR
460	98	NR	590	314	NR	720	15	NR	850	0	NR	980	0	NR
465	76	NR	595	310	NR	725	13	NR	855	0	NR	985	0	NR
470	53	NR	600	307	NR	730	11	NR	860	0	NR	990	0	NR
475	39	NR	605	303	NR	735	9	NR	865	0	NR	995	0	NR
480	35	NR	610	331	NR	740	8	NR	870	0	NR	1000	0	NR
485	36	NR	615	353	NR	745	7	NR	875	0	NR			

REPORT NUMBER: SP1-2506-472-2

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 2.34




λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	43	NR	620	294	NR	750	6	NR	880	0	NR
365	0	NR	495	59	NR	625	294	NR	755	5	NR	885	0	NR
370	0	NR	500	81	NR	630	1000	NR	760	4	NR	890	0	NR
375	0	NR	505	109	NR	635	637	NR	765	4	NR	895	0	NR
380	0	NR	510	135	NR	640	175	NR	770	3	NR	900	0	NR
385	0	NR	515	160	NR	645	171	NR	775	3	NR	905	0	NR
390	1	NR	520	180	NR	650	146	NR	780	2	NR	910	0	NR
395	1	NR	525	195	NR	655	119	NR	785	2	NR	915	0	NR
400	2	NR	530	207	NR	660	99	NR	790	2	NR	920	0	NR
405	3	NR	535	218	NR	665	82	NR	795	2	NR	925	0	NR
410	5	NR	540	227	NR	670	76	NR	800	1	NR	930	0	NR
415	10	NR	545	237	NR	675	61	NR	805	1	NR	935	0	NR
420	20	NR	550	247	NR	680	52	NR	810	1	NR	940	0	NR
425	35	NR	555	259	NR	685	44	NR	815	1	NR	945	0	NR
430	58	NR	560	271	NR	690	38	NR	820	1	NR	950	0	NR
435	90	NR	565	283	NR	695	33	NR	825	1	NR	955	0	NR
440	135	NR	570	293	NR	700	27	NR	830	1	NR	960	0	NR
445	204	NR	575	303	NR	705	24	NR	835	1	NR	965	0	NR
450	233	NR	580	310	NR	710	20	NR	840	0	NR	970	0	NR
455	153	NR	585	313	NR	715	17	NR	845	0	NR	975	0	NR
460	98	NR	590	314	NR	720	15	NR	850	0	NR	980	0	NR
465	76	NR	595	310	NR	725	13	NR	855	0	NR	985	0	NR
470	53	NR	600	307	NR	730	11	NR	860	0	NR	990	0	NR
475	39	NR	605	303	NR	735	9	NR	865	0	NR	995	0	NR
480	35	NR	610	331	NR	740	8	NR	870	0	NR	1000	0	NR
485	36	NR	615	353	NR	745	7	NR	875	0	NR			

Summary

$R_f = 81.2$
 $R_g = 101.5$
 CIE $R_a = 83.4$
 $R_9 = 29.4$




Color Vector Graphics




Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 86	CES26 = 71	CES51 = 89	CES76 = 65
CES02 = 63	CES27 = 89	CES52 = 89	CES77 = 82
CES03 = 31	CES28 = 86	CES53 = 80	CES78 = 67
CES04 = 70	CES29 = 68	CES54 = 92	CES79 = 89
CES05 = 50	CES30 = 77	CES55 = 90	CES80 = 85
CES06 = 51	CES31 = 70	CES56 = 81	CES81 = 75
CES07 = 43	CES32 = 64	CES57 = 79	CES82 = 93
CES08 = 41	CES33 = 74	CES58 = 81	CES83 = 89
CES09 = 29	CES34 = 76	CES59 = 92	CES84 = 91
CES10 = 76	CES35 = 87	CES60 = 96	CES85 = 81
CES11 = 59	CES36 = 99	CES61 = 91	CES86 = 74
CES12 = 65	CES37 = 81	CES62 = 93	CES87 = 83
CES13 = 44	CES38 = 83	CES63 = 79	CES88 = 86
CES14 = 74	CES39 = 94	CES64 = 81	CES89 = 74
CES15 = 72	CES40 = 89	CES65 = 78	CES90 = 85
CES16 = 48	CES41 = 88	CES66 = 76	CES91 = 87
CES17 = 50	CES42 = 80	CES67 = 74	CES92 = 73
CES18 = 57	CES43 = 75	CES68 = 79	CES93 = 84
CES19 = 72	CES44 = 99	CES69 = 83	CES94 = 64
CES20 = 67	CES45 = 83	CES70 = 72	CES95 = 80
CES21 = 87	CES46 = 82	CES71 = 70	CES96 = 86
CES22 = 79	CES47 = 79	CES72 = 90	CES97 = 85
CES23 = 92	CES48 = 78	CES73 = 65	CES98 = 83
CES24 = 91	CES49 = 79	CES74 = 94	CES99 = 82
CES25 = 72	CES50 = 88	CES75 = 70	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)