

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: METALUX

Report Number: P1433407

Luminaire Tested: EHBR1-60-UNV-W-L930-UPL30

Issue Date: 3/20/2026

Test Information

Test Method: LM-79-2019
Report Number: P1433407
REPORT IS A COMBINATION OF REPORTS P1431920 AND P1431635
Test Lab: INNOVATION CENTER
Issue Date: 3/20/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: METALUX
Catalog Number: EHBR1-60-UNV-W-L930-UPL30
Description: Elevate Round Highbay at, 60000 lumens, 3000K 90CRI LEDs with W lens
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 55371.3 lumens
Efficiency: N/A
Efficacy: 157.1 lumens/watt
Spacing Criteria (0/90/45): 1.54 / 1.54 / 1.31
Luminous Opening: Vertical Cylinder (Dia: 1.71' x H: 0.1')
CIE Type: Direct

Input Watts (W): 352.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1433407
CATALOG NUMBER: EHBR1-60-UNV-W-L930-UPL30

Luminous Intensity Polar Plot





TEST NUMBER: P1433407
 CATALOG NUMBER: EHBR1-60-UNV-W-L930-UPL30

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	118	118	118	118	115	115	115	115	108	108	108	103	103	103	98	98	98	98	98	98	95
1	110	106	103	100	107	104	101	98	99	96	94	94	92	90	90	88	87	87	87	87	85
2	102	96	90	86	99	93	89	84	89	85	82	85	82	79	82	79	77	77	77	77	75
3	95	86	80	74	92	85	78	74	81	76	72	78	74	70	75	71	68	68	68	68	66
4	88	78	71	65	86	77	70	65	74	68	63	71	66	62	68	64	61	61	61	61	59
5	82	71	64	58	80	70	63	58	67	61	57	65	60	56	63	58	55	55	55	55	53
6	76	65	57	52	74	64	57	51	62	55	51	60	54	50	58	53	49	49	49	49	47
7	71	60	52	47	70	59	51	46	57	50	46	55	49	45	53	48	44	44	44	44	43
8	67	55	47	42	65	54	47	42	52	46	41	51	45	41	49	44	40	40	40	40	39
9	63	51	43	38	61	50	43	38	48	42	38	47	41	37	46	41	37	37	37	37	35
10	59	47	40	35	57	46	39	35	45	39	34	44	38	34	43	37	34	34	34	34	32

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	103532	103532	103532
5°	104220	104220	104220
10°	107841	107841	107841
15°	114674	114674	114674
20°	124310	124310	124310
25°	135137	135137	135137
30°	141646	141646	141646
35°	134824	134824	134824
40°	106983	106983	106983
45°	66125	66125	66125
50°	38290	38290	38290
55°	28970	28970	28970
60°	24851	24851	24851
65°	22445	22445	22445
70°	20649	20649	20649
75°	18241	18241	18241
80°	14869	14869	14869
85°	8764	8764	8764

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 66125 cd/sqm



TEST NUMBER: P1433407
 CATALOG NUMBER: EHBR1-60-UNV-W-L930-UPL30

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	2145.0	3.9
10°-20°	6876.7	12.4
20°-30°	12412.6	22.4
30°-40°	14999.4	27.1
40°-50°	8569.6	15.5
50°-60°	3629.5	6.6
60°-70°	2341.0	4.2
70°-80°	1361.2	2.5
80°-90°	365.0	0.7
90°-100°	76.9	0.1
100°-110°	473.3	0.9
110°-120°	845.4	1.5
120°-130°	497.4	0.9
130°-140°	308.7	0.6
140°-150°	217.5	0.4
150°-160°	142.7	0.3
160°-170°	82.1	0.1
170°-180°	27.3	0.0
0°-30°	21434.3	38.7
0°-40°	36433.7	65.8
0°-60°	48632.9	87.8
0°-90°	52700.1	95.2
90°-120°	1395.5	2.5
90°-150°	2419.1	4.4
90°-180°	2671.0	4.8
0°-180°	55371.3	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	22046	22046	22046	22046	22046	
5°	22253	22253	22253	22253	22253	2145
15°	24058	24058	24058	24058	24058	6877
25°	26987	26987	26987	26987	26987	12413
35°	24745	24745	24745	24745	24745	14999
45°	10699	10699	10699	10699	10699	8570
55°	3915	3915	3915	3915	3915	3630
65°	2343	2343	2343	2343	2343	2341
75°	1285	1285	1285	1285	1285	1361
85°	301	301	301	301	301	347
90°	21	34	56	36	21	23
95°	35	58	124	62	40	33
105°	166	326	831	360	219	222
115°	761	800	983	942	936	701
125°	550	514	528	535	600	501
135°	406	394	407	383	382	317
145°	339	334	354	350	348	215
155°	300	297	311	311	311	140
165°	284	284	291	291	290	81
175°	282	282	287	287	287	27
180°	286	286	286	286	286	



TEST NUMBER: P1433407

CATALOG NUMBER: EHBR1-60-UNV-W-L930-UPL30

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	22046.4	22046.4	22046.4	22046.4	22046.4
2.5°	22120.4	22120.4	22120.4	22120.4	22120.4
5°	22252.6	22252.6	22252.6	22252.6	22252.6
7.5°	22512.3	22512.3	22512.3	22512.3	22512.3
10°	22912.3	22912.3	22912.3	22912.3	22912.3
12.5°	23431.9	23431.9	23431.9	23431.9	23431.9
15°	24058.1	24058.1	24058.1	24058.1	24058.1
17.5°	24775.0	24775.0	24775.0	24775.0	24775.0
20°	25549.3	25549.3	25549.3	25549.3	25549.3
22.5°	26328.7	26328.7	26328.7	26328.7	26328.7
25°	26986.7	26986.7	26986.7	26986.7	26986.7
27.5°	27340.7	27340.7	27340.7	27340.7	27340.7
30°	27245.6	27245.6	27245.6	27245.6	27245.6
32.5°	26438.0	26438.0	26438.0	26438.0	26438.0
35°	24745.1	24745.1	24745.1	24745.1	24745.1
37.5°	22105.4	22105.4	22105.4	22105.4	22105.4
40°	18542.8	18542.8	18542.8	18542.8	18542.8
42.5°	14513.3	14513.3	14513.3	14513.3	14513.3
45°	10698.7	10698.7	10698.7	10698.7	10698.7
47.5°	7646.8	7646.8	7646.8	7646.8	7646.8
50°	5706.5	5706.5	5706.5	5706.5	5706.5
52.5°	4620.5	4620.5	4620.5	4620.5	4620.5
55°	3915.0	3915.0	3915.0	3915.0	3915.0
57.5°	3399.8	3399.8	3399.8	3399.8	3399.8
60°	2987.5	2987.5	2987.5	2987.5	2987.5
62.5°	2644.1	2644.1	2644.1	2644.1	2644.1
65°	2342.8	2342.8	2342.8	2342.8	2342.8
67.5°	2076.8	2076.8	2076.8	2076.8	2076.8
70°	1811.8	1811.8	1811.8	1811.8	1811.8
72.5°	1547.5	1547.5	1547.5	1547.5	1547.5
75°	1285.0	1285.0	1285.0	1285.0	1285.0
77.5°	1032.3	1032.3	1032.3	1032.3	1032.3
80°	782.2	782.2	782.2	782.2	782.2
82.5°	536.4	536.4	536.4	536.4	536.4
85°	301.2	301.2	301.2	301.2	301.2
87.5°	95.1	95.1	95.1	95.1	95.1
90°	21.4	33.5	56.1	36.5	21.4
92.5°	29.6	49.2	88.5	46.2	26.6
95°	35.0	57.7	124.0	62.2	39.6
97.5°	44.0	63.7	142.2	75.7	60.7
100°	57.7	74.2	220.7	92.4	80.3
102.5°	96.9	155.8	466.8	172.4	121.1
105°	166.4	326.4	830.7	359.7	219.2
107.5°	287.1	583.1	1094.9	635.9	413.9
110°	535.7	774.2	1148.7	873.9	662.5



TEST NUMBER: P1433407

CATALOG NUMBER: EHBR1-60-UNV-W-L930-UPL30

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	722.9	831.6	1100.4	964.5	861.8
115°	760.6	799.9	982.6	941.8	935.8
117.5°	734.9	730.5	834.6	846.7	904.1
120°	680.6	650.4	697.2	739.5	816.5
122.5°	612.7	576.4	597.6	629.2	706.3
125°	550.1	513.9	527.5	535.0	600.0
127.5°	494.3	470.1	477.7	468.6	509.4
130°	457.3	436.2	446.7	425.6	445.2
132.5°	427.4	413.8	425.9	400.2	406.3
135°	405.6	393.5	407.2	383.0	381.5
137.5°	386.9	376.3	390.0	371.8	367.2
140°	370.5	361.5	376.6	363.1	360.0
142.5°	351.8	345.8	363.9	354.9	351.8
145°	339.1	334.5	354.1	349.6	348.1
147.5°	327.9	324.8	343.0	341.5	341.5
150°	317.3	314.3	332.4	330.9	332.4
152.5°	306.7	303.7	320.3	318.8	320.3
155°	300.0	297.0	310.7	310.7	310.7
157.5°	294.0	292.5	303.1	303.1	303.1
160°	290.4	288.9	297.9	297.9	296.4
162.5°	286.8	285.3	295.8	294.3	294.3
165°	283.7	283.7	291.3	291.3	289.8
167.5°	283.7	282.2	289.8	289.8	288.3
170°	282.2	282.2	288.3	286.8	285.3
172.5°	283.1	283.1	289.2	287.7	286.1
175°	282.5	282.5	287.0	287.0	287.0
177.5°	284.0	284.0	287.0	287.0	285.5
180°	286.4	286.4	286.4	286.4	286.4



TEST NUMBER: P1433407
 CATALOG NUMBER: EHBR1-60-UNV-W-L930-UPL30

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	20.23	21.45	20.68	21.87	22.31	20.23	21.45	20.68	21.87	22.31
	3H	21.73	22.82	22.19	23.25	23.73	21.73	22.82	22.19	23.25	23.73
	4H	22.29	23.31	22.77	23.75	24.26	22.29	23.31	22.77	23.75	24.26
	6H	22.67	23.61	23.17	24.08	24.59	22.67	23.61	23.17	24.08	24.59
	8H	22.77	23.66	23.29	24.15	24.67	22.77	23.66	23.29	24.15	24.67
	12H	22.81	23.66	23.33	24.14	24.68	22.81	23.66	23.33	24.14	24.68
4H	2H	20.67	21.69	21.16	22.14	22.64	20.67	21.69	21.16	22.14	22.64
	3H	22.39	23.23	22.89	23.73	24.25	22.39	23.23	22.89	23.73	24.25
	4H	23.07	23.82	23.59	24.33	24.89	23.07	23.82	23.59	24.33	24.89
	6H	23.57	24.22	24.11	24.75	25.33	23.57	24.22	24.11	24.75	25.33
	8H	23.70	24.31	24.25	24.84	25.42	23.70	24.31	24.25	24.84	25.42
	12H	23.76	24.30	24.33	24.87	25.45	23.76	24.30	24.33	24.87	25.45
8H	4H	23.28	23.88	23.83	24.42	25.00	23.28	23.88	23.83	24.42	25.00
	6H	23.87	24.37	24.45	24.95	25.54	23.87	24.37	24.45	24.95	25.54
	8H	24.06	24.50	24.66	25.10	25.70	24.06	24.50	24.66	25.10	25.70
	12H	24.17	24.56	24.76	25.14	25.81	24.17	24.56	24.76	25.14	25.81
12H	4H	23.27	23.81	23.84	24.38	24.96	23.27	23.81	23.84	24.38	24.96
	6H	23.89	24.33	24.49	24.93	25.53	23.89	24.33	24.49	24.93	25.53
	8H	24.11	24.50	24.71	25.08	25.76	24.11	24.50	24.71	25.08	25.76

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Report Prepared for

Cooper Lighting Solutions

Metalux

Report Number: SP1-2506-472-5

Test Date: 08/01/2025

Luminaire Tested: EHBR-60-L930-N

Data in this report applies to families of products including EHBR-60-L930-N

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2506-472-5
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 08/05/2025
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: Metalux
 Catalog Number: **EHBR-60-L930-N**
 Description: Elevate Round Highbay at, 60000 lumens, 3000K 90CRI LEDs with N lens

Spectral Parameters

CCT (K): 2996
 CIE u': 0.2519
 CIE v': 0.5169
 Duv: -0.0033
 CIE x: 0.4325
 CIE y: 0.3945
 CIE z: 0.1730
 Peak Wavelength (nm): 630
 Dominant Wavelength (nm): 584
 Purity: 48.21818
 Rf: 91.3
 Rg: 102

CRI (Ra):	94.4		
R1:	96.8	R9:	61.4
R2:	98.1	R10:	94.4
R3:	97.8	R11:	95.7
R4:	95.6	R12:	88.5
R5:	96.9	R13:	97.3
R6:	95.7	R14:	97.8
R7:	90.9	R15:	92.3
R8:	83.0		



Test Conditions


Stabilization Time: 40M
 Operation Time: 1H 40M
 Sphere Temperature (°C): 25.0

REPORT NUMBER: SP1-2506-472-5

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	76INCH SPHERE IN0058	6/16/2025	12/16/2025
Power Meter	XITRON INXT2011004	1/21/2025	1/21/2026
AC Power Source	CHROMA 61603 IN0063	10/22/2024	10/22/2025
DC Power Source	AGILENT E3634A IN0208	10/22/2024	10/22/2025
Sphere Thermometer	ONSET IN0085	10/22/2024	10/22/2025
Room Thermometer	ONSET IN0046	10/22/2024	10/22/2025

REPORT NUMBER: SP1-2506-472-5

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



CCT = 2996K
 CIE x = 0.4325
 CIE y = 0.3945
 Duv = -0.0033

Point lies inside the ANSI 3000K 7-step quadrangle

REPORT NUMBER: SP1-2506-472-5

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	101	NR	620	317	NR	750	7	NR	880	0	NR
365	0	NR	495	121	NR	625	320	NR	755	6	NR	885	0	NR
370	0	NR	500	141	NR	630	1000	NR	760	5	NR	890	0	NR
375	0	NR	505	158	NR	635	651	NR	765	4	NR	895	0	NR
380	0	NR	510	171	NR	640	207	NR	770	4	NR	900	0	NR
385	0	NR	515	182	NR	645	201	NR	775	3	NR	905	0	NR
390	0	NR	520	189	NR	650	174	NR	780	3	NR	910	0	NR
395	1	NR	525	194	NR	655	146	NR	785	2	NR	915	0	NR
400	1	NR	530	199	NR	660	124	NR	790	2	NR	920	0	NR
405	3	NR	535	205	NR	665	105	NR	795	2	NR	925	0	NR
410	4	NR	540	210	NR	670	96	NR	800	1	NR	930	0	NR
415	7	NR	545	216	NR	675	79	NR	805	1	NR	935	0	NR
420	13	NR	550	222	NR	680	67	NR	810	1	NR	940	0	NR
425	22	NR	555	230	NR	685	58	NR	815	1	NR	945	0	NR
430	37	NR	560	240	NR	690	49	NR	820	1	NR	950	0	NR
435	60	NR	565	248	NR	695	42	NR	825	1	NR	955	0	NR
440	101	NR	570	258	NR	700	36	NR	830	1	NR	960	0	NR
445	172	NR	575	268	NR	705	30	NR	835	1	NR	965	0	NR
450	223	NR	580	278	NR	710	26	NR	840	1	NR	970	0	NR
455	167	NR	585	287	NR	715	22	NR	845	0	NR	975	0	NR
460	126	NR	590	295	NR	720	19	NR	850	0	NR	980	0	NR
465	111	NR	595	298	NR	725	16	NR	855	0	NR	985	0	NR
470	86	NR	600	303	NR	730	14	NR	860	0	NR	990	0	NR
475	74	NR	605	307	NR	735	12	NR	865	0	NR	995	0	NR
480	77	NR	610	341	NR	740	10	NR	870	0	NR	1000	0	NR
485	86	NR	615	368	NR	745	8	NR	875	0	NR			

REPORT NUMBER: SP1-2506-472-5

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR

S/P: 1.44

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	101	NR	620	317	NR	750	7	NR	880	0	NR
365	0	NR	495	121	NR	625	320	NR	755	6	NR	885	0	NR
370	0	NR	500	141	NR	630	1000	NR	760	5	NR	890	0	NR
375	0	NR	505	158	NR	635	651	NR	765	4	NR	895	0	NR
380	0	NR	510	171	NR	640	207	NR	770	4	NR	900	0	NR
385	0	NR	515	182	NR	645	201	NR	775	3	NR	905	0	NR
390	0	NR	520	189	NR	650	174	NR	780	3	NR	910	0	NR
395	1	NR	525	194	NR	655	146	NR	785	2	NR	915	0	NR
400	1	NR	530	199	NR	660	124	NR	790	2	NR	920	0	NR
405	3	NR	535	205	NR	665	105	NR	795	2	NR	925	0	NR
410	4	NR	540	210	NR	670	96	NR	800	1	NR	930	0	NR
415	7	NR	545	216	NR	675	79	NR	805	1	NR	935	0	NR
420	13	NR	550	222	NR	680	67	NR	810	1	NR	940	0	NR
425	22	NR	555	230	NR	685	58	NR	815	1	NR	945	0	NR
430	37	NR	560	240	NR	690	49	NR	820	1	NR	950	0	NR
435	60	NR	565	248	NR	695	42	NR	825	1	NR	955	0	NR
440	101	NR	570	258	NR	700	36	NR	830	1	NR	960	0	NR
445	172	NR	575	268	NR	705	30	NR	835	1	NR	965	0	NR
450	223	NR	580	278	NR	710	26	NR	840	1	NR	970	0	NR
455	167	NR	585	287	NR	715	22	NR	845	0	NR	975	0	NR
460	126	NR	590	295	NR	720	19	NR	850	0	NR	980	0	NR
465	111	NR	595	298	NR	725	16	NR	855	0	NR	985	0	NR
470	86	NR	600	303	NR	730	14	NR	860	0	NR	990	0	NR
475	74	NR	605	307	NR	735	12	NR	865	0	NR	995	0	NR
480	77	NR	610	341	NR	740	10	NR	870	0	NR	1000	0	NR
485	86	NR	615	368	NR	745	8	NR	875	0	NR			

REPORT NUMBER: SP1-2506-472-5

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 2.85

λ (nm)	Power W [^] /nm	Lumens (ϕ /nm)	λ (nm)	Power W [^] /nm	Lumens (ϕ /nm)	λ (nm)	Power W [^] /nm	Lumens (ϕ /nm)	λ (nm)	Power W [^] /nm	Lumens (ϕ /nm)	λ (nm)	Power W [^] /nm	Lumens (ϕ /nm)
360	0	NR	490	101	NR	620	317	NR	750	7	NR	880	0	NR
365	0	NR	495	121	NR	625	320	NR	755	6	NR	885	0	NR
370	0	NR	500	141	NR	630	1000	NR	760	5	NR	890	0	NR
375	0	NR	505	158	NR	635	651	NR	765	4	NR	895	0	NR
380	0	NR	510	171	NR	640	207	NR	770	4	NR	900	0	NR
385	0	NR	515	182	NR	645	201	NR	775	3	NR	905	0	NR
390	0	NR	520	189	NR	650	174	NR	780	3	NR	910	0	NR
395	1	NR	525	194	NR	655	146	NR	785	2	NR	915	0	NR
400	1	NR	530	199	NR	660	124	NR	790	2	NR	920	0	NR
405	3	NR	535	205	NR	665	105	NR	795	2	NR	925	0	NR
410	4	NR	540	210	NR	670	96	NR	800	1	NR	930	0	NR
415	7	NR	545	216	NR	675	79	NR	805	1	NR	935	0	NR
420	13	NR	550	222	NR	680	67	NR	810	1	NR	940	0	NR
425	22	NR	555	230	NR	685	58	NR	815	1	NR	945	0	NR
430	37	NR	560	240	NR	690	49	NR	820	1	NR	950	0	NR
435	60	NR	565	248	NR	695	42	NR	825	1	NR	955	0	NR
440	101	NR	570	258	NR	700	36	NR	830	1	NR	960	0	NR
445	172	NR	575	268	NR	705	30	NR	835	1	NR	965	0	NR
450	223	NR	580	278	NR	710	26	NR	840	1	NR	970	0	NR
455	167	NR	585	287	NR	715	22	NR	845	0	NR	975	0	NR
460	126	NR	590	295	NR	720	19	NR	850	0	NR	980	0	NR
465	111	NR	595	298	NR	725	16	NR	855	0	NR	985	0	NR
470	86	NR	600	303	NR	730	14	NR	860	0	NR	990	0	NR
475	74	NR	605	307	NR	735	12	NR	865	0	NR	995	0	NR
480	77	NR	610	341	NR	740	10	NR	870	0	NR	1000	0	NR
485	86	NR	615	368	NR	745	8	NR	875	0	NR			

Summary

$R_f = 91.3$
 $R_g = 102$
 $CIE R_a = 94.4$
 $R_9 = 61.4$



Color Vector Graphics



Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 86	CES26 = 91	CES51 = 96	CES76 = 89
CES02 = 63	CES27 = 96	CES52 = 95	CES77 = 85
CES03 = 32	CES28 = 96	CES53 = 93	CES78 = 86
CES04 = 70	CES29 = 90	CES54 = 98	CES79 = 89
CES05 = 51	CES30 = 96	CES55 = 98	CES80 = 91
CES06 = 51	CES31 = 90	CES56 = 95	CES81 = 72
CES07 = 44	CES32 = 84	CES57 = 95	CES82 = 95
CES08 = 42	CES33 = 91	CES58 = 95	CES83 = 93
CES09 = 29	CES34 = 92	CES59 = 99	CES84 = 96
CES10 = 76	CES35 = 96	CES60 = 96	CES85 = 80
CES11 = 59	CES36 = 90	CES61 = 96	CES86 = 77
CES12 = 65	CES37 = 94	CES62 = 95	CES87 = 91
CES13 = 44	CES38 = 99	CES63 = 94	CES88 = 96
CES14 = 74	CES39 = 97	CES64 = 96	CES89 = 82
CES15 = 72	CES40 = 94	CES65 = 92	CES90 = 97
CES16 = 48	CES41 = 94	CES66 = 95	CES91 = 82
CES17 = 50	CES42 = 91	CES67 = 94	CES92 = 78
CES18 = 57	CES43 = 88	CES68 = 93	CES93 = 87
CES19 = 72	CES44 = 99	CES69 = 94	CES94 = 73
CES20 = 67	CES45 = 93	CES70 = 90	CES95 = 85
CES21 = 86	CES46 = 93	CES71 = 90	CES96 = 92
CES22 = 79	CES47 = 86	CES72 = 96	CES97 = 93
CES23 = 92	CES48 = 95	CES73 = 85	CES98 = 94
CES24 = 91	CES49 = 91	CES74 = 90	CES99 = 93
CES25 = 72	CES50 = 96	CES75 = 90	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)