

Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: METALUX

Report Number: P1431667

Luminaire Tested: EHBR1-12-UNV-W-L950

Issue Date: 3/13/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1431667  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2601-654-2)  
Test Lab: INNOVATION CENTER  
Issue Date: 3/13/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: METALUX  
Catalog Number: EHBR1-12-UNV-W-L950  
Description: Elevate Round Highbay at, 12000 lumens, 5000K 90CRI LEDs with W lens  
Light Source: -  
Ballast/Driver: -


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 11380.8 lumens  
Efficiency: N/A  
Efficacy: 175.9 lumens/watt  
Spacing Criteria (0/90/45): 1.54 / 1.54 / 1.31  
Luminous Opening: Circular (Dia: 1.71' x H: 0')  
CIE Type: Direct

Input Watts (W): 64.7  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1431667  
CATALOG NUMBER: EHBR1-12-UNV-W-L950

### Luminous Intensity Polar Plot





TEST NUMBER: P1431667  
 CATALOG NUMBER: EHBR1-12-UNV-W-L950

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	111	108	104	101	109	105	102	100	101	99	96	97	95	94	94	92	91	89
2	103	97	91	87	101	95	90	86	92	88	84	89	85	82	86	83	80	78
3	96	88	81	76	94	86	80	75	83	78	74	81	76	72	78	74	71	69
4	89	79	72	67	87	78	71	66	76	70	65	74	69	64	72	67	64	62
5	83	72	65	59	81	71	64	59	69	63	58	67	62	58	66	61	57	55
6	78	66	58	53	76	65	58	53	64	57	52	62	56	52	60	55	51	50
7	72	61	53	48	71	60	53	47	58	52	47	57	51	47	56	51	47	45
8	68	56	48	43	66	55	48	43	54	47	43	53	47	43	52	46	42	41
9	64	52	44	39	62	51	44	39	50	43	39	49	43	39	48	43	39	37
10	60	48	41	36	59	47	40	36	46	40	36	45	40	35	45	39	35	34

**AVERAGE LUMINANCE (cd/sqm):**

	0°	45°	90°
0°	22346	22346	22346
5°	22641	22641	22641
10°	23582	23582	23582
15°	25245	25245	25245
20°	27558	27558	27558
25°	30181	30181	30181
30°	31887	31887	31887
35°	30618	30618	30618
40°	24535	24535	24535
45°	15335	15335	15335
50°	8998	8998	8998
55°	6918	6918	6918
60°	6056	6056	6056
65°	5618	5618	5618
70°	5370	5370	5370
75°	5031	5031	5031
80°	4565	4565	4565
85°	3502	3502	3502

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 15335 cd/sqm



TEST NUMBER: P1431667  
 CATALOG NUMBER: EHBR1-12-UNV-W-L950

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	463.0	4.1
10°-20°	1484.2	13.0
20°-30°	2679.1	23.5
30°-40°	3237.4	28.4
40°-50°	1849.6	16.3
50°-60°	783.4	6.9
60°-70°	505.3	4.4
70°-80°	293.8	2.6
80°-90°	77.7	0.7
90°-100°	0.4	0.0
100°-110°	0.4	0.0
110°-120°	0.6	0.0
120°-130°	0.6	0.0
130°-140°	1.2	0.0
140°-150°	1.5	0.0
150°-160°	1.3	0.0
160°-170°	0.9	0.0
170°-180°	0.3	0.0
0°-30°	4626.3	40.6
0°-40°	7863.6	69.1
0°-60°	10496.6	92.2
0°-90°	11373.5	99.9
90°-120°	1.4	0.0
90°-150°	4.7	0.0
90°-180°	7.0	0.1
0°-180°	11380.8	100.0

**CANDELA DISTRIBUTION:**

	0°	22.5°	45°	67.5°	90°	Flux
0°	4758	4758	4758	4758	4758	
5°	4803	4803	4803	4803	4803	463
15°	5193	5193	5193	5193	5193	1484
25°	5825	5825	5825	5825	5825	2679
35°	5341	5341	5341	5341	5341	3237
45°	2309	2309	2309	2309	2309	1850
55°	845	845	845	845	845	783
65°	506	506	506	506	506	505
75°	277	277	277	277	277	294
85°	65	65	65	65	65	75
90°	0	0	0	0	0	3
95°	0	0	0	0	0	0
105°	0	0	0	0	0	0
115°	1	1	1	1	1	1
125°	1	1	1	1	1	1
135°	2	2	2	2	2	1
145°	2	2	2	2	2	2
155°	3	3	3	3	3	1
165°	3	3	3	3	3	1
175°	4	4	4	4	4	0
180°	4	4	4	4	4	



TEST NUMBER: P1431667  
 CATALOG NUMBER: EHBR1-12-UNV-W-L950

**CANDELA DISTRIBUTION (FULL):**

	0°	22.5°	45°	67.5°	90°
0°	4758.4	4758.4	4758.4	4758.4	4758.4
2.5°	4774.3	4774.3	4774.3	4774.3	4774.3
5°	4802.9	4802.9	4802.9	4802.9	4802.9
7.5°	4859.0	4859.0	4859.0	4859.0	4859.0
10°	4945.3	4945.3	4945.3	4945.3	4945.3
12.5°	5057.4	5057.4	5057.4	5057.4	5057.4
15°	5192.6	5192.6	5192.6	5192.6	5192.6
17.5°	5347.3	5347.3	5347.3	5347.3	5347.3
20°	5514.4	5514.4	5514.4	5514.4	5514.4
22.5°	5682.6	5682.6	5682.6	5682.6	5682.6
25°	5824.7	5824.7	5824.7	5824.7	5824.7
27.5°	5901.1	5901.1	5901.1	5901.1	5901.1
30°	5880.5	5880.5	5880.5	5880.5	5880.5
32.5°	5706.2	5706.2	5706.2	5706.2	5706.2
35°	5340.8	5340.8	5340.8	5340.8	5340.8
37.5°	4771.1	4771.1	4771.1	4771.1	4771.1
40°	4002.2	4002.2	4002.2	4002.2	4002.2
42.5°	3132.5	3132.5	3132.5	3132.5	3132.5
45°	2309.1	2309.1	2309.1	2309.1	2309.1
47.5°	1650.5	1650.5	1650.5	1650.5	1650.5
50°	1231.6	1231.6	1231.6	1231.6	1231.6
52.5°	997.3	997.3	997.3	997.3	997.3
55°	845.0	845.0	845.0	845.0	845.0
57.5°	733.8	733.8	733.8	733.8	733.8
60°	644.8	644.8	644.8	644.8	644.8
62.5°	570.7	570.7	570.7	570.7	570.7
65°	505.6	505.6	505.6	505.6	505.6
67.5°	448.3	448.3	448.3	448.3	448.3
70°	391.1	391.1	391.1	391.1	391.1
72.5°	334.0	334.0	334.0	334.0	334.0
75°	277.3	277.3	277.3	277.3	277.3
77.5°	222.8	222.8	222.8	222.8	222.8
80°	168.8	168.8	168.8	168.8	168.8
82.5°	115.8	115.8	115.8	115.8	115.8
85°	65.0	65.0	65.0	65.0	65.0
87.5°	20.5	20.5	20.5	20.5	20.5
90°	0.4	0.4	0.4	0.4	0.4
92.5°	0.2	0.2	0.2	0.2	0.2
95°	0.4	0.4	0.4	0.4	0.4
97.5°	0.4	0.4	0.4	0.4	0.4
100°	0.4	0.4	0.4	0.4	0.4
102.5°	0.4	0.4	0.4	0.4	0.4
105°	0.4	0.4	0.4	0.4	0.4
107.5°	0.4	0.4	0.4	0.4	0.4
110°	0.6	0.6	0.6	0.6	0.6



TEST NUMBER: P1431667  
 CATALOG NUMBER: EHBR1-12-UNV-W-L950

**CANDELA DISTRIBUTION (continued):**

	0°	22.5°	45°	67.5°	90°
112.5°	0.6	0.6	0.6	0.6	0.6
115°	0.6	0.6	0.6	0.6	0.6
117.5°	0.6	0.6	0.6	0.6	0.6
120°	0.6	0.6	0.6	0.6	0.6
122.5°	0.6	0.6	0.6	0.6	0.6
125°	0.7	0.7	0.7	0.7	0.7
127.5°	0.7	0.7	0.7	0.7	0.7
130°	0.9	0.9	0.9	0.9	0.9
132.5°	1.3	1.3	1.3	1.3	1.3
135°	1.5	1.5	1.5	1.5	1.5
137.5°	1.7	1.7	1.7	1.7	1.7
140°	2.1	2.1	2.1	2.1	2.1
142.5°	2.3	2.3	2.3	2.3	2.3
145°	2.5	2.5	2.5	2.5	2.5
147.5°	2.7	2.7	2.7	2.7	2.7
150°	2.7	2.7	2.7	2.7	2.7
152.5°	2.7	2.7	2.7	2.7	2.7
155°	2.9	2.9	2.9	2.9	2.9
157.5°	2.9	2.9	2.9	2.9	2.9
160°	3.1	3.1	3.1	3.1	3.1
162.5°	3.3	3.3	3.3	3.3	3.3
165°	3.3	3.3	3.3	3.3	3.3
167.5°	3.3	3.3	3.3	3.3	3.3
170°	3.3	3.3	3.3	3.3	3.3
172.5°	3.4	3.4	3.4	3.4	3.4
175°	3.6	3.6	3.6	3.6	3.6
177.5°	3.6	3.6	3.6	3.6	3.6
180°	3.8	3.8	3.8	3.8	3.8



TEST NUMBER: P1431667  
 CATALOG NUMBER: EHBR1-12-UNV-W-L950

**CIE UGR TABLE:**

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	15.75	17.06	16.12	17.38	17.69	15.75	17.06	16.12	17.38	17.69
	3H	17.34	18.51	17.72	18.84	19.20	17.34	18.51	17.72	18.84	19.20
	4H	17.97	19.05	18.37	19.40	19.79	17.97	19.05	18.37	19.40	19.79
	6H	18.43	19.43	18.84	19.80	20.19	18.43	19.43	18.84	19.80	20.19
	8H	18.57	19.52	19.00	19.91	20.31	18.57	19.52	19.00	19.91	20.31
	12H	18.64	19.55	19.08	19.93	20.36	18.64	19.55	19.08	19.93	20.36
4H	2H	16.25	17.33	16.65	17.68	18.07	16.25	17.33	16.65	17.68	18.07
	3H	18.08	18.97	18.49	19.37	19.78	18.08	18.97	18.49	19.37	19.78
	4H	18.83	19.63	19.27	20.05	20.49	18.83	19.63	19.27	20.05	20.49
	6H	19.42	20.11	19.89	20.56	21.03	19.42	20.11	19.89	20.56	21.03
	8H	19.60	20.25	20.07	20.69	21.17	19.60	20.25	20.07	20.69	21.17
	12H	19.71	20.28	20.20	20.76	21.24	19.71	20.28	20.20	20.76	21.24
8H	4H	19.09	19.73	19.56	20.18	20.65	19.09	19.73	19.56	20.18	20.65
	6H	19.80	20.33	20.30	20.82	21.31	19.80	20.33	20.30	20.82	21.31
	8H	20.05	20.52	20.57	21.04	21.53	20.05	20.52	20.57	21.04	21.53
	12H	20.22	20.64	20.74	21.14	21.71	20.22	20.64	20.74	21.14	21.71
12H	4H	19.10	19.67	19.59	20.15	20.63	19.10	19.67	19.59	20.15	20.63
	6H	19.84	20.31	20.36	20.83	21.32	19.84	20.31	20.36	20.83	21.32
	8H	20.14	20.56	20.66	21.05	21.63	20.14	20.56	20.66	21.05	21.63

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Report Prepared for

Cooper Lighting Solutions

Metalux

Report Number: SP1-2506-472-8

Test Date: 08/04/2025

Luminaire Tested: EHBR-60-L950-N

Data in this report applies to families of products including EHBR-60-L950-N


**Test Information**

Test Method: LM-79-2019  
 Report Number: SP1-2506-472-8  
 Test Lab: COOPER LIGHTING SOLUTIONS  
 Photometer: SP1 - 76IN SPHERE  
 Measurement Geometry: 4π  
 Issue Date: 08/05/2025  
 Manufacturer: COOPER LIGHTING SOLUTIONS  
 Product Line: Metalux  
 Catalog Number: **EHBR-60-L950-N**  
 Description: Elevate Round Highbay at, 60000 lumens, 5000K 90CRI LEDs with N lens

**Spectral Parameters**

CCT (K): 4901  
 CIE u': 0.2131  
 CIE v': 0.4853  
 Duv: -0.0008  
 CIE x: 0.3477  
 CIE y: 0.3520  
 CIE z: 0.3003  
 Peak Wavelength (nm): 630  
 Dominant Wavelength (nm): 574  
 Purity: 9.953987  
 Rf: 90.7  
 Rg: 100.5

CRI (Ra):	94.3		
R1:	95.8	R9:	72.3
R2:	96.5	R10:	89.1
R3:	94.4	R11:	94.9
R4:	95.3	R12:	68.4
R5:	94.1	R13:	96.4
R6:	92.5	R14:	96.4
R7:	95.5	R15:	93.9
R8:	90.1		




**Test Conditions**  
 Stabilization Time: 35M  
 Operation Time: 1H 35M  
 Sphere Temperature (°C): 25.0

REPORT NUMBER: SP1-2506-472-8


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	76INCH SPHERE IN0058	6/16/2025	12/16/2025
Power Meter	XITRON INXT2011004	1/21/2025	1/21/2026
AC Power Source	CHROMA 61603 IN0063	10/22/2024	10/22/2025
DC Power Source	AGILENT E3634A IN0208	10/22/2024	10/22/2025
Sphere Thermometer	ONSET IN0085	10/22/2024	10/22/2025
Room Thermometer	ONSET IN0046	10/22/2024	10/22/2025

REPORT NUMBER: SP1-2506-472-8

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



CCT = 4901K  
 CIE x = 0.3477  
 CIE y = 0.3520  
 Duv = -0.0008

Point lies inside the ANSI 5000K 4-step quadrangle

REPORT NUMBER: SP1-2506-472-8

**Photopic Flux vs. Wavelength**



**Photopic Lumens: NR**

λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)
360	0	NR	490	221	NR	620	326	NR	750	7	NR	880	0	NR
365	0	NR	495	250	NR	625	325	NR	755	6	NR	885	0	NR
370	0	NR	500	284	NR	630	1000	NR	760	5	NR	890	0	NR
375	0	NR	505	311	NR	635	643	NR	765	4	NR	895	0	NR
380	0	NR	510	329	NR	640	206	NR	770	4	NR	900	0	NR
385	1	NR	515	344	NR	645	199	NR	775	3	NR	905	0	NR
390	2	NR	520	353	NR	650	172	NR	780	3	NR	910	0	NR
395	3	NR	525	357	NR	655	143	NR	785	2	NR	915	0	NR
400	5	NR	530	362	NR	660	122	NR	790	2	NR	920	0	NR
405	6	NR	535	365	NR	665	102	NR	795	2	NR	925	0	NR
410	9	NR	540	367	NR	670	94	NR	800	2	NR	930	0	NR
415	15	NR	545	369	NR	675	76	NR	805	1	NR	935	0	NR
420	26	NR	550	370	NR	680	65	NR	810	1	NR	940	0	NR
425	47	NR	555	372	NR	685	56	NR	815	1	NR	945	0	NR
430	81	NR	560	372	NR	690	48	NR	820	1	NR	950	0	NR
435	143	NR	565	371	NR	695	41	NR	825	1	NR	955	0	NR
440	243	NR	570	370	NR	700	35	NR	830	1	NR	960	0	NR
445	434	NR	575	367	NR	705	30	NR	835	1	NR	965	0	NR
450	675	NR	580	365	NR	710	25	NR	840	1	NR	970	0	NR
455	615	NR	585	361	NR	715	22	NR	845	0	NR	975	0	NR
460	418	NR	590	356	NR	720	19	NR	850	0	NR	980	0	NR
465	344	NR	595	348	NR	725	16	NR	855	0	NR	985	0	NR
470	272	NR	600	343	NR	730	13	NR	860	0	NR	990	0	NR
475	206	NR	605	337	NR	735	11	NR	865	0	NR	995	0	NR
480	190	NR	610	362	NR	740	10	NR	870	0	NR	1000	0	NR
485	202	NR	615	381	NR	745	8	NR	875	0	NR			

REPORT NUMBER: SP1-2506-472-8

**Scotopic Flux vs. Wavelength**



**Scotopic Lumens: NR**

**S/P: 2.04**

$\lambda$ (nm)	Power $W^{\wedge}/nm$	Lumens ( $\phi/nm$ )	$\lambda$ (nm)	Power $W^{\wedge}/nm$	Lumens ( $\phi/nm$ )	$\lambda$ (nm)	Power $W^{\wedge}/nm$	Lumens ( $\phi/nm$ )	$\lambda$ (nm)	Power $W^{\wedge}/nm$	Lumens ( $\phi/nm$ )	$\lambda$ (nm)	Power $W^{\wedge}/nm$	Lumens ( $\phi/nm$ )
360	0	NR	490	221	NR	620	326	NR	750	7	NR	880	0	NR
365	0	NR	495	250	NR	625	325	NR	755	6	NR	885	0	NR
370	0	NR	500	284	NR	630	1000	NR	760	5	NR	890	0	NR
375	0	NR	505	311	NR	635	643	NR	765	4	NR	895	0	NR
380	0	NR	510	329	NR	640	206	NR	770	4	NR	900	0	NR
385	1	NR	515	344	NR	645	199	NR	775	3	NR	905	0	NR
390	2	NR	520	353	NR	650	172	NR	780	3	NR	910	0	NR
395	3	NR	525	357	NR	655	143	NR	785	2	NR	915	0	NR
400	5	NR	530	362	NR	660	122	NR	790	2	NR	920	0	NR
405	6	NR	535	365	NR	665	102	NR	795	2	NR	925	0	NR
410	9	NR	540	367	NR	670	94	NR	800	2	NR	930	0	NR
415	15	NR	545	369	NR	675	76	NR	805	1	NR	935	0	NR
420	26	NR	550	370	NR	680	65	NR	810	1	NR	940	0	NR
425	47	NR	555	372	NR	685	56	NR	815	1	NR	945	0	NR
430	81	NR	560	372	NR	690	48	NR	820	1	NR	950	0	NR
435	143	NR	565	371	NR	695	41	NR	825	1	NR	955	0	NR
440	243	NR	570	370	NR	700	35	NR	830	1	NR	960	0	NR
445	434	NR	575	367	NR	705	30	NR	835	1	NR	965	0	NR
450	675	NR	580	365	NR	710	25	NR	840	1	NR	970	0	NR
455	615	NR	585	361	NR	715	22	NR	845	0	NR	975	0	NR
460	418	NR	590	356	NR	720	19	NR	850	0	NR	980	0	NR
465	344	NR	595	348	NR	725	16	NR	855	0	NR	985	0	NR
470	272	NR	600	343	NR	730	13	NR	860	0	NR	990	0	NR
475	206	NR	605	337	NR	735	11	NR	865	0	NR	995	0	NR
480	190	NR	610	362	NR	740	10	NR	870	0	NR	1000	0	NR
485	202	NR	615	381	NR	745	8	NR	875	0	NR			

REPORT NUMBER: SP1-2506-472-8

**Melanopic Flux vs. Wavelength**



**Melanopic Lumens: NR**

**M/P: 4.41**

λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)
360	0	NR	490	221	NR	620	326	NR	750	7	NR	880	0	NR
365	0	NR	495	250	NR	625	325	NR	755	6	NR	885	0	NR
370	0	NR	500	284	NR	630	1000	NR	760	5	NR	890	0	NR
375	0	NR	505	311	NR	635	643	NR	765	4	NR	895	0	NR
380	0	NR	510	329	NR	640	206	NR	770	4	NR	900	0	NR
385	1	NR	515	344	NR	645	199	NR	775	3	NR	905	0	NR
390	2	NR	520	353	NR	650	172	NR	780	3	NR	910	0	NR
395	3	NR	525	357	NR	655	143	NR	785	2	NR	915	0	NR
400	5	NR	530	362	NR	660	122	NR	790	2	NR	920	0	NR
405	6	NR	535	365	NR	665	102	NR	795	2	NR	925	0	NR
410	9	NR	540	367	NR	670	94	NR	800	2	NR	930	0	NR
415	15	NR	545	369	NR	675	76	NR	805	1	NR	935	0	NR
420	26	NR	550	370	NR	680	65	NR	810	1	NR	940	0	NR
425	47	NR	555	372	NR	685	56	NR	815	1	NR	945	0	NR
430	81	NR	560	372	NR	690	48	NR	820	1	NR	950	0	NR
435	143	NR	565	371	NR	695	41	NR	825	1	NR	955	0	NR
440	243	NR	570	370	NR	700	35	NR	830	1	NR	960	0	NR
445	434	NR	575	367	NR	705	30	NR	835	1	NR	965	0	NR
450	675	NR	580	365	NR	710	25	NR	840	1	NR	970	0	NR
455	615	NR	585	361	NR	715	22	NR	845	0	NR	975	0	NR
460	418	NR	590	356	NR	720	19	NR	850	0	NR	980	0	NR
465	344	NR	595	348	NR	725	16	NR	855	0	NR	985	0	NR
470	272	NR	600	343	NR	730	13	NR	860	0	NR	990	0	NR
475	206	NR	605	337	NR	735	11	NR	865	0	NR	995	0	NR
480	190	NR	610	362	NR	740	10	NR	870	0	NR	1000	0	NR
485	202	NR	615	381	NR	745	8	NR	875	0	NR			

**Summary**

$R_f = 90.7$   
 $R_g = 100.5$   
 CIE  $R_a = 94.3$   
 $R_9 = 72.3$



**Color Vector Graphics**



**Individual Sample Fidelity Index ( $R_{f,i}$ )**

CES01 = 85	CES26 = 91	CES51 = 98	CES76 = 83
CES02 = 61	CES27 = 92	CES52 = 98	CES77 = 87
CES03 = 31	CES28 = 94	CES53 = 97	CES78 = 80
CES04 = 69	CES29 = 94	CES54 = 93	CES79 = 94
CES05 = 48	CES30 = 93	CES55 = 92	CES80 = 91
CES06 = 50	CES31 = 95	CES56 = 95	CES81 = 84
CES07 = 41	CES32 = 86	CES57 = 94	CES82 = 96
CES08 = 40	CES33 = 99	CES58 = 94	CES83 = 96
CES09 = 29	CES34 = 90	CES59 = 97	CES84 = 93
CES10 = 73	CES35 = 94	CES60 = 92	CES85 = 83
CES11 = 56	CES36 = 81	CES61 = 92	CES86 = 86
CES12 = 62	CES37 = 92	CES62 = 86	CES87 = 91
CES13 = 43	CES38 = 88	CES63 = 92	CES88 = 98
CES14 = 74	CES39 = 99	CES64 = 89	CES89 = 87
CES15 = 71	CES40 = 97	CES65 = 88	CES90 = 98
CES16 = 47	CES41 = 97	CES66 = 85	CES91 = 73
CES17 = 48	CES42 = 90	CES67 = 84	CES92 = 79
CES18 = 56	CES43 = 91	CES68 = 86	CES93 = 87
CES19 = 70	CES44 = 99	CES69 = 87	CES94 = 78
CES20 = 65	CES45 = 95	CES70 = 83	CES95 = 83
CES21 = 85	CES46 = 97	CES71 = 77	CES96 = 92
CES22 = 77	CES47 = 95	CES72 = 92	CES97 = 95
CES23 = 91	CES48 = 93	CES73 = 77	CES98 = 95
CES24 = 90	CES49 = 95	CES74 = 92	CES99 = 94
CES25 = 70	CES50 = 98	CES75 = 79	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)