

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: METALUX

Report Number: P980771

Luminaire Tested: UHBS2-2436-W-L83065-MID-4000K-CLR3

Issue Date: 4/4/2025

Test Information

Test Method: LM-79-2019
Report Number: P980771
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2502-344-1)
Test Lab: INNOVATION CENTER
Issue Date: 4/4/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: METALUX
Catalog Number: UHBS2-2436-W-L83065-MID-4000K-CLR3
Description: UHBS2 LED High Bay at 4000K and MID lumen setting 3in Deep Clear Refractor
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 32819.0 lumens
Efficiency: N/A
Efficacy: 172.7 lumens/watt
Spacing Criteria (0/90/45): 1.31 / 1.31 / 1.34
Luminous Opening: Vertical Cylinder (Dia: 1.34' x H: 0.25')
CIE Type: Direct

Input Watts (W): 190
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.998
Total Harmonic Distortion (THDi): 5.15
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P980771

CATALOG NUMBER: UHBS2-2436-W-L83065-MID-4000K-CLR3

Luminous Intensity Polar Plot



TEST NUMBER: P980771

CATALOG NUMBER: UHBS2-2436-W-L83065-MID-4000K-CLR3

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	110	110	110		105	105	105		100
1	111	107	104	101	108	105	102	99	100	98	95		96	94	92		92
2	103	96	91	86	100	94	89	85	90	86	83		87	84	81		84
3	95	87	80	75	93	85	79	74	82	77	72		79	75	71		76
4	88	78	71	65	86	77	70	65	74	68	64		72	67	63		70
5	82	71	63	58	80	70	63	57	68	61	57		66	60	56		64
6	76	65	57	51	74	64	56	51	62	55	50		60	54	50		58
7	71	59	51	46	69	58	51	46	57	50	45		55	49	45		54
8	67	54	47	41	65	54	46	41	52	46	41		51	45	41		50
9	62	50	43	38	61	49	42	37	48	42	37		47	41	37		46
10	58	46	39	34	57	46	39	34	45	38	34		44	38	34		43

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	116867
5°	114570
10°	112814
15°	110770
20°	108869
25°	107138
30°	105039
35°	102420
40°	97252
45°	81099
50°	56923
55°	35807
60°	17039
65°	8634
70°	9246
75°	10933
80°	8516
85°	4435

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 81099 cd/sqm

TEST NUMBER: P980771

CATALOG NUMBER: UHBS2-2436-W-L83065-MID-4000K-CLR3

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1447.6	4.4
10°-20°	4195.3	12.8
20°-30°	6486.0	19.8
30°-40°	7954.0	24.2
40°-50°	6985.9	21.3
50°-60°	3257.3	9.9
60°-70°	846.2	2.6
70°-80°	683.1	2.1
80°-90°	244.8	0.7
90°-100°	158.4	0.5
100°-110°	217.7	0.7
110°-120°	125.4	0.4
120°-130°	68.8	0.2
130°-140°	51.9	0.2
140°-150°	44.2	0.1
150°-160°	32.1	0.1
160°-170°	16.3	0.0
170°-180°	4.3	0.0
0°-30°	12128.9	37.0
0°-40°	20082.8	61.2
0°-60°	30326.0	92.4
0°-90°	32100.0	97.8
90°-120°	501.5	1.5
90°-150°	666.3	2.0
90°-180°	719.0	2.2
0°-180°	32819.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	15243	
5°	15197	###
15°	14846	4195
25°	14071	6486
35°	12767	7954
45°	9260	6986
55°	3590	3257
65°	719	846
75°	697	683
85°	188	211
90°	112	66
95°	139	127
105°	217	218
115°	122	125
125°	76	69
135°	66	52
145°	71	44
155°	71	32
165°	56	16
175°	44	4
180°	44	

TEST NUMBER: P980771

CATALOG NUMBER: UHBS2-2436-W-L83065-MID-4000K-CLR3

CANDELA DISTRIBUTION (FULL):

0°	
0°	15243.1
2.5°	15230.9
5°	15196.8
7.5°	15152.9
10°	15099.3
12.5°	14989.6
15°	14845.9
17.5°	14687.4
20°	14499.8
22.5°	14304.8
25°	14070.9
27.5°	13795.5
30°	13495.8
32.5°	13193.6
35°	12767.1
37.5°	12252.9
40°	11658.3
42.5°	10530.0
45°	9260.4
47.5°	7703.2
50°	6126.5
52.5°	4732.5
55°	3589.6
57.5°	2524.7
60°	1569.4
62.5°	911.4
65°	718.9
67.5°	672.6
70°	682.3
72.5°	709.2
75°	697.0
77.5°	611.7
80°	453.3
82.5°	292.4
85°	187.6
87.5°	136.5
90°	112.1
92.5°	119.4
95°	138.9
97.5°	168.1
100°	197.4
102.5°	216.9
105°	216.9
107.5°	202.3
110°	175.5

TEST NUMBER: P980771

CATALOG NUMBER: UHBS2-2436-W-L83065-MID-4000K-CLR3

CANDELA DISTRIBUTION (continued):

	0°
112.5°	146.2
115°	121.8
117.5°	102.4
120°	90.2
122.5°	80.4
125°	75.5
127.5°	70.7
130°	68.2
132.5°	65.8
135°	65.8
137.5°	68.2
140°	68.2
142.5°	70.7
145°	70.7
147.5°	70.7
150°	70.7
152.5°	70.7
155°	70.7
157.5°	68.2
160°	63.4
162.5°	60.9
165°	56.0
167.5°	53.6
170°	48.7
172.5°	43.9
175°	43.9
177.5°	43.9
180°	43.9

(END OF REPORT)