Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled data based on original data using

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: McGRAW-EDISON

Report Number: P954243

Luminaire Tested: **GALN-SB7C-760-U-SL2-HSS**

Issue Date: 1/21/2025

Report Generated By 670246001

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Test Information

Test Method:	LM-79-08
Report Number:	P954243
	TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2411-289-11)
Test Lab:	INNOVATION CENTER
Issue Date:	1/21/2025
Manufacturer:	COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line:	McGRAW-EDISON
Catalog Number:	GALN-SB7C-760-U-SL2-HSS
Description:	GALLEON AREA AND ROADWAY HIGH DENSITY LED LUMINAIRE
	(7) 70 CRI, 5700K, 615mA LIGHTSQUARES WITH 26 LEDS EACH AND TYPE II SPILL LIGHT ELIMINATOR OPTICS WITH HOUSE SIDE SHIELD
Light Source:	-
Ballast/Driver:	-

Summary

Lumens per Lamp:	N/A
Luminaire Lumens:	45670 lumens
Efficiency:	N/A
Efficacy:	130.3 lumens/watt
Luminous Opening:	Rectangular (W 1.5' x L: 1.5' x H: 0')
IES Classification:	Type II - Medium
BUG Rating:	B3 - U0 - G5

Input Watts (W):	350.5
Input Voltage (V):	NR
Input Current (Ain):	NR
Voltage Rise (V):	NR
Power Factor:	NR
Total Harmonic Distortion (THDi):	NR
Frequency (hertz):	60
Stabilization Time:	NR
Operation Time:	NR
Ambient Temperature (°C):	NR
Test Distance:	24 FT

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P954243
CATALOG NUMBER: GALN-SB7C-760-U-SL2-HSS

Iso-Footcandle Lines of Horizontal Illumination



Based on 25 foot mounting height. Maximum calculated value = 16.7 fc
Type II - Medium - N/A

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P954243
CATALOG NUMBER: GALN-SB7C-760-U-SL2-HSS

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P954243
CATALOG NUMBER: GALN-SB7C-760-U-SL2-HSS

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	4674.3	0.0	4674.3
	% Fixture	10.2	0.0	10.2
Street Side	Lumens	40995.7	0.0	40995.7
	% Fixture	89.8	0.0	89.8
Total	Lumens	45670.0	0.0	45670.0
	% Fixture	100.0	0.0	100.0

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	717.8	1.6
10°-20°	1924.6	4.2
20°-30°	3046.1	6.7
30°-40°	4712.9	10.3
40°-50°	7158.0	15.7
50°-60°	9868.1	21.6
60°-70°	10425.0	22.8
70°-80°	7151.8	15.7
80°-90°	665.6	1.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	45670.0	100.0
0°-180°	45670.0	100.0



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P954243
CATALOG NUMBER: GALN-SB7C-760-U-SL2-HSS

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit B	U	G
FL	(0°-30°)	4432.2	9.7			
FM	(30°-60°)	19586.9	42.9			
FH	(60°-80°)	16329.0	35.8			G5
FVH	(80°-90°)	647.6	1.4			G4/750
BL	(0°-30°)	1256.4	2.8	B3/2500		
BM	(30°-60°)	2152.1	4.7	B2/2500		
BH	(60°-80°)	1247.8	2.7	B3/2500		G3/2500
BVH	(80°-90°)	18.0	0.0			G1/100
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B3-U0-G5
Type II Medium



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P954243
CATALOG NUMBER: GALN-SB7C-760-U-SL2-HSS

CANDELA DISTRIBUTION (FULL):

	0°	5°	15°	25°	35°	45°	55°	65°	75°	76°
0°	7892.2	7892.2	7892.2	7892.2	7892.2	7892.2	7892.2	7892.2	7892.2	*7892.2*
2.5°	9174.9	9053.5	9077.2	8955.7	8899.4	8763.2	8621.0	8434.3	8226.9	*8226.9*
5°	10140.7	10063.7	10063.7	9921.5	9811.9	9598.6	9343.8	9015.0	8623.9	*8585.4*
7.5°	10733.2	10685.8	10715.5	10632.5	10543.6	10321.4	10019.3	9589.7	9035.7	*8988.3*
10°	10848.8	10845.8	10928.8	10952.5	11011.7	10899.1	10629.5	10134.8	9441.6	*9373.4*
12.5°	10401.4	10345.1	10549.6	10789.5	11127.3	11278.3	11139.1	10632.5	9811.9	*9717.1*
15°	9666.7	9678.6	9874.1	10244.4	10807.3	11346.5	11527.2	11118.4	10188.1	*10075.6*
17.5°	9246.0	9201.6	9370.5	9702.3	10324.4	11085.8	11707.9	11571.6	10588.1	*10460.7*
20°	9195.7	9192.7	9231.2	9382.3	9856.3	10712.5	11687.2	12013.0	11059.1	*10911.0*
22.5°	9545.3	9539.3	9506.8	9477.1	9607.5	10348.1	11598.3	12433.7	11622.0	*11462.0*
25°	10081.5	10072.6	10022.2	9841.5	9714.1	10152.6	11515.3	12824.8	12288.6	*12110.8*
27.5°	10736.2	10730.3	10638.4	10365.9	10037.0	10170.4	11473.9	13227.7	13058.8	*12884.0*
30°	11539.0	11527.2	11337.6	10952.5	10522.9	10451.8	11530.2	13681.0	13861.7	*13728.4*
32.5°	12546.3	12513.7	12264.9	11684.2	11082.8	10828.0	11636.8	14146.1	14812.6	*14688.2*
35°	13325.4	13275.1	13129.9	12617.4	11731.6	11290.2	11885.7	14697.1	15956.2	*15846.6*
37.5°	13995.0	13944.6	13826.1	13405.4	12661.8	11879.7	12285.6	15431.8	17307.1	*17253.8*
40°	14717.8	14634.9	14578.6	14128.3	13455.8	12730.0	12857.4	16290.9	18862.4	*18868.3*
42.5°	15274.8	15242.2	15248.1	14901.5	14223.1	13737.2	13615.8	17259.7	20725.8	*20782.1*
45°	15751.8	15725.1	15834.7	15591.8	14996.3	14397.9	14504.5	18355.8	22764.1	*22879.6*
47.5°	16119.1	16148.7	16305.8	16148.7	15799.2	14863.0	15292.6	19537.9	24906.0	*24920.8*
50°	16486.5	16498.3	16759.0	16682.0	16539.8	15452.5	16018.4	20859.2	27163.4	*27190.1*
52.5°	16602.0	16584.2	16999.0	17188.6	17194.5	16181.3	16957.5	22298.9	29376.4	*29462.3*
55°	16009.5	16059.9	16729.4	17499.7	17804.8	17188.6	18225.5	24120.9	31734.6	*31770.1*
57.5°	13112.1	13390.6	14871.9	16658.3	18198.8	18631.3	20047.4	26251.0	34457.2	*34424.6*
60°	7957.3	8289.2	10060.7	13971.3	16913.1	20080.0	22731.5	29551.2	37431.5	*37339.7*
62.5°	4449.7	4550.4	5116.3	8363.2	12863.3	19158.7	25353.3	33790.6	41425.0	*41114.0*
65°	3279.5	3312.1	3445.4	4097.2	6322.0	14735.6	24778.6	38859.5	47036.0	*46482.1*
67.5°	2850.0	2882.5	3012.9	3101.8	2823.3	7741.1	20414.8	41670.9	54160.9	*53435.1*
70°	2399.6	2417.4	2627.8	2687.0	2020.4	2944.8	13115.1	40802.9	60755.5	*60237.1*
72.5°	*1789.4*	*1860.5*	*2165.6*	*2307.8*	*1620.5*	*1564.2*	*6173.9*	*35674.8*	*61872.4*	*61878.3*
75°	1214.6	1279.8	1629.4	1899.0	1250.2	1096.1	2491.5	26639.0	53876.5	*53876.5*
77.5°	829.5	882.8	1134.6	1490.2	948.0	752.5	1291.7	16907.1	38652.1	*40011.9*
80°	367.4	399.9	731.7	1081.3	719.9	485.9	731.7	9257.9	23374.3	*23087.0*
82.5°	180.7	207.4	468.1	675.5	465.1	299.2	385.1	4402.3	7575.2	*7198.9*
85°	35.6	47.4	251.8	287.4	216.3	133.3	145.2	1353.9	912.5	*1042.8*
87.5°	0.0	0.0	77.0	53.3	23.7	29.6	29.6	121.5	71.1	*83.0*
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	*0.0*

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P954243
CATALOG NUMBER: GALN-SB7C-760-U-SL2-HSS

CANDELA DISTRIBUTION (continued):

85°		90°	95°	105°	115°	125°	135°	145°	155°	165°	175°
7892.2	0°	7892.2	7892.2	7892.2	7892.2	7892.2	7892.2	7892.2	7892.2	7892.2	7892.2
8025.5	2.5°	7918.8	7809.2	7569.3	7332.3	7089.3	6867.1	6713.1	6559.0	6464.2	6422.8
8203.2	5°	7981.0	7758.9	7255.2	6727.9	6206.5	5696.9	5314.8	4956.3	4843.7	4657.1
8413.6	7.5°	8078.8	7717.4	6923.4	6034.7	5187.4	4440.8	3901.6	3472.1	3300.3	3134.4
8594.3	10°	8144.0	7640.4	6485.0	5297.0	4150.5	3312.1	2796.6	2485.6	2373.0	2272.3
8763.2	12.5°	8170.7	7498.2	5981.3	4470.5	3229.2	2524.1	2216.0	2070.8	2032.3	1996.7
8923.1	15°	8194.4	7358.9	5418.5	3673.5	2550.7	2112.3	1990.8	1943.4	1916.8	1893.1
9086.1	17.5°	8215.1	7181.2	4775.6	2986.2	2153.8	1946.4	1887.1	1836.8	1816.0	1789.4
9320.1	20°	8286.2	7009.3	4200.9	2464.8	1937.5	1827.9	1762.7	1709.4	1691.6	1673.8
9651.9	22.5°	8419.5	6870.1	3643.9	2112.3	1807.1	1706.4	1623.5	1564.2	1552.4	1540.5
10054.8	25°	8579.5	6698.3	3119.5	1884.2	1679.8	1567.2	1475.3	1425.0	1413.1	1416.1
10519.9	27.5°	8783.9	6508.7	2669.2	1739.0	1567.2	1436.8	1333.1	1294.6	1300.5	1312.4
11056.2	30°	9009.0	6333.9	2316.7	1638.3	1466.5	1321.3	1217.6	1190.9	1211.7	1229.4
11773.1	32.5°	9343.8	6179.8	2070.8	1558.3	1377.6	1226.5	1143.5	1110.9	1134.6	1158.3
12688.5	35°	9800.0	6102.8	1931.6	1490.2	1300.5	1152.4	1069.5	1045.8	1069.5	1075.4
13805.4	37.5°	10360.0	6096.9	1872.3	1433.9	1229.4	1090.2	998.4	989.5	1007.3	1010.2
15147.4	40°	11082.8	6135.4	1827.9	1392.4	1155.4	1019.1	933.2	924.3	930.2	951.0
16762.0	42.5°	11998.2	6295.4	1765.7	1339.1	1075.4	948.0	879.9	859.1	856.2	879.9
18569.1	45°	13147.7	6647.9	1682.7	1253.1	1004.3	888.8	820.6	796.9	788.0	794.0
20435.5	47.5°	14400.8	7080.4	1599.8	1173.2	953.9	841.4	773.2	743.6	728.8	728.8
22180.4	50°	15615.5	7569.3	1543.5	1090.2	918.4	796.9	722.9	693.2	669.5	663.6
23975.7	52.5°	16818.3	8049.2	1499.0	1007.3	876.9	740.6	675.5	642.9	616.2	604.4
25753.3	55°	17914.4	8505.4	1422.0	927.3	823.6	681.4	628.1	595.5	562.9	542.1
27554.5	57.5°	18966.1	8884.6	1279.8	844.3	740.6	625.1	577.7	542.1	503.6	477.0
29376.4	60°	19923.0	9080.1	1102.1	755.4	657.7	565.8	521.4	488.8	438.5	394.0
31168.8	62.5°	20651.8	9003.1	909.5	654.7	571.8	512.5	456.2	423.6	364.4	311.1
33316.6	65°	21398.3	8582.4	725.8	548.1	500.7	441.4	382.2	349.6	281.4	225.2
36222.8	67.5°	22367.1	7684.8	571.8	456.2	432.5	349.6	299.2	278.5	231.1	177.8
39342.4	70°	22989.2	5969.5	444.4	370.3	355.5	254.8	231.1	228.1	183.7	136.3
39132.0	72.5°	*21282.8*	*3913.5*	*340.7*	*281.4*	*254.8*	*165.9*	*177.8*	*177.8*	*133.3*	*91.8*
34303.1	75°	17766.3	2290.0	245.9	201.5	145.2	106.7	121.5	121.5	83.0	44.4
24449.7	77.5°	12688.5	1220.6	162.9	124.4	74.1	47.4	65.2	62.2	26.7	3.0
9583.8	80°	4852.6	420.7	77.0	50.4	20.7	8.9	5.9	3.0	3.0	0.0
1496.1	82.5°	740.6	109.6	14.8	11.9	0.0	0.0	0.0	0.0	0.0	0.0
317.0	85°	133.3	14.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
83.0	87.5°	29.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
0.0	90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END O

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

180°
7892.2
6428.7
4668.9
3131.4
2269.3
1996.7
1893.1
1789.4
1676.8
1531.6
1410.2
1306.5
1223.5
1152.4
1072.4
1004.3
948.0
876.9
802.8
728.8
660.6
598.4
533.3
465.1
382.2
290.3
210.3
165.9
121.5
80.0
35.6
0.0
0.0
0.0
0.0
0.0
0.0

F REPORT)