

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: McGRAW-EDISON

Report Number: P957458

Luminaire Tested: **GALN-SB9D-760-U-SL3-HSS**

Issue Date: 1/21/2025

Test Information

Test Method: LM-79-08
Report Number: P957458
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2411-289-13)
Test Lab: INNOVATION CENTER
Issue Date: 1/21/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: McGRAW-EDISON
Catalog Number: GALN-SB9D-760-U-SL3-HSS
Description: GALLEON AREA AND ROADWAY HIGH DENSITY LED LUMINAIRE
(9) 70 CRI, 5700K, 900mA LIGHTSQUARES WITH 26 LEDS EACH AND TYPE III
SPILL LIGHT ELIMINATOR OPTICS WITH HOUSE SIDE SHIELD
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 78968 lumens
Efficiency: N/A
Efficacy: 120.0 lumens/watt
Luminous Opening: Rectangular (W 1.5' x L: 1.5' x H: 0')
IES Classification: Type III - Medium
BUG Rating: B3 - U0 - G5


Input Watts (W): 658
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



REPORT NUMBER: P957458
 CATALOG NUMBER: GALN-SB9D-760-U-SL3-HSS

Iso-Footcandle Lines of Horizontal Illumination


✕ Max cd
 - - - 1/2 Max cd



Based on 25 foot mounting height. Maximum calculated value = 23.1 fc
 Type III - Medium - N/A

REPORT NUMBER: P957458
CATALOG NUMBER: GALN-SB9D-760-U-SL3-HSS

Luminous Intensity Polar Plot



REPORT NUMBER: P957458
 CATALOG NUMBER: GALN-SB9D-760-U-SL3-HSS

FLUX DISTRIBUTION:

| | | Downward | Upward | Total |
|--------------------|-----------|----------|--------|---------|
| House Side | Lumens | 8340.7 | 0.0 | 8340.7 |
| | % Fixture | 10.6 | 0.0 | 10.6 |
| Street Side | Lumens | 70627.3 | 0.0 | 70627.3 |
| | % Fixture | 89.4 | 0.0 | 89.4 |
| Total | Lumens | 78968.0 | 0.0 | 78968.0 |
| | % Fixture | 100.0 | 0.0 | 100.0 |

Coefficient of Utilization

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|---------|-----------|
| 0°-10° | 1056.5 | 1.3 |
| 10°-20° | 2806.2 | 3.6 |
| 20°-30° | 4447.5 | 5.6 |
| 30°-40° | 7137.4 | 9.0 |
| 40°-50° | 11399.7 | 14.4 |
| 50°-60° | 16505.3 | 20.9 |
| 60°-70° | 19587.7 | 24.8 |
| 70°-80° | 14541.0 | 18.4 |
| 80°-90° | 1486.7 | 1.9 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-90° | 78968.0 | 100.0 |
| 0°-180° | 78968.0 | 100.0 |



REPORT NUMBER: P957458


CATALOG NUMBER: GALN-SB9D-760-U-SL3-HSS

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

| Zone | Lumens | % Fixture | Zone Rating/Lumen Limit | | |
|----------------|---------|-----------|-------------------------|------|---------|
| | | | B | U | G |
| FL (0°-30°) | 6173.6 | 7.8 | | | |
| FM (30°-60°) | 31175.4 | 39.5 | | | |
| FH (60°-80°) | 31828.6 | 40.3 | | | G5 |
| FVH (80°-90°) | 1449.7 | 1.8 | | | G5 |
| BL (0°-30°) | 2136.6 | 2.7 | B3/2500 | | |
| BM (30°-60°) | 3867.0 | 4.9 | B3/5000 | | |
| BH (60°-80°) | 2300.1 | 2.9 | B3/2500 | | G3/2500 |
| BVH (80°-90°) | 37.0 | 0.0 | | | G1/100 |
| UL (90°-100°) | 0.0 | 0.0 | | U0/0 | |
| UH (100°-180°) | 0.0 | 0.0 | | U0/0 | |

BUG Rating: B3-U0-G5

Type III Medium



REPORT NUMBER: P957458

CATALOG NUMBER: GALN-SB9D-760-U-SL3-HSS

CANDELA DISTRIBUTION (FULL):

| | 0° | 5° | 15° | 25° | 35° | 45° | 55° | 59° | 65° | 75° |
|-------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| 0° | 11677.5 | 11677.5 | 11677.5 | 11677.5 | 11677.5 | 11677.5 | 11677.5 | 11677.5 | 11677.5 | 11677.5 |
| 2.5° | 12956.1 | 12883.9 | 12894.2 | 12770.5 | 12682.8 | 12590.0 | 12409.6 | 12383.8 | 12254.9 | 12028.1 |
| 5° | 14085.2 | 14038.8 | 13997.5 | 13858.3 | 13677.9 | 13451.0 | 13146.8 | 13038.6 | 12801.4 | 12409.6 |
| 7.5° | 14910.1 | 14853.3 | 14874.0 | 14734.8 | 14590.4 | 14337.8 | 13920.2 | 13719.1 | 13404.6 | 12806.6 |
| 10° | 15069.9 | 15039.0 | 15173.0 | 15224.6 | 15224.6 | 15064.7 | 14657.4 | 14456.4 | 13997.5 | 13234.5 |
| 12.5° | 14172.8 | 14178.0 | 14513.1 | 14915.2 | 15441.1 | 15590.6 | 15317.4 | 15100.8 | 14647.1 | 13688.2 |
| 15° | 13126.2 | 13131.4 | 13456.2 | 13971.7 | 14832.7 | 15693.7 | 15910.3 | 15771.1 | 15301.9 | 14178.0 |
| 17.5° | 12497.2 | 12471.5 | 12688.0 | 13110.7 | 14013.0 | 15224.6 | 16271.1 | 16363.9 | 15982.4 | 14719.3 |
| 20° | 12409.6 | 12363.2 | 12476.6 | 12688.0 | 13332.4 | 14636.8 | 16312.4 | 16750.6 | 16683.6 | 15332.8 |
| 22.5° | 12945.8 | 12873.6 | 12811.7 | 12822.0 | 13095.3 | 14147.0 | 16209.3 | 16967.2 | 17405.4 | 16070.1 |
| 25° | 14007.8 | 13894.4 | 13693.3 | 13435.6 | 13378.8 | 14043.9 | 16137.1 | 17204.3 | 18075.6 | 17013.6 |
| 27.5° | 15307.0 | 15147.2 | 14760.5 | 14373.9 | 14043.9 | 14332.6 | 16286.6 | 17580.7 | 18833.5 | 18111.7 |
| 30° | 16735.2 | 16539.2 | 16152.6 | 15420.5 | 14894.6 | 14977.1 | 16642.4 | 18075.6 | 19802.7 | 19354.2 |
| 32.5° | 18833.5 | 18379.8 | 17704.4 | 16585.6 | 15889.6 | 15673.1 | 17178.5 | 18704.6 | 21004.0 | 21009.2 |
| 35° | 20632.8 | 20380.2 | 19699.6 | 18307.6 | 16879.5 | 16596.0 | 17884.9 | 19591.4 | 22669.3 | 23200.3 |
| 37.5° | 21813.4 | 21468.0 | 20870.0 | 19823.4 | 18415.9 | 17544.6 | 18828.3 | 20679.2 | 24432.5 | 25695.6 |
| 40° | 23133.3 | 22793.0 | 21999.0 | 21014.3 | 20199.7 | 19173.8 | 20019.3 | 21932.0 | 26365.9 | 28258.0 |
| 42.5° | 24726.4 | 24283.0 | 23344.7 | 22282.6 | 21431.9 | 21318.5 | 21576.3 | 23494.2 | 28350.8 | 31042.0 |
| 45° | 26597.9 | 26180.3 | 25102.7 | 23762.3 | 23014.7 | 22813.6 | 23535.4 | 25314.1 | 30562.5 | 34094.1 |
| 47.5° | 28350.8 | 27866.1 | 26706.1 | 25484.2 | 24654.2 | 24020.0 | 25618.3 | 27464.0 | 33068.2 | 37285.5 |
| 50° | 29840.7 | 29345.8 | 28283.7 | 26979.4 | 26417.4 | 25587.4 | 27665.1 | 29861.4 | 35553.2 | 40528.4 |
| 52.5° | 30861.6 | 30423.3 | 29175.7 | 28288.9 | 27907.4 | 27489.8 | 30062.4 | 32403.1 | 38027.9 | 43498.0 |
| 55° | 30629.6 | 30237.7 | 29139.6 | 29077.7 | 29051.9 | 29490.2 | 32929.0 | 35285.1 | 40549.0 | 46307.8 |
| 57.5° | 29892.3 | 29448.9 | 28077.5 | 29021.0 | 29933.5 | 31274.0 | 36032.6 | 38693.0 | 43312.4 | 48957.8 |
| 60° | 27721.8 | 27567.1 | 26731.9 | 28912.7 | 30304.8 | 33021.8 | 39579.7 | 42116.3 | 46302.7 | 51288.1 |
| 62.5° | 23128.1 | 23262.2 | 23257.0 | 29139.6 | 30975.0 | 35011.8 | 42802.0 | 45580.9 | 49225.9 | 53530.8 |
| 65° | 17317.7 | 17781.7 | 18374.6 | 27098.0 | 31872.1 | 38564.1 | 46653.2 | 49339.3 | 52195.5 | 56139.6 |
| 67.5° | 11636.2 | 12007.4 | 12409.6 | 22231.0 | 29201.4 | 42296.7 | 53051.4 | 54489.8 | 55752.9 | 59031.9 |
| 70° | 6661.1 | 6779.6 | 7341.6 | 13884.1 | 22509.5 | 41265.6 | 63470.9 | 63991.6 | 61058.0 | 62594.4 |
| 72.5° | 3732.7 | 3691.4 | 4433.8 | 6588.9 | 12579.7 | 35336.6 | 67121.1 | 72199.3 | 65806.4 | 62537.7 |
| 75° | 2495.3 | 2500.5 | 3052.1 | 4155.4 | 4903.0 | 24736.7 | 57840.9 | 66945.8 | 62960.5 | 55453.9 |
| 77.5° | 1701.4 | 1758.1 | 2242.7 | 3212.0 | 2268.5 | 12069.3 | 38265.0 | 46895.5 | 50973.6 | 42822.6 |
| 80° | 737.3 | 742.4 | 1479.7 | 2304.6 | 1531.2 | 3840.9 | 19838.8 | 25123.4 | 31970.0 | 24045.8 |
| 82.5° | 381.5 | 433.1 | 943.5 | 1490.0 | 964.1 | 1345.6 | 9372.9 | 10976.3 | 13414.9 | 7058.0 |
| 85° | 134.0 | 159.8 | 582.6 | 732.1 | 484.6 | 479.5 | 3263.5 | 3325.4 | 2840.7 | 1062.1 |
| 87.5° | 0.0 | 25.8 | 226.8 | 180.4 | 61.9 | 56.7 | 386.7 | 324.8 | 257.8 | 149.5 |
| 90° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |

REPORT NUMBER: P957458
 CATALOG NUMBER: GALN-SB9D-760-U-SL3-HSS

CANDELA DISTRIBUTION (continued):

| 85° | | 90° | 95° | 105° | 115° | 125° | 135° | 145° | 155° | 165° | 175° |
|---------|-------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| 11677.5 | 0° | 11677.5 | 11677.5 | 11677.5 | 11677.5 | 11677.5 | 11677.5 | 11677.5 | 11677.5 | 11677.5 | 11677.5 |
| 11796.1 | 2.5° | 11687.8 | 11548.6 | 11321.7 | 11043.3 | 10718.5 | 10543.2 | 10290.6 | 10136.0 | 9996.8 | 10001.9 |
| 11955.9 | 5° | 11703.3 | 11471.3 | 10893.8 | 10280.3 | 9599.8 | 9099.7 | 8542.9 | 8151.0 | 7852.0 | 7779.8 |
| 12120.9 | 7.5° | 11749.7 | 11357.8 | 10414.4 | 9393.5 | 8259.3 | 7418.9 | 6650.8 | 6166.1 | 5892.9 | 5820.7 |
| 12291.0 | 10° | 11811.5 | 11234.1 | 9873.0 | 8310.9 | 6903.4 | 5892.9 | 5253.6 | 4944.2 | 4820.5 | 4727.7 |
| 12507.5 | 12.5° | 11863.1 | 11105.2 | 9192.5 | 7192.1 | 5697.0 | 4908.2 | 4423.5 | 4165.7 | 4057.5 | 3990.5 |
| 12760.2 | 15° | 11950.7 | 10935.1 | 8455.2 | 6150.7 | 4882.4 | 4237.9 | 3779.1 | 3588.3 | 3557.4 | 3567.7 |
| 13038.6 | 17.5° | 12038.4 | 10770.1 | 7630.3 | 5336.1 | 4284.3 | 3650.2 | 3371.8 | 3340.8 | 3382.1 | 3423.3 |
| 13358.2 | 20° | 12136.3 | 10532.9 | 6795.1 | 4722.6 | 3732.7 | 3242.9 | 3170.7 | 3191.3 | 3212.0 | 3284.1 |
| 13796.4 | 22.5° | 12280.7 | 10233.9 | 6063.0 | 4201.8 | 3273.8 | 3047.0 | 3010.9 | 3026.4 | 3041.8 | 3114.0 |
| 14373.9 | 25° | 12486.9 | 9914.3 | 5470.1 | 3722.4 | 2985.1 | 2887.1 | 2851.1 | 2851.1 | 2871.7 | 2938.7 |
| 15044.1 | 27.5° | 12703.5 | 9460.6 | 4990.6 | 3279.0 | 2815.0 | 2711.9 | 2650.0 | 2650.0 | 2675.8 | 2753.1 |
| 15884.5 | 30° | 12945.8 | 9048.1 | 4614.3 | 2949.0 | 2670.6 | 2536.6 | 2454.1 | 2433.5 | 2464.4 | 2562.3 |
| 17101.2 | 32.5° | 13384.0 | 8780.0 | 4346.2 | 2794.3 | 2541.7 | 2376.7 | 2263.3 | 2206.6 | 2237.5 | 2351.0 |
| 18802.6 | 35° | 14049.1 | 8718.2 | 4160.6 | 2717.0 | 2418.0 | 2232.4 | 2072.6 | 1984.9 | 2010.7 | 2129.3 |
| 20900.9 | 37.5° | 14827.6 | 8847.0 | 3980.1 | 2613.9 | 2299.4 | 2093.2 | 1881.8 | 1768.4 | 1809.6 | 1917.9 |
| 23298.3 | 40° | 15946.3 | 9383.2 | 3840.9 | 2536.6 | 2180.8 | 1928.2 | 1691.0 | 1577.6 | 1644.6 | 1737.4 |
| 25793.6 | 42.5° | 17297.1 | 10337.0 | 3804.8 | 2464.4 | 2036.5 | 1752.9 | 1515.8 | 1433.3 | 1484.8 | 1572.5 |
| 28314.7 | 45° | 18972.7 | 11553.8 | 3969.8 | 2371.6 | 1876.6 | 1582.8 | 1376.6 | 1330.2 | 1345.6 | 1433.3 |
| 30696.6 | 47.5° | 20772.0 | 12801.4 | 4423.5 | 2289.1 | 1737.4 | 1443.6 | 1268.3 | 1227.0 | 1216.7 | 1299.2 |
| 32872.3 | 50° | 22591.9 | 13909.9 | 4959.7 | 2227.2 | 1639.5 | 1330.2 | 1185.8 | 1134.2 | 1108.5 | 1160.0 |
| 35022.1 | 52.5° | 24391.3 | 14791.5 | 5310.3 | 2124.1 | 1541.5 | 1216.7 | 1113.6 | 1036.3 | 989.9 | 1015.7 |
| 37161.7 | 55° | 26216.3 | 15564.8 | 5330.9 | 1969.4 | 1448.7 | 1144.5 | 1041.4 | 953.8 | 897.1 | 897.1 |
| 39224.0 | 57.5° | 27922.9 | 16245.4 | 5026.7 | 1763.2 | 1319.8 | 1077.5 | 943.5 | 871.3 | 809.4 | 788.8 |
| 41054.2 | 60° | 29433.5 | 16750.6 | 4521.5 | 1531.2 | 1206.4 | 989.9 | 845.5 | 788.8 | 711.5 | 670.2 |
| 42683.4 | 62.5° | 30779.1 | 16998.1 | 3830.6 | 1294.1 | 1067.2 | 886.8 | 752.7 | 690.9 | 587.7 | 536.2 |
| 44338.4 | 65° | 31918.5 | 16745.5 | 3108.8 | 1072.4 | 948.6 | 773.3 | 644.5 | 582.6 | 469.2 | 407.3 |
| 46199.5 | 67.5° | 33047.5 | 15590.6 | 2351.0 | 902.2 | 824.9 | 649.6 | 531.0 | 474.3 | 391.8 | 340.3 |
| 47555.5 | 70° | 33191.9 | 13162.3 | 1644.6 | 757.9 | 685.7 | 500.1 | 427.9 | 391.8 | 319.6 | 273.2 |
| 44529.1 | 72.5° | 29546.9 | 9470.9 | 1000.2 | 618.7 | 536.2 | 355.7 | 340.3 | 309.3 | 237.2 | 206.2 |
| 36383.2 | 75° | 23617.9 | 5805.2 | 587.7 | 464.0 | 355.7 | 252.6 | 252.6 | 221.7 | 159.8 | 134.0 |
| 25118.2 | 77.5° | 16322.7 | 3036.7 | 345.4 | 299.0 | 211.4 | 149.5 | 165.0 | 134.0 | 77.3 | 61.9 |
| 9950.4 | 80° | 6537.3 | 1154.9 | 185.6 | 139.2 | 98.0 | 67.0 | 56.7 | 30.9 | 15.5 | 10.3 |
| 2041.6 | 82.5° | 1304.4 | 304.2 | 61.9 | 36.1 | 36.1 | 15.5 | 0.0 | 0.0 | 0.0 | 0.0 |
| 562.0 | 85° | 335.1 | 67.0 | 15.5 | 10.3 | 10.3 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 185.6 | 87.5° | 103.1 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 0.0 | 90° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |

(END O

| |
|---------|
| 180° |
| 11677.5 |
| 10115.3 |
| 7888.1 |
| 5892.9 |
| 4784.4 |
| 4026.5 |
| 3583.2 |
| 3438.8 |
| 3304.8 |
| 3134.6 |
| 2964.5 |
| 2784.0 |
| 2588.1 |
| 2381.9 |
| 2165.4 |
| 1948.8 |
| 1752.9 |
| 1587.9 |
| 1474.5 |
| 1350.8 |
| 1180.6 |
| 1036.3 |
| 907.4 |
| 794.0 |
| 659.9 |
| 531.0 |
| 407.3 |
| 340.3 |
| 268.1 |
| 201.1 |
| 134.0 |
| 61.9 |
| 15.5 |
| 0.0 |
| 0.0 |
| 0.0 |
| 0.0 |

F REPORT)