

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: McGRAW-EDISON

Report Number: P1437266

Luminaire Tested: **GALN-SB6B-850-U-T2LG-HSS**

Issue Date: 03/27/202

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.

Report Generated By 670245763



**Test Information**

Test Method: LM-79-08  
Report Number: P1437266  
Test Lab: INNOVATION CENTER(G1)  
Issue Date: 03/27/202  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: McGRAW-EDISON  
Catalog Number: GALN-SB6B-850-U-T2LG-HSS  
Description: GALLEON II AREA AND ROADWAY HIGH DENSITY LUMINAIRE 450mA 6xLight Square PACKAGE 80CRI 5000K FIXTURE w/ TYPE II LOW GLARE WITH HOUSE SIDE SHIELD  
Light Source: (156) 5000K CCT, 80 CRI LEDS  
Ballast/Driver: ELECTRONIC DRIVER  
Luminaire Equipment: 

<u>Sample No.</u>	<u>Condition</u>	<u>Description</u>
a	good	reflector
b	good	lens
c	good	housing
d	good	cord


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 23655.9 lumens  
Efficiency: N/A  
Efficacy: 107.3 lumens/watt  
Luminous Opening: Rectangular (W 1.5' x L: 1' x H: 0')  
IES Classification: Type II - Short  
BUG Rating: B2 - U0 - G3  
  
Input Watts (W): 220.4  
Input Voltage (V): 120  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: 0.97  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 28.75 FT

REPORT NUMBER: P1437266  
 CATALOG NUMBER: GALN-SB6B-850-U-T2LG-HSS

### Iso-Footcandle Lines of Horizontal Illumination


✕ Max cd  
 - - - 1/2 Max cd



Based on 20 foot mounting height. Maximum calculated value = 17 fc  
 Type II - Short - N/A

REPORT NUMBER: P1437266  
CATALOG NUMBER: GALN-SB6B-850-U-T2LG-HSS

### Luminous Intensity Polar Plot



— Vertical Plane Through 63-Deg Lateral      - - - Horizontal Cone Through 64-Deg Vertical

REPORT NUMBER: P1437266  
 CATALOG NUMBER: GALN-SB6B-850-U-T2LG-HSS


**FLUX DISTRIBUTION:**

		Downward	Upward	Total
<b>House Side</b>	Lumens	2807.2	0.0	2807.2
	% Fixture	11.9	0.0	11.9
<b>Street Side</b>	Lumens	20848.7	0.0	20848.7
	% Fixture	88.1	0.0	88.1
<b>Total</b>	Lumens	23655.9	0.0	23655.9
	% Fixture	100.0	0.0	100.0

**Coefficient of Utilization**

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	322.1	1.4
10°-20°	905.1	3.8
20°-30°	1612.0	6.8
30°-40°	3079.0	13.0
40°-50°	5103.6	21.6
50°-60°	6361.7	26.9
60°-70°	4743.7	20.1
70°-80°	1360.5	5.8
80°-90°	168.2	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	23655.9	100.0
0°-180°	23655.9	100.0




REPORT NUMBER: P1437266  
 CATALOG NUMBER: GALN-SB6B-850-U-T2LG-HSS

**LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:**

Zone	Lumens	% Fixture	Zone Rating/Lumen Limit		
			B	U	G
FL (0°-30°)	2184.3	9.2			
FM (30°-60°)	12824.9	54.2			
FH (60°-80°)	5679.6	24.0			G3/7500
FVH (80°-90°)	159.9	0.7			G2/225
BL (0°-30°)	654.9	2.8	B2/1000		
BM (30°-60°)	1719.4	7.3	B2/2500		
BH (60°-80°)	424.6	1.8	B1/500		G1/500
BVH (80°-90°)	8.3	0.0			G0/10
UL (90°-100°)	0.0	0.0		U0/0	
UH (100°-180°)	0.0	0.0		U0/0	

**BUG Rating: B2-U0-G3**  
 Type II Short





REPORT NUMBER: P1437266

CATALOG NUMBER: GALN-SB6B-850-U-T2LG-HSS

**CANDELA DISTRIBUTION (FULL):**

	0°	5°	15°	25°	35°	45°	55°	63°	65°	75°	85°
0°	3824.9	3824.9	3824.9	3824.9	3824.9	3824.9	3824.9	3824.9	3824.9	3824.9	3824.9
2.5°	4286.1	4271.9	4257.8	4236.5	4208.1	4179.7	4144.2	4094.5	4073.3	4002.3	3917.1
5°	4506.1	4506.1	4499.0	4484.8	4470.6	4442.3	4399.7	4335.8	4307.4	4208.1	4059.1
7.5°	4562.9	4570.0	4591.3	4619.7	4662.2	4655.1	4655.1	4584.2	4570.0	4463.5	4264.9
10°	4463.5	4470.6	4527.4	4605.5	4733.2	4853.8	4939.0	4896.4	4875.1	4768.7	4520.3
12.5°	4321.6	4321.6	4413.9	4534.5	4733.2	4960.3	5208.7	5251.2	5258.3	5137.7	4839.6
15°	3952.6	3966.8	4115.8	4357.1	4683.5	5038.3	5457.0	5620.2	5662.8	5584.8	5229.9
17.5°	3463.0	3477.2	3626.2	3952.6	4442.3	5038.3	5669.9	6046.0	6102.8	6117.0	5726.7
20°	3257.2	3257.2	3342.3	3590.7	4101.6	4903.5	5797.6	6500.2	6627.9	6784.0	6273.1
22.5°	3285.6	3285.6	3335.2	3477.2	3888.7	4719.0	5875.7	6904.7	7167.2	7564.6	6975.6
25°	3441.7	3441.7	3484.3	3576.5	3910.0	4690.6	6024.7	7266.6	7685.2	8437.5	7777.5
27.5°	3690.1	3683.0	3718.4	3810.7	4115.8	4825.5	6273.1	7628.5	8096.8	9416.7	8700.0
30°	4052.0	4030.7	4044.9	4151.3	4449.4	5137.7	6635.0	8089.7	8565.2	10488.3	9721.9
32.5°	4889.3	4882.2	4676.4	4619.7	4939.0	5641.5	7131.7	8664.5	9196.8	11623.7	10772.1
35°	6400.8	6500.2	6209.2	5464.1	5528.0	6315.7	7841.4	9445.1	9934.8	12830.0	11914.6
37.5°	7933.6	7933.6	7813.0	6933.0	6486.0	7060.8	8607.8	10247.0	10757.9	13802.2	13014.5
40°	9147.1	9210.9	9069.0	8409.1	7827.2	7912.3	9374.2	10949.5	11417.9	14398.3	13795.1
42.5°	10048.3	10034.1	9977.3	9544.5	9218.0	9026.4	10069.6	11474.7	11921.7	14703.4	14284.8
45°	11020.5	11020.5	10942.4	10587.6	10318.0	10154.7	10587.6	11914.6	12383.0	14888.0	14589.9
47.5°	12035.3	12021.1	11943.0	11552.7	11261.8	11020.5	11112.7	12198.5	12666.8	14767.3	14639.6
50°	12283.6	12269.4	12446.8	12461.0	12198.5	11737.2	11531.4	12439.7	12851.3	14774.4	14795.7
52.5°	11992.7	12077.8	12340.4	12659.7	12957.8	12475.2	11978.5	12822.9	13248.7	14973.1	15186.0
55°	11268.9	11304.3	11808.2	12319.1	13014.5	13184.8	12695.2	13433.2	13809.3	15164.7	15533.7
57.5°	9920.6	10055.4	10594.7	11481.7	12539.1	13248.7	13944.1	14455.1	14738.9	15242.8	15342.1
60°	7486.6	7557.5	8728.4	9878.0	11552.7	12737.8	15107.9	16186.6	16151.1	14362.8	14000.9
62.5°	4555.8	4619.7	5457.0	7280.8	9388.4	11673.3	15498.2	18123.8	17932.2	12879.7	11786.9
64°	3711.3	3832.0	4350.0	5911.2	7720.7	10559.2	15384.7	18287.1	18138.0	11921.7	10502.5
65°	3172.0	3335.2	3867.5	5130.6	6564.0	9360.0	15072.5	17832.9	17733.6	11339.8	9438.0
67.5°	1994.0	2072.1	2859.8	3988.1	4520.3	5989.2	12957.8	15420.2	15597.6	10105.1	6961.4
70°	1483.1	1518.6	1965.7	3086.9	3526.8	3484.3	8898.7	12489.4	12532.0	8082.6	4201.0
72.5°	1078.6	1085.7	1376.7	2285.0	2760.4	2377.2	4690.6	9281.9	8976.8	4733.2	2292.1
75°	716.7	745.1	965.1	1610.9	2150.2	1745.7	2136.0	5286.7	5194.5	2313.4	1312.8
77.5°	525.1	532.2	652.9	1078.6	1688.9	1284.4	1291.5	2277.9	2348.9	1376.7	830.3
80°	298.0	312.2	425.8	660.0	1099.9	879.9	723.8	1099.9	1263.1	936.7	553.5
82.5°	177.4	191.6	305.1	432.9	752.2	361.9	369.0	603.2	752.2	674.1	298.0
85°	106.4	113.5	191.6	234.2	447.1	241.3	134.8	298.0	390.3	397.4	163.2
87.5°	71.0	71.0	106.4	99.3	127.7	113.5	56.8	78.1	99.3	134.8	63.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1437266

CATALOG NUMBER: GALN-SB6B-850-U-T2LG-HSS

**CANDELA DISTRIBUTION (continued):**

	90°	95°	105°	115°	125°	135°	145°	155°	165°	175°	180°
0°	3824.9	3824.9	3824.9	3824.9	3824.9	3824.9	3824.9	3824.9	3824.9	3824.9	3824.9
2.5°	3846.2	3803.6	3675.9	3505.6	3349.4	3228.8	3079.8	2980.4	2888.2	2888.2	2810.1
5°	3938.4	3824.9	3512.6	3122.4	2703.7	2306.3	2050.8	1767.0	1674.7	1596.7	1610.9
7.5°	4094.5	3888.7	3335.2	2632.7	1965.7	1539.9	1256.0	1128.3	1071.5	1036.1	1043.2
10°	4286.1	4002.3	3122.4	2136.0	1447.6	1128.3	993.5	943.8	922.5	915.4	915.4
12.5°	4548.7	4137.1	2909.5	1717.3	1142.5	972.2	901.2	872.8	851.6	837.4	837.4
15°	4860.9	4307.4	2661.1	1412.2	1000.6	894.1	837.4	809.0	780.6	773.5	773.5
17.5°	5258.3	4484.8	2441.1	1213.5	929.6	837.4	780.6	745.1	723.8	716.7	716.7
20°	5698.3	4704.8	2221.1	1099.9	879.9	780.6	723.8	695.4	674.1	660.0	667.0
22.5°	6258.9	4981.6	2079.2	1043.2	837.4	730.9	674.1	645.8	624.5	610.3	617.4
25°	6876.3	5329.3	2001.1	1043.2	809.0	695.4	631.6	603.2	581.9	567.7	567.7
27.5°	7628.5	5719.6	2008.2	1085.7	801.9	667.0	596.1	567.7	546.4	525.1	525.1
30°	8458.7	6180.8	2086.3	1163.8	816.1	638.7	567.7	525.1	510.9	489.6	489.6
32.5°	9338.7	6713.1	2285.0	1263.1	801.9	603.2	525.1	489.6	468.4	454.2	454.2
35°	10268.3	7316.2	2533.4	1305.7	730.9	553.5	489.6	454.2	440.0	432.9	425.8
37.5°	11155.3	7841.4	2668.2	1220.6	638.7	510.9	447.1	411.6	404.5	390.3	390.3
40°	11843.7	8274.2	2590.1	1043.2	589.0	468.4	411.6	376.1	361.9	347.7	347.7
42.5°	12248.1	8430.4	2306.3	887.0	553.5	425.8	376.1	340.6	326.4	319.3	319.3
45°	12482.3	8409.1	1972.8	794.8	518.0	390.3	340.6	319.3	298.0	290.9	283.9
47.5°	12475.2	8189.1	1731.5	716.7	482.5	361.9	319.3	298.0	276.8	269.7	269.7
50°	12425.5	7862.7	1461.8	660.0	454.2	340.6	298.0	283.9	262.6	255.5	248.4
52.5°	12546.2	7678.2	1220.6	624.5	418.7	326.4	290.9	269.7	241.3	234.2	234.2
55°	12695.2	7571.7	979.3	589.0	390.3	319.3	276.8	255.5	227.1	220.0	220.0
57.5°	12262.3	7167.2	809.0	532.2	354.8	305.1	262.6	248.4	220.0	198.7	198.7
60°	10899.9	5925.4	667.0	468.4	326.4	283.9	248.4	227.1	198.7	170.3	170.3
62.5°	8863.2	4520.3	553.5	397.4	305.1	262.6	227.1	205.8	170.3	134.8	134.8
64°	7699.4	3839.1	496.7	347.7	290.9	241.3	205.8	184.5	149.0	113.5	106.4
65°	6904.7	3392.0	461.3	326.4	283.9	227.1	198.7	177.4	134.8	106.4	99.3
67.5°	4860.9	2277.9	369.0	269.7	248.4	191.6	170.3	149.0	120.6	92.3	85.2
70°	2831.4	1291.5	290.9	227.1	191.6	149.0	141.9	134.8	106.4	71.0	71.0
72.5°	1539.9	645.8	220.0	184.5	149.0	106.4	120.6	106.4	85.2	56.8	49.7
75°	943.8	397.4	163.2	134.8	99.3	78.1	92.3	78.1	49.7	35.5	28.4
77.5°	631.6	255.5	120.6	92.3	63.9	49.7	63.9	42.6	21.3	7.1	7.1
80°	390.3	177.4	78.1	56.8	35.5	21.3	14.2	7.1	7.1	0.0	0.0
82.5°	170.3	113.5	42.6	28.4	14.2	7.1	7.1	0.0	0.0	0.0	0.0
85°	92.3	35.5	14.2	7.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	28.4	14.2	7.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-12

Test Date: 10/11/2024

Luminaire Tested: GSS-SB1A-850-U-5WQ

Data in this report applies to families of products including GSS-SB1A-850-U-5WQ



REPORT NUMBER: SP1-2407-184-12

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-12

**CIE 1931 Chromaticity Diagram**




**CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles**



Point lies inside the ANSI 5000K 7-step quadrangle

REPORT NUMBER: SP1-2407-184-12

**Photopic Flux vs. Wavelength**



**Photopic Lumens: NR**

$\lambda$ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens $(\phi/\text{nm})$	$\lambda$ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens $(\phi/\text{nm})$	$\lambda$ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens $(\phi/\text{nm})$	$\lambda$ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens $(\phi/\text{nm})$	$\lambda$ (nm)	Power $\text{W}^{\wedge}/\text{nm}$	Lumens $(\phi/\text{nm})$
360	0	NR	490	270	NR	620	517	NR	750	17	NR	880	0	NR
365	0	NR	495	335	NR	625	486	NR	755	15	NR	885	0	NR
370	0	NR	500	397	NR	630	454	NR	760	12	NR	890	0	NR
375	0	NR	505	451	NR	635	419	NR	765	11	NR	895	0	NR
380	0	NR	510	492	NR	640	384	NR	770	9	NR	900	0	NR
385	1	NR	515	524	NR	645	347	NR	775	8	NR	905	0	NR
390	3	NR	520	545	NR	650	313	NR	780	7	NR	910	0	NR
395	5	NR	525	558	NR	655	280	NR	785	6	NR	915	0	NR
400	7	NR	530	568	NR	660	248	NR	790	5	NR	920	0	NR
405	13	NR	535	575	NR	665	219	NR	795	4	NR	925	0	NR
410	24	NR	540	579	NR	670	192	NR	800	4	NR	930	0	NR
415	47	NR	545	585	NR	675	167	NR	805	3	NR	935	0	NR
420	95	NR	550	588	NR	680	146	NR	810	3	NR	940	0	NR
425	181	NR	555	593	NR	685	126	NR	815	2	NR	945	0	NR
430	319	NR	560	595	NR	690	109	NR	820	2	NR	950	0	NR
435	539	NR	565	600	NR	695	94	NR	825	2	NR	955	0	NR
440	868	NR	570	603	NR	700	80	NR	830	2	NR	960	0	NR
445	977	NR	575	606	NR	705	69	NR	835	1	NR	965	0	NR
450	601	NR	580	609	NR	710	59	NR	840	1	NR	970	0	NR
455	397	NR	585	611	NR	715	51	NR	845	1	NR	975	0	NR
460	302	NR	590	610	NR	720	44	NR	850	1	NR	980	0	NR
465	201	NR	595	604	NR	725	37	NR	855	1	NR	985	0	NR
470	157	NR	600	596	NR	730	32	NR	860	1	NR	990	0	NR
475	157	NR	605	583	NR	735	27	NR	865	1	NR	995	0	NR
480	171	NR	610	566	NR	740	23	NR	870	1	NR	1000	0	NR
485	210	NR	615	543	NR	745	20	NR	875	0	NR			

REPORT NUMBER: SP1-2407-184-12

**Scotopic Flux vs. Wavelength**



**Scotopic Lumens: NR**

**S/P: 1.83**

λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)
360	0	NR	490	270	NR	620	517	NR	750	17	NR	880	0	NR
365	0	NR	495	335	NR	625	486	NR	755	15	NR	885	0	NR
370	0	NR	500	397	NR	630	454	NR	760	12	NR	890	0	NR
375	0	NR	505	451	NR	635	419	NR	765	11	NR	895	0	NR
380	0	NR	510	492	NR	640	384	NR	770	9	NR	900	0	NR
385	1	NR	515	524	NR	645	347	NR	775	8	NR	905	0	NR
390	3	NR	520	545	NR	650	313	NR	780	7	NR	910	0	NR
395	5	NR	525	558	NR	655	280	NR	785	6	NR	915	0	NR
400	7	NR	530	568	NR	660	248	NR	790	5	NR	920	0	NR
405	13	NR	535	575	NR	665	219	NR	795	4	NR	925	0	NR
410	24	NR	540	579	NR	670	192	NR	800	4	NR	930	0	NR
415	47	NR	545	585	NR	675	167	NR	805	3	NR	935	0	NR
420	95	NR	550	588	NR	680	146	NR	810	3	NR	940	0	NR
425	181	NR	555	593	NR	685	126	NR	815	2	NR	945	0	NR
430	319	NR	560	595	NR	690	109	NR	820	2	NR	950	0	NR
435	539	NR	565	600	NR	695	94	NR	825	2	NR	955	0	NR
440	868	NR	570	603	NR	700	80	NR	830	2	NR	960	0	NR
445	977	NR	575	606	NR	705	69	NR	835	1	NR	965	0	NR
450	601	NR	580	609	NR	710	59	NR	840	1	NR	970	0	NR
455	397	NR	585	611	NR	715	51	NR	845	1	NR	975	0	NR
460	302	NR	590	610	NR	720	44	NR	850	1	NR	980	0	NR
465	201	NR	595	604	NR	725	37	NR	855	1	NR	985	0	NR
470	157	NR	600	596	NR	730	32	NR	860	1	NR	990	0	NR
475	157	NR	605	583	NR	735	27	NR	865	1	NR	995	0	NR
480	171	NR	610	566	NR	740	23	NR	870	1	NR	1000	0	NR
485	210	NR	615	543	NR	745	20	NR	875	0	NR			

REPORT NUMBER: SP1-2407-184-12

**Melanopic Flux vs. Wavelength**



**Melanopic Lumens: NR**

**M/P: 3.74**


λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)
360	0	NR	490	270	NR	620	517	NR	750	17	NR	880	0	NR
365	0	NR	495	335	NR	625	486	NR	755	15	NR	885	0	NR
370	0	NR	500	397	NR	630	454	NR	760	12	NR	890	0	NR
375	0	NR	505	451	NR	635	419	NR	765	11	NR	895	0	NR
380	0	NR	510	492	NR	640	384	NR	770	9	NR	900	0	NR
385	1	NR	515	524	NR	645	347	NR	775	8	NR	905	0	NR
390	3	NR	520	545	NR	650	313	NR	780	7	NR	910	0	NR
395	5	NR	525	558	NR	655	280	NR	785	6	NR	915	0	NR
400	7	NR	530	568	NR	660	248	NR	790	5	NR	920	0	NR
405	13	NR	535	575	NR	665	219	NR	795	4	NR	925	0	NR
410	24	NR	540	579	NR	670	192	NR	800	4	NR	930	0	NR
415	47	NR	545	585	NR	675	167	NR	805	3	NR	935	0	NR
420	95	NR	550	588	NR	680	146	NR	810	3	NR	940	0	NR
425	181	NR	555	593	NR	685	126	NR	815	2	NR	945	0	NR
430	319	NR	560	595	NR	690	109	NR	820	2	NR	950	0	NR
435	539	NR	565	600	NR	695	94	NR	825	2	NR	955	0	NR
440	868	NR	570	603	NR	700	80	NR	830	2	NR	960	0	NR
445	977	NR	575	606	NR	705	69	NR	835	1	NR	965	0	NR
450	601	NR	580	609	NR	710	59	NR	840	1	NR	970	0	NR
455	397	NR	585	611	NR	715	51	NR	845	1	NR	975	0	NR
460	302	NR	590	610	NR	720	44	NR	850	1	NR	980	0	NR
465	201	NR	595	604	NR	725	37	NR	855	1	NR	985	0	NR
470	157	NR	600	596	NR	730	32	NR	860	1	NR	990	0	NR
475	157	NR	605	583	NR	735	27	NR	865	1	NR	995	0	NR
480	171	NR	610	566	NR	740	23	NR	870	1	NR	1000	0	NR
485	210	NR	615	543	NR	745	20	NR	875	0	NR			

**Summary**

$R_f = 82$   
 $R_g = 99.4$   
 $CIE R_a = 81.1$   
 $R_9 = 8.7$



**Color Vector Graphics**



**Individual Sample Fidelity Index ( $R_{f,i}$ )**

CES01 = 85	CES26 = 73	CES51 = 92	CES76 = 66
CES02 = 60	CES27 = 90	CES52 = 93	CES77 = 80
CES03 = 30	CES28 = 87	CES53 = 84	CES78 = 65
CES04 = 69	CES29 = 69	CES54 = 88	CES79 = 87
CES05 = 47	CES30 = 73	CES55 = 88	CES80 = 83
CES06 = 50	CES31 = 72	CES56 = 80	CES81 = 84
CES07 = 40	CES32 = 69	CES57 = 78	CES82 = 93
CES08 = 39	CES33 = 75	CES58 = 80	CES83 = 90
CES09 = 29	CES34 = 78	CES59 = 93	CES84 = 92
CES10 = 73	CES35 = 88	CES60 = 95	CES85 = 87
CES11 = 56	CES36 = 98	CES61 = 93	CES86 = 80
CES12 = 62	CES37 = 85	CES62 = 88	CES87 = 84
CES13 = 42	CES38 = 81	CES63 = 83	CES88 = 85
CES14 = 74	CES39 = 93	CES64 = 83	CES89 = 80
CES15 = 71	CES40 = 88	CES65 = 77	CES90 = 83
CES16 = 46	CES41 = 89	CES66 = 81	CES91 = 89
CES17 = 48	CES42 = 82	CES67 = 80	CES92 = 73
CES18 = 55	CES43 = 80	CES68 = 83	CES93 = 85
CES19 = 70	CES44 = 99	CES69 = 89	CES94 = 67
CES20 = 64	CES45 = 87	CES70 = 75	CES95 = 78
CES21 = 85	CES46 = 85	CES71 = 73	CES96 = 84
CES22 = 77	CES47 = 82	CES72 = 91	CES97 = 87
CES23 = 91	CES48 = 78	CES73 = 67	CES98 = 81
CES24 = 90	CES49 = 84	CES74 = 98	CES99 = 74
CES25 = 71	CES50 = 91	CES75 = 70	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)