Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled data based on original data using

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: McGRAW-EDISON

Report Number: P955136

Luminaire Tested: **GALN-SB8A-935-U-T2U**

Issue Date: 1/21/2025

Report Generated By 670246001

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Test Information

Test Method:	LM-79-08
Report Number:	P955136
	TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2411-289-16)
Test Lab:	INNOVATION CENTER
Issue Date:	1/21/2025
Manufacturer:	COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line:	McGRAW-EDISON
Catalog Number:	GALN-SB8A-935-U-T2U
Description:	GALLEON AREA AND ROADWAY HIGH DENSITY LED LUMINAIRE
	(8) 90 CRI, 3500K, 350mA LIGHTSQUARES WITH 26 LEDS EACH AND TYPE II U OPTICS
Light Source:	-
Ballast/Driver:	-

Summary

Lumens per Lamp:	N/A
Luminaire Lumens:	25571 lumens
Efficiency:	N/A
Efficacy:	112.6 lumens/watt
Luminous Opening:	Rectangular (W 1.5' x L: 1.5' x H: 0')
IES Classification:	Type II - Short
BUG Rating:	B4 - U0 - G4

Input Watts (W):	227.1
Input Voltage (V):	NR
Input Current (Ain):	NR
Voltage Rise (V):	NR
Power Factor:	NR
Total Harmonic Distortion (THDi):	NR
Frequency (hertz):	60
Stabilization Time:	NR
Operation Time:	NR
Ambient Temperature (°C):	NR
Test Distance:	24 FT

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P955136
CATALOG NUMBER: GALN-SB8A-935-U-T2U

Iso-Footcandle Lines of Horizontal Illumination



Based on 25 foot mounting height. Maximum calculated value = 7.2 fc
Type II - Short - N/A

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P955136
CATALOG NUMBER: GALN-SB8A-935-U-T2U

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P955136
CATALOG NUMBER: GALN-SB8A-935-U-T2U

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	8069.1	0.0	8069.1
	% Fixture	31.6	0.0	31.6
Street Side	Lumens	17501.9	0.0	17501.9
	% Fixture	68.4	0.0	68.4
Total	Lumens	25571.0	0.0	25571.0
	% Fixture	100.0	0.0	100.0

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	280.9	1.1
10°-20°	952.7	3.7
20°-30°	1931.6	7.6
30°-40°	3342.7	13.1
40°-50°	5058.5	19.8
50°-60°	5930.7	23.2
60°-70°	4972.2	19.4
70°-80°	2745.1	10.7
80°-90°	356.6	1.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	25571.0	100.0
0°-180°	25571.0	100.0



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P955136
CATALOG NUMBER: GALN-SB8A-935-U-T2U

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit B	U	G
FL	(0°-30°)	1685.5	6.6			
FM	(30°-60°)	10479.8	41.0			
FH	(60°-80°)	5128.8	20.1			G3/7500
FVH	(80°-90°)	207.8	0.8			G2/225
BL	(0°-30°)	1479.8	5.8	B3/2500		
BM	(30°-60°)	3852.1	15.1	B3/5000		
BH	(60°-80°)	2588.5	10.1	B4/5000		G4/5000
BVH	(80°-90°)	148.8	0.6			G2/225
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B4-U0-G4
Type II Short



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P955136
CATALOG NUMBER: GALN-SB8A-935-U-T2U

CANDELA DISTRIBUTION (FULL):

	0°	5°	15°	25°	35°	45°	55°	65°	67°	75°
0°	2817.8	2817.8	2817.8	2817.8	2817.8	2817.8	2817.8	*2817.8*	2817.8	2817.8
2.5°	2799.2	2791.3	2797.9	2797.9	2800.6	2799.2	2808.5	*2811.2*	2815.2	2823.1
5°	2771.4	2770.1	2782.0	2792.6	2803.2	2812.5	2824.4	*2841.7*	2844.3	2853.6
7.5°	2762.1	2754.1	2772.7	2786.0	2811.2	2833.7	2865.6	*2894.8*	2906.7	2910.7
10°	2833.7	2820.5	2837.7	2845.7	2866.9	2889.5	2926.6	*2973.0*	2986.3	3002.2
12.5°	2955.8	2941.2	2966.4	2978.3	2998.2	3018.1	3043.3	*3088.5*	3095.1	3124.3
15°	3122.9	3105.7	3121.6	3136.2	3169.4	3187.9	3213.2	*3256.9*	3256.9	3279.5
17.5°	3349.8	3327.2	3339.2	3344.5	3365.7	3393.6	3436.0	*3474.5*	3494.4	3486.4
20°	3688.1	3660.2	3660.2	3633.7	3625.7	3648.3	3704.0	*3757.1*	3778.3	3737.2
22.5°	4196.2	4156.4	4133.9	4043.6	4007.8	4010.5	4066.2	*4131.2*	4148.4	4075.5
25°	4842.3	4779.9	4749.4	4616.8	4535.8	4465.5	4509.3	*4592.9*	4616.8	4526.5
27.5°	5488.4	5492.3	5463.2	5304.0	5170.0	5041.3	5018.7	*5106.3*	5131.5	5029.3
30°	6394.5	6300.3	6244.6	6053.5	5862.5	5682.1	5589.2	*5625.0*	5631.6	5509.6
32.5°	7175.9	7152.0	7032.6	6865.4	6620.0	6337.4	6182.2	*6125.2*	6114.5	5940.8
35°	8066.1	8052.8	7926.8	7727.8	7462.4	7069.7	6789.8	*6626.6*	6613.4	6369.3
37.5°	8970.8	8970.8	8847.5	8629.9	8355.3	7864.4	7438.5	*7179.9*	7137.4	6819.0
40°	9692.5	9648.8	9671.3	9579.8	9265.4	8744.0	8158.9	*7783.5*	7726.4	7344.4
42.5°	10102.5	10087.9	10223.2	10325.3	10196.7	9780.1	8952.3	*8437.5*	8357.9	7922.8
45°	10194.0	10178.1	10419.5	10793.7	10974.1	10802.9	9814.6	*9126.1*	9029.2	8527.7
47.5°	9983.1	9951.2	10305.4	10895.8	11474.2	11775.4	10748.6	*9873.0*	9732.3	9116.8
50°	9348.9	9318.4	9854.4	10638.4	11642.7	12436.1	11762.1	*10665.0*	10450.1	9748.3
52.5°	7970.5	7985.1	8824.9	9902.1	11421.2	12847.3	12635.1	*11499.4*	11240.7	10394.3
55°	6208.7	6240.6	7272.7	8458.7	10535.0	12785.0	13230.7	*12359.1*	12101.7	11001.9
57.5°	4445.6	4586.2	5553.4	6727.5	8832.9	11796.6	13360.7	*13176.3*	12926.9	11665.3
60°	2881.5	2906.7	3901.7	5085.1	6726.1	10040.1	13096.7	*13795.9*	13600.9	12341.9
62.5°	*1846.7*	*1863.9*	*2470.2*	*3556.8*	*4841.0*	*7427.9*	*12207.9*	*14065.2*	*14005.5*	*12788.9*
65°	1357.2	1343.9	1659.6	2350.8	3260.9	4580.9	10481.9	*13935.2*	14053.2	13068.9
67.5°	1133.0	1114.4	1269.6	1627.8	2402.6	2601.6	7755.6	*13090.1*	13522.6	13037.0
70°	1032.1	1016.2	1110.4	1208.6	1874.6	1741.9	3909.6	*11380.0*	12046.0	12674.9
72.5°	874.3	846.4	975.1	1073.3	1458.0	1335.9	1615.9	*8741.3*	9553.2	11514.0
75°	677.9	659.3	769.5	944.6	1095.8	1042.8	1021.5	*5307.9*	6194.1	8904.5
77.5°	537.3	512.1	612.9	736.3	985.7	786.7	744.3	*2285.8*	3164.1	5684.7
80°	404.6	382.1	465.7	582.4	757.5	593.0	481.6	*932.6*	1192.7	2880.2
82.5°	287.9	268.0	325.0	427.2	509.4	532.0	295.8	*522.7*	587.7	1110.4
85°	184.4	172.5	217.6	268.0	323.7	342.3	180.4	*273.3*	299.8	457.7
87.5°	100.8	82.3	116.7	124.7	149.9	136.6	86.2	*99.5*	107.5	165.8
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	*0.0*	0.0	0.0

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P955136
CATALOG NUMBER: GALN-SB8A-935-U-T2U

CANDELA DISTRIBUTION (continued):

85°		90°	95°	105°	115°	125°	135°	145°	155°	165°	175°
2817.8	0°	2817.8	2817.8	2817.8	2817.8	2817.8	2817.8	2817.8	2817.8	2817.8	2817.8
2823.1	2.5°	2828.4	2832.4	2845.7	2849.7	2858.9	2870.9	2878.8	2886.8	2886.8	2894.8
2865.6	5°	2866.9	2876.2	2904.0	2918.6	2942.5	2966.4	2981.0	2998.2	3008.9	3014.2
2933.2	7.5°	2941.2	2955.8	2995.6	3020.8	3061.9	3095.1	3117.6	3141.5	3146.8	3161.4
3027.4	10°	3042.0	3059.3	3104.4	3152.1	3201.2	3242.3	3263.6	3280.8	3287.4	3290.1
3148.2	12.5°	3157.4	3182.6	3241.0	3299.4	3351.1	3386.9	3392.3	3388.3	3369.7	3353.8
3296.7	15°	3299.4	3321.9	3386.9	3450.6	3501.0	3507.7	3474.5	3453.3	3430.7	3426.7
3462.6	17.5°	3469.2	3481.1	3540.8	3603.2	3607.2	3584.6	3535.5	3515.6	3494.4	3479.8
3678.8	20°	3666.9	3662.9	3705.3	3731.9	3704.0	3635.0	3560.7	3527.6	3506.3	3489.1
3944.1	22.5°	3903.0	3872.5	3867.2	3860.6	3786.3	3641.7	3540.8	3498.4	3465.2	3441.3
4314.3	25°	4246.6	4129.9	4048.9	4003.8	3836.7	3605.8	3477.2	3383.0	3320.6	3279.5
4766.7	27.5°	4676.5	4480.1	4275.8	4165.7	3836.7	3532.9	3323.3	3170.7	3068.6	3026.1
5204.5	30°	5086.4	4880.8	4579.6	4360.7	3827.4	3413.5	3075.2	2862.9	2743.5	2701.1
5578.6	32.5°	5436.6	5212.4	4902.0	4574.3	3804.8	3219.8	2767.4	2532.6	2417.2	2366.8
5948.7	35°	5761.7	5522.9	5225.7	4809.1	3745.1	2935.9	2429.1	2250.0	2121.3	2040.4
6325.5	37.5°	6094.6	5810.7	5532.1	5021.4	3637.7	2604.2	2169.1	2016.5	1865.3	1756.5
6726.1	40°	6456.8	6117.2	5859.8	5147.4	3461.2	2288.5	1967.4	1828.1	1667.6	1552.2
7187.8	42.5°	6880.0	6484.7	6224.7	5212.4	3219.8	2064.3	1836.1	1699.4	1548.2	1454.0
7682.7	45°	7321.8	6889.3	6557.7	5211.1	2950.5	1959.5	1793.6	1658.3	1491.2	1393.0
8190.8	47.5°	7784.8	7312.5	6845.5	5126.2	2717.0	1974.1	1769.8	1569.4	1385.0	1289.5
8704.2	50°	8249.1	7775.5	7124.1	4967.0	2617.5	1942.2	1680.9	1444.7	1227.2	1140.9
9185.8	52.5°	8709.5	8267.7	7364.3	4740.1	2516.7	1824.1	1566.8	1282.9	1162.1	1102.4
9683.2	55°	9172.5	8754.6	7625.6	4409.8	2264.6	1686.2	1375.7	1221.8	1110.4	1056.0
10170.1	57.5°	9636.8	9317.1	7873.7	4079.5	1947.5	1516.4	1270.9	1147.6	1058.7	1012.2
10577.4	60°	10119.7	9960.5	8129.7	3775.7	1634.4	1298.8	1194.0	1087.9	997.6	945.9
10968.8	62.5°	*10617.2*	*10669.0*	*8330.1*	*3384.3*	*1346.6*	*1166.1*	*1125.0*	*1016.2*	*928.7*	*879.6*
11292.5	65°	11118.7	11352.2	8461.4	2841.7	1091.8	1040.1	1050.7	937.9	849.1	806.6
11530.0	67.5°	11496.8	11844.4	8424.3	2150.5	895.5	920.7	957.8	855.7	772.1	738.9
11491.5	70°	11539.2	11786.0	8058.1	1472.6	749.6	804.0	854.4	774.8	688.5	664.7
10950.2	72.5°	10974.1	10990.0	7037.9	961.8	634.1	705.8	745.6	692.5	608.9	585.1
9579.8	75°	9492.2	9088.9	5167.3	634.1	530.7	606.3	643.4	606.3	525.4	530.7
7167.9	77.5°	7191.8	6436.9	3137.5	451.1	443.1	509.4	559.8	533.3	464.3	521.4
3604.5	80°	3705.3	3482.5	1399.6	337.0	350.2	407.3	460.3	425.9	367.5	350.2
805.3	82.5°	849.1	987.0	551.9	241.5	253.4	293.2	351.6	319.7	264.0	222.9
335.6	85°	297.2	325.0	244.1	151.2	148.6	183.1	238.8	213.6	179.1	143.3
142.0	87.5°	94.2	123.4	91.5	61.0	63.7	82.3	110.1	100.8	83.6	54.4
0.0	90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END O

Scaled Data Report

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

180°
2817.8
2894.8
3016.8
3156.1
3283.5
3353.8
3426.7
3481.1
3490.4
3449.3
3295.4
3047.3
2726.3
2392.0
2066.9
1785.7
1574.7
1472.6
1408.9
1302.8
1146.2
1102.4
1050.7
1004.3
941.9
878.2
805.3
740.3
666.0
583.7
512.1
459.0
319.7
220.2
151.2
57.0
0.0

F REPORT)