Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled data based on original data using

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: McGRAW-EDISON

Report Number: P956560

Luminaire Tested: **GALN-SB9A-935-U-SLR**

Issue Date: 1/21/2025

Report Generated By 670246001

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Test Information

Test Method:	LM-79-08
Report Number:	P956560
	TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2411-289-8)
Test Lab:	INNOVATION CENTER
Issue Date:	1/21/2025
Manufacturer:	COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line:	McGRAW-EDISON
Catalog Number:	GALN-SB9A-935-U-SLR
Description:	GALLEON AREA AND ROADWAY HIGH DENSITY LED LUMINAIRE
	(9) 90 CRI, 3500K, 350mA LIGHTSQUARES WITH 26 LEDS EACH AND SPILL LIGHT ELIMINATOR RIGHT OPTICS
Light Source:	-
Ballast/Driver:	-

Summary

Lumens per Lamp:	N/A
Luminaire Lumens:	28321 lumens
Efficiency:	N/A
Efficacy:	110.8 lumens/watt
Luminous Opening:	Rectangular (W 1.5' x L: 1.5' x H: 0')
IES Classification:	Type IV - Short
BUG Rating:	B3 - U0 - G5

Input Watts (W):	255.5
Input Voltage (V):	NR
Input Current (Ain):	NR
Voltage Rise (V):	NR
Power Factor:	NR
Total Harmonic Distortion (THDi):	NR
Frequency (hertz):	60
Stabilization Time:	NR
Operation Time:	NR
Ambient Temperature (°C):	NR
Test Distance:	24 FT

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P956560
CATALOG NUMBER: GALN-SB9A-935-U-SLR

Iso-Footcandle Lines of Horizontal Illumination



Based on 25 foot mounting height. Maximum calculated value = 7.7 fc
Type IV - Short - N/A

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P956560
CATALOG NUMBER: GALN-SB9A-935-U-SLR

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P956560
CATALOG NUMBER: GALN-SB9A-935-U-SLR

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	7197.8	0.0	7197.8
	% Fixture	25.4	0.0	25.4
Street Side	Lumens	21123.2	0.0	21123.2
	% Fixture	74.6	0.0	74.6
Total	Lumens	28321.0	0.0	28321.0
	% Fixture	100.0	0.0	100.0

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	386.3	1.4
10°-20°	1212.7	4.3
20°-30°	1873.3	6.6
30°-40°	2373.9	8.4
40°-50°	3580.4	12.6
50°-60°	5784.7	20.4
60°-70°	7211.6	25.5
70°-80°	4729.0	16.7
80°-90°	1169.1	4.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	28321.0	100.0
0°-180°	28321.0	100.0



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P956560
CATALOG NUMBER: GALN-SB9A-935-U-SLR

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit B	U	G
FL	(0°-30°)	1904.9	6.7			
FM	(30°-60°)	8260.6	29.2			
FH	(60°-80°)	9994.6	35.3			G4/12000
FVH	(80°-90°)	963.1	3.4			G5
BL	(0°-30°)	1567.4	5.5	B3/2500		
BM	(30°-60°)	3478.4	12.3	B3/5000		
BH	(60°-80°)	1945.9	6.9	B3/2500		G3/2500
BVH	(80°-90°)	206.0	0.7			G2/225
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B3-U0-G5
Type IV Short



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P956560
CATALOG NUMBER: GALN-SB9A-935-U-SLR

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°
0°	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4
2.5°	4188.0	4155.9	4123.8	4089.5	4055.5	4021.1	3986.7	3953.9	3921.0	3889.2
5°	4503.3	4432.4	4361.4	4290.5	4219.9	4148.6	4077.4	4010.9	3944.4	3881.7
7.5°	4820.2	4703.0	4586.0	4477.8	4369.6	4264.2	4158.9	4066.1	3973.3	3887.7
10°	5063.0	4914.9	4766.8	4623.8	4480.9	4353.0	4224.9	4115.3	4005.3	3899.6
12.5°	5211.7	5048.9	4886.4	4724.4	4562.4	4411.4	4260.5	4136.3	4012.1	3901.1
15°	5302.1	5132.5	4962.9	4787.1	4611.4	4437.6	4263.8	4120.0	3976.3	3853.3
17.5°	5352.9	5180.9	5008.9	4817.2	4625.4	4423.7	4222.0	4049.1	3876.1	3731.5
20°	5408.9	5230.2	5051.3	4840.6	4629.9	4385.4	4141.0	3926.7	3712.4	3543.9
22.5°	5474.0	5291.3	5108.6	4872.3	4635.9	4338.5	4041.1	3783.0	3525.0	3333.2
25°	5557.6	5378.6	5199.7	4929.7	4659.5	4292.2	3925.0	3622.7	3320.5	3124.0
27.5°	5671.2	5500.6	5329.7	5019.4	4708.8	4261.3	3813.7	3476.1	3138.5	2959.6
30°	5824.4	5659.4	5494.6	5135.5	4776.4	4246.8	3716.8	3353.6	2990.3	2840.1
32.5°	6005.2	5841.9	5678.7	5256.7	4834.7	4228.8	3622.7	3247.9	2873.0	2751.9
35°	6224.9	6068.6	5912.1	5394.7	4877.4	4195.1	3513.0	3144.0	2775.1	2674.2
37.5°	6594.7	6395.4	6196.0	5549.4	4902.8	4137.2	3371.6	3021.8	2672.0	2583.8
40°	7153.6	6863.1	6572.6	5745.8	4918.8	4057.6	3196.5	2876.0	2555.4	2475.5
42.5°	7894.9	7475.5	7056.2	6002.7	4949.1	3975.4	3001.9	2715.0	2428.1	2354.4
45°	8810.2	8244.6	7678.9	6340.7	5002.5	3899.0	2795.7	2544.1	2292.4	2217.7
47.5°	9954.9	9158.8	8362.6	6700.8	5039.1	3836.0	2632.8	2408.8	2184.8	2088.4
50°	11455.2	10255.1	9054.8	7035.0	5015.2	3767.2	2519.2	2319.0	2118.7	1992.0
52.5°	13177.5	11406.7	9635.8	7252.0	4868.0	3651.1	2434.4	2259.8	2085.4	1939.7
55°	15011.2	12427.6	9844.3	7204.2	4563.9	3458.6	2353.4	2216.9	2080.5	1944.9
57.5°	16678.9	13151.2	9623.6	6867.6	4111.8	3187.2	2262.5	2166.1	2069.7	1950.2
60°	17686.9	13332.1	8977.1	6241.3	3505.5	2834.9	2164.2	2088.4	2012.6	1933.7
62.5°	17175.0	12570.7	7966.3	5394.5	2822.6	2413.1	2003.7	1953.3	1903.1	1893.4
65°	*16150.6*	*11493.4*	*6836.1*	*4530.4*	*2224.8*	*2033.7*	*1842.6*	*1818.8*	*1795.1*	*1796.3*
67.5°	14778.0	10211.3	5644.6	3684.0	1723.3	1669.1	1614.7	1628.0	1641.1	1637.9
70°	13129.0	8812.4	4495.9	2900.6	1305.4	1320.9	1336.3	1397.9	1459.3	1459.3
72.5°	11163.8	7295.9	3428.1	2217.5	1006.9	1053.7	1100.6	1187.9	1275.0	1289.7
75°	8677.9	5557.5	2437.1	1609.5	781.9	824.3	866.7	964.5	1062.2	1129.8
77.5°	6200.2	3889.7	1579.3	1090.6	601.9	630.8	659.8	754.7	849.6	960.9
80°	4058.0	2506.1	954.2	702.7	451.3	463.3	475.2	555.6	635.9	768.9
82.5°	2358.9	1450.5	542.2	432.2	322.5	324.6	327.0	386.2	445.3	558.9
85°	1037.9	652.5	267.2	231.0	195.0	194.0	192.8	236.1	279.5	363.9
87.5°	321.3	213.7	106.1	95.8	85.5	84.4	83.4	101.0	118.8	153.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P956560
CATALOG NUMBER: GALN-SB9A-935-U-SLR

CANDELA DISTRIBUTION (continued):

50°		55°	60°	65°	70°	75°	80°	85°	90°	95°	100°
3894.4	0°	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4
3853.7	2.5°	3825.0	3796.5	3770.6	3744.9	3722.4	3699.8	3677.1	3654.5	3637.0	3619.4
3819.7	5°	3765.6	3711.3	3665.9	3620.6	3580.6	3540.5	3504.2	3467.7	3439.8	3411.7
3807.4	7.5°	3735.4	3663.5	3603.7	3543.9	3493.6	3443.1	3398.5	3354.2	3320.8	3287.7
3813.4	10°	3737.5	3661.6	3601.8	3542.0	3487.8	3433.4	3383.3	3333.2	3293.5	3253.6
3820.9	12.5°	3758.7	3696.8	3657.1	3617.6	3574.9	3532.4	3480.6	3428.9	3378.1	3327.3
3789.0	15°	3759.3	3729.7	3735.1	3740.5	3729.4	3718.3	3673.4	3628.4	3556.1	3483.7
3691.9	17.5°	3702.8	3713.6	3778.7	3843.9	3878.5	3913.1	3876.7	3840.6	3744.8	3649.0
3533.5	20°	3584.3	3635.1	3748.2	3861.5	3934.0	4006.5	3989.7	3972.8	3863.3	3753.9
3353.7	22.5°	3428.9	3504.0	3633.2	3762.6	3856.9	3951.2	3961.3	3971.3	3866.7	3762.1
3179.3	25°	3266.0	3352.7	3468.8	3585.0	3677.8	3770.6	3805.3	3839.8	3754.1	3668.4
3026.9	27.5°	3110.6	3194.3	3289.8	3385.1	3459.5	3533.9	3572.5	3611.2	3550.1	3489.1
2892.8	30°	2959.2	3025.8	3105.0	3184.2	3246.0	3307.8	3339.2	3370.6	3324.1	3277.5
2775.4	32.5°	2814.7	2854.0	2917.2	2980.6	3039.7	3099.1	3133.9	3168.9	3126.1	3083.2
2664.5	35°	2675.3	2686.2	2734.4	2782.6	2841.1	2899.9	2941.7	2983.6	2953.1	2922.7
2548.2	37.5°	2536.3	2524.3	2559.0	2593.5	2651.9	2710.5	2762.2	2813.9	2799.9	2785.8
2420.9	40°	2393.9	2366.8	2391.8	2416.7	2473.2	2529.7	2589.2	2648.8	2652.2	2655.5
2285.7	42.5°	2249.8	2213.9	2234.3	2254.7	2308.2	2361.9	2426.1	2490.4	2507.6	2524.8
2151.2	45°	2116.2	2081.4	2098.4	2115.8	2166.6	2217.4	2284.0	2350.7	2375.3	2400.0
2031.2	47.5°	2001.9	1972.6	1988.7	2004.7	2054.5	2104.1	2169.9	2235.6	2264.0	2292.4
1925.5	50°	1899.5	1873.7	1898.8	1924.0	1971.0	2017.7	2076.6	2135.5	2171.9	2208.4
1846.8	52.5°	1821.1	1795.5	1833.3	1871.0	1914.0	1956.9	2011.7	2066.7	2109.9	2153.1
1804.9	55°	1764.3	1723.8	1777.4	1830.9	1877.3	1923.6	1971.7	2019.7	2065.4	2111.3
1779.8	57.5°	1720.6	1661.5	1719.1	1776.8	1831.2	1885.6	1933.1	1980.8	2027.0	2073.0
1756.2	60°	1679.5	1602.7	1653.4	1703.9	1766.4	1828.8	1877.1	1925.5	1971.8	2018.2
1728.7	62.5°	1632.8	1537.0	1569.1	1601.2	1674.0	1746.9	1798.5	1850.1	1892.5	1934.9
1670.7	65°	*1568.8*	*1466.7*	*1479.1*	*1491.4*	*1569.4*	*1647.6*	*1696.9*	*1746.2*	*1783.6*	*1820.9*
1567.3	67.5°	1482.4	1397.6	1393.7	1389.8	1461.8	1534.0	1580.8	1627.4	1659.7	1691.9
1436.1	70°	1375.7	1315.4	1301.9	1288.5	1351.8	1415.2	1455.5	1495.9	1525.0	1554.2
1290.0	72.5°	1248.6	1207.2	1187.4	1167.9	1217.8	1267.5	1304.0	1340.5	1369.0	1397.6
1124.1	75°	1092.2	1060.3	1041.4	1022.5	1059.5	1096.6	1129.6	1162.6	1188.6	1214.6
957.9	77.5°	932.4	906.8	887.7	868.5	898.7	928.8	957.2	985.6	1012.9	1040.1
768.4	80°	747.0	725.5	709.5	693.4	718.5	743.5	767.4	791.3	812.1	832.7
565.2	82.5°	554.7	544.3	532.9	521.5	519.5	517.4	509.0	500.6	544.9	589.1
372.1	85°	360.9	349.7	337.0	324.3	313.5	302.6	279.5	256.3	297.7	339.2
164.4	87.5°	159.9	155.4	153.0	150.6	150.2	149.7	132.1	114.3	131.7	149.1
0.0	90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P956560
CATALOG NUMBER: GALN-SB9A-935-U-SLR

CANDELA DISTRIBUTION (continued):

105°		110°	115°	120°	125°	130°	135°	140°	145°	150°	155°
3894.4	0°	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4
3605.2	2.5°	3591.0	3580.0	3568.9	3558.7	3548.4	3535.7	3548.4	3558.7	3568.9	3580.0
3392.1	5°	3372.5	3358.6	3344.7	3334.1	3323.5	3313.1	3323.5	3334.1	3344.7	3358.6
3264.3	7.5°	3241.0	3225.0	3209.2	3199.6	3190.2	3183.1	3190.2	3199.6	3209.2	3225.0
3227.6	10°	3201.3	3186.2	3171.1	3163.0	3155.0	3151.7	3155.0	3163.0	3171.1	3186.2
3293.6	12.5°	3260.0	3243.1	3226.4	3219.5	3212.6	3211.4	3212.6	3219.5	3226.4	3243.1
3432.6	15°	3381.5	3358.0	3334.7	3325.8	3316.8	3316.1	3316.8	3325.8	3334.7	3358.0
3573.7	17.5°	3498.4	3463.7	3428.9	3417.5	3406.0	3404.2	3406.0	3417.5	3428.9	3463.7
3661.6	20°	3569.4	3525.0	3480.4	3466.2	3452.0	3447.6	3452.0	3466.2	3480.4	3525.0
3667.1	22.5°	3571.9	3525.1	3478.2	3462.5	3446.8	3440.1	3446.8	3462.5	3478.2	3525.1
3583.8	25°	3499.6	3458.9	3418.4	3403.6	3389.0	3380.3	3389.0	3403.6	3418.4	3458.9
3423.5	27.5°	3357.9	3330.7	3303.4	3296.6	3289.9	3287.7	3289.9	3296.6	3303.4	3330.7
3230.6	30°	3183.4	3169.5	3155.4	3155.4	3155.4	3157.6	3155.4	3155.4	3155.4	3169.5
3045.7	32.5°	3008.2	2999.1	2990.0	2991.2	2992.5	2994.8	2992.5	2991.2	2990.0	2999.1
2888.1	35°	2853.5	2839.6	2825.9	2822.9	2819.9	2818.4	2819.9	2822.9	2825.9	2839.6
2754.0	37.5°	2722.0	2696.8	2671.7	2658.4	2645.1	2637.6	2645.1	2658.4	2671.7	2696.8
2628.5	40°	2601.4	2564.7	2528.2	2503.4	2478.9	2464.2	2478.9	2503.4	2528.2	2564.7
2501.9	42.5°	2479.2	2433.6	2388.0	2352.0	2316.0	2292.4	2316.0	2352.0	2388.0	2433.6
2379.4	45°	2358.9	2306.7	2254.7	2212.4	2170.2	2143.0	2170.2	2212.4	2254.7	2306.7
2278.0	47.5°	2263.7	2217.4	2171.1	2131.9	2092.9	2066.7	2092.9	2131.9	2171.1	2217.4
2207.5	50°	2206.9	2169.9	2132.8	2096.6	2060.5	2035.4	2060.5	2096.6	2132.8	2169.9
2160.9	52.5°	2168.7	2138.5	2108.3	2075.9	2043.6	2020.4	2043.6	2075.9	2108.3	2138.5
2122.0	55°	2132.8	2106.5	2080.2	2051.8	2023.4	2002.5	2023.4	2051.8	2080.2	2106.5
2083.9	57.5°	2094.8	2068.2	2041.6	2013.5	1985.3	1963.6	1985.3	2013.5	2041.6	2068.2
2030.1	60°	2042.1	2016.1	1990.2	1961.2	1932.2	1909.8	1932.2	1961.2	1990.2	2016.1
1946.4	62.5°	1958.0	1934.5	1911.0	1880.5	1850.1	1823.2	1850.1	1880.5	1911.0	1934.5
1832.7	65°	*1844.4*	*1821.8*	*1799.2*	*1769.7*	*1740.2*	*1717.1*	*1740.2*	*1769.7*	*1799.2*	*1821.8*
1703.5	67.5°	1714.8	1694.0	1673.4	1645.9	1618.4	1597.5	1618.4	1645.9	1673.4	1694.0
1565.2	70°	1576.3	1559.4	1542.5	1516.2	1489.9	1466.0	1489.9	1516.2	1542.5	1559.4
1410.7	72.5°	1423.9	1409.8	1395.8	1370.7	1345.7	1322.5	1345.7	1370.7	1395.8	1409.8
1228.4	75°	1242.1	1235.3	1228.4	1207.3	1186.2	1164.1	1186.2	1207.3	1228.4	1235.3
1052.9	77.5°	1065.8	1056.2	1046.4	1025.2	1003.9	986.3	1003.9	1025.2	1046.4	1056.2
849.7	80°	866.7	862.6	858.5	830.0	801.3	768.1	801.3	830.0	858.5	862.6
618.1	82.5°	647.1	645.3	643.3	619.3	595.1	573.8	595.1	619.3	643.3	645.3
375.1	85°	411.0	408.0	405.0	386.2	367.3	348.2	367.3	386.2	405.0	408.0
163.6	87.5°	178.1	174.5	170.7	161.1	151.2	142.0	151.2	161.1	170.7	174.5
0.0	90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P956560
CATALOG NUMBER: GALN-SB9A-935-U-SLR

CANDELA DISTRIBUTION (continued):

160°		165°	170°	175°	180°	185°	190°	195°	200°	205°	210°
3894.4	0°	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4
3591.0	2.5°	3605.2	3619.4	3637.0	3654.5	3677.1	3699.8	3722.4	3744.9	3770.6	3796.5
3372.5	5°	3392.1	3411.7	3439.8	3467.7	3504.2	3540.5	3580.6	3620.6	3665.9	3711.3
3241.0	7.5°	3264.3	3287.7	3320.8	3354.2	3398.5	3443.1	3493.6	3543.9	3603.7	3663.5
3201.3	10°	3227.6	3253.6	3293.5	3333.2	3383.3	3433.4	3487.8	3542.0	3601.8	3661.6
3260.0	12.5°	3293.6	3327.3	3378.1	3428.9	3480.6	3532.4	3574.9	3617.6	3657.1	3696.8
3381.5	15°	3432.6	3483.7	3556.1	3628.4	3673.4	3718.3	3729.4	3740.5	3735.1	3729.7
3498.4	17.5°	3573.7	3649.0	3744.8	3840.6	3876.7	3913.1	3878.5	3843.9	3778.7	3713.6
3569.4	20°	3661.6	3753.9	3863.3	3972.8	3989.7	4006.5	3934.0	3861.5	3748.2	3635.1
3571.9	22.5°	3667.1	3762.1	3866.7	3971.3	3961.3	3951.2	3856.9	3762.6	3633.2	3504.0
3499.6	25°	3583.8	3668.4	3754.1	3839.8	3805.3	3770.6	3677.8	3585.0	3468.8	3352.7
3357.9	27.5°	3423.5	3489.1	3550.1	3611.2	3572.5	3533.9	3459.5	3385.1	3289.8	3194.3
3183.4	30°	3230.6	3277.5	3324.1	3370.6	3339.2	3307.8	3246.0	3184.2	3105.0	3025.8
3008.2	32.5°	3045.7	3083.2	3126.1	3168.9	3133.9	3099.1	3039.7	2980.6	2917.2	2854.0
2853.5	35°	2888.1	2922.7	2953.1	2983.6	2941.7	2899.9	2841.1	2782.6	2734.4	2686.2
2722.0	37.5°	2754.0	2785.8	2799.9	2813.9	2762.2	2710.5	2651.9	2593.5	2559.0	2524.3
2601.4	40°	2628.5	2655.5	2652.2	2648.8	2589.2	2529.7	2473.2	2416.7	2391.8	2366.8
2479.2	42.5°	2501.9	2524.8	2507.6	2490.4	2426.1	2361.9	2308.2	2254.7	2234.3	2213.9
2358.9	45°	2379.4	2400.0	2375.3	2350.7	2284.0	2217.4	2166.6	2115.8	2098.4	2081.4
2263.7	47.5°	2278.0	2292.4	2264.0	2235.6	2169.9	2104.1	2054.5	2004.7	1988.7	1972.6
2206.9	50°	2207.5	2208.4	2171.9	2135.5	2076.6	2017.7	1971.0	1924.0	1898.8	1873.7
2168.7	52.5°	2160.9	2153.1	2109.9	2066.7	2011.7	1956.9	1914.0	1871.0	1833.3	1795.5
2132.8	55°	2122.0	2111.3	2065.4	2019.7	1971.7	1923.6	1877.3	1830.9	1777.4	1723.8
2094.8	57.5°	2083.9	2073.0	2027.0	1980.8	1933.1	1885.6	1831.2	1776.8	1719.1	1661.5
2042.1	60°	2030.1	2018.2	1971.8	1925.5	1877.1	1828.8	1766.4	1703.9	1653.4	1602.7
1958.0	62.5°	1946.4	1934.9	1892.5	1850.1	1798.5	1746.9	1674.0	1601.2	1569.1	1537.0
1844.4	65°	*1832.7*	*1820.9*	*1783.6*	*1746.2*	*1696.9*	*1647.6*	*1569.4*	*1491.4*	*1479.1*	*1466.7*
1714.8	67.5°	1703.5	1691.9	1659.7	1627.4	1580.8	1534.0	1461.8	1389.8	1393.7	1397.6
1576.3	70°	1565.2	1554.2	1525.0	1495.9	1455.5	1415.2	1351.8	1288.5	1301.9	1315.4
1423.9	72.5°	1410.7	1397.6	1369.0	1340.5	1304.0	1267.5	1217.8	1167.9	1187.4	1207.2
1242.1	75°	1228.4	1214.6	1188.6	1162.6	1129.6	1096.6	1059.5	1022.5	1041.4	1060.3
1065.8	77.5°	1052.9	1040.1	1012.9	985.6	957.2	928.8	898.7	868.5	887.7	906.8
866.7	80°	849.7	832.7	812.1	791.3	767.4	743.5	718.5	693.4	709.5	725.5
647.1	82.5°	618.1	589.1	544.9	500.6	509.0	517.4	519.5	521.5	532.9	544.3
411.0	85°	375.1	339.2	297.7	256.3	279.5	302.6	313.5	324.3	337.0	349.7
178.1	87.5°	163.6	149.1	131.7	114.3	132.1	149.7	150.2	150.6	153.0	155.4
0.0	90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P956560
CATALOG NUMBER: GALN-SB9A-935-U-SLR

CANDELA DISTRIBUTION (continued):

215°		220°	225°	230°	235°	240°	245°	250°	255°	260°	265°
3894.4	0°	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4
3825.0	2.5°	3853.7	3889.2	3921.0	3953.9	3986.7	4021.1	4055.5	4089.5	4123.8	4155.9
3765.6	5°	3819.7	3881.7	3944.4	4010.9	4077.4	4148.6	4219.9	4290.5	4361.4	4432.4
3735.4	7.5°	3807.4	3887.7	3973.3	4066.1	4158.9	4264.2	4369.6	4477.8	4586.0	4703.0
3737.5	10°	3813.4	3899.6	4005.3	4115.3	4224.9	4353.0	4480.9	4623.8	4766.8	4914.9
3758.7	12.5°	3820.9	3901.1	4012.1	4136.3	4260.5	4411.4	4562.4	4724.4	4886.4	5048.9
3759.3	15°	3789.0	3853.3	3976.3	4120.0	4263.8	4437.6	4611.4	4787.1	4962.9	5132.5
3702.8	17.5°	3691.9	3731.5	3876.1	4049.1	4222.0	4423.7	4625.4	4817.2	5008.9	5180.9
3584.3	20°	3533.5	3543.9	3712.4	3926.7	4141.0	4385.4	4629.9	4840.6	5051.3	5230.2
3428.9	22.5°	3353.7	3333.2	3525.0	3783.0	4041.1	4338.5	4635.9	4872.3	5108.6	5291.3
3266.0	25°	3179.3	3124.0	3320.5	3622.7	3925.0	4292.2	4659.5	4929.7	5199.7	5378.6
3110.6	27.5°	3026.9	2959.6	3138.5	3476.1	3813.7	4261.3	4708.8	5019.4	5329.7	5500.6
2959.2	30°	2892.8	2840.1	2990.3	3353.6	3716.8	4246.8	4776.4	5135.5	5494.6	5659.4
2814.7	32.5°	2775.4	2751.9	2873.0	3247.9	3622.7	4228.8	4834.7	5256.7	5678.7	5841.9
2675.3	35°	2664.5	2674.2	2775.1	3144.0	3513.0	4195.1	4877.4	5394.7	5912.1	6068.6
2536.3	37.5°	2548.2	2583.8	2672.0	3021.8	3371.6	4137.2	4902.8	5549.4	6196.0	6395.4
2393.9	40°	2420.9	2475.5	2555.4	2876.0	3196.5	4057.6	4918.8	5745.8	6572.6	6863.1
2249.8	42.5°	2285.7	2354.4	2428.1	2715.0	3001.9	3975.4	4949.1	6002.7	7056.2	7475.5
2116.2	45°	2151.2	2217.7	2292.4	2544.1	2795.7	3899.0	5002.5	6340.7	7678.9	8244.6
2001.9	47.5°	2031.2	2088.4	2184.8	2408.8	2632.8	3836.0	5039.1	6700.8	8362.6	9158.8
1899.5	50°	1925.5	1992.0	2118.7	2319.0	2519.2	3767.2	5015.2	7035.0	9054.8	10255.1
1821.1	52.5°	1846.8	1939.7	2085.4	2259.8	2434.4	3651.1	4868.0	7252.0	9635.8	11406.7
1764.3	55°	1804.9	1944.9	2080.5	2216.9	2353.4	3458.6	4563.9	7204.2	9844.3	12427.6
1720.6	57.5°	1779.8	1950.2	2069.7	2166.1	2262.5	3187.2	4111.8	6867.6	9623.6	13151.2
1679.5	60°	1756.2	1933.7	2012.6	2088.4	2164.2	2834.9	3505.5	6241.3	8977.1	13332.1
1632.8	62.5°	1728.7	1893.4	1903.1	1953.3	2003.7	2413.1	2822.6	5394.5	7966.3	12570.7
1568.8	65°	*1670.7*	*1796.3*	*1795.1*	*1818.8*	*1842.6*	*2033.7*	*2224.8*	*4530.4*	*6836.1*	*11493.4*
1482.4	67.5°	1567.3	1637.9	1641.1	1628.0	1614.7	1669.1	1723.3	3684.0	5644.6	10211.3
1375.7	70°	1436.1	1459.3	1459.3	1397.9	1336.3	1320.9	1305.4	2900.6	4495.9	8812.4
1248.6	72.5°	1290.0	1289.7	1275.0	1187.9	1100.6	1053.7	1006.9	2217.5	3428.1	7295.9
1092.2	75°	1124.1	1129.8	1062.2	964.5	866.7	824.3	781.9	1609.5	2437.1	5557.5
932.4	77.5°	957.9	960.9	849.6	754.7	659.8	630.8	601.9	1090.6	1579.3	3889.7
747.0	80°	768.4	768.9	635.9	555.6	475.2	463.3	451.3	702.7	954.2	2506.1
554.7	82.5°	565.2	558.9	445.3	386.2	327.0	324.6	322.5	432.2	542.2	1450.5
360.9	85°	372.1	363.9	279.5	236.1	192.8	194.0	195.0	231.0	267.2	652.5
159.9	87.5°	164.4	153.9	118.8	101.0	83.4	84.4	85.5	95.8	106.1	213.7
0.0	90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P956560
CATALOG NUMBER: GALN-SB9A-935-U-SLR

CANDELA DISTRIBUTION (continued):

270°		275°	280°	285°	290°	295°	300°	305°	310°	315°	320°
3894.4	0°	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	*3894.4*	3894.4
4188.0	2.5°	4203.9	4219.9	4242.4	4265.0	4278.4	4291.9	4298.6	4305.3	*4302.3*	4305.3
4503.3	5°	4558.8	4614.4	4669.4	4724.5	4754.4	4784.3	4802.4	4820.6	*4834.4*	4820.6
4820.2	7.5°	4910.4	5000.5	5081.7	5162.8	5211.7	5260.6	5287.0	5313.3	*5326.0*	5313.3
5063.0	10°	5169.7	5276.4	5371.6	5466.8	5524.5	5581.8	5607.6	5633.1	*5642.8*	5633.1
5211.7	12.5°	5327.4	5442.9	5528.9	5614.7	5656.6	5698.4	5712.5	5726.5	*5728.0*	5726.5
5302.1	15°	5401.9	5501.6	5555.5	5609.6	5611.1	5612.6	5597.7	5582.7	*5565.1*	5582.7
5352.9	17.5°	5420.3	5487.7	5488.7	5489.6	5429.1	5368.6	5313.2	5257.6	*5218.4*	5257.6
5408.9	20°	5432.4	5456.0	5385.0	5314.1	5180.5	5046.9	4949.6	4852.3	*4792.5*	4852.3
5474.0	22.5°	5443.2	5412.4	5265.3	5118.3	4921.8	4725.3	4603.6	4482.0	*4415.9*	4482.0
5557.6	25°	5460.5	5363.4	5140.1	4916.8	4678.2	4439.5	4311.6	4184.0	*4121.5*	4184.0
5671.2	27.5°	5497.6	5323.8	5028.0	4732.4	4467.9	4203.4	4077.6	3951.9	*3892.9*	3951.9
5824.4	30°	5565.4	5306.6	4942.5	4578.5	4302.9	4027.4	3910.7	3794.0	*3739.0*	3794.0
6005.2	32.5°	5650.6	5296.1	4884.3	4472.4	4213.4	3954.5	3862.8	3771.1	*3731.5*	3771.1
6224.9	35°	5790.9	5357.1	4927.9	4498.9	4318.9	4139.2	4117.8	4096.4	*4093.1*	4096.4
6594.7	37.5°	6084.3	5573.8	5183.7	4793.7	4782.0	4770.4	4868.1	4965.9	*5016.7*	4965.9
7153.6	40°	6598.5	6043.3	5753.3	5463.2	5667.9	5872.7	6110.3	6347.9	*6466.2*	6347.9
7894.9	42.5°	7344.0	6793.2	6626.1	6459.1	6905.6	7352.1	7784.3	8216.5	*8470.2*	8216.5
8810.2	45°	8315.4	7820.4	7746.8	7672.9	8388.3	9103.8	9814.0	10524.2	*10955.4*	10524.2
9954.9	47.5°	9473.5	8992.0	8977.1	8962.2	9994.2	11025.9	12065.6	13105.1	*13715.5*	13105.1
11455.2	50°	10860.6	10266.2	10268.7	10271.2	11601.3	12931.3	14303.6	15675.9	*16505.5*	15675.9
13177.5	52.5°	12457.5	11737.7	11664.9	11592.0	13180.7	14769.4	16467.3	18165.1	*19159.6*	18165.1
15011.2	55°	14299.8	13588.5	13304.7	13020.9	14789.1	16557.1	18581.3	20605.4	*21788.2*	20605.4
16678.9	57.5°	16291.5	15904.0	15334.8	14765.8	16551.1	18336.5	20629.2	22921.7	*24388.5*	22921.7
17686.9	60°	18288.5	18890.3	18183.4	17476.6	19166.2	20855.7	23310.4	25765.1	*27350.3*	25765.1
17175.0	62.5°	18819.0	20463.0	20383.3	20303.5	21851.3	23399.2	25734.6	28069.9	*29535.1*	28069.9
16150.6	65°	*17693.6*	*19236.5*	*19541.8*	*19847.0*	*21813.9*	*23781.0*	*26045.6*	*28310.0*	*29557.5*	*28310.0*
14778.0	67.5°	16245.5	17713.0	17856.2	17999.2	20048.6	22097.8	24372.2	26646.5	*27623.8*	26646.5
13129.0	70°	14725.1	16321.4	16385.4	16449.5	18282.2	20114.8	22072.0	24029.1	*24572.3*	24029.1
11163.8	72.5°	12995.5	14827.3	14873.4	14919.2	16353.1	17787.0	19252.8	20718.5	*20773.5*	20718.5
8677.9	75°	10573.7	12469.5	12639.7	12809.9	13925.5	15041.0	16072.9	17104.8	*16828.3*	17104.8
6200.2	77.5°	7969.9	9739.7	9983.3	10226.9	11074.9	11923.0	12654.8	13386.7	*12911.5*	13386.7
4058.0	80°	5546.9	7035.6	7338.4	7641.1	8281.6	8921.8	9306.2	9690.4	*8926.0*	9690.4
2358.9	82.5°	3376.7	4394.7	4732.9	5071.2	5512.1	5952.9	6113.3	6273.5	*5672.7*	6273.5
1037.9	85°	1578.1	2118.3	2406.0	2693.6	3055.9	3418.0	3509.0	3600.0	*3118.8*	3600.0
321.3	87.5°	502.9	684.4	844.9	1005.4	1186.5	1367.7	1375.4	1383.1	*1161.1*	1383.1
0.0	90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	*0.0*	0.0

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P956560
CATALOG NUMBER: GALN-SB9A-935-U-SLR

CANDELA DISTRIBUTION (continued):

325°		330°	335°	340°	345°	350°	355°	360°
3894.4	0°	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4	3894.4
4298.6	2.5°	4291.9	4278.4	4265.0	4242.4	4219.9	4203.9	4188.0
4802.4	5°	4784.3	4754.4	4724.5	4669.4	4614.4	4558.8	4503.3
5287.0	7.5°	5260.6	5211.7	5162.8	5081.7	5000.5	4910.4	4820.2
5607.6	10°	5581.8	5524.5	5466.8	5371.6	5276.4	5169.7	5063.0
5712.5	12.5°	5698.4	5656.6	5614.7	5528.9	5442.9	5327.4	5211.7
5597.7	15°	5612.6	5611.1	5609.6	5555.5	5501.6	5401.9	5302.1
5313.2	17.5°	5368.6	5429.1	5489.6	5488.7	5487.7	5420.3	5352.9
4949.6	20°	5046.9	5180.5	5314.1	5385.0	5456.0	5432.4	5408.9
4603.6	22.5°	4725.3	4921.8	5118.3	5265.3	5412.4	5443.2	5474.0
4311.6	25°	4439.5	4678.2	4916.8	5140.1	5363.4	5460.5	5557.6
4077.6	27.5°	4203.4	4467.9	4732.4	5028.0	5323.8	5497.6	5671.2
3910.7	30°	4027.4	4302.9	4578.5	4942.5	5306.6	5565.4	5824.4
3862.8	32.5°	3954.5	4213.4	4472.4	4884.3	5296.1	5650.6	6005.2
4117.8	35°	4139.2	4318.9	4498.9	4927.9	5357.1	5790.9	6224.9
4868.1	37.5°	4770.4	4782.0	4793.7	5183.7	5573.8	6084.3	6594.7
6110.3	40°	5872.7	5667.9	5463.2	5753.3	6043.3	6598.5	7153.6
7784.3	42.5°	7352.1	6905.6	6459.1	6626.1	6793.2	7344.0	7894.9
9814.0	45°	9103.8	8388.3	7672.9	7746.8	7820.4	8315.4	8810.2
12065.6	47.5°	11025.9	9994.2	8962.2	8977.1	8992.0	9473.5	9954.9
14303.6	50°	12931.3	11601.3	10271.2	10268.7	10266.2	10860.6	11455.2
16467.3	52.5°	14769.4	13180.7	11592.0	11664.9	11737.7	12457.5	13177.5
18581.3	55°	16557.1	14789.1	13020.9	13304.7	13588.5	14299.8	15011.2
20629.2	57.5°	18336.5	16551.1	14765.8	15334.8	15904.0	16291.5	16678.9
23310.4	60°	20855.7	19166.2	17476.6	18183.4	18890.3	18288.5	17686.9
25734.6	62.5°	23399.2	21851.3	20303.5	20383.3	20463.0	18819.0	17175.0
26045.6	65°	*23781.0*	*21813.9*	*19847.0*	*19541.8*	*19236.5*	*17693.6*	*16150.6*
24372.2	67.5°	22097.8	20048.6	17999.2	17856.2	17713.0	16245.5	14778.0
22072.0	70°	20114.8	18282.2	16449.5	16385.4	16321.4	14725.1	13129.0
19252.8	72.5°	17787.0	16353.1	14919.2	14873.4	14827.3	12995.5	11163.8
16072.9	75°	15041.0	13925.5	12809.9	12639.7	12469.5	10573.7	8677.9
12654.8	77.5°	11923.0	11074.9	10226.9	9983.3	9739.7	7969.9	6200.2
9306.2	80°	8921.8	8281.6	7641.1	7338.4	7035.6	5546.9	4058.0
6113.3	82.5°	5952.9	5512.1	5071.2	4732.9	4394.7	3376.7	2358.9
3509.0	85°	3418.0	3055.9	2693.6	2406.0	2118.3	1578.1	1037.9
1375.4	87.5°	1367.7	1186.5	1005.4	844.9	684.4	502.9	321.3
0.0	90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)