

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: McGRAW-EDISON

Report Number: P955182

Luminaire Tested: **GALN-SB8A-950-U-T4W**

Issue Date: 1/21/2025

Test Information

Test Method: LM-79-08
Report Number: P955182
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2411-289-1)
Test Lab: INNOVATION CENTER
Issue Date: 1/21/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: MCGRAW-EDISON
Catalog Number: GALN-SB8A-950-U-T4W
Description: GALLEON AREA AND ROADWAY HIGH DENSITY LED LUMINAIRE
(8) 90 CRI, 5000K, 350mA LIGHTSQUARES WITH 26 LEDS EACH AND TYPE IV WIDE OPTICS
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 25184 lumens
Efficiency: N/A
Efficacy: 110.9 lumens/watt
Luminous Opening: Rectangular (W 1.5' x L: 1.5' x H: 0')
IES Classification: Type IV - Short
BUG Rating: B3 - U0 - G4


Input Watts (W): 227.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



REPORT NUMBER: P955182
 CATALOG NUMBER: GALN-SB8A-950-U-T4W

Iso-Footcandle Lines of Horizontal Illumination


✕ Max cd
 - - - 1/2 Max cd



Based on 25 foot mounting height. Maximum calculated value = 5 fc
 Type IV - Short - N/A

REPORT NUMBER: P955182
CATALOG NUMBER: GALN-SB8A-950-U-T4W

Luminous Intensity Polar Plot



— Vertical Plane Through 45-Deg Lateral - - - Horizontal Cone Through 72.5-Deg Vertical

REPORT NUMBER: P955182
 CATALOG NUMBER: GALN-SB8A-950-U-T4W

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	5693.2	0.0	5693.2
	% Fixture	22.6	0.0	22.6
Street Side	Lumens	19490.8	0.0	19490.8
	% Fixture	77.4	0.0	77.4
Total	Lumens	25184.0	0.0	25184.0
	% Fixture	100.0	0.0	100.0

Coefficient of Utilization

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	258.6	1.0
10°-20°	862.1	3.4
20°-30°	1499.7	6.0
30°-40°	2150.0	8.5
40°-50°	3027.3	12.0
50°-60°	4636.9	18.4
60°-70°	6717.2	26.7
70°-80°	5364.1	21.3
80°-90°	668.1	2.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	25184.0	100.0
0°-180°	25184.0	100.0



REPORT NUMBER: P955182


CATALOG NUMBER: GALN-SB8A-950-U-T4W

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone	Lumens	% Fixture	Zone Rating/Lumen Limit		
			B	U	G
FL (0°-30°)	1408.3	5.6			
FM (30°-60°)	7133.4	28.3			
FH (60°-80°)	10469.7	41.6			G4/12000
FVH (80°-90°)	479.3	1.9			G3/500
BL (0°-30°)	1212.1	4.8	B3/2500		
BM (30°-60°)	2680.7	10.6	B3/5000		
BH (60°-80°)	1611.6	6.4	B3/2500		G3/2500
BVH (80°-90°)	188.8	0.7			G2/225
UL (90°-100°)	0.0	0.0		U0/0	
UH (100°-180°)	0.0	0.0		U0/0	

BUG Rating: B3-U0-G4

Type IV Short



REPORT NUMBER: P955182

CATALOG NUMBER: GALN-SB8A-950-U-T4W

CANDELA DISTRIBUTION (FULL):

	0°	5°	15°	25°	35°	45°	46°	55°	65°	75°
0°	2540.6	2540.6	2540.6	2540.6	2540.6	2540.6	2540.6	2540.6	2540.6	2540.6
2.5°	2640.1	2657.3	2641.4	2626.8	2620.2	2602.9	2601.6	2591.0	2584.4	2565.8
5°	2824.5	2847.0	2820.5	2791.3	2764.8	2722.3	2717.0	2686.5	2652.0	2612.2
7.5°	3032.8	3052.7	3022.2	2978.4	2931.9	2861.6	2860.3	2804.6	2750.2	2682.5
10°	3214.5	3241.1	3199.9	3140.2	3081.9	3002.3	2993.0	2929.3	2860.3	2772.7
12.5°	3375.1	3393.6	3353.8	3280.9	3213.2	3133.6	3121.7	3051.3	2974.4	2874.9
15°	3502.4	3526.3	3473.2	3395.0	3323.3	3245.0	3234.4	3170.7	3093.8	2989.0
17.5°	3586.0	3605.9	3551.5	3463.9	3395.0	3329.9	3322.0	3268.9	3201.3	3095.1
20°	3617.8	3639.1	3582.0	3493.1	3429.4	3379.0	3375.1	3336.6	3290.1	3193.3
22.5°	3649.7	3669.6	3595.3	3502.4	3446.7	3414.9	3413.5	3388.3	3369.7	3290.1
25°	3778.4	3783.7	3684.2	3550.2	3470.6	3442.7	3441.4	3440.1	3448.0	3385.7
27.5°	3889.8	3888.5	3803.6	3677.5	3554.2	3495.8	3494.5	3507.7	3532.9	3481.2
30°	4053.0	4038.4	3937.6	3806.2	3693.5	3603.2	3595.3	3583.3	3603.2	3562.1
32.5°	4399.2	4352.8	4189.6	3956.1	3808.9	3739.9	3729.3	3655.0	3662.9	3637.7
35°	4895.4	4834.4	4616.8	4240.0	3952.2	3854.0	3848.7	3754.5	3738.6	3716.0
37.5°	5485.8	5410.2	5156.8	4651.3	4198.9	3986.6	3978.7	3893.8	3828.8	3804.9
40°	6078.8	5983.3	5773.7	5152.8	4562.4	4208.2	4183.0	4054.3	3980.0	3940.2
42.5°	6654.6	6575.0	6395.9	5715.3	5010.8	4531.9	4476.2	4256.0	4200.2	4163.1
45°	7164.0	7092.4	6961.0	6316.3	5536.2	4972.4	4918.0	4558.4	4541.2	4541.2
47.5°	7577.9	7562.0	7422.7	6929.2	6155.8	5473.8	5379.7	4979.0	5025.4	5097.1
50°	8037.0	7993.2	7844.6	7532.8	6884.1	6048.3	5971.3	5495.1	5668.9	5865.2
52.5°	8458.9	8482.7	8316.9	8161.7	7706.6	6689.1	6553.8	6104.0	6479.5	6804.5
55°	8892.7	8894.0	8847.6	8826.3	8569.0	7397.5	7248.9	6836.3	7433.3	7836.6
57.5°	9300.0	9302.6	9371.6	9558.7	9569.3	8214.7	8046.3	7735.8	8493.3	8904.6
60°	9663.5	9682.0	9870.4	10308.2	10448.9	9151.4	8992.2	8798.5	9589.2	10003.1
62.5°	9785.5	9853.2	10272.4	10894.6	11317.8	10300.3	10143.7	10028.3	10740.7	11125.5
65°	9578.6	9733.8	10544.4	11378.9	12212.0	11665.4	11510.2	11384.2	11937.4	12299.6
67.5°	9070.5	9270.8	10528.5	11887.0	13297.2	13307.8	13163.2	12867.4	13220.3	13359.6
70°	7731.8	8031.7	9601.1	12076.7	14543.0	15553.9	15414.6	14653.1	14500.5	13826.6
72.5°	4981.7	5385.0	7069.8	10515.2	14820.2	17667.3	17659.3	16265.0	14905.2	12919.1
75°	1817.5	2064.3	3284.8	6600.2	12440.2	17559.8	17611.6	15989.0	13606.3	9979.2
77.5°	662.0	724.4	1072.0	2536.6	7650.9	14089.2	14196.7	12782.5	9684.7	5008.2
80°	347.6	382.1	549.2	984.4	3278.2	8367.3	8535.8	7596.5	4551.8	1508.4
82.5°	192.4	208.3	307.8	534.6	1476.6	3578.0	3678.9	3000.9	1601.3	639.5
85°	103.5	110.1	144.6	291.9	721.7	1240.4	1268.3	896.8	638.1	375.4
87.5°	30.5	37.1	47.8	92.9	282.6	278.6	285.2	177.8	252.1	189.7
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P955182
 CATALOG NUMBER: GALN-SB8A-950-U-T4W

CANDELA DISTRIBUTION (continued):

85°		90°	95°	105°	115°	125°	135°	145°	155°	165°	175°
2540.6	0°	2540.6	2540.6	2540.6	2540.6	2540.6	2540.6	2540.6	2540.6	2540.6	2540.6
2560.5	2.5°	2552.5	2548.5	2533.9	2527.3	2519.3	2518.0	2524.7	2526.0	2527.3	2528.6
2589.7	5°	2576.4	2563.1	2549.9	2541.9	2544.6	2545.9	2559.1	2568.4	2575.1	2580.4
2644.1	7.5°	2622.8	2612.2	2589.7	2588.3	2592.3	2604.3	2621.5	2642.7	2654.7	2664.0
2714.4	10°	2691.8	2671.9	2645.4	2649.4	2657.3	2674.6	2710.4	2727.6	2747.5	2764.8
2800.6	12.5°	2762.1	2744.9	2714.4	2717.0	2730.3	2760.8	2795.3	2816.5	2829.8	2843.1
2893.5	15°	2853.7	2823.2	2790.0	2790.0	2813.9	2847.0	2863.0	2880.2	2888.2	2902.8
2993.0	17.5°	2947.9	2908.1	2864.3	2861.6	2890.8	2906.7	2916.0	2918.7	2921.3	2937.3
3089.8	20°	3042.1	2998.3	2935.9	2930.6	2937.3	2934.6	2933.3	2930.6	2934.6	2954.5
3189.3	22.5°	3134.9	3084.5	2998.3	2974.4	2955.8	2930.6	2929.3	2928.0	2930.6	2950.5
3296.8	25°	3243.7	3182.7	3067.3	2995.6	2933.3	2898.8	2902.8	2904.1	2906.7	2922.7
3408.2	27.5°	3361.8	3294.1	3130.9	2989.0	2876.2	2852.3	2845.7	2849.7	2859.0	2884.2
3519.7	30°	3479.9	3400.3	3189.3	2962.5	2804.6	2771.4	2750.2	2759.5	2788.7	2813.9
3616.5	32.5°	3587.3	3507.7	3235.8	2904.1	2713.0	2661.3	2633.4	2645.4	2674.6	2683.9
3724.0	35°	3713.4	3623.1	3255.7	2811.2	2613.5	2533.9	2496.8	2479.5	2494.1	2484.9
3850.0	37.5°	3854.0	3759.8	3253.0	2689.2	2496.8	2405.3	2353.5	2288.5	2258.0	2226.2
4035.7	40°	4062.3	3926.9	3221.2	2541.9	2352.2	2268.6	2175.7	2065.6	1996.6	1934.3
4335.6	42.5°	4346.2	4159.1	3162.8	2380.0	2189.0	2110.7	1984.7	1856.0	1747.2	1643.7
4790.6	45°	4769.4	4462.9	3089.8	2207.6	2012.6	1935.6	1799.0	1654.4	1531.0	1398.3
5436.7	47.5°	5379.7	4871.5	3020.8	2011.2	1826.8	1756.5	1633.1	1499.1	1353.2	1224.5
6370.7	50°	6218.1	5457.9	2957.2	1820.2	1643.7	1590.7	1492.5	1355.9	1208.6	1105.1
7465.2	52.5°	7284.8	6255.3	2930.6	1635.8	1472.6	1452.7	1374.4	1247.1	1107.8	1020.2
8741.4	55°	8509.3	7209.1	2930.6	1459.3	1322.7	1329.3	1274.9	1156.9	1036.1	957.9
10057.5	57.5°	9759.0	8174.9	2877.5	1296.2	1195.3	1223.2	1188.7	1085.2	976.4	895.5
11441.2	60°	10910.5	8984.2	2662.6	1147.6	1082.6	1126.3	1103.8	1014.9	882.2	814.6
12598.1	62.5°	11795.4	9440.6	2248.7	1029.5	989.7	1040.1	1028.2	922.0	865.0	837.1
13548.0	65°	12238.5	9366.3	1719.4	924.7	911.4	989.7	964.5	960.5	915.4	883.6
13857.1	67.5°	11966.6	8726.8	1247.1	847.7	866.3	943.3	1040.1	1056.0	972.5	910.1
12986.8	70°	10773.9	7570.0	928.7	774.8	809.3	944.6	1186.0	1105.1	953.9	880.9
10415.7	72.5°	8196.2	5645.0	720.4	697.8	735.0	951.2	1251.1	1082.6	900.8	973.8
6488.7	75°	4687.1	3099.1	578.4	603.6	642.1	888.9	1217.9	1024.2	859.7	894.2
2571.1	77.5°	1787.0	1191.4	477.6	510.8	516.1	776.1	1164.8	1020.2	818.6	798.7
770.8	80°	619.6	465.7	395.3	406.0	399.3	689.9	1117.1	887.5	670.0	599.7
318.4	82.5°	253.4	232.2	313.1	299.8	283.9	536.0	902.1	725.7	547.9	484.2
153.9	85°	110.1	147.3	207.0	181.8	164.5	371.5	723.0	614.2	463.0	399.3
50.4	87.5°	22.6	55.7	87.6	82.3	84.9	248.1	513.4	436.5	327.7	245.4
0.0	90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END O

<u>180°</u>
2540.6
2533.9
2583.0
2666.6
2760.8
2848.4
2908.1
2942.6
2962.5
2963.8
2943.9
2909.4
2841.7
2717.0
2514.0
2246.1
1938.3
1634.5
1382.4
1209.9
1098.5
1013.6
949.9
882.2
804.0
827.8
872.9
899.5
869.0
965.8
894.2
728.3
579.8
478.9
398.0
192.4
0.0

F REPORT)