Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled data based on original data using

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: McGRAW-EDISON

Report Number: P949825

Luminaire Tested: **GALN-SB4B-950-U-T3R**

Issue Date: 1/21/2025

Report Generated By 670246001

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Test Information

Test Method:	LM-79-08
Report Number:	P949825
	TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2411-289-5)
Test Lab:	INNOVATION CENTER
Issue Date:	1/21/2025
Manufacturer:	COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line:	McGRAW-EDISON
Catalog Number:	GALN-SB4B-950-U-T3R
Description:	GALLEON AREA AND ROADWAY HIGH DENSITY LED LUMINAIRE
	(4) 90 CRI, 5000K, 450mA LIGHTSQUARES WITH 26 LEDS EACH AND TYPE III ROADWAY OPTICS
Light Source:	-
Ballast/Driver:	-

Summary

Lumens per Lamp:	N/A
Luminaire Lumens:	16117 lumens
Efficiency:	N/A
Efficacy:	109.6 lumens/watt
Luminous Opening:	Rectangular (W 1' x L: 1' x H: 0')
IES Classification:	Type III - Medium
BUG Rating:	B2 - U0 - G3

Input Watts (W):	147
Input Voltage (V):	NR
Input Current (Ain):	NR
Voltage Rise (V):	NR
Power Factor:	NR
Total Harmonic Distortion (THDi):	NR
Frequency (hertz):	60
Stabilization Time:	NR
Operation Time:	NR
Ambient Temperature (°C):	NR
Test Distance:	24 FT

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P949825
CATALOG NUMBER: GALN-SB4B-950-U-T3R

Iso-Footcandle Lines of Horizontal Illumination



Based on 25 foot mounting height. Maximum calculated value = 4.3 fc
Type III - Medium - N/A

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P949825
CATALOG NUMBER: GALN-SB4B-950-U-T3R

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P949825
CATALOG NUMBER: GALN-SB4B-950-U-T3R

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	3529.4	0.0	3529.4
	% Fixture	21.9	0.0	21.9
Street Side	Lumens	12587.6	0.0	12587.6
	% Fixture	78.1	0.0	78.1
Total	Lumens	16117.0	0.0	16117.0
	% Fixture	100.0	0.0	100.0

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	214.4	1.3
10°-20°	618.9	3.8
20°-30°	1058.4	6.6
30°-40°	1702.0	10.6
40°-50°	2657.3	16.5
50°-60°	3549.6	22.0
60°-70°	3783.3	23.5
70°-80°	2329.0	14.5
80°-90°	204.1	1.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	16117.0	100.0
0°-180°	16117.0	100.0



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P949825
CATALOG NUMBER: GALN-SB4B-950-U-T3R

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit B	U	G
FL	(0°-30°)	987.4	6.1			
FM	(30°-60°)	6288.5	39.0			
FH	(60°-80°)	5169.0	32.1			G3/7500
FVH	(80°-90°)	142.7	0.9			G2/225
BL	(0°-30°)	904.3	5.6	B2/1000		
BM	(30°-60°)	1620.4	10.1	B2/2500		
BH	(60°-80°)	943.2	5.9	B2/1000		G2/1000
BVH	(80°-90°)	61.4	0.4			G1/100
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B2-U0-G3
Type III Medium



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P949825
CATALOG NUMBER: GALN-SB4B-950-U-T3R

CANDELA DISTRIBUTION (FULL):

	0°	5°	15°	25°	35°	45°	55°	65°	75°	77°
0°	2248.5	2248.5	2248.5	2248.5	2248.5	2248.5	2248.5	2248.5	2248.5	*2248.5*
2.5°	2072.7	2071.8	2082.6	2085.9	2105.7	2119.7	2146.1	2174.2	2210.5	*2214.6*
5°	1953.0	1953.0	1965.3	1978.6	2004.1	2032.2	2072.7	2121.4	2184.1	*2194.0*
7.5°	1851.4	1858.0	1868.8	1894.4	1924.1	1964.5	2026.4	2095.8	2178.3	*2194.0*
10°	1769.7	1777.1	1790.4	1811.0	1855.6	1911.7	1992.6	2081.7	2192.3	*2217.1*
12.5°	1744.1	1751.6	1759.0	1774.7	1815.9	1882.0	1978.6	2088.3	2226.2	*2250.9*
15°	1803.6	1812.6	1806.9	1802.7	1824.2	1884.5	1985.2	2112.3	2268.3	*2303.8*
17.5°	1940.6	1943.9	1930.7	1891.9	1888.6	1920.8	2016.5	2145.3	2321.1	*2359.9*
20°	2161.8	2156.0	2128.8	2052.0	2008.3	2001.7	2070.2	2194.8	2375.6	*2416.9*
22.5°	2462.3	2455.7	2401.2	2279.8	2182.4	2118.1	2147.8	2259.2	2436.7	*2482.9*
25°	2837.0	2827.9	2747.9	2582.8	2431.7	2272.4	2253.4	2344.2	2511.8	*2554.7*
27.5°	3274.5	3267.0	3180.4	2962.5	2744.6	2483.7	2384.7	2444.1	2590.2	*2638.9*
30°	3745.0	3766.4	3612.9	3378.5	3102.8	2759.4	2561.3	2567.1	2691.7	*2735.5*
32.5°	4298.0	4335.2	4150.3	3853.1	3476.7	3059.0	2784.2	2738.8	2839.5	*2875.8*
35°	4846.1	4888.2	4734.7	4406.1	3972.8	3412.3	3016.9	2936.1	3035.9	*3075.5*
37.5°	5319.9	5376.0	5296.8	5011.2	4503.5	3838.2	3320.7	3168.0	3277.8	*3327.3*
40°	5693.8	5779.7	5773.9	5595.6	5129.2	4355.0	3706.2	3454.4	3578.2	*3631.9*
42.5°	5997.6	6071.9	6136.2	6127.2	5782.1	4941.8	4159.3	3826.7	3920.8	*3982.7*
45°	6207.2	6286.5	6425.1	6574.5	6410.3	5570.0	4678.5	4268.3	4354.1	*4447.4*
47.5°	6394.6	6484.6	6664.5	6901.4	6943.5	6200.6	5247.3	4782.5	4861.0	*4957.5*
50°	6411.1	6488.7	6767.7	7103.6	7322.4	6806.5	5858.1	5359.5	5433.0	*5536.2*
52.5°	6012.4	6134.6	6621.6	7097.9	7496.5	7313.3	6464.8	5959.6	6042.1	*6166.0*
55°	4667.0	4846.1	6193.2	6876.6	7434.6	7641.0	7041.7	6597.7	6703.3	*6832.9*
57.5°	4019.8	4098.3	4916.3	6473.8	7152.3	7726.0	7528.7	7242.3	7412.4	*7554.3*
60°	3612.9	3678.1	4161.8	5847.3	6780.9	7591.5	7905.1	7843.2	8137.1	*8306.3*
62.5°	3177.1	3239.0	3678.9	4882.4	6305.5	7367.8	8142.9	8397.9	8880.0	*9064.9*
65°	2744.6	2797.4	3219.2	4102.4	5701.2	7144.1	8265.8	8877.5	9567.5	*9759.0*
67.5°	2262.5	2306.2	2704.9	3461.0	4966.6	6837.9	8326.9	9254.7	10166.0	*10330.2*
70°	*1632.7*	*1666.5*	*2078.4*	*2737.1*	*4044.6*	*6311.2*	*8302.2*	*9522.1*	*10476.3*	*10607.6*
72.5°	771.8	802.3	1286.0	1777.1	2856.8	5286.0	7801.1	9310.0	10161.0	*10095.8*
75°	411.9	438.3	738.8	974.8	1508.9	3623.6	6383.9	8019.9	8532.5	*8215.5*
77.5°	279.0	299.6	457.3	585.2	689.2	1720.2	4103.2	5552.7	5342.2	*4818.9*
80°	221.2	242.7	374.7	396.2	333.5	621.5	1695.4	2570.4	1846.5	*1476.7*
82.5°	170.0	194.0	315.3	287.2	181.6	255.1	493.6	813.0	473.0	*359.9*
85°	104.0	129.6	247.6	183.2	102.4	116.4	167.6	226.2	144.5	*120.5*
87.5°	52.8	74.3	125.5	66.9	46.2	27.2	44.6	44.6	38.0	*33.0*
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	*0.0*

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P949825
CATALOG NUMBER: GALN-SB4B-950-U-T3R

CANDELA DISTRIBUTION (continued):

85°		90°	95°	105°	115°	125°	135°	145°	155°	165°	175°
2248.5	0°	2248.5	2248.5	2248.5	2248.5	2248.5	2248.5	2248.5	2248.5	2248.5	2248.5
2236.9	2.5°	2256.7	2273.2	2301.3	2327.7	2348.3	2368.2	2388.0	2398.7	2402.0	2415.2
2249.3	5°	2283.1	2313.7	2368.2	2419.3	2451.5	2471.3	2485.4	2493.6	2495.3	2499.4
2283.1	7.5°	2331.8	2380.5	2456.5	2507.7	2531.6	2529.9	2524.2	2503.5	2495.3	2487.8
2332.7	10°	2400.3	2464.7	2558.0	2593.5	2578.6	2539.0	2487.8	2427.6	2399.5	2372.3
2400.3	12.5°	2485.4	2567.1	2658.7	2657.1	2583.6	2482.1	2363.2	2270.8	2212.1	2170.1
2483.7	15°	2588.5	2682.6	2752.8	2696.7	2535.7	2353.3	2179.1	2058.6	2005.8	1959.6
2567.9	17.5°	2695.0	2795.7	2827.9	2684.3	2415.2	2162.6	1965.3	1870.4	1818.4	1793.7
2658.7	20°	2799.0	2898.9	2872.5	2613.3	2232.0	1946.4	1770.5	1718.5	1707.8	1713.6
2747.0	22.5°	2908.8	2998.0	2881.6	2476.3	1998.4	1725.1	1628.6	1630.2	1654.2	1671.5
2839.5	25°	3021.1	3081.3	2857.6	2278.2	1747.4	1562.5	1538.6	1565.0	1612.1	1645.9
2943.5	27.5°	3129.2	3155.6	2805.6	2033.0	1532.0	1446.2	1450.3	1504.8	1575.7	1622.8
3069.8	30°	3251.4	3221.6	2705.8	1757.3	1382.6	1346.3	1380.9	1444.5	1515.5	1557.6
3229.1	32.5°	3389.2	3278.6	2547.3	1502.3	1276.9	1266.2	1323.2	1364.4	1395.8	1408.2
3440.4	35°	3560.9	3358.7	2344.2	1323.2	1182.0	1207.6	1262.1	1241.4	1229.1	1222.5
3724.3	37.5°	3783.8	3466.8	2106.5	1206.8	1105.2	1165.5	1187.8	1123.4	1074.7	1050.8
4068.5	40°	4052.0	3625.3	1877.9	1116.8	1056.5	1129.2	1090.4	1012.8	950.9	917.1
4455.7	42.5°	4350.0	3791.2	1685.5	1049.1	1029.3	1099.5	1018.6	926.1	826.3	815.5
4917.1	45°	4662.8	3962.1	1554.3	997.1	1016.1	1073.9	977.3	827.9	756.9	800.7
5380.1	47.5°	4975.7	4118.9	1475.0	958.3	1009.5	1045.0	941.0	773.4	723.1	786.6
5876.2	50°	5324.0	4259.2	1439.5	930.3	1002.1	1033.4	886.5	759.4	687.6	729.7
6389.6	52.5°	5669.9	4368.2	1413.1	902.2	991.3	1024.4	860.1	742.9	644.7	647.1
6906.4	55°	6014.9	4439.2	1384.2	865.0	967.4	1004.5	857.6	724.7	612.5	600.9
7452.8	57.5°	6383.0	4479.6	1348.8	823.8	926.1	954.2	855.1	710.7	602.6	583.6
8011.6	60°	6757.8	4539.0	1302.5	773.4	870.8	893.9	849.4	705.7	596.8	564.6
8538.2	62.5°	7093.7	4559.7	1247.2	725.6	799.8	834.5	837.0	701.6	581.1	525.8
8975.7	65°	7314.1	4470.5	1150.6	671.1	723.1	773.4	813.0	687.6	553.0	497.7
9192.0	67.5°	7305.0	4216.3	999.6	600.9	648.8	705.7	778.4	663.6	519.2	463.1
9028.5	70°	*6965.0*	*3714.4*	*808.1*	*519.2*	*567.1*	*633.1*	*733.8*	*628.2*	*478.7*	*425.1*
8028.1	72.5°	5973.6	2907.2	586.9	423.4	472.1	558.0	676.0	585.2	437.5	391.3
5933.2	75°	4267.5	1839.9	397.9	325.2	367.3	473.0	604.2	534.9	399.5	392.9
2971.5	77.5°	2180.0	879.1	263.3	237.7	255.9	373.1	507.6	477.9	405.3	324.4
845.2	80°	709.0	324.4	165.9	161.8	170.0	248.5	392.9	392.1	307.1	220.4
204.7	82.5°	226.2	139.5	108.1	104.0	99.9	156.0	274.0	310.4	207.2	139.5
73.5	85°	90.0	83.4	63.6	58.6	42.1	73.5	143.6	206.4	154.4	100.7
19.0	87.5°	33.0	33.0	17.3	12.4	9.1	24.8	38.8	61.9	88.3	52.0
0.0	90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END O

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

180°
2248.5
2422.6
2506.0
2489.5
2364.0
2160.1
1954.6
1801.1
1711.1
1675.6
1655.0
1634.3
1567.5
1414.8
1229.1
1056.5
919.5
826.3
823.8
816.3
761.0
664.5
609.2
586.1
567.1
525.8
497.7
465.5
430.0
388.8
370.6
288.9
194.8
138.7
103.2
51.2
0.0

F REPORT)