Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled data based on original data using

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: McGRAW-EDISON

Report Number: P944655

Luminaire Tested: **GALN-SB9C-950-U-T2**

Issue Date: 1/21/2025

Report Generated By 670246001

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Test Information

Test Method:	LM-79-08
Report Number:	P944655
	TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2405-108-3)
Test Lab:	INNOVATION CENTER
Issue Date:	1/21/2025
Manufacturer:	COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line:	McGRAW-EDISON
Catalog Number:	GALN-SB9C-950-U-T2
Description:	GALLEON AREA AND ROADWAY HIGH DENSITY LED LUMINAIRE
	(9) 90 CRI, 5000K, 615mA LIGHTSQUARES WITH 26 LEDS EACH AND TYPE II OPTICS
Light Source:	-
Ballast/Driver:	-

Summary

Lumens per Lamp:	N/A
Luminaire Lumens:	47018 lumens
Efficiency:	N/A
Efficacy:	104.5 lumens/watt
Luminous Opening:	Rectangular (W 1.5' x L: 1.5' x H: 0')
IES Classification:	Type II - Medium
BUG Rating:	B4 - U0 - G5

Input Watts (W):	449.8
Input Voltage (V):	NR
Input Current (Ain):	NR
Voltage Rise (V):	NR
Power Factor:	NR
Total Harmonic Distortion (THDi):	NR
Frequency (hertz):	60
Stabilization Time:	NR
Operation Time:	NR
Ambient Temperature (°C):	NR
Test Distance:	24 FT

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P944655
CATALOG NUMBER: GALN-SB9C-950-U-T2

Iso-Footcandle Lines of Horizontal Illumination



Based on 25 foot mounting height. Maximum calculated value = 12.5 fc
Type II - Medium - N/A

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P944655
CATALOG NUMBER: GALN-SB9C-950-U-T2

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P944655
CATALOG NUMBER: GALN-SB9C-950-U-T2

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	11591.1	0.0	11591.1
	% Fixture	24.7	0.0	24.7
Street Side	Lumens	35426.9	0.0	35426.9
	% Fixture	75.3	0.0	75.3
Total	Lumens	47018.0	0.0	47018.0
	% Fixture	100.0	0.0	100.0

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	650.9	1.4
10°-20°	1870.0	4.0
20°-30°	3128.3	6.7
30°-40°	4887.2	10.4
40°-50°	7783.4	16.6
50°-60°	10831.5	23.0
60°-70°	11330.2	24.1
70°-80°	5921.8	12.6
80°-90°	614.9	1.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	47018.0	100.0
0°-180°	47018.0	100.0



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P944655
CATALOG NUMBER: GALN-SB9C-950-U-T2

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit B	U	G
FL	(0°-30°)	3237.7	6.9			
FM	(30°-60°)	18402.4	39.1			
FH	(60°-80°)	13442.6	28.6			G5
FVH	(80°-90°)	344.2	0.7			G3/500
BL	(0°-30°)	2411.4	5.1	B3/2500		
BM	(30°-60°)	5099.6	10.8	B4/8500		
BH	(60°-80°)	3809.4	8.1	B4/5000		G4/5000
BVH	(80°-90°)	270.7	0.6			G3/500
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B4-U0-G5
Type II Medium



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P944655
CATALOG NUMBER: GALN-SB9C-950-U-T2

CANDELA DISTRIBUTION (FULL):

	0°	5°	15°	25°	35°	45°	55°	65°	75°	82°
0°	6893.4	6893.4	6893.4	6893.4	6893.4	6893.4	6893.4	6893.4	6893.4	*6893.4*
2.5°	7058.1	7098.0	7085.5	7073.1	7073.1	7055.6	7053.1	7028.2	7008.2	*6975.8*
5°	7147.9	7190.3	7185.3	7195.3	7227.7	7235.2	7242.7	7227.7	7187.8	*7147.9*
7.5°	7068.1	7115.5	7130.4	7190.3	7290.1	7379.9	7447.3	7474.7	7437.3	*7379.9*
10°	6798.6	6851.0	6903.4	7045.6	7222.8	7434.8	7614.5	7721.7	7714.3	*7659.4*
12.5°	6252.2	6307.1	6419.4	6696.3	7020.7	7394.9	7729.2	7953.8	8031.1	*7991.2*
15°	5815.6	5863.0	5947.9	6232.3	6653.9	7222.8	7771.6	8208.2	8405.3	*8382.9*
17.5°	5803.2	5823.1	5875.5	6010.2	6334.6	6953.3	7726.7	8457.7	8834.5	*8832.0*
20°	6022.7	6030.2	6060.1	6087.6	6272.2	6748.7	7612.0	8664.8	9316.0	*9316.0*
22.5°	6327.1	6322.1	6352.0	6327.1	6416.9	6731.3	7539.6	8846.9	9852.4	*9892.3*
25°	6783.7	6758.7	6751.2	6693.8	6711.3	6893.4	7619.4	9054.0	10488.6	*10570.9*
27.5°	7392.4	7352.5	7325.0	7192.8	7147.9	7227.7	7863.9	9303.5	11197.1	*11339.4*
30°	8185.8	8113.4	8073.5	7844.0	7681.8	7694.3	8233.2	9635.3	11938.1	*12167.7*
32.5°	9268.6	9156.3	9049.0	8672.3	8375.4	8278.1	8709.7	10094.4	12741.5	*13108.2*
35°	10481.1	10391.3	10276.5	9695.2	9238.6	9014.1	9353.4	10735.6	13682.1	*14263.4*
37.5°	11648.7	11571.4	11626.3	10842.9	10254.1	9927.2	10196.7	11596.3	14842.2	*15700.4*
40°	12856.3	12796.4	12803.9	12055.4	11369.3	11002.5	11219.6	12676.6	16172.0	*17409.5*
42.5°	14168.6	14123.7	13974.0	13310.3	12539.4	12197.6	12397.2	13924.1	17599.1	*19355.5*
45°	15638.1	15610.6	15470.9	14710.0	13826.8	13442.6	13712.0	15301.3	19033.6	*21186.7*
47.5°	16908.0	16930.4	16913.0	16271.8	15356.1	14792.3	15114.1	16738.3	20368.4	*22908.2*
50°	17519.2	17636.5	17808.6	17609.1	17040.2	16466.4	16528.8	18125.5	21640.8	*24522.4*
52.5°	17199.9	17421.9	17891.0	18210.3	18429.9	18310.1	18143.0	19502.7	22838.4	*25979.5*
55°	16009.8	16321.7	17100.1	17871.0	18991.2	19862.0	20081.5	21029.6	24006.0	*27261.8*
57.5°	13841.7	14348.2	15046.8	16606.1	18492.2	20612.9	22341.9	23147.7	25243.5	*28631.5*
60°	10124.3	10802.9	11671.2	13991.4	16745.8	20211.2	24265.5	26401.1	27002.4	*30405.4*
62.5°	6479.3	6898.4	7696.8	9882.3	13048.4	18152.9	24854.3	30467.8	29983.8	*33314.5*
65°	4435.9	4705.4	5436.4	6663.9	8435.3	13512.4	23277.5	33516.6	34719.1	*37925.1*
67.5°	3223.4	3428.0	4051.7	5127.0	5496.3	7996.2	18063.1	33376.9	39322.2	*42675.4*
70°	*2350.2*	*2494.9*	*3018.8*	*4051.7*	*4228.9*	*4448.4*	*10942.7*	*28372.1*	*39222.4*	*43937.8*
72.5°	1741.4	1841.2	2193.0	3143.6	3423.0	3003.9	5416.4	20620.4	33703.7	*39741.4*
75°	1259.9	1334.8	1594.2	2405.1	2739.4	2287.8	2702.0	12050.4	23509.5	*27955.4*
77.5°	963.0	1020.4	1190.1	1761.4	2193.0	1716.5	1676.6	5543.7	11147.2	*11202.1*
80°	773.4	810.8	903.2	1240.0	1681.6	1284.9	1092.8	2237.9	3522.8	*2981.4*
82.5°	568.8	631.2	763.4	870.7	1202.5	885.7	666.1	1130.2	1339.8	*1152.6*
85°	324.3	366.8	461.6	623.7	768.4	541.4	381.7	501.5	623.7	*511.5*
87.5°	114.8	149.7	162.2	244.5	334.3	224.5	147.2	144.7	204.6	*152.2*
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	*0.0*

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

REPORT NUMBER: P944655
CATALOG NUMBER: GALN-SB9C-950-U-T2

CANDELA DISTRIBUTION (continued):

85°		90°	95°	105°	115°	125°	135°	145°	155°	165°	175°
6893.4	0°	6893.4	6893.4	6893.4	6893.4	6893.4	6893.4	6893.4	6893.4	6893.4	6893.4
6968.3	2.5°	6943.3	6930.9	6881.0	6813.6	6743.7	6676.4	6653.9	6606.5	6574.1	6556.6
7130.4	5°	7083.0	7043.1	6925.9	6776.2	6619.0	6449.3	6329.6	6219.8	6140.0	6065.1
7352.5	7.5°	7282.6	7212.8	7010.7	6748.7	6469.3	6187.4	5977.8	5818.1	5710.8	5641.0
7612.0	10°	7514.7	7407.4	7098.0	6706.3	6274.7	5870.5	5623.5	5486.3	5418.9	5381.5
7908.9	12.5°	7781.6	7629.4	7187.8	6609.0	5977.8	5516.2	5346.6	5306.7	5309.2	5311.7
8283.1	15°	8110.9	7898.9	7260.2	6396.9	5591.1	5244.3	5214.4	5279.2	5346.6	5379.0
8707.2	17.5°	8482.7	8183.3	7272.7	6047.7	5211.9	5069.7	5164.5	5304.2	5406.5	5451.4
9181.3	20°	8881.9	8472.7	7182.8	5553.7	4900.0	4927.4	5097.1	5276.7	5389.0	5446.4
9722.7	22.5°	9338.4	8782.1	6968.3	5034.7	4645.5	4772.8	4972.3	5147.0	5264.3	5321.6
10358.9	25°	9859.9	9128.9	6631.5	4598.1	4426.0	4598.1	4797.7	4942.4	5037.2	5089.6
11069.9	27.5°	10438.7	9490.6	6182.4	4251.3	4233.9	4418.5	4583.1	4695.4	4745.3	4785.2
11825.9	30°	11020.0	9820.0	5638.5	3989.4	4066.7	4241.3	4358.6	4408.5	4423.5	4431.0
12669.1	32.5°	11648.7	10104.4	5067.2	3772.3	3907.0	4069.2	4139.0	4161.5	4091.6	4044.2
13692.0	35°	12409.7	10408.8	4508.3	3600.2	3749.8	3889.6	3912.0	3892.1	3809.7	3712.4
14974.4	37.5°	13350.2	10788.0	4061.7	3477.9	3602.6	3695.0	3667.5	3662.5	3670.0	3555.2
16516.3	40°	14502.9	11282.0	3734.9	3383.1	3482.9	3502.8	3425.5	3467.9	3505.3	3330.7
18207.8	42.5°	15782.8	11878.2	3527.8	3318.2	3383.1	3335.7	3215.9	3263.3	3258.3	3028.8
19906.9	45°	17087.6	12526.9	3455.4	3270.8	3290.8	3196.0	3063.7	3076.2	2971.4	2764.4
21536.0	47.5°	18385.0	13223.0	3500.4	3230.9	3176.0	3068.7	2966.4	2911.6	2756.9	2602.2
23097.8	50°	19657.4	13954.0	3665.0	3151.1	3018.8	2956.5	2881.6	2784.3	2619.7	2487.4
24574.8	52.5°	20837.5	14690.0	3849.6	3018.8	2821.7	2859.2	2811.8	2699.5	2537.3	2402.6
25972.0	55°	21955.2	15426.0	3922.0	2836.7	2637.1	2774.3	2746.9	2539.8	2345.2	2235.4
27434.0	57.5°	23172.7	16311.7	3842.2	2604.7	2487.4	2677.0	2572.2	2342.7	2230.4	2148.1
29337.6	60°	24859.2	17701.4	3670.0	2317.8	2345.2	2532.3	2352.7	2257.9	2135.6	2043.3
32191.8	62.5°	27661.0	20293.6	3393.1	2033.3	2178.1	2317.8	2247.9	2153.1	2028.4	1938.5
37071.8	65°	31802.6	23896.2	2871.6	1811.3	1990.9	2108.2	2135.6	2040.8	1911.1	1816.3
41348.1	67.5°	35295.4	26156.6	2173.1	1626.7	1798.8	1938.5	2015.9	1923.6	1786.4	1694.0
42348.5	70°	*35103.3*	*24515.0*	*1659.1*	*1444.6*	*1629.2*	*1771.4*	*1871.2*	*1798.8*	*1651.6*	*1564.3*
38466.5	72.5°	31178.8	20508.1	1342.3	1259.9	1457.0	1596.7	1716.5	1661.6	1511.9	1427.1
28180.0	75°	22905.7	14557.8	1072.8	1072.8	1242.5	1414.6	1546.8	1511.9	1374.7	1314.8
11830.8	77.5°	9655.3	6107.5	840.8	890.7	1032.9	1215.0	1379.7	1392.2	1272.4	1347.2
3128.6	80°	2567.3	1684.1	641.2	701.1	810.8	1003.0	1200.1	1195.1	1065.3	995.5
1162.6	82.5°	978.0	663.6	456.6	494.0	586.3	768.4	950.6	980.5	850.8	736.0
456.6	85°	376.7	284.4	281.9	296.9	341.8	509.0	718.5	743.5	641.2	543.9
127.2	87.5°	97.3	84.8	104.8	99.8	157.2	271.9	411.7	426.6	391.7	227.0
0.0	90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END O

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

180°
6893.4
6576.6
6095.1
5656.0
5391.5
5316.6
5376.5
5461.4
5461.4
5336.6
5104.6
4800.2
4448.4
4059.2
3717.4
3562.7
3335.7
3026.3
2771.8
2602.2
2477.4
2405.1
2225.5
2140.6
2038.3
1938.5
1821.3
1696.5
1571.8
1427.1
1297.4
1222.5
925.6
736.0
561.4
324.3
0.0

F REPORT)