Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled data based on original data using

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: McGRAW-EDISON

Report Number: P1363891

Luminaire Tested: **GSS-SB4A-760-U-SL3-HSS**

Issue Date: 02/18/2026

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.

Report Generated By 670245763

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

Test Information

Test Method:	LM-79-08
Report Number:	P1363891
Test Lab:	INNOVATION CENTER(G1)
Issue Date:	02/18/2026
Manufacturer:	COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line:	McGRAW-EDISON
Catalog Number:	GSS-SB4A-760-U-SL3-HSS
Description:	GALLEON II SLIM SITE HIGH DENSITY LED ARRAYS 4SQUARE 114W 70CRI 5700K FIXTURE w/ TYPE III SPILL CONTROL DISTRIBUTION OPTIC AND HOUSE SIDE SHIELD
Light Source:	(104) 5700K CCT, 70 CRI LEDS
Ballast/Driver:	ELECTRONIC DRIVER

Luminaire Equipment:

Sample No.	Condition	Description
a	good	reflector
b	good	lens
c	good	housing
d	good	cord

Summary

Lumens per Lamp:	N/A
Luminaire Lumens:	13130.1 lumens
Efficiency:	N/A
Efficacy:	115.2 lumens/watt
Luminous Opening:	Rectangular (W 1.5' x L: 1' x H: 0')
IES Classification:	Type III - Medium
BUG Rating:	B1 - U0 - G3


Input Watts (W):	114
Input Voltage (V):	120
Input Current (Ain):	NR
Voltage Rise (V):	NR
Power Factor:	0.98
Total Harmonic Distortion (THDi):	8.2%
Frequency (hertz):	60
Stabilization Time:	NR
Operation Time:	NR
Ambient Temperature (°C):	NR
Test Distance:	28.75 FT

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P1363891
CATALOG NUMBER: GSS-SB4A-760-U-SL3-HSS

Iso-Footcandle Lines of Horizontal Illumination




Based on 20 foot mounting height. Maximum calculated value = 7.7 fc
Type III - Medium - N/A

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P1363891
CATALOG NUMBER: GSS-SB4A-760-U-SL3-HSS

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report


REPORT NUMBER: P1363891
CATALOG NUMBER: GSS-SB4A-760-U-SL3-HSS

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	1176.1	0.0	1176.1
	% Fixture	9.0	0.0	9.0
Street Side	Lumens	11954.0	0.0	11954.0
	% Fixture	91.0	0.0	91.0
Total	Lumens	13130.1	0.0	13130.1
	% Fixture	100.0	0.0	100.0

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	195.8	1.5
10°-20°	561.6	4.3
20°-30°	852.3	6.5
30°-40°	1234.4	9.4
40°-50°	1843.4	14.0
50°-60°	2669.1	20.3
60°-70°	3233.5	24.6
70°-80°	2335.3	17.8
80°-90°	204.8	1.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	13130.1	100.0
0°-180°	13130.1	100.0



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269


Scaled Data Report

REPORT NUMBER: P1363891
CATALOG NUMBER: GSS-SB4A-760-U-SL3-HSS

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit B	U	G
FL	(0°-30°)	1246.1	9.5			
FM	(30°-60°)	5193.6	39.6			
FH	(60°-80°)	5327.2	40.6			G3/7500
FVH	(80°-90°)	187.0	1.4			G2/225
BL	(0°-30°)	363.6	2.8	B1/500		
BM	(30°-60°)	553.2	4.2	B1/1000		
BH	(60°-80°)	241.6	1.8	B1/500		G1/500
BVH	(80°-90°)	17.8	0.1			G1/100
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B1-U0-G3
Type III Medium



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P1363891
CATALOG NUMBER: GSS-SB4A-760-U-SL3-HSS

CANDELA DISTRIBUTION (FULL):

	0°	5°	15°	25°	35°	45°	55°	57°	65°	75°	85°
0°	2112.2	2112.2	2112.2	2112.2	2112.2	2112.2	2112.2	*2112.2*	2112.2	2112.2	2112.2
2.5°	2539.8	2548.3	2518.4	2501.3	2467.1	2411.5	2355.9	*2355.9*	2291.8	2231.9	2154.9
5°	2916.0	2890.4	2877.5	2834.8	2770.6	2702.2	2603.9	*2578.2*	2475.6	2347.4	2193.4
7.5°	3202.5	3172.6	3159.7	3121.3	3048.6	2958.8	2826.2	*2804.9*	2655.2	2467.1	2244.7
10°	3377.8	3356.4	3356.4	3326.5	3270.9	3176.8	3044.3	*3014.4*	2834.8	2578.2	2278.9
12.5°	3300.8	3292.3	3343.6	3412.0	3437.7	3382.1	3241.0	*3202.5*	2997.3	2702.2	2321.7
15°	2950.2	2941.7	3035.7	3215.3	3433.4	3527.4	3420.6	*3386.3*	3172.6	2830.5	2364.5
17.5°	2612.4	2599.6	2689.4	2869.0	3193.9	3544.5	3608.7	*3565.9*	3347.9	2958.8	2411.5
20°	2420.0	2407.2	2467.1	2612.4	2907.5	3407.7	3707.0	*3715.6*	3540.3	3099.9	2458.5
22.5°	2351.6	2347.4	2377.3	2475.6	2685.1	3172.6	3745.5	*3796.8*	3749.8	3262.4	2526.9
25°	2381.6	2364.5	2373.0	2411.5	2561.1	2984.4	3724.1	*3822.5*	3925.1	3459.0	2616.7
27.5°	2458.5	2445.7	2432.9	2432.9	2509.8	2847.6	3668.5	*3831.0*	4104.7	3672.8	2693.7
30°	2586.8	2569.7	2531.2	2484.2	2509.8	2762.1	3604.4	*3809.6*	4258.6	3903.7	2800.6
32.5°	2877.5	2864.7	2753.5	2603.9	2569.7	2740.7	3531.7	*3771.2*	4425.3	4177.4	2924.6
35°	3164.0	3151.2	3074.2	2860.4	2672.3	2757.8	3484.7	*3745.5*	4630.6	4510.9	3069.9
37.5°	3292.3	3270.9	3211.0	3095.6	2911.7	2856.2	3497.5	*3775.4*	4925.6	4878.6	3249.5
40°	3454.8	3420.6	3330.8	3223.9	3142.6	3082.8	3600.1	*3878.1*	5254.8	5301.9	3446.2
42.5°	3694.2	3655.7	3523.2	3373.5	3279.5	3399.2	3796.8	*4061.9*	5661.0	5772.2	3685.6
45°	4023.4	3972.1	3801.1	3604.4	3489.0	3557.4	4061.9	*4322.7*	6114.2	6306.6	3963.6
47.5°	4322.7	4309.9	4117.5	3890.9	3754.1	3664.3	4348.4	*4626.3*	6593.1	6905.2	4250.0
50°	4604.9	4557.9	4369.8	4147.4	4032.0	3882.3	4664.8	*4964.1*	7072.0	7452.5	4557.9
52.5°	4912.8	4861.5	4604.9	4352.7	4237.2	4203.0	5075.2	*5366.0*	7491.0	8029.7	4870.0
55°	5152.2	5079.5	4797.3	4587.8	4404.0	4519.4	5515.6	*5849.1*	7863.0	8551.4	5186.4
57.5°	5451.5	5357.4	4955.5	4801.6	4660.5	4840.1	6011.6	*6332.3*	8252.1	8991.8	5502.8
60°	5712.3	5639.6	5250.5	5058.1	4925.6	5203.5	6494.8	*6777.0*	8555.7	9368.0	5793.6
62.5°	4917.0	4908.5	5011.1	5588.3	5391.6	5755.1	7012.1	*7260.1*	8739.5	9620.3	5913.3
65°	3489.0	3514.6	3801.1	5596.9	6298.1	6678.6	7692.0	*7854.4*	8748.1	9333.8	5678.1
67.5°	2219.1	2193.4	2548.3	4686.2	6332.3	8500.1	8726.7	*8564.2*	8354.7	9026.0	5708.0
70°	1329.7	1338.3	1458.0	3399.2	5220.6	8914.8	10171.9	*9752.9*	8589.9	9252.6	5733.7
72.5°	722.6	739.7	910.7	1667.5	3459.0	7093.4	11702.6	*11762.4*	9393.7	9359.5	5635.4
73°	*658.5*	*662.7*	*816.7*	*1393.9*	*2993.0*	*6742.8*	*11629.9*	*11873.6*	*9556.2*	*9389.4*	*5571.2*
75°	436.1	436.1	555.8	791.0	1312.6	5242.0	9654.5	*10732.0*	10107.7	9081.6	5071.0
77.5°	269.4	286.5	384.8	547.3	478.9	2638.1	5678.1	*6567.5*	9013.2	6832.6	3185.4
80°	98.3	106.9	239.4	359.2	277.9	1000.5	2381.6	*2732.2*	4177.4	3467.6	1150.2
82.5°	51.3	55.6	149.6	183.9	149.6	260.8	1064.6	*1137.3*	1684.6	902.2	213.8
85°	25.7	29.9	64.1	77.0	59.9	85.5	265.1	*248.0*	380.5	119.7	59.9
87.5°	0.0	0.0	4.3	8.6	12.8	17.1	25.7	*25.7*	29.9	34.2	34.2
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	*0.0*	0.0	0.0	0.0

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P1363891
CATALOG NUMBER: GSS-SB4A-760-U-SL3-HSS

CANDELA DISTRIBUTION (continued):

	90°	95°	105°	115°	125°	135°	145°	155°	165°	175°	180°
0°	2112.2	2112.2	2112.2	2112.2	2112.2	2112.2	2112.2	2112.2	2112.2	2112.2	2112.2
2.5°	2107.9	2073.7	1992.5	1911.2	1851.4	1787.2	1727.4	1676.1	1646.1	1633.3	1646.1
5°	2112.2	2039.5	1872.8	1706.0	1543.5	1411.0	1287.0	1197.2	1133.1	1111.7	1103.1
7.5°	2112.2	1992.5	1731.7	1458.0	1218.6	1043.3	919.3	863.7	833.8	829.5	829.5
10°	2107.9	1936.9	1573.5	1214.3	940.7	820.9	782.5	773.9	773.9	773.9	778.2
12.5°	2103.6	1885.6	1393.9	979.1	791.0	752.5	739.7	739.7	744.0	748.2	752.5
15°	2095.1	1808.6	1205.7	816.7	735.4	722.6	714.0	714.0	718.3	726.9	726.9
17.5°	2086.5	1731.7	1021.9	744.0	709.8	696.9	692.7	688.4	696.9	705.5	705.5
20°	2069.4	1633.3	868.0	705.5	684.1	675.6	671.3	667.0	671.3	679.8	684.1
22.5°	2048.1	1509.3	765.3	679.8	662.7	649.9	645.6	641.4	641.4	658.5	658.5
25°	2026.7	1372.5	705.5	654.2	637.1	624.3	615.7	611.4	615.7	628.5	628.5
27.5°	1983.9	1222.8	667.0	632.8	615.7	598.6	590.0	581.5	585.8	598.6	598.6
30°	1919.8	1064.6	645.6	611.4	590.0	568.7	555.8	547.3	551.6	564.4	568.7
32.5°	1825.7	927.8	637.1	594.3	568.7	538.7	521.6	508.8	513.1	530.2	530.2
35°	1727.4	829.5	632.8	577.2	543.0	513.1	483.2	466.1	474.6	491.7	496.0
37.5°	1624.8	773.9	632.8	568.7	525.9	487.4	444.7	427.6	431.8	448.9	453.2
40°	1535.0	748.2	637.1	560.1	504.5	457.5	410.5	389.1	397.6	419.0	414.7
42.5°	1500.8	744.0	637.1	538.7	483.2	427.6	376.3	354.9	363.4	376.3	380.5
45°	1539.2	761.1	628.5	517.4	453.2	393.4	350.6	329.2	333.5	342.1	350.6
47.5°	1671.8	782.5	615.7	491.7	427.6	367.7	325.0	307.8	299.3	312.1	316.4
50°	1855.7	795.3	594.3	466.1	406.2	342.1	303.6	282.2	273.6	277.9	282.2
52.5°	2065.2	795.3	572.9	440.4	384.8	316.4	286.5	265.1	248.0	252.3	252.3
55°	2274.7	786.7	517.4	419.0	363.4	299.3	269.4	239.4	226.6	226.6	222.3
57.5°	2492.7	773.9	448.9	389.1	337.8	277.9	248.0	222.3	205.2	196.7	196.7
60°	2706.5	756.8	410.5	359.2	307.8	260.8	226.6	205.2	183.9	171.0	166.8
62.5°	2817.7	709.8	367.7	320.7	277.9	235.2	205.2	183.9	158.2	141.1	136.8
65°	2757.8	611.4	316.4	286.5	252.3	209.5	183.9	162.5	132.5	111.2	111.2
67.5°	2822.0	513.1	269.4	243.7	218.1	179.6	153.9	141.1	115.4	98.3	98.3
70°	2843.3	401.9	226.6	209.5	188.1	149.6	132.5	124.0	102.6	85.5	81.2
72.5°	2685.1	299.3	183.9	175.3	153.9	115.4	111.2	102.6	85.5	68.4	68.4
73°	*2621.0*	*277.9*	*175.3*	*166.8*	*145.4*	*111.2*	*106.9*	*98.3*	*81.2*	*68.4*	*64.1*
75°	2308.9	213.8	145.4	136.8	115.4	94.1	89.8	81.2	68.4	55.6	55.6
77.5°	1530.7	153.9	111.2	102.6	85.5	72.7	68.4	59.9	51.3	42.8	42.8
80°	564.4	102.6	81.2	72.7	64.1	59.9	51.3	42.8	34.2	34.2	29.9
82.5°	115.4	68.4	59.9	51.3	47.0	42.8	34.2	29.9	25.7	25.7	25.7
85°	47.0	42.8	34.2	34.2	34.2	29.9	25.7	25.7	21.4	21.4	17.1
87.5°	29.9	25.7	25.7	21.4	21.4	17.1	17.1	17.1	17.1	17.1	17.1
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

McGraw-Edison

Report Number: SP1-2407-184-7

Test Date: 10/10/2024

Luminaire Tested: GSS-SB1A-757-U-5WQ

Data in this report applies to families of products including GSS-SB1A-757-U-5WQ

Report Generated By FNC07603 / LDUCLS01DT446
Version: v7.04


Test Information

Test Method:	LM-79-2019
Report Number:	SP1-2407-184-7
Test Lab:	COOPER LIGHTING SOLUTIONS
Photometer:	SP1 - 76IN SPHERE
Measurement Geometry:	4π
Issue Date:	10/15/2024
Manufacturer:	COOPER LIGHTING SOLUTIONS
Product Line:	McGraw-Edison
Catalog Number:	**GSS-SB1A-757-U-5WQ**
Description:	GALLEON II SITE SLIM 1SQ 350MA 5WQ HIGH DENSITY LIGHTSQUARE WITH 70 CRI 5700K CCT 26 LEDS

Spectral Parameters

CCT (K):	5571
CIE u':	0.2033
CIE v':	0.4806
Duv:	0.0041
CIE x:	0.3308
CIE y:	0.3476
CIE z:	0.3216
Peak Wavelength (nm):	442
Dominant Wavelength (nm):	544
Purity:	3.635698
Rf:	70.4
Rg:	97.1

CRI (Ra):	69.9
R1:	68.8
R2:	72.5
R3:	76.8
R4:	72.0
R5:	70.9
R6:	65.6
R7:	75.5
R8:	56.8
R9:	-35.4
R10:	36.7
R11:	73.9
R12:	47.8
R13:	68.0
R14:	87.0
R15:	59.8



Test Conditions


Stabilization Time:	20M
Operation Time:	1H 20M
Sphere Temperature (°C):	25.2

REPORT NUMBER: SP1-2407-184-7


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-184-7

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles




CCT = 5571K
CIE x = 0.3308
CIE y = 0.3476
Duv = 0.0041

Point lies inside the ANSI 5700K 4-step quadrangle

REPORT NUMBER: SP1-2407-184-7

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)
360	0	NR	490	120	NR	620	298	NR	750	9	NR	880	0	NR
365	0	NR	495	167	NR	625	270	NR	755	7	NR	885	0	NR
370	0	NR	500	222	NR	630	245	NR	760	6	NR	890	0	NR
375	0	NR	505	279	NR	635	219	NR	765	6	NR	895	0	NR
380	1	NR	510	329	NR	640	196	NR	770	5	NR	900	0	NR
385	2	NR	515	371	NR	645	173	NR	775	4	NR	905	0	NR
390	4	NR	520	403	NR	650	153	NR	780	4	NR	910	0	NR
395	6	NR	525	424	NR	655	135	NR	785	3	NR	915	0	NR
400	9	NR	530	439	NR	660	117	NR	790	3	NR	920	0	NR
405	14	NR	535	449	NR	665	103	NR	795	2	NR	925	0	NR
410	28	NR	540	454	NR	670	89	NR	800	2	NR	930	0	NR
415	55	NR	545	459	NR	675	77	NR	805	2	NR	935	0	NR
420	118	NR	550	463	NR	680	67	NR	810	2	NR	940	0	NR
425	237	NR	555	466	NR	685	58	NR	815	1	NR	945	0	NR
430	420	NR	560	467	NR	690	50	NR	820	1	NR	950	0	NR
435	677	NR	565	469	NR	695	43	NR	825	1	NR	955	0	NR
440	962	NR	570	469	NR	700	37	NR	830	1	NR	960	0	NR
445	894	NR	575	466	NR	705	32	NR	835	1	NR	965	0	NR
450	472	NR	580	461	NR	710	28	NR	840	1	NR	970	0	NR
455	275	NR	585	450	NR	715	24	NR	845	1	NR	975	0	NR
460	180	NR	590	437	NR	720	21	NR	850	1	NR	980	0	NR
465	107	NR	595	420	NR	725	18	NR	855	0	NR	985	0	NR
470	76	NR	600	400	NR	730	15	NR	860	0	NR	990	0	NR
475	68	NR	605	376	NR	735	13	NR	865	0	NR	995	0	NR
480	69	NR	610	352	NR	740	11	NR	870	0	NR	1000	0	NR
485	86	NR	615	325	NR	745	10	NR	875	0	NR			

REPORT NUMBER: SP1-2407-184-7

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR **S/P: 1.84**

λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)
360	0	NR	490	120	NR	620	298	NR	750	9	NR	880	0	NR
365	0	NR	495	167	NR	625	270	NR	755	7	NR	885	0	NR
370	0	NR	500	222	NR	630	245	NR	760	6	NR	890	0	NR
375	0	NR	505	279	NR	635	219	NR	765	6	NR	895	0	NR
380	1	NR	510	329	NR	640	196	NR	770	5	NR	900	0	NR
385	2	NR	515	371	NR	645	173	NR	775	4	NR	905	0	NR
390	4	NR	520	403	NR	650	153	NR	780	4	NR	910	0	NR
395	6	NR	525	424	NR	655	135	NR	785	3	NR	915	0	NR
400	9	NR	530	439	NR	660	117	NR	790	3	NR	920	0	NR
405	14	NR	535	449	NR	665	103	NR	795	2	NR	925	0	NR
410	28	NR	540	454	NR	670	89	NR	800	2	NR	930	0	NR
415	55	NR	545	459	NR	675	77	NR	805	2	NR	935	0	NR
420	118	NR	550	463	NR	680	67	NR	810	2	NR	940	0	NR
425	237	NR	555	466	NR	685	58	NR	815	1	NR	945	0	NR
430	420	NR	560	467	NR	690	50	NR	820	1	NR	950	0	NR
435	677	NR	565	469	NR	695	43	NR	825	1	NR	955	0	NR
440	962	NR	570	469	NR	700	37	NR	830	1	NR	960	0	NR
445	894	NR	575	466	NR	705	32	NR	835	1	NR	965	0	NR
450	472	NR	580	461	NR	710	28	NR	840	1	NR	970	0	NR
455	275	NR	585	450	NR	715	24	NR	845	1	NR	975	0	NR
460	180	NR	590	437	NR	720	21	NR	850	1	NR	980	0	NR
465	107	NR	595	420	NR	725	18	NR	855	0	NR	985	0	NR
470	76	NR	600	400	NR	730	15	NR	860	0	NR	990	0	NR
475	68	NR	605	376	NR	735	13	NR	865	0	NR	995	0	NR
480	69	NR	610	352	NR	740	11	NR	870	0	NR	1000	0	NR
485	86	NR	615	325	NR	745	10	NR	875	0	NR			

REPORT NUMBER: SP1-2407-184-7

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR **M/P: 3.71**

λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)
360	0	NR	490	120	NR	620	298	NR	750	9	NR	880	0	NR
365	0	NR	495	167	NR	625	270	NR	755	7	NR	885	0	NR
370	0	NR	500	222	NR	630	245	NR	760	6	NR	890	0	NR
375	0	NR	505	279	NR	635	219	NR	765	6	NR	895	0	NR
380	1	NR	510	329	NR	640	196	NR	770	5	NR	900	0	NR
385	2	NR	515	371	NR	645	173	NR	775	4	NR	905	0	NR
390	4	NR	520	403	NR	650	153	NR	780	4	NR	910	0	NR
395	6	NR	525	424	NR	655	135	NR	785	3	NR	915	0	NR
400	9	NR	530	439	NR	660	117	NR	790	3	NR	920	0	NR
405	14	NR	535	449	NR	665	103	NR	795	2	NR	925	0	NR
410	28	NR	540	454	NR	670	89	NR	800	2	NR	930	0	NR
415	55	NR	545	459	NR	675	77	NR	805	2	NR	935	0	NR
420	118	NR	550	463	NR	680	67	NR	810	2	NR	940	0	NR
425	237	NR	555	466	NR	685	58	NR	815	1	NR	945	0	NR
430	420	NR	560	467	NR	690	50	NR	820	1	NR	950	0	NR
435	677	NR	565	469	NR	695	43	NR	825	1	NR	955	0	NR
440	962	NR	570	469	NR	700	37	NR	830	1	NR	960	0	NR
445	894	NR	575	466	NR	705	32	NR	835	1	NR	965	0	NR
450	472	NR	580	461	NR	710	28	NR	840	1	NR	970	0	NR
455	275	NR	585	450	NR	715	24	NR	845	1	NR	975	0	NR
460	180	NR	590	437	NR	720	21	NR	850	1	NR	980	0	NR
465	107	NR	595	420	NR	725	18	NR	855	0	NR	985	0	NR
470	76	NR	600	400	NR	730	15	NR	860	0	NR	990	0	NR
475	68	NR	605	376	NR	735	13	NR	865	0	NR	995	0	NR
480	69	NR	610	352	NR	740	11	NR	870	0	NR	1000	0	NR
485	86	NR	615	325	NR	745	10	NR	875	0	NR			


REPORT NUMBER: SP1-2407-184-7

TM-30-18


Summary


R_f = 70.4
R_g = 97.1
CIE R_a = 69.9
R_9 = -35.4


Spectral Power Distribution Comparison




Color Vector Graphics










REPORT NUMBER: SP1-2407-184-7

TM-30-18

Individual Sample Fidelity Index ($R_{f,i}$)


CES01 = 85	CES26 = 52	CES51 = 87	CES76 = 40
CES02 = 59	CES27 = 77	CES52 = 88	CES77 = 62
CES03 = 30	CES28 = 76	CES53 = 74	CES78 = 43
CES04 = 68	CES29 = 46	CES54 = 79	CES79 = 72
CES05 = 45	CES30 = 54	CES55 = 78	CES80 = 68
CES06 = 49	CES31 = 52	CES56 = 67	CES81 = 70
CES07 = 38	CES32 = 49	CES57 = 64	CES82 = 87
CES08 = 37	CES33 = 59	CES58 = 66	CES83 = 81
CES09 = 29	CES34 = 61	CES59 = 87	CES84 = 87
CES10 = 72	CES35 = 78	CES60 = 91	CES85 = 83
CES11 = 55	CES36 = 88	CES61 = 88	CES86 = 75
CES12 = 61	CES37 = 71	CES62 = 77	CES87 = 74
CES13 = 41	CES38 = 64	CES63 = 74	CES88 = 76
CES14 = 74	CES39 = 90	CES64 = 71	CES89 = 75
CES15 = 70	CES40 = 81	CES65 = 63	CES90 = 73
CES16 = 46	CES41 = 82	CES66 = 66	CES91 = 93
CES17 = 48	CES42 = 69	CES67 = 63	CES92 = 69
CES18 = 55	CES43 = 67	CES68 = 71	CES93 = 82
CES19 = 70	CES44 = 98	CES69 = 81	CES94 = 58
CES20 = 63	CES45 = 77	CES70 = 57	CES95 = 72
CES21 = 85	CES46 = 76	CES71 = 54	CES96 = 78
CES22 = 77	CES47 = 73	CES72 = 84	CES97 = 82
CES23 = 91	CES48 = 65	CES73 = 45	CES98 = 70
CES24 = 90	CES49 = 77	CES74 = 92	CES99 = 59
CES25 = 71	CES50 = 85	CES75 = 49	





REPORT NUMBER: SP1-2407-184-7

TM-30-18

Color Rendition by Hue-Angle Bin









REPORT NUMBER: SP1-2407-184-7

TM-30-18

Measure Comparisons





(END OF REPORT)