

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: McGRAW-EDISON

Report Number: P1445175

Luminaire Tested: TPTN-VA2-830-U-MQ-CG-GM

Issue Date: 05/21/2026

Test Information

Test Method: LM-79-2024
Report Number: P1445175
Test Lab: INNOVATION CENTER(G1)
Issue Date: 5/21/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: MCGRAW-EDISON
Catalog Number: TPTN-VA2-830-U-MQ-CG-GM
Description: TOPTIER NANO SPIDER MOUNT VISUAL COMFORT LED LUMINAIRE 42W 80CRI 3000K w/
TYPE V MEDIUM DISTRIBUTION OPTIC AND GLASS
Light Source: 3000K CCT, 80 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3634.3 lumens
Efficiency: N/A
Efficacy: 86.3 lumens/watt
Luminous Opening: Circular (Dia: 0.71' x H: 0')
IES Classification: Type V - Short
BUG Rating: B2 - U0 - G1

Input Watts (W): 42.1
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.98
Total Harmonic Distortion (THDi): 7.5%
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT


REPORT NUMBER: P1445175

CATALOG NUMBER: TPTN-VA2-830-U-MQ-CG-GM

Iso-Footcandle Lines of Horizontal Illumination

× Max cd

--- 1/2 Max cd




Based on 10 foot mounting height. Maximum calculated value = 6.4 fc

Type V - Short - N/A

REPORT NUMBER: P1445175

CATALOG NUMBER: TPTN-VA2-830-U-MQ-CG-GM

Luminous Intensity Polar Plot



REPORT NUMBER: P1445175

CATALOG NUMBER: TPTN-VA2-830-U-MQ-CG-GM


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	1817.2	0.0	1817.2
	% Fixture	50.0	0.0	50.0
Street Side	Lumens	1817.2	0.0	1817.2
	% Fixture	50.0	0.0	50.0
Total	Lumens	3634.3	0.0	3634.3
	% Fixture	100.0	0.0	100.0

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	57.9	1.6
10°-20°	168.4	4.6
20°-30°	313.5	8.6
30°-40°	459.1	12.6
40°-50°	594.3	16.4
50°-60°	741.9	20.4
60°-70°	735.8	20.2
70°-80°	464.5	12.8
80°-90°	98.9	2.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	3634.3	100.0
0°-180°	3634.3	100.0

Coefficient of Utilization



REPORT NUMBER: P1445175


CATALOG NUMBER: TPTN-VA2-830-U-MQ-CG-GM

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	269.9	7.4			
FM	(30°-60°)	897.7	24.7			
FH	(60°-80°)	600.2	16.5			G0/660
FVH	(80°-90°)	49.4	1.4			G1/100
BL	(0°-30°)	269.9	7.4	B1/500		
BM	(30°-60°)	897.7	24.7	B1/1000		
BH	(60°-80°)	600.2	16.5	B2/1000		G0/660
BVH	(80°-90°)	49.4	1.4			G1/100
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B2-U0-G1

Type V Short



REPORT NUMBER: P1445175

CATALOG NUMBER: TPTN-VA2-830-U-MQ-CG-GM

CANDELA DISTRIBUTION (FULL):

	0°	5°	15°	25°	35°	45°	55°	65°	75°	85°	90°
0°	640.2	640.2	640.2	640.2	640.2	640.2	640.2	640.2	640.2	640.2	640.2
2.5°	633.7	633.7	633.7	633.7	633.7	633.7	633.7	634.4	634.4	634.4	634.4
5°	619.4	618.7	618.7	618.7	620.7	622.0	625.2	627.2	629.1	629.8	629.8
7.5°	590.7	591.4	592.0	592.7	594.0	597.2	601.8	606.3	609.6	611.6	612.2
10°	567.9	567.9	568.6	567.9	569.9	573.8	579.6	587.5	593.3	596.6	596.6
12.5°	562.7	562.7	564.7	566.6	569.2	573.1	579.6	586.2	592.0	594.6	594.6
15°	571.2	573.1	575.7	580.9	583.6	584.2	588.1	593.3	599.2	602.4	603.1
17.5°	590.7	592.0	599.2	603.1	602.4	599.2	599.2	602.4	609.0	613.5	613.5
20°	626.5	627.8	631.1	631.7	627.2	618.1	610.9	612.2	620.7	626.5	627.8
22.5°	675.4	675.4	672.1	670.8	657.8	640.2	626.5	624.6	633.1	642.2	642.8
25°	727.5	727.5	721.0	709.3	690.4	665.0	644.8	636.3	645.4	655.8	657.8
27.5°	773.1	772.4	760.1	740.5	721.0	689.7	663.0	648.7	655.2	668.2	670.2
30°	803.0	800.4	780.2	754.8	734.7	702.1	672.1	655.2	661.1	675.4	677.3
32.5°	823.9	820.0	794.6	766.6	744.4	711.2	678.0	659.8	665.0	680.6	681.9
35°	836.3	831.7	805.0	777.0	752.2	718.4	681.9	661.1	666.3	683.2	685.2
37.5°	843.4	838.9	815.4	787.4	760.7	728.1	685.8	663.0	666.9	684.5	686.5
40°	846.0	844.7	825.8	799.1	770.5	737.3	691.0	663.7	666.9	685.8	688.4
42.5°	848.6	849.9	836.3	811.5	783.5	748.3	696.9	665.0	666.9	687.8	689.1
45°	856.4	857.1	851.9	831.7	804.3	769.2	707.9	671.5	670.2	691.7	694.9
47.5°	871.4	873.4	873.4	860.3	838.9	803.7	728.8	682.5	679.3	706.0	708.6
50°	881.2	883.8	893.6	884.4	870.8	833.0	749.0	690.4	687.8	715.8	718.4
52.5°	891.6	894.9	910.5	915.1	904.6	863.0	770.5	704.0	693.0	724.9	727.5
55°	904.6	905.3	927.4	943.1	938.5	904.6	792.6	713.2	698.8	734.0	738.6
57.5°	891.0	892.9	923.5	942.4	950.2	917.7	798.5	702.1	686.5	722.3	726.8
60°	864.9	869.5	900.7	929.4	935.2	902.7	784.8	681.2	661.7	701.4	704.0
62.5°	833.6	841.5	870.1	903.3	915.1	886.4	766.6	651.9	631.7	678.0	679.3
65°	780.9	791.3	833.6	862.3	885.7	857.1	741.8	613.5	595.9	635.0	635.0
67.5°	713.2	719.7	760.1	807.6	822.6	802.4	689.7	565.3	536.0	575.1	579.6
70°	639.6	643.5	674.1	724.9	741.8	733.3	625.2	503.4	468.9	512.6	513.9
72.5°	549.0	555.5	586.2	628.5	650.0	643.5	548.4	430.5	399.9	437.7	433.8
75°	440.3	448.1	478.0	516.5	541.2	534.1	461.1	349.7	325.6	351.0	350.4
77.5°	340.6	340.6	367.3	403.1	418.8	413.6	355.6	269.6	244.2	265.7	267.7
80°	236.4	235.8	258.6	284.0	297.0	296.3	256.0	186.9	170.6	182.4	179.1
82.5°	142.6	143.9	157.6	174.5	187.6	188.2	161.5	115.3	103.6	108.1	105.5
85°	61.9	65.1	74.9	86.0	95.7	95.7	84.7	57.3	50.8	46.9	43.0
87.5°	15.0	15.0	19.5	24.1	28.7	30.6	28.0	21.5	18.9	11.1	5.2
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

MCGRAW EDISON

Report Number: SP1-2411-284-4

Test Date: 11/22/2024

Luminaire Tested: TTN-D0-830-U-WQ

Data in this report applies to families of products including TTN-D0-830-U-WQ


Test Information

Test Method: LM-79-2019
 Report Number: SP1-2411-284-4
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 11/22/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: MCGRAW EDISON
 Catalog Number: **TTN-D0-830-U-WQ**
 Description: TOPTIER NANO LED PARKING GARAGE LUMINAIRE. 3000K, 80 CRI LEDS AND WIDE DISTRIBUTION

Spectral Parameters

CCT (K): 2963
 CIE u' : 0.2515
 CIE v' : 0.5238
 Duv: 0.0012
 CIE x: 0.4414
 CIE y: 0.4086
 CIE z: 0.1501
 Peak Wavelength (nm): 603
 Dominant Wavelength (nm): 582
 Purity: 55.12798
 R_f: 86.1
 R_g: 94.9

CRI (Ra): 82.9
 R1: 81.4
 R2: 91.9
 R3: 95.2
 R4: 81.6
 R5: 82.3
 R6: 91.4
 R7: 82.0
 R8: 57.2
 R9: 3.9
 R10: 82.5
 R11: 82.3
 R12: 76.5
 R13: 83.9
 R14: 97.8
 R15: 72.6



Test Conditions


Stabilization Time: 37M
 Operation Time: 1H 37M
 Sphere Temperature (°C): 25.0

REPORT NUMBER: SP1-2411-284-4


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/22/2024	10/22/2025
DC Power Source	IN0208	10/22/2024	10/22/2025
Sphere Thermometer	IN0085	10/22/2024	10/22/2025
Room Thermometer	IN0046	10/22/2024	10/22/2025

REPORT NUMBER: SP1-2411-284-4

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3000K 4-step quadrangle

REPORT NUMBER: SP1-2411-284-4

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	267	NR	620	915	NR	750	23	NR	880	0	NR
365	0	NR	495	315	NR	625	866	NR	755	20	NR	885	0	NR
370	0	NR	500	360	NR	630	811	NR	760	17	NR	890	0	NR
375	0	NR	505	396	NR	635	750	NR	765	14	NR	895	0	NR
380	0	NR	510	418	NR	640	686	NR	770	12	NR	900	0	NR
385	0	NR	515	435	NR	645	619	NR	775	10	NR	905	0	NR
390	0	NR	520	448	NR	650	554	NR	780	9	NR	910	0	NR
395	0	NR	525	462	NR	655	491	NR	785	7	NR	915	0	NR
400	1	NR	530	476	NR	660	431	NR	790	6	NR	920	0	NR
405	2	NR	535	495	NR	665	376	NR	795	5	NR	925	0	NR
410	5	NR	540	520	NR	670	325	NR	800	4	NR	930	0	NR
415	10	NR	545	547	NR	675	280	NR	805	4	NR	935	0	NR
420	21	NR	550	576	NR	680	241	NR	810	3	NR	940	0	NR
425	42	NR	555	612	NR	685	207	NR	815	3	NR	945	0	NR
430	77	NR	560	651	NR	690	176	NR	820	2	NR	950	0	NR
435	135	NR	565	693	NR	695	149	NR	825	2	NR	955	0	NR
440	215	NR	570	741	NR	700	127	NR	830	2	NR	960	0	NR
445	321	NR	575	793	NR	705	107	NR	835	2	NR	965	0	NR
450	479	NR	580	847	NR	710	89	NR	840	1	NR	970	0	NR
455	432	NR	585	897	NR	715	75	NR	845	1	NR	975	0	NR
460	265	NR	590	940	NR	720	62	NR	850	1	NR	980	0	NR
465	231	NR	595	971	NR	725	51	NR	855	1	NR	985	0	NR
470	204	NR	600	993	NR	730	43	NR	860	1	NR	990	0	NR
475	168	NR	605	996	NR	735	36	NR	865	1	NR	995	0	NR
480	183	NR	610	986	NR	740	31	NR	870	1	NR	1000	0	NR
485	223	NR	615	957	NR	745	26	NR	875	0	NR			

REPORT NUMBER: SP1-2411-284-4

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.34

λ (nm)	Power W ^λ /nm	Lumens (Φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (Φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (Φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (Φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (Φ/nm)
360	0	NR	490	267	NR	620	915	NR	750	23	NR	880	0	NR
365	0	NR	495	315	NR	625	866	NR	755	20	NR	885	0	NR
370	0	NR	500	360	NR	630	811	NR	760	17	NR	890	0	NR
375	0	NR	505	396	NR	635	750	NR	765	14	NR	895	0	NR
380	0	NR	510	418	NR	640	686	NR	770	12	NR	900	0	NR
385	0	NR	515	435	NR	645	619	NR	775	10	NR	905	0	NR
390	0	NR	520	448	NR	650	554	NR	780	9	NR	910	0	NR
395	0	NR	525	462	NR	655	491	NR	785	7	NR	915	0	NR
400	1	NR	530	476	NR	660	431	NR	790	6	NR	920	0	NR
405	2	NR	535	495	NR	665	376	NR	795	5	NR	925	0	NR
410	5	NR	540	520	NR	670	325	NR	800	4	NR	930	0	NR
415	10	NR	545	547	NR	675	280	NR	805	4	NR	935	0	NR
420	21	NR	550	576	NR	680	241	NR	810	3	NR	940	0	NR
425	42	NR	555	612	NR	685	207	NR	815	3	NR	945	0	NR
430	77	NR	560	651	NR	690	176	NR	820	2	NR	950	0	NR
435	135	NR	565	693	NR	695	149	NR	825	2	NR	955	0	NR
440	215	NR	570	741	NR	700	127	NR	830	2	NR	960	0	NR
445	321	NR	575	793	NR	705	107	NR	835	2	NR	965	0	NR
450	479	NR	580	847	NR	710	89	NR	840	1	NR	970	0	NR
455	432	NR	585	897	NR	715	75	NR	845	1	NR	975	0	NR
460	265	NR	590	940	NR	720	62	NR	850	1	NR	980	0	NR
465	231	NR	595	971	NR	725	51	NR	855	1	NR	985	0	NR
470	204	NR	600	993	NR	730	43	NR	860	1	NR	990	0	NR
475	168	NR	605	996	NR	735	36	NR	865	1	NR	995	0	NR
480	183	NR	610	986	NR	740	31	NR	870	1	NR	1000	0	NR
485	223	NR	615	957	NR	745	26	NR	875	0	NR			

REPORT NUMBER: SP1-2411-284-4

Melanopic Flux vs. Wavelength


Melanopic Lumens: NR
M/P: 2.58


λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	267	NR	620	915	NR	750	23	NR	880	0	NR
365	0	NR	495	315	NR	625	866	NR	755	20	NR	885	0	NR
370	0	NR	500	360	NR	630	811	NR	760	17	NR	890	0	NR
375	0	NR	505	396	NR	635	750	NR	765	14	NR	895	0	NR
380	0	NR	510	418	NR	640	686	NR	770	12	NR	900	0	NR
385	0	NR	515	435	NR	645	619	NR	775	10	NR	905	0	NR
390	0	NR	520	448	NR	650	554	NR	780	9	NR	910	0	NR
395	0	NR	525	462	NR	655	491	NR	785	7	NR	915	0	NR
400	1	NR	530	476	NR	660	431	NR	790	6	NR	920	0	NR
405	2	NR	535	495	NR	665	376	NR	795	5	NR	925	0	NR
410	5	NR	540	520	NR	670	325	NR	800	4	NR	930	0	NR
415	10	NR	545	547	NR	675	280	NR	805	4	NR	935	0	NR
420	21	NR	550	576	NR	680	241	NR	810	3	NR	940	0	NR
425	42	NR	555	612	NR	685	207	NR	815	3	NR	945	0	NR
430	77	NR	560	651	NR	690	176	NR	820	2	NR	950	0	NR
435	135	NR	565	693	NR	695	149	NR	825	2	NR	955	0	NR
440	215	NR	570	741	NR	700	127	NR	830	2	NR	960	0	NR
445	321	NR	575	793	NR	705	107	NR	835	2	NR	965	0	NR
450	479	NR	580	847	NR	710	89	NR	840	1	NR	970	0	NR
455	432	NR	585	897	NR	715	75	NR	845	1	NR	975	0	NR
460	265	NR	590	940	NR	720	62	NR	850	1	NR	980	0	NR
465	231	NR	595	971	NR	725	51	NR	855	1	NR	985	0	NR
470	204	NR	600	993	NR	730	43	NR	860	1	NR	990	0	NR
475	168	NR	605	996	NR	735	36	NR	865	1	NR	995	0	NR
480	183	NR	610	986	NR	740	31	NR	870	1	NR	1000	0	NR
485	223	NR	615	957	NR	745	26	NR	875	0	NR			

REPORT NUMBER: SP1-2411-284-4





TM-30-18

Summary

$R_f = 86.1$
 $R_g = 94.9$
 $CIE R_a = 82.9$
 $R_9 = 3.9$




Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)



CES01 = 86	CES26 = 87	CES51 = 95	CES76 = 85
CES02 = 63	CES27 = 95	CES52 = 95	CES77 = 85
CES03 = 31	CES28 = 96	CES53 = 91	CES78 = 83
CES04 = 70	CES29 = 90	CES54 = 92	CES79 = 89
CES05 = 50	CES30 = 96	CES55 = 91	CES80 = 89
CES06 = 51	CES31 = 92	CES56 = 88	CES81 = 70
CES07 = 42	CES32 = 86	CES57 = 87	CES82 = 96
CES08 = 41	CES33 = 94	CES58 = 88	CES83 = 94
CES09 = 29	CES34 = 94	CES59 = 92	CES84 = 92
CES10 = 76	CES35 = 97	CES60 = 93	CES85 = 76
CES11 = 59	CES36 = 88	CES61 = 90	CES86 = 66
CES12 = 65	CES37 = 98	CES62 = 92	CES87 = 85
CES13 = 44	CES38 = 95	CES63 = 90	CES88 = 87
CES14 = 74	CES39 = 98	CES64 = 85	CES89 = 75
CES15 = 72	CES40 = 96	CES65 = 81	CES90 = 89
CES16 = 48	CES41 = 97	CES66 = 84	CES91 = 80
CES17 = 50	CES42 = 98	CES67 = 83	CES92 = 64
CES18 = 57	CES43 = 92	CES68 = 85	CES93 = 79
CES19 = 72	CES44 = 99	CES69 = 89	CES94 = 61
CES20 = 67	CES45 = 94	CES70 = 83	CES95 = 75
CES21 = 87	CES46 = 91	CES71 = 81	CES96 = 84
CES22 = 79	CES47 = 92	CES72 = 93	CES97 = 89
CES23 = 92	CES48 = 84	CES73 = 78	CES98 = 85
CES24 = 91	CES49 = 92	CES74 = 91	CES99 = 76
CES25 = 72	CES50 = 95	CES75 = 84	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)