Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled data based on original data using

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: McGRAW-EDISON

Report Number: P821198

Luminaire Tested: **TT-D1-735-24VDC-RW-UPL**

Issue Date: 10/29/2020

Report Generated By 670245763

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

Test Information

Test Method:	LM-79-08
Report Number:	P821198
	REPORT IS FROM IESNA LM-79-08 TEST DATA - UPLIGHT (G2-2002-677-2) AND
Test Lab:	INNOVATION CENTER
Issue Date:	10/29/2020
Manufacturer:	COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line:	McGRAW-EDISON
Catalog Number:	TT-D1-735-24VDC-RW-UPL
Description:	TOPTIER LED PARKING GARAGE LUMINAIRE WITH UPLIGHT
	3500K, 70 CRI LEDS AND RECTANGULAR DISTRIBUTION
Light Source:	-
Ballast/Driver:	ELECTRONIC DRIVER

Summary

Lumens per Lamp:	N/A
Luminaire Lumens:	3762.7 lumens
Efficiency:	N/A
Efficacy:	134.4 lumens/watt
Luminous Opening:	Vertical Cylinder (Dia: 1.12' x H: 0.1')
IES Classification:	Type IV - Short
BUG Rating:	B2 - U4 - G2


Input Watts (W):	28
Input Voltage (V):	NR
Input Current (Ain):	NR
Voltage Rise (V):	NR
Power Factor:	NR
Total Harmonic Distortion (THDi):	NR
Frequency (hertz):	60
Stabilization Time:	NR
Operation Time:	NR
Ambient Temperature (°C):	NR
Test Distance:	25 FT

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P821198
CATALOG NUMBER: TT-D1-735-24VDC-RW-UPL

Iso-Footcandle Lines of Horizontal Illumination




Based on 15 foot mounting height. Maximum calculated value = 0.9 fc
Type IV - Short - N/A

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P821198
CATALOG NUMBER: TT-D1-735-24VDC-RW-UPL

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report


REPORT NUMBER: P821198
CATALOG NUMBER: TT-D1-735-24VDC-RW-UPL

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	1465.5	415.9	1881.4
	% Fixture	38.9	11.1	50.0
Street Side	Lumens	1465.5	415.9	1881.4
	% Fixture	38.9	11.1	50.0
Total	Lumens	2931.0	831.7	3762.7
	% Fixture	77.9	22.1	100.0

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	5.6	0.1
10°-20°	20.9	0.6
20°-30°	48.2	1.3
30°-40°	109.1	2.9
40°-50°	265.7	7.1
50°-60°	597.4	15.9
60°-70°	873.1	23.2
70°-80°	760.7	20.2
80°-90°	250.4	6.7
90°-100°	42.6	1.1
100°-110°	66.0	1.8
110°-120°	91.9	2.4
120°-130°	119.0	3.2
130°-140°	138.7	3.7
140°-150°	140.5	3.7
150°-160°	121.9	3.2
160°-170°	82.2	2.2
170°-180°	28.9	0.8
0°-90°	2931.0	77.9
0°-180°	3762.7	100.0



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269


Scaled Data Report

REPORT NUMBER: P821198
CATALOG NUMBER: TT-D1-735-24VDC-RW-UPL

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit B	U	G
FL	(0°-30°)	37.3	1.0			
FM	(30°-60°)	486.1	12.9			
FH	(60°-80°)	816.9	21.7			G1/1800
FVH	(80°-90°)	125.2	3.3			G2/225
BL	(0°-30°)	37.3	1.0	B0/110		
BM	(30°-60°)	486.1	12.9	B1/1000		
BH	(60°-80°)	816.9	21.7	B2/1000		G2/1000
BVH	(80°-90°)	125.2	3.3			G2/225
UL	(90°-100°)	42.6	1.1		U2/50	
UH	(100°-180°)	789.1	21.0		U4/1000	

BUG Rating: B2-U4-G2
Type IV Short



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P821198
CATALOG NUMBER: TT-D1-735-24VDC-RW-UPL

CANDELA DISTRIBUTION (FULL):

	0°	5°	15°	25°	35°	45°	55°	65°	75°	85°	90°
0°	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	53.5	*53.5*
2.5°	54.2	54.2	54.9	54.9	54.9	54.9	54.9	54.9	54.9	54.9	*54.9*
5°	56.3	56.3	56.3	56.3	56.9	56.9	56.3	56.3	56.3	56.3	*56.3*
7.5°	59.7	59.0	59.7	59.7	59.7	59.0	59.0	59.0	58.3	58.3	*58.3*
10°	63.2	63.2	63.9	63.2	63.2	62.5	62.5	62.5	61.8	61.8	*61.8*
12.5°	68.1	68.1	68.1	68.1	67.4	67.4	66.7	66.0	65.3	65.3	*65.3*
15°	74.3	73.6	73.6	72.9	72.2	71.5	70.8	70.8	70.1	70.1	*70.1*
17.5°	80.6	80.6	79.9	79.2	77.8	77.1	77.1	76.4	75.7	75.7	*75.7*
20°	88.2	88.2	87.5	86.1	84.7	84.0	83.3	83.3	82.6	82.6	*82.6*
22.5°	97.2	96.5	95.1	93.8	92.4	91.7	91.0	90.3	90.3	90.3	*90.3*
25°	107.0	106.3	105.6	103.5	101.4	100.7	99.3	99.3	98.6	99.3	*99.3*
27.5°	118.8	118.1	116.7	114.6	111.8	110.4	109.7	109.7	110.4	110.4	*111.1*
30°	133.3	132.0	130.6	127.8	125.0	122.9	122.9	123.6	125.7	127.1	*127.1*
32.5°	150.7	150.0	147.9	145.2	140.3	138.9	140.3	144.5	147.2	149.3	*150.7*
35°	170.8	170.2	167.4	162.5	159.0	158.3	162.5	169.5	178.5	181.3	*182.7*
37.5°	193.1	193.8	190.3	184.7	181.3	182.7	191.0	204.2	213.2	219.5	*220.9*
40°	220.9	222.2	218.1	211.8	208.4	213.9	227.1	242.4	258.4	266.0	*268.1*
42.5°	253.5	255.6	250.0	243.8	241.7	250.7	269.5	294.5	322.9	332.0	*335.4*
45°	293.8	295.2	288.2	282.7	281.3	297.2	329.2	370.9	416.0	436.8	*440.3*
47.5°	341.7	341.0	334.8	327.8	329.2	352.1	400.0	456.3	504.2	536.2	*543.1*
50°	396.6	393.1	388.2	379.9	388.9	422.3	482.7	550.7	631.3	659.8	*672.3*
52.5°	451.4	445.2	441.0	435.5	451.4	494.5	579.2	698.0	819.5	884.8	*898.0*
55°	500.7	495.9	493.8	494.5	519.5	581.3	692.4	844.5	961.9	1016.1	*1025.8*
57.5°	549.4	546.6	544.5	548.7	588.2	668.8	793.8	936.2	1032.7	1073.0	*1080.0*
60°	595.2	598.0	596.6	609.1	657.0	738.3	846.6	986.9	1080.0	1116.8	*1124.4*
62.5°	645.9	648.0	648.0	661.9	700.8	772.3	882.7	1046.6	1164.7	1218.9	*1227.2*
65°	*689.6*	*691.0*	*693.8*	*694.5*	*730.6*	*802.2*	*946.6*	*1101.5*	*1207.0*	*1269.6*	*1275.1*
67.5°	722.3	723.7	720.2	716.7	744.5	809.1	941.7	1094.5	1188.3	1235.5	*1239.7*
70°	748.7	742.4	732.7	715.3	724.4	773.0	901.5	1039.0	1133.4	1175.8	*1182.0*
72.5°	752.1	746.6	716.0	677.1	666.0	708.4	830.6	954.2	1035.5	1075.8	*1076.5*
75°	731.3	716.7	666.0	607.7	586.9	627.1	732.0	844.5	909.8	943.8	*947.3*
77.5°	661.2	647.3	583.4	516.7	493.1	527.8	616.7	707.7	770.2	803.5	*805.6*
80°	536.9	532.0	473.7	412.5	384.1	404.2	482.0	553.5	604.2	643.8	*647.3*
82.5°	395.9	391.7	347.3	293.8	270.9	287.5	343.1	395.9	443.1	475.0	*477.1*
85°	247.2	238.9	211.1	173.6	158.3	169.5	206.3	241.7	284.1	309.1	*310.4*
87.5°	82.6	79.2	68.1	56.3	47.2	49.3	60.4	73.6	107.6	118.8	*125.7*
90°	30.1	29.1	29.1	29.1	29.1	29.1	29.1	29.1	29.1	29.1	*29.1*
92.5°	34.8	34.2	34.2	33.8	33.8	33.8	33.8	33.8	33.8	33.8	*33.8*
95°	39.4	39.4	39.4	38.5	38.5	38.5	38.5	38.5	38.5	38.5	*38.5*
97.5°	44.6	44.6	44.6	44.2	44.2	44.2	44.2	44.2	44.2	44.2	*44.2*
100°	49.8	49.8	49.8	49.8	49.8	49.8	49.8	49.8	49.8	49.8	*49.8*
102.5°	55.9	55.9	55.9	55.9	55.9	55.9	55.9	56.4	55.9	55.9	*55.9*
105°	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.9	62.0	62.0	*62.0*
107.5°	68.6	68.6	69.0	69.0	69.0	69.0	69.0	69.5	69.0	69.0	*69.0*
110°	75.1	75.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1	*76.1*

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P821198
CATALOG NUMBER: TT-D1-735-24VDC-RW-UPL

CANDELA DISTRIBUTION (continued):

	0°	5°	15°	25°	35°	45°	55°	65°	75°	85°	90°
112.5°	83.1	83.1	84.0	84.0	84.0	84.0	84.6	84.6	84.0	84.0	*84.0*
115°	91.1	91.1	92.0	92.0	92.0	92.0	93.0	93.0	92.0	92.0	*92.0*
117.5°	100.5	100.5	101.0	101.4	101.4	101.4	102.4	102.4	101.4	101.4	*101.4*
120°	109.9	109.9	109.9	110.8	110.8	110.8	111.8	111.8	110.8	110.8	*110.8*
122.5°	120.7	120.7	121.2	121.6	121.6	121.6	122.6	122.6	122.1	122.1	*121.6*
125°	131.5	131.5	132.4	132.4	132.4	132.4	133.4	133.4	133.4	133.4	*132.4*
127.5°	143.2	143.2	144.2	144.2	144.2	144.2	145.1	145.1	145.1	145.1	*144.2*
130°	155.0	155.0	155.9	155.9	155.9	155.9	156.8	156.8	156.8	156.8	*155.9*
132.5°	167.2	167.2	167.6	167.6	167.6	168.1	168.6	168.6	168.6	168.6	*168.1*
135°	179.4	179.4	179.4	179.4	179.4	180.3	180.3	180.3	180.3	180.3	*180.3*
137.5°	191.2	190.6	191.2	190.6	191.2	191.6	191.6	191.6	191.6	191.6	*191.6*
140°	202.9	201.9	202.9	201.9	202.9	202.9	202.9	202.9	202.9	202.9	*202.9*
142.5°	213.7	213.2	213.7	212.7	213.7	213.7	213.7	213.7	213.7	213.7	*213.7*
145°	224.5	224.5	224.5	223.5	224.5	224.5	224.5	224.5	224.5	224.5	*224.5*
147.5°	235.8	235.3	235.8	234.8	235.8	235.8	235.8	235.8	235.8	235.8	*235.8*
150°	247.0	246.1	247.0	246.1	247.0	247.0	247.0	247.0	247.0	247.0	*247.0*
152.5°	256.0	255.5	256.4	255.5	256.0	256.0	256.4	256.0	256.0	256.0	*256.0*
155°	264.9	264.9	265.8	264.9	264.9	264.9	265.8	264.9	264.9	264.9	*264.9*
157.5°	272.4	272.4	273.3	272.4	272.4	272.4	273.3	272.4	272.4	272.4	*272.4*
160°	279.9	279.9	280.8	279.9	279.9	279.9	280.8	279.9	279.9	279.9	*279.9*
162.5°	286.0	286.0	286.9	286.0	286.0	286.0	286.9	286.0	286.0	286.0	*286.0*
165°	292.1	292.1	293.0	292.1	292.1	292.1	293.0	292.1	292.1	292.1	*292.1*
167.5°	295.8	295.8	296.8	295.8	295.8	295.8	296.8	295.8	295.8	295.8	*295.8*
170°	299.6	299.6	300.5	299.6	299.6	299.6	300.5	299.6	299.6	299.6	*299.6*
172.5°	302.0	302.0	302.8	302.0	302.4	302.0	302.8	302.0	302.0	302.0	*302.0*
175°	304.3	304.3	305.2	304.3	305.2	304.3	305.2	304.3	304.3	304.3	*304.3*
177.5°	305.2	305.2	305.7	305.2	305.7	305.2	305.7	305.2	305.2	305.2	*305.2*
180°	306.2	306.2	306.2	306.2	306.2	306.2	306.2	306.2	306.2	306.2	*306.2*

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

Streetworks

Report Number: SP1-2407-176-4

Test Date: 09/24/2024

Luminaire Tested: MEM2-HTN-VA-30-735-U-WQ

Data in this report applies to families of products including MEM2-HTN-VA-30-735-U-WQ


Report Generated By FNC07603 / LDUCLS01DT446
Version: v7.04

Test Information

Test Method:	LM-79-2019
Report Number:	SP1-2407-176-4
Test Lab:	COOPER LIGHTING SOLUTIONS
Photometer:	SP1 - 76IN SPHERE
Measurement Geometry:	4π
Issue Date:	09/27/2024
Manufacturer:	COOPER LIGHTING SOLUTIONS
Product Line:	Streetworks
Catalog Number:	**MEM2-HTN-VA-30-735-U-WQ**
Description:	EPIC MODERN VISUAL COMFORT 30W WAVESTREAM WIDE

Spectral Parameters

CCT (K):	3348	CRI (Ra):	73.4		
CIE u':	0.2384	R1:	70.8	R9:	-19.2
CIE v':	0.5184	R2:	79.9	R10:	52.5
Duv:	0.0030	R3:	87.6	R11:	68.0
CIE x:	0.4177	R4:	72.6	R12:	42.6
CIE y:	0.4036	R5:	69.3	R13:	72.0
CIE z:	0.1787	R6:	71.3	R14:	92.6
Peak Wavelength (nm):	593	R7:	82.1	R15:	63.8
Dominant Wavelength (nm):	580	R8:	53.3		
Purity:	46.5223				
Rf:	75.8				
Rg:	95.8				



Test Conditions


Stabilization Time:	30M
Operation Time:	1H 30M
Sphere Temperature (°C):	25.2

REPORT NUMBER: SP1-2407-176-4


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-176-4

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles




CCT = 3348K
CIE x = 0.4177
CIE y = 0.4036
Duv = 0.0030

Point lies inside the ANSI 3500K 4-step quadrangle

REPORT NUMBER: SP1-2407-176-4

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)
360	0	NR	490	110	NR	620	844	NR	750	28	NR	880	0	NR
365	0	NR	495	150	NR	625	792	NR	755	25	NR	885	0	NR
370	0	NR	500	214	NR	630	737	NR	760	22	NR	890	0	NR
375	0	NR	505	293	NR	635	683	NR	765	19	NR	895	0	NR
380	0	NR	510	376	NR	640	625	NR	770	16	NR	900	0	NR
385	0	NR	515	458	NR	645	566	NR	775	14	NR	905	0	NR
390	0	NR	520	526	NR	650	509	NR	780	12	NR	910	0	NR
395	1	NR	525	584	NR	655	453	NR	785	10	NR	915	0	NR
400	3	NR	530	631	NR	660	401	NR	790	9	NR	920	0	NR
405	5	NR	535	671	NR	665	353	NR	795	8	NR	925	0	NR
410	10	NR	540	704	NR	670	308	NR	800	7	NR	930	0	NR
415	21	NR	545	737	NR	675	269	NR	805	6	NR	935	0	NR
420	44	NR	550	766	NR	680	235	NR	810	5	NR	940	0	NR
425	90	NR	555	797	NR	685	204	NR	815	4	NR	945	0	NR
430	171	NR	560	832	NR	690	177	NR	820	4	NR	950	0	NR
435	305	NR	565	866	NR	695	152	NR	825	3	NR	955	0	NR
440	455	NR	570	901	NR	700	131	NR	830	3	NR	960	0	NR
445	615	NR	575	933	NR	705	112	NR	835	3	NR	965	0	NR
450	771	NR	580	963	NR	710	96	NR	840	2	NR	970	0	NR
455	579	NR	585	984	NR	715	80	NR	845	2	NR	975	0	NR
460	313	NR	590	1000	NR	720	67	NR	850	2	NR	980	0	NR
465	221	NR	595	999	NR	725	55	NR	855	1	NR	985	0	NR
470	156	NR	600	990	NR	730	46	NR	860	1	NR	990	0	NR
475	103	NR	605	968	NR	735	40	NR	865	1	NR	995	0	NR
480	89	NR	610	937	NR	740	35	NR	870	1	NR	1000	0	NR
485	93	NR	615	893	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-176-4

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR **S/P: 1.31**

λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)
360	0	NR	490	110	NR	620	844	NR	750	28	NR	880	0	NR
365	0	NR	495	150	NR	625	792	NR	755	25	NR	885	0	NR
370	0	NR	500	214	NR	630	737	NR	760	22	NR	890	0	NR
375	0	NR	505	293	NR	635	683	NR	765	19	NR	895	0	NR
380	0	NR	510	376	NR	640	625	NR	770	16	NR	900	0	NR
385	0	NR	515	458	NR	645	566	NR	775	14	NR	905	0	NR
390	0	NR	520	526	NR	650	509	NR	780	12	NR	910	0	NR
395	1	NR	525	584	NR	655	453	NR	785	10	NR	915	0	NR
400	3	NR	530	631	NR	660	401	NR	790	9	NR	920	0	NR
405	5	NR	535	671	NR	665	353	NR	795	8	NR	925	0	NR
410	10	NR	540	704	NR	670	308	NR	800	7	NR	930	0	NR
415	21	NR	545	737	NR	675	269	NR	805	6	NR	935	0	NR
420	44	NR	550	766	NR	680	235	NR	810	5	NR	940	0	NR
425	90	NR	555	797	NR	685	204	NR	815	4	NR	945	0	NR
430	171	NR	560	832	NR	690	177	NR	820	4	NR	950	0	NR
435	305	NR	565	866	NR	695	152	NR	825	3	NR	955	0	NR
440	455	NR	570	901	NR	700	131	NR	830	3	NR	960	0	NR
445	615	NR	575	933	NR	705	112	NR	835	3	NR	965	0	NR
450	771	NR	580	963	NR	710	96	NR	840	2	NR	970	0	NR
455	579	NR	585	984	NR	715	80	NR	845	2	NR	975	0	NR
460	313	NR	590	1000	NR	720	67	NR	850	2	NR	980	0	NR
465	221	NR	595	999	NR	725	55	NR	855	1	NR	985	0	NR
470	156	NR	600	990	NR	730	46	NR	860	1	NR	990	0	NR
475	103	NR	605	968	NR	735	40	NR	865	1	NR	995	0	NR
480	89	NR	610	937	NR	740	35	NR	870	1	NR	1000	0	NR
485	93	NR	615	893	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-176-4

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR **M/P: 2.4**

λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)
360	0	NR	490	110	NR	620	844	NR	750	28	NR	880	0	NR
365	0	NR	495	150	NR	625	792	NR	755	25	NR	885	0	NR
370	0	NR	500	214	NR	630	737	NR	760	22	NR	890	0	NR
375	0	NR	505	293	NR	635	683	NR	765	19	NR	895	0	NR
380	0	NR	510	376	NR	640	625	NR	770	16	NR	900	0	NR
385	0	NR	515	458	NR	645	566	NR	775	14	NR	905	0	NR
390	0	NR	520	526	NR	650	509	NR	780	12	NR	910	0	NR
395	1	NR	525	584	NR	655	453	NR	785	10	NR	915	0	NR
400	3	NR	530	631	NR	660	401	NR	790	9	NR	920	0	NR
405	5	NR	535	671	NR	665	353	NR	795	8	NR	925	0	NR
410	10	NR	540	704	NR	670	308	NR	800	7	NR	930	0	NR
415	21	NR	545	737	NR	675	269	NR	805	6	NR	935	0	NR
420	44	NR	550	766	NR	680	235	NR	810	5	NR	940	0	NR
425	90	NR	555	797	NR	685	204	NR	815	4	NR	945	0	NR
430	171	NR	560	832	NR	690	177	NR	820	4	NR	950	0	NR
435	305	NR	565	866	NR	695	152	NR	825	3	NR	955	0	NR
440	455	NR	570	901	NR	700	131	NR	830	3	NR	960	0	NR
445	615	NR	575	933	NR	705	112	NR	835	3	NR	965	0	NR
450	771	NR	580	963	NR	710	96	NR	840	2	NR	970	0	NR
455	579	NR	585	984	NR	715	80	NR	845	2	NR	975	0	NR
460	313	NR	590	1000	NR	720	67	NR	850	2	NR	980	0	NR
465	221	NR	595	999	NR	725	55	NR	855	1	NR	985	0	NR
470	156	NR	600	990	NR	730	46	NR	860	1	NR	990	0	NR
475	103	NR	605	968	NR	735	40	NR	865	1	NR	995	0	NR
480	89	NR	610	937	NR	740	35	NR	870	1	NR	1000	0	NR
485	93	NR	615	893	NR	745	31	NR	875	1	NR			


REPORT NUMBER: SP1-2407-176-4

TM-30-18


Summary


R_f = 75.8
R_g = 95.8
CIE R_a = 73.4
R_9 = -19.2


Spectral Power Distribution Comparison




Color Vector Graphics










REPORT NUMBER: SP1-2407-176-4

TM-30-18

Individual Sample Fidelity Index ($R_{f,i}$)


CES01 = 86	CES26 = 65	CES51 = 88	CES76 = 55
CES02 = 62	CES27 = 88	CES52 = 87	CES77 = 74
CES03 = 31	CES28 = 83	CES53 = 77	CES78 = 58
CES04 = 70	CES29 = 66	CES54 = 86	CES79 = 84
CES05 = 48	CES30 = 79	CES55 = 84	CES80 = 81
CES06 = 51	CES31 = 69	CES56 = 74	CES81 = 78
CES07 = 41	CES32 = 62	CES57 = 73	CES82 = 92
CES08 = 40	CES33 = 75	CES58 = 75	CES83 = 89
CES09 = 29	CES34 = 73	CES59 = 87	CES84 = 88
CES10 = 75	CES35 = 85	CES60 = 91	CES85 = 79
CES11 = 58	CES36 = 95	CES61 = 84	CES86 = 71
CES12 = 64	CES37 = 80	CES62 = 88	CES87 = 79
CES13 = 43	CES38 = 88	CES63 = 73	CES88 = 81
CES14 = 74	CES39 = 96	CES64 = 69	CES89 = 71
CES15 = 71	CES40 = 91	CES65 = 66	CES90 = 80
CES16 = 47	CES41 = 91	CES66 = 62	CES91 = 81
CES17 = 50	CES42 = 81	CES67 = 60	CES92 = 63
CES18 = 56	CES43 = 77	CES68 = 68	CES93 = 78
CES19 = 72	CES44 = 99	CES69 = 76	CES94 = 56
CES20 = 65	CES45 = 85	CES70 = 60	CES95 = 70
CES21 = 87	CES46 = 82	CES71 = 55	CES96 = 79
CES22 = 79	CES47 = 83	CES72 = 85	CES97 = 84
CES23 = 92	CES48 = 75	CES73 = 52	CES98 = 77
CES24 = 91	CES49 = 79	CES74 = 96	CES99 = 68
CES25 = 72	CES50 = 87	CES75 = 57	





REPORT NUMBER: SP1-2407-176-4

TM-30-18

Color Rendition by Hue-Angle Bin









REPORT NUMBER: SP1-2407-176-4

TM-30-18

Measure Comparisons





(END OF REPORT)