Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled data based on original data using

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: McGRAW-EDISON

Report Number: P821219

Luminaire Tested: **TT-D3-735-24VDC-CQ-UPL**

Issue Date: 7/23/2020

Report Generated By 670245763

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

Test Information

Test Method:	LM-79-08
Report Number:	P821219
	REPORT IS FROM IESNA LM-79-08 TEST DATA - UPLIGHT (G2-2002-677-2) AND
Test Lab:	INNOVATION CENTER
Issue Date:	7/23/2020
Manufacturer:	COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line:	McGRAW-EDISON
Catalog Number:	TT-D3-735-24VDC-CQ-UPL
Description:	TOPTIER LED PARKING GARAGE LUMINAIRE WITH UPLIGHT
	3500K, 70 CRI LEDS AND CONCENTRATED DISTRIBUTION
Light Source:	-
Ballast/Driver:	ELECTRONIC DRIVER

Summary

Lumens per Lamp:	N/A
Luminaire Lumens:	6775.7 lumens
Efficiency:	N/A
Efficacy:	147.3 lumens/watt
Luminous Opening:	Vertical Cylinder (Dia: 1.12' x H: 0.1')
IES Classification:	Type V - Short
BUG Rating:	B2 - U4 - G1


Input Watts (W):	46
Input Voltage (V):	NR
Input Current (Ain):	NR
Voltage Rise (V):	NR
Power Factor:	NR
Total Harmonic Distortion (THDi):	NR
Frequency (hertz):	60
Stabilization Time:	NR
Operation Time:	NR
Ambient Temperature (°C):	NR
Test Distance:	25 FT

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P821219
CATALOG NUMBER: TT-D3-735-24VDC-CQ-UPL

Iso-Footcandle Lines of Horizontal Illumination




Based on 15 foot mounting height. Maximum calculated value = 6.6 fc
Type V - Short - N/A

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P821219
CATALOG NUMBER: TT-D3-735-24VDC-CQ-UPL

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report


REPORT NUMBER: P821219
CATALOG NUMBER: TT-D3-735-24VDC-CQ-UPL

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	2972.0	415.9	3387.9
	% Fixture	43.9	6.1	50.0
Street Side	Lumens	2972.0	415.9	3387.9
	% Fixture	43.9	6.1	50.0
Total	Lumens	5944.0	831.7	6775.7
	% Fixture	87.7	12.3	100.0

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	141.3	2.1
10°-20°	413.9	6.1
20°-30°	658.2	9.7
30°-40°	865.9	12.8
40°-50°	1059.8	15.6
50°-60°	1147.9	16.9
60°-70°	987.6	14.6
70°-80°	555.2	8.2
80°-90°	114.1	1.7
90°-100°	42.6	0.6
100°-110°	66.0	1.0
110°-120°	91.9	1.4
120°-130°	119.0	1.8
130°-140°	138.7	2.0
140°-150°	140.5	2.1
150°-160°	121.9	1.8
160°-170°	82.2	1.2
170°-180°	28.9	0.4
0°-90°	5944.0	87.7
0°-180°	6775.7	100.0



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269


Scaled Data Report

REPORT NUMBER: P821219
CATALOG NUMBER: TT-D3-735-24VDC-CQ-UPL

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit B	U	G
FL	(0°-30°)	606.7	9.0			
FM	(30°-60°)	1536.8	22.7			
FH	(60°-80°)	771.4	11.4			G1/1800
FVH	(80°-90°)	57.0	0.8			G1/100
BL	(0°-30°)	606.7	9.0	B2/1000		
BM	(30°-60°)	1536.8	22.7	B2/2500		
BH	(60°-80°)	771.4	11.4	B2/1000		G1/1800
BVH	(80°-90°)	57.0	0.8			G1/100
UL	(90°-100°)	42.6	0.6		U2/50	
UH	(100°-180°)	789.1	11.6		U4/1000	

BUG Rating: B2-U4-G1
Type V Short



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P821219
CATALOG NUMBER: TT-D3-735-24VDC-CQ-UPL

CANDELA DISTRIBUTION (FULL):

	0°	5°	15°	25°	35°	45°	55°	65°	75°	85°	90°
0°	1486.0	*1486.0*	1486.0	1486.0	1486.0	1486.0	1486.0	1486.0	1486.0	1486.0	1486.0
2.5°	*1482.2*	*1487.0*	*1485.1*	*1485.1*	*1485.1*	*1485.1*	*1483.2*	*1485.1*	*1485.1*	*1486.0*	*1485.1*
5°	1483.2	*1482.2*	1482.2	1483.2	1483.2	1484.1	1482.2	1483.2	1484.1	1484.1	1485.1
7.5°	1480.3	*1481.3*	1479.4	1481.3	1479.4	1480.3	1480.3	1481.3	1480.3	1481.3	1483.2
10°	1474.7	*1475.6*	1474.7	1474.7	1474.7	1476.6	1472.8	1475.6	1474.7	1475.6	1474.7
12.5°	1464.3	*1469.0*	1467.1	1469.0	1469.0	1469.0	1466.2	1468.1	1469.0	1469.0	1469.0
15°	1459.5	*1460.5*	1457.7	1461.4	1462.4	1463.3	1459.5	1461.4	1461.4	1462.4	1463.3
17.5°	1449.1	*1453.9*	1452.9	1455.8	1454.8	1457.7	1456.7	1455.8	1454.8	1456.7	1454.8
20°	1441.6	*1446.3*	1445.4	1448.2	1449.1	1452.0	1449.1	1449.1	1446.3	1447.3	1450.1
22.5°	1434.0	*1435.9*	1435.9	1438.7	1438.7	1441.6	1438.7	1437.8	1437.8	1436.9	1439.7
25°	1421.7	*1422.7*	1421.7	1424.6	1426.5	1428.4	1427.4	1425.5	1424.6	1424.6	1423.6
27.5°	1401.9	*1405.7*	1407.6	1411.3	1412.3	1415.1	1411.3	1411.3	1409.4	1407.6	1408.5
30°	1386.8	*1388.6*	1388.6	1397.2	1397.2	1401.9	1397.2	1396.2	1395.3	1394.3	1392.4
32.5°	1372.6	*1375.4*	1378.2	1384.9	1389.6	1391.5	1388.6	1386.8	1382.0	1379.2	1378.2
35°	1361.2	*1362.2*	1367.9	1377.3	1383.0	1387.7	1383.9	1379.2	1372.6	1367.9	1371.6
37.5°	1352.7	*1353.7*	1362.2	1374.5	1384.9	1388.6	1383.0	1375.4	1365.0	1359.3	1357.5
40°	1345.2	*1350.8*	1360.3	1377.3	1388.6	1394.3	1389.6	1379.2	1364.1	1352.7	1351.8
42.5°	1341.4	*1344.2*	1358.4	1378.2	1394.3	1401.9	1395.3	1381.1	1362.2	1348.9	1348.0
45°	1331.9	*1340.4*	1353.7	1379.2	1397.2	1406.6	1397.2	1379.2	1356.5	1341.4	1338.5
47.5°	1324.4	*1327.2*	1348.0	1377.3	1399.0	1406.6	1397.2	1374.5	1346.1	1326.3	1324.4
50°	1306.4	*1313.0*	1333.8	1365.0	1390.5	1398.1	1386.8	1356.5	1324.4	1302.6	1298.8
52.5°	1279.0	*1284.7*	1309.2	1348.0	1372.6	1381.1	1364.1	1331.9	1294.1	1267.6	1267.6
55°	1236.5	*1245.0*	1270.5	1310.2	1341.4	1348.9	1329.1	1295.1	1252.5	1226.1	1225.1
57.5°	1185.4	*1191.1*	1218.5	1262.0	1292.2	1303.6	1283.7	1245.9	1203.4	1172.2	1169.3
60°	1119.2	*1126.8*	1156.1	1197.7	1228.9	1238.3	1221.3	1183.5	1140.0	1106.9	1106.9
62.5°	1039.8	*1048.3*	1077.6	1120.2	1152.3	1166.5	1142.9	1106.9	1061.6	1029.4	1026.6
65°	947.2	*954.8*	981.2	1025.7	1058.7	1069.1	1051.2	1013.4	969.9	939.6	936.8
67.5°	843.2	*853.6*	880.1	917.9	946.2	959.5	948.1	914.1	868.7	837.5	834.7
70°	730.7	*738.3*	759.1	794.1	826.2	835.6	818.6	795.9	753.4	725.0	721.3
72.5°	610.7	*617.3*	634.3	667.4	690.1	702.4	692.9	663.6	629.6	605.9	609.7
75°	489.7	*488.7*	507.6	531.3	552.1	560.6	553.9	535.0	503.8	484.0	483.0
77.5°	368.7	*378.1*	384.7	404.6	421.6	428.2	418.8	403.6	380.0	363.9	366.8
80°	259.0	*253.3*	265.6	277.9	289.3	295.9	290.2	281.7	265.6	253.3	251.5
82.5°	158.8	*154.1*	159.8	171.1	178.7	180.6	181.5	171.1	164.5	155.0	156.9
85°	70.0	*70.9*	75.6	83.2	84.1	85.1	85.1	83.2	75.6	74.7	72.8
87.5°	17.0	*17.0*	18.0	20.8	20.8	21.7	21.7	18.9	18.0	16.1	17.0
90°	30.1	*29.1*	29.1	29.1	29.1	29.1	29.1	29.1	29.1	29.1	29.1
92.5°	34.8	*34.2*	34.2	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8
95°	39.4	*39.4*	39.4	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5
97.5°	44.6	*44.6*	44.6	44.2	44.2	44.2	44.2	44.2	44.2	44.2	44.2
100°	49.8	*49.8*	49.8	49.8	49.8	49.8	49.8	49.8	49.8	49.8	49.8
102.5°	55.9	*55.9*	55.9	55.9	55.9	55.9	55.9	56.4	55.9	55.9	55.9
105°	62.0	*62.0*	62.0	62.0	62.0	62.0	62.0	62.9	62.0	62.0	62.0
107.5°	68.6	*68.6*	69.0	69.0	69.0	69.0	69.0	69.5	69.0	69.0	69.0
110°	75.1	*75.1*	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P821219
CATALOG NUMBER: TT-D3-735-24VDC-CQ-UPL

CANDELA DISTRIBUTION (continued):

	0°	5°	15°	25°	35°	45°	55°	65°	75°	85°	90°
112.5°	83.1	*83.1*	84.0	84.0	84.0	84.0	84.6	84.6	84.0	84.0	84.0
115°	91.1	*91.1*	92.0	92.0	92.0	92.0	93.0	93.0	92.0	92.0	92.0
117.5°	100.5	*100.5*	101.0	101.4	101.4	101.4	102.4	102.4	101.4	101.4	101.4
120°	109.9	*109.9*	109.9	110.8	110.8	110.8	111.8	111.8	110.8	110.8	110.8
122.5°	120.7	*120.7*	121.2	121.6	121.6	121.6	122.6	122.6	122.1	122.1	121.6
125°	131.5	*131.5*	132.4	132.4	132.4	132.4	133.4	133.4	133.4	133.4	132.4
127.5°	143.2	*143.2*	144.2	144.2	144.2	144.2	145.1	145.1	145.1	145.1	144.2
130°	155.0	*155.0*	155.9	155.9	155.9	155.9	156.8	156.8	156.8	156.8	155.9
132.5°	167.2	*167.2*	167.6	167.6	167.6	168.1	168.6	168.6	168.6	168.6	168.1
135°	179.4	*179.4*	179.4	179.4	179.4	180.3	180.3	180.3	180.3	180.3	180.3
137.5°	191.2	*190.6*	191.2	190.6	191.2	191.6	191.6	191.6	191.6	191.6	191.6
140°	202.9	*201.9*	202.9	201.9	202.9	202.9	202.9	202.9	202.9	202.9	202.9
142.5°	213.7	*213.2*	213.7	212.7	213.7	213.7	213.7	213.7	213.7	213.7	213.7
145°	224.5	*224.5*	224.5	223.5	224.5	224.5	224.5	224.5	224.5	224.5	224.5
147.5°	235.8	*235.3*	235.8	234.8	235.8	235.8	235.8	235.8	235.8	235.8	235.8
150°	247.0	*246.1*	247.0	246.1	247.0	247.0	247.0	247.0	247.0	247.0	247.0
152.5°	256.0	*255.5*	256.4	255.5	256.0	256.0	256.4	256.0	256.0	256.0	256.0
155°	264.9	*264.9*	265.8	264.9	264.9	264.9	265.8	264.9	264.9	264.9	264.9
157.5°	272.4	*272.4*	273.3	272.4	272.4	272.4	273.3	272.4	272.4	272.4	272.4
160°	279.9	*279.9*	280.8	279.9	279.9	279.9	280.8	279.9	279.9	279.9	279.9
162.5°	286.0	*286.0*	286.9	286.0	286.0	286.0	286.9	286.0	286.0	286.0	286.0
165°	292.1	*292.1*	293.0	292.1	292.1	292.1	293.0	292.1	292.1	292.1	292.1
167.5°	295.8	*295.8*	296.8	295.8	295.8	295.8	296.8	295.8	295.8	295.8	295.8
170°	299.6	*299.6*	300.5	299.6	299.6	299.6	300.5	299.6	299.6	299.6	299.6
172.5°	302.0	*302.0*	302.8	302.0	302.4	302.0	302.8	302.0	302.0	302.0	302.0
175°	304.3	*304.3*	305.2	304.3	305.2	304.3	305.2	304.3	304.3	304.3	304.3
177.5°	305.2	*305.2*	305.7	305.2	305.7	305.2	305.7	305.2	305.2	305.2	305.2
180°	306.2	*306.2*	306.2	306.2	306.2	306.2	306.2	306.2	306.2	306.2	306.2

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

Streetworks

Report Number: SP1-2407-176-4

Test Date: 09/24/2024

Luminaire Tested: MEM2-HTN-VA-30-735-U-WQ

Data in this report applies to families of products including MEM2-HTN-VA-30-735-U-WQ


Report Generated By FNC07603 / LDUCLS01DT446
Version: v7.04

Test Information

Test Method:	LM-79-2019
Report Number:	SP1-2407-176-4
Test Lab:	COOPER LIGHTING SOLUTIONS
Photometer:	SP1 - 76IN SPHERE
Measurement Geometry:	4π
Issue Date:	09/27/2024
Manufacturer:	COOPER LIGHTING SOLUTIONS
Product Line:	Streetworks
Catalog Number:	**MEM2-HTN-VA-30-735-U-WQ**
Description:	EPIC MODERN VISUAL COMFORT 30W WAVESTREAM WIDE

Spectral Parameters

CCT (K):	3348	CRI (Ra):	73.4		
CIE u':	0.2384	R1:	70.8	R9:	-19.2
CIE v':	0.5184	R2:	79.9	R10:	52.5
Duv:	0.0030	R3:	87.6	R11:	68.0
CIE x:	0.4177	R4:	72.6	R12:	42.6
CIE y:	0.4036	R5:	69.3	R13:	72.0
CIE z:	0.1787	R6:	71.3	R14:	92.6
Peak Wavelength (nm):	593	R7:	82.1	R15:	63.8
Dominant Wavelength (nm):	580	R8:	53.3		
Purity:	46.5223				
Rf:	75.8				
Rg:	95.8				



Test Conditions


Stabilization Time:	30M
Operation Time:	1H 30M
Sphere Temperature (°C):	25.2

REPORT NUMBER: SP1-2407-176-4


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-176-4

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles




CCT = 3348K
CIE x = 0.4177
CIE y = 0.4036
Duv = 0.0030

Point lies inside the ANSI 3500K 4-step quadrangle

REPORT NUMBER: SP1-2407-176-4

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)
360	0	NR	490	110	NR	620	844	NR	750	28	NR	880	0	NR
365	0	NR	495	150	NR	625	792	NR	755	25	NR	885	0	NR
370	0	NR	500	214	NR	630	737	NR	760	22	NR	890	0	NR
375	0	NR	505	293	NR	635	683	NR	765	19	NR	895	0	NR
380	0	NR	510	376	NR	640	625	NR	770	16	NR	900	0	NR
385	0	NR	515	458	NR	645	566	NR	775	14	NR	905	0	NR
390	0	NR	520	526	NR	650	509	NR	780	12	NR	910	0	NR
395	1	NR	525	584	NR	655	453	NR	785	10	NR	915	0	NR
400	3	NR	530	631	NR	660	401	NR	790	9	NR	920	0	NR
405	5	NR	535	671	NR	665	353	NR	795	8	NR	925	0	NR
410	10	NR	540	704	NR	670	308	NR	800	7	NR	930	0	NR
415	21	NR	545	737	NR	675	269	NR	805	6	NR	935	0	NR
420	44	NR	550	766	NR	680	235	NR	810	5	NR	940	0	NR
425	90	NR	555	797	NR	685	204	NR	815	4	NR	945	0	NR
430	171	NR	560	832	NR	690	177	NR	820	4	NR	950	0	NR
435	305	NR	565	866	NR	695	152	NR	825	3	NR	955	0	NR
440	455	NR	570	901	NR	700	131	NR	830	3	NR	960	0	NR
445	615	NR	575	933	NR	705	112	NR	835	3	NR	965	0	NR
450	771	NR	580	963	NR	710	96	NR	840	2	NR	970	0	NR
455	579	NR	585	984	NR	715	80	NR	845	2	NR	975	0	NR
460	313	NR	590	1000	NR	720	67	NR	850	2	NR	980	0	NR
465	221	NR	595	999	NR	725	55	NR	855	1	NR	985	0	NR
470	156	NR	600	990	NR	730	46	NR	860	1	NR	990	0	NR
475	103	NR	605	968	NR	735	40	NR	865	1	NR	995	0	NR
480	89	NR	610	937	NR	740	35	NR	870	1	NR	1000	0	NR
485	93	NR	615	893	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-176-4

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR **S/P: 1.31**

λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)
360	0	NR	490	110	NR	620	844	NR	750	28	NR	880	0	NR
365	0	NR	495	150	NR	625	792	NR	755	25	NR	885	0	NR
370	0	NR	500	214	NR	630	737	NR	760	22	NR	890	0	NR
375	0	NR	505	293	NR	635	683	NR	765	19	NR	895	0	NR
380	0	NR	510	376	NR	640	625	NR	770	16	NR	900	0	NR
385	0	NR	515	458	NR	645	566	NR	775	14	NR	905	0	NR
390	0	NR	520	526	NR	650	509	NR	780	12	NR	910	0	NR
395	1	NR	525	584	NR	655	453	NR	785	10	NR	915	0	NR
400	3	NR	530	631	NR	660	401	NR	790	9	NR	920	0	NR
405	5	NR	535	671	NR	665	353	NR	795	8	NR	925	0	NR
410	10	NR	540	704	NR	670	308	NR	800	7	NR	930	0	NR
415	21	NR	545	737	NR	675	269	NR	805	6	NR	935	0	NR
420	44	NR	550	766	NR	680	235	NR	810	5	NR	940	0	NR
425	90	NR	555	797	NR	685	204	NR	815	4	NR	945	0	NR
430	171	NR	560	832	NR	690	177	NR	820	4	NR	950	0	NR
435	305	NR	565	866	NR	695	152	NR	825	3	NR	955	0	NR
440	455	NR	570	901	NR	700	131	NR	830	3	NR	960	0	NR
445	615	NR	575	933	NR	705	112	NR	835	3	NR	965	0	NR
450	771	NR	580	963	NR	710	96	NR	840	2	NR	970	0	NR
455	579	NR	585	984	NR	715	80	NR	845	2	NR	975	0	NR
460	313	NR	590	1000	NR	720	67	NR	850	2	NR	980	0	NR
465	221	NR	595	999	NR	725	55	NR	855	1	NR	985	0	NR
470	156	NR	600	990	NR	730	46	NR	860	1	NR	990	0	NR
475	103	NR	605	968	NR	735	40	NR	865	1	NR	995	0	NR
480	89	NR	610	937	NR	740	35	NR	870	1	NR	1000	0	NR
485	93	NR	615	893	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-176-4

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR **M/P: 2.4**

λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)
360	0	NR	490	110	NR	620	844	NR	750	28	NR	880	0	NR
365	0	NR	495	150	NR	625	792	NR	755	25	NR	885	0	NR
370	0	NR	500	214	NR	630	737	NR	760	22	NR	890	0	NR
375	0	NR	505	293	NR	635	683	NR	765	19	NR	895	0	NR
380	0	NR	510	376	NR	640	625	NR	770	16	NR	900	0	NR
385	0	NR	515	458	NR	645	566	NR	775	14	NR	905	0	NR
390	0	NR	520	526	NR	650	509	NR	780	12	NR	910	0	NR
395	1	NR	525	584	NR	655	453	NR	785	10	NR	915	0	NR
400	3	NR	530	631	NR	660	401	NR	790	9	NR	920	0	NR
405	5	NR	535	671	NR	665	353	NR	795	8	NR	925	0	NR
410	10	NR	540	704	NR	670	308	NR	800	7	NR	930	0	NR
415	21	NR	545	737	NR	675	269	NR	805	6	NR	935	0	NR
420	44	NR	550	766	NR	680	235	NR	810	5	NR	940	0	NR
425	90	NR	555	797	NR	685	204	NR	815	4	NR	945	0	NR
430	171	NR	560	832	NR	690	177	NR	820	4	NR	950	0	NR
435	305	NR	565	866	NR	695	152	NR	825	3	NR	955	0	NR
440	455	NR	570	901	NR	700	131	NR	830	3	NR	960	0	NR
445	615	NR	575	933	NR	705	112	NR	835	3	NR	965	0	NR
450	771	NR	580	963	NR	710	96	NR	840	2	NR	970	0	NR
455	579	NR	585	984	NR	715	80	NR	845	2	NR	975	0	NR
460	313	NR	590	1000	NR	720	67	NR	850	2	NR	980	0	NR
465	221	NR	595	999	NR	725	55	NR	855	1	NR	985	0	NR
470	156	NR	600	990	NR	730	46	NR	860	1	NR	990	0	NR
475	103	NR	605	968	NR	735	40	NR	865	1	NR	995	0	NR
480	89	NR	610	937	NR	740	35	NR	870	1	NR	1000	0	NR
485	93	NR	615	893	NR	745	31	NR	875	1	NR			


REPORT NUMBER: SP1-2407-176-4

TM-30-18


Summary


R_f = 75.8
R_g = 95.8
CIE R_a = 73.4
R_9 = -19.2


Spectral Power Distribution Comparison




Color Vector Graphics










REPORT NUMBER: SP1-2407-176-4

TM-30-18

Individual Sample Fidelity Index ($R_{f,i}$)


CES01 = 86	CES26 = 65	CES51 = 88	CES76 = 55
CES02 = 62	CES27 = 88	CES52 = 87	CES77 = 74
CES03 = 31	CES28 = 83	CES53 = 77	CES78 = 58
CES04 = 70	CES29 = 66	CES54 = 86	CES79 = 84
CES05 = 48	CES30 = 79	CES55 = 84	CES80 = 81
CES06 = 51	CES31 = 69	CES56 = 74	CES81 = 78
CES07 = 41	CES32 = 62	CES57 = 73	CES82 = 92
CES08 = 40	CES33 = 75	CES58 = 75	CES83 = 89
CES09 = 29	CES34 = 73	CES59 = 87	CES84 = 88
CES10 = 75	CES35 = 85	CES60 = 91	CES85 = 79
CES11 = 58	CES36 = 95	CES61 = 84	CES86 = 71
CES12 = 64	CES37 = 80	CES62 = 88	CES87 = 79
CES13 = 43	CES38 = 88	CES63 = 73	CES88 = 81
CES14 = 74	CES39 = 96	CES64 = 69	CES89 = 71
CES15 = 71	CES40 = 91	CES65 = 66	CES90 = 80
CES16 = 47	CES41 = 91	CES66 = 62	CES91 = 81
CES17 = 50	CES42 = 81	CES67 = 60	CES92 = 63
CES18 = 56	CES43 = 77	CES68 = 68	CES93 = 78
CES19 = 72	CES44 = 99	CES69 = 76	CES94 = 56
CES20 = 65	CES45 = 85	CES70 = 60	CES95 = 70
CES21 = 87	CES46 = 82	CES71 = 55	CES96 = 79
CES22 = 79	CES47 = 83	CES72 = 85	CES97 = 84
CES23 = 92	CES48 = 75	CES73 = 52	CES98 = 77
CES24 = 91	CES49 = 79	CES74 = 96	CES99 = 68
CES25 = 72	CES50 = 87	CES75 = 57	





REPORT NUMBER: SP1-2407-176-4

TM-30-18

Color Rendition by Hue-Angle Bin









REPORT NUMBER: SP1-2407-176-4

TM-30-18

Measure Comparisons





(END OF REPORT)