

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: McGRAW-EDISON

Report Number: P1212037

Luminaire Tested: **GKO-PB2E-835-U-T1**

Issue Date: 11/5/2025



Test Information

Test Method: LM-79-08
Report Number: P1212037
Test Lab: INNOVATION CENTER(G1)
Issue Date: 11/5/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: MCGRAW-EDISON
Catalog Number: GKO-PB2E-835-U-T1
Description: GEKKO WALL PACK 12000LM PACKAGE 80CRI 3500K FIXTURE w/ TYPE I DISTRIBUTION OPTIC
Light Source: (20) 3500K CCT, 80 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 12054.1 lumens
Efficiency: N/A
Efficacy: 115.1 lumens/watt
Luminous Opening: Rectangular (W 0.67' x L: 0.33' x H: 0')
IES Classification: Type I - Short
BUG Rating: B3 - U0 - G3

Input Watts (W): 104.7
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.97
Total Harmonic Distortion (THDi): 6%
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT

REPORT NUMBER: P1212037
 CATALOG NUMBER: GKO-PB2E-835-U-T1

Iso-Footcandle Lines of Horizontal Illumination


✕ Max cd
 - - - 1/2 Max cd



Based on 15 foot mounting height. Maximum calculated value = 13.3 fc
 Type I - Short - N/A

REPORT NUMBER: P1212037
CATALOG NUMBER: GKO-PB2E-835-U-T1

Luminous Intensity Polar Plot



REPORT NUMBER: P1212037

CATALOG NUMBER: GKO-PB2E-835-U-T1

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	6027.1	0.0	6027.1
	% Fixture	50.0	0.0	50.0
Street Side	Lumens	6027.1	0.0	6027.1
	% Fixture	50.0	0.0	50.0
Total	Lumens	12054.1	0.0	12054.1
	% Fixture	100.0	0.0	100.0

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	286.9	2.4
10°-20°	864.4	7.2
20°-30°	1437.4	11.9
30°-40°	1909.6	15.8
40°-50°	2152.8	17.9
50°-60°	2213.7	18.4
60°-70°	2092.0	17.4
70°-80°	1024.1	8.5
80°-90°	73.3	0.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	12054.1	100.0
0°-180°	12054.1	100.0

Coefficient of Utilization



REPORT NUMBER: P1212037


CATALOG NUMBER: GKO-PB2E-835-U-T1

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	1294.4	10.7			
FM	(30°-60°)	3138.0	26.0			
FH	(60°-80°)	1558.0	12.9			G1/1800
FVH	(80°-90°)	36.6	0.3			G1/100
BL	(0°-30°)	1294.4	10.7	B3/2500		
BM	(30°-60°)	3138.0	26.0	B3/5000		
BH	(60°-80°)	1558.0	12.9	B3/2500		G3/2500
BVH	(80°-90°)	36.6	0.3			G1/100
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B3-U0-G3

Type I Short



REPORT NUMBER: P1212037

CATALOG NUMBER: GKO-PB2E-835-U-T1

CANDELA DISTRIBUTION (FULL):

	0°	5°	15°	25°	35°	45°	55°	65°	70°	75°	80°
0°	2991.1	2991.1	2991.1	2991.1	2991.1	2991.1	2991.1	2991.1	2991.1	2991.1	2991.1
2.5°	2993.3	2997.8	2988.9	2988.9	2993.3	2995.6	2995.6	2997.8	2993.3	2993.3	2991.1
5°	2993.3	2995.6	2991.1	2991.1	2995.6	3002.2	3000.0	3004.5	3004.5	3002.2	3002.2
7.5°	2991.1	2995.6	2991.1	2993.3	3000.0	3013.3	3013.3	3013.3	3017.8	3022.2	3022.2
10°	2988.9	2993.3	2995.6	2997.8	3006.7	3026.7	3031.1	3033.4	3040.0	3046.7	3046.7
12.5°	2977.8	2982.2	2988.9	2997.8	3013.3	3040.0	3048.9	3055.6	3066.7	3073.4	3077.8
15°	2962.2	2964.5	2980.0	2997.8	3022.2	3055.6	3073.4	3084.5	3100.0	3108.9	3115.6
17.5°	2940.0	2942.2	2966.7	2993.3	3028.9	3075.6	3104.5	3122.2	3137.8	3151.1	3160.0
20°	2911.1	2917.8	2946.7	2988.9	3040.0	3095.6	3137.8	3168.9	3184.5	3197.8	3211.1
22.5°	2875.6	2882.2	2917.8	2977.8	3051.1	3122.2	3177.8	3217.8	3237.8	3255.6	3271.1
25°	2822.2	2831.1	2873.3	2951.1	3055.6	3151.1	3222.2	3273.4	3291.1	3313.4	3326.7
27.5°	2740.0	2746.7	2797.8	2897.8	3042.2	3182.2	3273.4	3333.4	3353.4	3377.8	3391.1
30°	2611.1	2624.5	2686.7	2811.1	3008.9	3206.7	3333.4	3393.4	3417.8	3442.2	3460.0
32.5°	2444.5	2464.5	2533.3	2693.3	2944.5	3215.6	3397.8	3466.7	3497.8	3524.5	3546.7
35°	2237.8	2257.8	2340.0	2542.2	2842.2	3197.8	3462.2	3551.1	3588.9	3624.5	3651.1
37.5°	2002.2	2020.0	2120.0	2351.1	2695.6	3142.2	3513.4	3644.5	3695.6	3742.2	3777.8
40°	1764.5	1784.5	1893.3	2140.0	2517.8	3035.6	3535.6	3746.7	3811.1	3871.1	3915.6
42.5°	1506.7	1531.1	1653.3	1915.6	2311.1	2888.9	3517.8	3846.7	3926.7	4008.9	4075.6
45°	1277.8	1282.2	1415.6	1668.9	2084.5	2700.0	3455.6	3942.2	4051.1	4166.7	4262.2
47.5°	1057.8	1066.7	1182.2	1433.3	1848.9	2486.7	3342.2	4017.8	4191.1	4340.0	4480.0
50°	862.2	873.3	977.8	1202.2	1613.3	2253.3	3188.9	4062.2	4311.1	4513.4	4708.9
52.5°	702.2	715.6	802.2	1000.0	1375.6	2008.9	3000.0	4068.9	4420.0	4686.7	4946.7
55°	584.4	593.3	660.0	817.8	1146.7	1755.6	2784.5	4035.6	4491.1	4842.2	5188.9
57.5°	493.3	502.2	548.9	673.3	940.0	1495.6	2522.2	3957.8	4528.9	4977.8	5433.4
60°	428.9	435.6	468.9	557.8	773.3	1251.1	2240.0	3820.0	4517.8	5062.3	5635.6
62.5°	382.2	384.4	413.3	475.6	637.8	1020.0	1922.2	3613.4	4426.7	5073.4	5773.4
65°	340.0	342.2	360.0	404.4	524.4	820.0	1591.1	3328.9	4253.4	4995.6	5793.4
67.5°	275.6	280.0	306.7	340.0	431.1	648.9	1253.3	2955.6	3982.2	4793.4	5680.0
70°	220.0	222.2	248.9	286.7	351.1	511.1	962.2	2453.3	3557.8	4464.5	5386.7
72.5°	164.4	168.9	193.3	231.1	286.7	395.6	695.6	1855.6	2844.5	3764.5	4691.1
75°	131.1	133.3	142.2	177.8	222.2	300.0	468.9	1124.5	1713.3	2328.9	2875.6
77.5°	111.1	113.3	113.3	137.8	164.4	202.2	248.9	446.7	724.4	1031.1	1366.7
80°	91.1	95.6	86.7	102.2	117.8	117.8	115.6	213.3	342.2	484.4	635.6
82.5°	66.7	71.1	66.7	71.1	71.1	64.4	60.0	80.0	108.9	148.9	162.2
85°	46.7	48.9	53.3	48.9	46.7	37.8	28.9	22.2	13.3	15.6	22.2
87.5°	31.1	37.8	44.4	42.2	35.6	28.9	20.0	13.3	6.7	8.9	8.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0



REPORT NUMBER: P1212037
 CATALOG NUMBER: GKO-PB2E-835-U-T1

CANDELA DISTRIBUTION (continued):

	85°	87.5°	90°
0°	2991.1	2991.1	2991.1
2.5°	2993.3	2991.1	2988.9
5°	3004.5	3002.2	3000.0
7.5°	3020.0	3020.0	3020.0
10°	3044.5	3048.9	3048.9
12.5°	3075.6	3080.0	3080.0
15°	3113.4	3115.6	3120.0
17.5°	3160.0	3162.2	3162.2
20°	3215.6	3213.4	3217.8
22.5°	3271.1	3271.1	3271.1
25°	3328.9	3328.9	3328.9
27.5°	3395.6	3395.6	3391.1
30°	3468.9	3468.9	3468.9
32.5°	3557.8	3560.0	3562.2
35°	3671.1	3675.6	3682.2
37.5°	3800.0	3811.1	3817.8
40°	3953.4	3957.8	3968.9
42.5°	4124.5	4137.8	4140.0
45°	4337.8	4360.0	4368.9
47.5°	4588.9	4620.0	4635.6
50°	4868.9	4904.5	4926.7
52.5°	5173.4	5231.1	5257.8
55°	5497.8	5597.8	5626.7
57.5°	5864.5	6000.0	6040.0
60°	6224.5	6415.6	6480.0
62.5°	6531.1	6800.0	6880.0
65°	6746.7	7071.2	7188.9
67.5°	6791.1	7175.6	7315.6
70°	6524.5	6917.8	7080.0
72.5°	5673.4	6028.9	6231.1
75°	3351.1	3606.7	3544.5
77.5°	1682.2	1755.6	1766.7
80°	737.8	782.2	800.0
82.5°	182.2	186.7	211.1
85°	24.4	28.9	26.7
87.5°	8.9	8.9	11.1
90°	0.0	0.0	0.0

(END OF REPORT)