

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1058383

Luminaire Tested: S122RDRP-H485D850-X4F0-XX-UDD-BVL-B

Issue Date: 8/7/2025

Test Information

Test Method: LM-79-2024
Report Number: P1058383
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2406-143-21)
Test Lab: INNOVATION CENTER
Issue Date: 8/7/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S122RDRP-H485D850-X4F0-XX-UDD-BVL-B
Description: DEFINE 2 BLACK REGRESSED DIRECT RECESSED HOUSING WITH BLACK STRAIGHT BLADE LOUVER WITH DIFFUSER
HIGH PERFORMANCE LIGHT ENGINE
Light Source: 5000K CCT, 80 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 334.1 lumens
Efficiency: N/A
Efficacy: 19.2 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.8 / 0.88
Luminous Opening: Rectangular (W 0.15' x L: 4' x H: 0')
CIE Type: Direct

Input Watts (W): 17.4
Input Voltage (V): 120
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1058383

CATALOG NUMBER: S122RDRP-H485D850-X4F0-XX-UDD-BVL-B

Luminous Intensity Polar Plot



TEST NUMBER: P1058383

CATALOG NUMBER: S122RDRP-H485D850-X4F0-XX-UDD-BVL-B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102
1	113	110	108	105	111	108	106	104	104	102	101	100	99	98	97	96	95
2	107	102	98	94	105	100	97	93	97	94	91	94	92	89	91	89	87
3	101	95	89	85	99	93	89	85	91	87	83	88	85	82	86	83	81
4	96	88	82	78	94	87	81	77	85	80	76	83	79	75	81	77	75
5	91	82	76	71	89	81	75	71	79	74	70	77	73	70	76	72	69
6	86	76	70	66	84	76	70	65	74	69	65	73	68	64	71	67	64
7	81	71	65	61	80	71	65	61	69	64	60	68	63	60	67	63	60
8	77	67	61	56	76	66	60	56	65	60	56	64	59	56	63	59	56
9	73	63	57	53	72	62	57	52	61	56	52	61	56	52	60	55	52
10	69	59	53	49	68	59	53	49	58	53	49	57	52	49	56	52	49

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	6556	6556	6556
5°	6511	6414	6442
10°	6376	6108	5953
15°	5998	5582	5353
20°	5355	4956	4675
25°	4681	4190	3976
30°	4016	3424	3200
35°	3350	2674	2404
40°	2606	1973	1537
45°	1824	1313	665
50°	993	689	238
55°	145	241	171
60°	30	55	111
65°	0	35	65
70°	0	0	43
75°	0	0	0
80°	0	0	0
85°	0	0	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 1824 cd/sqm



TEST NUMBER: P1058383

CATALOG NUMBER: S122RDRP-H485D850-X4F0-XX-UDD-BVL-B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	32.6	9.8
10°-20°	82.3	24.6
20°-30°	95.9	28.7
30°-40°	76.9	23.0
40°-50°	38.2	11.4
50°-60°	7.5	2.3
60°-70°	0.7	0.2
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	210.8	63.1
0°-40°	287.7	86.1
0°-60°	333.4	99.8
0°-90°	334.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	334.1	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	355	355	355	355	355	
5°	352	352	346	347	348	33
15°	314	308	292	285	280	87
25°	230	219	206	201	195	106
35°	149	134	119	113	107	93
45°	70	62	50	34	26	54
55°	4	9	8	4	5	9
65°	0	0	1	1	2	0
75°	0	0	0	0	0	0
85°	0	0	0	0	0	0
90°	0	0	0	0	0	0



TEST NUMBER: P1058383

CATALOG NUMBER: S122RDRP-H485D850-X4F0-XX-UDD-BVL-B

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	355.3	355.3	355.3	355.3	355.3
2.5°	353.8	355.3	351.5	355.3	356.1
5°	351.5	351.5	346.3	347.0	347.8
7.5°	347.8	346.3	337.3	335.8	334.3
10°	340.3	337.3	326.0	320.0	317.7
12.5°	329.8	325.3	310.2	303.5	299.7
15°	314.0	308.0	292.2	284.7	280.2
17.5°	293.7	288.4	273.4	265.2	260.7
20°	272.7	265.2	252.4	244.1	238.1
22.5°	252.4	242.6	229.1	223.1	217.1
25°	229.9	218.6	205.8	201.3	195.3
27.5°	211.1	196.8	181.8	178.8	173.5
30°	188.5	175.0	160.7	156.2	150.2
32.5°	169.0	154.0	139.7	134.5	129.2
35°	148.7	133.7	118.7	113.4	106.7
37.5°	129.2	114.9	99.9	91.6	85.6
40°	108.2	96.1	81.9	71.4	63.8
42.5°	89.4	78.9	65.4	51.8	44.3
45°	69.9	61.6	50.3	33.8	25.5
47.5°	51.8	45.8	36.8	19.5	13.5
50°	34.6	32.3	24.0	9.8	8.3
52.5°	18.8	20.3	14.3	6.0	6.8
55°	4.5	9.0	7.5	4.5	5.3
57.5°	0.8	1.5	3.8	3.8	3.8
60°	0.8	0.8	1.5	2.3	3.0
62.5°	0.8	0.0	0.8	1.5	2.3
65°	0.0	0.0	0.8	0.8	1.5
67.5°	0.0	0.0	0.0	0.8	0.8
70°	0.0	0.0	0.0	0.8	0.8
72.5°	0.0	0.0	0.0	0.0	0.8
75°	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0



TEST NUMBER: P1058383
 CATALOG NUMBER: S122RDRP-H485D850-X4F0-XX-UDD-BVL-B

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	6H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	8H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	12H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
4H	2H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	6H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	8H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	12H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
8H	4H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	6H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	8H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	12H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
12H	4H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	6H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	8H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00