

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P996370

Luminaire Tested: S123RDRP-B1165DB35-4F0-XX-W2A-A

Issue Date: 5/2/2025

**Test Information**

Test Method: LM-79-2019  
Report Number: P996370  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1802-639-30)  
Test Lab: INNOVATION CENTER  
Issue Date: 5/2/2025  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: NEO-RAY  
Catalog Number: S123RDRP-B1165DB35-4F0-XX-W2A-A  
Description: Define 3 Regressed Direct Perimeter with 3500K BioUP LEDs {m-DER=0.721} {m-EER=0.792}  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 4602.0 lumens  
Efficiency: N/A  
Efficacy: 75.1 lumens/watt  
Spacing Criteria (0/90/45): 1.22 / 1.2 / 1.34  
Luminous Opening: Rectangular (W 0.25' x L: 4' x H: 0')  
CIE Type: Direct

Input Watts (W): 61.3  
Input Voltage (V):  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P996370

CATALOG NUMBER: S123RDRP-B1165DB35-4F0-XX-W2A-A

### Luminous Intensity Polar Plot



TEST NUMBER: P996370

CATALOG NUMBER: S123RDRP-B1165DB35-4F0-XX-W2A-A

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |     |     |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|-----|-----|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |     |     |     |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |     |     | 0   |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  | 30  | 10  | 0   |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |     |     |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 | 102 | 102 | 100 |
| 1   | 110 | 106 | 102 | 99  | 108 | 104 | 100 | 97  | 100 | 97  | 94  |  | 96  | 93  | 91  |  | 92  | 90  | 89  | 87  |
| 2   | 101 | 94  | 88  | 83  | 99  | 92  | 87  | 82  | 89  | 84  | 80  |  | 86  | 82  | 78  |  | 83  | 79  | 77  | 74  |
| 3   | 93  | 84  | 76  | 71  | 91  | 82  | 75  | 70  | 79  | 74  | 69  |  | 77  | 72  | 68  |  | 74  | 70  | 66  | 64  |
| 4   | 86  | 75  | 67  | 61  | 84  | 74  | 66  | 61  | 71  | 65  | 60  |  | 69  | 64  | 59  |  | 67  | 62  | 58  | 56  |
| 5   | 80  | 68  | 60  | 53  | 78  | 67  | 59  | 53  | 65  | 58  | 53  |  | 63  | 57  | 52  |  | 61  | 56  | 52  | 50  |
| 6   | 74  | 62  | 53  | 47  | 72  | 61  | 53  | 47  | 59  | 52  | 47  |  | 57  | 51  | 46  |  | 56  | 50  | 46  | 44  |
| 7   | 69  | 56  | 48  | 42  | 67  | 55  | 48  | 42  | 54  | 47  | 42  |  | 53  | 46  | 42  |  | 51  | 46  | 41  | 39  |
| 8   | 64  | 52  | 44  | 38  | 63  | 51  | 43  | 38  | 50  | 43  | 38  |  | 48  | 42  | 38  |  | 47  | 42  | 37  | 36  |
| 9   | 60  | 48  | 40  | 35  | 59  | 47  | 40  | 35  | 46  | 39  | 34  |  | 45  | 39  | 34  |  | 44  | 38  | 34  | 32  |
| 10  | 57  | 44  | 37  | 32  | 55  | 44  | 36  | 32  | 43  | 36  | 31  |  | 42  | 36  | 31  |  | 41  | 35  | 31  | 29  |

**AVERAGE LUMINANCE (cd/sqm):**

|     | 0°    | 90°   | 180°  | 270°  |
|-----|-------|-------|-------|-------|
| 0°  | 19894 | 19894 | 19894 | 19894 |
| 5°  | 19953 | 23714 | 20003 | 17593 |
| 10° | 19819 | 29608 | 19907 | 15894 |
| 15° | 19661 | 34755 | 19661 | 14495 |
| 20° | 19303 | 38788 | 19412 | 13304 |
| 25° | 19056 | 38168 | 19018 | 12573 |
| 30° | 18762 | 27435 | 18723 | 11820 |
| 35° | 18402 | 18318 | 18318 | 11332 |
| 40° | 17942 | 13496 | 17854 | 10828 |
| 45° | 17101 | 11321 | 17078 | 10333 |
| 50° | 16057 | 9989  | 16004 | 9646  |
| 55° | 14876 | 8760  | 14758 | 8700  |
| 60° | 13728 | 7802  | 13591 | 7972  |
| 65° | 12373 | 6851  | 12452 | 7414  |
| 70° | 11154 | 5378  | 11453 | 6773  |
| 75° | 9674  | 4737  | 10069 | 6184  |
| 80° | 8046  | 4122  | 8728  | 6081  |
| 85° | 6447  | 3322  | 7040  | 6447  |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 30°

Vertical Angle: 45°

Luminance: 32445 cd/sqm

TEST NUMBER: P996370

CATALOG NUMBER: S123RDRP-B1165DB35-4F0-XX-W2A-A

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 181.5  | 3.9       |
| 10°-20°   | 568.1  | 12.3      |
| 20°-30°   | 894.8  | 19.4      |
| 30°-40°   | 930.5  | 20.2      |
| 40°-50°   | 796.0  | 17.3      |
| 50°-60°   | 606.9  | 13.2      |
| 60°-70°   | 388.8  | 8.4       |
| 70°-80°   | 186.3  | 4.0       |
| 80°-90°   | 49.0   | 1.1       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 1644.5 | 35.7      |
| 0°-40°    | 2574.9 | 56.0      |
| 0°-60°    | 3977.9 | 86.4      |
| 0°-90°    | 4602.0 | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 4602.0 | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°   | 90°  | 180° | 270° | 360° | Flux |
|-----|------|------|------|------|------|------|
| 0°  | 1848 | 1848 | 1848 | 1848 | 1848 |      |
| 5°  | 1847 | 2195 | 1851 | 1628 | 1847 | 175  |
| 15° | 1764 | 3119 | 1764 | 1301 | 1764 | 496  |
| 25° | 1604 | 3214 | 1601 | 1059 | 1604 | 739  |
| 35° | 1400 | 1394 | 1394 | 862  | 1400 | 876  |
| 45° | 1123 | 744  | 1122 | 679  | 1123 | 865  |
| 55° | 793  | 467  | 786  | 464  | 793  | 710  |
| 65° | 486  | 269  | 489  | 291  | 486  | 485  |
| 75° | 233  | 114  | 242  | 149  | 233  | 251  |
| 85° | 52   | 27   | 57   | 52   | 52   | 61   |
| 90° | 0    | 0    | 0    | 0    | 0    |      |

TEST NUMBER: P996370

CATALOG NUMBER: S123RDRP-B1165DB35-4F0-XX-W2A-A

**CANDELA DISTRIBUTION (FULL):**

|       | 0°     | 5°     | 10°    | 15°    | 20°    | 22.5°  | 25°    | 30°    | 35°    | 40°    | 45°    |
|-------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°    | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 |
| 2.5°  | 1852.9 | 1865.6 | 1875.1 | 1881.4 | 1897.2 | 1906.7 | 1914.6 | 1928.9 | 1928.9 | 1932.0 | 1938.3 |
| 5°    | 1846.6 | 1873.5 | 1892.5 | 1917.8 | 1951.0 | 1966.8 | 1989.0 | 2008.0 | 2034.9 | 2049.1 | 2063.3 |
| 7.5°  | 1832.3 | 1870.3 | 1909.9 | 1947.8 | 1996.9 | 2028.5 | 2050.7 | 2099.7 | 2134.6 | 2177.3 | 2210.5 |
| 10°   | 1813.3 | 1865.6 | 1916.2 | 1974.7 | 2041.2 | 2088.7 | 2121.9 | 2186.8 | 2253.2 | 2313.4 | 2364.0 |
| 12.5° | 1789.6 | 1852.9 | 1925.7 | 1996.9 | 2090.2 | 2137.7 | 2191.5 | 2272.2 | 2367.2 | 2443.1 | 2511.1 |
| 15°   | 1764.3 | 1837.1 | 1919.4 | 2006.4 | 2123.5 | 2189.9 | 2267.5 | 2365.6 | 2471.6 | 2580.8 | 2674.1 |
| 17.5° | 1724.7 | 1816.5 | 1908.3 | 2034.9 | 2172.5 | 2212.1 | 2278.5 | 2413.0 | 2544.4 | 2642.5 | 2756.4 |
| 20°   | 1685.2 | 1788.0 | 1903.5 | 2017.5 | 2166.2 | 2258.0 | 2319.7 | 2462.1 | 2602.9 | 2721.6 | 2830.8 |
| 22.5° | 1648.8 | 1756.4 | 1876.6 | 2020.6 | 2159.9 | 2251.6 | 2329.2 | 2477.9 | 2640.9 | 2773.8 | 2908.3 |
| 25°   | 1604.5 | 1721.6 | 1854.5 | 1990.6 | 2159.9 | 2229.5 | 2314.9 | 2487.4 | 2659.9 | 2813.4 | 2979.5 |
| 27.5° | 1557.0 | 1675.7 | 1807.0 | 1946.3 | 2101.3 | 2204.2 | 2288.0 | 2473.2 | 2683.6 | 2848.2 | 3019.1 |
| 30°   | 1509.5 | 1631.4 | 1758.0 | 1883.0 | 2057.0 | 2155.1 | 2251.6 | 2455.8 | 2696.3 | 2884.6 | 3015.9 |
| 32.5° | 1463.6 | 1566.5 | 1691.5 | 1813.3 | 1985.8 | 2093.4 | 2202.6 | 2438.4 | 2701.0 | 2859.3 | 2922.5 |
| 35°   | 1400.4 | 1508.0 | 1609.2 | 1739.0 | 1913.0 | 2019.0 | 2147.2 | 2436.8 | 2680.5 | 2778.6 | 2746.9 |
| 37.5° | 1341.8 | 1432.0 | 1528.5 | 1644.0 | 1822.8 | 1960.5 | 2093.4 | 2395.6 | 2612.4 | 2618.7 | 2439.9 |
| 40°   | 1276.9 | 1351.3 | 1432.0 | 1553.8 | 1746.9 | 1883.0 | 2027.0 | 2332.3 | 2489.0 | 2395.6 | 2080.8 |
| 42.5° | 1202.6 | 1269.0 | 1332.3 | 1451.0 | 1661.4 | 1813.3 | 1968.4 | 2253.2 | 2310.2 | 2095.0 | 1767.5 |
| 45°   | 1123.4 | 1177.2 | 1235.8 | 1360.8 | 1571.2 | 1721.6 | 1876.6 | 2131.4 | 2072.8 | 1769.0 | 1457.3 |
| 47.5° | 1041.2 | 1087.1 | 1144.0 | 1257.9 | 1474.7 | 1628.2 | 1775.4 | 1957.3 | 1808.6 | 1482.6 | 1221.6 |
| 50°   | 958.9  | 995.3  | 1050.7 | 1167.8 | 1376.6 | 1515.9 | 1651.9 | 1770.6 | 1561.8 | 1272.2 | 1009.5 |
| 52.5° | 878.2  | 906.7  | 963.6  | 1063.3 | 1265.9 | 1398.8 | 1496.9 | 1542.8 | 1330.7 | 1050.7 | 876.6  |
| 55°   | 792.7  | 824.4  | 862.4  | 963.6  | 1164.6 | 1262.7 | 1327.6 | 1326.0 | 1107.6 | 890.8  | 724.7  |
| 57.5° | 710.5  | 738.9  | 772.2  | 873.4  | 1036.4 | 1102.9 | 1158.3 | 1131.4 | 924.1  | 729.5  | 621.9  |
| 60°   | 637.7  | 653.5  | 689.9  | 775.3  | 898.8  | 955.7  | 987.4  | 941.5  | 754.8  | 615.5  | 514.3  |
| 62.5° | 558.6  | 574.4  | 604.4  | 685.1  | 761.1  | 791.2  | 818.1  | 759.5  | 623.4  | 501.6  | 439.9  |
| 65°   | 485.8  | 506.3  | 525.3  | 590.2  | 631.3  | 667.7  | 664.6  | 615.5  | 487.4  | 408.2  | 357.6  |
| 67.5° | 422.5  | 430.4  | 446.2  | 485.8  | 504.8  | 531.7  | 533.2  | 477.9  | 392.4  | 332.3  | 302.2  |
| 70°   | 354.4  | 362.4  | 373.4  | 392.4  | 405.1  | 411.4  | 408.2  | 359.2  | 295.9  | 259.5  | 232.6  |
| 72.5° | 295.9  | 294.3  | 302.2  | 302.2  | 314.9  | 313.3  | 303.8  | 265.8  | 224.7  | 194.6  | 178.8  |
| 75°   | 232.6  | 234.2  | 235.8  | 232.6  | 227.9  | 221.5  | 213.6  | 185.1  | 158.2  | 144.0  | 129.8  |
| 77.5° | 182.0  | 178.8  | 180.4  | 169.3  | 163.0  | 156.6  | 145.6  | 131.3  | 109.2  | 106.0  | 99.7   |
| 80°   | 129.8  | 128.2  | 126.6  | 121.8  | 107.6  | 101.3  | 93.4   | 85.4   | 80.7   | 77.5   | 76.0   |
| 82.5° | 87.0   | 87.0   | 83.9   | 74.4   | 66.5   | 61.7   | 60.1   | 57.0   | 52.2   | 52.2   | 50.6   |
| 85°   | 52.2   | 50.6   | 47.5   | 38.0   | 33.2   | 33.2   | 33.2   | 33.2   | 30.1   | 30.1   | 28.5   |
| 87.5° | 20.6   | 19.0   | 14.2   | 14.2   | 12.7   | 12.7   | 12.7   | 11.1   | 11.1   | 9.5    | 9.5    |
| 90°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |

TEST NUMBER: P996370

CATALOG NUMBER: S123RDRP-B1165DB35-4F0-XX-W2A-A

**CANDELA DISTRIBUTION (continued):**

|       | 50°    | 55°    | 60°    | 65°    | 67.5°  | 70°    | 75°    | 80°    | 85°    | 90°    | 95°    |
|-------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°    | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 |
| 2.5°  | 1951.0 | 1951.0 | 1965.2 | 1979.5 | 1971.6 | 1976.3 | 1993.7 | 1987.4 | 2000.1 | 1998.5 | 2003.2 |
| 5°    | 2098.2 | 2115.6 | 2129.8 | 2159.9 | 2164.6 | 2159.9 | 2189.9 | 2197.8 | 2212.1 | 2194.7 | 2202.6 |
| 7.5°  | 2264.3 | 2300.7 | 2335.5 | 2379.8 | 2394.1 | 2397.2 | 2413.0 | 2435.2 | 2454.2 | 2419.4 | 2436.8 |
| 10°   | 2425.7 | 2481.1 | 2552.3 | 2591.8 | 2626.7 | 2639.3 | 2652.0 | 2666.2 | 2688.4 | 2708.9 | 2693.1 |
| 12.5° | 2599.8 | 2680.5 | 2748.5 | 2819.7 | 2862.4 | 2857.7 | 2894.1 | 2903.6 | 2921.0 | 2925.7 | 2932.0 |
| 15°   | 2742.2 | 2856.1 | 2898.8 | 3004.8 | 3014.3 | 3046.0 | 3087.1 | 3123.5 | 3128.3 | 3118.8 | 3118.8 |
| 17.5° | 2878.2 | 2976.3 | 3052.3 | 3137.7 | 3155.1 | 3182.0 | 3234.3 | 3251.7 | 3258.0 | 3256.4 | 3256.4 |
| 20°   | 2989.0 | 3053.9 | 3182.0 | 3253.3 | 3281.7 | 3316.5 | 3352.9 | 3375.1 | 3379.8 | 3386.2 | 3376.7 |
| 22.5° | 3061.8 | 3159.9 | 3264.3 | 3322.9 | 3346.6 | 3359.3 | 3383.0 | 3389.3 | 3381.4 | 3383.0 | 3384.6 |
| 25°   | 3118.8 | 3215.3 | 3278.6 | 3294.4 | 3292.8 | 3277.0 | 3259.6 | 3229.5 | 3226.4 | 3213.7 | 3188.4 |
| 27.5° | 3134.6 | 3171.0 | 3163.1 | 3098.2 | 3033.3 | 3027.0 | 2922.5 | 2865.6 | 2800.7 | 2810.2 | 2773.8 |
| 30°   | 3049.1 | 3001.7 | 2889.3 | 2724.8 | 2656.7 | 2546.0 | 2428.9 | 2307.0 | 2259.6 | 2207.3 | 2303.9 |
| 32.5° | 2840.3 | 2671.0 | 2471.6 | 2258.0 | 2144.0 | 2045.9 | 1920.9 | 1832.3 | 1781.7 | 1739.0 | 1821.3 |
| 35°   | 2525.4 | 2261.1 | 1996.9 | 1794.4 | 1701.0 | 1612.4 | 1495.3 | 1451.0 | 1387.7 | 1394.0 | 1401.9 |
| 37.5° | 2120.3 | 1829.2 | 1629.8 | 1430.4 | 1368.7 | 1332.3 | 1246.9 | 1178.8 | 1156.7 | 1150.3 | 1150.3 |
| 40°   | 1740.6 | 1501.6 | 1324.4 | 1167.8 | 1120.3 | 1090.2 | 1022.2 | 990.5  | 966.8  | 960.5  | 968.4  |
| 42.5° | 1439.9 | 1235.8 | 1098.1 | 993.7  | 960.5  | 922.5  | 894.0  | 854.5  | 849.7  | 838.6  | 852.9  |
| 45°   | 1208.9 | 1031.7 | 928.8  | 852.9  | 824.4  | 810.1  | 778.5  | 754.8  | 745.3  | 743.7  | 754.8  |
| 47.5° | 1025.3 | 887.7  | 797.5  | 750.0  | 727.9  | 713.6  | 686.7  | 677.2  | 667.7  | 670.9  | 666.2  |
| 50°   | 860.8  | 757.9  | 699.4  | 656.7  | 642.4  | 628.2  | 610.8  | 601.3  | 596.5  | 596.5  | 595.0  |
| 52.5° | 738.9  | 653.5  | 615.5  | 576.0  | 569.6  | 561.7  | 542.7  | 536.4  | 528.5  | 526.9  | 533.2  |
| 55°   | 632.9  | 574.4  | 536.4  | 512.7  | 506.3  | 490.5  | 482.6  | 474.7  | 469.9  | 466.8  | 468.4  |
| 57.5° | 541.2  | 496.8  | 471.5  | 451.0  | 439.9  | 433.6  | 419.3  | 417.7  | 414.6  | 414.6  | 413.0  |
| 60°   | 465.2  | 433.6  | 403.5  | 390.8  | 382.9  | 375.0  | 373.4  | 363.9  | 359.2  | 362.4  | 360.8  |
| 62.5° | 394.0  | 368.7  | 351.3  | 337.0  | 332.3  | 326.0  | 321.2  | 318.0  | 313.3  | 314.9  | 314.9  |
| 65°   | 329.1  | 308.6  | 295.9  | 283.2  | 281.7  | 275.3  | 273.7  | 270.6  | 270.6  | 269.0  | 272.2  |
| 67.5° | 270.6  | 256.3  | 245.3  | 237.3  | 232.6  | 234.2  | 227.9  | 223.1  | 223.1  | 221.5  | 226.3  |
| 70°   | 215.2  | 207.3  | 196.2  | 186.7  | 180.4  | 180.4  | 172.5  | 170.9  | 170.9  | 170.9  | 169.3  |
| 72.5° | 166.1  | 151.9  | 147.2  | 144.0  | 144.0  | 144.0  | 140.8  | 140.8  | 139.2  | 140.8  | 139.2  |
| 75°   | 123.4  | 121.8  | 118.7  | 117.1  | 117.1  | 115.5  | 113.9  | 113.9  | 113.9  | 113.9  | 113.9  |
| 77.5° | 96.5   | 96.5   | 93.4   | 91.8   | 91.8   | 91.8   | 90.2   | 90.2   | 88.6   | 88.6   | 88.6   |
| 80°   | 71.2   | 71.2   | 68.0   | 68.0   | 68.0   | 66.5   | 66.5   | 66.5   | 68.0   | 66.5   | 66.5   |
| 82.5° | 49.1   | 49.1   | 47.5   | 49.1   | 47.5   | 45.9   | 45.9   | 45.9   | 44.3   | 45.9   | 45.9   |
| 85°   | 28.5   | 28.5   | 26.9   | 25.3   | 26.9   | 26.9   | 25.3   | 26.9   | 25.3   | 26.9   | 25.3   |
| 87.5° | 11.1   | 9.5    | 9.5    | 9.5    | 7.9    | 9.5    | 7.9    | 7.9    | 9.5    | 7.9    | 9.5    |
| 90°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |

TEST NUMBER: P996370

CATALOG NUMBER: S123RDRP-B1165DB35-4F0-XX-W2A-A

**CANDELA DISTRIBUTION (continued):**

|       | 100°   | 105°   | 110°   | 112.5° | 115°   | 120°   | 125°   | 130°   | 135°   | 140°   | 145°   |
|-------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°    | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 |
| 2.5°  | 1995.3 | 1985.8 | 1979.5 | 1974.7 | 1970.0 | 1984.2 | 1965.2 | 1944.7 | 1930.4 | 1920.9 | 1917.8 |
| 5°    | 2204.2 | 2183.6 | 2166.2 | 2152.0 | 2155.1 | 2155.1 | 2121.9 | 2085.5 | 2053.9 | 2036.4 | 2017.5 |
| 7.5°  | 2446.3 | 2424.1 | 2389.3 | 2381.4 | 2375.1 | 2335.5 | 2302.3 | 2235.8 | 2196.3 | 2156.7 | 2121.9 |
| 10°   | 2686.8 | 2658.3 | 2625.1 | 2614.0 | 2598.2 | 2549.1 | 2498.5 | 2413.0 | 2364.0 | 2291.2 | 2245.3 |
| 12.5° | 2911.5 | 2876.7 | 2843.4 | 2835.5 | 2811.8 | 2769.1 | 2682.0 | 2593.4 | 2509.6 | 2432.0 | 2351.3 |
| 15°   | 3099.8 | 3090.3 | 3039.6 | 3008.0 | 2955.8 | 2897.2 | 2878.2 | 2758.0 | 2652.0 | 2571.3 | 2425.7 |
| 17.5° | 3258.0 | 3213.7 | 3166.2 | 3145.7 | 3125.1 | 3057.0 | 2989.0 | 2865.6 | 2751.7 | 2633.0 | 2539.6 |
| 20°   | 3384.6 | 3335.5 | 3302.3 | 3272.2 | 3262.7 | 3185.2 | 3077.6 | 2968.4 | 2843.4 | 2710.5 | 2588.7 |
| 22.5° | 3390.9 | 3384.6 | 3362.4 | 3345.0 | 3326.0 | 3275.4 | 3190.0 | 3053.9 | 2921.0 | 2775.4 | 2615.6 |
| 25°   | 3259.6 | 3250.1 | 3313.4 | 3297.6 | 3310.2 | 3291.2 | 3245.3 | 3131.4 | 2976.3 | 2805.5 | 2644.1 |
| 27.5° | 2864.0 | 2960.5 | 3060.2 | 3095.0 | 3118.8 | 3186.8 | 3208.9 | 3145.7 | 3020.7 | 2838.7 | 2658.3 |
| 30°   | 2326.0 | 2454.2 | 2615.6 | 2702.6 | 2769.1 | 2895.6 | 3060.2 | 3080.8 | 3022.2 | 2876.7 | 2655.1 |
| 32.5° | 1826.0 | 1943.1 | 2072.8 | 2175.7 | 2264.3 | 2523.8 | 2745.3 | 2905.1 | 2933.6 | 2857.7 | 2663.0 |
| 35°   | 1471.6 | 1522.2 | 1645.6 | 1743.7 | 1864.0 | 2085.5 | 2346.6 | 2604.5 | 2778.6 | 2788.1 | 2639.3 |
| 37.5° | 1213.6 | 1240.5 | 1348.1 | 1403.5 | 1474.7 | 1669.3 | 1913.0 | 2250.1 | 2520.6 | 2648.8 | 2572.9 |
| 40°   | 1004.8 | 1066.5 | 1128.2 | 1159.8 | 1210.5 | 1345.0 | 1579.2 | 1843.4 | 2178.9 | 2416.2 | 2470.0 |
| 42.5° | 871.9  | 898.8  | 938.3  | 982.6  | 1014.3 | 1131.4 | 1288.0 | 1530.1 | 1832.3 | 2163.0 | 2311.8 |
| 45°   | 769.0  | 778.5  | 819.6  | 848.1  | 881.4  | 963.6  | 1074.4 | 1276.9 | 1542.8 | 1868.7 | 2121.9 |
| 47.5° | 683.6  | 702.6  | 724.7  | 742.1  | 764.3  | 827.6  | 922.5  | 1069.6 | 1303.8 | 1595.0 | 1867.1 |
| 50°   | 607.6  | 618.7  | 647.2  | 655.1  | 670.9  | 715.2  | 788.0  | 900.3  | 1093.4 | 1326.0 | 1607.6 |
| 52.5° | 536.4  | 557.0  | 568.1  | 579.1  | 593.4  | 629.8  | 677.2  | 769.0  | 914.6  | 1132.9 | 1371.9 |
| 55°   | 481.0  | 487.4  | 503.2  | 512.7  | 523.7  | 549.1  | 590.2  | 658.2  | 772.2  | 946.2  | 1172.5 |
| 57.5° | 427.2  | 427.2  | 443.1  | 451.0  | 462.0  | 481.0  | 517.4  | 569.6  | 651.9  | 781.7  | 989.0  |
| 60°   | 370.3  | 371.8  | 384.5  | 394.0  | 397.2  | 416.2  | 446.2  | 487.4  | 550.6  | 645.6  | 814.9  |
| 62.5° | 319.6  | 327.5  | 333.9  | 337.0  | 348.1  | 359.2  | 384.5  | 413.0  | 457.3  | 541.2  | 661.4  |
| 65°   | 276.9  | 278.5  | 283.2  | 286.4  | 291.1  | 303.8  | 322.8  | 341.8  | 379.8  | 441.5  | 539.6  |
| 67.5° | 227.9  | 234.2  | 240.5  | 240.5  | 245.3  | 251.6  | 270.6  | 286.4  | 314.9  | 351.3  | 417.7  |
| 70°   | 170.9  | 174.1  | 183.5  | 188.3  | 194.6  | 205.7  | 215.2  | 224.7  | 246.8  | 273.7  | 324.4  |
| 72.5° | 142.4  | 142.4  | 145.6  | 147.2  | 147.2  | 155.1  | 169.3  | 178.8  | 189.9  | 208.9  | 243.7  |
| 75°   | 113.9  | 113.9  | 118.7  | 117.1  | 120.3  | 123.4  | 125.0  | 131.3  | 137.7  | 151.9  | 172.5  |
| 77.5° | 90.2   | 91.8   | 91.8   | 93.4   | 93.4   | 94.9   | 96.5   | 99.7   | 102.9  | 110.8  | 120.3  |
| 80°   | 66.5   | 68.0   | 68.0   | 69.6   | 69.6   | 71.2   | 72.8   | 74.4   | 77.5   | 80.7   | 85.4   |
| 82.5° | 45.9   | 47.5   | 47.5   | 49.1   | 47.5   | 49.1   | 50.6   | 50.6   | 52.2   | 55.4   | 57.0   |
| 85°   | 26.9   | 26.9   | 28.5   | 26.9   | 26.9   | 26.9   | 28.5   | 28.5   | 30.1   | 34.8   | 34.8   |
| 87.5° | 7.9    | 9.5    | 7.9    | 9.5    | 9.5    | 9.5    | 9.5    | 11.1   | 11.1   | 12.7   | 14.2   |
| 90°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |

TEST NUMBER: P996370

CATALOG NUMBER: S123RDRP-B1165DB35-4F0-XX-W2A-A

**CANDELA DISTRIBUTION (continued):**

|       | 150°   | 155°   | 157.5° | 160°   | 165°   | 170°   | 175°   | 180°   | 185°   | 190°   | 195°   |
|-------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°    | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 |
| 2.5°  | 1913.0 | 1905.1 | 1897.2 | 1897.2 | 1879.8 | 1864.0 | 1856.1 | 1859.2 | 1849.7 | 1837.1 | 1824.4 |
| 5°    | 1996.9 | 1965.2 | 1958.9 | 1941.5 | 1917.8 | 1884.5 | 1867.1 | 1851.3 | 1832.3 | 1807.0 | 1783.3 |
| 7.5°  | 2074.4 | 2033.3 | 2011.1 | 1993.7 | 1947.8 | 1902.0 | 1864.0 | 1838.7 | 1805.4 | 1767.5 | 1739.0 |
| 10°   | 2175.7 | 2099.7 | 2076.0 | 2036.4 | 1971.6 | 1906.7 | 1862.4 | 1821.3 | 1775.4 | 1731.1 | 1693.1 |
| 12.5° | 2256.4 | 2169.4 | 2125.1 | 2085.5 | 2001.6 | 1919.4 | 1845.0 | 1794.4 | 1739.0 | 1689.9 | 1640.9 |
| 15°   | 2348.2 | 2250.1 | 2172.5 | 2125.1 | 2019.0 | 1919.4 | 1835.5 | 1764.3 | 1702.6 | 1642.4 | 1599.7 |
| 17.5° | 2392.5 | 2269.0 | 2234.2 | 2166.2 | 2012.7 | 1913.0 | 1810.2 | 1734.2 | 1659.9 | 1590.2 | 1539.6 |
| 20°   | 2462.1 | 2318.1 | 2231.1 | 2185.2 | 2049.1 | 1902.0 | 1781.7 | 1694.7 | 1617.1 | 1542.8 | 1489.0 |
| 22.5° | 2466.8 | 2310.2 | 2253.2 | 2166.2 | 1998.5 | 1868.7 | 1756.4 | 1650.4 | 1560.2 | 1490.5 | 1435.2 |
| 25°   | 2455.8 | 2295.9 | 2216.8 | 2147.2 | 2008.0 | 1849.7 | 1705.7 | 1601.3 | 1512.7 | 1432.0 | 1367.1 |
| 27.5° | 2451.0 | 2254.8 | 2180.4 | 2110.8 | 1954.2 | 1794.4 | 1675.7 | 1557.0 | 1455.7 | 1384.5 | 1318.1 |
| 30°   | 2444.7 | 2210.5 | 2120.3 | 2039.6 | 1895.6 | 1751.6 | 1609.2 | 1506.4 | 1409.8 | 1319.7 | 1253.2 |
| 32.5° | 2403.5 | 2150.4 | 2058.6 | 1973.2 | 1818.1 | 1674.1 | 1561.8 | 1452.6 | 1348.1 | 1264.3 | 1204.1 |
| 35°   | 2390.9 | 2095.0 | 1974.7 | 1883.0 | 1731.1 | 1602.9 | 1484.2 | 1394.0 | 1295.9 | 1212.1 | 1140.9 |
| 37.5° | 2354.5 | 2038.0 | 1908.3 | 1791.2 | 1633.0 | 1511.1 | 1424.1 | 1333.9 | 1239.0 | 1148.8 | 1091.8 |
| 40°   | 2291.2 | 1971.6 | 1824.4 | 1704.2 | 1541.2 | 1417.8 | 1337.1 | 1270.6 | 1177.2 | 1096.5 | 1026.9 |
| 42.5° | 2197.8 | 1903.5 | 1745.3 | 1618.7 | 1438.3 | 1322.8 | 1256.4 | 1193.1 | 1114.0 | 1030.1 | 973.1  |
| 45°   | 2090.2 | 1813.3 | 1666.2 | 1525.4 | 1341.8 | 1229.5 | 1159.8 | 1121.9 | 1049.1 | 977.9  | 911.4  |
| 47.5° | 1943.1 | 1720.0 | 1574.4 | 1428.8 | 1242.1 | 1132.9 | 1077.6 | 1039.6 | 989.0  | 911.4  | 857.6  |
| 50°   | 1758.0 | 1599.7 | 1462.1 | 1332.3 | 1144.0 | 1039.6 | 984.2  | 955.7  | 913.0  | 857.6  | 805.4  |
| 52.5° | 1552.3 | 1460.5 | 1346.6 | 1226.3 | 1044.3 | 946.2  | 895.6  | 873.4  | 841.8  | 789.6  | 745.3  |
| 55°   | 1345.0 | 1305.4 | 1227.9 | 1109.2 | 939.9  | 859.2  | 814.9  | 786.4  | 762.7  | 724.7  | 686.7  |
| 57.5° | 1159.8 | 1140.9 | 1087.1 | 995.3  | 852.9  | 769.0  | 731.0  | 712.0  | 693.1  | 664.6  | 626.6  |
| 60°   | 968.4  | 989.0  | 933.6  | 887.7  | 757.9  | 685.1  | 651.9  | 631.3  | 621.9  | 596.5  | 572.8  |
| 62.5° | 802.2  | 821.2  | 789.6  | 754.8  | 663.0  | 598.1  | 577.5  | 558.6  | 552.2  | 530.1  | 506.3  |
| 65°   | 651.9  | 675.7  | 651.9  | 632.9  | 577.5  | 523.7  | 498.4  | 488.9  | 482.6  | 468.4  | 449.4  |
| 67.5° | 519.0  | 542.7  | 531.7  | 507.9  | 490.5  | 446.2  | 432.0  | 422.5  | 419.3  | 408.2  | 392.4  |
| 70°   | 390.8  | 424.1  | 427.2  | 413.0  | 397.2  | 376.6  | 367.1  | 363.9  | 356.0  | 346.5  | 337.0  |
| 72.5° | 281.7  | 319.6  | 321.2  | 321.2  | 311.7  | 311.7  | 302.2  | 297.5  | 297.5  | 288.0  | 276.9  |
| 75°   | 207.3  | 232.6  | 235.8  | 238.9  | 243.7  | 248.4  | 242.1  | 242.1  | 240.5  | 231.0  | 226.3  |
| 77.5° | 137.7  | 159.8  | 167.7  | 178.8  | 185.1  | 185.1  | 188.3  | 191.5  | 188.3  | 183.5  | 180.4  |
| 80°   | 88.6   | 104.4  | 113.9  | 120.3  | 129.8  | 134.5  | 139.2  | 140.8  | 137.7  | 136.1  | 131.3  |
| 82.5° | 58.5   | 63.3   | 68.0   | 76.0   | 87.0   | 94.9   | 94.9   | 93.4   | 96.5   | 94.9   | 93.4   |
| 85°   | 33.2   | 36.4   | 38.0   | 39.6   | 45.9   | 53.8   | 55.4   | 57.0   | 60.1   | 57.0   | 53.8   |
| 87.5° | 12.7   | 14.2   | 14.2   | 14.2   | 17.4   | 19.0   | 23.7   | 30.1   | 28.5   | 25.3   | 25.3   |
| 90°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |

TEST NUMBER: P996370

CATALOG NUMBER: S123RDRP-B1165DB35-4F0-XX-W2A-A

**CANDELA DISTRIBUTION (continued):**

|       | 200°   | 202.5° | 205°   | 210°   | 215°   | 220°   | 225°   | 230°   | 235°   | 240°   | 245°   |
|-------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°    | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 |
| 2.5°  | 1824.4 | 1816.5 | 1813.3 | 1805.4 | 1786.4 | 1773.8 | 1759.5 | 1750.0 | 1751.6 | 1743.7 | 1748.5 |
| 5°    | 1767.5 | 1765.9 | 1754.8 | 1739.0 | 1712.1 | 1697.8 | 1672.5 | 1659.9 | 1653.5 | 1655.1 | 1645.6 |
| 7.5°  | 1720.0 | 1705.7 | 1697.8 | 1672.5 | 1647.2 | 1617.1 | 1596.6 | 1585.5 | 1576.0 | 1566.5 | 1560.2 |
| 10°   | 1666.2 | 1653.5 | 1640.9 | 1614.0 | 1579.2 | 1550.7 | 1522.2 | 1511.1 | 1496.9 | 1490.5 | 1485.8 |
| 12.5° | 1609.2 | 1601.3 | 1585.5 | 1553.8 | 1514.3 | 1487.4 | 1454.2 | 1447.8 | 1428.8 | 1416.2 | 1413.0 |
| 15°   | 1557.0 | 1552.3 | 1523.8 | 1487.4 | 1447.8 | 1420.9 | 1392.4 | 1373.5 | 1341.8 | 1348.1 | 1337.1 |
| 17.5° | 1501.6 | 1481.1 | 1463.6 | 1414.6 | 1395.6 | 1354.5 | 1321.2 | 1311.7 | 1289.6 | 1275.4 | 1261.1 |
| 20°   | 1439.9 | 1427.3 | 1405.1 | 1373.5 | 1327.6 | 1280.1 | 1254.8 | 1239.0 | 1226.3 | 1204.1 | 1197.8 |
| 22.5° | 1381.4 | 1365.5 | 1346.6 | 1305.4 | 1265.9 | 1226.3 | 1191.5 | 1177.2 | 1161.4 | 1145.6 | 1136.1 |
| 25°   | 1335.5 | 1311.7 | 1291.2 | 1240.5 | 1201.0 | 1167.8 | 1145.6 | 1121.9 | 1099.7 | 1090.2 | 1087.1 |
| 27.5° | 1264.3 | 1250.0 | 1229.5 | 1182.0 | 1145.6 | 1109.2 | 1088.6 | 1072.8 | 1049.1 | 1038.0 | 1028.5 |
| 30°   | 1218.4 | 1189.9 | 1166.2 | 1128.2 | 1091.8 | 1052.2 | 1033.3 | 1014.3 | 1000.0 | 985.8  | 974.7  |
| 32.5° | 1156.7 | 1134.5 | 1115.5 | 1077.6 | 1041.2 | 1004.8 | 984.2  | 955.7  | 947.8  | 936.7  | 924.1  |
| 35°   | 1096.5 | 1082.3 | 1061.7 | 1020.6 | 981.0  | 955.7  | 933.6  | 906.7  | 897.2  | 889.3  | 878.2  |
| 37.5° | 1039.6 | 1019.0 | 1004.8 | 965.2  | 930.4  | 900.3  | 882.9  | 860.8  | 854.5  | 845.0  | 837.0  |
| 40°   | 990.5  | 970.0  | 955.7  | 916.2  | 879.8  | 848.1  | 837.0  | 814.9  | 805.4  | 794.3  | 789.6  |
| 42.5° | 935.2  | 917.7  | 898.8  | 870.3  | 832.3  | 800.7  | 778.5  | 765.8  | 753.2  | 748.4  | 738.9  |
| 45°   | 876.6  | 860.8  | 846.5  | 814.9  | 775.3  | 753.2  | 734.2  | 716.8  | 707.3  | 699.4  | 693.1  |
| 47.5° | 826.0  | 811.7  | 792.7  | 757.9  | 726.3  | 705.7  | 686.7  | 669.3  | 659.8  | 650.3  | 642.4  |
| 50°   | 767.4  | 759.5  | 738.9  | 705.7  | 675.7  | 651.9  | 634.5  | 618.7  | 612.4  | 601.3  | 588.6  |
| 52.5° | 715.2  | 701.0  | 683.6  | 656.7  | 629.8  | 601.3  | 577.5  | 568.1  | 557.0  | 550.6  | 539.6  |
| 55°   | 653.5  | 644.0  | 625.0  | 601.3  | 572.8  | 549.1  | 531.7  | 519.0  | 504.8  | 498.4  | 484.2  |
| 57.5° | 601.3  | 583.9  | 574.4  | 544.3  | 517.4  | 493.7  | 481.0  | 468.4  | 452.5  | 443.1  | 436.7  |
| 60°   | 544.3  | 528.5  | 514.3  | 488.9  | 469.9  | 444.6  | 425.6  | 414.6  | 403.5  | 390.8  | 384.5  |
| 62.5° | 488.9  | 476.3  | 458.9  | 438.3  | 414.6  | 394.0  | 379.8  | 363.9  | 357.6  | 344.9  | 340.2  |
| 65°   | 428.8  | 419.3  | 405.1  | 381.3  | 362.4  | 344.9  | 330.7  | 318.0  | 311.7  | 307.0  | 303.8  |
| 67.5° | 375.0  | 362.4  | 352.9  | 332.3  | 311.7  | 297.5  | 289.6  | 281.7  | 273.7  | 269.0  | 264.2  |
| 70°   | 319.6  | 310.1  | 300.6  | 281.7  | 267.4  | 254.8  | 248.4  | 242.1  | 237.3  | 232.6  | 227.9  |
| 72.5° | 262.7  | 257.9  | 248.4  | 235.8  | 224.7  | 215.2  | 210.4  | 202.5  | 197.8  | 189.9  | 186.7  |
| 75°   | 216.8  | 208.9  | 204.1  | 193.0  | 183.5  | 175.6  | 169.3  | 159.8  | 153.5  | 150.3  | 148.7  |
| 77.5° | 170.9  | 167.7  | 161.4  | 151.9  | 147.2  | 139.2  | 129.8  | 126.6  | 123.4  | 123.4  | 121.8  |
| 80°   | 128.2  | 123.4  | 118.7  | 110.8  | 106.0  | 99.7   | 99.7   | 99.7   | 98.1   | 99.7   | 98.1   |
| 82.5° | 87.0   | 83.9   | 80.7   | 76.0   | 74.4   | 74.4   | 76.0   | 76.0   | 76.0   | 76.0   | 76.0   |
| 85°   | 50.6   | 50.6   | 50.6   | 52.2   | 50.6   | 50.6   | 52.2   | 53.8   | 52.2   | 52.2   | 50.6   |
| 87.5° | 23.7   | 23.7   | 25.3   | 25.3   | 26.9   | 26.9   | 26.9   | 26.9   | 26.9   | 26.9   | 28.5   |
| 90°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |

TEST NUMBER: P996370

CATALOG NUMBER: S123RDRP-B1165DB35-4F0-XX-W2A-A

**CANDELA DISTRIBUTION (continued):**

|       | 247.5° | 250°   | 255°   | 260°   | 265°   | 270°   | 275°   | 280°   | 285°   | 290°   | 292.5° |
|-------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°    | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 |
| 2.5°  | 1746.9 | 1748.5 | 1743.7 | 1734.2 | 1732.6 | 1735.8 | 1745.3 | 1742.1 | 1734.2 | 1748.5 | 1735.8 |
| 5°    | 1650.4 | 1642.4 | 1639.3 | 1642.4 | 1633.0 | 1628.2 | 1637.7 | 1633.0 | 1637.7 | 1639.3 | 1644.0 |
| 7.5°  | 1557.0 | 1558.6 | 1549.1 | 1550.7 | 1538.0 | 1541.2 | 1541.2 | 1541.2 | 1545.9 | 1549.1 | 1555.4 |
| 10°   | 1476.3 | 1479.5 | 1468.4 | 1470.0 | 1460.5 | 1454.2 | 1458.9 | 1468.4 | 1468.4 | 1468.4 | 1471.6 |
| 12.5° | 1411.4 | 1397.2 | 1389.3 | 1387.7 | 1376.6 | 1373.5 | 1382.9 | 1386.1 | 1394.0 | 1394.0 | 1398.8 |
| 15°   | 1330.7 | 1327.6 | 1321.2 | 1321.2 | 1294.3 | 1300.7 | 1303.8 | 1314.9 | 1330.7 | 1318.1 | 1321.2 |
| 17.5° | 1257.9 | 1250.0 | 1242.1 | 1239.0 | 1235.8 | 1226.3 | 1239.0 | 1237.4 | 1246.9 | 1248.5 | 1253.2 |
| 20°   | 1193.1 | 1186.7 | 1170.9 | 1172.5 | 1175.7 | 1161.4 | 1169.3 | 1169.3 | 1178.8 | 1188.3 | 1199.4 |
| 22.5° | 1129.8 | 1123.4 | 1115.5 | 1118.7 | 1109.2 | 1106.0 | 1106.0 | 1114.0 | 1125.0 | 1132.9 | 1131.4 |
| 25°   | 1080.7 | 1069.6 | 1064.9 | 1060.2 | 1055.4 | 1058.6 | 1053.8 | 1061.7 | 1069.6 | 1074.4 | 1069.6 |
| 27.5° | 1025.3 | 1020.6 | 1011.1 | 1006.4 | 998.4  | 1001.6 | 1004.8 | 1011.1 | 1015.9 | 1015.9 | 1020.6 |
| 30°   | 971.5  | 965.2  | 962.1  | 957.3  | 957.3  | 951.0  | 952.6  | 958.9  | 963.6  | 968.4  | 974.7  |
| 32.5° | 919.3  | 914.6  | 909.8  | 909.8  | 906.7  | 905.1  | 903.5  | 913.0  | 913.0  | 922.5  | 922.5  |
| 35°   | 876.6  | 868.7  | 868.7  | 860.8  | 863.9  | 862.4  | 859.2  | 865.5  | 867.1  | 873.4  | 871.9  |
| 37.5° | 829.1  | 829.1  | 826.0  | 818.1  | 811.7  | 813.3  | 821.2  | 821.2  | 826.0  | 824.4  | 829.1  |
| 40°   | 781.7  | 778.5  | 778.5  | 773.8  | 772.2  | 770.6  | 772.2  | 773.8  | 781.7  | 780.1  | 781.7  |
| 42.5° | 734.2  | 735.8  | 727.9  | 727.9  | 727.9  | 723.1  | 724.7  | 726.3  | 729.5  | 732.6  | 737.4  |
| 45°   | 688.3  | 685.1  | 683.6  | 680.4  | 677.2  | 678.8  | 677.2  | 683.6  | 682.0  | 685.1  | 689.9  |
| 47.5° | 639.3  | 634.5  | 632.9  | 626.6  | 626.6  | 629.8  | 628.2  | 632.9  | 634.5  | 639.3  | 636.1  |
| 50°   | 591.8  | 585.5  | 580.7  | 582.3  | 572.8  | 576.0  | 576.0  | 580.7  | 585.5  | 587.0  | 590.2  |
| 52.5° | 536.4  | 534.8  | 533.2  | 525.3  | 523.7  | 522.2  | 523.7  | 525.3  | 531.7  | 536.4  | 538.0  |
| 55°   | 482.6  | 481.0  | 471.5  | 468.4  | 463.6  | 463.6  | 466.8  | 468.4  | 479.4  | 481.0  | 487.4  |
| 57.5° | 433.6  | 428.8  | 417.7  | 416.2  | 416.2  | 416.2  | 411.4  | 417.7  | 420.9  | 428.8  | 428.8  |
| 60°   | 379.8  | 379.8  | 370.3  | 370.3  | 371.8  | 370.3  | 370.3  | 371.8  | 371.8  | 378.2  | 381.3  |
| 62.5° | 337.0  | 335.5  | 335.5  | 332.3  | 330.7  | 332.3  | 330.7  | 330.7  | 332.3  | 337.0  | 341.8  |
| 65°   | 299.1  | 297.5  | 295.9  | 294.3  | 291.1  | 291.1  | 292.7  | 295.9  | 295.9  | 299.1  | 300.6  |
| 67.5° | 262.7  | 262.7  | 259.5  | 259.5  | 257.9  | 256.3  | 257.9  | 256.3  | 262.7  | 262.7  | 264.2  |
| 70°   | 226.3  | 224.7  | 219.9  | 218.4  | 213.6  | 215.2  | 215.2  | 219.9  | 221.5  | 224.7  | 227.9  |
| 72.5° | 182.0  | 182.0  | 178.8  | 175.6  | 177.2  | 174.1  | 174.1  | 175.6  | 175.6  | 180.4  | 182.0  |
| 75°   | 150.3  | 147.2  | 145.6  | 147.2  | 145.6  | 148.7  | 145.6  | 145.6  | 148.7  | 148.7  | 148.7  |
| 77.5° | 123.4  | 123.4  | 121.8  | 121.8  | 123.4  | 121.8  | 123.4  | 123.4  | 123.4  | 121.8  | 123.4  |
| 80°   | 101.3  | 99.7   | 99.7   | 99.7   | 98.1   | 98.1   | 98.1   | 98.1   | 98.1   | 98.1   | 98.1   |
| 82.5° | 76.0   | 76.0   | 74.4   | 76.0   | 76.0   | 74.4   | 76.0   | 74.4   | 74.4   | 76.0   | 76.0   |
| 85°   | 50.6   | 53.8   | 50.6   | 50.6   | 52.2   | 52.2   | 53.8   | 52.2   | 53.8   | 50.6   | 52.2   |
| 87.5° | 26.9   | 28.5   | 28.5   | 26.9   | 26.9   | 28.5   | 28.5   | 28.5   | 30.1   | 26.9   | 28.5   |
| 90°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |

TEST NUMBER: P996370

CATALOG NUMBER: S123RDRP-B1165DB35-4F0-XX-W2A-A

**CANDELA DISTRIBUTION (continued):**

|       | 295°   | 300°   | 305°   | 310°   | 315°   | 320°   | 325°   | 330°   | 335°   | 337.5° | 340°   |
|-------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°    | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 | 1848.2 |
| 2.5°  | 1748.5 | 1754.8 | 1748.5 | 1735.8 | 1748.5 | 1756.4 | 1764.3 | 1776.9 | 1783.3 | 1783.3 | 1792.8 |
| 5°    | 1648.8 | 1661.4 | 1656.7 | 1653.5 | 1666.2 | 1674.1 | 1686.8 | 1702.6 | 1720.0 | 1731.1 | 1743.7 |
| 7.5°  | 1560.2 | 1568.1 | 1576.0 | 1576.0 | 1588.7 | 1606.1 | 1625.0 | 1644.0 | 1666.2 | 1682.0 | 1691.5 |
| 10°   | 1482.6 | 1489.0 | 1493.7 | 1500.0 | 1519.0 | 1538.0 | 1563.3 | 1587.1 | 1606.1 | 1623.5 | 1639.3 |
| 12.5° | 1408.3 | 1417.8 | 1428.8 | 1433.6 | 1447.8 | 1471.6 | 1495.3 | 1523.8 | 1553.8 | 1571.2 | 1587.1 |
| 15°   | 1337.1 | 1341.8 | 1354.5 | 1368.7 | 1381.4 | 1406.7 | 1436.7 | 1466.8 | 1492.1 | 1519.0 | 1533.3 |
| 17.5° | 1264.3 | 1265.9 | 1299.1 | 1291.2 | 1332.3 | 1356.0 | 1371.9 | 1400.4 | 1441.5 | 1463.6 | 1485.8 |
| 20°   | 1193.1 | 1208.9 | 1223.1 | 1231.0 | 1253.2 | 1280.1 | 1326.0 | 1348.1 | 1381.4 | 1401.9 | 1420.9 |
| 22.5° | 1137.7 | 1161.4 | 1161.4 | 1180.4 | 1191.5 | 1216.8 | 1250.0 | 1292.8 | 1329.2 | 1343.4 | 1370.3 |
| 25°   | 1088.6 | 1099.7 | 1118.7 | 1125.0 | 1145.6 | 1167.8 | 1189.9 | 1235.8 | 1275.4 | 1294.3 | 1313.3 |
| 27.5° | 1025.3 | 1039.6 | 1064.9 | 1064.9 | 1091.8 | 1115.5 | 1142.4 | 1172.5 | 1212.1 | 1239.0 | 1259.5 |
| 30°   | 976.3  | 990.5  | 1001.6 | 1019.0 | 1030.1 | 1052.2 | 1099.7 | 1121.9 | 1156.7 | 1180.4 | 1205.7 |
| 32.5° | 930.4  | 941.5  | 951.0  | 970.0  | 982.6  | 1007.9 | 1033.3 | 1072.8 | 1102.9 | 1125.0 | 1151.9 |
| 35°   | 879.8  | 890.8  | 903.5  | 917.7  | 936.7  | 960.5  | 984.2  | 1017.4 | 1047.5 | 1068.1 | 1090.2 |
| 37.5° | 832.3  | 840.2  | 859.2  | 868.7  | 884.5  | 906.7  | 936.7  | 971.5  | 998.4  | 1014.3 | 1036.4 |
| 40°   | 786.4  | 792.7  | 807.0  | 824.4  | 835.5  | 852.9  | 884.5  | 914.6  | 947.8  | 966.8  | 984.2  |
| 42.5° | 737.4  | 745.3  | 757.9  | 775.3  | 792.7  | 811.7  | 829.1  | 863.9  | 894.0  | 909.8  | 928.8  |
| 45°   | 694.6  | 699.4  | 708.9  | 726.3  | 743.7  | 757.9  | 784.8  | 816.5  | 845.0  | 857.6  | 878.2  |
| 47.5° | 644.0  | 648.8  | 663.0  | 670.9  | 689.9  | 708.9  | 735.8  | 767.4  | 792.7  | 805.4  | 824.4  |
| 50°   | 591.8  | 596.5  | 606.0  | 623.4  | 636.1  | 656.7  | 680.4  | 707.3  | 738.9  | 756.3  | 767.4  |
| 52.5° | 541.2  | 550.6  | 558.6  | 572.8  | 588.6  | 609.2  | 631.3  | 656.7  | 683.6  | 701.0  | 713.6  |
| 55°   | 490.5  | 498.4  | 507.9  | 515.8  | 534.8  | 553.8  | 579.1  | 602.9  | 626.6  | 642.4  | 656.7  |
| 57.5° | 433.6  | 444.6  | 454.1  | 469.9  | 484.2  | 500.0  | 528.5  | 547.5  | 576.0  | 587.0  | 599.7  |
| 60°   | 384.5  | 395.6  | 403.5  | 416.2  | 428.8  | 449.4  | 468.4  | 492.1  | 515.8  | 530.1  | 545.9  |
| 62.5° | 343.4  | 348.1  | 352.9  | 365.5  | 378.2  | 397.2  | 416.2  | 439.9  | 465.2  | 473.1  | 485.8  |
| 65°   | 302.2  | 307.0  | 314.9  | 326.0  | 335.5  | 346.5  | 367.1  | 386.1  | 409.8  | 422.5  | 427.2  |
| 67.5° | 267.4  | 272.2  | 273.7  | 281.7  | 289.6  | 302.2  | 313.3  | 332.3  | 354.4  | 362.4  | 371.8  |
| 70°   | 227.9  | 235.8  | 237.3  | 243.7  | 246.8  | 254.8  | 267.4  | 281.7  | 299.1  | 313.3  | 321.2  |
| 72.5° | 182.0  | 193.0  | 196.2  | 205.7  | 210.4  | 218.4  | 227.9  | 238.9  | 250.0  | 256.3  | 262.7  |
| 75°   | 148.7  | 151.9  | 153.5  | 161.4  | 169.3  | 180.4  | 185.1  | 191.5  | 201.0  | 208.9  | 215.2  |
| 77.5° | 123.4  | 125.0  | 126.6  | 126.6  | 128.2  | 134.5  | 144.0  | 151.9  | 158.2  | 161.4  | 166.1  |
| 80°   | 99.7   | 98.1   | 98.1   | 99.7   | 99.7   | 99.7   | 102.9  | 113.9  | 117.1  | 125.0  | 123.4  |
| 82.5° | 77.5   | 74.4   | 76.0   | 74.4   | 74.4   | 74.4   | 74.4   | 76.0   | 76.0   | 80.7   | 83.9   |
| 85°   | 50.6   | 52.2   | 50.6   | 50.6   | 49.1   | 50.6   | 49.1   | 49.1   | 47.5   | 47.5   | 45.9   |
| 87.5° | 26.9   | 28.5   | 26.9   | 26.9   | 25.3   | 26.9   | 25.3   | 25.3   | 23.7   | 23.7   | 20.6   |
| 90°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |

TEST NUMBER: P996370

CATALOG NUMBER: S123RDRP-B1165DB35-4F0-XX-W2A-A

**CANDELA DISTRIBUTION (continued):**

|       | 345°   | 350°   | 355°   | 360°   |
|-------|--------|--------|--------|--------|
| 0°    | 1848.2 | 1848.2 | 1848.2 | 1848.2 |
| 2.5°  | 1800.7 | 1811.8 | 1833.9 | 1852.9 |
| 5°    | 1762.7 | 1780.1 | 1813.3 | 1846.6 |
| 7.5°  | 1716.8 | 1743.7 | 1786.4 | 1832.3 |
| 10°   | 1672.5 | 1707.3 | 1759.5 | 1813.3 |
| 12.5° | 1628.2 | 1664.6 | 1720.0 | 1789.6 |
| 15°   | 1576.0 | 1614.0 | 1680.4 | 1764.3 |
| 17.5° | 1530.1 | 1580.7 | 1640.9 | 1724.7 |
| 20°   | 1481.1 | 1519.0 | 1596.6 | 1685.2 |
| 22.5° | 1419.3 | 1482.6 | 1555.4 | 1648.8 |
| 25°   | 1370.3 | 1425.7 | 1498.5 | 1604.5 |
| 27.5° | 1310.2 | 1375.0 | 1463.6 | 1557.0 |
| 30°   | 1261.1 | 1314.9 | 1397.2 | 1509.5 |
| 32.5° | 1204.1 | 1267.4 | 1352.9 | 1463.6 |
| 35°   | 1153.5 | 1207.3 | 1288.0 | 1400.4 |
| 37.5° | 1093.4 | 1151.9 | 1242.1 | 1341.8 |
| 40°   | 1041.2 | 1098.1 | 1183.6 | 1276.9 |
| 42.5° | 977.9  | 1038.0 | 1123.4 | 1202.6 |
| 45°   | 927.2  | 982.6  | 1050.7 | 1123.4 |
| 47.5° | 865.5  | 924.1  | 990.5  | 1041.2 |
| 50°   | 810.1  | 863.9  | 916.2  | 958.9  |
| 52.5° | 750.0  | 799.1  | 846.5  | 878.2  |
| 55°   | 694.6  | 732.6  | 770.6  | 792.7  |
| 57.5° | 629.8  | 666.2  | 697.8  | 710.5  |
| 60°   | 572.8  | 602.9  | 623.4  | 637.7  |
| 62.5° | 512.7  | 534.8  | 550.6  | 558.6  |
| 65°   | 454.1  | 469.9  | 477.9  | 485.8  |
| 67.5° | 394.0  | 408.2  | 413.0  | 422.5  |
| 70°   | 330.7  | 346.5  | 349.7  | 354.4  |
| 72.5° | 283.2  | 283.2  | 289.6  | 295.9  |
| 75°   | 226.3  | 229.4  | 232.6  | 232.6  |
| 77.5° | 177.2  | 177.2  | 180.4  | 182.0  |
| 80°   | 129.8  | 131.3  | 131.3  | 129.8  |
| 82.5° | 88.6   | 91.8   | 88.6   | 87.0   |
| 85°   | 49.1   | 55.4   | 52.2   | 52.2   |
| 87.5° | 20.6   | 20.6   | 23.7   | 20.6   |
| 90°   | 0.0    | 0.0    | 0.0    | 0.0    |

(END OF REPORT)