

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P996494

Luminaire Tested: S124DRP-B1195DB50-4F0-XX-W2A-D

Issue Date: 5/2/2025

Test Information

Test Method: LM-79-2019
Report Number: P996494
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1802-639-16)
Test Lab: INNOVATION CENTER
Issue Date: 5/2/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S124DRP-B1195DB50-4F0-XX-W2A-D
Description: Define 4 Direct Perimeter with 5000K BioUP LEDs {m-DER=1.015} {m-EER=1.115}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4685.0 lumens
Efficiency: N/A
Efficacy: 76.4 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.28 / 1.39
Luminous Opening: Rectangular (W 0.33' x L: 4' x H: 0')
CIE Type: Direct

Input Watts (W): 61.3
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P996494

CATALOG NUMBER: S124DRP-B1195DB50-4F0-XX-W2A-D

Luminous Intensity Polar Plot



TEST NUMBER: P996494

CATALOG NUMBER: S124DRP-B1195DB50-4F0-XX-W2A-D

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	117	117	117	117	114	114	114	114	107	107	107	101	101	101	95	95	95
1	105	100	95	91	102	97	93	89	91	88	84	86	83	80	81	79	77
2	95	86	79	73	92	84	77	71	79	73	68	74	70	66	70	67	63
3	87	75	67	60	83	73	65	59	69	62	57	65	60	55	62	57	53
4	79	66	57	50	76	65	56	49	61	54	48	58	52	47	55	49	45
5	73	59	50	43	70	58	49	42	55	47	41	52	45	40	49	44	39
6	67	53	44	37	64	52	43	37	49	42	36	47	40	35	45	39	34
7	62	48	39	33	60	47	38	32	45	37	32	43	36	31	41	35	30
8	58	44	35	29	56	43	35	29	41	33	28	39	32	28	37	31	27
9	54	40	32	26	52	39	31	26	38	30	25	36	29	25	34	29	24
10	50	37	29	24	49	36	29	23	35	28	23	33	27	23	32	26	22

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	11205	11205	11205
5°	11261	11135	11223
10°	11212	11136	11238
15°	11133	11107	11211
20°	11003	11056	11190
25°	10855	10980	11145
30°	10693	10910	11099
35°	10508	10846	11106
40°	10369	10811	11122
45°	10151	10825	11215
50°	9975	10834	11341
55°	9801	10917	11486
60°	9511	10992	11770
65°	9204	11164	12144
70°	8841	11482	12732
75°	8340	12168	13964
80°	7875	13947	16694
85°	7635	20153	25917

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 90°

Vertical Angle: 87.5°

Luminance: 44886 cd/sqm

TEST NUMBER: P996494

CATALOG NUMBER: S124DRP-B1195DB50-4F0-XX-W2A-D

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	130.2	2.8
10°-20°	373.1	8.0
20°-30°	564.1	12.0
30°-40°	682.4	14.6
40°-50°	721.4	15.4
50°-60°	678.9	14.5
60°-70°	563.4	12.0
70°-80°	395.4	8.4
80°-90°	222.9	4.8
90°-100°	132.7	2.8
100°-110°	98.3	2.1
110°-120°	65.9	1.4
120°-130°	37.1	0.8
130°-140°	16.1	0.3
140°-150°	3.2	0.1
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1067.3	22.8
0°-40°	1749.7	37.3
0°-60°	3150.1	67.2
0°-90°	4331.7	92.5
90°-120°	296.9	6.3
90°-150°	353.3	7.5
90°-180°	353.0	7.5
0°-180°	4685.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1374	1374	1374	1374	1374	
5°	1376	1371	1360	1373	1371	131
15°	1319	1320	1316	1330	1328	372
25°	1206	1216	1220	1237	1239	556
35°	1056	1074	1090	1111	1116	661
45°	880	909	939	965	972	680
55°	689	722	768	799	808	614
65°	477	526	579	617	629	473
75°	265	322	386	429	443	281
85°	82	146	215	262	277	85
90°	25	86	152	197	209	17
95°	20	71	134	175	189	16
105°	14	45	102	140	152	16
115°	9	23	72	106	117	10
125°	6	5	43	72	82	6
135°	3	3	14	38	48	3
145°	2	0	0	9	15	1
155°	0	0	0	0	0	0
165°	0	0	0	0	0	0
175°	0	0	0	0	0	0
180°	0	0	0	0	0	0

TEST NUMBER: P996494

CATALOG NUMBER: S124DRP-B1195DB50-4F0-XX-W2A-D

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1374.1	1374.1	1374.1	1374.1	1374.1
2.5°	1380.3	1375.7	1363.4	1374.1	1372.6
5°	1375.7	1371.1	1360.3	1372.6	1371.1
7.5°	1366.4	1363.4	1354.1	1368.0	1366.4
10°	1354.1	1352.6	1344.9	1358.8	1357.2
12.5°	1337.2	1337.2	1332.6	1344.9	1344.9
15°	1318.7	1320.3	1315.7	1329.5	1328.0
17.5°	1294.1	1298.7	1297.2	1311.0	1309.5
20°	1268.0	1272.6	1274.1	1289.5	1289.5
22.5°	1238.7	1244.9	1248.0	1263.3	1266.4
25°	1206.4	1215.6	1220.3	1237.2	1238.7
27.5°	1171.0	1184.9	1191.0	1206.4	1207.9
30°	1135.6	1147.9	1158.7	1175.6	1178.7
32.5°	1097.2	1112.5	1124.9	1144.9	1147.9
35°	1055.6	1074.1	1089.5	1111.0	1115.6
37.5°	1014.1	1035.6	1054.1	1075.6	1080.2
40°	974.1	994.1	1015.6	1038.7	1044.8
42.5°	927.9	951.0	977.1	1003.3	1007.9
45°	880.2	909.4	938.7	964.8	972.5
47.5°	835.6	864.8	898.7	924.8	934.0
50°	786.3	820.2	854.0	884.8	894.0
52.5°	737.1	770.9	810.9	841.7	850.9
55°	689.4	721.7	767.9	798.6	807.9
57.5°	635.5	675.5	720.2	757.1	764.8
60°	583.2	623.2	674.0	709.4	721.7
62.5°	532.4	577.0	627.8	663.2	675.5
65°	477.0	526.3	578.6	617.1	629.4
67.5°	424.7	477.0	532.4	570.9	583.2
70°	370.8	423.2	481.6	523.2	534.0
72.5°	318.5	372.4	435.5	475.5	487.8
75°	264.7	321.6	386.2	429.3	443.2
77.5°	213.9	273.9	341.6	384.7	400.1
80°	167.7	229.3	297.0	343.1	355.5
82.5°	121.6	186.2	253.9	301.6	315.5
85°	81.6	146.2	215.4	261.6	277.0
87.5°	50.8	113.9	181.6	226.2	240.1
90°	24.6	86.2	152.3	197.0	209.3
92.5°	23.1	76.9	143.1	186.2	198.5
95°	20.0	70.8	133.9	175.4	189.3
97.5°	18.5	63.1	126.2	166.2	180.0
100°	16.9	56.9	116.9	158.5	169.3
102.5°	16.9	50.8	109.3	149.3	161.6
105°	13.8	44.6	101.6	140.0	152.3
107.5°	13.8	40.0	93.9	132.3	143.1
110°	12.3	33.9	87.7	123.1	135.4



TEST NUMBER: P996494

CATALOG NUMBER: S124DRP-B1195DB50-4F0-XX-W2A-D

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	10.8	29.2	80.0	113.9	126.2
115°	9.2	23.1	72.3	106.2	116.9
117.5°	9.2	18.5	64.6	96.9	109.3
120°	7.7	12.3	56.9	87.7	100.0
122.5°	7.7	7.7	49.2	80.0	90.8
125°	6.2	4.6	43.1	72.3	81.6
127.5°	6.2	4.6	35.4	63.1	73.9
130°	4.6	3.1	27.7	55.4	64.6
132.5°	4.6	3.1	21.5	47.7	56.9
135°	3.1	3.1	13.8	38.5	47.7
137.5°	3.1	1.5	7.7	30.8	38.5
140°	3.1	1.5	3.1	23.1	30.8
142.5°	1.5	1.5	0.0	16.9	23.1
145°	1.5	0.0	0.0	9.2	15.4
147.5°	1.5	0.0	0.0	1.5	7.7
150°	1.5	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)