

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1037997

Luminaire Tested: S125DS-B375DB2750-4F0-XX-W2A-D_2700K

Issue Date: 5/2/2025

Test Information

Test Method: LM-79-2019
Report Number: P1037997
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1802-639-17)
Test Lab: INNOVATION CENTER
Issue Date: 5/2/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S125DS-B375DB2750-4F0-XX-W2A-D_2700K
Description: Define 5 Direct Surface with 2700K BioUP LEDs {m-DER=0.473} {m-EER=0.52}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1409.0 lumens
Efficiency: N/A
Efficacy: 108.4 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.21 / 1.34
Luminous Opening: Rectangular (W 0.42' x L: 4' x H: 0')
CIE Type: Direct

Input Watts (W): 13
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1037997

CATALOG NUMBER: S125DS-B375DB2750-4F0-XX-W2A-D_2700K

Luminous Intensity Polar Plot



TEST NUMBER: P1037997

CATALOG NUMBER: S125DS-B375DB2750-4F0-XX-W2A-D_2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			0
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	118	118	118	118	114	114	114	114	108	108	108		102	102	102		96	96	96	94
1	106	101	96	92	103	98	94	90	93	89	86		88	85	82		83	81	79	76
2	96	88	80	74	93	85	78	73	81	75	70		76	72	68		72	69	65	63
3	88	77	68	61	84	75	67	60	71	64	59		67	61	57		64	59	55	53
4	80	68	59	52	77	66	58	51	63	55	50		60	53	48		57	51	47	45
5	74	60	51	44	71	59	50	44	56	49	43		53	47	42		51	45	41	39
6	68	54	45	39	66	53	45	38	51	43	38		48	42	37		46	40	36	34
7	63	49	40	34	61	48	40	34	46	39	33		44	37	33		42	36	32	30
8	59	45	36	30	57	44	36	30	42	35	30		40	34	29		39	33	29	27
9	55	41	33	27	53	40	33	27	39	32	27		37	31	26		36	30	26	24
10	51	38	30	25	50	37	30	25	36	29	24		35	28	24		33	28	23	22

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	2914	2914	2914
5°	2925	2899	2919
10°	2910	2887	2904
15°	2881	2863	2869
20°	2840	2825	2834
25°	2790	2780	2778
30°	2728	2728	2731
35°	2672	2686	2696
40°	2615	2640	2663
45°	2550	2614	2647
50°	2489	2587	2649
55°	2416	2575	2650
60°	2337	2565	2668
65°	2257	2576	2705
70°	2171	2581	2789
75°	2030	2671	2948
80°	1860	2911	3339
85°	1801	4029	5014

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 90°

Vertical Angle: 87.5°

Luminance: 8578 cd/sqm

TEST NUMBER: P1037997

CATALOG NUMBER: S125DS-B375DB2750-4F0-XX-W2A-D_2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	43.0	3.1
10°-20°	122.2	8.7
20°-30°	181.7	12.9
30°-40°	215.2	15.3
40°-50°	222.5	15.8
50°-60°	204.9	14.5
60°-70°	165.7	11.8
70°-80°	110.8	7.9
80°-90°	57.3	4.1
90°-100°	32.3	2.3
100°-110°	23.8	1.7
110°-120°	15.9	1.1
120°-130°	9.0	0.6
130°-140°	3.9	0.3
140°-150°	0.8	0.1
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	346.9	24.6
0°-40°	562.1	39.9
0°-60°	989.5	70.2
0°-90°	1323.2	93.9
90°-120°	72.0	5.1
90°-150°	85.7	6.1
90°-180°	86.0	6.1
0°-180°	1409.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	455	455	455	455	455	
5°	455	454	451	454	454	43
15°	434	435	432	434	432	122
25°	395	396	393	395	393	182
35°	342	345	343	345	345	214
45°	281	286	288	292	292	217
55°	216	223	230	235	237	193
65°	149	159	170	177	178	148
75°	82	94	108	117	119	87
85°	24	39	55	65	68	26
90°	7	21	37	47	50	5
95°	6	17	33	42	46	5
105°	4	11	24	33	37	4
115°	3	6	17	25	28	3
125°	2	1	10	17	20	1
135°	1	0	4	9	12	1
145°	0	0	0	2	4	0
155°	0	0	0	0	0	0
165°	0	0	0	0	0	0
175°	0	0	0	0	0	0
180°	0	0	0	0	0	0

TEST NUMBER: P1037997

CATALOG NUMBER: S125DS-B375DB2750-4F0-XX-W2A-D_2700K

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	454.8	454.8	454.8	454.8	454.8
2.5°	456.2	455.3	452.2	455.3	454.8
5°	454.8	453.9	450.8	454.4	453.9
7.5°	451.7	451.3	448.1	451.3	450.8
10°	447.3	447.3	443.7	446.8	446.4
12.5°	441.0	441.5	438.8	441.0	439.7
15°	434.3	434.8	431.6	434.3	432.5
17.5°	425.9	426.7	423.6	425.9	424.5
20°	416.5	417.4	414.3	415.6	415.6
22.5°	405.8	407.6	404.0	405.8	404.4
25°	394.6	396.0	393.3	395.1	392.9
27.5°	382.6	384.4	381.3	382.6	381.7
30°	368.8	371.4	368.8	369.7	369.2
32.5°	356.3	358.5	356.7	357.6	357.2
35°	341.6	344.7	343.4	344.7	344.7
37.5°	327.3	330.0	329.5	331.3	330.9
40°	312.6	316.2	315.7	317.5	318.4
42.5°	296.5	301.4	302.8	305.0	305.0
45°	281.4	286.3	288.5	291.6	292.1
47.5°	265.8	270.2	273.8	278.3	279.1
50°	249.7	254.6	259.5	264.4	265.8
52.5°	232.8	239.0	245.3	250.6	251.5
55°	216.3	223.4	230.5	235.4	237.2
57.5°	199.3	207.8	215.8	221.2	222.5
60°	182.4	191.3	200.2	206.9	208.2
62.5°	165.9	174.8	184.6	192.2	194.0
65°	148.9	159.2	169.9	176.6	178.4
67.5°	133.3	143.1	153.8	161.9	164.1
70°	115.9	126.2	137.8	146.3	148.9
72.5°	99.0	109.7	122.6	132.0	133.8
75°	82.0	93.6	107.9	116.8	119.1
77.5°	65.5	78.9	92.3	102.1	103.9
80°	50.4	63.8	78.9	88.7	90.5
82.5°	36.6	50.8	66.4	75.8	79.4
85°	24.5	39.2	54.8	64.7	68.2
87.5°	15.6	29.9	45.0	55.3	58.4
90°	7.1	21.4	36.6	46.8	49.9
92.5°	6.2	19.2	34.8	44.6	47.7
95°	5.8	17.4	32.6	42.4	45.5
97.5°	5.4	16.1	30.8	40.1	43.3
100°	4.9	14.3	28.5	37.9	40.6
102.5°	4.5	12.9	26.8	35.7	38.3
105°	4.0	11.1	24.5	33.4	36.6
107.5°	3.6	9.8	22.7	31.7	34.3
110°	3.1	8.5	21.0	29.4	32.6

TEST NUMBER: P1037997

CATALOG NUMBER: S125DS-B375DB2750-4F0-XX-W2A-D_2700K

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	3.1	7.1	19.2	27.2	30.3
115°	2.7	5.8	17.4	25.4	28.1
117.5°	2.2	4.5	15.6	23.2	26.3
120°	2.2	3.6	13.8	21.4	24.1
122.5°	1.8	2.2	12.0	19.2	21.8
125°	1.8	1.3	10.3	17.4	19.6
127.5°	1.3	0.9	8.5	15.2	17.8
130°	1.3	0.9	7.1	13.4	15.6
132.5°	0.9	0.9	5.4	11.6	13.4
135°	0.9	0.4	3.6	9.4	11.6
137.5°	0.9	0.4	2.2	7.6	9.4
140°	0.4	0.4	0.9	5.8	7.6
142.5°	0.4	0.0	0.0	4.0	5.8
145°	0.4	0.0	0.0	2.2	4.0
147.5°	0.0	0.0	0.0	0.9	1.8
150°	0.0	0.0	0.0	0.0	0.4
152.5°	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)