

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P929978

Luminaire Tested: DFN2DS-4P4F0-050DS930-RLL

Issue Date: 11/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P929978
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P333882)
Test Lab: INNOVATION CENTER
Issue Date: 11/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DS-4P4F0-050DS930-RLL
Description: 4 foot, 90deg - 4way Define Geo, with Direct 1in Regressed Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3463.8 lumens
Efficiency: N/A
Efficacy: 68.5 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular (W 4.07' x L: 4.07' x H: 0')
CIE Type: Direct

Input Watts (W): 50.6
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9951
Total Harmonic Distortion (THDi): 0.07
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P929978

CATALOG NUMBER: DFN2DS-4P4F0-050DS930-RLL

Luminous Intensity Polar Plot



TEST NUMBER: P929978

CATALOG NUMBER: DFN2DS-4P4F0-050DS930-RLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	110	106	102	98	107	103	100	97	99	96	94		95	93	91		92
2	101	94	87	82	98	92	86	81	88	83	79		85	81	78		82
3	93	83	76	70	90	82	75	69	79	73	68		76	71	67		74
4	86	75	66	60	83	73	66	60	71	64	59		69	63	58		66
5	79	67	59	53	77	66	58	52	64	57	52		62	56	51		60
6	74	61	53	47	72	60	52	46	58	51	46		57	50	46		55
7	68	56	47	42	67	55	47	42	53	46	41		52	46	41		51
8	64	51	43	38	62	51	43	37	49	42	37		48	42	37		47
9	60	47	39	34	59	47	39	34	46	39	34		44	38	34		44
10	56	44	36	31	55	43	36	31	42	36	31		41	35	31		41

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1093	1093	1093
5°	1097	1079	1085
10°	1088	1061	1052
15°	1076	1030	1000
20°	1059	985	935
25°	1041	934	873
30°	1016	881	792
35°	992	825	722
40°	968	765	640
45°	940	699	566
50°	911	632	494
55°	881	560	424
60°	846	484	352
65°	807	407	321
70°	760	335	295
75°	703	306	275
80°	621	273	251
85°	488	215	215

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 940 cd/sqm

TEST NUMBER: P929978

CATALOG NUMBER: DFN2DS-4P4F0-050DS930-RLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	157.8	4.6
10°-20°	433.3	12.5
20°-30°	608.4	17.6
30°-40°	663.2	19.1
40°-50°	609.5	17.6
50°-60°	478.7	13.8
60°-70°	311.6	9.0
70°-80°	160.4	4.6
80°-90°	40.9	1.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1199.5	34.6
0°-40°	1862.7	53.8
0°-60°	2950.9	85.2
0°-90°	3463.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3463.8	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1684	1684	1684	1684	1684	
5°	1684	1677	1657	1670	1666	160
15°	1602	1585	1533	1504	1489	451
25°	1454	1405	1305	1242	1219	669
35°	1253	1175	1041	945	911	784
45°	1024	922	762	654	617	791
55°	779	660	495	404	375	696
65°	526	402	265	213	209	521
75°	280	174	122	111	110	297
85°	66	34	29	29	29	79
90°	0	0	0	0	0	

TEST NUMBER: P929978

CATALOG NUMBER: DFN2DS-4P4F0-050DS930-RLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1684.2	1684.2	1684.2	1684.2	1684.2
2.5°	1691.8	1684.2	1667.4	1682.7	1679.6
5°	1684.2	1676.6	1656.7	1670.4	1665.9
7.5°	1670.4	1661.4	1640.0	1646.1	1638.4
10°	1652.2	1641.5	1611.1	1606.4	1597.3
12.5°	1629.3	1615.7	1574.4	1565.4	1548.5
15°	1601.9	1585.1	1533.3	1504.4	1489.2
17.5°	1569.9	1545.5	1481.4	1447.9	1423.5
20°	1533.3	1502.8	1426.6	1388.6	1354.9
22.5°	1493.7	1458.6	1370.2	1318.4	1295.6
25°	1454.0	1405.2	1304.7	1242.2	1219.2
27.5°	1406.9	1354.9	1243.7	1172.1	1137.0
30°	1356.6	1298.5	1176.6	1098.9	1057.7
32.5°	1307.7	1237.6	1112.7	1021.2	983.1
35°	1252.9	1175.1	1041.1	945.0	911.4
37.5°	1199.5	1115.7	974.0	868.7	830.7
40°	1143.1	1051.8	903.8	795.6	756.0
42.5°	1085.3	987.7	833.7	720.9	682.9
45°	1024.3	922.1	762.1	653.8	617.2
47.5°	966.3	858.2	693.6	585.3	551.8
50°	902.4	794.1	626.5	521.2	489.3
52.5°	839.8	725.4	562.4	461.9	432.9
55°	778.8	659.9	495.3	403.9	375.0
57.5°	716.4	594.5	435.9	350.6	326.2
60°	652.3	530.4	373.4	295.8	271.3
62.5°	589.9	468.0	320.1	246.9	234.8
65°	525.8	402.4	265.2	213.4	208.8
67.5°	464.9	341.4	213.4	187.4	182.9
70°	400.9	282.0	176.8	161.5	155.4
72.5°	339.9	227.1	147.8	135.7	132.6
75°	280.4	173.7	121.9	111.2	109.8
77.5°	221.0	123.4	96.1	89.9	86.8
80°	166.1	88.4	73.1	67.1	67.1
82.5°	115.8	59.5	50.3	47.2	47.2
85°	65.5	33.5	28.9	28.9	28.9
87.5°	24.4	12.1	12.1	10.7	10.7
90°	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P929978

CATALOG NUMBER: DFN2DS-4P4F0-050DS930-RLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	11.54	13.06	11.91	13.38	13.69	7.50	9.03	7.87	9.34	9.65
	3H	13.31	14.67	13.69	15.00	15.36	8.77	10.13	9.15	10.46	10.82
	4H	13.97	15.25	14.37	15.60	15.98	9.27	10.55	9.67	10.90	11.28
	6H	14.46	15.65	14.88	16.01	16.40	9.65	10.83	10.06	11.20	11.59
	8H	14.63	15.75	15.05	16.14	16.55	9.78	10.90	10.20	11.29	11.69
	12H	14.73	15.81	15.16	16.19	16.62	9.86	10.93	10.29	11.32	11.75
4H	2H	11.65	12.93	12.05	13.28	13.65	8.20	9.48	8.60	9.83	10.21
	3H	13.58	14.64	13.99	15.04	15.44	9.64	10.70	10.05	11.10	11.51
	4H	14.33	15.29	14.76	15.70	16.14	10.24	11.20	10.67	11.61	12.05
	6H	14.92	15.75	15.38	16.20	16.66	10.73	11.56	11.19	12.00	12.46
	8H	15.14	15.91	15.60	16.36	16.82	10.89	11.67	11.35	12.11	12.58
	12H	15.29	15.98	15.77	16.46	16.93	11.01	11.70	11.49	12.18	12.65
8H	4H	14.35	15.13	14.82	15.58	16.04	10.59	11.37	11.06	11.82	12.28
	6H	14.99	15.63	15.49	16.12	16.60	11.18	11.82	11.68	12.31	12.79
	8H	15.24	15.82	15.76	16.33	16.82	11.40	11.98	11.92	12.49	12.98
	12H	15.45	15.96	15.96	16.45	17.01	11.58	12.09	12.09	12.58	13.15
12H	4H	14.34	15.03	14.82	15.51	15.98	10.64	11.33	11.12	11.81	12.28
	6H	14.97	15.55	15.49	16.06	16.55	11.24	11.82	11.76	12.33	12.82
	8H	15.26	15.77	15.77	16.26	16.82	11.52	12.03	12.03	12.52	13.08