

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P930130

Luminaire Tested: DFN2DS-HX3F0-030DS830-RLL

Issue Date: 11/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P930130
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P333882)
Test Lab: INNOVATION CENTER
Issue Date: 11/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DS-HX3F0-030DS830-RLL
Description: 3 foot, Hexagon Define Geo, with Direct 1in Regressed Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2402.1 lumens
Efficiency: N/A
Efficacy: 85.5 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular (W 3.28' x L: 2.84' x H: 0')
CIE Type: Direct

Input Watts (W): 28.1
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.983
Total Harmonic Distortion (THDi): 0.073
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P930130

CATALOG NUMBER: DFN2DS-HX3F0-030DS830-RLL

Luminous Intensity Polar Plot



TEST NUMBER: P930130

CATALOG NUMBER: DFN2DS-HX3F0-030DS830-RLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	110	106	102	98	107	103	100	97	99	96	94		95	93	91		92
2	101	94	87	82	98	92	86	81	88	83	79		85	81	78		82
3	93	83	76	70	90	82	75	69	79	73	68		76	71	67		74
4	86	75	66	60	83	73	66	60	71	64	59		69	63	58		66
5	79	67	59	53	77	66	58	52	64	57	52		62	56	51		60
6	74	61	53	47	72	60	52	46	58	51	46		57	50	46		55
7	68	56	47	42	67	55	47	42	53	46	41		52	46	41		51
8	64	51	43	38	62	51	43	37	49	42	37		48	42	37		47
9	60	47	39	34	59	47	39	34	46	39	34		44	38	34		44
10	56	44	36	31	55	43	36	31	42	36	31		41	35	31		41

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1353	1353	1353
5°	1358	1336	1343
10°	1348	1314	1303
15°	1332	1275	1238
20°	1311	1220	1158
25°	1289	1156	1081
30°	1258	1091	981
35°	1229	1021	894
40°	1199	948	793
45°	1164	866	701
50°	1128	783	611
55°	1091	694	525
60°	1048	600	436
65°	999	504	397
70°	942	415	365
75°	870	379	341
80°	768	338	310
85°	603	267	267

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1164 cd/sqm

TEST NUMBER: P930130

CATALOG NUMBER: DFN2DS-HX3F0-030DS830-RLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	109.5	4.6
10°-20°	300.5	12.5
20°-30°	421.9	17.6
30°-40°	459.9	19.1
40°-50°	422.7	17.6
50°-60°	332.0	13.8
60°-70°	216.1	9.0
70°-80°	111.2	4.6
80°-90°	28.4	1.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	831.9	34.6
0°-40°	1291.8	53.8
0°-60°	2046.4	85.2
0°-90°	2402.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2402.1	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1168	1168	1168	1168	1168	
5°	1168	1163	1149	1158	1155	111
15°	1111	1099	1063	1043	1033	313
25°	1008	974	905	862	846	464
35°	869	815	722	655	632	544
45°	710	639	529	453	428	549
55°	540	458	344	280	260	483
65°	365	279	184	148	145	362
75°	194	120	85	77	76	206
85°	45	23	20	20	20	54
90°	0	0	0	0	0	

TEST NUMBER: P930130

CATALOG NUMBER: DFN2DS-HX3F0-030DS830-RLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1168.0	1168.0	1168.0	1168.0	1168.0
2.5°	1173.3	1168.0	1156.3	1166.9	1164.9
5°	1168.0	1162.7	1149.0	1158.5	1155.3
7.5°	1158.5	1152.2	1137.4	1141.5	1136.2
10°	1145.8	1138.4	1117.3	1114.0	1107.8
12.5°	1129.9	1120.4	1091.9	1085.6	1073.9
15°	1110.9	1099.2	1063.3	1043.3	1032.7
17.5°	1088.7	1071.8	1027.3	1004.2	987.2
20°	1063.3	1042.1	989.3	963.0	939.6
22.5°	1035.9	1011.5	950.2	914.3	898.5
25°	1008.4	974.5	904.8	861.5	845.5
27.5°	975.6	939.6	862.5	812.9	788.5
30°	940.8	900.6	816.0	762.2	733.5
32.5°	906.9	858.3	771.7	708.2	681.7
35°	868.9	814.9	721.9	655.3	632.1
37.5°	831.9	773.7	675.4	602.4	576.1
40°	792.8	729.4	626.8	551.7	524.3
42.5°	752.6	685.0	578.2	499.9	473.5
45°	710.4	639.4	528.6	453.4	428.0
47.5°	670.1	595.2	481.0	405.8	382.6
50°	625.8	550.7	434.5	361.4	339.3
52.5°	582.3	503.1	390.1	320.3	300.2
55°	540.0	457.6	343.5	280.2	260.1
57.5°	496.8	412.2	302.4	243.1	226.2
60°	452.3	367.9	259.0	205.1	188.2
62.5°	409.1	324.5	221.9	171.3	162.9
65°	364.6	279.0	183.9	148.0	144.8
67.5°	322.4	236.7	148.0	130.0	126.8
70°	278.0	195.6	122.6	112.0	107.8
72.5°	235.7	157.4	102.5	94.1	91.9
75°	194.4	120.5	84.6	77.1	76.1
77.5°	153.3	85.5	66.6	62.4	60.2
80°	115.2	61.3	50.7	46.5	46.5
82.5°	80.3	41.3	34.9	32.8	32.8
85°	45.4	23.2	20.1	20.1	20.1
87.5°	17.0	8.4	8.4	7.4	7.4
90°	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P930130

CATALOG NUMBER: DFN2DS-HX3F0-030DS830-RLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	12.28	13.81	12.65	14.12	14.43	8.24	9.77	8.61	10.08	10.39
	3H	14.05	15.42	14.43	15.74	16.10	9.51	10.88	9.89	11.20	11.57
	4H	14.72	16.00	15.12	16.35	16.72	10.01	11.29	10.41	11.64	12.02
	6H	15.20	16.39	15.62	16.75	17.15	10.39	11.58	10.80	11.94	12.33
	8H	15.37	16.50	15.80	16.89	17.29	10.52	11.64	10.94	12.03	12.43
	12H	15.47	16.55	15.90	16.93	17.36	10.60	11.68	11.03	12.06	12.49
4H	2H	12.39	13.67	12.79	14.02	14.40	8.94	10.22	9.34	10.57	10.95
	3H	14.32	15.38	14.73	15.78	16.19	10.38	11.45	10.79	11.85	12.25
	4H	15.07	16.03	15.50	16.44	16.88	10.98	11.94	11.42	12.35	12.79
	6H	15.66	16.49	16.12	16.94	17.40	11.47	12.30	11.93	12.75	13.20
	8H	15.88	16.65	16.34	17.10	17.57	11.63	12.41	12.10	12.85	13.32
	12H	16.03	16.73	16.51	17.20	17.67	11.75	12.45	12.23	12.92	13.39
8H	4H	15.10	15.87	15.56	16.32	16.78	11.34	12.11	11.80	12.56	13.03
	6H	15.73	16.38	16.23	16.87	17.34	11.92	12.57	12.42	13.06	13.53
	8H	15.98	16.56	16.50	17.07	17.56	12.14	12.72	12.66	13.23	13.72
	12H	16.19	16.70	16.70	17.19	17.75	12.32	12.83	12.83	13.33	13.89
12H	4H	15.08	15.77	15.56	16.25	16.72	11.38	12.07	11.86	12.55	13.02
	6H	15.71	16.29	16.23	16.80	17.29	11.99	12.56	12.50	13.07	13.56
	8H	16.00	16.51	16.51	17.00	17.56	12.26	12.77	12.77	13.26	13.83