

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P930262

Luminaire Tested: DFN2DS-HX4F0-040DS850-RLL

Issue Date: 11/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P930262
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P333882)
Test Lab: INNOVATION CENTER
Issue Date: 11/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DS-HX4F0-040DS850-RLL
Description: 4 foot, Hexagon Define Geo, with Direct 1in Regressed Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3770.6 lumens
Efficiency: N/A
Efficacy: 99.0 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular (W 4.09' x L: 3.54' x H: 0')
CIE Type: Direct

Input Watts (W): 38.1
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9977
Total Harmonic Distortion (THDi): 0.049
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P930262

CATALOG NUMBER: DFN2DS-HX4F0-040DS850-RLL

Luminous Intensity Polar Plot



TEST NUMBER: P930262

CATALOG NUMBER: DFN2DS-HX4F0-040DS850-RLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	110	106	102	98	107	103	100	97	99	96	94		95	93	91		92
2	101	94	87	82	98	92	86	81	88	83	79		85	81	78		82
3	93	83	76	70	90	82	75	69	79	73	68		76	71	67		74
4	86	75	66	60	83	73	66	60	71	64	59		69	63	58		66
5	79	67	59	53	77	66	58	52	64	57	52		62	56	51		60
6	74	61	53	47	72	60	52	46	58	51	46		57	50	46		55
7	68	56	47	42	67	55	47	42	53	46	41		52	46	41		51
8	64	51	43	38	62	51	43	37	49	42	37		48	42	37		47
9	60	47	39	34	59	47	39	34	46	39	34		44	38	34		44
10	56	44	36	31	55	43	36	31	42	36	31		41	35	31		41

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1363	1363	1363
5°	1368	1346	1354
10°	1358	1324	1313
15°	1342	1285	1248
20°	1321	1229	1167
25°	1299	1165	1089
30°	1268	1100	989
35°	1238	1029	901
40°	1208	955	799
45°	1172	872	707
50°	1136	789	616
55°	1099	699	529
60°	1056	604	439
65°	1007	508	400
70°	949	418	368
75°	877	381	344
80°	774	340	313
85°	608	269	269

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1172 cd/sqm

TEST NUMBER: P930262

CATALOG NUMBER: DFN2DS-HX4F0-040DS850-RLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	171.8	4.6
10°-20°	471.7	12.5
20°-30°	662.3	17.6
30°-40°	721.9	19.1
40°-50°	663.5	17.6
50°-60°	521.1	13.8
60°-70°	339.2	9.0
70°-80°	174.6	4.6
80°-90°	44.6	1.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1305.8	34.6
0°-40°	2027.7	53.8
0°-60°	3212.2	85.2
0°-90°	3770.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3770.6	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1833	1833	1833	1833	1833	
5°	1833	1825	1804	1818	1814	174
15°	1744	1726	1669	1638	1621	491
25°	1583	1530	1420	1352	1327	728
35°	1364	1279	1133	1029	992	854
45°	1115	1004	830	712	672	861
55°	848	718	539	440	408	758
65°	572	438	289	232	227	568
75°	305	189	133	121	120	323
85°	71	36	32	32	32	86
90°	0	0	0	0	0	

TEST NUMBER: P930262

CATALOG NUMBER: DFN2DS-HX4F0-040DS850-RLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1833.4	1833.4	1833.4	1833.4	1833.4
2.5°	1841.7	1833.4	1815.1	1831.8	1828.4
5°	1833.4	1825.1	1803.5	1818.4	1813.5
7.5°	1818.4	1808.6	1785.4	1791.8	1783.6
10°	1798.6	1786.9	1753.8	1748.7	1738.9
12.5°	1773.7	1758.8	1713.8	1704.0	1685.7
15°	1743.8	1725.5	1669.2	1637.7	1621.1
17.5°	1709.0	1682.4	1612.6	1576.2	1549.6
20°	1669.2	1635.9	1552.9	1511.6	1475.0
22.5°	1626.0	1587.9	1491.5	1435.2	1410.4
25°	1582.9	1529.8	1420.2	1352.3	1327.3
27.5°	1531.5	1475.0	1353.9	1275.9	1237.6
30°	1476.7	1413.5	1280.8	1196.3	1151.5
32.5°	1423.6	1347.2	1211.2	1111.7	1070.1
35°	1364.0	1279.2	1133.3	1028.7	992.1
37.5°	1305.8	1214.5	1060.2	945.6	904.3
40°	1244.4	1144.9	983.9	866.1	823.0
42.5°	1181.3	1075.2	907.6	784.7	743.4
45°	1115.0	1003.8	829.6	711.8	671.9
47.5°	1052.0	934.2	755.0	637.1	600.6
50°	982.2	864.5	681.9	567.4	532.7
52.5°	914.1	789.7	612.3	502.7	471.2
55°	847.8	718.4	539.2	439.7	408.2
57.5°	779.8	647.1	474.5	381.6	355.1
60°	710.1	577.3	406.4	321.9	295.4
62.5°	642.2	509.5	348.3	268.8	255.6
65°	572.5	437.9	288.7	232.3	227.2
67.5°	506.1	371.6	232.3	204.1	199.1
70°	436.4	307.0	192.4	175.9	169.1
72.5°	370.1	247.2	160.9	147.7	144.4
75°	305.2	189.1	132.7	121.1	119.6
77.5°	240.7	134.3	104.6	97.9	94.5
80°	180.8	96.3	79.5	73.1	73.1
82.5°	126.1	64.8	54.8	51.3	51.3
85°	71.3	36.5	31.5	31.5	31.5
87.5°	26.6	13.2	13.2	11.6	11.6
90°	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P930262

CATALOG NUMBER: DFN2DS-HX4F0-040DS850-RLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	12.31	13.83	12.68	14.15	14.46	8.27	9.79	8.64	10.11	10.42
	3H	14.08	15.44	14.45	15.77	16.13	9.54	10.90	9.91	11.23	11.59
	4H	14.74	16.02	15.14	16.37	16.75	10.04	11.32	10.44	11.67	12.05
	6H	15.23	16.42	15.64	16.78	17.17	10.42	11.60	10.83	11.97	12.36
	8H	15.40	16.52	15.82	16.91	17.31	10.54	11.67	10.97	12.06	12.46
	12H	15.50	16.58	15.93	16.96	17.39	10.63	11.70	11.06	12.09	12.51
4H	2H	12.42	13.70	12.81	14.04	14.42	8.97	10.25	9.37	10.60	10.97
	3H	14.35	15.41	14.76	15.81	16.21	10.41	11.47	10.82	11.87	12.27
	4H	15.10	16.05	15.53	16.47	16.91	11.01	11.97	11.44	12.38	12.82
	6H	15.69	16.52	16.15	16.96	17.42	11.50	12.33	11.96	12.77	13.23
	8H	15.90	16.68	16.37	17.13	17.59	11.66	12.44	12.12	12.88	13.35
	12H	16.06	16.75	16.54	17.23	17.70	11.78	12.47	12.26	12.95	13.42
8H	4H	15.12	15.90	15.59	16.34	16.81	11.36	12.14	11.83	12.59	13.05
	6H	15.76	16.40	16.26	16.89	17.37	11.95	12.59	12.45	13.08	13.56
	8H	16.01	16.59	16.52	17.10	17.58	12.17	12.75	12.68	13.26	13.75
	12H	16.21	16.72	16.72	17.22	17.78	12.35	12.86	12.86	13.35	13.92
12H	4H	15.11	15.80	15.59	16.28	16.75	11.41	12.10	11.89	12.58	13.05
	6H	15.74	16.32	16.25	16.83	17.32	12.01	12.59	12.53	13.10	13.59
	8H	16.03	16.54	16.53	17.03	17.59	12.29	12.80	12.80	13.29	13.85