

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P930486

Luminaire Tested: DFN2DS-PN2F0-050DS940-RLL

Issue Date: 11/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P930486
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P333882)
Test Lab: INNOVATION CENTER
Issue Date: 11/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DS-PN2F0-050DS940-RLL
Description: 2 foot, Pentagon Define Geo, with Direct 1in Regressed Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3791.0 lumens
Efficiency: N/A
Efficacy: 70.2 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular (W 2.29' x L: 2.17' x H: 0')
CIE Type: Direct

Input Watts (W): 54
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9821
Total Harmonic Distortion (THDi): 0.08
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P930486

CATALOG NUMBER: DFN2DS-PN2F0-050DS940-RLL

Luminous Intensity Polar Plot



TEST NUMBER: P930486

CATALOG NUMBER: DFN2DS-PN2F0-050DS940-RLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	110	106	102	98	107	103	100	97	99	96	94		95	93	91		92
2	101	94	87	82	98	92	86	81	88	83	79		85	81	78		82
3	93	83	76	70	90	82	75	69	79	73	68		76	71	67		74
4	86	75	66	60	83	73	66	60	71	64	59		69	63	58		66
5	79	67	59	53	77	66	58	52	64	57	52		62	56	51		60
6	74	61	53	47	72	60	52	46	58	51	46		57	50	46		55
7	68	56	47	42	67	55	47	42	53	46	41		52	46	41		51
8	64	51	43	38	62	51	43	37	49	42	37		48	42	37		47
9	60	47	39	34	59	47	39	34	46	39	34		44	38	34		44
10	56	44	36	31	55	43	36	31	42	36	31		41	35	31		41

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	3992	3992	3992
5°	4008	3942	3964
10°	3977	3878	3845
15°	3931	3763	3655
20°	3868	3599	3418
25°	3803	3412	3189
30°	3713	3221	2895
35°	3626	3013	2637
40°	3537	2797	2339
45°	3434	2555	2069
50°	3328	2310	1805
55°	3219	2047	1550
60°	3093	1770	1286
65°	2949	1488	1171
70°	2779	1225	1077
75°	2568	1116	1006
80°	2268	998	916
85°	1782	788	788

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 3434 cd/sqm

TEST NUMBER: P930486

CATALOG NUMBER: DFN2DS-PN2F0-050DS940-RLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	172.8	4.6
10°-20°	474.3	12.5
20°-30°	665.8	17.6
30°-40°	725.8	19.1
40°-50°	667.1	17.6
50°-60°	523.9	13.8
60°-70°	341.0	9.0
70°-80°	175.5	4.6
80°-90°	44.8	1.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1312.9	34.6
0°-40°	2038.7	53.8
0°-60°	3229.7	85.2
0°-90°	3791.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3791.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1843	1843	1843	1843	1843	
5°	1843	1835	1813	1828	1823	175
15°	1753	1735	1678	1646	1630	494
25°	1591	1538	1428	1360	1334	732
35°	1371	1286	1139	1034	998	858
45°	1121	1009	834	716	676	866
55°	852	722	542	442	410	762
65°	576	440	290	234	228	571
75°	307	190	133	122	120	325
85°	72	37	32	32	32	86
90°	0	0	0	0	0	

TEST NUMBER: P930486

CATALOG NUMBER: DFN2DS-PN2F0-050DS940-RLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1843.3	1843.3	1843.3	1843.3	1843.3
2.5°	1851.6	1843.3	1824.9	1841.7	1838.3
5°	1843.3	1835.0	1813.3	1828.2	1823.3
7.5°	1828.2	1818.3	1795.0	1801.6	1793.2
10°	1808.3	1796.6	1763.3	1758.2	1748.2
12.5°	1783.3	1768.3	1723.2	1713.3	1694.8
15°	1753.2	1734.9	1678.2	1646.5	1629.9
17.5°	1718.2	1691.5	1621.4	1584.7	1558.0
20°	1678.2	1644.8	1561.4	1519.8	1483.0
22.5°	1634.9	1596.4	1499.6	1443.0	1418.0
25°	1591.4	1538.0	1427.9	1359.6	1334.4
27.5°	1539.8	1483.0	1361.2	1282.8	1244.4
30°	1484.7	1421.2	1287.8	1202.8	1157.6
32.5°	1431.3	1354.5	1217.8	1117.7	1075.9
35°	1371.3	1286.2	1139.4	1034.3	997.5
37.5°	1312.8	1221.1	1066.0	950.8	909.2
40°	1251.1	1151.1	989.1	870.8	827.4
42.5°	1187.8	1081.0	912.5	789.0	747.4
45°	1121.1	1009.2	834.1	715.6	675.5
47.5°	1057.6	939.3	759.1	640.5	603.9
50°	987.6	869.2	685.7	570.4	535.6
52.5°	919.1	794.0	615.6	505.5	473.8
55°	852.4	722.3	542.1	442.1	410.4
57.5°	784.1	650.6	477.1	383.7	357.0
60°	714.0	580.5	408.6	323.7	296.9
62.5°	645.6	512.2	350.3	270.3	257.0
65°	575.5	440.4	290.3	233.6	228.5
67.5°	508.8	373.7	233.6	205.2	200.2
70°	438.8	308.6	193.5	176.8	170.1
72.5°	372.1	248.5	161.8	148.5	145.1
75°	306.9	190.1	133.4	121.8	120.2
77.5°	241.9	135.0	105.2	98.4	95.0
80°	181.8	96.8	80.0	73.4	73.4
82.5°	126.8	65.1	55.0	51.6	51.6
85°	71.7	36.7	31.7	31.7	31.7
87.5°	26.8	13.3	13.3	11.7	11.7
90°	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P930486

CATALOG NUMBER: DFN2DS-PN2F0-050DS940-RLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	16.04	17.57	16.41	17.88	18.19	12.01	13.53	12.37	13.84	14.15
	3H	17.81	19.18	18.19	19.50	19.86	13.27	14.64	13.65	14.96	15.33
	4H	18.48	19.76	18.88	20.11	20.48	13.77	15.05	14.17	15.40	15.78
	6H	18.97	20.15	19.38	20.51	20.91	14.15	15.34	14.57	15.70	16.09
	8H	19.13	20.26	19.56	20.65	21.05	14.28	15.40	14.70	15.79	16.19
	12H	19.23	20.31	19.66	20.69	21.12	14.36	15.44	14.79	15.82	16.25
4H	2H	16.15	17.43	16.55	17.78	18.16	12.70	13.98	13.10	14.33	14.71
	3H	18.08	19.14	18.49	19.54	19.95	14.14	15.21	14.55	15.61	16.01
	4H	18.83	19.79	19.26	20.20	20.64	14.74	15.70	15.18	16.12	16.55
	6H	19.42	20.26	19.88	20.70	21.16	15.23	16.06	15.69	16.51	16.97
	8H	19.64	20.42	20.10	20.86	21.33	15.39	16.17	15.86	16.61	17.08
	12H	19.79	20.49	20.27	20.96	21.44	15.51	16.20	15.99	16.68	17.15
8H	4H	18.86	19.63	19.32	20.08	20.54	15.10	15.87	15.56	16.32	16.79
	6H	19.49	20.14	19.99	20.63	21.10	15.68	16.33	16.18	16.82	17.29
	8H	19.74	20.32	20.26	20.83	21.32	15.90	16.48	16.42	16.99	17.48
	12H	19.95	20.46	20.46	20.95	21.51	16.08	16.59	16.59	17.08	17.65
12H	4H	18.84	19.53	19.32	20.01	20.48	15.14	15.84	15.62	16.31	16.78
	6H	19.47	20.05	19.99	20.56	21.05	15.75	16.32	16.26	16.83	17.32
	8H	19.76	20.27	20.27	20.76	21.32	16.02	16.53	16.53	17.02	17.59