

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P930522

Luminaire Tested: DFN2DS-PN3F0-030DS940-RLL

Issue Date: 11/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P930522
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P333882)
Test Lab: INNOVATION CENTER
Issue Date: 11/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DS-PN3F0-030DS940-RLL
Description: 3 foot, Pentagon Define Geo, with Direct 1in Regressed Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2274.6 lumens
Efficiency: N/A
Efficacy: 80.9 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular (W 3.11' x L: 2.96' x H: 0')
CIE Type: Direct

Input Watts (W): 28.1
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.099
Total Harmonic Distortion (THDi): 0.979
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P930522

CATALOG NUMBER: DFN2DS-PN3F0-030DS940-RLL

Luminous Intensity Polar Plot



TEST NUMBER: P930522

CATALOG NUMBER: DFN2DS-PN3F0-030DS940-RLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	110	106	102	98	107	103	100	97	99	96	94		95	93	91		92
2	101	94	87	82	98	92	86	81	88	83	79		85	81	78		82
3	93	83	76	70	90	82	75	69	79	73	68		76	71	67		74
4	86	75	66	60	83	73	66	60	71	64	59		69	63	58		66
5	79	67	59	53	77	66	58	52	64	57	52		62	56	51		60
6	74	61	53	47	72	60	52	46	58	51	46		57	50	46		55
7	68	56	47	42	67	55	47	42	53	46	41		52	46	41		51
8	64	51	43	38	62	51	43	37	49	42	37		48	42	37		47
9	60	47	39	34	59	47	39	34	46	39	34		44	38	34		44
10	56	44	36	31	55	43	36	31	42	36	31		41	35	31		41

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1293	1293	1293
5°	1298	1277	1284
10°	1288	1256	1245
15°	1273	1219	1183
20°	1253	1165	1107
25°	1232	1105	1033
30°	1202	1043	938
35°	1174	976	854
40°	1146	906	758
45°	1112	827	670
50°	1078	748	584
55°	1042	663	502
60°	1001	573	417
65°	955	482	379
70°	900	396	349
75°	832	362	326
80°	734	323	297
85°	577	255	255

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1112 cd/sqm

TEST NUMBER: P930522

CATALOG NUMBER: DFN2DS-PN3F0-030DS940-RLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	103.7	4.6
10°-20°	284.6	12.5
20°-30°	399.5	17.6
30°-40°	435.5	19.1
40°-50°	400.3	17.6
50°-60°	314.3	13.8
60°-70°	204.6	9.0
70°-80°	105.3	4.6
80°-90°	26.9	1.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	787.7	34.6
0°-40°	1223.2	53.8
0°-60°	1937.8	85.2
0°-90°	2274.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2274.6	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1106	1106	1106	1106	1106	
5°	1106	1101	1088	1097	1094	105
15°	1052	1041	1007	988	978	296
25°	955	923	857	816	801	439
35°	823	772	684	621	598	515
45°	673	606	500	429	405	519
55°	511	433	325	265	246	457
65°	345	264	174	140	137	342
75°	184	114	80	73	72	195
85°	43	22	19	19	19	52
90°	0	0	0	0	0	

TEST NUMBER: P930522

CATALOG NUMBER: DFN2DS-PN3F0-030DS940-RLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1106.0	1106.0	1106.0	1106.0	1106.0
2.5°	1111.0	1106.0	1094.9	1105.0	1103.0
5°	1106.0	1101.0	1088.0	1097.0	1093.9
7.5°	1097.0	1091.0	1077.0	1080.9	1075.9
10°	1084.9	1078.0	1058.0	1054.9	1049.0
12.5°	1070.0	1060.9	1033.9	1027.9	1016.9
15°	1051.9	1040.9	1006.9	987.9	977.9
17.5°	1030.9	1014.9	972.8	950.9	934.8
20°	1006.9	986.8	936.8	911.9	889.8
22.5°	980.9	957.8	899.8	865.8	850.8
25°	954.9	922.8	856.8	815.7	800.7
27.5°	923.8	889.8	816.7	769.7	746.6
30°	890.8	852.8	772.7	721.7	694.6
32.5°	858.7	812.7	730.7	670.6	645.5
35°	822.8	771.7	683.6	620.6	598.5
37.5°	787.7	732.6	639.6	570.4	545.5
40°	750.7	690.7	593.5	522.4	496.5
42.5°	712.6	648.7	547.5	473.4	448.4
45°	672.7	605.5	500.5	429.3	405.3
47.5°	634.6	563.6	455.5	384.3	362.3
50°	592.6	521.5	411.4	342.3	321.3
52.5°	551.4	476.4	369.4	303.3	284.3
55°	511.4	433.3	325.2	265.3	246.3
57.5°	470.4	390.3	286.3	230.2	214.2
60°	428.3	348.3	245.2	194.2	178.2
62.5°	387.4	307.3	210.2	162.2	154.2
65°	345.3	264.2	174.1	140.1	137.1
67.5°	305.3	224.2	140.1	123.1	120.1
70°	263.2	185.2	116.0	106.1	102.0
72.5°	223.2	149.1	97.0	89.1	87.1
75°	184.1	114.1	80.1	73.1	72.1
77.5°	145.1	81.0	63.1	59.1	57.0
80°	109.1	58.1	48.0	44.1	44.1
82.5°	76.0	39.1	33.0	31.0	31.0
85°	43.0	21.9	19.0	19.0	19.0
87.5°	16.1	7.9	7.9	7.0	7.0
90°	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P930522

CATALOG NUMBER: DFN2DS-PN3F0-030DS940-RLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	12.13	13.65	12.49	13.96	14.28	8.09	9.61	8.45	9.92	10.24
	3H	13.89	15.26	14.27	15.58	15.95	9.35	10.72	9.73	11.05	11.41
	4H	14.56	15.84	14.96	16.19	16.57	9.85	11.14	10.25	11.48	11.86
	6H	15.05	16.23	15.46	16.60	16.99	10.24	11.42	10.65	11.79	12.18
	8H	15.21	16.34	15.64	16.73	17.13	10.36	11.49	10.79	11.88	12.28
	12H	15.32	16.39	15.75	16.78	17.21	10.44	11.52	10.87	11.90	12.33
4H	2H	12.23	13.51	12.63	13.86	14.24	8.78	10.06	9.18	10.41	10.79
	3H	14.16	15.23	14.57	15.63	16.03	10.23	11.29	10.64	11.69	12.09
	4H	14.91	15.87	15.35	16.29	16.72	10.83	11.78	11.26	12.20	12.64
	6H	15.51	16.34	15.96	16.78	17.24	11.31	12.15	11.77	12.59	13.05
	8H	15.72	16.50	16.18	16.94	17.41	11.48	12.25	11.94	12.70	13.17
	12H	15.87	16.57	16.36	17.05	17.52	11.59	12.29	12.08	12.77	13.24
8H	4H	14.94	15.72	15.40	16.16	16.63	11.18	11.96	11.64	12.40	12.87
	6H	15.58	16.22	16.07	16.71	17.19	11.77	12.41	12.26	12.90	13.38
	8H	15.83	16.40	16.34	16.91	17.40	11.99	12.56	12.50	13.07	13.56
	12H	16.03	16.54	16.54	17.03	17.60	12.17	12.68	12.68	13.17	13.73
12H	4H	14.92	15.62	15.40	16.10	16.57	11.22	11.92	11.71	12.40	12.87
	6H	15.56	16.13	16.07	16.64	17.13	11.83	12.41	12.34	12.92	13.41
	8H	15.84	16.35	16.35	16.84	17.41	12.10	12.61	12.61	13.11	13.67