

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P930667

Luminaire Tested: DFN2DS-PN4F0-050DS950-FLL

Issue Date: 11/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P930667
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P333812)
Test Lab: INNOVATION CENTER
Issue Date: 11/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DS-PN4F0-050DS950-FLL
Description: 4 foot, Pentagon Define Geo, with Direct Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4677.7 lumens
Efficiency: N/A
Efficacy: 95.9 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.16 / 1.29
Luminous Opening: Rectangular (W 3.94' x L: 3.74' x H: 0')
CIE Type: Direct

Input Watts (W): 48.8
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9951
Total Harmonic Distortion (THDi): 0.07
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P930667

CATALOG NUMBER: DFN2DS-PN4F0-050DS950-FLL

Luminous Intensity Polar Plot



TEST NUMBER: P930667

CATALOG NUMBER: DFN2DS-PN4F0-050DS950-FLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	109	104	100	96	106	102	98	95	98	95	92		94	91	89		90
2	99	91	85	79	97	89	83	78	86	81	76		83	78	74		80
3	91	80	72	66	88	79	71	65	76	69	64		73	68	63		71
4	83	71	63	56	81	70	62	56	68	61	55		65	59	54		63
5	77	64	55	49	75	63	55	48	61	53	48		59	52	47		57
6	71	58	49	43	69	57	48	42	55	48	42		53	47	42		52
7	66	52	44	38	64	52	43	38	50	43	37		49	42	37		47
8	61	48	40	34	60	47	39	34	46	39	33		45	38	33		44
9	57	44	36	30	56	43	36	30	42	35	30		41	35	30		40
10	54	41	33	28	53	40	33	28	39	32	27		38	32	27		37

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1342	1342	1342
5°	1347	1328	1336
10°	1339	1314	1321
15°	1323	1297	1296
20°	1299	1272	1270
25°	1276	1240	1240
30°	1246	1211	1201
35°	1218	1177	1160
40°	1183	1142	1120
45°	1148	1108	1080
50°	1110	1072	1034
55°	1071	1030	992
60°	1027	981	945
65°	980	931	889
70°	921	871	830
75°	837	802	783
80°	744	721	684
85°	606	578	518

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1148 cd/sqm

TEST NUMBER: P930667

CATALOG NUMBER: DFN2DS-PN4F0-050DS950-FLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	173.0	3.7
10°-20°	486.9	10.4
20°-30°	715.5	15.3
30°-40°	831.0	17.8
40°-50°	830.0	17.7
50°-60°	723.7	15.5
60°-70°	535.0	11.4
70°-80°	302.7	6.5
80°-90°	79.9	1.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1375.4	29.4
0°-40°	2206.5	47.2
0°-60°	3760.2	80.4
0°-90°	4677.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4677.7	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1838	1838	1838	1838	1838	
5°	1838	1832	1812	1826	1823	175
15°	1750	1740	1717	1724	1715	493
25°	1584	1570	1540	1543	1540	729
35°	1367	1349	1321	1310	1301	853
45°	1112	1100	1073	1054	1047	858
55°	842	831	810	788	780	752
65°	568	557	539	523	514	561
75°	297	294	284	274	278	317
85°	72	71	69	64	62	85
90°	0	0	0	0	0	

TEST NUMBER: P930667

CATALOG NUMBER: DFN2DS-PN4F0-050DS950-FLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1838.5	1838.5	1838.5	1838.5	1838.5
2.5°	1849.2	1840.4	1820.9	1838.5	1835.2
5°	1838.5	1831.6	1812.0	1826.1	1822.8
7.5°	1826.1	1815.6	1796.2	1810.4	1806.8
10°	1806.8	1794.5	1773.3	1787.3	1782.1
12.5°	1780.2	1769.7	1748.5	1757.3	1753.7
15°	1750.1	1739.7	1716.6	1723.8	1714.9
17.5°	1713.0	1702.5	1679.5	1688.2	1679.5
20°	1672.4	1661.9	1637.1	1642.3	1635.4
22.5°	1631.8	1615.9	1592.8	1592.8	1589.2
25°	1584.0	1569.9	1539.9	1543.3	1539.9
27.5°	1530.9	1518.5	1495.7	1490.4	1481.6
30°	1478.0	1463.8	1437.3	1432.1	1425.0
32.5°	1421.4	1410.9	1382.5	1371.9	1364.8
35°	1366.6	1349.0	1320.6	1310.0	1301.2
37.5°	1304.7	1288.8	1260.4	1248.1	1239.3
40°	1241.2	1226.9	1198.5	1182.8	1175.7
42.5°	1179.3	1165.0	1136.8	1119.0	1108.5
45°	1112.1	1099.7	1073.0	1053.8	1046.6
47.5°	1046.6	1034.2	1006.0	986.4	975.9
50°	977.6	968.8	944.1	919.3	910.4
52.5°	910.4	898.0	875.2	855.7	843.3
55°	841.6	830.9	809.7	788.5	779.7
57.5°	772.5	763.7	740.7	719.5	712.3
60°	703.6	696.7	671.9	652.3	647.1
62.5°	636.5	624.1	606.4	588.7	581.6
65°	567.6	556.9	539.2	523.3	514.5
67.5°	496.9	487.9	472.1	459.7	452.6
70°	431.4	424.3	408.3	396.0	389.1
72.5°	364.3	357.1	348.3	335.9	330.7
75°	296.9	293.5	284.5	274.0	277.6
77.5°	236.9	229.7	226.2	220.9	215.7
80°	176.9	175.0	171.4	166.2	162.6
82.5°	120.2	120.2	118.5	111.4	111.4
85°	72.4	70.7	69.0	63.6	61.9
87.5°	31.8	28.4	24.8	19.5	17.7
90°	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P930667

CATALOG NUMBER: DFN2DS-PN4F0-050DS950-FLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	12.30	13.91	12.67	14.23	14.54	11.86	13.47	12.23	13.78	14.10
	3H	14.05	15.51	14.43	15.84	16.20	13.56	15.02	13.94	15.34	15.71
	4H	14.70	16.07	15.10	16.42	16.79	14.21	15.58	14.60	15.92	16.30
	6H	15.17	16.44	15.58	16.80	17.19	14.67	15.94	15.08	16.30	16.69
	8H	15.31	16.52	15.74	16.91	17.31	14.81	16.02	15.23	16.41	16.81
	12H	15.40	16.56	15.83	16.95	17.37	14.89	16.05	15.32	16.43	16.86
4H	2H	12.86	14.23	13.26	14.58	14.96	12.51	13.88	12.91	14.23	14.60
	3H	14.84	15.99	15.25	16.38	16.78	14.43	15.58	14.84	15.98	16.38
	4H	15.62	16.65	16.05	17.07	17.50	15.19	16.23	15.62	16.64	17.08
	6H	16.21	17.12	16.67	17.56	18.01	15.78	16.69	16.24	17.13	17.58
	8H	16.40	17.25	16.86	17.69	18.16	15.96	16.81	16.43	17.25	17.72
	12H	16.53	17.29	17.01	17.77	18.24	16.08	16.84	16.56	17.32	17.79
8H	4H	15.89	16.74	16.35	17.18	17.64	15.52	16.36	15.98	16.80	17.27
	6H	16.60	17.31	17.10	17.80	18.27	16.22	16.93	16.72	17.41	17.89
	8H	16.86	17.49	17.37	18.00	18.49	16.47	17.10	16.98	17.61	18.10
	12H	17.06	17.62	17.57	18.11	18.67	16.65	17.21	17.16	17.70	18.26
12H	4H	15.92	16.68	16.40	17.15	17.62	15.55	16.31	16.03	16.79	17.26
	6H	16.65	17.28	17.16	17.79	18.27	16.28	16.91	16.79	17.42	17.91
	8H	16.96	17.52	17.47	18.01	18.57	16.59	17.14	17.09	17.63	18.19