

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P931330

Luminaire Tested: DFN2DS-TR3F0-030DS935-RLL

Issue Date: 11/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P931330
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P333882)
Test Lab: INNOVATION CENTER
Issue Date: 11/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DS-TR3F0-030DS935-RLL
Description: 3 foot, Triangle Define Geo, with Direct 1in Regressed Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2193.0 lumens
Efficiency: N/A
Efficacy: 77.8 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular (W 3.16' x L: 2.74' x H: 0')
CIE Type: Direct

Input Watts (W): 28.2
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9968
Total Harmonic Distortion (THDi): 0.064
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P931330

CATALOG NUMBER: DFN2DS-TR3F0-030DS935-RLL

Luminous Intensity Polar Plot



TEST NUMBER: P931330

CATALOG NUMBER: DFN2DS-TR3F0-030DS935-RLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	110	106	102	98	107	103	100	97	99	96	94		95	93	91		92
2	101	94	87	82	98	92	86	81	88	83	79		85	81	78		82
3	93	83	76	70	90	82	75	69	79	73	68		76	71	67		74
4	86	75	66	60	83	73	66	60	71	64	59		69	63	58		66
5	79	67	59	53	77	66	58	52	64	57	52		62	56	51		60
6	74	61	53	47	72	60	52	46	58	51	46		57	50	46		55
7	68	56	47	42	67	55	47	42	53	46	41		52	46	41		51
8	64	51	43	38	62	51	43	37	49	42	37		48	42	37		47
9	60	47	39	34	59	47	39	34	46	39	34		44	38	34		44
10	56	44	36	31	55	43	36	31	42	36	31		41	35	31		41

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1329	1329	1329
5°	1334	1312	1319
10°	1324	1291	1280
15°	1308	1252	1216
20°	1287	1198	1138
25°	1266	1136	1061
30°	1236	1072	964
35°	1207	1003	878
40°	1177	931	779
45°	1143	850	689
50°	1108	769	601
55°	1071	681	516
60°	1029	589	428
65°	982	495	390
70°	925	408	359
75°	855	372	335
80°	755	332	305
85°	593	262	262

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1143 cd/sqm

TEST NUMBER: P931330

CATALOG NUMBER: DFN2DS-TR3F0-030DS935-RLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	99.9	4.6
10°-20°	274.3	12.5
20°-30°	385.2	17.6
30°-40°	419.9	19.1
40°-50°	385.9	17.6
50°-60°	303.1	13.8
60°-70°	197.3	9.0
70°-80°	101.5	4.6
80°-90°	25.9	1.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	759.4	34.6
0°-40°	1179.3	53.8
0°-60°	1868.3	85.2
0°-90°	2193.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2193.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1066	1066	1066	1066	1066	
5°	1066	1062	1049	1058	1055	101
15°	1014	1004	971	952	943	286
25°	921	890	826	786	772	423
35°	793	744	659	598	577	497
45°	648	584	482	414	391	501
55°	493	418	314	256	237	441
65°	333	255	168	135	132	330
75°	178	110	77	70	70	188
85°	42	21	18	18	18	50
90°	0	0	0	0	0	

TEST NUMBER: P931330

CATALOG NUMBER: DFN2DS-TR3F0-030DS935-RLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1066.3	1066.3	1066.3	1066.3	1066.3
2.5°	1071.1	1066.3	1055.6	1065.4	1063.5
5°	1066.3	1061.5	1048.9	1057.6	1054.7
7.5°	1057.6	1051.9	1038.4	1042.1	1037.3
10°	1046.0	1039.3	1020.0	1017.0	1011.4
12.5°	1031.6	1022.9	996.8	991.1	980.4
15°	1014.2	1003.5	970.8	952.4	942.8
17.5°	993.9	978.5	937.9	916.8	901.3
20°	970.8	951.4	903.2	879.2	857.8
22.5°	945.7	923.5	867.5	834.7	820.3
25°	920.6	889.7	826.0	786.5	771.9
27.5°	890.7	857.8	787.4	742.1	719.8
30°	858.9	822.2	744.9	695.8	669.7
32.5°	827.9	783.5	704.5	646.5	622.4
35°	793.3	744.0	659.1	598.3	577.1
37.5°	759.5	706.3	616.6	550.0	526.0
40°	723.8	665.9	572.2	503.7	478.7
42.5°	687.1	625.4	527.9	456.4	432.3
45°	648.5	583.8	482.5	413.9	390.8
47.5°	611.8	543.3	439.1	370.5	349.3
50°	571.3	502.8	396.6	330.0	309.8
52.5°	531.7	459.3	356.1	292.4	274.1
55°	493.0	417.8	313.6	255.8	237.4
57.5°	453.6	376.3	276.1	222.0	206.5
60°	413.0	335.8	236.4	187.2	171.8
62.5°	373.5	296.3	202.6	156.3	148.7
65°	332.9	254.7	167.9	135.1	132.2
67.5°	294.4	216.1	135.1	118.7	115.8
70°	253.8	178.5	111.9	102.3	98.4
72.5°	215.2	143.7	93.6	85.9	83.9
75°	177.5	110.0	77.2	70.4	69.5
77.5°	139.9	78.1	60.8	56.9	55.0
80°	105.2	56.0	46.3	42.5	42.5
82.5°	73.3	37.7	31.8	29.9	29.9
85°	41.5	21.2	18.3	18.3	18.3
87.5°	15.5	7.7	7.7	6.8	6.8
90°	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P931330

CATALOG NUMBER: DFN2DS-TR3F0-030DS935-RLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	12.22	13.74	12.59	14.06	14.37	8.18	9.71	8.55	10.02	10.33
	3H	13.99	15.35	14.36	15.68	16.04	9.45	10.81	9.83	11.14	11.50
	4H	14.65	15.93	15.05	16.28	16.66	9.95	11.23	10.35	11.58	11.96
	6H	15.14	16.33	15.55	16.69	17.08	10.33	11.51	10.74	11.88	12.27
	8H	15.31	16.43	15.73	16.82	17.22	10.46	11.58	10.88	11.97	12.37
	12H	15.41	16.49	15.84	16.87	17.30	10.54	11.61	10.97	12.00	12.43
4H	2H	12.33	13.61	12.73	13.95	14.33	8.88	10.16	9.28	10.51	10.89
	3H	14.26	15.32	14.67	15.72	16.12	10.32	11.38	10.73	11.78	12.19
	4H	15.01	15.97	15.44	16.38	16.82	10.92	11.88	11.35	12.29	12.73
	6H	15.60	16.43	16.06	16.87	17.33	11.41	12.24	11.87	12.68	13.14
	8H	15.81	16.59	16.28	17.04	17.50	11.57	12.35	12.03	12.79	13.26
	12H	15.97	16.66	16.45	17.14	17.61	11.69	12.38	12.17	12.86	13.33
8H	4H	15.03	15.81	15.50	16.25	16.72	11.27	12.05	11.74	12.50	12.96
	6H	15.67	16.31	16.17	16.80	17.28	11.86	12.50	12.36	13.00	13.47
	8H	15.92	16.50	16.43	17.01	17.50	12.08	12.66	12.60	13.17	13.66
	12H	16.13	16.63	16.63	17.13	17.69	12.26	12.77	12.77	13.26	13.83
12H	4H	15.02	15.71	15.50	16.19	16.66	11.32	12.01	11.80	12.49	12.96
	6H	15.65	16.23	16.16	16.74	17.23	11.92	12.50	12.44	13.01	13.50
	8H	15.94	16.45	16.45	16.94	17.50	12.20	12.71	12.71	13.20	13.76