

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P997887

Luminaire Tested: SA2XXDIP-B1005D330UB40-4F0-XX-W2A-D1

Issue Date: 5/6/2025

Test Information

Test Method: LM-79-2019
Report Number: P997887
REPORT IS A COMBINATION OF REPORTS P983624 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/6/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: SA2XXDIP-B1005D330UB40-4F0-XX-W2A-D1
Description: Define 2 Direct/Indirect Pendant with 4000K BioUP LEDs {m-DER=0.865} {m-EER=0.951}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 5193.0 lumens
Efficiency: N/A
Efficacy: 73.6 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.31 / 1.42
Luminous Opening: Rectangular w/ Sides (W: 0.17' x L: 4' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 70.6
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P997887

CATALOG NUMBER: SA2XXDIP-B1005D330UB40-4F0-XX-W2A-D1

Luminous Intensity Polar Plot



TEST NUMBER: P997887

CATALOG NUMBER: SA2XXDIP-B1005D330UB40-4F0-XX-W2A-D1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	112	112	112	112	105	105	105	105	94	94	94	83	83	83	73	73	73
1	100	95	90	85	94	89	85	81	79	76	73	70	68	65	62	60	58
2	90	81	74	68	85	77	70	65	68	63	59	60	56	53	53	50	47
3	82	71	63	56	77	67	59	53	60	54	49	53	48	44	46	43	39
4	75	62	54	47	70	59	51	45	53	46	41	47	41	37	41	37	33
5	68	55	46	40	64	53	44	38	47	40	35	42	36	32	37	32	29
6	63	50	41	34	59	47	39	33	42	35	30	38	32	28	33	29	25
7	58	45	36	30	55	43	35	29	38	31	27	34	29	24	30	26	22
8	54	41	32	27	51	39	31	26	35	28	24	31	26	22	28	23	20
9	50	37	29	24	47	35	28	23	32	26	21	29	23	19	26	21	18
10	47	34	26	21	44	33	25	21	29	23	19	27	21	18	24	19	16

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	16681	16681	16681
5°	16757	15969	15880
10°	16645	15416	15191
15°	16409	14845	14486
20°	16112	14243	13816
25°	15821	13668	13209
30°	15411	13083	12607
35°	14996	12520	12166
40°	14558	12033	11726
45°	14144	11591	11345
50°	13695	11183	10966
55°	13227	10751	10583
60°	12651	10300	10179
65°	12055	9782	9714
70°	11377	9225	9213
75°	10511	8668	8741
80°	9141	8090	8252
85°	7769	7544	7828

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 14144 cd/sqm

TEST NUMBER: P997887

CATALOG NUMBER: SA2XXDIP-B1005D330UB40-4F0-XX-W2A-D1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	99.9	1.9
10°-20°	286.5	5.5
20°-30°	434.1	8.4
30°-40°	528.7	10.2
40°-50°	568.8	11.0
50°-60°	552.4	10.6
60°-70°	482.4	9.3
70°-80°	371.3	7.1
80°-90°	249.9	4.8
90°-100°	197.5	3.8
100°-110°	207.6	4.0
110°-120°	223.6	4.3
120°-130°	231.4	4.5
130°-140°	227.4	4.4
140°-150°	207.3	4.0
150°-160°	171.1	3.3
160°-170°	113.5	2.2
170°-180°	39.7	0.8
0°-30°	820.6	15.8
0°-40°	1349.2	26.0
0°-60°	2470.4	47.6
0°-90°	3573.9	68.8
90°-120°	628.7	12.1
90°-150°	1294.8	24.9
90°-180°	1619.0	31.2
0°-180°	5193.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1054	1054	1054	1054	1054	
5°	1057	1052	1043	1052	1051	100
15°	1008	1011	1011	1025	1023	284
25°	916	927	941	959	964	421
35°	790	816	845	878	889	494
45°	648	689	742	790	805	500
55°	496	551	631	686	706	444
65°	339	414	504	567	586	337
75°	188	273	371	437	457	199
85°	55	150	247	312	333	58
90°	16	108	214	274	293	12
95°	31	106	198	256	274	30
105°	84	129	209	263	280	89
115°	148	166	234	280	296	145
125°	209	212	260	300	313	187
135°	268	272	288	319	330	207
145°	323	326	328	337	343	202
155°	369	370	371	373	372	170
165°	402	402	402	404	402	113
175°	418	417	416	419	417	40
180°	419	419	419	419	419	



TEST NUMBER: P997887

CATALOG NUMBER: SA2XXDIP-B1005D330UB40-4F0-XX-W2A-D1

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1053.8	1053.8	1053.8	1053.8	1053.8
2.5°	1061.5	1056.9	1046.2	1053.8	1050.8
5°	1056.9	1052.3	1043.1	1052.3	1050.8
7.5°	1049.2	1046.2	1038.5	1049.2	1047.7
10°	1040.1	1037.0	1032.4	1044.7	1043.1
12.5°	1024.8	1026.3	1023.3	1035.5	1034.0
15°	1008.0	1011.1	1011.1	1024.8	1023.3
17.5°	986.6	992.7	997.3	1011.1	1011.1
20°	965.2	972.9	979.0	995.8	995.8
22.5°	942.3	951.5	960.7	977.5	980.5
25°	916.4	927.1	940.8	959.1	963.7
27.5°	885.8	902.6	917.9	940.8	943.9
30°	855.3	875.1	895.0	919.4	924.0
32.5°	821.7	844.6	869.0	898.0	907.2
35°	789.6	815.6	844.6	878.2	888.9
37.5°	754.5	783.5	820.1	856.8	867.5
40°	719.3	752.9	794.2	833.9	847.6
42.5°	685.7	719.3	768.2	812.5	826.3
45°	647.6	688.8	742.3	789.6	804.9
47.5°	610.9	655.2	716.3	765.2	782.0
50°	572.7	620.1	688.8	740.7	757.5
52.5°	536.1	586.5	659.8	713.2	731.6
55°	496.4	551.3	630.8	685.7	705.6
57.5°	458.2	519.3	598.7	658.3	678.1
60°	416.9	482.6	569.7	627.7	649.1
62.5°	380.3	449.0	536.1	598.7	618.5
65°	339.1	413.9	504.0	566.6	586.5
67.5°	302.4	380.3	471.9	534.5	555.9
70°	262.7	342.1	436.8	502.5	520.8
72.5°	226.0	308.5	404.7	468.9	491.8
75°	187.9	273.4	371.1	436.8	456.7
77.5°	151.2	239.8	339.1	404.7	426.1
80°	114.5	207.7	307.0	371.1	392.5
82.5°	84.0	175.6	276.4	340.6	360.4
85°	55.0	149.7	247.4	311.6	332.9
87.5°	33.6	125.2	223.0	285.6	305.5
90°	15.7	108.5	214.0	274.4	293.0
92.5°	21.5	105.3	198.9	258.7	277.0
95°	30.6	105.9	198.2	256.3	273.9
97.5°	41.4	110.3	200.2	256.8	275.1
100°	55.6	114.9	201.5	258.0	274.4
102.5°	68.9	121.4	205.3	260.6	277.1
105°	83.6	128.9	209.0	263.3	280.1
107.5°	99.8	137.9	214.3	266.6	281.6
110°	113.9	146.6	221.4	270.3	286.0

TEST NUMBER: P997887

CATALOG NUMBER: SA2XXDIP-B1005D330UB40-4F0-XX-W2A-D1

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	130.8	157.4	227.3	275.2	291.2
115°	147.5	166.4	234.4	279.9	295.7
117.5°	162.6	177.6	239.9	284.8	298.9
120°	179.2	188.1	246.4	289.1	304.8
122.5°	194.4	199.4	254.1	294.4	307.4
125°	208.8	212.0	259.7	299.9	313.3
127.5°	224.3	226.6	266.5	303.2	315.9
130°	238.8	241.8	273.2	309.2	320.0
132.5°	255.1	257.0	280.3	313.7	324.8
135°	267.6	271.5	287.5	319.2	330.4
137.5°	283.2	286.3	294.7	323.4	332.7
140°	296.9	298.6	303.5	327.9	335.7
142.5°	311.1	312.8	313.8	332.5	338.8
145°	323.0	325.5	327.6	337.2	343.3
147.5°	335.0	338.2	339.6	341.8	345.0
150°	347.4	349.5	350.9	352.0	350.9
152.5°	358.3	360.5	362.2	363.6	362.2
155°	369.3	370.4	371.4	373.2	372.1
157.5°	378.8	379.5	380.3	382.7	381.0
160°	387.3	388.0	388.4	390.5	389.1
162.5°	395.1	395.1	395.4	397.9	396.2
165°	401.8	401.5	401.5	403.9	402.2
167.5°	407.8	406.8	406.8	409.2	407.5
170°	412.4	411.4	411.0	413.5	411.4
172.5°	415.6	414.5	414.2	416.7	414.5
175°	418.1	417.0	416.3	418.8	416.7
177.5°	419.5	418.4	417.7	419.8	417.7
180°	418.8	418.8	418.8	418.8	418.8

TEST NUMBER: P997887

CATALOG NUMBER: SA2XXDIP-B1005D330UB40-4F0-XX-W2A-D1

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	16.53	17.67	17.30	18.46	19.43	19.61	20.74	20.37	21.54	22.51
	3H	18.01	19.04	18.78	19.85	20.85	22.21	23.24	22.99	24.05	25.05
	4H	18.49	19.48	19.29	20.29	21.30	23.47	24.46	24.27	25.27	26.28
	6H	18.79	19.70	19.60	20.53	21.55	24.78	25.70	25.59	26.52	27.54
	8H	18.86	19.73	19.67	20.57	21.60	25.45	26.32	26.27	27.17	28.19
	12H	18.88	19.72	19.71	20.55	21.61	26.19	27.02	27.01	27.86	28.91
4H	2H	17.61	18.59	18.41	19.40	20.41	19.96	20.95	20.76	21.76	22.77
	3H	19.34	20.17	20.15	21.02	22.05	22.77	23.61	23.58	24.46	25.48
	4H	19.97	20.74	20.79	21.58	22.63	24.20	24.97	25.02	25.82	26.87
	6H	20.40	21.07	21.24	21.94	23.00	25.68	26.36	26.52	27.23	28.28
	8H	20.51	21.15	21.36	22.01	23.08	26.45	27.08	27.29	27.95	29.02
	12H	20.57	21.15	21.43	22.03	23.11	27.29	27.87	28.15	28.75	29.83
8H	4H	20.78	21.42	21.62	22.28	23.35	24.37	25.00	25.21	25.87	26.94
	6H	21.42	21.96	22.29	22.87	23.94	26.01	26.54	26.88	27.45	28.52
	8H	21.65	22.13	22.53	23.03	24.12	26.90	27.38	27.78	28.28	29.37
	12H	21.80	22.23	22.68	23.12	24.25	27.91	28.34	28.79	29.23	30.37
12H	4H	20.99	21.57	21.86	22.45	23.53	24.35	24.93	25.22	25.82	26.89
	6H	21.76	22.24	22.64	23.14	24.23	26.04	26.52	26.91	27.42	28.50
	8H	22.08	22.51	22.96	23.40	24.54	26.98	27.41	27.86	28.30	29.44