

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P997997

Luminaire Tested: SA2XXDIP-B1005D725UB35-4F0-XX-W2A-D

Issue Date: 5/7/2025

Test Information

Test Method: LM-79-2019
Report Number: P997997
REPORT IS A COMBINATION OF REPORTS P983734 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: SA2XXDIP-B1005D725UB35-4F0-XX-W2A-D
Description: Define 2 Direct/Indirect Pendant with 3500K BioUP LEDs {m-DER=0.721} {m-EER=0.792}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 6905.0 lumens
Efficiency: N/A
Efficacy: 83.8 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.31 / 1.42
Luminous Opening: Rectangular w/ Sides (W: 0.17' x L: 4' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 82.4
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P997997

CATALOG NUMBER: SA2XXDIP-B1005D725UB35-4F0-XX-W2A-D

Luminous Intensity Polar Plot



TEST NUMBER: P997997

CATALOG NUMBER: SA2XXDIP-B1005D725UB35-4F0-XX-W2A-D

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	108	108	108	108	100	100	100	100	85	85	85	71	71	71	58	58	58
1	97	92	87	83	89	85	81	77	72	69	66	60	58	56	49	47	46
2	87	79	72	67	80	73	67	62	62	58	54	52	48	45	42	40	38
3	79	69	61	55	73	64	57	51	54	49	44	45	41	38	37	34	31
4	72	61	52	46	66	56	49	43	48	42	37	40	36	32	33	29	27
5	66	54	45	39	61	50	42	37	43	37	32	36	31	27	29	26	23
6	61	48	40	34	56	45	37	32	38	32	28	32	27	24	26	23	20
7	56	43	35	29	52	40	33	28	35	29	24	29	24	21	24	20	18
8	52	39	31	26	48	37	29	24	31	26	21	27	22	19	22	18	16
9	49	36	28	23	45	33	26	22	29	23	19	24	20	17	20	17	14
10	45	33	25	20	42	31	24	19	27	21	17	23	18	15	19	15	13

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	16847	16847	16847
5°	16924	16128	16037
10°	16809	15569	15342
15°	16572	14992	14631
20°	16273	14385	13954
25°	15978	13805	13340
30°	15564	13214	12733
35°	15146	12644	12286
40°	14704	12153	11844
45°	14283	11705	11458
50°	13832	11295	11076
55°	13358	10856	10688
60°	12778	10401	10279
65°	12172	9879	9810
70°	11489	9316	9305
75°	10612	8755	8828
80°	9237	8169	8334
85°	7840	7620	7908

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 14283 cd/sqm

TEST NUMBER: P997997

CATALOG NUMBER: SA2XXDIP-B1005D725UB35-4F0-XX-W2A-D

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	100.9	1.5
10°-20°	289.4	4.2
20°-30°	438.5	6.3
30°-40°	533.9	7.7
40°-50°	574.5	8.3
50°-60°	557.9	8.1
60°-70°	487.2	7.1
70°-80°	375.0	5.4
80°-90°	252.8	3.7
90°-100°	205.2	3.0
100°-110°	245.7	3.6
110°-120°	399.6	5.8
120°-130°	570.8	8.3
130°-140°	576.4	8.3
140°-150°	520.8	7.5
150°-160°	416.1	6.0
160°-170°	268.1	3.9
170°-180°	92.3	1.3
0°-30°	828.7	12.0
0°-40°	1362.6	19.7
0°-60°	2495.0	36.1
0°-90°	3610.0	52.3
90°-120°	850.5	12.3
90°-150°	2518.5	36.5
90°-180°	3295.0	47.7
0°-180°	6905.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1064	1064	1064	1064	1064	
5°	1067	1063	1054	1063	1061	101
15°	1018	1021	1021	1035	1034	287
25°	926	936	950	969	973	426
35°	798	824	853	887	898	498
45°	654	696	750	798	813	505
55°	501	557	637	693	713	448
65°	342	418	509	572	592	340
75°	190	276	375	441	461	201
85°	56	151	250	315	336	59
90°	16	113	218	283	303	13
95°	58	107	205	267	285	64
105°	221	287	176	237	257	237
115°	410	438	525	247	213	403
125°	573	583	645	692	708	512
135°	707	718	740	780	791	547
145°	819	818	830	844	848	512
155°	902	895	904	908	902	415
165°	950	946	948	953	948	268
175°	972	967	968	973	966	92
180°	970	970	970	970	970	

TEST NUMBER: P997997

CATALOG NUMBER: SA2XXDIP-B1005D725UB35-4F0-XX-W2A-D

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1064.3	1064.3	1064.3	1064.3	1064.3
2.5°	1072.0	1067.4	1056.6	1064.3	1061.2
5°	1067.4	1062.8	1053.5	1062.8	1061.2
7.5°	1059.7	1056.6	1048.9	1059.7	1058.1
10°	1050.4	1047.3	1042.7	1055.0	1053.5
12.5°	1035.0	1036.5	1033.5	1045.8	1044.2
15°	1018.0	1021.1	1021.1	1035.0	1033.5
17.5°	996.4	1002.6	1007.2	1021.1	1021.1
20°	974.8	982.6	988.7	1005.7	1005.7
22.5°	951.7	961.0	970.2	987.2	990.3
25°	925.5	936.3	950.2	968.7	973.3
27.5°	894.6	911.6	927.0	950.2	953.2
30°	863.8	883.8	903.9	928.6	933.2
32.5°	829.8	853.0	877.7	907.0	916.2
35°	797.5	823.7	853.0	886.9	897.7
37.5°	762.0	791.3	828.3	865.3	876.1
40°	726.5	760.4	802.1	842.2	856.1
42.5°	692.6	726.5	775.9	820.6	834.5
45°	654.0	695.7	749.6	797.5	812.9
47.5°	617.0	661.7	723.4	772.8	789.7
50°	578.4	626.2	695.7	748.1	765.1
52.5°	541.4	592.3	666.3	720.3	738.8
55°	501.3	556.8	637.0	692.6	712.6
57.5°	462.7	524.4	604.6	664.8	684.9
60°	421.1	487.4	575.3	634.0	655.5
62.5°	384.1	453.5	541.4	604.6	624.7
65°	342.4	418.0	509.0	572.3	592.3
67.5°	305.4	384.1	476.6	539.9	561.5
70°	265.3	345.5	441.1	507.5	526.0
72.5°	228.3	311.6	408.8	473.5	496.7
75°	189.7	276.1	374.8	441.1	461.2
77.5°	152.7	242.2	342.4	408.8	430.3
80°	115.7	209.8	310.0	374.8	396.4
82.5°	84.8	177.4	279.2	344.0	364.0
85°	55.5	151.2	249.9	314.7	336.3
87.5°	33.9	126.5	225.2	288.4	308.5
90°	16.1	113.3	217.6	282.8	302.7
92.5°	31.4	110.3	206.5	268.1	287.3
95°	57.9	107.2	204.8	266.9	284.7
97.5°	92.9	101.7	202.4	261.6	280.8
100°	135.0	96.0	194.2	256.9	275.3
102.5°	179.8	229.3	184.8	248.1	267.1
105°	221.0	286.7	175.5	237.1	256.9
107.5°	270.8	325.3	166.1	226.2	246.0
110°	317.0	362.5	235.4	214.6	234.3



TEST NUMBER: P997997

CATALOG NUMBER: SA2XXDIP-B1005D725UB35-4F0-XX-W2A-D

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	361.9	399.1	458.2	205.2	224.2
115°	409.6	438.4	525.3	246.8	213.3
117.5°	449.4	475.8	552.5	498.4	330.0
120°	495.7	512.4	586.7	638.3	560.6
122.5°	535.0	547.8	618.8	664.7	679.3
125°	573.4	582.6	645.2	691.8	707.8
127.5°	609.9	618.1	670.4	716.0	730.5
130°	644.3	653.9	694.0	738.9	750.5
132.5°	679.4	686.9	717.8	759.6	771.2
135°	707.2	718.5	740.3	779.7	790.6
137.5°	738.1	746.5	761.3	797.7	806.4
140°	768.3	772.4	783.2	814.2	819.9
142.5°	793.5	796.9	806.1	830.2	834.4
145°	818.7	818.0	829.9	844.1	848.3
147.5°	841.8	839.7	851.7	856.7	858.6
150°	864.3	859.4	870.6	874.8	871.3
152.5°	883.2	877.6	888.1	892.4	887.4
155°	901.5	895.2	903.6	907.8	902.2
157.5°	916.2	910.6	916.9	921.8	916.2
160°	928.8	924.6	928.8	933.0	928.1
162.5°	940.1	935.8	939.4	944.3	938.0
165°	949.9	945.7	947.8	952.7	947.8
167.5°	957.6	953.4	955.5	960.4	954.1
170°	963.9	959.7	961.1	966.0	959.7
172.5°	968.1	963.9	965.3	970.2	963.9
175°	971.6	966.7	968.1	973.0	966.0
177.5°	973.0	968.1	968.8	973.7	967.4
180°	969.5	969.5	969.5	969.5	969.5

TEST NUMBER: P997997

CATALOG NUMBER: SA2XXDIP-B1005D725UB35-4F0-XX-W2A-D

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	15.23	16.16	16.15	17.11	18.35	18.30	19.24	19.23	20.19	21.42
	3H	16.69	17.54	17.63	18.50	19.75	20.90	21.74	21.83	22.70	23.96
	4H	17.17	17.97	18.12	18.94	20.20	22.15	22.96	23.10	23.92	25.19
	6H	17.46	18.20	18.42	19.17	20.45	23.45	24.20	24.41	25.17	26.45
	8H	17.52	18.23	18.49	19.22	20.49	24.11	24.83	25.08	25.81	27.09
	12H	17.54	18.22	18.51	19.20	20.50	24.84	25.52	25.81	26.50	27.80
4H	2H	16.28	17.09	17.24	18.05	19.32	18.64	19.44	19.59	20.41	21.67
	3H	18.00	18.68	18.96	19.67	20.95	21.44	22.12	22.40	23.11	24.39
	4H	18.62	19.25	19.60	20.24	21.54	22.85	23.48	23.83	24.47	25.77
	6H	19.04	19.59	20.03	20.60	21.90	24.33	24.88	25.31	25.89	27.19
	8H	19.15	19.67	20.14	20.67	21.99	25.09	25.60	26.07	26.61	27.92
	12H	19.20	19.67	20.21	20.69	22.01	25.92	26.39	26.93	27.41	28.73
8H	4H	19.42	19.93	20.41	20.94	22.25	23.00	23.52	23.99	24.52	25.84
	6H	20.05	20.49	21.07	21.53	22.85	24.64	25.07	25.65	26.12	27.43
	8H	20.28	20.66	21.30	21.69	23.02	25.53	25.91	26.55	26.95	28.28
	12H	20.41	20.76	21.44	21.78	23.16	26.53	26.87	27.55	27.90	29.27
12H	4H	19.62	20.09	20.63	21.11	22.43	22.98	23.45	23.99	24.47	25.79
	6H	20.39	20.78	21.41	21.81	23.14	24.66	25.05	25.68	26.08	27.41
	8H	20.70	21.04	21.72	22.07	23.44	25.60	25.94	26.62	26.96	28.34

END OF REPORT