

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P997759

Luminaire Tested: SA2XXRDP-B675DB35-4F0-XX-W2A-F

Issue Date: 5/2/2025

Test Information

Test Method: LM-79-2019
Report Number: P997759
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1802-639-24)
Test Lab: INNOVATION CENTER
Issue Date: 5/2/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: SA2XXRDP-B675DB35-4F0-XX-W2A-F
Description: Define 2 Regressed Direct Recessed with 3500K BioUP LEDs {m-DER=0.721} {m-EER=0.792}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2342.0 lumens
Efficiency: N/A
Efficacy: 65.2 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular (W 0.17' x L: 4' x H: 0')
CIE Type: Direct

Input Watts (W): 35.9
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P997759

CATALOG NUMBER: SA2XXRDP-B675DB35-4F0-XX-W2A-F

Luminous Intensity Polar Plot



TEST NUMBER: P997759

CATALOG NUMBER: SA2XXRDP-B675DB35-4F0-XX-W2A-F

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				0
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		0
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		100
1	110	106	102	98	107	103	100	97	99	96	94		95	93	91		86
2	101	94	87	82	98	92	86	81	88	83	79		85	81	78		74
3	93	83	76	70	90	82	75	69	79	73	68		76	71	67		64
4	86	75	66	60	83	73	66	60	71	64	59		69	63	58		55
5	79	67	59	53	77	66	58	52	64	57	52		62	56	51		49
6	74	61	53	47	72	60	52	46	58	51	46		57	50	46		43
7	68	56	47	42	67	55	47	42	53	46	41		52	46	41		39
8	64	51	43	38	62	51	43	37	49	42	37		48	42	37		35
9	60	47	39	34	59	47	39	34	46	39	34		44	38	34		32
10	56	44	36	31	55	43	36	31	42	36	31		41	35	31		29

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	18026	18026	18026
5°	18095	17800	17898
10°	17956	17509	17359
15°	17750	16989	16499
20°	17463	16249	15434
25°	17171	15408	14399
30°	16765	14542	13072
35°	16369	13602	11909
40°	15971	12628	10563
45°	15502	11536	9344
50°	15024	10432	8146
55°	14533	9242	6996
60°	13965	7994	5806
65°	13315	6716	5289
70°	12542	5531	4864
75°	11596	5040	4538
80°	10237	4512	4129
85°	8046	3560	3560

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 15502 cd/sqm

TEST NUMBER: P997759

CATALOG NUMBER: SA2XXRDP-B675DB35-4F0-XX-W2A-F

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	106.7	4.6
10°-20°	293.0	12.5
20°-30°	411.3	17.6
30°-40°	448.4	19.1
40°-50°	412.1	17.6
50°-60°	323.6	13.8
60°-70°	210.7	9.0
70°-80°	108.4	4.6
80°-90°	27.7	1.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	811.1	34.6
0°-40°	1259.4	53.8
0°-60°	1995.2	85.2
0°-90°	2342.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2342.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1139	1139	1139	1139	1139	
5°	1139	1134	1120	1130	1126	108
15°	1083	1072	1037	1017	1007	305
25°	983	950	882	840	824	452
35°	847	795	704	639	616	530
45°	692	624	515	442	417	535
55°	527	446	335	273	254	471
65°	356	272	179	144	141	352
75°	190	118	82	75	74	201
85°	44	23	20	20	20	53
90°	0	0	0	0	0	

TEST NUMBER: P997759

CATALOG NUMBER: SA2XXRDP-B675DB35-4F0-XX-W2A-F

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1138.8	1138.8	1138.8	1138.8	1138.8
2.5°	1143.9	1138.8	1127.4	1137.7	1135.7
5°	1138.8	1133.6	1120.2	1129.5	1126.4
7.5°	1129.5	1123.3	1108.9	1113.0	1107.8
10°	1117.1	1109.9	1089.3	1086.2	1080.0
12.5°	1101.7	1092.4	1064.6	1058.4	1047.0
15°	1083.1	1071.8	1036.7	1017.2	1006.8
17.5°	1061.5	1045.0	1001.7	979.0	962.5
20°	1036.7	1016.1	964.6	938.8	916.2
22.5°	1009.9	986.2	926.5	891.4	876.0
25°	983.1	950.2	882.2	839.9	824.4
27.5°	951.2	916.2	840.9	792.5	768.8
30°	917.2	878.0	795.6	743.0	715.2
32.5°	884.2	836.8	752.3	690.5	664.7
35°	847.1	794.6	703.9	638.9	616.3
37.5°	811.0	754.4	658.5	587.4	561.6
40°	772.9	711.1	611.1	537.9	511.2
42.5°	733.8	667.8	563.7	487.4	461.7
45°	692.5	623.5	515.3	442.1	417.4
47.5°	653.4	580.2	468.9	395.7	373.1
50°	610.1	536.9	423.6	352.4	330.8
52.5°	567.8	490.5	380.3	312.3	292.7
55°	526.6	446.2	334.9	273.1	253.5
57.5°	484.4	401.9	294.7	237.0	220.5
60°	441.1	358.6	252.5	199.9	183.4
62.5°	398.8	316.4	216.4	166.9	158.7
65°	355.5	272.1	179.3	144.3	141.2
67.5°	314.3	230.8	144.3	126.8	123.7
70°	271.0	190.7	119.5	109.2	105.1
72.5°	229.8	153.6	100.0	91.7	89.7
75°	189.6	117.5	82.4	75.2	74.2
77.5°	149.4	83.5	64.9	60.8	58.7
80°	112.3	59.8	49.5	45.3	45.3
82.5°	78.3	40.2	34.0	31.9	31.9
85°	44.3	22.7	19.6	19.6	19.6
87.5°	16.5	8.2	8.2	7.2	7.2
90°	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P997759

CATALOG NUMBER: SA2XXRDP-B675DB35-4F0-XX-W2A-F

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	21.28	22.80	21.65	23.12	23.43	17.24	18.76	17.61	19.08	19.39
	3H	23.05	24.41	23.42	24.74	25.10	18.51	19.87	18.89	20.20	20.56
	4H	23.71	24.99	24.11	25.34	25.72	19.01	20.29	19.41	20.64	21.02
	6H	24.20	25.39	24.61	25.75	26.14	19.39	20.57	19.80	20.94	21.33
	8H	24.37	25.49	24.79	25.88	26.28	19.51	20.64	19.94	21.03	21.43
	12H	24.47	25.55	24.90	25.93	26.36	19.59	20.67	20.03	21.05	21.48
4H	2H	21.39	22.67	21.79	23.01	23.39	17.94	19.22	18.34	19.57	19.94
	3H	23.32	24.38	23.73	24.78	25.18	19.38	20.44	19.79	20.84	21.24
	4H	24.07	25.03	24.50	25.44	25.88	19.98	20.94	20.41	21.35	21.79
	6H	24.66	25.49	25.12	25.94	26.39	20.47	21.30	20.92	21.74	22.20
	8H	24.87	25.65	25.34	26.10	26.56	20.63	21.41	21.09	21.85	22.32
	12H	25.03	25.72	25.51	26.20	26.67	20.75	21.44	21.23	21.92	22.39
8H	4H	24.09	24.87	24.56	25.31	25.78	20.33	21.11	20.80	21.56	22.02
	6H	24.73	25.37	25.23	25.86	26.34	20.92	21.56	21.42	22.05	22.53
	8H	24.98	25.56	25.49	26.07	26.56	21.14	21.72	21.65	22.23	22.71
	12H	25.19	25.69	25.69	26.19	26.75	21.32	21.83	21.83	22.32	22.89
12H	4H	24.08	24.77	24.56	25.25	25.72	20.38	21.07	20.86	21.55	22.02
	6H	24.71	25.29	25.23	25.80	26.29	20.98	21.56	21.50	22.07	22.56
	8H	25.00	25.51	25.51	26.00	26.56	21.26	21.77	21.77	22.26	22.82