

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1000895

Luminaire Tested: SA4XXDIP-B1195D1205UB30-4F0-XX-W2A-D4

Issue Date: 5/7/2025

Test Information

Test Method: LM-79-2019
Report Number: P1000895
REPORT IS A COMBINATION OF REPORTS P995508 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: SA4XXDIP-B1195D1205UB30-4F0-XX-W2A-D4
Description: Define 4 Direct/Indirect Pendant with 3000K BioUP LEDs {m-DER=0.589} {m-EER=0.647}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 9187.6 lumens
Efficiency: N/A
Efficacy: 95.4 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.28 / 1.39
Luminous Opening: Rectangular w/ Sides (W: 0.33' x L: 4' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 96.3
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1000895

CATALOG NUMBER: SA4XXDIP-B1195D1205UB30-4F0-XX-W2A-D4

Luminous Intensity Polar Plot



TEST NUMBER: P1000895

CATALOG NUMBER: SA4XXDIP-B1195D1205UB30-4F0-XX-W2A-D4

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	107	107	107	107	99	99	99	99	83	83	83	68	68	68	55	55	55
1	97	92	88	84	89	85	81	78	71	68	66	59	57	55	47	46	45
2	88	80	73	68	80	73	68	63	62	57	54	51	48	45	41	39	37
3	80	70	62	56	73	64	57	52	54	49	45	45	41	38	36	33	31
4	73	61	53	47	66	57	49	44	48	42	38	40	35	32	32	29	26
5	67	54	46	40	61	50	43	37	43	37	32	35	31	27	29	25	23
6	61	49	40	34	56	45	38	32	38	32	28	32	27	24	26	23	20
7	57	44	36	30	52	41	33	28	35	29	25	29	24	21	24	20	18
8	52	40	32	26	48	37	30	25	32	26	22	26	22	19	22	18	16
9	49	36	29	23	45	34	27	22	29	23	19	24	20	17	20	17	14
10	46	33	26	21	42	31	24	20	27	21	17	22	18	15	18	15	13

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	11653	11653	11653
5°	11685	11349	11370
10°	11609	11126	11094
15°	11501	10875	10783
20°	11339	10603	10481
25°	11158	10303	10156
30°	10962	10006	9823
35°	10739	9702	9528
40°	10561	9411	9221
45°	10298	9137	8950
50°	10073	8827	8665
55°	9841	8527	8336
60°	9481	8155	8027
65°	9085	7753	7654
70°	8605	7294	7225
75°	7931	6784	6815
80°	7173	6263	6384
85°	6171	5740	6037

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 10298 cd/sqm

TEST NUMBER: P1000895

CATALOG NUMBER: SA4XXDIP-B1195D1205UB30-4F0-XX-W2A-D4

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	135.4	1.5
10°-20°	387.9	4.2
20°-30°	586.6	6.4
30°-40°	709.6	7.7
40°-50°	750.2	8.2
50°-60°	706.0	7.7
60°-70°	585.9	6.4
70°-80°	411.1	4.5
80°-90°	234.0	2.5
90°-100°	577.0	6.3
100°-110°	995.1	10.8
110°-120°	864.5	9.4
120°-130°	707.2	7.7
130°-140°	574.6	6.3
140°-150°	429.4	4.7
150°-160°	299.5	3.3
160°-170°	176.2	1.9
170°-180°	57.3	0.6
0°-30°	1109.9	12.1
0°-40°	1819.6	19.8
0°-60°	3275.8	35.7
0°-90°	4506.9	49.1
90°-120°	2436.6	26.5
90°-150°	4147.8	45.1
90°-180°	4681.0	50.9
0°-180°	9187.6	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1429	1429	1429	1429	1429	
5°	1431	1426	1415	1427	1426	136
15°	1371	1373	1368	1383	1381	386
25°	1255	1264	1269	1287	1288	578
35°	1098	1117	1133	1155	1160	687
45°	915	946	976	1003	1011	707
55°	717	750	798	830	840	639
65°	496	547	602	642	654	492
75°	275	334	402	446	461	292
85°	85	152	224	272	288	88
90°	27	99	179	228	242	20
95°	59	194	1086	651	480	59
105°	150	243	867	1786	1792	161
115°	249	324	754	1416	1690	247
125°	340	401	721	1186	1336	303
135°	399	475	684	1026	1169	309
145°	458	523	666	841	930	288
155°	519	560	648	734	765	239
165°	566	583	621	658	668	160
175°	590	591	596	604	602	56
180°	591	591	591	591	591	

TEST NUMBER: P1000895

CATALOG NUMBER: SA4XXDIP-B1195D1205UB30-4F0-XX-W2A-D4

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1429.0	1429.0	1429.0	1429.0	1429.0
2.5°	1435.4	1430.6	1417.8	1429.0	1427.4
5°	1430.6	1425.8	1414.6	1427.4	1425.8
7.5°	1421.0	1417.8	1408.2	1422.6	1421.0
10°	1408.2	1406.6	1398.6	1413.0	1411.4
12.5°	1390.6	1390.6	1385.8	1398.6	1398.6
15°	1371.4	1373.0	1368.2	1382.6	1381.0
17.5°	1345.8	1350.6	1349.0	1363.4	1361.8
20°	1318.6	1323.4	1325.0	1341.0	1341.0
22.5°	1288.2	1294.6	1297.8	1313.8	1317.0
25°	1254.6	1264.2	1269.0	1286.6	1288.2
27.5°	1217.8	1232.2	1238.6	1254.6	1256.2
30°	1181.0	1193.8	1205.0	1222.6	1225.8
32.5°	1140.9	1157.0	1169.8	1190.6	1193.8
35°	1097.7	1116.9	1132.9	1155.4	1160.2
37.5°	1054.5	1076.9	1096.1	1118.5	1123.3
40°	1012.9	1033.7	1056.1	1080.1	1086.5
42.5°	964.9	988.9	1016.1	1043.3	1048.1
45°	915.3	945.7	976.1	1003.3	1011.3
47.5°	868.9	899.3	934.5	961.7	971.3
50°	817.7	852.9	888.1	920.1	929.7
52.5°	766.5	801.7	843.3	875.3	884.9
55°	716.9	750.5	798.5	830.5	840.1
57.5°	660.9	702.5	748.9	787.3	795.3
60°	606.5	648.1	700.9	737.7	750.5
62.5°	553.7	600.1	652.9	689.7	702.5
65°	496.1	547.3	601.7	641.7	654.5
67.5°	441.7	496.1	553.7	593.7	606.5
70°	385.7	440.1	500.9	544.1	555.3
72.5°	331.2	387.3	452.9	494.5	507.3
75°	275.2	334.4	401.7	446.5	460.9
77.5°	222.4	284.8	355.2	400.1	416.1
80°	174.4	238.4	308.8	356.8	369.6
82.5°	126.4	193.6	264.0	313.6	328.0
85°	84.8	152.0	224.0	272.0	288.0
87.5°	52.8	118.4	188.8	235.2	249.6
90°	26.8	98.9	179.3	228.0	242.0
92.5°	40.3	169.4	604.0	344.0	312.1
95°	59.1	194.4	1085.6	650.9	480.1
97.5°	83.1	199.1	1143.7	1129.6	867.6
100°	105.8	210.2	1055.2	1488.6	1240.8
102.5°	129.1	224.7	948.5	1708.8	1567.2
105°	150.3	243.2	867.3	1785.8	1792.2
107.5°	177.0	264.0	811.7	1751.6	1894.0
110°	202.1	283.1	783.3	1649.2	1888.4

TEST NUMBER: P1000895

CATALOG NUMBER: SA4XXDIP-B1195D1205UB30-4F0-XX-W2A-D4

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	226.0	303.8	764.8	1525.8	1810.3
115°	248.8	324.2	754.5	1415.6	1690.3
117.5°	274.3	344.3	745.3	1325.8	1574.4
120°	298.3	362.4	737.3	1262.2	1476.5
122.5°	321.5	381.3	728.2	1218.9	1397.2
125°	339.7	400.8	720.6	1185.9	1336.5
127.5°	358.2	421.6	710.3	1152.4	1296.0
130°	371.7	440.4	701.1	1116.0	1258.6
132.5°	386.8	457.8	693.6	1074.4	1219.2
135°	399.2	474.6	684.4	1025.8	1169.0
137.5°	413.1	487.6	678.0	976.0	1111.8
140°	428.2	500.9	672.0	927.4	1051.5
142.5°	442.8	513.1	668.8	883.2	987.8
145°	457.9	522.6	666.5	841.0	929.8
147.5°	475.4	533.0	663.0	804.6	875.4
150°	491.6	542.8	659.5	776.8	829.1
152.5°	505.1	552.2	653.7	754.8	794.2
155°	519.0	560.3	647.9	733.8	765.2
157.5°	533.0	567.8	642.1	714.1	738.5
160°	545.8	574.2	635.2	694.4	714.1
162.5°	557.4	579.4	628.2	675.2	690.9
165°	565.5	582.9	621.2	657.8	667.7
167.5°	574.8	585.8	614.3	642.8	649.1
170°	580.6	588.2	607.3	627.6	631.7
172.5°	586.4	589.8	600.3	614.2	614.3
175°	589.9	591.0	595.7	603.8	601.5
177.5°	592.2	591.0	592.2	596.2	592.2
180°	591.0	591.0	591.0	591.0	591.0

(END OF REPORT)