

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1001839

Luminaire Tested: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

Issue Date: 5/7/2025

**Test Information**

Test Method: LM-79-2019  
Report Number: P1001839  
REPORT IS A COMBINATION OF REPORTS P996464 AND P1007351  
Test Lab: INNOVATION CENTER  
Issue Date: 5/7/2025  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: NEO-RAY  
Catalog Number: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1  
Description: Define 4 Direct/Indirect Pendant with 3000K BioUP LEDs {m-DER=0.589} {m-EER=0.647}  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 4837.0 lumens  
Efficiency: N/A  
Efficacy: 107.0 lumens/watt  
Spacing Criteria (0/90/45): 1.22 / 1.3 / 1.41  
Luminous Opening: Rectangular w/ Sides (W: 0.33' x L: 4' x H: 0.1')  
CIE Type: Semi-Direct

Input Watts (W): 45.2  
Input Voltage (V):  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1001839

CATALOG NUMBER: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

### Luminous Intensity Polar Plot



TEST NUMBER: P1001839

CATALOG NUMBER: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |    |    |    |    |    |    |    |    |    |    |    |    |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|----|----|----|----|----|----|----|----|----|
| RF  | 20  |     |     |     | 20  |     |     |     |    | 20 |    |    |    |    | 20 |    |    |    |    | 20 |
| RC  | 80  |     |     |     | 70  |     |     |     |    | 50 |    |    |    |    | 30 |    |    |    |    | 0  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 |
| RCR |     |     |     |     |     |     |     |     |    |    |    |    |    |    |    |    |    |    |    |    |
| 0   | 113 | 113 | 113 | 113 | 107 | 107 | 107 | 107 | 96 | 96 | 96 | 87 | 87 | 87 | 78 | 78 | 78 | 74 |    |    |
| 1   | 103 | 99  | 95  | 92  | 98  | 94  | 91  | 88  | 85 | 83 | 80 | 77 | 75 | 73 | 69 | 68 | 66 | 63 |    |    |
| 2   | 94  | 87  | 81  | 75  | 89  | 83  | 77  | 73  | 75 | 71 | 67 | 68 | 65 | 62 | 61 | 59 | 56 | 53 |    |    |
| 3   | 86  | 77  | 69  | 63  | 82  | 73  | 67  | 61  | 67 | 61 | 57 | 60 | 56 | 53 | 55 | 51 | 48 | 45 |    |    |
| 4   | 79  | 68  | 60  | 54  | 75  | 65  | 58  | 52  | 59 | 53 | 49 | 54 | 49 | 45 | 49 | 45 | 42 | 39 |    |    |
| 5   | 73  | 61  | 53  | 47  | 69  | 58  | 51  | 45  | 53 | 47 | 42 | 49 | 44 | 40 | 44 | 40 | 37 | 34 |    |    |
| 6   | 67  | 55  | 47  | 41  | 64  | 53  | 45  | 40  | 48 | 42 | 37 | 44 | 39 | 35 | 40 | 36 | 33 | 30 |    |    |
| 7   | 63  | 50  | 42  | 36  | 59  | 48  | 40  | 35  | 44 | 38 | 33 | 40 | 35 | 31 | 37 | 33 | 29 | 27 |    |    |
| 8   | 58  | 46  | 38  | 32  | 55  | 44  | 36  | 31  | 40 | 34 | 30 | 37 | 32 | 28 | 34 | 30 | 26 | 24 |    |    |
| 9   | 54  | 42  | 34  | 29  | 52  | 40  | 33  | 28  | 37 | 31 | 27 | 34 | 29 | 25 | 32 | 27 | 24 | 22 |    |    |
| 10  | 51  | 38  | 31  | 26  | 48  | 37  | 30  | 25  | 34 | 28 | 24 | 32 | 27 | 23 | 29 | 25 | 22 | 20 |    |    |

**AVERAGE LUMINANCE (cd/sqm):**

|     | 0°    | 90°   | 180°  | 270°  |
|-----|-------|-------|-------|-------|
| 0°  | 10523 | 10523 | 10523 | 10523 |
| 5°  | 10496 | 12072 | 10558 | 9071  |
| 10° | 10419 | 14085 | 10498 | 7959  |
| 15° | 10293 | 16237 | 10365 | 7121  |
| 20° | 10160 | 17607 | 10233 | 6384  |
| 25° | 9965  | 17405 | 10061 | 5841  |
| 30° | 9775  | 14386 | 9895  | 5561  |
| 35° | 9509  | 10721 | 9613  | 5391  |
| 40° | 9197  | 8076  | 9286  | 5309  |
| 45° | 8721  | 6482  | 8830  | 5195  |
| 50° | 8153  | 5461  | 8271  | 5142  |
| 55° | 7485  | 4753  | 7602  | 5081  |
| 60° | 6836  | 4185  | 7036  | 4997  |
| 65° | 6227  | 3601  | 6285  | 4789  |
| 70° | 5511  | 2962  | 5629  | 4409  |
| 75° | 4807  | 2277  | 4775  | 3747  |
| 80° | 3780  | 1496  | 3739  | 2845  |
| 85° | 2489  | 673   | 2336  | 1658  |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 145°

Vertical Angle: 45°

Luminance: 13607 cd/sqm

TEST NUMBER: P1001839

CATALOG NUMBER: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 125.6  | 2.6       |
| 10°-20°   | 387.7  | 8.0       |
| 20°-30°   | 615.8  | 12.7      |
| 30°-40°   | 684.3  | 14.1      |
| 40°-50°   | 622.3  | 12.9      |
| 50°-60°   | 508.5  | 10.5      |
| 60°-70°   | 363.0  | 7.5       |
| 70°-80°   | 199.8  | 4.1       |
| 80°-90°   | 55.0   | 1.1       |
| 90°-100°  | 30.0   | 0.6       |
| 100°-110° | 89.7   | 1.9       |
| 110°-120° | 152.4  | 3.2       |
| 120°-130° | 201.0  | 4.2       |
| 130°-140° | 225.8  | 4.7       |
| 140°-150° | 221.9  | 4.6       |
| 150°-160° | 186.6  | 3.9       |
| 160°-170° | 124.2  | 2.6       |
| 170°-180° | 43.5   | 0.9       |
| 0°-30°    | 1129.1 | 23.3      |
| 0°-40°    | 1813.4 | 37.5      |
| 0°-60°    | 2944.3 | 60.9      |
| 0°-90°    | 3562.0 | 73.6      |
| 90°-120°  | 272.1  | 5.6       |
| 90°-150°  | 920.8  | 19.0      |
| 90°-180°  | 1275.0 | 26.4      |
| 0°-180°   | 4837.0 | 100.0     |

**CANDELA DISTRIBUTION:**

|      | 0°   | 90°  | 180° | 270° | 360° | Flux |
|------|------|------|------|------|------|------|
| 0°   | 1290 | 1290 | 1290 | 1290 | 1290 |      |
| 5°   | 1285 | 1514 | 1293 | 1138 | 1285 | 122  |
| 15°  | 1227 | 2080 | 1236 | 912  | 1227 | 346  |
| 25°  | 1120 | 2208 | 1131 | 741  | 1120 | 516  |
| 35°  | 972  | 1306 | 983  | 656  | 972  | 607  |
| 45°  | 775  | 732  | 785  | 587  | 775  | 598  |
| 55°  | 545  | 479  | 554  | 512  | 545  | 490  |
| 65°  | 340  | 308  | 343  | 410  | 340  | 336  |
| 75°  | 167  | 154  | 166  | 253  | 167  | 175  |
| 85°  | 34   | 32   | 32   | 79   | 34   | 40   |
| 90°  | 1    | 11   | 1    | 11   | 1    | 4    |
| 95°  | 21   | 28   | 21   | 28   | 21   | 23   |
| 105° | 83   | 87   | 83   | 87   | 83   | 88   |
| 115° | 155  | 154  | 155  | 154  | 155  | 153  |
| 125° | 226  | 224  | 226  | 224  | 226  | 201  |
| 135° | 291  | 291  | 291  | 291  | 291  | 225  |
| 145° | 354  | 354  | 354  | 354  | 354  | 221  |
| 155° | 405  | 405  | 405  | 405  | 405  | 186  |
| 165° | 441  | 440  | 441  | 440  | 441  | 124  |
| 175° | 459  | 457  | 459  | 457  | 459  | 44   |
| 180° | 460  | 460  | 460  | 460  | 460  |      |

TEST NUMBER: P1001839

CATALOG NUMBER: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

**CANDELA DISTRIBUTION (FULL):**

|        | 0°     | 5°     | 10°    | 15°    | 20°    | 22.5°  | 25°    | 30°    | 35°    | 40°    | 45°    |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°     | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 |
| 2.5°   | 1290.5 | 1303.3 | 1308.7 | 1312.9 | 1326.8 | 1331.1 | 1332.2 | 1338.6 | 1343.9 | 1345.0 | 1345.0 |
| 5°     | 1285.1 | 1305.5 | 1321.5 | 1336.5 | 1358.9 | 1368.5 | 1380.3 | 1393.1 | 1410.2 | 1420.9 | 1426.3 |
| 7.5°   | 1276.6 | 1306.5 | 1331.1 | 1356.8 | 1387.8 | 1407.0 | 1417.7 | 1451.9 | 1475.5 | 1494.7 | 1518.2 |
| 10°    | 1263.8 | 1302.2 | 1337.5 | 1374.9 | 1418.8 | 1442.3 | 1465.8 | 1507.5 | 1540.7 | 1578.1 | 1608.0 |
| 12.5°  | 1244.5 | 1294.8 | 1337.5 | 1389.9 | 1444.4 | 1472.2 | 1500.0 | 1572.7 | 1611.2 | 1644.4 | 1697.8 |
| 15°    | 1227.4 | 1277.7 | 1338.6 | 1392.1 | 1459.4 | 1501.1 | 1541.7 | 1588.8 | 1649.7 | 1721.4 | 1772.7 |
| 17.5°  | 1208.2 | 1271.2 | 1327.9 | 1402.7 | 1477.6 | 1517.1 | 1550.3 | 1623.0 | 1708.5 | 1779.1 | 1826.1 |
| 20°    | 1181.4 | 1245.6 | 1320.4 | 1399.5 | 1488.3 | 1519.3 | 1563.1 | 1660.4 | 1737.4 | 1806.9 | 1883.9 |
| 22.5°  | 1150.4 | 1225.3 | 1304.4 | 1380.3 | 1472.2 | 1537.5 | 1585.6 | 1671.1 | 1764.1 | 1844.3 | 1930.9 |
| 25°    | 1120.5 | 1201.7 | 1271.2 | 1374.9 | 1472.2 | 1516.1 | 1570.6 | 1672.2 | 1773.7 | 1871.0 | 1959.8 |
| 27.5°  | 1088.4 | 1164.3 | 1258.4 | 1340.7 | 1450.9 | 1499.0 | 1557.8 | 1669.0 | 1777.0 | 1874.3 | 1969.4 |
| 30°    | 1053.1 | 1134.4 | 1212.4 | 1309.7 | 1416.6 | 1478.7 | 1533.2 | 1654.0 | 1764.1 | 1865.7 | 1954.4 |
| 32.5°  | 1013.6 | 1090.6 | 1173.9 | 1265.9 | 1378.2 | 1441.2 | 1509.7 | 1633.7 | 1751.3 | 1839.0 | 1907.4 |
| 35°    | 971.9  | 1049.9 | 1122.6 | 1216.7 | 1332.2 | 1395.3 | 1461.6 | 1598.4 | 1714.9 | 1786.6 | 1826.1 |
| 37.5°  | 925.9  | 999.7  | 1071.3 | 1164.3 | 1279.8 | 1347.2 | 1414.5 | 1547.1 | 1657.2 | 1717.1 | 1706.4 |
| 40°    | 882.1  | 948.4  | 1014.6 | 1102.3 | 1223.1 | 1294.8 | 1353.6 | 1487.2 | 1583.4 | 1609.1 | 1573.8 |
| 42.5°  | 831.8  | 888.5  | 952.6  | 1042.4 | 1160.0 | 1227.4 | 1301.2 | 1423.1 | 1494.7 | 1484.0 | 1424.1 |
| 45°    | 775.1  | 825.4  | 889.5  | 974.0  | 1093.8 | 1163.3 | 1225.3 | 1340.7 | 1393.1 | 1366.4 | 1257.3 |
| 47.5°  | 720.6  | 769.8  | 822.2  | 906.7  | 1023.2 | 1082.0 | 1145.1 | 1248.8 | 1278.7 | 1222.1 | 1113.0 |
| 50°    | 661.8  | 702.4  | 757.0  | 837.2  | 946.2  | 1008.2 | 1060.6 | 1144.0 | 1154.7 | 1085.2 | 971.9  |
| 52.5°  | 605.1  | 639.4  | 691.8  | 770.9  | 872.4  | 921.6  | 972.9  | 1046.7 | 1038.2 | 966.5  | 857.5  |
| 55°    | 545.3  | 577.4  | 625.5  | 698.2  | 788.0  | 835.0  | 878.9  | 944.1  | 925.9  | 852.1  | 757.0  |
| 57.5°  | 495.0  | 517.5  | 564.5  | 631.9  | 705.7  | 757.0  | 794.4  | 845.7  | 817.9  | 744.1  | 655.4  |
| 60°    | 437.3  | 465.1  | 504.6  | 559.2  | 631.9  | 666.1  | 699.2  | 733.4  | 714.2  | 643.6  | 564.5  |
| 62.5°  | 384.9  | 406.3  | 440.5  | 492.9  | 549.6  | 580.6  | 615.8  | 637.2  | 618.0  | 552.8  | 486.5  |
| 65°    | 340.0  | 357.1  | 383.8  | 426.6  | 481.1  | 506.8  | 527.1  | 547.4  | 531.4  | 470.4  | 422.3  |
| 67.5°  | 290.8  | 305.8  | 328.2  | 362.4  | 408.4  | 426.6  | 445.8  | 459.7  | 441.6  | 400.9  | 353.9  |
| 70°    | 247.0  | 257.7  | 279.1  | 304.7  | 336.8  | 353.9  | 369.9  | 383.8  | 367.8  | 333.6  | 298.3  |
| 72.5°  | 202.1  | 210.6  | 229.9  | 248.0  | 276.9  | 288.7  | 300.4  | 311.1  | 305.8  | 273.7  | 244.8  |
| 75°    | 166.8  | 170.0  | 182.8  | 197.8  | 216.0  | 228.8  | 237.4  | 243.8  | 239.5  | 213.8  | 195.7  |
| 77.5°  | 126.2  | 130.4  | 140.1  | 151.8  | 167.9  | 175.3  | 180.7  | 187.1  | 181.8  | 161.4  | 148.6  |
| 80°    | 91.9   | 93.0   | 98.4   | 109.1  | 119.7  | 120.8  | 126.2  | 134.7  | 131.5  | 117.6  | 108.0  |
| 82.5°  | 58.8   | 62.0   | 64.2   | 70.6   | 78.0   | 80.2   | 83.4   | 85.5   | 84.5   | 75.9   | 72.7   |
| 85°    | 34.2   | 34.2   | 36.4   | 40.6   | 42.8   | 46.0   | 47.0   | 48.1   | 50.3   | 44.9   | 41.7   |
| 87.5°  | 15.0   | 16.0   | 16.0   | 17.1   | 19.2   | 19.2   | 20.3   | 21.4   | 22.5   | 21.4   | 18.2   |
| 90°    | 1.1    | 2.0    | 2.8    | 3.7    | 4.6    | 5.0    | 5.3    | 5.9    | 6.6    | 7.2    | 7.8    |
| 92.5°  | 9.2    | 10.2   | 11.3   | 12.3   | 13.4   | 13.9   | 14.1   | 14.5   | 14.8   | 15.2   | 15.6   |
| 95°    | 21.3   | 22.0   | 22.7   | 23.4   | 24.1   | 24.5   | 24.8   | 25.3   | 25.9   | 26.4   | 27.0   |
| 97.5°  | 34.1   | 34.7   | 35.4   | 36.0   | 36.7   | 37.0   | 37.3   | 37.9   | 38.6   | 39.2   | 39.8   |
| 100°   | 49.8   | 50.1   | 50.4   | 50.7   | 51.0   | 51.2   | 51.6   | 52.3   | 53.0   | 53.7   | 54.4   |
| 102.5° | 66.1   | 66.2   | 66.3   | 66.4   | 66.5   | 66.5   | 66.8   | 67.4   | 68.1   | 68.7   | 69.3   |
| 105°   | 82.8   | 82.9   | 83.0   | 83.1   | 83.2   | 83.2   | 83.4   | 83.7   | 84.0   | 84.3   | 84.6   |
| 107.5° | 100.2  | 100.3  | 100.4  | 100.5  | 100.6  | 100.6  | 100.6  | 100.7  | 100.8  | 100.8  | 100.9  |
| 110°   | 118.0  | 118.2  | 118.3  | 118.5  | 118.6  | 118.7  | 118.7  | 118.6  | 118.5  | 118.4  | 118.3  |

TEST NUMBER: P1001839

CATALOG NUMBER: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

**CANDELA DISTRIBUTION (continued):**

|        | 0°    | 5°    | 10°   | 15°   | 20°   | 22.5° | 25°   | 30°   | 35°   | 40°   | 45°   |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 112.5° | 136.5 | 136.5 | 136.5 | 136.5 | 136.5 | 136.5 | 136.4 | 136.3 | 136.1 | 136.0 | 135.8 |
| 115°   | 155.0 | 155.0 | 155.0 | 155.0 | 155.0 | 155.0 | 154.9 | 154.7 | 154.6 | 154.4 | 154.2 |
| 117.5° | 172.4 | 172.4 | 172.4 | 172.4 | 172.4 | 172.4 | 172.4 | 172.3 | 172.2 | 172.1 | 172.0 |
| 120°   | 189.8 | 190.1 | 190.4 | 190.7 | 191.0 | 191.2 | 191.1 | 190.8 | 190.6 | 190.3 | 190.1 |
| 122.5° | 207.9 | 208.0 | 208.1 | 208.2 | 208.3 | 208.3 | 208.3 | 208.2 | 208.1 | 208.0 | 207.9 |
| 125°   | 225.7 | 225.7 | 225.7 | 225.7 | 225.7 | 225.7 | 225.7 | 225.6 | 225.5 | 225.4 | 225.3 |
| 127.5° | 241.7 | 241.9 | 242.1 | 242.4 | 242.6 | 242.7 | 242.6 | 242.5 | 242.3 | 242.2 | 242.0 |
| 130°   | 258.7 | 258.9 | 259.2 | 259.4 | 259.7 | 259.8 | 259.8 | 259.8 | 259.8 | 259.8 | 259.8 |
| 132.5° | 276.1 | 276.3 | 276.5 | 276.6 | 276.8 | 276.9 | 276.9 | 276.8 | 276.7 | 276.6 | 276.5 |
| 135°   | 291.1 | 291.6 | 292.0 | 292.5 | 293.0 | 293.2 | 293.2 | 293.2 | 293.2 | 293.2 | 293.2 |
| 137.5° | 307.8 | 308.0 | 308.2 | 308.5 | 308.7 | 308.8 | 308.9 | 309.0 | 309.2 | 309.3 | 309.5 |
| 140°   | 324.5 | 324.7 | 324.8 | 325.0 | 325.1 | 325.2 | 325.2 | 325.2 | 325.2 | 325.2 | 325.2 |
| 142.5° | 339.8 | 340.0 | 340.1 | 340.3 | 340.4 | 340.5 | 340.5 | 340.4 | 340.3 | 340.2 | 340.1 |
| 145°   | 353.6 | 353.9 | 354.2 | 354.5 | 354.8 | 355.0 | 355.0 | 355.1 | 355.2 | 355.3 | 355.4 |
| 147.5° | 367.8 | 368.2 | 368.6 | 369.0 | 369.4 | 369.6 | 369.6 | 369.5 | 369.4 | 369.4 | 369.3 |
| 150°   | 380.6 | 380.9 | 381.3 | 381.6 | 381.9 | 382.1 | 382.1 | 382.1 | 382.1 | 382.1 | 382.1 |
| 152.5° | 392.7 | 392.9 | 393.0 | 393.2 | 393.3 | 393.4 | 393.4 | 393.5 | 393.6 | 393.7 | 393.8 |
| 155°   | 405.2 | 405.2 | 405.2 | 405.2 | 405.2 | 405.2 | 405.2 | 405.1 | 405.0 | 404.9 | 404.8 |
| 157.5° | 415.8 | 415.6 | 415.5 | 415.3 | 415.2 | 415.1 | 415.1 | 415.1 | 415.1 | 415.1 | 415.1 |
| 160°   | 425.1 | 425.0 | 424.9 | 424.8 | 424.7 | 424.7 | 424.7 | 424.6 | 424.5 | 424.4 | 424.3 |
| 162.5° | 433.6 | 433.4 | 433.1 | 432.9 | 432.6 | 432.5 | 432.5 | 432.4 | 432.3 | 432.3 | 432.2 |
| 165°   | 441.0 | 440.8 | 440.6 | 440.3 | 440.1 | 440.0 | 439.9 | 439.8 | 439.6 | 439.5 | 439.3 |
| 167.5° | 447.1 | 446.8 | 446.5 | 446.2 | 445.9 | 445.7 | 445.7 | 445.7 | 445.7 | 445.7 | 445.7 |
| 170°   | 452.1 | 451.7 | 451.3 | 450.9 | 450.5 | 450.3 | 450.3 | 450.4 | 450.5 | 450.5 | 450.6 |
| 172.5° | 455.6 | 455.3 | 455.0 | 454.7 | 454.4 | 454.2 | 454.2 | 454.2 | 454.2 | 454.2 | 454.2 |
| 175°   | 458.8 | 458.4 | 458.0 | 457.6 | 457.2 | 457.0 | 457.0 | 456.9 | 456.8 | 456.8 | 456.7 |
| 177.5° | 460.2 | 459.8 | 459.4 | 459.1 | 458.7 | 458.5 | 458.5 | 458.5 | 458.5 | 458.5 | 458.5 |
| 180°   | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 |

TEST NUMBER: P1001839

CATALOG NUMBER: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

**CANDELA DISTRIBUTION (continued):**

|        | 50°    | 55°    | 60°    | 65°    | 67.5°  | 70°    | 75°    | 80°    | 85°    | 90°    | 95°    |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°     | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 |
| 2.5°   | 1348.2 | 1367.5 | 1376.0 | 1378.2 | 1389.9 | 1382.4 | 1385.6 | 1384.6 | 1393.1 | 1394.2 | 1394.2 |
| 5°     | 1446.6 | 1469.0 | 1476.5 | 1487.2 | 1503.2 | 1507.5 | 1504.3 | 1510.7 | 1522.5 | 1513.9 | 1526.8 |
| 7.5°   | 1550.3 | 1574.9 | 1592.0 | 1615.5 | 1620.9 | 1634.8 | 1643.3 | 1650.8 | 1652.9 | 1654.0 | 1656.1 |
| 10°    | 1646.5 | 1677.5 | 1701.0 | 1740.6 | 1749.2 | 1756.6 | 1794.1 | 1779.1 | 1798.3 | 1791.9 | 1794.1 |
| 12.5°  | 1724.6 | 1785.5 | 1804.8 | 1871.0 | 1877.5 | 1903.1 | 1901.0 | 1924.5 | 1928.8 | 1937.3 | 1928.8 |
| 15°    | 1827.2 | 1897.8 | 1928.8 | 1966.2 | 1987.6 | 2017.5 | 2022.9 | 2054.9 | 2067.8 | 2079.5 | 2067.8 |
| 17.5°  | 1921.3 | 1958.7 | 2037.8 | 2067.8 | 2081.7 | 2097.7 | 2138.3 | 2150.1 | 2169.3 | 2161.9 | 2183.2 |
| 20°    | 1968.3 | 2021.8 | 2105.2 | 2156.5 | 2177.9 | 2192.9 | 2227.1 | 2245.3 | 2252.7 | 2252.7 | 2254.9 |
| 22.5°  | 2010.0 | 2087.0 | 2149.0 | 2207.8 | 2227.1 | 2237.8 | 2258.1 | 2272.0 | 2275.2 | 2277.3 | 2279.5 |
| 25°    | 2047.5 | 2117.0 | 2167.2 | 2200.3 | 2207.8 | 2207.8 | 2219.6 | 2211.0 | 2197.1 | 2207.8 | 2214.2 |
| 27.5°  | 2047.5 | 2096.6 | 2119.1 | 2130.9 | 2130.9 | 2102.0 | 2084.9 | 2049.6 | 2019.7 | 2011.1 | 2030.3 |
| 30°    | 2013.2 | 2035.7 | 2004.7 | 1975.8 | 1953.4 | 1934.1 | 1866.8 | 1813.3 | 1802.6 | 1795.1 | 1824.0 |
| 32.5°  | 1934.1 | 1905.3 | 1844.3 | 1760.9 | 1727.8 | 1683.9 | 1631.5 | 1590.9 | 1566.3 | 1557.8 | 1551.4 |
| 35°    | 1794.1 | 1719.2 | 1640.1 | 1527.8 | 1504.3 | 1448.7 | 1377.1 | 1347.2 | 1306.5 | 1305.5 | 1319.4 |
| 37.5°  | 1641.2 | 1525.7 | 1440.2 | 1333.3 | 1300.1 | 1241.3 | 1173.9 | 1142.9 | 1115.1 | 1093.8 | 1119.4 |
| 40°    | 1462.6 | 1362.1 | 1231.7 | 1144.0 | 1097.0 | 1066.0 | 1009.3 | 975.1  | 962.3  | 951.6  | 967.6  |
| 42.5°  | 1295.8 | 1185.7 | 1084.1 | 994.3  | 955.8  | 920.6  | 883.1  | 850.0  | 840.4  | 839.3  | 851.1  |
| 45°    | 1130.1 | 1022.1 | 928.0  | 851.1  | 826.5  | 805.1  | 768.7  | 759.1  | 743.1  | 732.4  | 737.7  |
| 47.5°  | 997.5  | 886.3  | 808.3  | 749.5  | 728.1  | 709.9  | 686.4  | 670.4  | 656.5  | 652.2  | 658.6  |
| 50°    | 867.1  | 792.3  | 712.1  | 662.9  | 646.8  | 629.7  | 611.6  | 596.6  | 590.2  | 585.9  | 590.2  |
| 52.5°  | 762.3  | 682.1  | 627.6  | 588.0  | 572.0  | 559.2  | 546.3  | 539.9  | 531.4  | 533.5  | 537.8  |
| 55°    | 668.2  | 597.7  | 551.7  | 522.8  | 513.2  | 507.9  | 491.8  | 484.3  | 481.1  | 479.0  | 481.1  |
| 57.5°  | 579.5  | 528.2  | 494.0  | 469.4  | 456.5  | 453.3  | 440.5  | 440.5  | 437.3  | 434.1  | 435.2  |
| 60°    | 508.9  | 465.1  | 431.9  | 412.7  | 410.6  | 405.2  | 396.7  | 395.6  | 388.1  | 391.3  | 392.4  |
| 62.5°  | 437.3  | 402.0  | 379.6  | 367.8  | 360.3  | 358.2  | 352.8  | 351.8  | 348.5  | 349.6  | 347.5  |
| 65°    | 380.6  | 351.8  | 329.3  | 319.7  | 316.5  | 315.4  | 311.1  | 307.9  | 305.8  | 307.9  | 305.8  |
| 67.5°  | 324.0  | 304.7  | 287.6  | 278.0  | 273.7  | 272.6  | 269.4  | 267.3  | 268.4  | 265.2  | 267.3  |
| 70°    | 270.5  | 251.3  | 240.6  | 235.2  | 233.1  | 229.9  | 229.9  | 229.9  | 229.9  | 227.7  | 226.7  |
| 72.5°  | 227.7  | 208.5  | 201.0  | 197.8  | 195.7  | 194.6  | 191.4  | 192.5  | 191.4  | 190.3  | 194.6  |
| 75°    | 180.7  | 168.9  | 161.4  | 158.2  | 160.4  | 157.2  | 154.0  | 156.1  | 152.9  | 154.0  | 158.2  |
| 77.5°  | 136.9  | 131.5  | 127.2  | 125.1  | 123.0  | 120.8  | 120.8  | 118.7  | 118.7  | 118.7  | 118.7  |
| 80°    | 99.4   | 98.4   | 90.9   | 89.8   | 89.8   | 87.7   | 87.7   | 87.7   | 87.7   | 86.6   | 87.7   |
| 82.5°  | 66.3   | 65.2   | 63.1   | 62.0   | 59.9   | 60.9   | 60.9   | 58.8   | 58.8   | 57.7   | 58.8   |
| 85°    | 38.5   | 38.5   | 36.4   | 35.3   | 34.2   | 35.3   | 33.1   | 32.1   | 33.1   | 32.1   | 33.1   |
| 87.5°  | 18.2   | 16.0   | 17.1   | 16.0   | 13.9   | 15.0   | 12.8   | 13.9   | 12.8   | 11.8   | 13.9   |
| 90°    | 8.3    | 8.8    | 9.3    | 9.8    | 10.0   | 10.1   | 10.2   | 10.4   | 10.5   | 10.7   | 10.5   |
| 92.5°  | 15.8   | 16.1   | 16.3   | 16.6   | 16.7   | 16.7   | 16.8   | 16.9   | 17.0   | 17.1   | 17.0   |
| 95°    | 27.2   | 27.5   | 27.7   | 28.0   | 28.1   | 28.1   | 28.1   | 28.1   | 28.1   | 28.1   | 28.1   |
| 97.5°  | 40.1   | 40.4   | 40.7   | 41.0   | 41.2   | 41.2   | 41.2   | 41.2   | 41.2   | 41.2   | 41.2   |
| 100°   | 54.6   | 54.7   | 54.9   | 55.0   | 55.1   | 55.1   | 55.1   | 55.1   | 55.1   | 55.1   | 55.1   |
| 102.5° | 69.5   | 69.8   | 70.0   | 70.3   | 70.4   | 70.4   | 70.5   | 70.6   | 70.6   | 70.7   | 70.6   |
| 105°   | 84.8   | 85.1   | 85.3   | 85.6   | 85.7   | 85.8   | 86.0   | 86.3   | 86.5   | 86.7   | 86.5   |
| 107.5° | 101.2  | 101.6  | 101.9  | 102.2  | 102.4  | 102.4  | 102.3  | 102.2  | 102.1  | 102.0  | 102.1  |
| 110°   | 118.1  | 118.0  | 117.8  | 117.7  | 117.6  | 117.7  | 118.0  | 118.2  | 118.5  | 118.7  | 118.5  |

TEST NUMBER: P1001839

CATALOG NUMBER: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

**CANDELA DISTRIBUTION (continued):**

|        | 50°   | 55°   | 60°   | 65°   | 67.5° | 70°   | 75°   | 80°   | 85°   | 90°   | 95°   |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 112.5° | 135.8 | 135.8 | 135.8 | 135.8 | 135.8 | 135.8 | 135.8 | 135.8 | 135.8 | 135.8 | 135.8 |
| 115°   | 154.1 | 154.1 | 154.0 | 153.9 | 153.9 | 153.9 | 153.8 | 153.7 | 153.6 | 153.5 | 153.6 |
| 117.5° | 171.8 | 171.5 | 171.3 | 171.0 | 170.9 | 170.8 | 170.6 | 170.3 | 170.1 | 169.9 | 170.1 |
| 120°   | 189.7 | 189.3 | 189.0 | 188.6 | 188.4 | 188.5 | 188.6 | 188.8 | 188.9 | 189.1 | 188.9 |
| 122.5° | 207.7 | 207.4 | 207.2 | 206.9 | 206.8 | 206.6 | 206.2 | 205.9 | 205.5 | 205.1 | 205.5 |
| 125°   | 225.1 | 225.0 | 224.8 | 224.7 | 224.6 | 224.5 | 224.4 | 224.2 | 224.1 | 223.9 | 224.1 |
| 127.5° | 241.8 | 241.7 | 241.5 | 241.4 | 241.3 | 241.3 | 241.2 | 241.1 | 241.1 | 241.0 | 241.1 |
| 130°   | 259.6 | 259.5 | 259.3 | 259.2 | 259.1 | 258.9 | 258.6 | 258.3 | 258.0 | 257.7 | 258.0 |
| 132.5° | 276.3 | 276.2 | 276.0 | 275.9 | 275.8 | 275.8 | 275.7 | 275.6 | 275.5 | 275.4 | 275.5 |
| 135°   | 293.0 | 292.9 | 292.7 | 292.6 | 292.5 | 292.4 | 292.1 | 291.9 | 291.6 | 291.4 | 291.6 |
| 137.5° | 309.3 | 309.1 | 308.8 | 308.6 | 308.5 | 308.5 | 308.6 | 308.7 | 308.7 | 308.8 | 308.7 |
| 140°   | 325.1 | 325.0 | 324.9 | 324.8 | 324.8 | 324.8 | 324.7 | 324.6 | 324.6 | 324.5 | 324.6 |
| 142.5° | 340.1 | 340.1 | 340.1 | 340.1 | 340.1 | 340.1 | 340.1 | 340.1 | 340.1 | 340.1 | 340.1 |
| 145°   | 355.3 | 355.2 | 355.1 | 355.0 | 355.0 | 354.9 | 354.7 | 354.4 | 354.2 | 354.0 | 354.2 |
| 147.5° | 369.2 | 369.1 | 369.0 | 368.9 | 368.9 | 368.9 | 368.8 | 368.7 | 368.6 | 368.5 | 368.6 |
| 150°   | 382.1 | 382.1 | 382.1 | 382.1 | 382.1 | 382.1 | 382.0 | 381.9 | 381.8 | 381.7 | 381.8 |
| 152.5° | 394.0 | 394.2 | 394.5 | 394.7 | 394.8 | 394.7 | 394.5 | 394.2 | 394.0 | 393.8 | 394.0 |
| 155°   | 405.1 | 405.4 | 405.7 | 406.0 | 406.2 | 406.0 | 405.7 | 405.4 | 405.1 | 404.8 | 405.1 |
| 157.5° | 415.3 | 415.6 | 415.8 | 416.1 | 416.2 | 416.1 | 415.8 | 415.6 | 415.3 | 415.1 | 415.3 |
| 160°   | 424.5 | 424.8 | 425.0 | 425.3 | 425.4 | 425.2 | 424.8 | 424.4 | 424.0 | 423.6 | 424.0 |
| 162.5° | 432.7 | 433.1 | 433.6 | 434.1 | 434.3 | 434.1 | 433.7 | 433.3 | 432.9 | 432.5 | 432.9 |
| 165°   | 439.8 | 440.2 | 440.7 | 441.2 | 441.4 | 441.2 | 440.9 | 440.6 | 440.3 | 440.0 | 440.3 |
| 167.5° | 446.2 | 446.6 | 447.1 | 447.6 | 447.8 | 447.6 | 447.1 | 446.6 | 446.2 | 445.7 | 446.2 |
| 170°   | 451.1 | 451.6 | 452.1 | 452.6 | 452.8 | 452.5 | 452.0 | 451.4 | 450.9 | 450.3 | 450.9 |
| 172.5° | 454.8 | 455.3 | 455.9 | 456.4 | 456.7 | 456.4 | 455.9 | 455.3 | 454.8 | 454.2 | 454.8 |
| 175°   | 457.3 | 457.8 | 458.4 | 458.9 | 459.2 | 458.9 | 458.4 | 457.8 | 457.3 | 456.7 | 457.3 |
| 177.5° | 459.0 | 459.6 | 460.1 | 460.6 | 460.9 | 460.6 | 460.0 | 459.3 | 458.7 | 458.1 | 458.7 |
| 180°   | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 |

TEST NUMBER: P1001839

CATALOG NUMBER: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

**CANDELA DISTRIBUTION (continued):**

|        | 100°   | 105°   | 110°   | 112.5° | 115°   | 120°   | 125°   | 130°   | 135°   | 140°   | 145°   |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°     | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 |
| 2.5°   | 1392.1 | 1388.8 | 1384.6 | 1384.6 | 1379.2 | 1379.2 | 1370.7 | 1355.7 | 1342.9 | 1338.6 | 1340.7 |
| 5°     | 1510.7 | 1511.8 | 1505.4 | 1500.0 | 1490.4 | 1482.9 | 1469.0 | 1442.3 | 1433.8 | 1416.6 | 1404.9 |
| 7.5°   | 1646.5 | 1642.2 | 1630.5 | 1621.9 | 1619.8 | 1602.7 | 1572.7 | 1540.7 | 1515.0 | 1497.9 | 1473.3 |
| 10°    | 1799.4 | 1782.3 | 1765.2 | 1759.8 | 1747.0 | 1718.2 | 1683.9 | 1648.7 | 1613.4 | 1576.0 | 1534.3 |
| 12.5°  | 1927.7 | 1894.6 | 1893.5 | 1880.7 | 1856.1 | 1840.0 | 1799.4 | 1749.2 | 1688.2 | 1646.5 | 1599.5 |
| 15°    | 2065.6 | 2034.6 | 2009.0 | 1985.4 | 1973.7 | 1926.6 | 1892.4 | 1829.3 | 1756.6 | 1711.7 | 1679.7 |
| 17.5°  | 2164.0 | 2150.1 | 2106.3 | 2095.6 | 2079.5 | 2025.0 | 1970.5 | 1908.5 | 1845.4 | 1782.3 | 1695.7 |
| 20°    | 2243.1 | 2234.6 | 2205.7 | 2190.7 | 2165.1 | 2122.3 | 2056.0 | 1984.4 | 1911.7 | 1821.9 | 1740.6 |
| 22.5°  | 2277.3 | 2266.6 | 2243.1 | 2230.3 | 2214.2 | 2177.9 | 2121.2 | 2040.0 | 1944.8 | 1864.6 | 1778.0 |
| 25°    | 2210.0 | 2229.2 | 2222.8 | 2217.5 | 2211.0 | 2189.7 | 2146.9 | 2075.3 | 1982.2 | 1891.4 | 1783.4 |
| 27.5°  | 2058.1 | 2091.3 | 2123.4 | 2127.6 | 2138.3 | 2146.9 | 2129.8 | 2078.5 | 2000.4 | 1904.2 | 1785.5 |
| 30°    | 1853.9 | 1868.9 | 1934.1 | 1953.4 | 1968.3 | 2022.9 | 2054.9 | 2042.1 | 1982.2 | 1895.6 | 1786.6 |
| 32.5°  | 1592.0 | 1631.5 | 1697.8 | 1743.8 | 1784.4 | 1845.4 | 1928.8 | 1961.9 | 1940.5 | 1870.0 | 1762.0 |
| 35°    | 1343.9 | 1391.0 | 1468.0 | 1526.8 | 1567.4 | 1654.0 | 1752.4 | 1824.0 | 1850.7 | 1815.4 | 1719.2 |
| 37.5°  | 1140.8 | 1197.5 | 1265.9 | 1288.3 | 1335.4 | 1442.3 | 1578.1 | 1677.5 | 1742.7 | 1746.0 | 1671.1 |
| 40°    | 987.9  | 1016.8 | 1071.3 | 1105.5 | 1151.5 | 1241.3 | 1373.9 | 1505.4 | 1603.8 | 1636.9 | 1597.3 |
| 42.5°  | 858.5  | 881.0  | 921.6  | 963.3  | 1005.0 | 1073.4 | 1195.3 | 1318.3 | 1450.9 | 1517.1 | 1516.1 |
| 45°    | 755.9  | 779.4  | 807.2  | 841.4  | 870.3  | 944.1  | 1040.3 | 1166.5 | 1280.9 | 1383.5 | 1409.2 |
| 47.5°  | 666.1  | 686.4  | 720.6  | 735.6  | 754.8  | 824.3  | 907.7  | 1025.3 | 1144.0 | 1261.6 | 1291.6 |
| 50°    | 599.8  | 616.9  | 640.4  | 650.1  | 671.4  | 722.8  | 791.2  | 886.3  | 1017.8 | 1125.8 | 1181.4 |
| 52.5°  | 539.9  | 552.8  | 570.9  | 578.4  | 593.4  | 631.9  | 693.9  | 768.7  | 877.8  | 989.0  | 1067.0 |
| 55°    | 488.6  | 497.2  | 510.0  | 518.5  | 529.2  | 563.5  | 609.4  | 676.8  | 770.9  | 867.1  | 943.0  |
| 57.5°  | 440.5  | 446.9  | 459.7  | 464.0  | 472.6  | 499.3  | 531.4  | 588.0  | 674.6  | 760.2  | 834.0  |
| 60°    | 395.6  | 399.9  | 407.4  | 417.0  | 423.4  | 441.6  | 471.5  | 518.5  | 588.0  | 666.1  | 726.0  |
| 62.5°  | 352.8  | 359.2  | 361.4  | 365.7  | 371.0  | 388.1  | 411.6  | 445.8  | 506.8  | 570.9  | 634.0  |
| 65°    | 309.0  | 314.3  | 318.6  | 319.7  | 325.0  | 337.9  | 359.2  | 389.2  | 428.7  | 484.3  | 543.1  |
| 67.5°  | 268.4  | 271.6  | 273.7  | 278.0  | 283.3  | 289.7  | 306.9  | 329.3  | 365.7  | 410.6  | 457.6  |
| 70°    | 230.9  | 230.9  | 234.1  | 235.2  | 241.6  | 249.1  | 256.6  | 278.0  | 310.1  | 346.4  | 378.5  |
| 72.5°  | 190.3  | 195.7  | 194.6  | 199.9  | 198.9  | 204.2  | 213.8  | 227.7  | 251.3  | 280.1  | 311.1  |
| 75°    | 155.0  | 158.2  | 158.2  | 158.2  | 160.4  | 164.7  | 170.0  | 182.8  | 201.0  | 224.5  | 242.7  |
| 77.5°  | 120.8  | 123.0  | 123.0  | 123.0  | 124.0  | 128.3  | 133.6  | 142.2  | 155.0  | 168.9  | 179.6  |
| 80°    | 86.6   | 88.7   | 88.7   | 90.9   | 90.9   | 91.9   | 97.3   | 101.6  | 108.0  | 118.7  | 129.4  |
| 82.5°  | 58.8   | 59.9   | 62.0   | 62.0   | 60.9   | 63.1   | 64.2   | 68.4   | 74.8   | 77.0   | 84.5   |
| 85°    | 32.1   | 33.1   | 34.2   | 34.2   | 35.3   | 37.4   | 36.4   | 40.6   | 40.6   | 44.9   | 47.0   |
| 87.5°  | 12.8   | 15.0   | 15.0   | 13.9   | 15.0   | 15.0   | 15.0   | 17.1   | 18.2   | 19.2   | 18.2   |
| 90°    | 10.4   | 10.2   | 10.1   | 10.0   | 9.8    | 9.3    | 8.8    | 8.3    | 7.8    | 7.2    | 6.6    |
| 92.5°  | 16.9   | 16.8   | 16.7   | 16.7   | 16.6   | 16.3   | 16.1   | 15.8   | 15.6   | 15.2   | 14.8   |
| 95°    | 28.1   | 28.1   | 28.1   | 28.1   | 28.0   | 27.7   | 27.5   | 27.2   | 27.0   | 26.4   | 25.9   |
| 97.5°  | 41.2   | 41.2   | 41.2   | 41.2   | 41.0   | 40.7   | 40.4   | 40.1   | 39.8   | 39.2   | 38.6   |
| 100°   | 55.1   | 55.1   | 55.1   | 55.1   | 55.0   | 54.9   | 54.7   | 54.6   | 54.4   | 53.7   | 53.0   |
| 102.5° | 70.6   | 70.5   | 70.4   | 70.4   | 70.3   | 70.0   | 69.8   | 69.5   | 69.3   | 68.7   | 68.1   |
| 105°   | 86.3   | 86.0   | 85.8   | 85.7   | 85.6   | 85.3   | 85.1   | 84.8   | 84.6   | 84.3   | 84.0   |
| 107.5° | 102.2  | 102.3  | 102.4  | 102.4  | 102.2  | 101.9  | 101.6  | 101.2  | 100.9  | 100.8  | 100.8  |
| 110°   | 118.2  | 118.0  | 117.7  | 117.6  | 117.7  | 117.8  | 118.0  | 118.1  | 118.3  | 118.4  | 118.5  |

TEST NUMBER: P1001839

CATALOG NUMBER: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

**CANDELA DISTRIBUTION (continued):**

|        | 100°  | 105°  | 110°  | 112.5° | 115°  | 120°  | 125°  | 130°  | 135°  | 140°  | 145°  |
|--------|-------|-------|-------|--------|-------|-------|-------|-------|-------|-------|-------|
| 112.5° | 135.8 | 135.8 | 135.8 | 135.8  | 135.8 | 135.8 | 135.8 | 135.8 | 135.8 | 136.0 | 136.1 |
| 115°   | 153.7 | 153.8 | 153.9 | 153.9  | 153.9 | 154.0 | 154.1 | 154.1 | 154.2 | 154.4 | 154.6 |
| 117.5° | 170.3 | 170.6 | 170.8 | 170.9  | 171.0 | 171.3 | 171.5 | 171.8 | 172.0 | 172.1 | 172.2 |
| 120°   | 188.8 | 188.6 | 188.5 | 188.4  | 188.6 | 189.0 | 189.3 | 189.7 | 190.1 | 190.3 | 190.6 |
| 122.5° | 205.9 | 206.2 | 206.6 | 206.8  | 206.9 | 207.2 | 207.4 | 207.7 | 207.9 | 208.0 | 208.1 |
| 125°   | 224.2 | 224.4 | 224.5 | 224.6  | 224.7 | 224.8 | 225.0 | 225.1 | 225.3 | 225.4 | 225.5 |
| 127.5° | 241.1 | 241.2 | 241.3 | 241.3  | 241.4 | 241.5 | 241.7 | 241.8 | 242.0 | 242.2 | 242.3 |
| 130°   | 258.3 | 258.6 | 258.9 | 259.1  | 259.2 | 259.3 | 259.5 | 259.6 | 259.8 | 259.8 | 259.8 |
| 132.5° | 275.6 | 275.7 | 275.8 | 275.8  | 275.9 | 276.0 | 276.2 | 276.3 | 276.5 | 276.6 | 276.7 |
| 135°   | 291.9 | 292.1 | 292.4 | 292.5  | 292.6 | 292.7 | 292.9 | 293.0 | 293.2 | 293.2 | 293.2 |
| 137.5° | 308.7 | 308.6 | 308.5 | 308.5  | 308.6 | 308.8 | 309.1 | 309.3 | 309.5 | 309.3 | 309.2 |
| 140°   | 324.6 | 324.7 | 324.8 | 324.8  | 324.8 | 324.9 | 325.0 | 325.1 | 325.2 | 325.2 | 325.2 |
| 142.5° | 340.1 | 340.1 | 340.1 | 340.1  | 340.1 | 340.1 | 340.1 | 340.1 | 340.1 | 340.2 | 340.3 |
| 145°   | 354.4 | 354.7 | 354.9 | 355.0  | 355.0 | 355.1 | 355.2 | 355.3 | 355.4 | 355.3 | 355.2 |
| 147.5° | 368.7 | 368.8 | 368.9 | 368.9  | 368.9 | 369.0 | 369.1 | 369.2 | 369.3 | 369.4 | 369.4 |
| 150°   | 381.9 | 382.0 | 382.1 | 382.1  | 382.1 | 382.1 | 382.1 | 382.1 | 382.1 | 382.1 | 382.1 |
| 152.5° | 394.2 | 394.5 | 394.7 | 394.8  | 394.7 | 394.5 | 394.2 | 394.0 | 393.8 | 393.7 | 393.6 |
| 155°   | 405.4 | 405.7 | 406.0 | 406.2  | 406.0 | 405.7 | 405.4 | 405.1 | 404.8 | 404.9 | 405.0 |
| 157.5° | 415.6 | 415.8 | 416.1 | 416.2  | 416.1 | 415.8 | 415.6 | 415.3 | 415.1 | 415.1 | 415.1 |
| 160°   | 424.4 | 424.8 | 425.2 | 425.4  | 425.3 | 425.0 | 424.8 | 424.5 | 424.3 | 424.4 | 424.5 |
| 162.5° | 433.3 | 433.7 | 434.1 | 434.3  | 434.1 | 433.6 | 433.1 | 432.7 | 432.2 | 432.3 | 432.3 |
| 165°   | 440.6 | 440.9 | 441.2 | 441.4  | 441.2 | 440.7 | 440.2 | 439.8 | 439.3 | 439.5 | 439.6 |
| 167.5° | 446.6 | 447.1 | 447.6 | 447.8  | 447.6 | 447.1 | 446.6 | 446.2 | 445.7 | 445.7 | 445.7 |
| 170°   | 451.4 | 452.0 | 452.5 | 452.8  | 452.6 | 452.1 | 451.6 | 451.1 | 450.6 | 450.5 | 450.5 |
| 172.5° | 455.3 | 455.9 | 456.4 | 456.7  | 456.4 | 455.9 | 455.3 | 454.8 | 454.2 | 454.2 | 454.2 |
| 175°   | 457.8 | 458.4 | 458.9 | 459.2  | 458.9 | 458.4 | 457.8 | 457.3 | 456.7 | 456.8 | 456.8 |
| 177.5° | 459.3 | 460.0 | 460.6 | 460.9  | 460.6 | 460.1 | 459.6 | 459.0 | 458.5 | 458.5 | 458.5 |
| 180°   | 459.5 | 459.5 | 459.5 | 459.5  | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 |

TEST NUMBER: P1001839

CATALOG NUMBER: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

**CANDELA DISTRIBUTION (continued):**

|        | 150°   | 155°   | 157.5° | 160°   | 165°   | 170°   | 175°   | 180°   | 185°   | 190°   | 195°   |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°     | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 |
| 2.5°   | 1331.1 | 1326.8 | 1323.6 | 1323.6 | 1314.0 | 1304.4 | 1299.0 | 1296.9 | 1294.8 | 1286.2 | 1274.4 |
| 5°     | 1385.6 | 1371.7 | 1362.1 | 1352.5 | 1336.5 | 1319.4 | 1302.2 | 1292.6 | 1278.7 | 1259.5 | 1245.6 |
| 7.5°   | 1446.6 | 1413.4 | 1402.7 | 1391.0 | 1358.9 | 1330.0 | 1306.5 | 1286.2 | 1263.8 | 1239.2 | 1214.6 |
| 10°    | 1497.9 | 1462.6 | 1439.1 | 1418.8 | 1377.1 | 1338.6 | 1303.3 | 1273.4 | 1244.5 | 1212.4 | 1182.5 |
| 12.5°  | 1547.1 | 1496.8 | 1472.2 | 1442.3 | 1398.5 | 1342.9 | 1296.9 | 1259.5 | 1216.7 | 1183.6 | 1147.2 |
| 15°    | 1615.5 | 1531.0 | 1490.4 | 1471.2 | 1412.4 | 1347.2 | 1291.6 | 1236.0 | 1200.7 | 1150.4 | 1118.3 |
| 17.5°  | 1626.2 | 1557.8 | 1531.0 | 1481.9 | 1411.3 | 1337.5 | 1273.4 | 1217.8 | 1164.3 | 1119.4 | 1077.7 |
| 20°    | 1663.6 | 1573.8 | 1531.0 | 1500.0 | 1407.0 | 1332.2 | 1261.6 | 1190.0 | 1138.7 | 1090.6 | 1043.5 |
| 22.5°  | 1687.1 | 1585.6 | 1540.7 | 1491.5 | 1402.7 | 1312.9 | 1229.5 | 1167.5 | 1104.4 | 1055.3 | 1017.8 |
| 25°    | 1680.7 | 1579.2 | 1528.9 | 1482.9 | 1374.9 | 1285.1 | 1210.3 | 1131.2 | 1072.4 | 1018.9 | 969.7  |
| 27.5°  | 1677.5 | 1563.1 | 1509.7 | 1458.3 | 1356.8 | 1262.7 | 1168.6 | 1104.4 | 1039.2 | 977.2  | 940.9  |
| 30°    | 1669.0 | 1542.8 | 1480.8 | 1425.2 | 1319.4 | 1221.0 | 1140.8 | 1066.0 | 1000.7 | 944.1  | 896.0  |
| 32.5°  | 1640.1 | 1508.6 | 1448.7 | 1388.8 | 1278.7 | 1180.4 | 1099.1 | 1029.6 | 964.4  | 905.6  | 859.6  |
| 35°    | 1601.6 | 1468.0 | 1402.7 | 1339.7 | 1229.5 | 1130.1 | 1055.3 | 982.6  | 921.6  | 865.0  | 821.1  |
| 37.5°  | 1563.1 | 1420.9 | 1360.0 | 1287.3 | 1185.7 | 1082.0 | 1005.0 | 939.8  | 883.1  | 824.3  | 776.2  |
| 40°    | 1507.5 | 1365.3 | 1298.0 | 1236.0 | 1117.3 | 1020.0 | 949.4  | 890.6  | 835.0  | 779.4  | 738.8  |
| 42.5°  | 1431.6 | 1304.4 | 1234.9 | 1166.5 | 1055.3 | 959.0  | 890.6  | 838.2  | 785.8  | 739.9  | 695.0  |
| 45°    | 1354.6 | 1230.6 | 1168.6 | 1107.7 | 986.8  | 896.0  | 832.9  | 784.8  | 740.9  | 690.7  | 654.3  |
| 47.5°  | 1261.6 | 1156.8 | 1094.8 | 1035.0 | 920.6  | 829.7  | 771.9  | 727.0  | 686.4  | 644.7  | 610.5  |
| 50°    | 1166.5 | 1075.6 | 1018.9 | 956.9  | 847.8  | 765.5  | 708.9  | 671.4  | 638.3  | 598.7  | 570.9  |
| 52.5°  | 1063.8 | 984.7  | 936.6  | 876.7  | 780.5  | 704.6  | 646.8  | 609.4  | 581.6  | 552.8  | 528.2  |
| 55°    | 954.8  | 897.0  | 845.7  | 797.6  | 706.7  | 638.3  | 587.0  | 553.8  | 534.6  | 507.9  | 486.5  |
| 57.5°  | 856.4  | 800.8  | 769.8  | 715.3  | 636.2  | 568.8  | 528.2  | 500.4  | 477.9  | 461.9  | 444.8  |
| 60°    | 753.8  | 708.9  | 674.6  | 635.1  | 565.6  | 508.9  | 466.2  | 450.1  | 426.6  | 414.8  | 407.4  |
| 62.5°  | 655.4  | 623.3  | 591.2  | 561.3  | 499.3  | 445.8  | 413.8  | 393.5  | 379.6  | 367.8  | 361.4  |
| 65°    | 562.4  | 532.4  | 510.0  | 483.3  | 431.9  | 389.2  | 359.2  | 343.2  | 329.3  | 326.1  | 318.6  |
| 67.5°  | 471.5  | 458.7  | 434.1  | 412.7  | 368.9  | 335.7  | 313.3  | 293.0  | 285.5  | 282.3  | 275.8  |
| 70°    | 394.5  | 379.6  | 360.3  | 342.1  | 309.0  | 280.1  | 259.8  | 252.3  | 241.6  | 240.6  | 233.1  |
| 72.5°  | 325.0  | 306.9  | 293.0  | 279.1  | 254.5  | 228.8  | 218.1  | 207.4  | 202.1  | 197.8  | 194.6  |
| 75°    | 257.7  | 244.8  | 235.2  | 223.5  | 202.1  | 185.0  | 170.0  | 165.7  | 162.5  | 161.4  | 159.3  |
| 77.5°  | 192.5  | 183.9  | 179.6  | 167.9  | 152.9  | 137.9  | 131.5  | 125.1  | 125.1  | 123.0  | 124.0  |
| 80°    | 136.9  | 131.5  | 126.2  | 119.7  | 106.9  | 100.5  | 95.2   | 90.9   | 88.7   | 87.7   | 88.7   |
| 82.5°  | 86.6   | 83.4   | 82.3   | 78.0   | 69.5   | 66.3   | 62.0   | 58.8   | 58.8   | 58.8   | 58.8   |
| 85°    | 48.1   | 48.1   | 48.1   | 41.7   | 38.5   | 35.3   | 33.1   | 32.1   | 32.1   | 32.1   | 33.1   |
| 87.5°  | 20.3   | 20.3   | 17.1   | 17.1   | 16.0   | 13.9   | 12.8   | 12.8   | 13.9   | 13.9   | 15.0   |
| 90°    | 5.9    | 5.3    | 5.0    | 4.6    | 3.7    | 2.8    | 2.0    | 1.1    | 2.0    | 2.8    | 3.7    |
| 92.5°  | 14.5   | 14.1   | 13.9   | 13.4   | 12.3   | 11.3   | 10.2   | 9.2    | 10.2   | 11.3   | 12.3   |
| 95°    | 25.3   | 24.8   | 24.5   | 24.1   | 23.4   | 22.7   | 22.0   | 21.3   | 22.0   | 22.7   | 23.4   |
| 97.5°  | 37.9   | 37.3   | 37.0   | 36.7   | 36.0   | 35.4   | 34.7   | 34.1   | 34.7   | 35.4   | 36.0   |
| 100°   | 52.3   | 51.6   | 51.2   | 51.0   | 50.7   | 50.4   | 50.1   | 49.8   | 50.1   | 50.4   | 50.7   |
| 102.5° | 67.4   | 66.8   | 66.5   | 66.5   | 66.4   | 66.3   | 66.2   | 66.1   | 66.2   | 66.3   | 66.4   |
| 105°   | 83.7   | 83.4   | 83.2   | 83.2   | 83.1   | 83.0   | 82.9   | 82.8   | 82.9   | 83.0   | 83.1   |
| 107.5° | 100.7  | 100.6  | 100.6  | 100.6  | 100.5  | 100.4  | 100.3  | 100.2  | 100.3  | 100.4  | 100.5  |
| 110°   | 118.6  | 118.7  | 118.7  | 118.6  | 118.5  | 118.3  | 118.2  | 118.0  | 118.2  | 118.3  | 118.5  |

TEST NUMBER: P1001839

CATALOG NUMBER: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

**CANDELA DISTRIBUTION (continued):**

|        | 150°  | 155°  | 157.5° | 160°  | 165°  | 170°  | 175°  | 180°  | 185°  | 190°  | 195°  |
|--------|-------|-------|--------|-------|-------|-------|-------|-------|-------|-------|-------|
| 112.5° | 136.3 | 136.4 | 136.5  | 136.5 | 136.5 | 136.5 | 136.5 | 136.5 | 136.5 | 136.5 | 136.5 |
| 115°   | 154.7 | 154.9 | 155.0  | 155.0 | 155.0 | 155.0 | 155.0 | 155.0 | 155.0 | 155.0 | 155.0 |
| 117.5° | 172.3 | 172.4 | 172.4  | 172.4 | 172.4 | 172.4 | 172.4 | 172.4 | 172.4 | 172.4 | 172.4 |
| 120°   | 190.8 | 191.1 | 191.2  | 191.0 | 190.7 | 190.4 | 190.1 | 189.8 | 190.1 | 190.4 | 190.7 |
| 122.5° | 208.2 | 208.3 | 208.3  | 208.3 | 208.2 | 208.1 | 208.0 | 207.9 | 208.0 | 208.1 | 208.2 |
| 125°   | 225.6 | 225.7 | 225.7  | 225.7 | 225.7 | 225.7 | 225.7 | 225.7 | 225.7 | 225.7 | 225.7 |
| 127.5° | 242.5 | 242.6 | 242.7  | 242.6 | 242.4 | 242.1 | 241.9 | 241.7 | 241.9 | 242.1 | 242.4 |
| 130°   | 259.8 | 259.8 | 259.8  | 259.7 | 259.4 | 259.2 | 258.9 | 258.7 | 258.9 | 259.2 | 259.4 |
| 132.5° | 276.8 | 276.9 | 276.9  | 276.8 | 276.6 | 276.5 | 276.3 | 276.1 | 276.3 | 276.5 | 276.6 |
| 135°   | 293.2 | 293.2 | 293.2  | 293.0 | 292.5 | 292.0 | 291.6 | 291.1 | 291.6 | 292.0 | 292.5 |
| 137.5° | 309.0 | 308.9 | 308.8  | 308.7 | 308.5 | 308.2 | 308.0 | 307.8 | 308.0 | 308.2 | 308.5 |
| 140°   | 325.2 | 325.2 | 325.2  | 325.1 | 325.0 | 324.8 | 324.7 | 324.5 | 324.7 | 324.8 | 325.0 |
| 142.5° | 340.4 | 340.5 | 340.5  | 340.4 | 340.3 | 340.1 | 340.0 | 339.8 | 340.0 | 340.1 | 340.3 |
| 145°   | 355.1 | 355.0 | 355.0  | 354.8 | 354.5 | 354.2 | 353.9 | 353.6 | 353.9 | 354.2 | 354.5 |
| 147.5° | 369.5 | 369.6 | 369.6  | 369.4 | 369.0 | 368.6 | 368.2 | 367.8 | 368.2 | 368.6 | 369.0 |
| 150°   | 382.1 | 382.1 | 382.1  | 381.9 | 381.6 | 381.3 | 380.9 | 380.6 | 380.9 | 381.3 | 381.6 |
| 152.5° | 393.5 | 393.4 | 393.4  | 393.3 | 393.2 | 393.0 | 392.9 | 392.7 | 392.9 | 393.0 | 393.2 |
| 155°   | 405.1 | 405.2 | 405.2  | 405.2 | 405.2 | 405.2 | 405.2 | 405.2 | 405.2 | 405.2 | 405.2 |
| 157.5° | 415.1 | 415.1 | 415.1  | 415.2 | 415.3 | 415.5 | 415.6 | 415.8 | 415.6 | 415.5 | 415.3 |
| 160°   | 424.6 | 424.7 | 424.7  | 424.7 | 424.8 | 424.9 | 425.0 | 425.1 | 425.0 | 424.9 | 424.8 |
| 162.5° | 432.4 | 432.5 | 432.5  | 432.6 | 432.9 | 433.1 | 433.4 | 433.6 | 433.4 | 433.1 | 432.9 |
| 165°   | 439.8 | 439.9 | 440.0  | 440.1 | 440.3 | 440.6 | 440.8 | 441.0 | 440.8 | 440.6 | 440.3 |
| 167.5° | 445.7 | 445.7 | 445.7  | 445.9 | 446.2 | 446.5 | 446.8 | 447.1 | 446.8 | 446.5 | 446.2 |
| 170°   | 450.4 | 450.3 | 450.3  | 450.5 | 450.9 | 451.3 | 451.7 | 452.1 | 451.7 | 451.3 | 450.9 |
| 172.5° | 454.2 | 454.2 | 454.2  | 454.4 | 454.7 | 455.0 | 455.3 | 455.6 | 455.3 | 455.0 | 454.7 |
| 175°   | 456.9 | 457.0 | 457.0  | 457.2 | 457.6 | 458.0 | 458.4 | 458.8 | 458.4 | 458.0 | 457.6 |
| 177.5° | 458.5 | 458.5 | 458.5  | 458.7 | 459.1 | 459.4 | 459.8 | 460.2 | 459.8 | 459.4 | 459.1 |
| 180°   | 459.5 | 459.5 | 459.5  | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 |

TEST NUMBER: P1001839

CATALOG NUMBER: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

**CANDELA DISTRIBUTION (continued):**

|        | 200°   | 202.5° | 205°   | 210°   | 215°   | 220°   | 225°   | 230°   | 235°   | 240°   | 245°   |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°     | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 |
| 2.5°   | 1271.2 | 1267.0 | 1269.1 | 1258.4 | 1248.8 | 1234.9 | 1223.1 | 1221.0 | 1218.9 | 1225.3 | 1221.0 |
| 5°     | 1234.9 | 1229.5 | 1224.2 | 1211.4 | 1192.1 | 1180.4 | 1163.3 | 1162.2 | 1155.8 | 1146.1 | 1148.3 |
| 7.5°   | 1195.3 | 1192.1 | 1184.6 | 1164.3 | 1147.2 | 1126.9 | 1113.0 | 1101.2 | 1095.9 | 1087.3 | 1084.1 |
| 10°    | 1163.3 | 1151.5 | 1145.1 | 1122.6 | 1102.3 | 1080.9 | 1062.8 | 1054.2 | 1044.6 | 1037.1 | 1031.7 |
| 12.5°  | 1119.4 | 1116.2 | 1098.0 | 1079.9 | 1062.8 | 1038.2 | 1024.3 | 999.7  | 986.8  | 993.3  | 991.1  |
| 15°    | 1090.6 | 1075.6 | 1071.3 | 1045.6 | 1016.8 | 1000.7 | 975.1  | 959.0  | 953.7  | 944.1  | 932.3  |
| 17.5°  | 1052.1 | 1042.4 | 1027.5 | 1003.9 | 970.8  | 948.4  | 930.2  | 915.2  | 908.8  | 896.0  | 886.3  |
| 20°    | 1015.7 | 999.7  | 987.9  | 966.5  | 934.5  | 905.6  | 883.1  | 873.5  | 857.5  | 846.8  | 841.4  |
| 22.5°  | 982.6  | 970.8  | 953.7  | 921.6  | 893.8  | 866.0  | 839.3  | 825.4  | 810.4  | 804.0  | 795.5  |
| 25°    | 941.9  | 922.7  | 910.9  | 875.6  | 845.7  | 823.3  | 798.7  | 780.5  | 771.9  | 761.2  | 759.1  |
| 27.5°  | 902.4  | 884.2  | 870.3  | 839.3  | 802.9  | 774.1  | 759.1  | 746.3  | 731.3  | 731.3  | 726.0  |
| 30°    | 862.8  | 850.0  | 828.6  | 798.7  | 764.5  | 736.7  | 719.5  | 707.8  | 702.4  | 698.2  | 697.1  |
| 32.5°  | 823.3  | 806.2  | 793.3  | 752.7  | 727.0  | 701.4  | 688.5  | 678.9  | 672.5  | 671.4  | 672.5  |
| 35°    | 782.6  | 763.4  | 750.6  | 714.2  | 688.5  | 665.0  | 659.7  | 651.1  | 647.9  | 646.8  | 652.2  |
| 37.5°  | 739.9  | 724.9  | 708.9  | 678.9  | 650.1  | 636.2  | 625.5  | 622.3  | 621.2  | 627.6  | 629.7  |
| 40°    | 700.3  | 687.5  | 672.5  | 640.4  | 619.0  | 604.1  | 598.7  | 595.5  | 599.8  | 606.2  | 609.4  |
| 42.5°  | 662.9  | 644.7  | 632.9  | 604.1  | 584.8  | 576.3  | 569.9  | 569.9  | 574.1  | 581.6  | 587.0  |
| 45°    | 623.3  | 609.4  | 597.7  | 572.0  | 554.9  | 545.3  | 544.2  | 545.3  | 550.6  | 556.0  | 562.4  |
| 47.5°  | 584.8  | 570.9  | 558.1  | 536.7  | 521.8  | 516.4  | 515.3  | 516.4  | 525.0  | 532.4  | 539.9  |
| 50°    | 549.6  | 534.6  | 522.8  | 502.5  | 490.7  | 484.3  | 485.4  | 490.7  | 497.2  | 507.9  | 517.5  |
| 52.5°  | 507.9  | 497.2  | 486.5  | 468.3  | 457.6  | 453.3  | 456.5  | 460.8  | 472.6  | 480.1  | 491.8  |
| 55°    | 467.2  | 457.6  | 449.1  | 435.2  | 426.6  | 423.4  | 425.5  | 431.9  | 441.6  | 454.4  | 468.3  |
| 57.5°  | 429.8  | 419.1  | 410.6  | 400.9  | 391.3  | 392.4  | 393.5  | 402.0  | 413.8  | 425.5  | 441.6  |
| 60°    | 388.1  | 381.7  | 374.2  | 362.4  | 358.2  | 358.2  | 361.4  | 371.0  | 381.7  | 400.9  | 414.8  |
| 62.5°  | 350.7  | 342.1  | 336.8  | 329.3  | 322.9  | 324.0  | 331.4  | 340.0  | 352.8  | 368.9  | 387.0  |
| 65°    | 312.2  | 302.6  | 298.3  | 291.9  | 289.7  | 290.8  | 296.2  | 309.0  | 322.9  | 336.8  | 353.9  |
| 67.5°  | 269.4  | 266.2  | 261.9  | 255.5  | 257.7  | 258.7  | 264.1  | 274.8  | 289.7  | 303.6  | 322.9  |
| 70°    | 233.1  | 226.7  | 225.6  | 220.2  | 220.2  | 223.5  | 234.1  | 241.6  | 255.5  | 270.5  | 290.8  |
| 72.5°  | 194.6  | 189.2  | 189.2  | 185.0  | 188.2  | 191.4  | 196.7  | 207.4  | 220.2  | 235.2  | 252.3  |
| 75°    | 155.0  | 152.9  | 155.0  | 152.9  | 152.9  | 158.2  | 164.7  | 173.2  | 187.1  | 203.1  | 217.0  |
| 77.5°  | 119.7  | 119.7  | 118.7  | 121.9  | 121.9  | 125.1  | 133.6  | 142.2  | 152.9  | 165.7  | 180.7  |
| 80°    | 87.7   | 87.7   | 87.7   | 90.9   | 94.1   | 94.1   | 99.4   | 110.1  | 119.7  | 128.3  | 142.2  |
| 82.5°  | 59.9   | 59.9   | 59.9   | 62.0   | 66.3   | 66.3   | 72.7   | 79.1   | 89.8   | 97.3   | 103.7  |
| 85°    | 36.4   | 36.4   | 35.3   | 37.4   | 38.5   | 41.7   | 47.0   | 51.3   | 56.7   | 63.1   | 69.5   |
| 87.5°  | 16.0   | 16.0   | 17.1   | 18.2   | 19.2   | 21.4   | 23.5   | 25.7   | 31.0   | 33.1   | 36.4   |
| 90°    | 4.6    | 5.0    | 5.3    | 5.9    | 6.6    | 7.2    | 7.8    | 8.3    | 8.8    | 9.3    | 9.8    |
| 92.5°  | 13.4   | 13.9   | 14.1   | 14.5   | 14.8   | 15.2   | 15.6   | 15.8   | 16.1   | 16.3   | 16.6   |
| 95°    | 24.1   | 24.5   | 24.8   | 25.3   | 25.9   | 26.4   | 27.0   | 27.2   | 27.5   | 27.7   | 28.0   |
| 97.5°  | 36.7   | 37.0   | 37.3   | 37.9   | 38.6   | 39.2   | 39.8   | 40.1   | 40.4   | 40.7   | 41.0   |
| 100°   | 51.0   | 51.2   | 51.6   | 52.3   | 53.0   | 53.7   | 54.4   | 54.6   | 54.7   | 54.9   | 55.0   |
| 102.5° | 66.5   | 66.5   | 66.8   | 67.4   | 68.1   | 68.7   | 69.3   | 69.5   | 69.8   | 70.0   | 70.3   |
| 105°   | 83.2   | 83.2   | 83.4   | 83.7   | 84.0   | 84.3   | 84.6   | 84.8   | 85.1   | 85.3   | 85.6   |
| 107.5° | 100.6  | 100.6  | 100.6  | 100.7  | 100.8  | 100.8  | 100.9  | 101.2  | 101.6  | 101.9  | 102.2  |
| 110°   | 118.6  | 118.7  | 118.7  | 118.6  | 118.5  | 118.4  | 118.3  | 118.1  | 118.0  | 117.8  | 117.7  |

TEST NUMBER: P1001839

CATALOG NUMBER: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

**CANDELA DISTRIBUTION (continued):**

|        | 200°  | 202.5° | 205°  | 210°  | 215°  | 220°  | 225°  | 230°  | 235°  | 240°  | 245°  |
|--------|-------|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 112.5° | 136.5 | 136.5  | 136.4 | 136.3 | 136.1 | 136.0 | 135.8 | 135.8 | 135.8 | 135.8 | 135.8 |
| 115°   | 155.0 | 155.0  | 154.9 | 154.7 | 154.6 | 154.4 | 154.2 | 154.1 | 154.1 | 154.0 | 153.9 |
| 117.5° | 172.4 | 172.4  | 172.4 | 172.3 | 172.2 | 172.1 | 172.0 | 171.8 | 171.5 | 171.3 | 171.0 |
| 120°   | 191.0 | 191.2  | 191.1 | 190.8 | 190.6 | 190.3 | 190.1 | 189.7 | 189.3 | 189.0 | 188.6 |
| 122.5° | 208.3 | 208.3  | 208.3 | 208.2 | 208.1 | 208.0 | 207.9 | 207.7 | 207.4 | 207.2 | 206.9 |
| 125°   | 225.7 | 225.7  | 225.7 | 225.6 | 225.5 | 225.4 | 225.3 | 225.1 | 225.0 | 224.8 | 224.7 |
| 127.5° | 242.6 | 242.7  | 242.6 | 242.5 | 242.3 | 242.2 | 242.0 | 241.8 | 241.7 | 241.5 | 241.4 |
| 130°   | 259.7 | 259.8  | 259.8 | 259.8 | 259.8 | 259.8 | 259.8 | 259.6 | 259.5 | 259.3 | 259.2 |
| 132.5° | 276.8 | 276.9  | 276.9 | 276.8 | 276.7 | 276.6 | 276.5 | 276.3 | 276.2 | 276.0 | 275.9 |
| 135°   | 293.0 | 293.2  | 293.2 | 293.2 | 293.2 | 293.2 | 293.2 | 293.0 | 292.9 | 292.7 | 292.6 |
| 137.5° | 308.7 | 308.8  | 308.9 | 309.0 | 309.2 | 309.3 | 309.5 | 309.3 | 309.1 | 308.8 | 308.6 |
| 140°   | 325.1 | 325.2  | 325.2 | 325.2 | 325.2 | 325.2 | 325.2 | 325.1 | 325.0 | 324.9 | 324.8 |
| 142.5° | 340.4 | 340.5  | 340.5 | 340.4 | 340.3 | 340.2 | 340.1 | 340.1 | 340.1 | 340.1 | 340.1 |
| 145°   | 354.8 | 355.0  | 355.0 | 355.1 | 355.2 | 355.3 | 355.4 | 355.3 | 355.2 | 355.1 | 355.0 |
| 147.5° | 369.4 | 369.6  | 369.6 | 369.5 | 369.4 | 369.4 | 369.3 | 369.2 | 369.1 | 369.0 | 368.9 |
| 150°   | 381.9 | 382.1  | 382.1 | 382.1 | 382.1 | 382.1 | 382.1 | 382.1 | 382.1 | 382.1 | 382.1 |
| 152.5° | 393.3 | 393.4  | 393.4 | 393.5 | 393.6 | 393.7 | 393.8 | 394.0 | 394.2 | 394.5 | 394.7 |
| 155°   | 405.2 | 405.2  | 405.2 | 405.1 | 405.0 | 404.9 | 404.8 | 405.1 | 405.4 | 405.7 | 406.0 |
| 157.5° | 415.2 | 415.1  | 415.1 | 415.1 | 415.1 | 415.1 | 415.1 | 415.3 | 415.6 | 415.8 | 416.1 |
| 160°   | 424.7 | 424.7  | 424.7 | 424.6 | 424.5 | 424.4 | 424.3 | 424.5 | 424.8 | 425.0 | 425.3 |
| 162.5° | 432.6 | 432.5  | 432.5 | 432.4 | 432.3 | 432.3 | 432.2 | 432.7 | 433.1 | 433.6 | 434.1 |
| 165°   | 440.1 | 440.0  | 439.9 | 439.8 | 439.6 | 439.5 | 439.3 | 439.8 | 440.2 | 440.7 | 441.2 |
| 167.5° | 445.9 | 445.7  | 445.7 | 445.7 | 445.7 | 445.7 | 445.7 | 446.2 | 446.6 | 447.1 | 447.6 |
| 170°   | 450.5 | 450.3  | 450.3 | 450.4 | 450.5 | 450.5 | 450.6 | 451.1 | 451.6 | 452.1 | 452.6 |
| 172.5° | 454.4 | 454.2  | 454.2 | 454.2 | 454.2 | 454.2 | 454.2 | 454.8 | 455.3 | 455.9 | 456.4 |
| 175°   | 457.2 | 457.0  | 457.0 | 456.9 | 456.8 | 456.8 | 456.7 | 457.3 | 457.8 | 458.4 | 458.9 |
| 177.5° | 458.7 | 458.5  | 458.5 | 458.5 | 458.5 | 458.5 | 458.5 | 459.0 | 459.6 | 460.1 | 460.6 |
| 180°   | 459.5 | 459.5  | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 |

TEST NUMBER: P1001839

CATALOG NUMBER: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

**CANDELA DISTRIBUTION (continued):**

|        | 247.5° | 250°   | 255°   | 260°   | 265°   | 270°   | 275°   | 280°   | 285°   | 290°   | 292.5° |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°     | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 |
| 2.5°   | 1217.8 | 1216.7 | 1211.4 | 1213.5 | 1207.1 | 1209.2 | 1212.4 | 1213.5 | 1217.8 | 1214.6 | 1213.5 |
| 5°     | 1142.9 | 1140.8 | 1137.6 | 1134.4 | 1133.3 | 1137.6 | 1130.1 | 1132.2 | 1134.4 | 1137.6 | 1141.9 |
| 7.5°   | 1082.0 | 1080.9 | 1077.7 | 1072.4 | 1070.2 | 1068.1 | 1069.2 | 1076.7 | 1075.6 | 1074.5 | 1082.0 |
| 10°    | 1026.4 | 1027.5 | 1021.1 | 1020.0 | 1013.6 | 1012.5 | 1013.6 | 1015.7 | 1018.9 | 1023.2 | 1024.3 |
| 12.5°  | 968.7  | 982.6  | 970.8  | 966.5  | 956.9  | 962.3  | 964.4  | 954.8  | 960.1  | 963.3  | 979.4  |
| 15°    | 932.3  | 925.9  | 918.4  | 918.4  | 914.1  | 912.0  | 906.7  | 914.1  | 918.4  | 924.8  | 922.7  |
| 17.5°  | 882.1  | 871.4  | 867.1  | 862.8  | 863.9  | 868.2  | 856.4  | 873.5  | 873.5  | 876.7  | 871.4  |
| 20°    | 838.2  | 829.7  | 824.3  | 822.2  | 819.0  | 816.8  | 815.8  | 820.1  | 826.5  | 828.6  | 834.0  |
| 22.5°  | 792.3  | 792.3  | 783.7  | 780.5  | 778.4  | 775.1  | 780.5  | 777.3  | 781.6  | 785.8  | 794.4  |
| 25°    | 753.8  | 753.8  | 750.6  | 746.3  | 743.1  | 740.9  | 744.1  | 743.1  | 746.3  | 751.6  | 753.8  |
| 27.5°  | 722.8  | 719.5  | 718.5  | 717.4  | 716.3  | 717.4  | 716.3  | 719.5  | 722.8  | 723.8  | 721.7  |
| 30°    | 696.0  | 692.8  | 693.9  | 693.9  | 695.0  | 693.9  | 692.8  | 696.0  | 697.1  | 695.0  | 696.0  |
| 32.5°  | 671.4  | 671.4  | 673.6  | 674.6  | 674.6  | 675.7  | 676.8  | 674.6  | 675.7  | 672.5  | 673.6  |
| 35°    | 651.1  | 653.3  | 655.4  | 656.5  | 657.5  | 656.5  | 658.6  | 657.5  | 655.4  | 653.3  | 652.2  |
| 37.5°  | 630.8  | 632.9  | 637.2  | 638.3  | 641.5  | 642.6  | 640.4  | 640.4  | 639.4  | 635.1  | 632.9  |
| 40°    | 609.4  | 611.6  | 616.9  | 620.1  | 622.3  | 625.5  | 623.3  | 623.3  | 619.0  | 614.8  | 611.6  |
| 42.5°  | 589.1  | 593.4  | 598.7  | 601.9  | 606.2  | 606.2  | 606.2  | 604.1  | 598.7  | 594.5  | 591.2  |
| 45°    | 568.8  | 569.9  | 577.4  | 582.7  | 587.0  | 587.0  | 587.0  | 583.8  | 580.6  | 572.0  | 567.7  |
| 47.5°  | 546.3  | 549.6  | 558.1  | 563.5  | 567.7  | 568.8  | 568.8  | 565.6  | 559.2  | 551.7  | 546.3  |
| 50°    | 521.8  | 527.1  | 536.7  | 544.2  | 549.6  | 551.7  | 548.5  | 546.3  | 538.9  | 530.3  | 523.9  |
| 52.5°  | 498.2  | 504.6  | 516.4  | 522.8  | 530.3  | 531.4  | 530.3  | 527.1  | 518.5  | 506.8  | 501.4  |
| 55°    | 474.7  | 480.1  | 492.9  | 503.6  | 510.0  | 512.1  | 510.0  | 504.6  | 494.0  | 482.2  | 476.8  |
| 57.5°  | 449.1  | 456.5  | 470.4  | 481.1  | 488.6  | 489.7  | 487.5  | 482.2  | 473.6  | 458.7  | 451.2  |
| 60°    | 422.3  | 431.9  | 445.8  | 456.5  | 466.2  | 467.2  | 465.1  | 457.6  | 446.9  | 431.9  | 425.5  |
| 62.5°  | 395.6  | 403.1  | 419.1  | 430.9  | 438.4  | 443.7  | 439.4  | 431.9  | 421.3  | 406.3  | 396.7  |
| 65°    | 364.6  | 375.3  | 389.2  | 399.9  | 408.4  | 409.5  | 407.4  | 400.9  | 389.2  | 373.1  | 365.7  |
| 67.5°  | 334.6  | 342.1  | 356.0  | 369.9  | 373.1  | 376.3  | 373.1  | 366.7  | 357.1  | 343.2  | 332.5  |
| 70°    | 298.3  | 304.7  | 321.8  | 331.4  | 335.7  | 338.9  | 336.8  | 330.4  | 321.8  | 309.0  | 300.4  |
| 72.5°  | 261.9  | 267.3  | 283.3  | 290.8  | 299.4  | 298.3  | 297.2  | 293.0  | 281.2  | 272.6  | 267.3  |
| 75°    | 223.5  | 229.9  | 240.6  | 250.2  | 253.4  | 253.4  | 253.4  | 250.2  | 242.7  | 228.8  | 223.5  |
| 77.5°  | 188.2  | 191.4  | 199.9  | 205.3  | 208.5  | 209.6  | 208.5  | 203.1  | 198.9  | 189.2  | 186.0  |
| 80°    | 144.3  | 152.9  | 159.3  | 160.4  | 164.7  | 164.7  | 164.7  | 162.5  | 158.2  | 148.6  | 147.5  |
| 82.5°  | 109.1  | 111.2  | 117.6  | 120.8  | 123.0  | 121.9  | 121.9  | 117.6  | 116.5  | 111.2  | 109.1  |
| 85°    | 73.8   | 77.0   | 75.9   | 80.2   | 81.3   | 79.1   | 79.1   | 81.3   | 75.9   | 77.0   | 73.8   |
| 87.5°  | 40.6   | 40.6   | 42.8   | 41.7   | 46.0   | 46.0   | 43.8   | 44.9   | 42.8   | 41.7   | 40.6   |
| 90°    | 10.0   | 10.1   | 10.2   | 10.4   | 10.5   | 10.7   | 10.5   | 10.4   | 10.2   | 10.1   | 10.0   |
| 92.5°  | 16.7   | 16.7   | 16.8   | 16.9   | 17.0   | 17.1   | 17.0   | 16.9   | 16.8   | 16.7   | 16.7   |
| 95°    | 28.1   | 28.1   | 28.1   | 28.1   | 28.1   | 28.1   | 28.1   | 28.1   | 28.1   | 28.1   | 28.1   |
| 97.5°  | 41.2   | 41.2   | 41.2   | 41.2   | 41.2   | 41.2   | 41.2   | 41.2   | 41.2   | 41.2   | 41.2   |
| 100°   | 55.1   | 55.1   | 55.1   | 55.1   | 55.1   | 55.1   | 55.1   | 55.1   | 55.1   | 55.1   | 55.1   |
| 102.5° | 70.4   | 70.4   | 70.5   | 70.6   | 70.6   | 70.7   | 70.6   | 70.6   | 70.5   | 70.4   | 70.4   |
| 105°   | 85.7   | 85.8   | 86.0   | 86.3   | 86.5   | 86.7   | 86.5   | 86.3   | 86.0   | 85.8   | 85.7   |
| 107.5° | 102.4  | 102.4  | 102.3  | 102.2  | 102.1  | 102.0  | 102.1  | 102.2  | 102.3  | 102.4  | 102.4  |
| 110°   | 117.6  | 117.7  | 118.0  | 118.2  | 118.5  | 118.7  | 118.5  | 118.2  | 118.0  | 117.7  | 117.6  |

TEST NUMBER: P1001839

CATALOG NUMBER: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

**CANDELA DISTRIBUTION (continued):**

|        | 247.5° | 250°  | 255°  | 260°  | 265°  | 270°  | 275°  | 280°  | 285°  | 290°  | 292.5° |
|--------|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--------|
| 112.5° | 135.8  | 135.8 | 135.8 | 135.8 | 135.8 | 135.8 | 135.8 | 135.8 | 135.8 | 135.8 | 135.8  |
| 115°   | 153.9  | 153.9 | 153.8 | 153.7 | 153.6 | 153.5 | 153.6 | 153.7 | 153.8 | 153.9 | 153.9  |
| 117.5° | 170.9  | 170.8 | 170.6 | 170.3 | 170.1 | 169.9 | 170.1 | 170.3 | 170.6 | 170.8 | 170.9  |
| 120°   | 188.4  | 188.5 | 188.6 | 188.8 | 188.9 | 189.1 | 188.9 | 188.8 | 188.6 | 188.5 | 188.4  |
| 122.5° | 206.8  | 206.6 | 206.2 | 205.9 | 205.5 | 205.1 | 205.5 | 205.9 | 206.2 | 206.6 | 206.8  |
| 125°   | 224.6  | 224.5 | 224.4 | 224.2 | 224.1 | 223.9 | 224.1 | 224.2 | 224.4 | 224.5 | 224.6  |
| 127.5° | 241.3  | 241.3 | 241.2 | 241.1 | 241.1 | 241.0 | 241.1 | 241.1 | 241.2 | 241.3 | 241.3  |
| 130°   | 259.1  | 258.9 | 258.6 | 258.3 | 258.0 | 257.7 | 258.0 | 258.3 | 258.6 | 258.9 | 259.1  |
| 132.5° | 275.8  | 275.8 | 275.7 | 275.6 | 275.5 | 275.4 | 275.5 | 275.6 | 275.7 | 275.8 | 275.8  |
| 135°   | 292.5  | 292.4 | 292.1 | 291.9 | 291.6 | 291.4 | 291.6 | 291.9 | 292.1 | 292.4 | 292.5  |
| 137.5° | 308.5  | 308.5 | 308.6 | 308.7 | 308.7 | 308.8 | 308.7 | 308.7 | 308.6 | 308.5 | 308.5  |
| 140°   | 324.8  | 324.8 | 324.7 | 324.6 | 324.6 | 324.5 | 324.6 | 324.6 | 324.7 | 324.8 | 324.8  |
| 142.5° | 340.1  | 340.1 | 340.1 | 340.1 | 340.1 | 340.1 | 340.1 | 340.1 | 340.1 | 340.1 | 340.1  |
| 145°   | 355.0  | 354.9 | 354.7 | 354.4 | 354.2 | 354.0 | 354.2 | 354.4 | 354.7 | 354.9 | 355.0  |
| 147.5° | 368.9  | 368.9 | 368.8 | 368.7 | 368.6 | 368.5 | 368.6 | 368.7 | 368.8 | 368.9 | 368.9  |
| 150°   | 382.1  | 382.1 | 382.0 | 381.9 | 381.8 | 381.7 | 381.8 | 381.9 | 382.0 | 382.1 | 382.1  |
| 152.5° | 394.8  | 394.7 | 394.5 | 394.2 | 394.0 | 393.8 | 394.0 | 394.2 | 394.5 | 394.7 | 394.8  |
| 155°   | 406.2  | 406.0 | 405.7 | 405.4 | 405.1 | 404.8 | 405.1 | 405.4 | 405.7 | 406.0 | 406.2  |
| 157.5° | 416.2  | 416.1 | 415.8 | 415.6 | 415.3 | 415.1 | 415.3 | 415.6 | 415.8 | 416.1 | 416.2  |
| 160°   | 425.4  | 425.2 | 424.8 | 424.4 | 424.0 | 423.6 | 424.0 | 424.4 | 424.8 | 425.2 | 425.4  |
| 162.5° | 434.3  | 434.1 | 433.7 | 433.3 | 432.9 | 432.5 | 432.9 | 433.3 | 433.7 | 434.1 | 434.3  |
| 165°   | 441.4  | 441.2 | 440.9 | 440.6 | 440.3 | 440.0 | 440.3 | 440.6 | 440.9 | 441.2 | 441.4  |
| 167.5° | 447.8  | 447.6 | 447.1 | 446.6 | 446.2 | 445.7 | 446.2 | 446.6 | 447.1 | 447.6 | 447.8  |
| 170°   | 452.8  | 452.5 | 452.0 | 451.4 | 450.9 | 450.3 | 450.9 | 451.4 | 452.0 | 452.5 | 452.8  |
| 172.5° | 456.7  | 456.4 | 455.9 | 455.3 | 454.8 | 454.2 | 454.8 | 455.3 | 455.9 | 456.4 | 456.7  |
| 175°   | 459.2  | 458.9 | 458.4 | 457.8 | 457.3 | 456.7 | 457.3 | 457.8 | 458.4 | 458.9 | 459.2  |
| 177.5° | 460.9  | 460.6 | 460.0 | 459.3 | 458.7 | 458.1 | 458.7 | 459.3 | 460.0 | 460.6 | 460.9  |
| 180°   | 459.5  | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5  |

TEST NUMBER: P1001839

CATALOG NUMBER: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

**CANDELA DISTRIBUTION (continued):**

|        | 295°   | 300°   | 305°   | 310°   | 315°   | 320°   | 325°   | 330°   | 335°   | 337.5° | 340°   |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°     | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 | 1290.5 |
| 2.5°   | 1213.5 | 1219.9 | 1213.5 | 1217.8 | 1219.9 | 1225.3 | 1227.4 | 1237.0 | 1240.2 | 1247.7 | 1247.7 |
| 5°     | 1140.8 | 1144.0 | 1145.1 | 1149.4 | 1153.6 | 1164.3 | 1171.8 | 1185.7 | 1201.7 | 1203.9 | 1213.5 |
| 7.5°   | 1082.0 | 1087.3 | 1095.9 | 1092.7 | 1100.2 | 1116.2 | 1125.8 | 1142.9 | 1159.0 | 1167.5 | 1179.3 |
| 10°    | 1029.6 | 1036.0 | 1039.2 | 1042.4 | 1056.3 | 1070.2 | 1085.2 | 1097.0 | 1118.3 | 1131.2 | 1140.8 |
| 12.5°  | 986.8  | 981.5  | 987.9  | 999.7  | 1015.7 | 1024.3 | 1044.6 | 1062.8 | 1078.8 | 1092.7 | 1101.2 |
| 15°    | 931.2  | 935.5  | 941.9  | 962.3  | 966.5  | 987.9  | 995.4  | 1015.7 | 1045.6 | 1058.5 | 1069.2 |
| 17.5°  | 877.8  | 891.7  | 904.5  | 912.0  | 924.8  | 941.9  | 963.3  | 985.8  | 1005.0 | 1020.0 | 1032.8 |
| 20°    | 835.0  | 848.9  | 856.4  | 861.7  | 874.6  | 898.1  | 918.4  | 946.2  | 970.8  | 982.6  | 999.7  |
| 22.5°  | 800.8  | 800.8  | 811.5  | 827.5  | 835.0  | 857.5  | 874.6  | 904.5  | 931.2  | 946.2  | 962.3  |
| 25°    | 758.0  | 764.5  | 773.0  | 786.9  | 797.6  | 815.8  | 840.4  | 866.0  | 894.9  | 907.7  | 928.0  |
| 27.5°  | 722.8  | 730.2  | 742.0  | 745.2  | 755.9  | 771.9  | 797.6  | 825.4  | 855.3  | 869.2  | 886.3  |
| 30°    | 696.0  | 700.3  | 704.6  | 711.0  | 720.6  | 734.5  | 755.9  | 780.5  | 816.8  | 827.5  | 848.9  |
| 32.5°  | 672.5  | 674.6  | 676.8  | 682.1  | 687.5  | 701.4  | 718.5  | 745.2  | 775.1  | 791.2  | 810.4  |
| 35°    | 651.1  | 649.0  | 650.1  | 653.3  | 658.6  | 664.0  | 682.1  | 704.6  | 732.4  | 751.6  | 766.6  |
| 37.5°  | 630.8  | 626.5  | 625.5  | 625.5  | 627.6  | 634.0  | 647.9  | 667.2  | 697.1  | 713.1  | 728.1  |
| 40°    | 608.4  | 604.1  | 601.9  | 600.9  | 599.8  | 604.1  | 614.8  | 634.0  | 657.5  | 672.5  | 689.6  |
| 42.5°  | 587.0  | 582.7  | 577.4  | 576.3  | 574.1  | 576.3  | 583.8  | 601.9  | 622.3  | 637.2  | 651.1  |
| 45°    | 565.6  | 558.1  | 551.7  | 547.4  | 548.5  | 545.3  | 550.6  | 564.5  | 588.0  | 597.7  | 611.6  |
| 47.5°  | 542.1  | 533.5  | 525.0  | 520.7  | 516.4  | 518.5  | 520.7  | 532.4  | 552.8  | 562.4  | 576.3  |
| 50°    | 519.6  | 507.9  | 498.2  | 492.9  | 489.7  | 487.5  | 489.7  | 501.4  | 516.4  | 525.0  | 536.7  |
| 52.5°  | 494.0  | 482.2  | 472.6  | 464.0  | 459.7  | 456.5  | 457.6  | 468.3  | 482.2  | 490.7  | 502.5  |
| 55°    | 470.4  | 455.5  | 442.6  | 431.9  | 428.7  | 427.7  | 426.6  | 434.1  | 445.8  | 454.4  | 464.0  |
| 57.5°  | 443.7  | 428.7  | 414.8  | 402.0  | 395.6  | 394.5  | 394.5  | 396.7  | 411.6  | 418.0  | 423.4  |
| 60°    | 417.0  | 400.9  | 386.0  | 374.2  | 364.6  | 361.4  | 360.3  | 364.6  | 372.1  | 378.5  | 386.0  |
| 62.5°  | 387.0  | 371.0  | 352.8  | 342.1  | 332.5  | 324.0  | 327.2  | 328.2  | 338.9  | 342.1  | 348.5  |
| 65°    | 358.2  | 340.0  | 325.0  | 307.9  | 297.2  | 291.9  | 289.7  | 291.9  | 300.4  | 301.5  | 305.8  |
| 67.5°  | 325.0  | 307.9  | 289.7  | 278.0  | 268.4  | 258.7  | 256.6  | 256.6  | 260.9  | 264.1  | 269.4  |
| 70°    | 293.0  | 275.8  | 255.5  | 242.7  | 233.1  | 224.5  | 221.3  | 220.2  | 223.5  | 225.6  | 230.9  |
| 72.5°  | 255.5  | 238.4  | 223.5  | 209.6  | 197.8  | 191.4  | 188.2  | 186.0  | 189.2  | 191.4  | 192.5  |
| 75°    | 216.0  | 202.1  | 187.1  | 173.2  | 165.7  | 159.3  | 155.0  | 151.8  | 154.0  | 154.0  | 154.0  |
| 77.5°  | 178.6  | 164.7  | 152.9  | 143.3  | 133.6  | 126.2  | 123.0  | 119.7  | 120.8  | 120.8  | 123.0  |
| 80°    | 139.0  | 129.4  | 119.7  | 111.2  | 102.6  | 96.2   | 94.1   | 90.9   | 88.7   | 87.7   | 87.7   |
| 82.5°  | 102.6  | 95.2   | 86.6   | 79.1   | 74.8   | 68.4   | 66.3   | 62.0   | 62.0   | 60.9   | 60.9   |
| 85°    | 68.4   | 64.2   | 55.6   | 50.3   | 47.0   | 43.8   | 41.7   | 39.6   | 36.4   | 36.4   | 35.3   |
| 87.5°  | 36.4   | 34.2   | 32.1   | 25.7   | 25.7   | 22.5   | 21.4   | 20.3   | 17.1   | 18.2   | 18.2   |
| 90°    | 9.8    | 9.3    | 8.8    | 8.3    | 7.8    | 7.2    | 6.6    | 5.9    | 5.3    | 5.0    | 4.6    |
| 92.5°  | 16.6   | 16.3   | 16.1   | 15.8   | 15.6   | 15.2   | 14.8   | 14.5   | 14.1   | 13.9   | 13.4   |
| 95°    | 28.0   | 27.7   | 27.5   | 27.2   | 27.0   | 26.4   | 25.9   | 25.3   | 24.8   | 24.5   | 24.1   |
| 97.5°  | 41.0   | 40.7   | 40.4   | 40.1   | 39.8   | 39.2   | 38.6   | 37.9   | 37.3   | 37.0   | 36.7   |
| 100°   | 55.0   | 54.9   | 54.7   | 54.6   | 54.4   | 53.7   | 53.0   | 52.3   | 51.6   | 51.2   | 51.0   |
| 102.5° | 70.3   | 70.0   | 69.8   | 69.5   | 69.3   | 68.7   | 68.1   | 67.4   | 66.8   | 66.5   | 66.5   |
| 105°   | 85.6   | 85.3   | 85.1   | 84.8   | 84.6   | 84.3   | 84.0   | 83.7   | 83.4   | 83.2   | 83.2   |
| 107.5° | 102.2  | 101.9  | 101.6  | 101.2  | 100.9  | 100.8  | 100.8  | 100.7  | 100.6  | 100.6  | 100.6  |
| 110°   | 117.7  | 117.8  | 118.0  | 118.1  | 118.3  | 118.4  | 118.5  | 118.6  | 118.7  | 118.7  | 118.6  |

TEST NUMBER: P1001839

CATALOG NUMBER: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

**CANDELA DISTRIBUTION (continued):**

|        | 295°  | 300°  | 305°  | 310°  | 315°  | 320°  | 325°  | 330°  | 335°  | 337.5° | 340°  |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--------|-------|
| 112.5° | 135.8 | 135.8 | 135.8 | 135.8 | 135.8 | 136.0 | 136.1 | 136.3 | 136.4 | 136.5  | 136.5 |
| 115°   | 153.9 | 154.0 | 154.1 | 154.1 | 154.2 | 154.4 | 154.6 | 154.7 | 154.9 | 155.0  | 155.0 |
| 117.5° | 171.0 | 171.3 | 171.5 | 171.8 | 172.0 | 172.1 | 172.2 | 172.3 | 172.4 | 172.4  | 172.4 |
| 120°   | 188.6 | 189.0 | 189.3 | 189.7 | 190.1 | 190.3 | 190.6 | 190.8 | 191.1 | 191.2  | 191.0 |
| 122.5° | 206.9 | 207.2 | 207.4 | 207.7 | 207.9 | 208.0 | 208.1 | 208.2 | 208.3 | 208.3  | 208.3 |
| 125°   | 224.7 | 224.8 | 225.0 | 225.1 | 225.3 | 225.4 | 225.5 | 225.6 | 225.7 | 225.7  | 225.7 |
| 127.5° | 241.4 | 241.5 | 241.7 | 241.8 | 242.0 | 242.2 | 242.3 | 242.5 | 242.6 | 242.7  | 242.6 |
| 130°   | 259.2 | 259.3 | 259.5 | 259.6 | 259.8 | 259.8 | 259.8 | 259.8 | 259.8 | 259.8  | 259.7 |
| 132.5° | 275.9 | 276.0 | 276.2 | 276.3 | 276.5 | 276.6 | 276.7 | 276.8 | 276.9 | 276.9  | 276.8 |
| 135°   | 292.6 | 292.7 | 292.9 | 293.0 | 293.2 | 293.2 | 293.2 | 293.2 | 293.2 | 293.2  | 293.0 |
| 137.5° | 308.6 | 308.8 | 309.1 | 309.3 | 309.5 | 309.3 | 309.2 | 309.0 | 308.9 | 308.8  | 308.7 |
| 140°   | 324.8 | 324.9 | 325.0 | 325.1 | 325.2 | 325.2 | 325.2 | 325.2 | 325.2 | 325.2  | 325.1 |
| 142.5° | 340.1 | 340.1 | 340.1 | 340.1 | 340.1 | 340.2 | 340.3 | 340.4 | 340.5 | 340.5  | 340.4 |
| 145°   | 355.0 | 355.1 | 355.2 | 355.3 | 355.4 | 355.3 | 355.2 | 355.1 | 355.0 | 355.0  | 354.8 |
| 147.5° | 368.9 | 369.0 | 369.1 | 369.2 | 369.3 | 369.4 | 369.4 | 369.5 | 369.6 | 369.6  | 369.4 |
| 150°   | 382.1 | 382.1 | 382.1 | 382.1 | 382.1 | 382.1 | 382.1 | 382.1 | 382.1 | 382.1  | 381.9 |
| 152.5° | 394.7 | 394.5 | 394.2 | 394.0 | 393.8 | 393.7 | 393.6 | 393.5 | 393.4 | 393.4  | 393.3 |
| 155°   | 406.0 | 405.7 | 405.4 | 405.1 | 404.8 | 404.9 | 405.0 | 405.1 | 405.2 | 405.2  | 405.2 |
| 157.5° | 416.1 | 415.8 | 415.6 | 415.3 | 415.1 | 415.1 | 415.1 | 415.1 | 415.1 | 415.1  | 415.2 |
| 160°   | 425.3 | 425.0 | 424.8 | 424.5 | 424.3 | 424.4 | 424.5 | 424.6 | 424.7 | 424.7  | 424.7 |
| 162.5° | 434.1 | 433.6 | 433.1 | 432.7 | 432.2 | 432.3 | 432.3 | 432.4 | 432.5 | 432.5  | 432.6 |
| 165°   | 441.2 | 440.7 | 440.2 | 439.8 | 439.3 | 439.5 | 439.6 | 439.8 | 439.9 | 440.0  | 440.1 |
| 167.5° | 447.6 | 447.1 | 446.6 | 446.2 | 445.7 | 445.7 | 445.7 | 445.7 | 445.7 | 445.7  | 445.9 |
| 170°   | 452.6 | 452.1 | 451.6 | 451.1 | 450.6 | 450.5 | 450.5 | 450.4 | 450.3 | 450.3  | 450.5 |
| 172.5° | 456.4 | 455.9 | 455.3 | 454.8 | 454.2 | 454.2 | 454.2 | 454.2 | 454.2 | 454.2  | 454.4 |
| 175°   | 458.9 | 458.4 | 457.8 | 457.3 | 456.7 | 456.8 | 456.8 | 456.9 | 457.0 | 457.0  | 457.2 |
| 177.5° | 460.6 | 460.1 | 459.6 | 459.0 | 458.5 | 458.5 | 458.5 | 458.5 | 458.5 | 458.5  | 458.7 |
| 180°   | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5 | 459.5  | 459.5 |

TEST NUMBER: P1001839

CATALOG NUMBER: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

**CANDELA DISTRIBUTION (continued):**

|        | 345°   | 350°   | 355°   | 360°   |
|--------|--------|--------|--------|--------|
| 0°     | 1290.5 | 1290.5 | 1290.5 | 1290.5 |
| 2.5°   | 1255.2 | 1265.9 | 1275.5 | 1290.5 |
| 5°     | 1227.4 | 1242.4 | 1262.7 | 1285.1 |
| 7.5°   | 1195.3 | 1218.9 | 1245.6 | 1276.6 |
| 10°    | 1165.4 | 1192.1 | 1226.3 | 1263.8 |
| 12.5°  | 1134.4 | 1166.5 | 1203.9 | 1244.5 |
| 15°    | 1099.1 | 1131.2 | 1172.9 | 1227.4 |
| 17.5°  | 1067.0 | 1105.5 | 1150.4 | 1208.2 |
| 20°    | 1029.6 | 1066.0 | 1115.1 | 1181.4 |
| 22.5°  | 996.5  | 1038.2 | 1092.7 | 1150.4 |
| 25°    | 960.1  | 996.5  | 1051.0 | 1120.5 |
| 27.5°  | 923.8  | 968.7  | 1021.1 | 1088.4 |
| 30°    | 888.5  | 925.9  | 982.6  | 1053.1 |
| 32.5°  | 850.0  | 894.9  | 947.3  | 1013.6 |
| 35°    | 808.3  | 851.1  | 900.2  | 971.9  |
| 37.5°  | 770.9  | 812.6  | 862.8  | 925.9  |
| 40°    | 729.2  | 773.0  | 819.0  | 882.1  |
| 42.5°  | 688.5  | 728.1  | 774.1  | 831.8  |
| 45°    | 649.0  | 683.2  | 724.9  | 775.1  |
| 47.5°  | 608.4  | 637.2  | 675.7  | 720.6  |
| 50°    | 564.5  | 595.5  | 624.4  | 661.8  |
| 52.5°  | 523.9  | 550.6  | 574.1  | 605.1  |
| 55°    | 484.3  | 502.5  | 521.8  | 545.3  |
| 57.5°  | 442.6  | 456.5  | 470.4  | 495.0  |
| 60°    | 400.9  | 413.8  | 421.3  | 437.3  |
| 62.5°  | 360.3  | 365.7  | 375.3  | 384.9  |
| 65°    | 315.4  | 322.9  | 328.2  | 340.0  |
| 67.5°  | 274.8  | 278.0  | 283.3  | 290.8  |
| 70°    | 232.0  | 239.5  | 241.6  | 247.0  |
| 72.5°  | 195.7  | 198.9  | 201.0  | 202.1  |
| 75°    | 155.0  | 158.2  | 160.4  | 166.8  |
| 77.5°  | 121.9  | 120.8  | 125.1  | 126.2  |
| 80°    | 89.8   | 86.6   | 87.7   | 91.9   |
| 82.5°  | 58.8   | 59.9   | 58.8   | 58.8   |
| 85°    | 36.4   | 35.3   | 33.1   | 34.2   |
| 87.5°  | 16.0   | 16.0   | 15.0   | 15.0   |
| 90°    | 3.7    | 2.8    | 2.0    | 1.1    |
| 92.5°  | 12.3   | 11.3   | 10.2   | 9.2    |
| 95°    | 23.4   | 22.7   | 22.0   | 21.3   |
| 97.5°  | 36.0   | 35.4   | 34.7   | 34.1   |
| 100°   | 50.7   | 50.4   | 50.1   | 49.8   |
| 102.5° | 66.4   | 66.3   | 66.2   | 66.1   |
| 105°   | 83.1   | 83.0   | 82.9   | 82.8   |
| 107.5° | 100.5  | 100.4  | 100.3  | 100.2  |
| 110°   | 118.5  | 118.3  | 118.2  | 118.0  |

TEST NUMBER: P1001839

CATALOG NUMBER: SA4XXDIP-B795D365UB30-4F0-XX-W2A-A1

**CANDELA DISTRIBUTION (continued):**

|        | 345°  | 350°  | 355°  | 360°  |
|--------|-------|-------|-------|-------|
| 112.5° | 136.5 | 136.5 | 136.5 | 136.5 |
| 115°   | 155.0 | 155.0 | 155.0 | 155.0 |
| 117.5° | 172.4 | 172.4 | 172.4 | 172.4 |
| 120°   | 190.7 | 190.4 | 190.1 | 189.8 |
| 122.5° | 208.2 | 208.1 | 208.0 | 207.9 |
| 125°   | 225.7 | 225.7 | 225.7 | 225.7 |
| 127.5° | 242.4 | 242.1 | 241.9 | 241.7 |
| 130°   | 259.4 | 259.2 | 258.9 | 258.7 |
| 132.5° | 276.6 | 276.5 | 276.3 | 276.1 |
| 135°   | 292.5 | 292.0 | 291.6 | 291.1 |
| 137.5° | 308.5 | 308.2 | 308.0 | 307.8 |
| 140°   | 325.0 | 324.8 | 324.7 | 324.5 |
| 142.5° | 340.3 | 340.1 | 340.0 | 339.8 |
| 145°   | 354.5 | 354.2 | 353.9 | 353.6 |
| 147.5° | 369.0 | 368.6 | 368.2 | 367.8 |
| 150°   | 381.6 | 381.3 | 380.9 | 380.6 |
| 152.5° | 393.2 | 393.0 | 392.9 | 392.7 |
| 155°   | 405.2 | 405.2 | 405.2 | 405.2 |
| 157.5° | 415.3 | 415.5 | 415.6 | 415.8 |
| 160°   | 424.8 | 424.9 | 425.0 | 425.1 |
| 162.5° | 432.9 | 433.1 | 433.4 | 433.6 |
| 165°   | 440.3 | 440.6 | 440.8 | 441.0 |
| 167.5° | 446.2 | 446.5 | 446.8 | 447.1 |
| 170°   | 450.9 | 451.3 | 451.7 | 452.1 |
| 172.5° | 454.7 | 455.0 | 455.3 | 455.6 |
| 175°   | 457.6 | 458.0 | 458.4 | 458.8 |
| 177.5° | 459.1 | 459.4 | 459.8 | 460.2 |
| 180°   | 459.5 | 459.5 | 459.5 | 459.5 |

(END OF REPORT)