

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1000331

Luminaire Tested: SA4XXDP-B350DB2750-4F0-XX-W2A-D_5000K

Issue Date: 5/2/2025

Test Information

Test Method: LM-79-2019
Report Number: P1000331
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1802-639-16)
Test Lab: INNOVATION CENTER
Issue Date: 5/2/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: SA4XXDP-B350DB2750-4F0-XX-W2A-D_5000K
Description: Define 4 Direct Recessed with 5000K BioUP LEDs {m-DER=1.015} {m-EER=1.115}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1349.0 lumens
Efficiency: N/A
Efficacy: 103.8 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.28 / 1.39
Luminous Opening: Rectangular (W 0.33' x L: 4' x H: 0')
CIE Type: Direct

Input Watts (W): 13
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1000331

CATALOG NUMBER: SA4XXDP-B350DB2750-4F0-XX-W2A-D_5000K

Luminous Intensity Polar Plot



TEST NUMBER: P1000331

CATALOG NUMBER: SA4XXDP-B350DB2750-4F0-XX-W2A-D_5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	117	117	117	117	114	114	114	114	107	107	107	101	101	101	95	95	95
1	105	100	95	91	102	97	93	89	91	88	84	86	83	80	81	79	77
2	95	86	79	73	92	84	77	71	79	73	68	74	70	66	70	67	63
3	87	75	67	60	83	73	65	59	69	62	57	65	60	55	62	57	53
4	79	66	57	50	76	65	56	49	61	54	48	58	52	47	55	49	45
5	73	59	50	43	70	58	49	42	55	47	41	52	45	40	49	44	39
6	67	53	44	37	64	52	43	37	49	42	36	47	40	35	45	39	34
7	62	48	39	33	60	47	38	32	45	37	32	43	36	31	41	35	30
8	58	44	35	29	56	43	35	29	41	33	28	39	32	28	37	31	27
9	54	40	32	26	52	39	31	26	38	30	25	36	29	25	34	29	24
10	50	37	29	24	49	36	29	23	35	28	23	33	27	23	32	26	22

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	3227	3227	3227
5°	3242	3206	3232
10°	3228	3207	3236
15°	3205	3198	3228
20°	3168	3184	3222
25°	3126	3162	3209
30°	3079	3141	3196
35°	3026	3123	3197
40°	2986	3113	3203
45°	2922	3117	3229
50°	2872	3120	3265
55°	2822	3143	3307
60°	2738	3166	3389
65°	2651	3215	3496
70°	2546	3307	3665
75°	2401	3504	4020
80°	2268	4015	4809
85°	2199	5801	7466

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 90°

Vertical Angle: 87.5°

Luminance: 12918 cd/sqm

TEST NUMBER: P1000331

CATALOG NUMBER: SA4XXDP-B350DB2750-4F0-XX-W2A-D_5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	37.5	2.8
10°-20°	107.4	8.0
20°-30°	162.4	12.0
30°-40°	196.5	14.6
40°-50°	207.7	15.4
50°-60°	195.5	14.5
60°-70°	162.2	12.0
70°-80°	113.8	8.4
80°-90°	64.2	4.8
90°-100°	38.2	2.8
100°-110°	28.3	2.1
110°-120°	19.0	1.4
120°-130°	10.7	0.8
130°-140°	4.6	0.3
140°-150°	0.9	0.1
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	307.3	22.8
0°-40°	503.8	37.3
0°-60°	907.0	67.2
0°-90°	1247.3	92.5
90°-120°	85.5	6.3
90°-150°	101.7	7.5
90°-180°	102.0	7.6
0°-180°	1349.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	396	396	396	396	396	
5°	396	395	392	395	395	38
15°	380	380	379	383	382	107
25°	347	350	351	356	357	160
35°	304	309	314	320	321	190
45°	253	262	270	278	280	196
55°	198	208	221	230	233	177
65°	137	152	167	178	181	136
75°	76	93	111	124	128	81
85°	24	42	62	75	80	24
90°	7	25	44	57	60	5
95°	6	20	38	50	54	5
105°	4	13	29	40	44	5
115°	3	7	21	31	34	3
125°	2	1	12	21	24	2
135°	1	1	4	11	14	1
145°	0	0	0	3	4	0
155°	0	0	0	0	0	0
165°	0	0	0	0	0	0
175°	0	0	0	0	0	0
180°	0	0	0	0	0	0

TEST NUMBER: P1000331

CATALOG NUMBER: SA4XXDP-B350DB2750-4F0-XX-W2A-D_5000K

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	395.7	395.7	395.7	395.7	395.7
2.5°	397.4	396.1	392.6	395.7	395.2
5°	396.1	394.8	391.7	395.2	394.8
7.5°	393.5	392.6	389.9	393.9	393.5
10°	389.9	389.5	387.3	391.2	390.8
12.5°	385.0	385.0	383.7	387.3	387.3
15°	379.7	380.2	378.8	382.8	382.4
17.5°	372.6	374.0	373.5	377.5	377.1
20°	365.1	366.4	366.9	371.3	371.3
22.5°	356.7	358.5	359.3	363.8	364.7
25°	347.4	350.0	351.4	356.2	356.7
27.5°	337.2	341.2	342.9	347.4	347.8
30°	327.0	330.5	333.6	338.5	339.4
32.5°	315.9	320.3	323.9	329.7	330.5
35°	304.0	309.3	313.7	319.9	321.2
37.5°	292.0	298.2	303.5	309.7	311.0
40°	280.5	286.2	292.4	299.1	300.9
42.5°	267.2	273.8	281.4	288.9	290.2
45°	253.4	261.9	270.3	277.8	280.0
47.5°	240.6	249.0	258.8	266.3	268.9
50°	226.4	236.2	245.9	254.8	257.4
52.5°	212.2	222.0	233.5	242.4	245.0
55°	198.5	207.8	221.1	230.0	232.6
57.5°	183.0	194.5	207.4	218.0	220.2
60°	167.9	179.4	194.1	204.3	207.8
62.5°	153.3	166.2	180.8	191.0	194.5
65°	137.4	151.5	166.6	177.7	181.2
67.5°	122.3	137.4	153.3	164.4	167.9
70°	106.8	121.8	138.7	150.6	153.7
72.5°	91.7	107.2	125.4	136.9	140.5
75°	76.2	92.6	111.2	123.6	127.6
77.5°	61.6	78.9	98.4	110.8	115.2
80°	48.3	66.0	85.5	98.8	102.4
82.5°	35.0	53.6	73.1	86.8	90.8
85°	23.5	42.1	62.0	75.3	79.8
87.5°	14.6	32.8	52.3	65.1	69.1
90°	7.1	24.8	43.9	56.7	60.3
92.5°	6.6	22.2	41.2	53.6	57.2
95°	5.8	20.4	38.5	50.5	54.5
97.5°	5.3	18.2	36.3	47.9	51.8
100°	4.9	16.4	33.7	45.6	48.7
102.5°	4.9	14.6	31.5	43.0	46.5
105°	4.0	12.8	29.2	40.3	43.9
107.5°	4.0	11.5	27.0	38.1	41.2
110°	3.5	9.7	25.3	35.4	39.0



TEST NUMBER: P1000331

CATALOG NUMBER: SA4XXDP-B350DB2750-4F0-XX-W2A-D_5000K

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	3.1	8.4	23.0	32.8	36.3
115°	2.7	6.6	20.8	30.6	33.7
117.5°	2.7	5.3	18.6	27.9	31.5
120°	2.2	3.5	16.4	25.3	28.8
122.5°	2.2	2.2	14.2	23.0	26.1
125°	1.8	1.3	12.4	20.8	23.5
127.5°	1.8	1.3	10.2	18.2	21.3
130°	1.3	0.9	8.0	16.0	18.6
132.5°	1.3	0.9	6.2	13.7	16.4
135°	0.9	0.9	4.0	11.1	13.7
137.5°	0.9	0.4	2.2	8.9	11.1
140°	0.9	0.4	0.9	6.6	8.9
142.5°	0.4	0.4	0.0	4.9	6.6
145°	0.4	0.0	0.0	2.7	4.4
147.5°	0.4	0.0	0.0	0.4	2.2
150°	0.4	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)