

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1008243

Luminaire Tested: S122DIP-B865D330UB2750-4F0-XX-W2A-D_5000K

Issue Date: 5/7/2025

Test Information

Test Method: LM-79-2019
Report Number: P1008243
REPORT IS A COMBINATION OF REPORTS P984796 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S122DIP-B865D330UB2750-4F0-XX-W2A-D_5000K
Description: Define 2 Direct/Indirect Pendant with 5000K BioUP LEDs {m-DER=1.015} {m-EER=1.115}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4607.0 lumens
Efficiency: N/A
Efficacy: 82.1 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.31 / 1.42
Luminous Opening: Rectangular w/ Sides (W: 0.17' x L: 4' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 56.1
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1008243

CATALOG NUMBER: S122DIP-B865D330UB2750-4F0-XX-W2A-D_5000K

Luminous Intensity Polar Plot



TEST NUMBER: P1008243

CATALOG NUMBER: S122DIP-B865D330UB2750-4F0-XX-W2A-D_5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	111	111	111	111	104	104	104	104	91	91	91		80	80	80		69
1	99	94	89	85	93	88	84	80	77	74	71		67	65	63		58
2	89	81	74	68	83	76	70	64	67	62	57		58	54	51		50
3	81	70	62	56	76	66	59	53	58	52	47		51	46	42		44
4	74	62	53	47	69	58	50	44	51	45	40		45	40	36		39
5	68	55	46	40	63	52	44	38	46	39	34		40	35	31		35
6	62	49	41	34	58	46	38	33	41	35	30		36	31	27		31
7	58	44	36	30	54	42	34	29	37	31	26		33	27	23		29
8	54	40	32	26	50	38	31	25	34	28	23		30	25	21		26
9	50	37	29	23	47	35	28	23	31	25	21		28	22	19		24
10	47	34	26	21	44	32	25	20	29	23	19		25	20	17		22

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	13852	13852	13852
5°	13914	13261	13185
10°	13822	12801	12614
15°	13625	12327	12029
20°	13380	11827	11473
25°	13136	11349	10969
30°	12796	10864	10469
35°	12453	10396	10102
40°	12089	9992	9738
45°	11743	9625	9421
50°	11373	9287	9106
55°	10984	8927	8787
60°	10505	8554	8452
65°	10007	8122	8066
70°	9445	7660	7651
75°	8727	7199	7258
80°	7593	6717	6851
85°	6455	6266	6502

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 11743 cd/sqm

TEST NUMBER: P1008243

CATALOG NUMBER: S122DIP-B865D330UB2750-4F0-XX-W2A-D_5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	83.0	1.8
10°-20°	237.9	5.2
20°-30°	360.5	7.8
30°-40°	439.0	9.5
40°-50°	472.3	10.3
50°-60°	458.7	10.0
60°-70°	400.6	8.7
70°-80°	308.3	6.7
80°-90°	207.3	4.5
90°-100°	156.7	3.4
100°-110°	157.2	3.4
110°-120°	209.6	4.5
120°-130°	272.0	5.9
130°-140°	264.3	5.7
140°-150°	233.5	5.1
150°-160°	185.5	4.0
160°-170°	119.5	2.6
170°-180°	41.1	0.9
0°-30°	681.4	14.8
0°-40°	1120.4	24.3
0°-60°	2051.4	44.5
0°-90°	2967.5	64.4
90°-120°	523.5	11.4
90°-150°	1293.3	28.1
90°-180°	1639.0	35.6
0°-180°	4607.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	875	875	875	875	875	
5°	878	874	866	874	872	83
15°	837	840	840	851	850	236
25°	761	770	781	796	800	350
35°	656	677	701	729	738	410
45°	538	572	616	656	668	415
55°	412	458	524	569	586	369
65°	282	344	418	470	487	280
75°	156	227	308	363	379	165
85°	46	124	206	259	276	48
90°	13	90	174	226	242	10
95°	30	80	158	208	223	32
105°	101	148	128	176	191	109
115°	185	204	269	162	154	182
125°	257	261	307	344	356	230
135°	316	321	336	366	376	244
145°	365	365	370	380	385	229
155°	402	399	403	405	402	185
165°	424	422	423	425	423	120
175°	433	431	432	434	431	41
180°	432	432	432	432	432	

TEST NUMBER: P1008243

CATALOG NUMBER: S122DIP-B865D330UB2750-4F0-XX-W2A-D_5000K

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	875.1	875.1	875.1	875.1	875.1
2.5°	881.4	877.6	868.7	875.1	872.5
5°	877.6	873.8	866.2	873.8	872.5
7.5°	871.3	868.7	862.4	871.3	870.0
10°	863.7	861.1	857.3	867.5	866.2
12.5°	851.0	852.3	849.7	859.9	858.6
15°	837.0	839.6	839.6	851.0	849.7
17.5°	819.3	824.4	828.2	839.6	839.6
20°	801.5	807.9	812.9	826.9	826.9
22.5°	782.5	790.1	797.7	811.7	814.2
25°	760.9	769.8	781.2	796.5	800.3
27.5°	735.6	749.5	762.2	781.2	783.8
30°	710.2	726.7	743.2	763.5	767.3
32.5°	682.3	701.3	721.6	745.7	753.3
35°	655.7	677.2	701.3	729.2	738.1
37.5°	626.5	650.6	681.0	711.5	720.4
40°	597.3	625.2	659.5	692.5	703.9
42.5°	569.4	597.3	637.9	674.7	686.1
45°	537.7	572.0	616.4	655.7	668.4
47.5°	507.3	544.1	594.8	635.4	649.3
50°	475.6	514.9	572.0	615.1	629.0
52.5°	445.1	487.0	547.9	592.3	607.5
55°	412.2	457.8	523.8	569.4	585.9
57.5°	380.5	431.2	497.1	546.6	563.1
60°	346.2	400.8	473.1	521.2	539.0
62.5°	315.8	372.9	445.1	497.1	513.6
65°	281.5	343.7	418.5	470.5	487.0
67.5°	251.1	315.8	391.9	443.9	461.6
70°	218.1	284.1	362.7	417.2	432.5
72.5°	187.7	256.2	336.1	389.3	408.4
75°	156.0	227.0	308.2	362.7	379.2
77.5°	125.6	199.1	281.5	336.1	353.8
80°	95.1	172.5	254.9	308.2	325.9
82.5°	69.8	145.8	229.6	282.8	299.3
85°	45.7	124.3	205.5	258.7	276.5
87.5°	27.9	104.0	185.2	237.2	253.6
90°	13.0	90.0	173.7	225.9	241.8
92.5°	19.2	85.2	163.5	213.6	229.1
95°	30.4	79.8	158.0	207.8	222.7
97.5°	45.5	74.3	153.0	200.8	216.3
100°	64.3	68.3	144.6	194.0	208.7
102.5°	83.6	124.9	136.4	185.5	200.4
105°	101.4	147.6	128.2	176.0	191.2
107.5°	123.6	161.9	119.9	166.4	181.7
110°	143.7	175.5	147.3	156.7	171.8

TEST NUMBER: P1008243

CATALOG NUMBER: S122DIP-B865D330UB2750-4F0-XX-W2A-D_5000K

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	163.7	189.6	242.6	148.4	163.2
115°	184.9	204.2	269.1	162.3	153.7
117.5°	202.1	218.6	277.1	270.4	201.1
120°	222.7	232.5	288.9	328.1	299.9
122.5°	240.3	246.6	299.7	335.8	347.6
125°	256.8	260.9	307.4	343.9	356.2
127.5°	273.1	276.2	315.1	350.0	361.7
130°	288.4	292.2	322.2	356.1	366.0
132.5°	304.0	306.9	329.3	361.3	371.1
135°	316.0	321.0	336.5	366.2	375.7
137.5°	329.7	333.5	342.9	370.1	378.1
140°	343.2	344.4	350.3	373.4	379.5
142.5°	354.4	355.3	359.4	377.1	381.9
145°	365.0	364.7	370.0	379.8	384.6
147.5°	375.3	374.4	379.7	382.6	385.1
150°	385.3	383.2	388.2	390.0	388.5
152.5°	393.8	391.3	396.0	397.9	395.7
155°	401.9	399.1	402.9	404.7	402.2
157.5°	408.5	406.0	408.8	411.0	408.5
160°	414.1	412.2	414.1	416.0	413.8
162.5°	419.1	417.2	418.8	421.0	418.2
165°	423.5	421.6	422.6	424.8	422.6
167.5°	426.9	425.1	426.0	428.2	425.4
170°	429.8	427.9	428.5	430.7	427.9
172.5°	431.6	429.8	430.4	432.6	429.8
175°	433.2	431.0	431.6	433.8	430.7
177.5°	433.8	431.6	431.9	434.1	431.3
180°	432.3	432.3	432.3	432.3	432.3

(END OF REPORT)