

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1007535

Luminaire Tested: S123IP-B365UB2750-4F0-XX-W2A-1_4000K

Issue Date: 5/5/2025

Test Information

Test Method: LM-79-2019
Report Number: P1007535
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-9)
Test Lab: INNOVATION CENTER
Issue Date: 5/5/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S123IP-B365UB2750-4F0-XX-W2A-1_4000K
Description: Define 3 Indirect Pendant with 4000K BioUP LEDs {m-DER=0.865} {m-EER=0.951}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1248.0 lumens
Efficiency: N/A
Efficacy: 134.2 lumens/watt
Spacing Criteria (0/90/45): - / - / -
Luminous Opening: Rectangular (W 0.25' x L: 4' x H: 0')
CIE Type: Indirect

Input Watts (W): 9.3
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1007535

CATALOG NUMBER: S123IP-B365UB2750-4F0-XX-W2A-1_4000K

Luminous Intensity Polar Plot



TEST NUMBER: P1007535

CATALOG NUMBER: S123IP-B365UB2750-4F0-XX-W2A-1_4000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	95	95	95	95	81	81	81	81	56	56	56	32	32	32	10	10	10
1	87	83	79	76	74	71	68	65	48	47	45	28	27	26	9	9	8
2	79	72	66	62	67	62	57	53	42	40	37	24	23	22	8	7	7
3	72	63	56	51	61	54	49	44	37	34	31	21	20	18	7	6	6
4	65	56	48	43	56	48	42	37	33	29	26	19	17	16	6	6	5
5	60	49	42	36	51	42	36	32	29	25	22	17	15	13	5	5	4
6	55	44	36	31	47	38	32	27	26	22	19	15	13	11	5	4	4
7	50	39	32	27	43	34	28	23	23	19	17	14	11	10	4	4	3
8	47	35	28	23	40	30	24	20	21	17	14	12	10	9	4	3	3
9	43	32	25	20	37	27	22	18	19	15	13	11	9	8	4	3	3
10	40	29	22	18	34	25	19	16	17	14	11	10	8	7	3	3	2

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	0	0	0
5°	0	0	0
10°	0	0	0
15°	0	0	0
20°	0	0	0
25°	0	0	0
30°	0	0	0
35°	0	0	0
40°	0	0	0
45°	0	0	0
50°	0	0	0
55°	0	0	0
60°	0	0	0
65°	0	0	0
70°	0	0	0
75°	0	0	0
80°	0	0	0
85°	0	0	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 0°
Luminance: 0 cd/sqm

TEST NUMBER: P1007535

CATALOG NUMBER: S123IP-B365UB2750-4F0-XX-W2A-1_4000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	0.0	0.0
10°-20°	0.0	0.0
20°-30°	0.0	0.0
30°-40°	0.0	0.0
40°-50°	0.0	0.0
50°-60°	0.0	0.0
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	1.0	0.1
90°-100°	29.0	2.3
100°-110°	87.7	7.0
110°-120°	149.3	12.0
120°-130°	196.4	15.7
130°-140°	220.7	17.7
140°-150°	217.0	17.4
150°-160°	182.7	14.6
160°-170°	121.6	9.7
170°-180°	42.6	3.4
0°-30°	0.0	0.0
0°-40°	0.0	0.0
0°-60°	0.0	0.0
0°-90°	1.0	0.1
90°-120°	265.9	21.3
90°-150°	900.1	72.1
90°-180°	1247.0	99.9
0°-180°	1248.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	0	0	0	0	0	
5°	0	0	0	0	0	0
15°	0	0	0	0	0	0
25°	0	0	0	0	0	0
35°	0	0	0	0	0	0
45°	0	0	0	0	0	0
55°	0	0	0	0	0	0
65°	0	0	0	0	0	0
75°	0	0	0	0	0	0
85°	0	0	0	0	0	0
90°	0	4	8	10	11	2
95°	21	23	26	28	28	23
105°	80	80	83	83	84	85
115°	150	151	151	151	151	149
125°	220	221	220	219	217	196
135°	285	287	287	286	285	220
145°	346	347	348	348	346	216
155°	396	396	397	398	396	182
165°	432	431	431	433	430	122
175°	449	448	448	450	447	43
180°	450	450	450	450	450	

TEST NUMBER: P1007535

CATALOG NUMBER: S123IP-B365UB2750-4F0-XX-W2A-1_4000K

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	0.0	0.0	0.0	0.0	0.0
2.5°	0.0	0.0	0.0	0.0	0.0
5°	0.0	0.0	0.0	0.0	0.0
7.5°	0.0	0.0	0.0	0.0	0.0
10°	0.0	0.0	0.0	0.0	0.0
12.5°	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0
90°	0.4	3.9	8.5	9.9	10.6
92.5°	10.6	12.7	14.8	15.9	15.2
95°	20.9	23.3	26.2	27.6	27.6
97.5°	34.3	36.1	38.2	40.0	39.6
100°	48.1	50.2	52.0	53.0	53.7
102.5°	64.0	65.1	67.5	68.6	68.2
105°	79.5	80.3	83.4	83.4	84.1
107.5°	97.9	98.3	99.7	100.8	100.4
110°	114.9	115.6	116.3	117.7	117.0

TEST NUMBER: P1007535

CATALOG NUMBER: S123IP-B365UB2750-4F0-XX-W2A-1_4000K

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	132.6	132.9	132.9	134.7	134.7
115°	150.3	151.3	150.6	151.0	150.6
117.5°	168.3	168.6	167.9	167.9	166.9
120°	184.9	187.0	185.3	184.9	184.2
122.5°	202.2	203.6	202.9	201.9	200.8
125°	219.9	221.0	220.3	218.8	217.4
127.5°	236.2	238.3	237.6	235.5	234.0
130°	252.4	255.3	254.2	252.8	250.3
132.5°	268.7	271.5	270.8	269.0	267.3
135°	285.3	287.4	287.1	285.7	285.0
137.5°	300.5	302.3	303.3	301.6	300.5
140°	316.4	318.2	318.5	318.2	315.7
142.5°	330.9	332.7	333.4	333.0	331.3
145°	346.1	346.8	347.9	347.5	346.1
147.5°	359.2	360.6	361.7	361.7	359.6
150°	373.0	373.7	374.4	374.4	372.3
152.5°	384.3	385.4	385.7	386.4	384.7
155°	396.3	396.3	396.7	398.1	395.6
157.5°	406.6	406.2	406.6	408.0	405.9
160°	416.1	415.4	415.4	417.2	415.8
162.5°	424.6	423.5	423.9	425.7	423.2
165°	431.7	430.6	430.6	432.7	430.3
167.5°	437.7	436.3	436.6	438.8	436.6
170°	442.6	441.2	441.2	443.7	441.2
172.5°	446.5	445.1	445.1	447.2	444.8
175°	449.0	447.6	447.6	449.7	447.2
177.5°	450.4	449.0	449.0	451.1	448.7
180°	450.1	450.1	450.1	450.1	450.1

(END OF REPORT)