

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1025034

Luminaire Tested: S124DIP-B1195D1035UB27-4F0-XX-W2A-D4

Issue Date: 5/7/2025

Test Information

Test Method: LM-79-2019
Report Number: P1025034
REPORT IS A COMBINATION OF REPORTS P995424 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S124DIP-B1195D1035UB27-4F0-XX-W2A-D4
Description: Define 4 Direct/Indirect Pendant with 2700K BioUP LEDs {m-DER=0.473} {m-EER=0.52}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 8472.3 lumens
Efficiency: N/A
Efficacy: 94.3 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.28 / 1.39
Luminous Opening: Rectangular w/ Sides (W: 0.33' x L: 4' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 89.8
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1025034

CATALOG NUMBER: S124DIP-B1195D1035UB27-4F0-XX-W2A-D4

Luminous Intensity Polar Plot



TEST NUMBER: P1025034

CATALOG NUMBER: S124DIP-B1195D1035UB27-4F0-XX-W2A-D4

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	108	108	108	108	100	100	100	100	85	85	85		71	71	71		59
1	97	93	88	84	90	86	82	79	73	70	68		61	59	57		50
2	88	80	74	68	81	74	68	64	63	59	55		53	50	47		43
3	80	70	62	56	74	65	58	53	55	50	46		46	42	39		38
4	73	62	53	47	67	57	50	44	49	43	39		41	37	33		34
5	67	55	46	40	62	51	43	38	44	38	33		37	32	29		30
6	62	49	41	35	57	46	38	33	39	33	29		33	28	25		27
7	57	44	36	30	52	41	34	29	35	30	25		30	25	22		25
8	53	40	32	27	49	37	30	25	32	26	22		27	23	19		23
9	49	37	29	24	45	34	27	22	30	24	20		25	21	17		21
10	46	34	26	21	42	31	25	20	27	22	18		23	19	16		20

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	11555	11555	11555
5°	11586	11254	11274
10°	11511	11032	11000
15°	11403	10783	10692
20°	11244	10513	10393
25°	11064	10216	10070
30°	10869	9922	9740
35°	10649	9621	9447
40°	10472	9331	9144
45°	10211	9060	8875
50°	9988	8752	8592
55°	9758	8456	8266
60°	9401	8086	7959
65°	9008	7688	7590
70°	8531	7233	7163
75°	7864	6726	6757
80°	7115	6210	6331
85°	6120	5691	5986

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 10211 cd/sqm

TEST NUMBER: P1025034

CATALOG NUMBER: S124DIP-B1195D1035UB27-4F0-XX-W2A-D4

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	134.3	1.6
10°-20°	384.7	4.5
20°-30°	581.6	6.9
30°-40°	703.7	8.3
40°-50°	743.9	8.8
50°-60°	700.1	8.3
60°-70°	581.0	6.9
70°-80°	407.7	4.8
80°-90°	231.7	2.7
90°-100°	507.3	6.0
100°-110°	854.7	10.1
110°-120°	739.5	8.7
120°-130°	602.4	7.1
130°-140°	487.3	5.8
140°-150°	362.8	4.3
150°-160°	252.7	3.0
160°-170°	148.6	1.8
170°-180°	48.3	0.6
0°-30°	1100.6	13.0
0°-40°	1804.2	21.3
0°-60°	3248.2	38.3
0°-90°	4468.6	52.7
90°-120°	2101.5	24.8
90°-150°	3554.0	41.9
90°-180°	4004.0	47.3
0°-180°	8472.3	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1417	1417	1417	1417	1417	
5°	1418	1414	1403	1415	1414	135
15°	1360	1361	1357	1371	1369	383
25°	1244	1254	1258	1276	1277	573
35°	1088	1108	1123	1146	1150	682
45°	908	938	968	995	1003	701
55°	711	744	792	824	833	633
65°	492	543	597	636	649	488
75°	273	332	398	443	457	290
85°	84	151	222	270	286	88
90°	26	97	175	223	236	20
95°	53	175	936	576	434	52
105°	129	212	747	1528	1536	138
115°	211	277	648	1211	1444	210
125°	288	339	615	1012	1140	257
135°	337	401	580	872	994	261
145°	387	441	562	711	787	243
155°	438	473	547	619	646	202
165°	477	492	524	555	563	135
175°	498	499	503	510	508	47
180°	499	499	499	499	499	

TEST NUMBER: P1025034

CATALOG NUMBER: S124DIP-B1195D1035UB27-4F0-XX-W2A-D4

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1417.0	1417.0	1417.0	1417.0	1417.0
2.5°	1423.3	1418.5	1405.9	1417.0	1415.4
5°	1418.5	1413.8	1402.7	1415.4	1413.8
7.5°	1409.0	1405.9	1396.3	1410.6	1409.0
10°	1396.3	1394.7	1386.8	1401.1	1399.5
12.5°	1378.9	1378.9	1374.1	1386.8	1386.8
15°	1359.8	1361.4	1356.7	1370.9	1369.4
17.5°	1334.5	1339.2	1337.6	1351.9	1350.3
20°	1307.5	1312.2	1313.8	1329.7	1329.7
22.5°	1277.3	1283.7	1286.8	1302.7	1305.9
25°	1244.0	1253.5	1258.3	1275.7	1277.3
27.5°	1207.5	1221.8	1228.1	1244.0	1245.6
30°	1171.0	1183.7	1194.8	1212.3	1215.4
32.5°	1131.3	1147.2	1159.9	1180.5	1183.7
35°	1088.5	1107.5	1123.4	1145.6	1150.4
37.5°	1045.7	1067.9	1086.9	1109.1	1113.9
40°	1004.4	1025.0	1047.2	1071.1	1077.4
42.5°	956.8	980.6	1007.6	1034.6	1039.3
45°	907.6	937.8	967.9	994.9	1002.8
47.5°	861.6	891.7	926.7	953.6	963.2
50°	810.8	845.7	880.6	912.4	921.9
52.5°	760.0	795.0	836.2	867.9	877.5
55°	710.9	744.2	791.8	823.5	833.0
57.5°	655.3	696.6	742.6	780.7	788.6
60°	601.4	642.6	695.0	731.5	744.2
62.5°	549.0	595.0	647.4	683.9	696.6
65°	491.9	542.7	596.6	636.3	649.0
67.5°	437.9	491.9	549.0	588.7	601.4
70°	382.4	436.4	496.7	539.5	550.6
72.5°	328.5	384.0	449.0	490.3	503.0
75°	272.9	331.6	398.3	442.7	457.0
77.5°	220.6	282.4	352.3	396.7	412.6
80°	173.0	236.4	306.2	353.8	366.5
82.5°	125.4	192.0	261.8	311.0	325.3
85°	84.1	150.7	222.1	269.7	285.6
87.5°	52.4	117.4	187.2	233.3	247.5
90°	26.4	96.7	174.7	222.7	236.4
92.5°	37.5	154.8	531.7	318.8	293.9
95°	52.9	174.9	936.5	576.2	434.3
97.5°	72.9	177.8	984.4	978.7	759.7
100°	92.0	186.0	908.3	1280.2	1072.9
102.5°	111.6	197.4	817.1	1464.8	1347.2
105°	128.9	212.1	747.4	1528.3	1535.6
107.5°	151.5	228.9	699.3	1498.4	1620.1
110°	172.4	244.0	674.3	1410.4	1614.1

TEST NUMBER: P1025034

CATALOG NUMBER: S124DIP-B1195D1035UB27-4F0-XX-W2A-D4

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	192.4	260.8	657.6	1304.8	1546.8
115°	211.3	277.0	647.7	1210.7	1444.2
117.5°	232.9	293.3	638.8	1133.6	1345.2
120°	252.8	307.6	630.9	1078.4	1261.1
122.5°	272.4	322.9	622.0	1040.7	1192.9
125°	287.5	338.9	614.6	1011.8	1140.3
127.5°	303.2	356.5	604.7	982.2	1104.9
130°	314.4	372.1	595.9	950.2	1071.8
132.5°	327.1	386.8	588.5	913.9	1037.5
135°	337.3	401.0	579.6	871.5	993.7
137.5°	349.0	411.6	573.2	828.2	944.0
140°	361.8	422.8	567.5	786.0	891.9
142.5°	373.9	433.2	564.3	747.8	837.0
145°	386.6	440.9	562.4	711.0	786.9
147.5°	401.3	449.7	559.4	679.1	739.8
150°	415.0	458.0	556.5	655.4	699.5
152.5°	426.2	465.8	551.6	636.8	670.1
155°	437.9	472.8	546.7	619.2	645.6
157.5°	449.7	479.1	541.8	602.5	623.1
160°	460.5	484.5	535.9	585.9	602.5
162.5°	470.3	488.9	530.0	569.7	582.9
165°	477.1	491.8	524.2	555.0	563.3
167.5°	485.0	494.2	518.3	542.3	547.7
170°	489.9	496.2	512.4	529.6	533.0
172.5°	494.8	497.7	506.5	518.3	518.3
175°	497.7	498.7	502.6	509.5	507.5
177.5°	499.7	498.7	499.7	503.1	499.7
180°	498.7	498.7	498.7	498.7	498.7

(END OF REPORT)