

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1025051

Luminaire Tested: S124DIP-B1195D1035UB35-4F0-XX-W2A-D1

Issue Date: 5/7/2025

Test Information

Test Method: LM-79-2019
Report Number: P1025051
REPORT IS A COMBINATION OF REPORTS P995456 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S124DIP-B1195D1035UB35-4F0-XX-W2A-D1
Description: Define 4 Direct/Indirect Pendant with 3500K BioUP LEDs {m-DER=0.721} {m-EER=0.792}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 8456.0 lumens
Efficiency: N/A
Efficacy: 94.2 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.28 / 1.39
Luminous Opening: Rectangular w/ Sides (W: 0.33' x L: 4' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 89.8
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1025051

CATALOG NUMBER: S124DIP-B1195D1035UB35-4F0-XX-W2A-D1

Luminous Intensity Polar Plot



TEST NUMBER: P1025051

CATALOG NUMBER: S124DIP-B1195D1035UB35-4F0-XX-W2A-D1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	108	108	108	108	100	100	100	100	85	85	85		72	72	72		59
1	97	93	88	84	90	86	82	79	73	70	68		62	59	58		51
2	88	80	74	68	81	74	69	64	63	59	55		53	50	47		44
3	80	70	62	56	74	65	58	53	56	50	46		47	43	39		39
4	73	62	54	47	67	57	50	44	49	43	39		41	37	33		34
5	67	55	46	40	62	51	44	38	44	38	33		37	32	29		31
6	62	49	41	35	57	46	38	33	39	33	29		33	29	25		28
7	57	44	36	30	53	41	34	29	36	30	25		30	26	22		25
8	53	40	32	27	49	38	30	25	32	27	22		28	23	20		23
9	49	37	29	24	46	34	27	22	30	24	20		25	21	18		21
10	46	34	26	21	43	31	25	20	27	22	18		24	19	16		20

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	11702	11702	11702
5°	11735	11398	11418
10°	11659	11173	11142
15°	11550	10922	10829
20°	11388	10649	10526
25°	11206	10347	10199
30°	11008	10049	9865
35°	10786	9744	9569
40°	10607	9452	9261
45°	10343	9176	8989
50°	10116	8864	8702
55°	9883	8564	8372
60°	9521	8190	8061
65°	9124	7787	7687
70°	8641	7325	7256
75°	7965	6812	6843
80°	7206	6291	6412
85°	6200	5766	6064

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 10343 cd/sqm

TEST NUMBER: P1025051

CATALOG NUMBER: S124DIP-B1195D1035UB35-4F0-XX-W2A-D1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	136.0	1.6
10°-20°	389.6	4.6
20°-30°	589.1	7.0
30°-40°	712.7	8.4
40°-50°	753.4	8.9
50°-60°	709.1	8.4
60°-70°	588.4	7.0
70°-80°	412.9	4.9
80°-90°	235.5	2.8
90°-100°	222.2	2.6
100°-110°	353.1	4.2
110°-120°	494.5	5.8
120°-130°	600.0	7.1
130°-140°	647.2	7.7
140°-150°	622.9	7.4
150°-160°	521.1	6.2
160°-170°	346.7	4.1
170°-180°	121.4	1.4
0°-30°	1114.7	13.2
0°-40°	1827.4	21.6
0°-60°	3289.9	38.9
0°-90°	4526.8	53.5
90°-120°	1069.8	12.7
90°-150°	2939.9	34.8
90°-180°	3929.0	46.5
0°-180°	8456.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1435	1435	1435	1435	1435	
5°	1437	1432	1421	1434	1432	136
15°	1377	1379	1374	1388	1387	388
25°	1260	1270	1274	1292	1294	580
35°	1102	1122	1138	1160	1165	690
45°	919	950	980	1008	1016	710
55°	720	754	802	834	844	642
65°	498	550	604	644	657	494
75°	276	336	403	448	463	294
85°	85	153	225	273	289	89
90°	29	104	181	234	248	22
95°	80	142	215	262	276	81
105°	246	279	342	385	401	262
115°	442	457	506	541	551	437
125°	637	635	674	703	710	568
135°	816	822	833	857	864	632
145°	989	991	992	1001	1004	619
155°	1131	1131	1130	1134	1130	521
165°	1232	1229	1227	1232	1229	347
175°	1281	1276	1275	1282	1275	122
180°	1283	1283	1283	1283	1283	

TEST NUMBER: P1025051

CATALOG NUMBER: S124DIP-B1195D1035UB35-4F0-XX-W2A-D1

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1435.1	1435.1	1435.1	1435.1	1435.1
2.5°	1441.6	1436.8	1423.9	1435.1	1433.5
5°	1436.8	1431.9	1420.7	1433.5	1431.9
7.5°	1427.1	1423.9	1414.3	1428.7	1427.1
10°	1414.3	1412.6	1404.6	1419.1	1417.5
12.5°	1396.6	1396.6	1391.8	1404.6	1404.6
15°	1377.3	1378.9	1374.1	1388.5	1386.9
17.5°	1351.6	1356.4	1354.8	1369.3	1367.6
20°	1324.3	1329.1	1330.7	1346.8	1346.8
22.5°	1293.7	1300.1	1303.4	1319.4	1322.6
25°	1260.0	1269.6	1274.4	1292.1	1293.7
27.5°	1223.0	1237.5	1243.9	1260.0	1261.6
30°	1186.0	1198.9	1210.2	1227.8	1231.0
32.5°	1145.9	1161.9	1174.8	1195.7	1198.9
35°	1102.5	1121.8	1137.8	1160.3	1165.2
37.5°	1059.1	1081.6	1100.9	1123.4	1128.2
40°	1017.3	1038.2	1060.7	1084.8	1091.2
42.5°	969.1	993.2	1020.5	1047.8	1052.7
45°	919.3	949.8	980.3	1007.7	1015.7
47.5°	872.7	903.2	938.5	965.9	975.5
50°	821.2	856.6	891.9	924.1	933.7
52.5°	769.8	805.2	846.9	879.1	888.7
55°	720.0	753.7	801.9	834.1	843.7
57.5°	663.7	705.5	752.1	790.7	798.7
60°	609.1	650.9	703.9	740.9	753.7
62.5°	556.1	602.7	655.7	692.7	705.5
65°	498.2	549.6	604.3	644.4	657.3
67.5°	443.6	498.2	556.1	596.2	609.1
70°	387.3	442.0	503.0	546.4	557.7
72.5°	332.7	388.9	454.8	496.6	509.5
75°	276.4	335.9	403.4	448.4	462.8
77.5°	223.4	286.1	356.8	401.8	417.8
80°	175.2	239.5	310.2	358.4	371.2
82.5°	127.0	194.5	265.2	315.0	329.5
85°	85.2	152.7	225.0	273.2	289.3
87.5°	53.0	118.9	189.6	236.2	250.7
90°	28.7	103.9	180.9	233.5	248.4
92.5°	49.9	119.1	193.2	241.1	254.9
95°	80.4	142.4	215.2	261.6	276.1
97.5°	114.6	169.1	242.9	288.7	303.1
100°	156.6	202.4	273.9	319.3	330.6
102.5°	202.3	238.6	307.6	352.4	366.2
105°	245.7	278.8	342.3	385.4	401.2
107.5°	294.4	322.6	379.8	424.0	434.3
110°	342.4	366.9	422.1	457.1	472.9

TEST NUMBER: P1025051

CATALOG NUMBER: S124DIP-B1195D1035UB35-4F0-XX-W2A-D1

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	392.3	411.6	462.7	498.0	510.9
115°	442.3	456.8	506.2	540.6	550.8
117.5°	490.9	500.6	547.8	578.5	588.5
120°	537.9	546.8	590.4	617.6	632.4
122.5°	588.5	589.5	631.9	661.2	667.4
125°	636.6	635.0	674.2	702.7	710.4
127.5°	681.2	682.6	712.8	739.7	749.9
130°	727.3	728.6	754.3	781.3	787.0
132.5°	775.9	776.3	794.6	819.9	828.6
135°	816.0	821.9	833.2	856.9	863.6
137.5°	862.6	864.0	872.4	893.5	902.6
140°	909.2	909.6	911.2	931.1	938.1
142.5°	950.3	952.3	949.7	967.4	973.8
145°	989.0	991.4	992.4	1001.0	1004.5
147.5°	1028.7	1032.1	1031.1	1031.7	1037.1
150°	1064.4	1066.8	1066.8	1066.8	1065.8
152.5°	1096.6	1098.6	1099.6	1102.5	1099.6
155°	1131.3	1131.3	1130.3	1134.3	1130.3
157.5°	1161.1	1159.1	1159.1	1162.1	1159.1
160°	1186.9	1185.9	1184.9	1187.9	1182.9
162.5°	1210.7	1207.7	1206.7	1212.7	1207.7
165°	1231.5	1228.6	1226.6	1232.5	1228.6
167.5°	1248.4	1244.4	1244.4	1250.4	1244.4
170°	1262.3	1257.3	1258.3	1264.3	1257.3
172.5°	1272.2	1268.3	1268.3	1275.2	1268.3
175°	1281.2	1276.2	1275.2	1282.2	1275.2
177.5°	1285.1	1280.2	1280.2	1287.1	1279.2
180°	1283.1	1283.1	1283.1	1283.1	1283.1

(END OF REPORT)