

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1025133

Luminaire Tested: S124DIP-B1195D365UB30-4F0-XX-W2A-D4

Issue Date: 5/7/2025

Test Information

Test Method: LM-79-2019
Report Number: P1025133
REPORT IS A COMBINATION OF REPORTS P995568 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S124DIP-B1195D365UB30-4F0-XX-W2A-D4
Description: Define 4 Direct/Indirect Pendant with 3000K BioUP LEDs {m-DER=0.589} {m-EER=0.647}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 6193.6 lumens
Efficiency: N/A
Efficacy: 87.7 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.28 / 1.39
Luminous Opening: Rectangular w/ Sides (W: 0.33' x L: 4' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 70.6
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1025133

CATALOG NUMBER: S124DIP-B1195D365UB30-4F0-XX-W2A-D4

Luminous Intensity Polar Plot



TEST NUMBER: P1025133

CATALOG NUMBER: S124DIP-B1195D365UB30-4F0-XX-W2A-D4

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	113	113	113	113	107	107	107	107	96	96	96	86	86	86	77	77	77
1	101	96	92	88	96	91	87	84	82	79	76	74	71	69	66	64	62
2	92	83	76	70	87	79	73	67	71	66	62	64	60	56	57	54	51
3	83	73	65	58	79	69	62	56	62	56	51	56	51	47	50	46	43
4	76	64	55	49	72	61	53	47	55	49	43	50	44	40	44	40	37
5	70	57	48	42	66	54	46	40	49	42	37	44	39	34	40	35	32
6	64	51	42	36	61	49	41	35	44	37	32	40	34	30	36	31	28
7	59	46	38	32	56	44	36	31	40	33	28	36	31	26	33	28	24
8	55	42	34	28	52	40	32	27	37	30	25	33	28	24	30	25	22
9	51	38	30	25	49	37	29	24	34	27	23	31	25	21	28	23	20
10	48	35	28	22	46	34	27	22	31	25	20	28	23	19	26	21	18

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	11653	11653	11653
5°	11685	11349	11370
10°	11609	11126	11094
15°	11501	10875	10783
20°	11339	10603	10481
25°	11158	10303	10156
30°	10962	10006	9823
35°	10739	9702	9528
40°	10561	9411	9221
45°	10298	9137	8950
50°	10073	8827	8665
55°	9841	8527	8336
60°	9481	8155	8027
65°	9085	7753	7654
70°	8605	7294	7225
75°	7931	6784	6815
80°	7173	6263	6384
85°	6171	5740	6037

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 10298 cd/sqm

TEST NUMBER: P1025133

CATALOG NUMBER: S124DIP-B1195D365UB30-4F0-XX-W2A-D4

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	135.4	2.2
10°-20°	387.9	6.3
20°-30°	586.6	9.5
30°-40°	709.6	11.5
40°-50°	750.2	12.1
50°-60°	706.0	11.4
60°-70°	585.9	9.5
70°-80°	411.1	6.6
80°-90°	232.5	3.8
90°-100°	272.4	4.4
100°-110°	375.6	6.1
110°-120°	312.3	5.0
120°-130°	243.4	3.9
130°-140°	187.5	3.0
140°-150°	133.8	2.2
150°-160°	91.7	1.5
160°-170°	53.9	0.9
170°-180°	17.5	0.3
0°-30°	1109.9	17.9
0°-40°	1819.6	29.4
0°-60°	3275.8	52.9
0°-90°	4505.3	72.7
90°-120°	960.4	15.5
90°-150°	1525.1	24.6
90°-180°	1688.0	27.3
0°-180°	6193.6	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1429	1429	1429	1429	1429	
5°	1431	1426	1415	1427	1426	136
15°	1371	1373	1368	1383	1381	386
25°	1255	1264	1269	1287	1288	578
35°	1098	1117	1133	1155	1160	687
45°	915	946	976	1003	1011	707
55°	717	750	798	830	840	639
65°	496	547	602	642	654	492
75°	275	334	402	446	461	292
85°	85	152	224	272	288	88
90°	26	92	165	212	225	18
95°	32	111	429	326	284	29
105°	56	107	339	648	659	61
115°	83	116	283	510	602	83
125°	108	126	252	415	468	97
135°	124	148	220	342	392	97
145°	141	160	204	264	296	89
155°	159	172	198	225	234	73
165°	173	178	190	201	204	49
175°	181	181	182	185	184	17
180°	181	181	181	181	181	

TEST NUMBER: P1025133

CATALOG NUMBER: S124DIP-B1195D365UB30-4F0-XX-W2A-D4

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1429.0	1429.0	1429.0	1429.0	1429.0
2.5°	1435.4	1430.6	1417.8	1429.0	1427.4
5°	1430.6	1425.8	1414.6	1427.4	1425.8
7.5°	1421.0	1417.8	1408.2	1422.6	1421.0
10°	1408.2	1406.6	1398.6	1413.0	1411.4
12.5°	1390.6	1390.6	1385.8	1398.6	1398.6
15°	1371.4	1373.0	1368.2	1382.6	1381.0
17.5°	1345.8	1350.6	1349.0	1363.4	1361.8
20°	1318.6	1323.4	1325.0	1341.0	1341.0
22.5°	1288.2	1294.6	1297.8	1313.8	1317.0
25°	1254.6	1264.2	1269.0	1286.6	1288.2
27.5°	1217.8	1232.2	1238.6	1254.6	1256.2
30°	1181.0	1193.8	1205.0	1222.6	1225.8
32.5°	1140.9	1157.0	1169.8	1190.6	1193.8
35°	1097.7	1116.9	1132.9	1155.4	1160.2
37.5°	1054.5	1076.9	1096.1	1118.5	1123.3
40°	1012.9	1033.7	1056.1	1080.1	1086.5
42.5°	964.9	988.9	1016.1	1043.3	1048.1
45°	915.3	945.7	976.1	1003.3	1011.3
47.5°	868.9	899.3	934.5	961.7	971.3
50°	817.7	852.9	888.1	920.1	929.7
52.5°	766.5	801.7	843.3	875.3	884.9
55°	716.9	750.5	798.5	830.5	840.1
57.5°	660.9	702.5	748.9	787.3	795.3
60°	606.5	648.1	700.9	737.7	750.5
62.5°	553.7	600.1	652.9	689.7	702.5
65°	496.1	547.3	601.7	641.7	654.5
67.5°	441.7	496.1	553.7	593.7	606.5
70°	385.7	440.1	500.9	544.1	555.3
72.5°	331.2	387.3	452.9	494.5	507.3
75°	275.2	334.4	401.7	446.5	460.9
77.5°	222.4	284.8	355.2	400.1	416.1
80°	174.4	238.4	308.8	356.8	369.6
82.5°	126.4	193.6	264.0	313.6	328.0
85°	84.8	152.0	224.0	272.0	288.0
87.5°	52.8	118.4	188.8	235.2	249.6
90°	26.0	92.4	164.8	211.9	225.1
92.5°	29.0	107.4	288.2	239.6	238.8
95°	32.5	110.6	429.0	325.8	283.6
97.5°	38.8	106.5	441.3	465.8	395.6
100°	44.6	105.4	407.5	570.2	502.1
102.5°	51.7	105.4	369.3	631.0	596.5
105°	56.0	106.6	338.9	647.9	658.7
107.5°	64.2	109.7	316.3	631.9	683.3
110°	70.8	111.1	303.1	593.8	676.0

TEST NUMBER: P1025133

CATALOG NUMBER: S124DIP-B1195D365UB30-4F0-XX-W2A-D4

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	77.0	114.1	291.9	549.4	645.4
115°	82.9	115.9	283.2	510.1	602.0
117.5°	90.7	118.8	274.9	476.0	561.0
120°	96.9	119.8	266.9	449.8	524.3
122.5°	104.0	122.3	258.5	431.0	493.4
125°	108.5	126.0	251.8	415.4	468.1
127.5°	114.1	132.5	243.1	398.5	450.2
130°	117.2	137.0	234.7	381.8	432.1
132.5°	121.8	142.4	227.9	363.4	414.4
135°	124.5	147.6	219.6	341.9	392.4
137.5°	128.7	150.5	213.2	321.1	368.2
140°	133.4	154.5	208.0	300.6	344.2
142.5°	136.7	158.2	204.8	282.7	319.2
145°	141.4	160.0	204.1	264.2	295.9
147.5°	146.7	163.2	203.1	247.5	273.6
150°	151.7	166.2	202.0	237.9	253.9
152.5°	154.7	169.1	200.2	231.2	243.2
155°	159.0	171.6	198.4	224.8	234.3
157.5°	163.2	173.9	196.6	218.7	226.2
160°	167.1	175.9	194.5	212.6	218.7
162.5°	170.7	177.4	192.4	206.8	211.6
165°	173.2	178.5	190.2	201.4	204.5
167.5°	176.0	179.4	188.1	196.9	198.8
170°	177.8	180.1	186.0	192.2	193.4
172.5°	179.6	180.6	183.8	188.2	188.1
175°	180.6	181.0	182.4	184.9	184.2
177.5°	181.4	181.0	181.4	182.6	181.4
180°	181.0	181.0	181.0	181.0	181.0

(END OF REPORT)