

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1025141

Luminaire Tested: S124DIP-B1195D365UB35-4F0-XX-W2A-D1

Issue Date: 5/7/2025

Test Information

Test Method: LM-79-2019
Report Number: P1025141
REPORT IS A COMBINATION OF REPORTS P995576 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S124DIP-B1195D365UB35-4F0-XX-W2A-D1
Description: Define 4 Direct/Indirect Pendant with 3500K BioUP LEDs {m-DER=0.721} {m-EER=0.792}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 6175.0 lumens
Efficiency: N/A
Efficacy: 87.5 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.28 / 1.39
Luminous Opening: Rectangular w/ Sides (W: 0.33' x L: 4' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 70.6
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1025141

CATALOG NUMBER: S124DIP-B1195D365UB35-4F0-XX-W2A-D1

Luminous Intensity Polar Plot



TEST NUMBER: P1025141

CATALOG NUMBER: S124DIP-B1195D365UB35-4F0-XX-W2A-D1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	113	113	113	113	107	107	107	107	96	96	96	86	86	86	78	78	78
1	102	96	92	88	96	92	87	84	82	79	76	74	71	69	66	64	63
2	92	83	76	70	87	79	73	68	71	66	62	64	60	57	57	54	52
3	83	73	65	58	79	69	62	56	62	56	51	56	51	47	50	46	43
4	76	64	55	49	72	61	53	47	55	49	43	50	44	40	45	40	37
5	70	57	48	42	66	54	46	40	49	43	37	45	39	35	40	35	32
6	64	51	42	36	61	49	41	35	44	38	32	40	34	30	36	32	28
7	60	46	38	32	56	44	36	31	40	33	29	37	31	27	33	28	25
8	55	42	34	28	52	40	32	27	37	30	25	33	28	24	30	26	22
9	52	38	30	25	49	37	29	24	34	27	23	31	25	21	28	23	20
10	48	35	28	22	46	34	27	22	31	25	21	28	23	19	26	21	18

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	11702	11702	11702
5°	11735	11398	11418
10°	11659	11173	11142
15°	11550	10922	10829
20°	11388	10649	10526
25°	11206	10347	10199
30°	11008	10049	9865
35°	10786	9744	9569
40°	10607	9452	9261
45°	10343	9176	8989
50°	10116	8864	8702
55°	9883	8564	8372
60°	9521	8190	8061
65°	9124	7787	7687
70°	8641	7325	7256
75°	7965	6812	6843
80°	7206	6291	6412
85°	6200	5766	6064

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 10343 cd/sqm

TEST NUMBER: P1025141

CATALOG NUMBER: S124DIP-B1195D365UB35-4F0-XX-W2A-D1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	136.0	2.2
10°-20°	389.6	6.3
20°-30°	589.1	9.5
30°-40°	712.7	11.5
40°-50°	753.4	12.2
50°-60°	709.1	11.5
60°-70°	588.4	9.5
70°-80°	412.9	6.7
80°-90°	233.8	3.8
90°-100°	168.7	2.7
100°-110°	192.8	3.1
110°-120°	222.0	3.6
120°-130°	240.7	3.9
130°-140°	243.6	3.9
140°-150°	226.2	3.7
150°-160°	187.5	3.0
160°-170°	124.8	2.0
170°-180°	43.7	0.7
0°-30°	1114.7	18.1
0°-40°	1827.4	29.6
0°-60°	3289.9	53.3
0°-90°	4525.0	73.3
90°-120°	583.4	9.4
90°-150°	1294.0	21.0
90°-180°	1650.0	26.7
0°-180°	6175.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1435	1435	1435	1435	1435	
5°	1437	1432	1421	1434	1432	136
15°	1377	1379	1374	1388	1387	388
25°	1260	1270	1274	1292	1294	580
35°	1102	1122	1138	1160	1165	690
45°	919	950	980	1008	1016	710
55°	720	754	802	834	844	642
65°	498	550	604	644	657	494
75°	276	336	403	448	463	294
85°	85	153	225	273	289	89
90°	27	95	167	216	229	19
95°	42	98	167	211	226	40
105°	98	130	191	232	246	105
115°	165	180	230	266	276	164
125°	233	232	271	301	310	208
135°	296	298	309	334	343	229
145°	357	357	357	366	372	224
155°	407	407	407	408	407	187
165°	443	442	441	444	442	125
175°	461	459	459	461	459	44
180°	462	462	462	462	462	

TEST NUMBER: P1025141

CATALOG NUMBER: S124DIP-B1195D365UB35-4F0-XX-W2A-D1

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1435.1	1435.1	1435.1	1435.1	1435.1
2.5°	1441.6	1436.8	1423.9	1435.1	1433.5
5°	1436.8	1431.9	1420.7	1433.5	1431.9
7.5°	1427.1	1423.9	1414.3	1428.7	1427.1
10°	1414.3	1412.6	1404.6	1419.1	1417.5
12.5°	1396.6	1396.6	1391.8	1404.6	1404.6
15°	1377.3	1378.9	1374.1	1388.5	1386.9
17.5°	1351.6	1356.4	1354.8	1369.3	1367.6
20°	1324.3	1329.1	1330.7	1346.8	1346.8
22.5°	1293.7	1300.1	1303.4	1319.4	1322.6
25°	1260.0	1269.6	1274.4	1292.1	1293.7
27.5°	1223.0	1237.5	1243.9	1260.0	1261.6
30°	1186.0	1198.9	1210.2	1227.8	1231.0
32.5°	1145.9	1161.9	1174.8	1195.7	1198.9
35°	1102.5	1121.8	1137.8	1160.3	1165.2
37.5°	1059.1	1081.6	1100.9	1123.4	1128.2
40°	1017.3	1038.2	1060.7	1084.8	1091.2
42.5°	969.1	993.2	1020.5	1047.8	1052.7
45°	919.3	949.8	980.3	1007.7	1015.7
47.5°	872.7	903.2	938.5	965.9	975.5
50°	821.2	856.6	891.9	924.1	933.7
52.5°	769.8	805.2	846.9	879.1	888.7
55°	720.0	753.7	801.9	834.1	843.7
57.5°	663.7	705.5	752.1	790.7	798.7
60°	609.1	650.9	703.9	740.9	753.7
62.5°	556.1	602.7	655.7	692.7	705.5
65°	498.2	549.6	604.3	644.4	657.3
67.5°	443.6	498.2	556.1	596.2	609.1
70°	387.3	442.0	503.0	546.4	557.7
72.5°	332.7	388.9	454.8	496.6	509.5
75°	276.4	335.9	403.4	448.4	462.8
77.5°	223.4	286.1	356.8	401.8	417.8
80°	175.2	239.5	310.2	358.4	371.2
82.5°	127.0	194.5	265.2	315.0	329.5
85°	85.2	152.7	225.0	273.2	289.3
87.5°	53.0	118.9	189.6	236.2	250.7
90°	26.8	95.0	167.0	215.7	229.3
92.5°	33.4	94.3	165.2	211.3	224.4
95°	42.3	98.5	166.9	211.4	225.9
97.5°	53.6	103.0	171.8	215.0	229.4
100°	67.7	110.9	176.7	220.8	232.1
102.5°	84.1	119.8	183.7	226.6	239.8
105°	97.7	130.2	191.1	232.3	246.2
107.5°	115.2	142.8	199.4	241.0	252.0
110°	131.4	154.7	210.5	246.8	260.7

TEST NUMBER: P1025141

CATALOG NUMBER: S124DIP-B1195D365UB35-4F0-XX-W2A-D1

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	148.3	167.6	220.0	255.3	268.2
115°	165.3	179.8	230.5	265.5	276.4
117.5°	182.8	192.5	240.3	272.9	284.8
120°	198.7	205.0	250.5	280.8	294.5
122.5°	216.9	217.2	260.3	291.4	300.8
125°	233.1	231.5	271.4	301.2	310.2
127.5°	249.2	248.7	280.2	308.3	319.2
130°	264.7	264.2	289.9	318.2	326.4
132.5°	282.2	281.4	300.3	326.9	336.2
135°	295.6	297.8	309.1	334.1	342.6
137.5°	312.4	311.9	319.0	342.0	350.5
140°	329.2	328.3	329.9	350.5	358.1
142.5°	343.0	343.7	341.7	359.4	365.8
145°	356.9	356.7	357.1	366.3	371.7
147.5°	371.2	371.3	371.0	372.2	378.3
150°	384.0	383.8	383.8	383.8	383.5
152.5°	394.6	395.3	395.6	396.7	395.6
155°	407.1	407.1	406.7	408.1	406.7
157.5°	417.8	417.1	417.1	418.1	417.1
160°	427.1	426.7	426.3	427.4	425.6
162.5°	435.6	434.6	434.2	436.3	434.6
165°	443.1	442.0	441.3	443.5	442.0
167.5°	449.2	447.8	447.8	449.9	447.8
170°	454.2	452.4	452.8	454.9	452.4
172.5°	457.8	456.3	456.3	458.8	456.3
175°	461.0	459.2	458.8	461.3	458.8
177.5°	462.4	460.6	460.6	463.1	460.3
180°	461.7	461.7	461.7	461.7	461.7

(END OF REPORT)