

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1025160

Luminaire Tested: S124DIP-B1195D365UB50-4F0-XX-W2A-D4

Issue Date: 5/6/2025

Test Information

Test Method: LM-79-2019
Report Number: P1025160
REPORT IS A COMBINATION OF REPORTS P995595 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/6/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S124DIP-B1195D365UB50-4F0-XX-W2A-D4
Description: Define 4 Direct/Indirect Pendant with 5000K BioUP LEDs {m-DER=1.015} {m-EER=1.115}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 5955.5 lumens
Efficiency: N/A
Efficacy: 84.4 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.28 / 1.39
Luminous Opening: Rectangular w/ Sides (W: 0.33' x L: 4' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 70.6
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1025160

CATALOG NUMBER: S124DIP-B1195D365UB50-4F0-XX-W2A-D4

Luminous Intensity Polar Plot



TEST NUMBER: P1025160

CATALOG NUMBER: S124DIP-B1195D365UB50-4F0-XX-W2A-D4

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	113	113	113	113	107	107	107	107	96	96	96	86	86	86	77	77	77
1	101	96	92	88	96	91	87	84	82	79	76	74	71	69	66	64	62
2	92	83	76	70	87	79	73	67	71	66	62	64	60	56	57	54	51
3	83	73	65	58	79	69	62	56	62	56	51	56	51	47	50	46	43
4	76	64	55	49	72	61	53	47	55	49	43	50	44	40	44	40	37
5	70	57	48	42	66	54	46	40	49	42	37	44	39	34	40	35	32
6	64	51	42	36	61	49	41	35	44	37	32	40	34	30	36	31	28
7	59	46	38	32	56	44	36	31	40	33	28	36	31	26	33	28	24
8	55	42	34	28	52	40	32	27	37	30	25	33	28	24	30	25	22
9	51	38	30	25	49	37	29	24	34	27	23	31	25	21	28	23	20
10	48	35	28	22	46	34	27	22	31	25	20	28	23	19	26	21	18

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	11205	11205	11205
5°	11236	10913	10933
10°	11163	10699	10668
15°	11059	10457	10369
20°	10904	10196	10078
25°	10729	9908	9765
30°	10541	9622	9446
35°	10327	9330	9162
40°	10156	9050	8867
45°	9903	8787	8607
50°	9686	8488	8332
55°	9463	8201	8017
60°	9117	7842	7719
65°	8735	7456	7361
70°	8272	7013	6947
75°	7628	6522	6553
80°	6897	6023	6141
85°	5938	5520	5806

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 9903 cd/sqm

TEST NUMBER: P1025160

CATALOG NUMBER: S124DIP-B1195D365UB50-4F0-XX-W2A-D4

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	130.2	2.2
10°-20°	373.1	6.3
20°-30°	564.1	9.5
30°-40°	682.4	11.5
40°-50°	721.4	12.1
50°-60°	678.9	11.4
60°-70°	563.4	9.5
70°-80°	395.4	6.6
80°-90°	223.6	3.8
90°-100°	261.9	4.4
100°-110°	361.1	6.1
110°-120°	300.2	5.0
120°-130°	234.0	3.9
130°-140°	180.3	3.0
140°-150°	128.6	2.2
150°-160°	88.2	1.5
160°-170°	51.9	0.9
170°-180°	16.9	0.3
0°-30°	1067.3	17.9
0°-40°	1749.7	29.4
0°-60°	3150.1	52.9
0°-90°	4332.4	72.7
90°-120°	923.3	15.5
90°-150°	1466.2	24.6
90°-180°	1623.0	27.3
0°-180°	5955.5	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1374	1374	1374	1374	1374	
5°	1376	1371	1360	1373	1371	131
15°	1319	1320	1316	1330	1328	372
25°	1206	1216	1220	1237	1239	556
35°	1056	1074	1090	1111	1116	661
45°	880	909	939	965	972	680
55°	689	722	768	799	808	614
65°	477	526	579	617	629	473
75°	265	322	386	429	443	281
85°	82	146	215	262	277	85
90°	25	89	158	204	216	18
95°	31	106	412	313	273	28
105°	54	103	326	623	633	58
115°	80	112	272	490	579	80
125°	104	121	242	399	450	93
135°	120	142	211	329	377	93
145°	136	154	196	254	284	85
155°	153	165	191	216	225	71
165°	166	172	183	194	197	47
175°	174	174	175	178	177	16
180°	174	174	174	174	174	

TEST NUMBER: P1025160

CATALOG NUMBER: S124DIP-B1195D365UB50-4F0-XX-W2A-D4

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1374.1	1374.1	1374.1	1374.1	1374.1
2.5°	1380.3	1375.7	1363.4	1374.1	1372.6
5°	1375.7	1371.1	1360.3	1372.6	1371.1
7.5°	1366.4	1363.4	1354.1	1368.0	1366.4
10°	1354.1	1352.6	1344.9	1358.8	1357.2
12.5°	1337.2	1337.2	1332.6	1344.9	1344.9
15°	1318.7	1320.3	1315.7	1329.5	1328.0
17.5°	1294.1	1298.7	1297.2	1311.0	1309.5
20°	1268.0	1272.6	1274.1	1289.5	1289.5
22.5°	1238.7	1244.9	1248.0	1263.3	1266.4
25°	1206.4	1215.6	1220.3	1237.2	1238.7
27.5°	1171.0	1184.9	1191.0	1206.4	1207.9
30°	1135.6	1147.9	1158.7	1175.6	1178.7
32.5°	1097.2	1112.5	1124.9	1144.9	1147.9
35°	1055.6	1074.1	1089.5	1111.0	1115.6
37.5°	1014.1	1035.6	1054.1	1075.6	1080.2
40°	974.1	994.1	1015.6	1038.7	1044.8
42.5°	927.9	951.0	977.1	1003.3	1007.9
45°	880.2	909.4	938.7	964.8	972.5
47.5°	835.6	864.8	898.7	924.8	934.0
50°	786.3	820.2	854.0	884.8	894.0
52.5°	737.1	770.9	810.9	841.7	850.9
55°	689.4	721.7	767.9	798.6	807.9
57.5°	635.5	675.5	720.2	757.1	764.8
60°	583.2	623.2	674.0	709.4	721.7
62.5°	532.4	577.0	627.8	663.2	675.5
65°	477.0	526.3	578.6	617.1	629.4
67.5°	424.7	477.0	532.4	570.9	583.2
70°	370.8	423.2	481.6	523.2	534.0
72.5°	318.5	372.4	435.5	475.5	487.8
75°	264.7	321.6	386.2	429.3	443.2
77.5°	213.9	273.9	341.6	384.7	400.1
80°	167.7	229.3	297.0	343.1	355.5
82.5°	121.6	186.2	253.9	301.6	315.5
85°	81.6	146.2	215.4	261.6	277.0
87.5°	50.8	113.9	181.6	226.2	240.1
90°	24.9	88.9	158.5	203.8	216.5
92.5°	27.9	103.2	277.1	230.4	229.6
95°	31.3	106.4	412.5	313.4	272.7
97.5°	37.3	102.4	424.3	447.8	380.3
100°	42.9	101.4	391.8	548.2	482.8
102.5°	49.7	101.4	355.1	606.7	573.5
105°	53.8	102.6	325.9	622.9	633.3
107.5°	61.7	105.4	304.1	607.4	656.9
110°	68.0	106.9	291.4	570.9	649.9



TEST NUMBER: P1025160

CATALOG NUMBER: S124DIP-B1195D365UB50-4F0-XX-W2A-D4

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	74.0	109.7	280.7	528.2	620.5
115°	79.6	111.5	272.3	490.4	578.7
117.5°	87.1	114.2	264.2	457.6	539.4
120°	93.2	115.2	256.5	432.4	504.1
122.5°	100.0	117.6	248.5	414.4	474.4
125°	104.3	121.2	242.1	399.3	450.1
127.5°	109.8	127.3	233.7	383.1	432.8
130°	112.6	131.8	225.6	367.0	415.3
132.5°	117.1	137.0	219.1	349.3	398.4
135°	119.7	141.8	211.1	328.8	377.2
137.5°	123.8	144.6	205.0	308.8	354.0
140°	128.2	148.5	200.0	289.1	330.9
142.5°	131.4	152.1	196.9	271.8	306.8
145°	135.8	153.8	196.2	254.0	284.4
147.5°	141.0	156.9	195.2	237.9	263.1
150°	145.8	159.8	194.2	228.7	244.1
152.5°	148.7	162.6	192.5	222.2	233.8
155°	152.8	165.0	190.8	216.0	225.3
157.5°	156.9	167.1	189.0	210.2	217.4
160°	160.7	169.0	187.0	204.4	210.2
162.5°	164.1	170.6	184.9	198.8	203.4
165°	166.5	171.6	182.9	193.6	196.6
167.5°	169.2	172.4	180.8	189.2	191.1
170°	170.9	173.1	178.8	184.8	186.0
172.5°	172.6	173.6	176.7	180.8	180.8
175°	173.7	174.0	175.4	177.8	177.1
177.5°	174.3	174.0	174.3	175.6	174.3
180°	174.0	174.0	174.0	174.0	174.0

(END OF REPORT)