

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1025196

Luminaire Tested: S124DIP-B1195D590UB40-4F0-XX-W2A-D4

Issue Date: 5/6/2025

Test Information

Test Method: LM-79-2019
Report Number: P1025196
REPORT IS A COMBINATION OF REPORTS P995646 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/6/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S124DIP-B1195D590UB40-4F0-XX-W2A-D4
Description: Define 4 Direct/Indirect Pendant with 4000K BioUP LEDs {m-DER=0.865} {m-EER=0.951}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 6957.2 lumens
Efficiency: N/A
Efficacy: 90.7 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.28 / 1.39
Luminous Opening: Rectangular w/ Sides (W: 0.33' x L: 4' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 76.7
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1025196

CATALOG NUMBER: S124DIP-B1195D590UB40-4F0-XX-W2A-D4

Luminous Intensity Polar Plot



TEST NUMBER: P1025196

CATALOG NUMBER: S124DIP-B1195D590UB40-4F0-XX-W2A-D4

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	111	111	111	111	104	104	104	104	91	91	91	80	80	80	69	69	69
1	100	95	90	86	93	89	85	81	78	75	72	68	66	64	59	58	56
2	90	82	75	69	84	77	71	66	68	63	59	59	56	52	51	49	46
3	82	72	64	57	77	67	60	54	59	54	49	52	47	44	45	42	39
4	75	63	55	48	70	59	52	46	53	46	41	46	41	37	40	36	33
5	69	56	47	41	64	53	45	39	47	40	36	41	36	32	36	32	28
6	63	50	42	35	59	47	40	34	42	36	31	37	32	28	32	28	25
7	58	45	37	31	55	43	35	30	38	32	27	34	28	25	30	25	22
8	54	41	33	27	51	39	32	26	35	29	24	31	26	22	27	23	20
9	51	38	30	24	47	36	28	23	32	26	22	28	23	20	25	21	18
10	47	35	27	22	44	33	26	21	29	23	19	26	21	18	23	19	16

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	11588	11588	11588
5°	11620	11286	11307
10°	11545	11064	11033
15°	11437	10814	10723
20°	11277	10544	10422
25°	11096	10246	10099
30°	10901	9951	9769
35°	10681	9649	9474
40°	10502	9359	9170
45°	10241	9087	8901
50°	10018	8778	8617
55°	9786	8480	8290
60°	9428	8109	7982
65°	9034	7709	7612
70°	8556	7253	7184
75°	7887	6745	6776
80°	7136	6228	6350
85°	6134	5709	6003

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 10241 cd/sqm

TEST NUMBER: P1025196

CATALOG NUMBER: S124DIP-B1195D590UB40-4F0-XX-W2A-D4

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	134.6	1.9
10°-20°	385.8	5.5
20°-30°	583.3	8.4
30°-40°	705.7	10.1
40°-50°	746.0	10.7
50°-60°	702.1	10.1
60°-70°	582.6	8.4
70°-80°	408.9	5.9
80°-90°	231.6	3.3
90°-100°	352.1	5.1
100°-110°	538.6	7.7
110°-120°	457.7	6.6
120°-130°	365.6	5.3
130°-140°	289.7	4.2
140°-150°	211.8	3.0
150°-160°	146.6	2.1
160°-170°	86.2	1.2
170°-180°	28.0	0.4
0°-30°	1103.7	15.9
0°-40°	1809.5	26.0
0°-60°	3257.6	46.8
0°-90°	4480.7	64.4
90°-120°	1348.5	19.4
90°-150°	2215.6	31.8
90°-180°	2476.0	35.6
0°-180°	6957.2	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1421	1421	1421	1421	1421	
5°	1423	1418	1407	1420	1418	135
15°	1364	1365	1361	1375	1373	384
25°	1248	1257	1262	1279	1281	575
35°	1092	1111	1127	1149	1154	684
45°	910	940	971	998	1006	704
55°	713	746	794	826	836	635
65°	493	544	598	638	651	489
75°	274	333	399	444	458	291
85°	84	151	223	270	286	88
90°	26	94	168	215	228	19
95°	40	132	602	411	334	37
105°	81	142	478	948	957	87
115°	127	171	407	749	889	126
125°	170	199	375	618	697	151
135°	197	234	342	522	597	153
145°	225	256	326	416	463	141
155°	254	274	317	359	374	117
165°	277	285	304	322	327	78
175°	289	289	292	296	294	27
180°	289	289	289	289	289	

TEST NUMBER: P1025196

CATALOG NUMBER: S124DIP-B1195D590UB40-4F0-XX-W2A-D4

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1421.1	1421.1	1421.1	1421.1	1421.1
2.5°	1427.4	1422.7	1409.9	1421.1	1419.5
5°	1422.7	1417.9	1406.7	1419.5	1417.9
7.5°	1413.1	1409.9	1400.4	1414.7	1413.1
10°	1400.4	1398.8	1390.8	1405.2	1403.6
12.5°	1382.9	1382.9	1378.1	1390.8	1390.8
15°	1363.8	1365.4	1360.6	1374.9	1373.3
17.5°	1338.3	1343.1	1341.5	1355.8	1354.2
20°	1311.3	1316.0	1317.6	1333.5	1333.5
22.5°	1281.0	1287.4	1290.6	1306.5	1309.7
25°	1247.6	1257.2	1261.9	1279.4	1281.0
27.5°	1211.0	1225.3	1231.7	1247.6	1249.2
30°	1174.4	1187.1	1198.3	1215.8	1219.0
32.5°	1134.6	1150.5	1163.3	1184.0	1187.1
35°	1091.7	1110.8	1126.7	1148.9	1153.7
37.5°	1048.7	1071.0	1090.1	1112.3	1117.1
40°	1007.3	1028.0	1050.3	1074.2	1080.5
42.5°	959.6	983.4	1010.5	1037.6	1042.3
45°	910.2	940.5	970.7	997.8	1005.7
47.5°	864.1	894.3	929.3	956.4	965.9
50°	813.2	848.2	883.2	915.0	924.6
52.5°	762.3	797.3	838.6	870.5	880.0
55°	712.9	746.3	794.1	825.9	835.5
57.5°	657.2	698.6	744.7	782.9	790.9
60°	603.1	644.5	697.0	733.6	746.3
62.5°	550.6	596.8	649.3	685.9	698.6
65°	493.3	544.2	598.3	638.1	650.9
67.5°	439.2	493.3	550.6	590.4	603.1
70°	383.5	437.6	498.1	541.1	552.2
72.5°	329.4	385.1	450.3	491.7	504.5
75°	273.7	332.6	399.4	444.0	458.3
77.5°	221.2	283.3	353.3	397.8	413.7
80°	173.5	237.1	307.1	354.9	367.6
82.5°	125.7	192.6	262.6	311.9	326.2
85°	84.3	151.2	222.8	270.5	286.4
87.5°	52.5	117.8	187.8	233.9	248.2
90°	26.1	93.6	167.7	215.1	228.3
92.5°	31.9	123.4	370.8	266.2	257.0
95°	39.5	132.3	601.6	410.8	334.4
97.5°	50.4	130.6	626.1	640.2	519.2
100°	60.7	132.8	577.8	811.8	696.1
102.5°	72.1	136.6	521.6	914.8	851.9
105°	80.8	142.4	477.8	947.6	957.1
107.5°	93.9	150.2	446.6	926.8	1002.2
110°	105.3	156.4	429.4	871.8	995.3

TEST NUMBER: P1025196

CATALOG NUMBER: S124DIP-B1195D590UB40-4F0-XX-W2A-D4

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	116.2	164.0	416.3	806.6	952.3
115°	126.6	170.8	407.3	748.6	888.7
117.5°	139.1	178.2	398.7	699.8	827.9
120°	150.1	183.8	390.8	663.8	775.2
122.5°	161.4	190.7	382.2	638.6	731.6
125°	169.5	198.6	375.4	618.4	696.9
127.5°	178.6	208.8	366.2	597.2	673.1
130°	184.4	217.2	357.7	575.3	649.9
132.5°	191.8	225.7	350.8	550.8	626.7
135°	197.0	233.9	342.2	522.3	597.2
137.5°	203.8	239.4	335.9	493.8	564.4
140°	211.2	246.0	330.6	466.0	530.8
142.5°	217.6	252.0	327.4	441.2	495.6
145°	224.9	255.8	326.2	416.4	463.2
147.5°	233.5	260.8	324.5	394.6	432.5
150°	241.4	265.7	322.8	380.2	405.8
152.5°	247.2	270.2	320.0	369.4	388.7
155°	254.0	274.2	317.1	359.2	374.5
157.5°	260.9	277.9	314.3	349.5	361.5
160°	267.1	281.0	310.9	339.8	349.5
162.5°	272.8	283.6	307.5	330.5	338.2
165°	276.8	285.3	304.1	322.0	326.8
167.5°	281.3	286.7	300.6	314.5	317.7
170°	284.2	287.8	297.2	307.2	309.2
172.5°	287.0	288.7	293.8	300.6	300.6
175°	288.7	289.3	291.5	295.5	294.4
177.5°	289.8	289.3	289.8	291.8	289.8
180°	289.3	289.3	289.3	289.3	289.3

(END OF REPORT)