

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1025214

Luminaire Tested: S124DIP-B1195D810UB27-4F0-XX-W2A-D4

Issue Date: 5/7/2025

Test Information

Test Method: LM-79-2019
Report Number: P1025214
REPORT IS A COMBINATION OF REPORTS P995664 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S124DIP-B1195D810UB27-4F0-XX-W2A-D4
Description: Define 4 Direct/Indirect Pendant with 2700K BioUP LEDs {m-DER=0.473} {m-EER=0.52}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 7644.6 lumens
Efficiency: N/A
Efficacy: 92.8 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.28 / 1.39
Luminous Opening: Rectangular w/ Sides (W: 0.33' x L: 4' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 82.4
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1025214

CATALOG NUMBER: S124DIP-B1195D810UB27-4F0-XX-W2A-D4

Luminous Intensity Polar Plot



TEST NUMBER: P1025214

CATALOG NUMBER: S124DIP-B1195D810UB27-4F0-XX-W2A-D4

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	109	109	109	109	102	102	102	102	88	88	88	75	75	75	64	64	64
1	99	94	89	85	92	87	83	80	75	73	70	65	62	60	55	53	52
2	89	81	74	69	83	76	70	65	65	61	57	56	53	50	47	45	43
3	81	71	63	57	75	66	59	53	57	52	47	49	45	41	42	38	36
4	74	62	54	48	69	58	51	45	51	45	40	44	39	35	37	33	30
5	68	56	47	41	63	52	44	38	45	39	34	39	34	30	33	29	26
6	62	50	41	35	58	47	39	33	41	34	30	35	30	26	30	26	23
7	58	45	36	31	54	42	34	29	37	31	26	32	27	23	27	23	20
8	54	41	33	27	50	38	31	26	34	27	23	29	24	21	25	21	18
9	50	37	29	24	46	35	28	23	31	25	21	27	22	18	23	19	16
10	47	34	27	22	43	32	25	21	28	23	19	25	20	17	21	18	15

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	11555	11555	11555
5°	11586	11254	11274
10°	11511	11032	11000
15°	11403	10783	10692
20°	11244	10513	10393
25°	11064	10216	10070
30°	10869	9922	9740
35°	10649	9621	9447
40°	10472	9331	9144
45°	10211	9060	8875
50°	9988	8752	8592
55°	9758	8456	8266
60°	9401	8086	7959
65°	9008	7688	7590
70°	8531	7233	7163
75°	7864	6726	6757
80°	7115	6210	6331
85°	6120	5691	5986

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 10211 cd/sqm

TEST NUMBER: P1025214

CATALOG NUMBER: S124DIP-B1195D810UB27-4F0-XX-W2A-D4

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	134.3	1.8
10°-20°	384.7	5.0
20°-30°	581.6	7.6
30°-40°	703.7	9.2
40°-50°	743.9	9.7
50°-60°	700.1	9.2
60°-70°	581.0	7.6
70°-80°	407.7	5.3
80°-90°	231.3	3.0
90°-100°	423.1	5.5
100°-110°	683.5	8.9
110°-120°	586.9	7.7
120°-130°	474.2	6.2
130°-140°	380.3	5.0
140°-150°	281.1	3.7
150°-160°	195.3	2.6
160°-170°	114.8	1.5
170°-180°	37.3	0.5
0°-30°	1100.6	14.4
0°-40°	1804.2	23.6
0°-60°	3248.2	42.5
0°-90°	4468.2	58.4
90°-120°	1693.5	22.2
90°-150°	2829.0	37.0
90°-180°	3176.0	41.5
0°-180°	7644.6	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1417	1417	1417	1417	1417	
5°	1418	1414	1403	1415	1414	135
15°	1360	1361	1357	1371	1369	383
25°	1244	1254	1258	1276	1277	573
35°	1088	1108	1123	1146	1150	682
45°	908	938	968	995	1003	701
55°	711	744	792	824	833	633
65°	492	543	597	636	649	488
75°	273	332	398	443	457	290
85°	84	151	222	270	286	88
90°	26	95	171	218	232	19
95°	46	152	755	486	380	44
105°	103	174	601	1214	1222	111
115°	166	220	518	960	1143	165
125°	224	263	485	799	900	200
135°	261	311	451	682	779	203
145°	299	341	434	552	612	188
155°	338	365	422	478	499	156
165°	369	380	405	429	435	104
175°	385	385	388	394	392	37
180°	385	385	385	385	385	

TEST NUMBER: P1025214

CATALOG NUMBER: S124DIP-B1195D810UB27-4F0-XX-W2A-D4

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1417.0	1417.0	1417.0	1417.0	1417.0
2.5°	1423.3	1418.5	1405.9	1417.0	1415.4
5°	1418.5	1413.8	1402.7	1415.4	1413.8
7.5°	1409.0	1405.9	1396.3	1410.6	1409.0
10°	1396.3	1394.7	1386.8	1401.1	1399.5
12.5°	1378.9	1378.9	1374.1	1386.8	1386.8
15°	1359.8	1361.4	1356.7	1370.9	1369.4
17.5°	1334.5	1339.2	1337.6	1351.9	1350.3
20°	1307.5	1312.2	1313.8	1329.7	1329.7
22.5°	1277.3	1283.7	1286.8	1302.7	1305.9
25°	1244.0	1253.5	1258.3	1275.7	1277.3
27.5°	1207.5	1221.8	1228.1	1244.0	1245.6
30°	1171.0	1183.7	1194.8	1212.3	1215.4
32.5°	1131.3	1147.2	1159.9	1180.5	1183.7
35°	1088.5	1107.5	1123.4	1145.6	1150.4
37.5°	1045.7	1067.9	1086.9	1109.1	1113.9
40°	1004.4	1025.0	1047.2	1071.1	1077.4
42.5°	956.8	980.6	1007.6	1034.6	1039.3
45°	907.6	937.8	967.9	994.9	1002.8
47.5°	861.6	891.7	926.7	953.6	963.2
50°	810.8	845.7	880.6	912.4	921.9
52.5°	760.0	795.0	836.2	867.9	877.5
55°	710.9	744.2	791.8	823.5	833.0
57.5°	655.3	696.6	742.6	780.7	788.6
60°	601.4	642.6	695.0	731.5	744.2
62.5°	549.0	595.0	647.4	683.9	696.6
65°	491.9	542.7	596.6	636.3	649.0
67.5°	437.9	491.9	549.0	588.7	601.4
70°	382.4	436.4	496.7	539.5	550.6
72.5°	328.5	384.0	449.0	490.3	503.0
75°	272.9	331.6	398.3	442.7	457.0
77.5°	220.6	282.4	352.3	396.7	412.6
80°	173.0	236.4	306.2	353.8	366.5
82.5°	125.4	192.0	261.8	311.0	325.3
85°	84.1	150.7	222.1	269.7	285.6
87.5°	52.4	117.4	187.2	233.3	247.5
90°	26.2	95.0	170.7	218.2	231.7
92.5°	34.4	137.6	444.4	290.0	273.6
95°	45.6	151.7	755.0	486.4	379.9
97.5°	60.6	152.2	790.2	795.2	629.2
100°	75.0	157.1	729.3	1026.4	868.7
102.5°	90.2	164.5	657.0	1166.9	1078.8
105°	102.9	174.3	601.3	1213.7	1222.3
107.5°	120.3	186.3	562.4	1188.8	1285.4
110°	136.1	196.5	541.6	1118.6	1278.9

TEST NUMBER: P1025214

CATALOG NUMBER: S124DIP-B1195D810UB27-4F0-XX-W2A-D4

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	151.2	208.4	526.9	1035.0	1224.8
115°	165.5	219.5	517.5	960.4	1143.4
117.5°	182.1	231.0	508.7	898.7	1065.1
120°	197.2	240.6	500.8	853.9	997.9
122.5°	212.3	251.3	492.2	822.9	943.0
125°	223.6	263.0	485.0	798.7	900.2
127.5°	235.7	276.6	475.6	773.7	871.1
130°	244.0	288.2	466.9	747.2	843.3
132.5°	253.9	299.6	459.8	717.3	815.0
135°	261.4	310.6	451.1	682.4	779.0
137.5°	270.4	318.5	444.7	647.2	738.4
140°	280.3	327.1	439.3	612.8	696.4
142.5°	289.3	335.1	436.1	581.8	652.1
145°	299.1	340.6	434.5	551.5	611.7
147.5°	310.5	347.5	432.3	525.1	573.4
150°	321.1	353.9	430.0	506.4	540.5
152.5°	329.3	360.0	426.2	492.1	517.8
155°	338.4	365.3	422.4	478.4	498.9
157.5°	347.5	370.2	418.6	465.6	481.5
160°	355.8	374.4	414.1	452.7	465.6
162.5°	363.4	377.8	409.6	440.2	450.4
165°	368.7	380.0	405.0	428.9	435.3
167.5°	374.7	381.9	400.5	419.0	423.2
170°	378.5	383.5	395.9	409.2	411.8
172.5°	382.3	384.6	391.4	400.4	400.5
175°	384.6	385.3	388.4	393.7	392.1
177.5°	386.1	385.3	386.1	388.8	386.1
180°	385.3	385.3	385.3	385.3	385.3

(END OF REPORT)