

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1026763

Luminaire Tested: S125DIP-B1270D1090UB2750-4F0-XX-W2A-D_5000K

Issue Date: 5/7/2025

Test Information

Test Method: LM-79-2019
Report Number: P1026763
REPORT IS A COMBINATION OF REPORTS P1001537 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S125DIP-B1270D1090UB2750-4F0-XX-W2A-D_5000K
Description: Define 5 Direct/Indirect Pendant with 5000K BioUP LEDs {m-DER=1.015} {m-EER=1.115}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 8687.0 lumens
Efficiency: N/A
Efficacy: 96.7 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.21 / 1.34
Luminous Opening: Rectangular w/ Sides (W: 0.42' x L: 4' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 89.8
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1026763

CATALOG NUMBER: S125DIP-B1270D1090UB2750-4F0-XX-W2A-D_5000K

Luminous Intensity Polar Plot



TEST NUMBER: P1026763

CATALOG NUMBER: S125DIP-B1270D1090UB2750-4F0-XX-W2A-D_5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	107	107	107	107	99	99	99	99	84	84	84		70	70	70		57
1	97	93	88	85	90	86	82	79	73	70	67		61	59	57		49
2	88	80	74	69	81	74	69	64	63	59	55		53	50	47		43
3	80	70	63	57	74	65	59	53	55	50	46		46	43	39		38
4	73	62	54	48	67	58	50	45	49	44	39		41	37	34		34
5	67	55	47	41	62	51	44	38	44	38	34		37	32	29		30
6	62	50	41	35	57	46	39	33	39	34	29		33	29	25		27
7	57	45	37	31	53	42	34	29	36	30	26		30	26	22		25
8	53	41	33	27	49	38	31	26	33	27	23		28	23	20		23
9	49	37	29	24	46	35	28	23	30	24	20		25	21	18		21
10	46	34	27	22	43	32	25	21	27	22	18		23	19	16		20

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	9818	9818	9818
5°	9834	9612	9636
10°	9760	9416	9389
15°	9642	9188	9086
20°	9481	8913	8786
25°	9291	8619	8421
30°	9061	8300	8091
35°	8846	8005	7785
40°	8627	7695	7478
45°	8380	7426	7201
50°	8143	7133	6952
55°	7858	6855	6662
60°	7546	6537	6365
65°	7220	6203	6031
70°	6847	5755	5683
75°	6258	5313	5258
80°	5487	4774	4788
85°	4723	4345	4541

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 8380 cd/sqm

TEST NUMBER: P1026763

CATALOG NUMBER: S125DIP-B1270D1090UB2750-4F0-XX-W2A-D_5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	145.0	1.7
10°-20°	411.6	4.7
20°-30°	612.1	7.0
30°-40°	724.9	8.3
40°-50°	749.5	8.6
50°-60°	690.4	7.9
60°-70°	558.1	6.4
70°-80°	373.4	4.3
80°-90°	194.9	2.2
90°-100°	152.2	1.8
100°-110°	369.5	4.3
110°-120°	574.7	6.6
120°-130°	699.2	8.0
130°-140°	732.6	8.4
140°-150°	677.7	7.8
150°-160°	546.1	6.3
160°-170°	353.2	4.1
170°-180°	121.8	1.4
0°-30°	1168.8	13.5
0°-40°	1893.7	21.8
0°-60°	3333.6	38.4
0°-90°	4460.1	51.3
90°-120°	1096.4	12.6
90°-150°	3205.9	36.9
90°-180°	4227.0	48.7
0°-180°	8687.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1532	1532	1532	1532	1532	
5°	1532	1529	1519	1531	1529	145
15°	1463	1465	1454	1463	1457	412
25°	1330	1334	1325	1331	1324	612
35°	1151	1161	1157	1161	1161	720
45°	948	964	972	982	984	731
55°	729	753	777	793	799	651
65°	502	536	572	595	601	498
75°	276	316	364	394	401	293
85°	83	132	185	218	230	86
90°	25	81	138	178	191	19
95°	74	110	125	163	173	82
105°	293	321	366	396	406	310
115°	534	549	589	612	615	529
125°	752	757	787	808	812	671
135°	933	938	946	964	966	720
145°	1080	1080	1080	1089	1089	675
155°	1188	1182	1184	1187	1179	547
165°	1254	1248	1249	1254	1247	354
175°	1282	1276	1277	1285	1276	122
180°	1282	1282	1282	1282	1282	

TEST NUMBER: P1026763

CATALOG NUMBER: S125DIP-B1270D1090UB2750-4F0-XX-W2A-D_5000K

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1532.4	1532.4	1532.4	1532.4	1532.4
2.5°	1536.9	1533.9	1523.4	1533.9	1532.4
5°	1532.4	1529.4	1518.8	1530.9	1529.4
7.5°	1521.8	1520.3	1509.8	1520.3	1518.8
10°	1506.8	1506.8	1494.8	1505.3	1503.8
12.5°	1485.8	1487.3	1478.3	1485.8	1481.3
15°	1463.3	1464.8	1454.2	1463.3	1457.2
17.5°	1434.7	1437.7	1427.2	1434.7	1430.2
20°	1403.2	1406.2	1395.7	1400.2	1400.2
22.5°	1367.1	1373.1	1361.1	1367.1	1362.6
25°	1329.6	1334.1	1325.0	1331.1	1323.5
27.5°	1289.0	1295.0	1284.5	1289.0	1286.0
30°	1242.4	1251.4	1242.4	1245.4	1243.9
32.5°	1200.4	1207.9	1201.9	1204.9	1203.4
35°	1150.8	1161.3	1156.8	1161.3	1161.3
37.5°	1102.7	1111.7	1110.2	1116.2	1114.7
40°	1053.1	1065.1	1063.6	1069.7	1072.7
42.5°	999.0	1015.6	1020.1	1027.6	1027.6
45°	948.0	964.5	972.0	982.5	984.0
47.5°	895.4	910.4	922.4	937.4	940.5
50°	841.3	857.8	874.3	890.9	895.4
52.5°	784.2	805.2	826.3	844.3	847.3
55°	728.6	752.7	776.7	793.2	799.2
57.5°	671.5	700.1	727.1	745.2	749.7
60°	614.4	644.5	674.5	697.1	701.6
62.5°	558.9	588.9	622.0	647.5	653.5
65°	501.8	536.3	572.4	594.9	600.9
67.5°	449.2	482.2	518.3	545.3	552.9
70°	390.6	425.2	464.2	492.8	501.8
72.5°	333.5	369.6	413.1	444.7	450.7
75°	276.4	315.5	363.6	393.6	401.1
77.5°	220.8	265.9	311.0	344.0	350.0
80°	169.8	214.8	265.9	299.0	305.0
82.5°	123.2	171.3	223.8	255.4	267.4
85°	82.6	132.2	184.8	217.8	229.9
87.5°	52.6	100.7	151.7	186.3	196.8
90°	25.0	80.7	138.4	177.7	191.1
92.5°	39.1	74.1	132.4	170.2	181.6
95°	73.7	109.9	124.9	162.7	173.2
97.5°	119.7	161.5	120.8	154.2	165.7
100°	175.2	209.7	261.5	151.5	156.7
102.5°	231.7	264.1	312.5	344.5	273.7
105°	292.9	320.8	365.8	395.9	405.5
107.5°	356.0	377.1	422.5	453.6	458.8
110°	417.2	435.2	479.3	505.0	516.4

TEST NUMBER: P1026763

CATALOG NUMBER: S125DIP-B1270D1090UB2750-4F0-XX-W2A-D_5000K

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	476.2	492.5	534.1	557.3	566.0
115°	533.6	548.8	588.9	612.1	615.4
117.5°	593.9	601.4	642.8	662.6	671.2
120°	650.9	654.4	691.9	715.5	719.7
122.5°	699.8	706.0	740.1	762.2	765.5
125°	752.0	757.2	787.3	807.5	812.1
127.5°	800.9	804.1	828.7	849.4	850.8
130°	846.5	849.8	871.7	890.0	892.7
132.5°	890.6	896.3	908.5	929.6	930.8
135°	933.4	937.6	946.2	963.8	965.7
137.5°	973.3	977.5	981.6	999.6	1000.9
140°	1010.8	1012.7	1013.2	1031.6	1031.9
142.5°	1045.9	1045.4	1047.3	1060.8	1061.1
145°	1080.1	1080.5	1080.5	1089.0	1089.3
147.5°	1109.1	1109.1	1110.0	1114.0	1110.3
150°	1137.6	1135.7	1137.6	1139.5	1133.4
152.5°	1165.1	1160.4	1162.3	1164.2	1157.5
155°	1187.9	1182.2	1184.1	1187.0	1179.4
157.5°	1206.0	1203.1	1203.1	1206.0	1198.4
160°	1225.0	1219.3	1220.2	1224.1	1216.4
162.5°	1240.2	1234.5	1235.5	1241.2	1232.6
165°	1253.5	1247.8	1248.8	1254.5	1246.9
167.5°	1264.0	1258.3	1259.2	1265.9	1257.3
170°	1272.5	1265.9	1266.8	1274.4	1265.9
172.5°	1278.2	1271.6	1273.5	1280.1	1271.6
175°	1282.0	1276.3	1277.3	1284.9	1276.3
177.5°	1284.9	1279.2	1280.1	1286.8	1279.2
180°	1282.0	1282.0	1282.0	1282.0	1282.0

(END OF REPORT)