

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1026911

Luminaire Tested: S125DIP-B610D1090UB2750-4F0-XX-W2A-D_3500K

Issue Date: 5/7/2025

Test Information

Test Method: LM-79-2019
Report Number: P1026911
REPORT IS A COMBINATION OF REPORTS P1002135 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S125DIP-B610D1090UB2750-4F0-XX-W2A-D_3500K
Description: Define 5 Direct/Indirect Pendant with 3500K BioUP LEDs {m-DER=0.721} {m-EER=0.792}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 6517.0 lumens
Efficiency: N/A
Efficacy: 124.1 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.21 / 1.34
Luminous Opening: Rectangular w/ Sides (W: 0.42' x L: 4' x H: 0.1')
CIE Type: Semi-Indirect

Input Watts (W): 52.5
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1026911

CATALOG NUMBER: S125DIP-B610D1090UB2750-4F0-XX-W2A-D_3500K

Luminous Intensity Polar Plot



TEST NUMBER: P1026911

CATALOG NUMBER: S125DIP-B610D1090UB2750-4F0-XX-W2A-D_3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	103	103	103	103	93	93	93	93	75	75	75		58	58	58		42
1	94	89	85	82	85	81	77	74	65	62	60		50	48	47		36
2	85	78	72	66	77	70	65	61	56	53	49		44	41	39		32
3	78	68	61	55	70	62	55	50	50	45	41		38	35	33		28
4	71	60	52	46	64	54	48	42	44	39	35		34	30	28		25
5	65	53	45	39	58	48	41	36	39	34	30		30	27	24		22
6	60	48	40	34	54	43	36	31	35	30	26		27	24	21		20
7	55	43	35	30	49	39	32	27	32	26	23		25	21	18		18
8	51	39	31	26	46	35	29	24	29	24	20		23	19	16		17
9	47	35	28	23	43	32	26	21	26	21	18		21	17	14		15
10	44	32	25	20	40	30	23	19	24	19	16		19	16	13		14

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	4966	4966	4966
5°	4974	4862	4873
10°	4936	4763	4749
15°	4876	4647	4596
20°	4795	4508	4444
25°	4699	4360	4259
30°	4583	4198	4092
35°	4475	4049	3938
40°	4364	3892	3782
45°	4239	3756	3642
50°	4119	3608	3517
55°	3974	3467	3369
60°	3817	3307	3220
65°	3652	3137	3050
70°	3464	2911	2874
75°	3165	2687	2660
80°	2776	2415	2422
85°	2390	2199	2297

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 4239 cd/sqm

TEST NUMBER: P1026911

CATALOG NUMBER: S125DIP-B610D1090UB2750-4F0-XX-W2A-D_3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	73.3	1.1
10°-20°	208.2	3.2
20°-30°	309.6	4.8
30°-40°	366.7	5.6
40°-50°	379.1	5.8
50°-60°	349.2	5.4
60°-70°	282.3	4.3
70°-80°	188.9	2.9
80°-90°	99.6	1.5
90°-100°	100.4	1.5
100°-110°	342.8	5.3
110°-120°	571.5	8.8
120°-130°	714.0	11.0
130°-140°	758.2	11.6
140°-150°	706.6	10.8
150°-160°	570.5	8.8
160°-170°	368.9	5.7
170°-180°	127.2	2.0
0°-30°	591.2	9.1
0°-40°	957.8	14.7
0°-60°	1686.1	25.9
0°-90°	2256.9	34.6
90°-120°	1014.7	15.6
90°-150°	3193.5	49.0
90°-180°	4260.0	65.4
0°-180°	6517.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	775	775	775	775	775	
5°	775	774	768	774	774	74
15°	740	741	736	740	737	209
25°	672	675	670	673	669	310
35°	582	587	585	587	587	364
45°	480	488	492	497	498	370
55°	368	381	393	401	404	329
65°	254	271	290	301	304	252
75°	140	160	184	199	203	148
85°	42	67	94	110	116	44
90°	13	45	78	101	109	11
95°	66	83	71	93	98	77
105°	299	315	338	353	357	316
115°	553	563	584	593	592	548
125°	782	789	804	812	813	699
135°	974	979	982	990	988	751
145°	1128	1129	1129	1134	1131	705
155°	1241	1235	1237	1240	1232	572
165°	1310	1304	1304	1310	1303	370
175°	1339	1333	1334	1342	1333	128
180°	1339	1339	1339	1339	1339	

TEST NUMBER: P1026911

CATALOG NUMBER: S125DIP-B610D1090UB2750-4F0-XX-W2A-D_3500K

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	775.1	775.1	775.1	775.1	775.1
2.5°	777.3	775.8	770.5	775.8	775.1
5°	775.1	773.5	768.2	774.3	773.5
7.5°	769.7	769.0	763.7	769.0	768.2
10°	762.1	762.1	756.1	761.4	760.6
12.5°	751.5	752.3	747.7	751.5	749.2
15°	740.1	740.9	735.5	740.1	737.1
17.5°	725.7	727.2	721.9	725.7	723.4
20°	709.7	711.2	705.9	708.2	708.2
22.5°	691.5	694.5	688.4	691.5	689.2
25°	672.5	674.8	670.2	673.2	669.4
27.5°	652.0	655.0	649.7	652.0	650.4
30°	628.4	633.0	628.4	629.9	629.2
32.5°	607.1	610.9	607.9	609.4	608.6
35°	582.1	587.4	585.1	587.4	587.4
37.5°	557.7	562.3	561.5	564.6	563.8
40°	532.7	538.7	538.0	541.0	542.5
42.5°	505.3	513.7	515.9	519.7	519.7
45°	479.5	487.8	491.6	497.0	497.7
47.5°	452.9	460.5	466.6	474.2	475.7
50°	425.5	433.9	442.2	450.6	452.9
52.5°	396.6	407.3	417.9	427.0	428.6
55°	368.5	380.7	392.8	401.2	404.2
57.5°	339.7	354.1	367.8	376.9	379.2
60°	310.8	326.0	341.2	352.6	354.9
62.5°	282.7	297.9	314.6	327.5	330.5
65°	253.8	271.3	289.5	300.9	303.9
67.5°	227.2	243.9	262.2	275.8	279.6
70°	197.6	215.0	234.8	249.2	253.8
72.5°	168.7	186.9	209.0	224.9	228.0
75°	139.8	159.6	183.9	199.1	202.9
77.5°	111.7	134.5	157.3	174.0	177.0
80°	85.9	108.7	134.5	151.2	154.3
82.5°	62.3	86.6	113.2	129.2	135.3
85°	41.8	66.9	93.5	110.2	116.3
87.5°	26.6	50.9	76.7	94.2	99.5
90°	13.2	45.4	78.2	100.6	108.9
92.5°	29.5	42.6	75.2	96.8	103.1
95°	66.5	83.2	71.4	93.0	98.3
97.5°	115.3	139.6	70.3	88.3	94.5
100°	174.2	193.1	221.3	89.4	89.9
102.5°	234.0	252.3	277.9	295.1	216.2
105°	298.7	314.9	337.7	352.9	357.2
107.5°	365.5	376.1	400.2	416.4	416.9
110°	430.2	439.3	462.6	474.1	480.4

TEST NUMBER: P1026911

CATALOG NUMBER: S125DIP-B610D1090UB2750-4F0-XX-W2A-D_3500K

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	491.8	501.7	523.1	532.9	536.2
115°	552.6	562.9	583.6	593.3	592.0
117.5°	616.4	620.2	643.1	650.1	653.4
120°	675.9	677.2	697.7	708.6	708.2
122.5°	727.7	733.5	751.2	761.4	760.0
125°	782.3	788.6	803.8	811.9	812.7
127.5°	834.3	838.4	850.3	859.8	856.4
130°	881.9	886.1	897.8	905.4	904.2
132.5°	928.8	934.7	939.4	950.1	948.1
135°	973.5	978.7	982.0	989.9	987.8
137.5°	1015.2	1020.4	1021.4	1030.5	1028.7
140°	1055.2	1057.1	1056.8	1067.2	1064.3
142.5°	1091.9	1092.1	1094.1	1100.9	1098.0
145°	1127.6	1128.8	1128.8	1133.6	1130.7
147.5°	1158.6	1158.6	1159.6	1162.1	1156.6
150°	1188.4	1186.4	1188.4	1190.4	1183.2
152.5°	1217.2	1212.2	1214.2	1216.2	1209.2
155°	1241.0	1235.0	1237.0	1240.0	1232.1
157.5°	1259.9	1256.9	1256.9	1259.9	1251.9
160°	1279.7	1273.8	1274.8	1278.7	1270.8
162.5°	1295.6	1289.6	1290.6	1296.6	1287.7
165°	1309.5	1303.5	1304.5	1310.5	1302.6
167.5°	1320.4	1314.5	1315.5	1322.4	1313.5
170°	1329.4	1322.4	1323.4	1331.3	1322.4
172.5°	1335.3	1328.4	1330.4	1337.3	1328.4
175°	1339.3	1333.3	1334.3	1342.3	1333.3
177.5°	1342.3	1336.3	1337.3	1344.3	1336.3
180°	1339.3	1339.3	1339.3	1339.3	1339.3

(END OF REPORT)