

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1027742

Luminaire Tested: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

Issue Date: 5/6/2025

Test Information

Test Method: LM-79-2019
Report Number: P1027742
REPORT IS A COMBINATION OF REPORTS P1001811 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/6/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S125DIP-B1270D850UB50-4F0-XX-W2A-A1
Description: Define 5 Direct/Indirect Pendant with 5000K BioUP LEDs {m-DER=1.015} {m-EER=1.115}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 7629.0 lumens
Efficiency: N/A
Efficacy: 92.6 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.43 / 1.52
Luminous Opening: Rectangular w/ Sides (W: 0.42' x L: 4' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 82.4
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1027742

CATALOG NUMBER: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

Luminous Intensity Polar Plot



TEST NUMBER: P1027742

CATALOG NUMBER: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	111	111	111	111	104	104	104	104	92	92	92	81	81	81	70	70	70
1	102	97	93	90	95	92	88	85	81	79	76	72	70	68	63	61	60
2	93	85	79	74	87	80	75	70	71	67	64	63	60	57	56	53	51
3	85	75	68	62	79	71	64	59	63	58	54	56	52	49	49	46	44
4	78	67	59	53	73	63	56	50	56	51	46	50	46	42	44	41	38
5	71	60	51	45	67	57	49	44	51	45	40	45	40	36	40	36	33
6	66	54	45	39	62	51	43	38	46	40	35	41	36	32	36	32	29
7	61	49	40	35	57	46	39	33	42	35	31	37	32	28	33	29	26
8	57	44	36	31	53	42	35	30	38	32	28	34	29	25	30	26	23
9	53	40	33	28	50	38	31	27	35	29	25	31	26	23	28	24	21
10	49	37	30	25	47	35	29	24	32	26	22	29	24	21	26	22	19

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	11339	11339	11339	11339
5°	11348	12863	11358	9759
10°	11278	14662	11259	8377
15°	11195	15897	11126	7569
20°	11054	17420	10953	6910
25°	10929	19960	10729	6520
30°	10748	21057	10562	6166
35°	10463	16880	10244	5882
40°	10018	11667	9871	5582
45°	9456	8686	9349	5332
50°	8812	7150	8667	5132
55°	8118	6099	8053	4959
60°	7436	5220	7307	4825
65°	6701	4508	6593	4629
70°	5925	3743	5846	4288
75°	5104	2894	5033	3721
80°	4030	1958	3884	2736
85°	2579	980	2493	1395

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 135°

Vertical Angle: 45°

Luminance: 17319 cd/sqm

TEST NUMBER: P1027742

CATALOG NUMBER: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	170.3	2.2
10°-20°	507.3	6.7
20°-30°	824.1	10.8
30°-40°	1007.2	13.2
40°-50°	913.6	12.0
50°-60°	727.7	9.5
60°-70°	506.8	6.6
70°-80°	270.0	3.5
80°-90°	68.4	0.9
90°-100°	62.7	0.8
100°-110°	186.4	2.4
110°-120°	316.1	4.1
120°-130°	416.2	5.5
130°-140°	466.4	6.1
140°-150°	457.1	6.0
150°-160°	384.0	5.0
160°-170°	255.2	3.3
170°-180°	89.3	1.2
0°-30°	1501.8	19.7
0°-40°	2509.0	32.9
0°-60°	4150.2	54.4
0°-90°	4995.5	65.5
90°-120°	565.3	7.4
90°-150°	1905.0	25.0
90°-180°	2634.0	34.5
0°-180°	7629.0	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1770	1770	1770	1770	1770	
5°	1768	2042	1770	1549	1768	168
15°	1699	2550	1689	1214	1699	480
25°	1564	3137	1535	1025	1564	720
35°	1361	2518	1333	877	1361	850
45°	1070	1187	1058	729	1070	824
55°	753	732	747	595	753	673
65°	466	449	458	461	466	462
75°	225	221	222	284	225	240
85°	45	50	44	71	45	54
90°	1	18	1	18	1	6
95°	48	63	48	63	48	50
105°	167	182	167	182	167	179
115°	316	319	316	319	316	313
125°	462	465	462	465	462	414
135°	601	603	601	603	601	463
145°	728	731	728	731	728	455
155°	833	833	833	833	833	384
165°	905	903	905	903	905	255
175°	941	938	941	938	941	89
180°	944	944	944	944	944	

TEST NUMBER: P1027742

CATALOG NUMBER: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	22.5°	25°	30°	35°	40°	45°
0°	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8
2.5°	1772.8	1783.3	1795.3	1804.3	1819.3	1823.8	1831.4	1835.9	1840.4	1844.9	1847.9
5°	1768.3	1793.8	1816.3	1832.9	1861.4	1871.9	1885.4	1902.0	1921.5	1938.0	1948.5
7.5°	1756.2	1796.8	1826.8	1859.9	1899.0	1924.5	1938.0	1972.6	2004.1	2028.2	2059.7
10°	1741.2	1789.3	1835.9	1885.4	1941.0	1969.6	1996.6	2044.7	2088.3	2127.3	2158.9
12.5°	1724.7	1783.3	1838.9	1903.5	1978.6	2013.1	2031.2	2113.8	2167.9	2188.9	2250.5
15°	1699.1	1768.3	1847.9	1927.5	1990.6	2031.2	2080.7	2146.8	2200.9	2247.5	2297.1
17.5°	1675.1	1750.2	1831.4	1920.0	2011.6	2064.2	2101.8	2160.4	2219.0	2279.1	2325.6
20°	1636.0	1733.7	1816.3	1911.0	2019.1	2056.7	2095.8	2164.9	2228.0	2292.6	2351.2
22.5°	1604.5	1697.6	1810.3	1900.5	1992.1	2029.7	2077.7	2149.8	2225.0	2298.6	2384.2
25°	1563.9	1667.6	1765.3	1861.4	1956.0	1996.6	2040.2	2133.3	2211.4	2306.1	2400.7
27.5°	1520.4	1627.0	1724.7	1811.8	1900.5	1956.0	2002.6	2100.3	2203.9	2307.6	2430.8
30°	1473.8	1574.5	1667.6	1753.2	1850.9	1908.0	1954.5	2068.7	2184.4	2316.6	2463.8
32.5°	1424.2	1518.9	1598.5	1685.6	1789.3	1841.9	1905.0	2029.7	2166.4	2324.1	2508.9
35°	1361.1	1451.3	1521.9	1610.5	1714.2	1781.8	1847.9	1987.6	2146.8	2322.6	2534.4
37.5°	1298.0	1368.6	1436.2	1530.9	1651.1	1712.7	1781.8	1935.0	2116.8	2318.1	2545.0
40°	1222.9	1292.0	1350.6	1446.8	1573.0	1643.6	1715.7	1876.4	2082.2	2301.6	2507.4
42.5°	1147.8	1206.4	1271.0	1371.6	1493.3	1568.4	1645.1	1823.8	2037.2	2253.5	2403.7
45°	1069.7	1114.7	1185.3	1277.0	1406.2	1478.3	1565.4	1759.2	1974.1	2166.4	2241.5
47.5°	988.5	1033.6	1099.7	1188.4	1316.1	1401.7	1484.3	1678.1	1894.5	2043.2	2043.2
50°	910.4	946.5	1011.1	1099.7	1228.9	1307.0	1391.2	1597.0	1771.3	1880.9	1783.3
52.5°	826.3	866.9	920.9	1014.1	1141.8	1212.4	1304.0	1479.8	1645.1	1690.1	1539.9
55°	752.7	785.7	836.8	925.4	1044.1	1117.7	1195.9	1364.1	1503.8	1500.8	1340.1
57.5°	676.1	703.1	757.2	838.3	948.0	1014.1	1092.2	1237.9	1352.1	1311.5	1159.8
60°	605.4	625.0	677.6	743.7	848.8	910.4	985.5	1104.2	1191.4	1134.3	981.0
62.5°	531.8	554.4	596.4	661.0	754.2	803.8	859.3	979.5	1035.1	984.0	827.8
65°	465.7	483.8	521.3	575.4	659.5	704.6	752.7	851.8	904.4	830.8	701.6
67.5°	399.6	420.7	447.7	495.8	561.9	603.9	646.0	731.6	755.7	689.6	581.4
70°	338.0	356.1	381.6	416.1	471.7	509.3	540.8	611.5	628.0	566.4	480.7
72.5°	277.9	290.0	311.0	339.5	390.6	411.6	444.7	492.8	513.8	458.2	396.6
75°	225.4	234.4	247.9	268.9	303.5	326.0	353.1	398.1	396.6	357.6	314.0
77.5°	174.3	175.8	190.8	210.3	231.4	250.9	264.4	296.0	299.0	274.9	238.9
80°	124.7	129.2	135.2	150.2	168.3	175.8	192.3	211.8	214.8	196.8	172.8
82.5°	79.6	82.6	87.1	96.1	108.2	117.2	126.2	133.7	141.2	130.7	111.2
85°	45.1	46.6	51.1	54.1	60.1	64.6	72.1	79.6	78.1	70.6	64.6
87.5°	22.5	22.5	22.5	25.5	28.5	28.5	31.5	33.1	34.6	31.5	28.5
90°	0.7	2.0	3.3	4.6	5.9	6.6	7.2	8.3	9.4	10.6	11.7
92.5°	22.0	22.8	23.6	24.5	25.3	25.7	26.4	27.9	29.4	30.8	32.3
95°	47.7	48.0	48.4	48.7	49.0	49.2	50.0	51.6	53.3	54.9	56.5
97.5°	73.4	73.6	73.8	73.9	74.1	74.2	75.3	77.6	79.9	82.1	84.4
100°	102.8	102.8	102.8	102.8	102.8	102.8	103.9	106.0	108.1	110.3	112.4
102.5°	134.4	135.2	136.0	136.9	137.7	138.1	138.5	139.3	140.1	140.9	141.7
105°	167.4	168.2	169.0	169.9	170.7	171.1	171.6	172.6	173.5	174.5	175.5
107.5°	203.4	204.2	205.0	205.9	206.7	207.1	207.5	208.3	209.2	210.0	210.8
110°	240.9	241.7	242.5	243.3	244.1	244.5	244.7	245.2	245.7	246.2	246.7

TEST NUMBER: P1027742

CATALOG NUMBER: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	22.5°	25°	30°	35°	40°	45°
112.5°	279.0	279.3	279.7	280.0	280.3	280.5	280.8	281.5	282.1	282.8	283.4
115°	316.5	317.1	317.8	318.4	319.1	319.4	319.6	319.9	320.2	320.6	320.9
117.5°	354.7	354.9	355.0	355.2	355.3	355.4	355.6	355.9	356.2	356.6	356.9
120°	389.9	390.7	391.5	392.4	393.2	393.6	393.7	393.8	394.0	394.1	394.3
122.5°	428.1	428.3	428.4	428.6	428.7	428.8	429.0	429.5	430.0	430.5	431.0
125°	461.9	462.9	463.9	464.8	465.8	466.3	466.4	466.5	466.7	466.8	467.0
127.5°	499.3	499.8	500.3	500.8	501.3	501.5	501.6	501.8	501.9	502.1	502.3
130°	532.4	533.2	534.0	534.9	535.7	536.1	536.3	536.6	536.9	537.2	537.5
132.5°	565.4	566.9	568.3	569.8	571.3	572.0	571.9	571.8	571.6	571.5	571.3
135°	600.7	601.7	602.7	603.6	604.6	605.1	605.2	605.3	605.5	605.6	605.8
137.5°	633.7	634.7	635.7	636.6	637.6	638.1	638.3	638.6	638.9	639.3	639.6
140°	665.3	666.1	666.9	667.8	668.6	669.0	669.2	669.7	670.2	670.7	671.2
142.5°	696.9	697.5	698.2	698.8	699.5	699.8	700.1	700.8	701.4	702.1	702.7
145°	727.7	728.4	729.0	729.7	730.4	730.7	730.9	731.4	731.9	732.4	732.9
147.5°	756.4	756.9	757.4	757.9	758.4	758.6	758.8	759.1	759.4	759.7	760.0
150°	785.0	784.8	784.7	784.5	784.4	784.3	784.6	785.3	785.9	786.6	787.2
152.5°	808.5	808.8	809.2	809.5	809.8	810.0	810.1	810.2	810.4	810.5	810.7
155°	832.7	832.7	832.7	832.7	832.7	832.7	832.8	833.0	833.1	833.3	833.5
157.5°	854.8	854.5	854.1	853.8	853.5	853.3	853.4	853.5	853.7	853.8	854.0
160°	873.8	873.3	872.8	872.3	871.8	871.6	871.7	871.9	872.0	872.2	872.4
162.5°	890.7	890.4	890.1	889.8	889.5	889.3	889.3	889.3	889.3	889.3	889.3
165°	905.4	905.1	904.8	904.5	904.2	904.0	904.1	904.2	904.4	904.5	904.7
167.5°	918.6	918.0	917.3	916.7	916.0	915.7	915.7	915.7	915.7	915.7	915.7
170°	928.9	928.3	927.6	927.0	926.3	926.0	926.0	926.0	926.0	926.0	926.0
172.5°	936.3	935.6	935.0	934.3	933.6	933.3	933.3	933.3	933.3	933.3	933.3
175°	941.4	940.8	940.1	939.5	938.8	938.5	938.5	938.5	938.5	938.5	938.5
177.5°	945.1	944.4	943.8	943.1	942.4	942.1	942.0	941.9	941.7	941.6	941.4
180°	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6

TEST NUMBER: P1027742

CATALOG NUMBER: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	50°	55°	60°	65°	67.5°	70°	75°	80°	85°	90°	95°
0°	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8
2.5°	1850.9	1861.4	1870.4	1877.9	1883.9	1892.9	1886.9	1888.4	1891.4	1897.5	1897.5
5°	1971.1	1987.6	1996.6	2026.7	2034.2	2032.7	2028.2	2052.2	2050.7	2041.7	2040.2
7.5°	2088.3	2116.8	2142.3	2166.4	2173.9	2193.4	2197.9	2208.4	2205.4	2220.5	2212.9
10°	2194.9	2240.0	2264.0	2300.1	2309.1	2318.1	2330.1	2336.1	2349.7	2348.2	2348.2
12.5°	2277.5	2331.6	2363.2	2372.2	2406.8	2417.3	2427.8	2447.3	2442.8	2444.3	2453.3
15°	2342.1	2394.7	2421.8	2463.8	2487.9	2499.9	2517.9	2539.0	2536.0	2549.5	2546.5
17.5°	2390.2	2439.8	2489.4	2552.5	2554.0	2585.5	2627.6	2636.6	2656.1	2642.6	2642.6
20°	2429.3	2495.4	2566.0	2647.1	2656.1	2675.7	2726.7	2761.3	2783.8	2776.3	2780.8
22.5°	2471.4	2566.0	2648.6	2729.8	2773.3	2807.9	2857.5	2911.5	2931.1	2943.1	2940.1
25°	2525.4	2624.6	2746.3	2859.0	2904.0	2970.1	3036.2	3088.8	3103.8	3136.9	3106.8
27.5°	2581.0	2720.7	2872.5	3004.7	3061.8	3115.9	3195.5	3234.5	3254.1	3269.1	3258.6
30°	2627.6	2819.9	2985.2	3106.8	3147.4	3179.0	3224.0	3233.0	3225.5	3237.5	3252.6
32.5°	2699.7	2887.5	3027.2	3085.8	3081.3	3079.8	3045.2	2997.2	2986.7	2958.1	2997.2
35°	2738.8	2889.0	2943.1	2865.0	2833.4	2776.3	2666.7	2594.5	2531.4	2517.9	2520.9
37.5°	2716.2	2774.8	2710.2	2504.4	2453.3	2366.2	2220.5	2118.3	2071.7	2035.7	2082.2
40°	2594.5	2529.9	2352.7	2101.8	2028.2	1945.5	1808.8	1753.2	1687.1	1673.6	1735.2
42.5°	2393.2	2196.4	1945.5	1751.7	1675.1	1628.5	1514.4	1461.8	1415.2	1394.2	1428.7
45°	2119.8	1880.9	1628.5	1469.3	1404.7	1349.1	1281.5	1225.9	1195.9	1186.8	1215.4
47.5°	1837.4	1585.0	1383.7	1265.0	1197.4	1155.3	1092.2	1060.7	1036.6	1039.6	1044.1
50°	1566.9	1337.1	1182.3	1063.7	1030.6	997.6	955.5	928.4	916.4	920.9	917.9
52.5°	1334.1	1147.8	1017.1	925.4	910.4	878.9	844.3	821.8	817.3	818.8	823.3
55°	1129.8	984.0	880.4	814.3	797.7	775.2	754.2	739.2	727.1	731.6	730.1
57.5°	975.0	847.3	767.7	713.6	701.6	688.1	668.5	661.0	656.5	647.5	655.0
60°	838.3	734.6	665.5	632.5	622.0	613.0	591.9	582.9	579.9	575.4	587.4
62.5°	709.1	635.5	582.9	552.9	542.3	533.3	522.8	515.3	516.8	510.8	516.8
65°	606.9	546.9	509.3	482.3	468.7	462.7	461.2	449.2	447.7	449.2	450.7
67.5°	512.3	461.2	432.7	416.1	405.6	399.6	395.1	387.6	393.6	389.1	392.1
70°	426.7	392.1	362.1	345.5	341.0	342.5	335.0	332.0	333.5	330.5	333.5
72.5°	344.0	315.5	303.5	291.5	285.4	283.9	279.4	274.9	279.4	277.9	277.9
75°	274.9	253.9	240.4	232.9	232.9	229.9	222.3	222.3	222.3	220.8	222.3
77.5°	211.8	193.8	187.8	180.3	180.3	175.8	174.3	174.3	171.3	175.8	172.8
80°	157.7	144.2	135.2	130.7	130.7	129.2	126.2	124.7	126.2	124.7	124.7
82.5°	102.2	96.1	91.6	87.1	85.6	87.1	85.6	82.6	84.1	82.6	85.6
85°	58.6	52.6	52.6	49.6	51.1	48.1	49.6	46.6	45.1	49.6	46.6
87.5°	25.5	24.0	24.0	21.0	21.0	21.0	19.5	21.0	19.5	18.0	19.5
90°	12.5	13.3	14.2	15.0	15.4	15.6	16.1	16.6	17.1	17.6	17.1
92.5°	33.5	34.6	35.8	36.9	37.5	37.7	38.0	38.3	38.6	38.9	38.6
95°	57.7	58.8	60.0	61.1	61.7	61.9	62.2	62.5	62.9	63.2	62.9
97.5°	85.4	86.4	87.4	88.4	88.9	89.0	89.1	89.3	89.4	89.6	89.4
100°	113.9	115.3	116.8	118.3	119.0	119.2	119.5	119.8	120.1	120.4	120.1
102.5°	143.3	145.0	146.6	148.3	149.1	149.3	149.8	150.3	150.8	151.3	150.8
105°	176.5	177.5	178.4	179.4	179.9	180.1	180.6	181.1	181.6	182.1	181.6
107.5°	211.3	211.8	212.3	212.8	213.0	213.0	213.0	213.0	213.0	213.0	213.0
110°	247.2	247.7	248.2	248.7	248.9	248.8	248.7	248.5	248.4	248.2	248.4

TEST NUMBER: P1027742

CATALOG NUMBER: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	50°	55°	60°	65°	67.5°	70°	75°	80°	85°	90°	95°
112.5°	283.6	283.8	283.9	284.1	284.2	284.0	283.7	283.4	283.0	282.7	283.0
115°	320.7	320.6	320.4	320.3	320.2	320.1	319.9	319.8	319.6	319.4	319.6
117.5°	357.1	357.2	357.4	357.5	357.6	357.3	356.6	356.0	355.3	354.7	355.3
120°	394.3	394.3	394.3	394.3	394.3	394.0	393.3	392.7	392.0	391.4	392.0
122.5°	430.8	430.7	430.5	430.4	430.3	430.1	429.6	429.1	428.6	428.1	428.6
125°	466.7	466.4	466.1	465.8	465.6	465.5	465.3	465.2	465.0	464.8	465.0
127.5°	502.1	501.9	501.8	501.6	501.5	501.3	501.0	500.7	500.4	500.1	500.4
130°	537.3	537.2	537.0	536.9	536.8	536.6	536.3	536.0	535.6	535.3	535.6
132.5°	571.1	571.0	570.8	570.7	570.6	570.4	569.9	569.4	568.9	568.4	568.9
135°	605.8	605.8	605.8	605.8	605.8	605.5	604.8	604.2	603.5	602.9	603.5
137.5°	639.8	639.9	640.1	640.2	640.3	639.9	639.1	638.3	637.5	636.7	637.5
140°	671.5	671.8	672.1	672.4	672.6	672.2	671.4	670.6	669.8	669.0	669.8
142.5°	702.9	703.1	703.2	703.4	703.5	703.1	702.3	701.4	700.6	699.8	700.6
145°	732.9	732.9	732.9	732.9	732.9	732.7	732.2	731.7	731.2	730.7	731.2
147.5°	760.5	761.0	761.5	762.0	762.2	761.6	760.3	759.0	757.7	756.4	757.7
150°	787.2	787.2	787.2	787.2	787.2	787.0	786.7	786.4	786.0	785.7	786.0
152.5°	811.2	811.7	812.2	812.7	812.9	812.6	811.9	811.3	810.6	810.0	810.6
155°	834.1	834.8	835.4	836.1	836.4	836.0	835.2	834.3	833.5	832.7	833.5
157.5°	854.7	855.3	856.0	856.7	857.0	856.4	855.3	854.1	853.0	851.8	853.0
160°	873.0	873.7	874.3	875.0	875.3	874.9	874.1	873.2	872.4	871.6	872.4
162.5°	890.1	890.9	891.7	892.5	892.9	892.4	891.4	890.5	889.5	888.5	889.5
165°	905.3	906.0	906.6	907.3	907.6	907.1	906.1	905.2	904.2	903.2	904.2
167.5°	916.7	917.7	918.6	919.6	920.1	919.6	918.6	917.7	916.7	915.7	916.7
170°	927.0	928.0	928.9	929.9	930.4	929.8	928.7	927.5	926.4	925.2	926.4
172.5°	934.3	935.3	936.2	937.2	937.7	937.2	936.2	935.3	934.3	933.3	934.3
175°	939.5	940.5	941.4	942.4	942.9	942.3	941.2	940.0	938.9	937.7	938.9
177.5°	942.4	943.4	944.3	945.3	945.8	945.2	944.1	943.0	941.8	940.7	941.8
180°	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6

TEST NUMBER: P1027742

CATALOG NUMBER: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	100°	105°	110°	112.5°	115°	120°	125°	130°	135°	140°	145°
0°	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8
2.5°	1894.5	1883.9	1886.9	1883.9	1876.4	1871.9	1859.9	1844.9	1838.9	1831.4	1826.8
5°	2046.2	2038.7	2037.2	2025.2	2022.2	2004.1	1974.1	1959.1	1941.0	1923.0	1905.0
7.5°	2211.4	2202.4	2172.4	2167.9	2170.9	2148.3	2109.3	2079.2	2041.7	2016.1	1981.6
10°	2348.2	2330.1	2304.6	2306.1	2295.6	2265.5	2226.5	2194.9	2140.8	2107.8	2058.2
12.5°	2430.8	2415.8	2412.8	2397.7	2388.7	2349.7	2303.1	2262.5	2222.0	2176.9	2139.3
15°	2531.4	2511.9	2498.4	2477.4	2471.4	2430.8	2379.7	2333.1	2286.6	2244.5	2164.9
17.5°	2642.6	2621.6	2570.5	2566.0	2529.9	2490.9	2441.3	2372.2	2322.6	2262.5	2203.9
20°	2768.8	2738.8	2672.7	2656.1	2627.6	2563.0	2495.4	2418.8	2339.1	2277.5	2208.4
22.5°	2910.0	2857.5	2809.4	2756.8	2735.8	2656.1	2563.0	2469.8	2373.7	2289.6	2206.9
25°	3093.3	3024.2	2956.6	2904.0	2868.0	2764.3	2639.6	2516.4	2405.2	2295.6	2187.4
27.5°	3237.5	3177.5	3103.8	3034.7	2988.2	2865.0	2722.2	2563.0	2424.8	2291.1	2175.4
30°	3248.1	3230.0	3185.0	3147.4	3096.3	2964.1	2806.4	2626.1	2454.8	2292.6	2151.4
32.5°	3051.3	3087.3	3106.8	3112.9	3102.3	3025.7	2881.5	2683.2	2481.9	2279.1	2130.3
35°	2627.6	2723.7	2842.4	2887.5	2931.1	2971.6	2896.5	2723.7	2490.9	2276.0	2097.3
37.5°	2163.4	2250.5	2447.3	2537.5	2588.5	2749.3	2810.9	2717.7	2508.9	2279.1	2065.7
40°	1745.7	1883.9	2025.2	2146.8	2226.5	2406.8	2597.5	2618.6	2483.4	2250.5	2025.2
42.5°	1469.3	1550.4	1657.1	1769.8	1840.4	2053.7	2312.1	2463.8	2403.7	2203.9	1975.6
45°	1251.5	1311.5	1412.2	1449.8	1539.9	1744.2	2017.6	2237.0	2267.0	2130.3	1918.5
47.5°	1074.2	1125.3	1189.9	1236.4	1308.5	1461.8	1693.1	1935.0	2079.2	2029.7	1838.9
50°	946.5	988.5	1042.6	1069.7	1116.2	1254.5	1428.7	1669.1	1862.9	1879.4	1735.2
52.5°	839.8	863.8	905.9	936.0	973.5	1057.6	1215.4	1413.7	1631.5	1721.7	1607.5
55°	746.7	766.2	803.8	823.3	842.8	914.9	1038.1	1218.4	1422.7	1541.4	1476.8
57.5°	662.5	679.1	710.6	728.6	739.2	808.3	902.9	1044.1	1227.4	1371.6	1335.6
60°	593.4	608.4	626.5	640.0	652.0	709.1	775.2	889.4	1053.1	1192.9	1183.8
62.5°	519.8	533.3	552.9	566.4	576.9	613.0	668.5	755.7	895.4	1024.6	1050.1
65°	455.2	465.7	479.2	485.3	498.8	525.8	570.9	649.0	763.2	878.9	896.9
67.5°	396.6	399.6	408.6	422.2	425.2	449.2	489.8	548.4	637.0	731.6	760.2
70°	333.5	338.0	345.5	356.1	362.1	377.1	411.6	450.7	527.3	610.0	631.0
72.5°	277.9	283.9	286.9	293.0	296.0	320.0	335.0	374.1	426.7	495.8	518.3
75°	225.4	231.4	232.9	235.9	238.9	249.4	270.4	294.5	338.0	383.1	413.1
77.5°	178.8	177.3	180.3	184.8	183.3	192.3	205.8	226.9	255.4	293.0	312.5
80°	126.2	126.2	130.7	135.2	133.7	142.7	147.2	162.3	186.3	210.3	217.8
82.5°	84.1	84.1	88.6	88.6	91.6	93.1	99.2	106.7	126.2	138.2	142.7
85°	48.1	48.1	49.6	49.6	49.6	52.6	57.1	60.1	66.1	73.6	76.6
87.5°	19.5	21.0	21.0	21.0	21.0	24.0	24.0	27.0	28.5	31.5	31.5
90°	16.6	16.1	15.6	15.4	15.0	14.2	13.3	12.5	11.7	10.6	9.4
92.5°	38.3	38.0	37.7	37.5	36.9	35.8	34.6	33.5	32.3	30.8	29.4
95°	62.5	62.2	61.9	61.7	61.1	60.0	58.8	57.7	56.5	54.9	53.3
97.5°	89.3	89.1	89.0	88.9	88.4	87.4	86.4	85.4	84.4	82.1	79.9
100°	119.8	119.5	119.2	119.0	118.3	116.8	115.3	113.9	112.4	110.3	108.1
102.5°	150.3	149.8	149.3	149.1	148.3	146.6	145.0	143.3	141.7	140.9	140.1
105°	181.1	180.6	180.1	179.9	179.4	178.4	177.5	176.5	175.5	174.5	173.5
107.5°	213.0	213.0	213.0	213.0	212.8	212.3	211.8	211.3	210.8	210.0	209.2
110°	248.5	248.7	248.8	248.9	248.7	248.2	247.7	247.2	246.7	246.2	245.7

TEST NUMBER: P1027742

CATALOG NUMBER: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	100°	105°	110°	112.5°	115°	120°	125°	130°	135°	140°	145°
112.5°	283.4	283.7	284.0	284.2	284.1	283.9	283.8	283.6	283.4	282.8	282.1
115°	319.8	319.9	320.1	320.2	320.3	320.4	320.6	320.7	320.9	320.6	320.2
117.5°	356.0	356.6	357.3	357.6	357.5	357.4	357.2	357.1	356.9	356.6	356.2
120°	392.7	393.3	394.0	394.3	394.3	394.3	394.3	394.3	394.3	394.1	394.0
122.5°	429.1	429.6	430.1	430.3	430.4	430.5	430.7	430.8	431.0	430.5	430.0
125°	465.2	465.3	465.5	465.6	465.8	466.1	466.4	466.7	467.0	466.8	466.7
127.5°	500.7	501.0	501.3	501.5	501.6	501.8	501.9	502.1	502.3	502.1	501.9
130°	536.0	536.3	536.6	536.8	536.9	537.0	537.2	537.3	537.5	537.2	536.9
132.5°	569.4	569.9	570.4	570.6	570.7	570.8	571.0	571.1	571.3	571.5	571.6
135°	604.2	604.8	605.5	605.8	605.8	605.8	605.8	605.8	605.8	605.6	605.5
137.5°	638.3	639.1	639.9	640.3	640.2	640.1	639.9	639.8	639.6	639.3	638.9
140°	670.6	671.4	672.2	672.6	672.4	672.1	671.8	671.5	671.2	670.7	670.2
142.5°	701.4	702.3	703.1	703.5	703.4	703.2	703.1	702.9	702.7	702.1	701.4
145°	731.7	732.2	732.7	732.9	732.9	732.9	732.9	732.9	732.9	732.4	731.9
147.5°	759.0	760.3	761.6	762.2	762.0	761.5	761.0	760.5	760.0	759.7	759.4
150°	786.4	786.7	787.0	787.2	787.2	787.2	787.2	787.2	787.2	786.6	785.9
152.5°	811.3	811.9	812.6	812.9	812.7	812.2	811.7	811.2	810.7	810.5	810.4
155°	834.3	835.2	836.0	836.4	836.1	835.4	834.8	834.1	833.5	833.3	833.1
157.5°	854.1	855.3	856.4	857.0	856.7	856.0	855.3	854.7	854.0	853.8	853.7
160°	873.2	874.1	874.9	875.3	875.0	874.3	873.7	873.0	872.4	872.2	872.0
162.5°	890.5	891.4	892.4	892.9	892.5	891.7	890.9	890.1	889.3	889.3	889.3
165°	905.2	906.1	907.1	907.6	907.3	906.6	906.0	905.3	904.7	904.5	904.4
167.5°	917.7	918.6	919.6	920.1	919.6	918.6	917.7	916.7	915.7	915.7	915.7
170°	927.5	928.7	929.8	930.4	929.9	928.9	928.0	927.0	926.0	926.0	926.0
172.5°	935.3	936.2	937.2	937.7	937.2	936.2	935.3	934.3	933.3	933.3	933.3
175°	940.0	941.2	942.3	942.9	942.4	941.4	940.5	939.5	938.5	938.5	938.5
177.5°	943.0	944.1	945.2	945.8	945.3	944.3	943.4	942.4	941.4	941.6	941.7
180°	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6

TEST NUMBER: P1027742

CATALOG NUMBER: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	150°	155°	157.5°	160°	165°	170°	175°	180°	185°	190°	195°
0°	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8
2.5°	1820.8	1813.3	1804.3	1804.3	1793.8	1789.3	1780.3	1777.3	1769.8	1757.7	1748.7
5°	1885.4	1865.9	1853.9	1843.4	1820.8	1804.3	1787.8	1769.8	1751.7	1730.7	1706.7
7.5°	1948.5	1912.5	1896.0	1877.9	1844.9	1810.3	1777.3	1753.2	1729.2	1696.1	1666.1
10°	2014.6	1969.6	1939.5	1915.5	1864.4	1820.8	1772.8	1738.2	1700.6	1658.6	1619.5
12.5°	2070.2	2011.6	1986.1	1941.0	1882.4	1829.9	1769.8	1717.2	1667.6	1618.0	1569.9
15°	2116.8	2061.2	1998.1	1980.1	1899.0	1823.8	1756.2	1688.6	1627.0	1577.5	1521.9
17.5°	2131.8	2061.2	2029.7	1986.1	1889.9	1811.8	1726.2	1652.6	1594.0	1520.4	1476.8
20°	2136.3	2068.7	2025.2	1984.6	1899.0	1795.3	1711.2	1621.0	1550.4	1476.8	1407.7
22.5°	2124.3	2044.7	2002.6	1963.6	1867.4	1778.8	1681.1	1582.0	1499.3	1431.7	1362.6
25°	2101.8	2008.6	1968.1	1926.0	1834.4	1736.7	1630.0	1535.4	1458.8	1377.6	1310.0
27.5°	2071.7	1965.1	1918.5	1874.9	1784.8	1693.1	1592.5	1494.8	1409.2	1323.6	1260.5
30°	2034.2	1911.0	1868.9	1811.8	1724.7	1637.6	1545.9	1448.3	1352.1	1271.0	1201.9
32.5°	1986.1	1856.9	1801.3	1747.2	1652.6	1573.0	1485.8	1394.2	1301.0	1221.4	1149.3
35°	1942.5	1795.3	1733.7	1679.6	1574.5	1490.3	1418.2	1332.6	1249.9	1167.3	1102.7
37.5°	1883.9	1733.7	1660.1	1604.5	1497.8	1412.2	1344.6	1278.5	1191.4	1111.7	1051.6
40°	1822.3	1657.1	1588.0	1532.4	1421.2	1328.1	1263.5	1204.9	1134.3	1060.7	997.6
42.5°	1766.8	1583.5	1509.9	1442.2	1329.6	1246.9	1180.8	1135.8	1071.2	1005.1	948.0
45°	1696.1	1505.3	1425.7	1355.1	1246.9	1156.8	1093.7	1057.6	1009.6	945.0	895.4
47.5°	1624.0	1421.2	1338.6	1269.5	1152.3	1072.7	1011.1	976.5	943.5	892.4	842.8
50°	1529.4	1332.6	1257.5	1177.8	1062.2	981.0	929.9	895.4	869.9	833.8	791.7
52.5°	1425.7	1240.9	1159.8	1090.7	976.5	902.9	844.3	824.8	799.2	772.2	736.1
55°	1316.1	1141.8	1063.7	996.1	890.9	815.8	767.7	746.7	727.1	706.1	682.1
57.5°	1206.4	1038.1	964.5	904.4	806.8	734.6	695.6	667.0	653.5	641.5	622.0
60°	1069.7	926.9	869.9	815.8	719.6	653.5	616.0	594.9	582.9	576.9	567.9
62.5°	949.5	832.3	769.2	716.6	640.0	581.4	545.3	528.8	518.3	515.3	504.8
65°	821.8	721.1	671.5	626.5	560.4	507.8	477.7	458.2	450.7	449.2	449.2
67.5°	701.6	620.5	570.9	539.3	482.3	435.7	407.1	399.6	395.1	389.1	387.6
70°	588.9	524.3	480.7	453.7	402.6	368.1	345.5	333.5	333.5	329.0	326.0
72.5°	489.8	425.2	396.6	374.1	332.0	302.0	285.4	282.4	271.9	270.4	270.4
75°	383.1	335.0	315.5	296.0	264.4	243.4	229.9	222.3	216.3	216.3	217.8
77.5°	288.4	255.4	237.4	222.3	199.8	186.3	175.8	172.8	166.8	166.8	166.8
80°	204.3	186.3	172.8	160.8	144.2	132.2	126.2	120.2	120.2	118.7	120.2
82.5°	132.2	117.2	109.7	108.2	93.1	88.6	81.1	82.6	78.1	76.6	79.6
85°	76.6	69.1	60.1	57.1	51.1	45.1	42.1	43.6	42.1	40.6	42.1
87.5°	30.0	25.5	24.0	24.0	19.5	18.0	16.5	18.0	15.0	15.0	16.5
90°	8.3	7.2	6.6	5.9	4.6	3.3	2.0	0.7	2.0	3.3	4.6
92.5°	27.9	26.4	25.7	25.3	24.5	23.6	22.8	22.0	22.8	23.6	24.5
95°	51.6	50.0	49.2	49.0	48.7	48.4	48.0	47.7	48.0	48.4	48.7
97.5°	77.6	75.3	74.2	74.1	73.9	73.8	73.6	73.4	73.6	73.8	73.9
100°	106.0	103.9	102.8	102.8	102.8	102.8	102.8	102.8	102.8	102.8	102.8
102.5°	139.3	138.5	138.1	137.7	136.9	136.0	135.2	134.4	135.2	136.0	136.9
105°	172.6	171.6	171.1	170.7	169.9	169.0	168.2	167.4	168.2	169.0	169.9
107.5°	208.3	207.5	207.1	206.7	205.9	205.0	204.2	203.4	204.2	205.0	205.9
110°	245.2	244.7	244.5	244.1	243.3	242.5	241.7	240.9	241.7	242.5	243.3

TEST NUMBER: P1027742

CATALOG NUMBER: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	150°	155°	157.5°	160°	165°	170°	175°	180°	185°	190°	195°
112.5°	281.5	280.8	280.5	280.3	280.0	279.7	279.3	279.0	279.3	279.7	280.0
115°	319.9	319.6	319.4	319.1	318.4	317.8	317.1	316.5	317.1	317.8	318.4
117.5°	355.9	355.6	355.4	355.3	355.2	355.0	354.9	354.7	354.9	355.0	355.2
120°	393.8	393.7	393.6	393.2	392.4	391.5	390.7	389.9	390.7	391.5	392.4
122.5°	429.5	429.0	428.8	428.7	428.6	428.4	428.3	428.1	428.3	428.4	428.6
125°	466.5	466.4	466.3	465.8	464.8	463.9	462.9	461.9	462.9	463.9	464.8
127.5°	501.8	501.6	501.5	501.3	500.8	500.3	499.8	499.3	499.8	500.3	500.8
130°	536.6	536.3	536.1	535.7	534.9	534.0	533.2	532.4	533.2	534.0	534.9
132.5°	571.8	571.9	572.0	571.3	569.8	568.3	566.9	565.4	566.9	568.3	569.8
135°	605.3	605.2	605.1	604.6	603.6	602.7	601.7	600.7	601.7	602.7	603.6
137.5°	638.6	638.3	638.1	637.6	636.6	635.7	634.7	633.7	634.7	635.7	636.6
140°	669.7	669.2	669.0	668.6	667.8	666.9	666.1	665.3	666.1	666.9	667.8
142.5°	700.8	700.1	699.8	699.5	698.8	698.2	697.5	696.9	697.5	698.2	698.8
145°	731.4	730.9	730.7	730.4	729.7	729.0	728.4	727.7	728.4	729.0	729.7
147.5°	759.1	758.8	758.6	758.4	757.9	757.4	756.9	756.4	756.9	757.4	757.9
150°	785.3	784.6	784.3	784.4	784.5	784.7	784.8	785.0	784.8	784.7	784.5
152.5°	810.2	810.1	810.0	809.8	809.5	809.2	808.8	808.5	808.8	809.2	809.5
155°	833.0	832.8	832.7	832.7	832.7	832.7	832.7	832.7	832.7	832.7	832.7
157.5°	853.5	853.4	853.3	853.5	853.8	854.1	854.5	854.8	854.5	854.1	853.8
160°	871.9	871.7	871.6	871.8	872.3	872.8	873.3	873.8	873.3	872.8	872.3
162.5°	889.3	889.3	889.3	889.5	889.8	890.1	890.4	890.7	890.4	890.1	889.8
165°	904.2	904.1	904.0	904.2	904.5	904.8	905.1	905.4	905.1	904.8	904.5
167.5°	915.7	915.7	915.7	916.0	916.7	917.3	918.0	918.6	918.0	917.3	916.7
170°	926.0	926.0	926.0	926.3	927.0	927.6	928.3	928.9	928.3	927.6	927.0
172.5°	933.3	933.3	933.3	933.6	934.3	935.0	935.6	936.3	935.6	935.0	934.3
175°	938.5	938.5	938.5	938.8	939.5	940.1	940.8	941.4	940.8	940.1	939.5
177.5°	941.9	942.0	942.1	942.4	943.1	943.8	944.4	945.1	944.4	943.8	943.1
180°	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6

TEST NUMBER: P1027742

CATALOG NUMBER: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	200°	202.5°	205°	210°	215°	220°	225°	230°	235°	240°	245°
0°	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8
2.5°	1745.7	1742.7	1735.2	1730.7	1715.7	1697.6	1691.6	1676.6	1682.6	1672.1	1672.1
5°	1699.1	1685.6	1676.6	1663.1	1634.5	1615.0	1594.0	1583.5	1577.5	1569.9	1563.9
7.5°	1639.1	1628.5	1619.5	1594.0	1562.4	1535.4	1509.9	1499.3	1479.8	1466.3	1460.3
10°	1586.5	1571.4	1550.4	1520.4	1487.3	1452.8	1430.2	1407.7	1392.7	1385.2	1368.6
12.5°	1532.4	1514.4	1491.8	1448.3	1412.2	1391.2	1350.6	1329.6	1322.1	1316.1	1296.5
15°	1476.8	1457.3	1430.2	1389.7	1358.1	1308.5	1284.5	1268.0	1249.9	1248.4	1233.4
17.5°	1427.2	1403.2	1380.7	1331.1	1292.0	1248.4	1234.9	1216.9	1200.4	1182.3	1174.8
20°	1364.1	1341.6	1325.1	1271.0	1227.4	1200.4	1177.8	1162.8	1152.3	1134.3	1131.3
22.5°	1307.0	1283.0	1260.5	1219.9	1182.3	1147.8	1120.7	1104.2	1099.7	1092.2	1078.7
25°	1251.5	1227.4	1200.4	1162.8	1123.8	1099.7	1075.7	1065.2	1056.1	1044.1	1033.6
27.5°	1204.9	1182.3	1156.8	1110.2	1077.2	1059.2	1033.6	1021.6	1009.6	1003.6	999.1
30°	1149.3	1123.8	1104.2	1068.2	1032.1	1008.1	990.0	979.5	969.0	963.0	960.0
32.5°	1095.2	1071.2	1057.6	1018.6	990.0	961.5	948.0	940.5	934.5	928.4	922.4
35°	1051.6	1027.6	1006.6	970.5	942.0	922.4	911.9	899.9	895.4	889.4	889.4
37.5°	997.6	979.5	958.5	923.9	898.4	883.4	874.4	859.3	857.8	854.8	850.3
40°	951.0	933.0	913.4	883.4	860.8	842.8	830.8	823.3	818.8	815.8	812.8
42.5°	901.4	881.9	872.9	838.3	818.8	800.7	794.7	787.2	785.7	779.7	772.2
45°	853.3	836.8	818.8	793.2	776.7	761.7	752.7	746.7	739.2	737.6	733.1
47.5°	811.3	791.7	775.2	751.2	733.1	721.1	713.6	706.1	700.1	695.6	691.1
50°	757.2	742.2	728.6	703.1	688.1	676.1	665.5	659.5	653.5	653.5	653.5
52.5°	704.6	691.1	679.1	661.0	643.0	632.5	620.5	616.0	613.0	608.4	613.0
55°	653.5	640.0	628.0	614.5	593.4	584.4	572.4	567.9	569.4	569.4	573.9
57.5°	599.4	588.9	581.4	564.9	545.3	536.3	528.8	524.3	524.3	530.3	531.8
60°	546.9	536.3	522.8	507.8	495.8	485.3	480.7	482.3	482.3	485.3	492.8
62.5°	488.3	482.3	474.7	453.7	446.2	438.7	432.7	437.2	435.7	443.2	453.7
65°	434.2	428.2	417.7	407.1	398.1	390.6	389.1	390.6	393.6	401.1	413.1
67.5°	374.1	374.1	365.1	356.1	348.5	341.0	342.5	344.0	347.0	356.1	374.1
70°	324.5	318.5	309.5	303.5	297.5	294.5	291.5	297.5	306.5	312.5	326.0
72.5°	270.4	265.9	258.4	252.4	250.9	247.9	246.4	249.4	258.4	268.9	283.9
75°	213.3	214.8	210.3	205.8	205.8	201.3	204.3	204.3	213.3	223.8	235.9
77.5°	165.3	163.8	162.3	159.2	157.7	157.7	157.7	160.8	169.8	175.8	187.8
80°	117.2	118.7	114.2	115.7	114.2	115.7	115.7	121.7	126.2	133.7	142.7
82.5°	78.1	78.1	75.1	76.6	76.6	76.6	78.1	81.1	87.1	93.1	99.2
85°	43.6	45.1	42.1	45.1	45.1	45.1	46.6	48.1	52.6	54.1	60.1
87.5°	16.5	19.5	19.5	16.5	18.0	19.5	21.0	19.5	22.5	25.5	27.0
90°	5.9	6.6	7.2	8.3	9.4	10.6	11.7	12.5	13.3	14.2	15.0
92.5°	25.3	25.7	26.4	27.9	29.4	30.8	32.3	33.5	34.6	35.8	36.9
95°	49.0	49.2	50.0	51.6	53.3	54.9	56.5	57.7	58.8	60.0	61.1
97.5°	74.1	74.2	75.3	77.6	79.9	82.1	84.4	85.4	86.4	87.4	88.4
100°	102.8	102.8	103.9	106.0	108.1	110.3	112.4	113.9	115.3	116.8	118.3
102.5°	137.7	138.1	138.5	139.3	140.1	140.9	141.7	143.3	145.0	146.6	148.3
105°	170.7	171.1	171.6	172.6	173.5	174.5	175.5	176.5	177.5	178.4	179.4
107.5°	206.7	207.1	207.5	208.3	209.2	210.0	210.8	211.3	211.8	212.3	212.8
110°	244.1	244.5	244.7	245.2	245.7	246.2	246.7	247.2	247.7	248.2	248.7

TEST NUMBER: P1027742

CATALOG NUMBER: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	200°	202.5°	205°	210°	215°	220°	225°	230°	235°	240°	245°
112.5°	280.3	280.5	280.8	281.5	282.1	282.8	283.4	283.6	283.8	283.9	284.1
115°	319.1	319.4	319.6	319.9	320.2	320.6	320.9	320.7	320.6	320.4	320.3
117.5°	355.3	355.4	355.6	355.9	356.2	356.6	356.9	357.1	357.2	357.4	357.5
120°	393.2	393.6	393.7	393.8	394.0	394.1	394.3	394.3	394.3	394.3	394.3
122.5°	428.7	428.8	429.0	429.5	430.0	430.5	431.0	430.8	430.7	430.5	430.4
125°	465.8	466.3	466.4	466.5	466.7	466.8	467.0	466.7	466.4	466.1	465.8
127.5°	501.3	501.5	501.6	501.8	501.9	502.1	502.3	502.1	501.9	501.8	501.6
130°	535.7	536.1	536.3	536.6	536.9	537.2	537.5	537.3	537.2	537.0	536.9
132.5°	571.3	572.0	571.9	571.8	571.6	571.5	571.3	571.1	571.0	570.8	570.7
135°	604.6	605.1	605.2	605.3	605.5	605.6	605.8	605.8	605.8	605.8	605.8
137.5°	637.6	638.1	638.3	638.6	638.9	639.3	639.6	639.8	639.9	640.1	640.2
140°	668.6	669.0	669.2	669.7	670.2	670.7	671.2	671.5	671.8	672.1	672.4
142.5°	699.5	699.8	700.1	700.8	701.4	702.1	702.7	702.9	703.1	703.2	703.4
145°	730.4	730.7	730.9	731.4	731.9	732.4	732.9	732.9	732.9	732.9	732.9
147.5°	758.4	758.6	758.8	759.1	759.4	759.7	760.0	760.5	761.0	761.5	762.0
150°	784.4	784.3	784.6	785.3	785.9	786.6	787.2	787.2	787.2	787.2	787.2
152.5°	809.8	810.0	810.1	810.2	810.4	810.5	810.7	811.2	811.7	812.2	812.7
155°	832.7	832.7	832.8	833.0	833.1	833.3	833.5	834.1	834.8	835.4	836.1
157.5°	853.5	853.3	853.4	853.5	853.7	853.8	854.0	854.7	855.3	856.0	856.7
160°	871.8	871.6	871.7	871.9	872.0	872.2	872.4	873.0	873.7	874.3	875.0
162.5°	889.5	889.3	889.3	889.3	889.3	889.3	889.3	890.1	890.9	891.7	892.5
165°	904.2	904.0	904.1	904.2	904.4	904.5	904.7	905.3	906.0	906.6	907.3
167.5°	916.0	915.7	915.7	915.7	915.7	915.7	915.7	916.7	917.7	918.6	919.6
170°	926.3	926.0	926.0	926.0	926.0	926.0	926.0	927.0	928.0	928.9	929.9
172.5°	933.6	933.3	933.3	933.3	933.3	933.3	933.3	934.3	935.3	936.2	937.2
175°	938.8	938.5	938.5	938.5	938.5	938.5	938.5	939.5	940.5	941.4	942.4
177.5°	942.4	942.1	942.0	941.9	941.7	941.6	941.4	942.4	943.4	944.3	945.3
180°	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6

TEST NUMBER: P1027742

CATALOG NUMBER: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	247.5°	250°	255°	260°	265°	270°	275°	280°	285°	290°	292.5°
0°	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8
2.5°	1678.1	1667.6	1666.1	1669.1	1663.1	1672.1	1669.1	1672.1	1664.6	1672.1	1667.6
5°	1562.4	1559.4	1553.4	1545.9	1547.4	1548.9	1556.4	1548.9	1554.9	1556.4	1563.9
7.5°	1454.3	1448.3	1452.8	1449.8	1436.2	1433.2	1436.2	1440.7	1449.8	1455.8	1460.3
10°	1367.1	1364.1	1358.1	1353.6	1346.1	1341.6	1347.6	1341.6	1353.6	1364.1	1364.1
12.5°	1301.0	1289.0	1281.5	1280.0	1263.5	1266.5	1272.5	1277.0	1290.5	1296.5	1296.5
15°	1231.9	1222.9	1219.9	1213.9	1207.9	1213.9	1210.9	1215.4	1221.4	1227.4	1230.4
17.5°	1171.8	1170.3	1171.8	1156.8	1161.3	1153.8	1155.3	1162.8	1158.3	1162.8	1171.8
20°	1117.7	1120.7	1116.2	1110.2	1110.2	1101.2	1111.7	1108.7	1110.2	1119.2	1132.8
22.5°	1077.2	1075.7	1071.2	1066.7	1060.7	1062.2	1063.7	1060.7	1072.7	1080.2	1081.7
25°	1033.6	1030.6	1029.1	1024.6	1018.6	1024.6	1023.1	1024.6	1027.6	1039.6	1030.6
27.5°	993.0	987.0	990.0	985.5	984.0	985.5	985.5	987.0	990.0	991.5	993.0
30°	958.5	952.5	951.0	948.0	946.5	948.0	951.0	948.0	960.0	958.5	958.5
32.5°	920.9	916.4	913.4	913.4	911.9	910.4	911.9	913.4	922.4	916.4	922.4
35°	884.9	881.9	881.9	878.9	877.4	877.4	877.4	883.4	880.4	884.9	884.9
37.5°	850.3	850.3	848.8	845.8	844.3	845.8	844.3	847.3	845.8	847.3	848.8
40°	814.3	811.3	809.8	809.8	805.3	800.7	805.3	805.3	806.8	811.3	812.8
42.5°	770.7	772.2	772.2	766.2	766.2	766.2	767.7	769.2	769.2	772.2	772.2
45°	733.1	730.1	730.1	730.1	727.1	728.6	731.6	731.6	731.6	731.6	728.6
47.5°	691.1	691.1	692.6	692.6	697.1	695.6	695.6	694.1	691.1	691.1	692.6
50°	652.0	656.5	658.0	658.0	659.5	661.0	661.0	658.0	656.5	652.0	652.0
52.5°	614.5	617.5	620.5	625.0	628.0	626.5	626.5	623.5	617.5	616.0	614.5
55°	573.9	578.4	584.4	588.9	593.4	594.9	594.9	588.9	582.9	575.4	575.4
57.5°	536.3	540.8	551.4	555.9	561.9	561.9	558.9	554.4	545.3	539.3	534.8
60°	498.8	506.3	513.8	522.8	530.3	531.8	527.3	521.3	510.8	503.3	497.3
62.5°	458.2	465.7	480.7	489.8	495.8	495.8	495.8	488.3	474.7	464.2	455.2
65°	419.2	426.7	440.2	452.2	456.7	461.2	456.7	449.2	438.7	426.7	417.7
67.5°	378.6	387.6	401.1	410.1	416.1	420.7	417.7	411.6	398.1	381.6	375.6
70°	333.5	338.0	357.6	366.6	375.6	378.6	375.6	366.6	353.1	335.0	329.0
72.5°	291.5	296.0	314.0	321.5	329.0	332.0	327.5	321.5	309.5	293.0	285.4
75°	243.4	250.9	259.9	271.9	280.9	283.9	279.4	274.9	259.9	249.4	243.4
77.5°	192.3	199.8	211.8	222.3	231.4	229.9	223.8	225.4	208.8	196.8	192.3
80°	145.7	151.7	160.8	169.8	174.3	174.3	172.8	166.8	160.8	151.7	144.2
82.5°	100.7	108.2	115.7	121.7	121.7	123.2	120.2	118.7	112.7	105.2	103.7
85°	60.1	61.6	67.6	67.6	73.6	70.6	69.1	73.6	67.6	63.1	61.6
87.5°	27.0	25.5	27.0	27.0	25.5	28.5	28.5	27.0	28.5	27.0	27.0
90°	15.4	15.6	16.1	16.6	17.1	17.6	17.1	16.6	16.1	15.6	15.4
92.5°	37.5	37.7	38.0	38.3	38.6	38.9	38.6	38.3	38.0	37.7	37.5
95°	61.7	61.9	62.2	62.5	62.9	63.2	62.9	62.5	62.2	61.9	61.7
97.5°	88.9	89.0	89.1	89.3	89.4	89.6	89.4	89.3	89.1	89.0	88.9
100°	119.0	119.2	119.5	119.8	120.1	120.4	120.1	119.8	119.5	119.2	119.0
102.5°	149.1	149.3	149.8	150.3	150.8	151.3	150.8	150.3	149.8	149.3	149.1
105°	179.9	180.1	180.6	181.1	181.6	182.1	181.6	181.1	180.6	180.1	179.9
107.5°	213.0	213.0	213.0	213.0	213.0	213.0	213.0	213.0	213.0	213.0	213.0
110°	248.9	248.8	248.7	248.5	248.4	248.2	248.4	248.5	248.7	248.8	248.9

TEST NUMBER: P1027742

CATALOG NUMBER: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	247.5°	250°	255°	260°	265°	270°	275°	280°	285°	290°	292.5°
112.5°	284.2	284.0	283.7	283.4	283.0	282.7	283.0	283.4	283.7	284.0	284.2
115°	320.2	320.1	319.9	319.8	319.6	319.4	319.6	319.8	319.9	320.1	320.2
117.5°	357.6	357.3	356.6	356.0	355.3	354.7	355.3	356.0	356.6	357.3	357.6
120°	394.3	394.0	393.3	392.7	392.0	391.4	392.0	392.7	393.3	394.0	394.3
122.5°	430.3	430.1	429.6	429.1	428.6	428.1	428.6	429.1	429.6	430.1	430.3
125°	465.6	465.5	465.3	465.2	465.0	464.8	465.0	465.2	465.3	465.5	465.6
127.5°	501.5	501.3	501.0	500.7	500.4	500.1	500.4	500.7	501.0	501.3	501.5
130°	536.8	536.6	536.3	536.0	535.6	535.3	535.6	536.0	536.3	536.6	536.8
132.5°	570.6	570.4	569.9	569.4	568.9	568.4	568.9	569.4	569.9	570.4	570.6
135°	605.8	605.5	604.8	604.2	603.5	602.9	603.5	604.2	604.8	605.5	605.8
137.5°	640.3	639.9	639.1	638.3	637.5	636.7	637.5	638.3	639.1	639.9	640.3
140°	672.6	672.2	671.4	670.6	669.8	669.0	669.8	670.6	671.4	672.2	672.6
142.5°	703.5	703.1	702.3	701.4	700.6	699.8	700.6	701.4	702.3	703.1	703.5
145°	732.9	732.7	732.2	731.7	731.2	730.7	731.2	731.7	732.2	732.7	732.9
147.5°	762.2	761.6	760.3	759.0	757.7	756.4	757.7	759.0	760.3	761.6	762.2
150°	787.2	787.0	786.7	786.4	786.0	785.7	786.0	786.4	786.7	787.0	787.2
152.5°	812.9	812.6	811.9	811.3	810.6	810.0	810.6	811.3	811.9	812.6	812.9
155°	836.4	836.0	835.2	834.3	833.5	832.7	833.5	834.3	835.2	836.0	836.4
157.5°	857.0	856.4	855.3	854.1	853.0	851.8	853.0	854.1	855.3	856.4	857.0
160°	875.3	874.9	874.1	873.2	872.4	871.6	872.4	873.2	874.1	874.9	875.3
162.5°	892.9	892.4	891.4	890.5	889.5	888.5	889.5	890.5	891.4	892.4	892.9
165°	907.6	907.1	906.1	905.2	904.2	903.2	904.2	905.2	906.1	907.1	907.6
167.5°	920.1	919.6	918.6	917.7	916.7	915.7	916.7	917.7	918.6	919.6	920.1
170°	930.4	929.8	928.7	927.5	926.4	925.2	926.4	927.5	928.7	929.8	930.4
172.5°	937.7	937.2	936.2	935.3	934.3	933.3	934.3	935.3	936.2	937.2	937.7
175°	942.9	942.3	941.2	940.0	938.9	937.7	938.9	940.0	941.2	942.3	942.9
177.5°	945.8	945.2	944.1	943.0	941.8	940.7	941.8	943.0	944.1	945.2	945.8
180°	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6

TEST NUMBER: P1027742

CATALOG NUMBER: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	295°	300°	305°	310°	315°	320°	325°	330°	335°	337.5°	340°
0°	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8	1769.8
2.5°	1681.1	1672.1	1682.6	1669.1	1672.1	1688.6	1687.1	1702.2	1711.2	1709.7	1717.2
5°	1569.9	1569.9	1574.5	1573.0	1588.0	1601.5	1619.5	1634.5	1651.1	1660.1	1670.6
7.5°	1460.3	1475.3	1478.3	1485.8	1503.8	1526.4	1544.4	1566.9	1591.0	1607.5	1619.5
10°	1370.1	1382.2	1394.2	1400.2	1419.7	1449.8	1475.3	1511.4	1541.4	1559.4	1576.0
12.5°	1290.5	1304.0	1310.0	1337.1	1350.6	1370.1	1406.2	1445.3	1478.3	1497.8	1511.4
15°	1233.4	1240.9	1254.5	1271.0	1284.5	1308.5	1338.6	1382.2	1413.7	1430.2	1476.8
17.5°	1185.3	1194.4	1201.9	1209.4	1230.4	1256.0	1284.5	1322.1	1362.6	1391.2	1415.2
20°	1135.8	1140.3	1149.3	1161.3	1176.3	1200.4	1225.9	1265.0	1301.0	1323.6	1355.1
22.5°	1077.2	1090.7	1099.7	1108.7	1125.3	1152.3	1176.3	1204.9	1249.9	1275.5	1308.5
25°	1042.6	1048.6	1054.6	1065.2	1077.2	1101.2	1128.3	1158.3	1194.4	1221.4	1249.9
27.5°	997.6	1006.6	1014.1	1027.6	1035.1	1054.6	1080.2	1110.2	1153.8	1176.3	1200.4
30°	960.0	969.0	975.0	981.0	991.5	1012.6	1036.6	1060.7	1101.2	1129.8	1153.8
32.5°	922.4	931.5	939.0	943.5	954.0	967.5	987.0	1017.1	1051.6	1071.2	1102.7
35°	889.4	889.4	898.4	904.4	913.4	925.4	943.5	966.0	1002.1	1027.6	1056.1
37.5°	851.8	853.3	860.8	865.3	874.4	886.4	904.4	925.4	955.5	975.0	1003.6
40°	812.8	817.3	820.3	827.8	838.3	842.8	860.8	884.9	914.9	933.0	957.0
42.5°	773.7	776.7	784.2	790.2	799.2	806.8	818.8	841.3	863.8	890.9	910.4
45°	730.1	737.6	742.2	752.7	757.2	764.7	776.7	794.7	821.8	838.3	860.8
47.5°	692.6	695.6	698.6	712.1	721.1	725.6	737.6	748.2	776.7	791.7	812.8
50°	652.0	652.0	656.5	662.5	673.0	682.1	692.6	704.6	727.1	742.2	763.2
52.5°	614.5	610.0	613.0	616.0	626.5	635.5	646.0	662.5	683.6	692.6	710.6
55°	573.9	566.4	570.9	575.4	578.4	590.4	602.4	613.0	629.5	643.0	659.5
57.5°	530.3	528.8	525.8	527.3	534.8	542.3	551.4	564.9	584.4	594.9	603.9
60°	491.3	482.3	479.2	482.3	486.8	491.3	503.3	515.3	531.8	542.3	552.9
62.5°	450.7	441.7	435.7	431.2	435.7	446.2	453.7	462.7	476.2	488.3	497.3
65°	411.6	398.1	392.1	389.1	387.6	395.1	401.1	413.1	425.2	429.7	440.2
67.5°	368.1	356.1	348.5	344.0	344.0	344.0	350.0	362.1	374.1	375.6	386.1
70°	324.5	311.0	303.5	297.5	294.5	297.5	305.0	306.5	317.0	320.0	326.0
72.5°	277.9	265.9	256.9	249.4	250.9	253.9	253.9	256.9	262.9	270.4	270.4
75°	234.4	217.8	213.3	207.3	204.3	204.3	204.3	210.3	214.8	220.8	219.3
77.5°	184.8	175.8	166.8	163.8	159.2	157.7	160.8	160.8	163.8	168.3	169.8
80°	142.7	132.2	126.2	123.2	117.2	115.7	117.2	117.2	121.7	120.2	121.7
82.5°	99.2	91.6	87.1	82.6	79.6	81.1	79.6	79.6	81.1	79.6	79.6
85°	57.1	55.6	52.6	51.1	49.6	46.6	49.6	48.1	46.6	45.1	48.1
87.5°	27.0	25.5	25.5	22.5	22.5	21.0	22.5	22.5	21.0	21.0	21.0
90°	15.0	14.2	13.3	12.5	11.7	10.6	9.4	8.3	7.2	6.6	5.9
92.5°	36.9	35.8	34.6	33.5	32.3	30.8	29.4	27.9	26.4	25.7	25.3
95°	61.1	60.0	58.8	57.7	56.5	54.9	53.3	51.6	50.0	49.2	49.0
97.5°	88.4	87.4	86.4	85.4	84.4	82.1	79.9	77.6	75.3	74.2	74.1
100°	118.3	116.8	115.3	113.9	112.4	110.3	108.1	106.0	103.9	102.8	102.8
102.5°	148.3	146.6	145.0	143.3	141.7	140.9	140.1	139.3	138.5	138.1	137.7
105°	179.4	178.4	177.5	176.5	175.5	174.5	173.5	172.6	171.6	171.1	170.7
107.5°	212.8	212.3	211.8	211.3	210.8	210.0	209.2	208.3	207.5	207.1	206.7
110°	248.7	248.2	247.7	247.2	246.7	246.2	245.7	245.2	244.7	244.5	244.1

TEST NUMBER: P1027742

CATALOG NUMBER: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	295°	300°	305°	310°	315°	320°	325°	330°	335°	337.5°	340°
112.5°	284.1	283.9	283.8	283.6	283.4	282.8	282.1	281.5	280.8	280.5	280.3
115°	320.3	320.4	320.6	320.7	320.9	320.6	320.2	319.9	319.6	319.4	319.1
117.5°	357.5	357.4	357.2	357.1	356.9	356.6	356.2	355.9	355.6	355.4	355.3
120°	394.3	394.3	394.3	394.3	394.3	394.1	394.0	393.8	393.7	393.6	393.2
122.5°	430.4	430.5	430.7	430.8	431.0	430.5	430.0	429.5	429.0	428.8	428.7
125°	465.8	466.1	466.4	466.7	467.0	466.8	466.7	466.5	466.4	466.3	465.8
127.5°	501.6	501.8	501.9	502.1	502.3	502.1	501.9	501.8	501.6	501.5	501.3
130°	536.9	537.0	537.2	537.3	537.5	537.2	536.9	536.6	536.3	536.1	535.7
132.5°	570.7	570.8	571.0	571.1	571.3	571.5	571.6	571.8	571.9	572.0	571.3
135°	605.8	605.8	605.8	605.8	605.8	605.6	605.5	605.3	605.2	605.1	604.6
137.5°	640.2	640.1	639.9	639.8	639.6	639.3	638.9	638.6	638.3	638.1	637.6
140°	672.4	672.1	671.8	671.5	671.2	670.7	670.2	669.7	669.2	669.0	668.6
142.5°	703.4	703.2	703.1	702.9	702.7	702.1	701.4	700.8	700.1	699.8	699.5
145°	732.9	732.9	732.9	732.9	732.9	732.4	731.9	731.4	730.9	730.7	730.4
147.5°	762.0	761.5	761.0	760.5	760.0	759.7	759.4	759.1	758.8	758.6	758.4
150°	787.2	787.2	787.2	787.2	787.2	786.6	785.9	785.3	784.6	784.3	784.4
152.5°	812.7	812.2	811.7	811.2	810.7	810.5	810.4	810.2	810.1	810.0	809.8
155°	836.1	835.4	834.8	834.1	833.5	833.3	833.1	833.0	832.8	832.7	832.7
157.5°	856.7	856.0	855.3	854.7	854.0	853.8	853.7	853.5	853.4	853.3	853.5
160°	875.0	874.3	873.7	873.0	872.4	872.2	872.0	871.9	871.7	871.6	871.8
162.5°	892.5	891.7	890.9	890.1	889.3	889.3	889.3	889.3	889.3	889.3	889.5
165°	907.3	906.6	906.0	905.3	904.7	904.5	904.4	904.2	904.1	904.0	904.2
167.5°	919.6	918.6	917.7	916.7	915.7	915.7	915.7	915.7	915.7	915.7	916.0
170°	929.9	928.9	928.0	927.0	926.0	926.0	926.0	926.0	926.0	926.0	926.3
172.5°	937.2	936.2	935.3	934.3	933.3	933.3	933.3	933.3	933.3	933.3	933.6
175°	942.4	941.4	940.5	939.5	938.5	938.5	938.5	938.5	938.5	938.5	938.8
177.5°	945.3	944.3	943.4	942.4	941.4	941.6	941.7	941.9	942.0	942.1	942.4
180°	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6	943.6

TEST NUMBER: P1027742

CATALOG NUMBER: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	345°	350°	355°	360°
0°	1769.8	1769.8	1769.8	1769.8
2.5°	1727.7	1742.7	1753.2	1772.8
5°	1688.6	1715.7	1741.2	1768.3
7.5°	1649.6	1681.1	1721.7	1756.2
10°	1606.0	1646.6	1694.6	1741.2
12.5°	1562.4	1610.5	1663.1	1724.7
15°	1509.9	1571.4	1633.0	1699.1
17.5°	1463.3	1526.4	1592.5	1675.1
20°	1410.7	1479.8	1551.9	1636.0
22.5°	1364.1	1440.7	1515.9	1604.5
25°	1311.5	1386.7	1469.3	1563.9
27.5°	1268.0	1337.1	1418.2	1520.4
30°	1215.4	1290.5	1371.6	1473.8
32.5°	1165.8	1237.9	1323.6	1424.2
35°	1114.7	1188.4	1265.0	1361.1
37.5°	1066.7	1129.8	1206.4	1298.0
40°	1012.6	1081.7	1150.8	1222.9
42.5°	963.0	1026.1	1090.7	1147.8
45°	907.4	961.5	1023.1	1069.7
47.5°	856.3	904.4	952.5	988.5
50°	805.3	842.8	878.9	910.4
52.5°	745.2	787.2	806.8	826.3
55°	691.1	715.1	733.1	752.7
57.5°	638.5	649.0	658.0	676.1
60°	569.4	581.4	591.9	605.4
62.5°	509.3	515.3	518.3	531.8
65°	452.2	450.7	458.2	465.7
67.5°	390.6	389.1	396.6	399.6
70°	330.5	329.0	330.5	338.0
72.5°	273.4	273.4	274.9	277.9
75°	220.8	220.8	222.3	225.4
77.5°	166.8	169.8	168.3	174.3
80°	121.7	118.7	121.7	124.7
82.5°	79.6	82.6	82.6	79.6
85°	45.1	45.1	45.1	45.1
87.5°	19.5	19.5	21.0	22.5
90°	4.6	3.3	2.0	0.7
92.5°	24.5	23.6	22.8	22.0
95°	48.7	48.4	48.0	47.7
97.5°	73.9	73.8	73.6	73.4
100°	102.8	102.8	102.8	102.8
102.5°	136.9	136.0	135.2	134.4
105°	169.9	169.0	168.2	167.4
107.5°	205.9	205.0	204.2	203.4
110°	243.3	242.5	241.7	240.9

TEST NUMBER: P1027742

CATALOG NUMBER: S125DIP-B1270D850UB50-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	345°	350°	355°	360°
112.5°	280.0	279.7	279.3	279.0
115°	318.4	317.8	317.1	316.5
117.5°	355.2	355.0	354.9	354.7
120°	392.4	391.5	390.7	389.9
122.5°	428.6	428.4	428.3	428.1
125°	464.8	463.9	462.9	461.9
127.5°	500.8	500.3	499.8	499.3
130°	534.9	534.0	533.2	532.4
132.5°	569.8	568.3	566.9	565.4
135°	603.6	602.7	601.7	600.7
137.5°	636.6	635.7	634.7	633.7
140°	667.8	666.9	666.1	665.3
142.5°	698.8	698.2	697.5	696.9
145°	729.7	729.0	728.4	727.7
147.5°	757.9	757.4	756.9	756.4
150°	784.5	784.7	784.8	785.0
152.5°	809.5	809.2	808.8	808.5
155°	832.7	832.7	832.7	832.7
157.5°	853.8	854.1	854.5	854.8
160°	872.3	872.8	873.3	873.8
162.5°	889.8	890.1	890.4	890.7
165°	904.5	904.8	905.1	905.4
167.5°	916.7	917.3	918.0	918.6
170°	927.0	927.6	928.3	928.9
172.5°	934.3	935.0	935.6	936.3
175°	939.5	940.1	940.8	941.4
177.5°	943.1	943.8	944.4	945.1
180°	943.6	943.6	943.6	943.6

(END OF REPORT)