

Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P911759

Luminaire Tested: DFN2DIP-SQ2F0-070D050US850-RLLONL

Issue Date: 11/21/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P911759  
REPORT IS A COMBINATION OF REPORTS P901324 AND P898215  
Test Lab: INNOVATION CENTER  
Issue Date: 11/21/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: NEO-RAY  
Catalog Number: DFN2DIP-SQ2F0-070D050US850-RLLONL  
Description: 2 foot, Square Define Geo, with Direct 1in Regressed Frosted Lens, Indirect Open No Lens  
Light Source: -  
Ballast/Driver: -


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 12088.1 lumens  
Efficiency: N/A  
Efficacy: 114.9 lumens/watt  
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16  
Luminous Opening: Rectangular w/ Sides (W: 2.21' x L: 2.21' x H: 0.1')  
CIE Type: General Diffuse  
  
Input Watts (W): 105.2  
Input Voltage (V):  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: 0.9977  
Total Harmonic Distortion (THDi): 0.049  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P911759

CATALOG NUMBER: DFN2DIP-SQ2F0-070D050US850-RLLONL

### Luminous Intensity Polar Plot



TEST NUMBER: P911759

CATALOG NUMBER: DFN2DIP-SQ2F0-070D050US850-RLLONL

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |    |    |    |    |    |    |    |    |    |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|----|----|----|----|----|----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20 |    |    |    | 20 |    |    |    | 20 |
| RC  | 80  |     |     |     | 70  |     |     |     | 50 |    |    |    | 30 |    |    |    | 10 |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 |
| RCR |     |     |     |     |     |     |     |     |    |    |    |    |    |    |    |    |    |
| 0   | 108 | 108 | 108 | 108 | 100 | 100 | 100 | 100 | 86 | 86 | 86 | 73 | 73 | 73 | 60 | 60 | 60 |
| 1   | 99  | 95  | 91  | 88  | 92  | 89  | 85  | 82  | 76 | 74 | 72 | 65 | 63 | 62 | 54 | 53 | 52 |
| 2   | 91  | 84  | 78  | 73  | 84  | 78  | 73  | 69  | 67 | 63 | 60 | 57 | 55 | 52 | 48 | 46 | 45 |
| 3   | 83  | 74  | 67  | 61  | 77  | 69  | 63  | 58  | 60 | 55 | 51 | 51 | 48 | 45 | 43 | 41 | 39 |
| 4   | 76  | 66  | 58  | 52  | 71  | 62  | 55  | 50  | 54 | 48 | 44 | 46 | 42 | 39 | 39 | 36 | 34 |
| 5   | 70  | 59  | 51  | 45  | 65  | 55  | 48  | 43  | 48 | 43 | 38 | 42 | 37 | 34 | 35 | 32 | 30 |
| 6   | 65  | 53  | 45  | 40  | 60  | 50  | 43  | 38  | 44 | 38 | 34 | 38 | 33 | 30 | 32 | 29 | 26 |
| 7   | 60  | 48  | 40  | 35  | 56  | 45  | 38  | 33  | 40 | 34 | 30 | 35 | 30 | 27 | 30 | 26 | 24 |
| 8   | 56  | 44  | 36  | 31  | 52  | 41  | 34  | 30  | 36 | 31 | 27 | 32 | 27 | 24 | 27 | 24 | 21 |
| 9   | 52  | 40  | 33  | 28  | 49  | 38  | 31  | 27  | 34 | 28 | 24 | 29 | 25 | 22 | 25 | 22 | 19 |
| 10  | 49  | 37  | 30  | 25  | 46  | 35  | 28  | 24  | 31 | 26 | 22 | 27 | 23 | 20 | 24 | 20 | 18 |

**AVERAGE LUMINANCE (cd/sqm):**

|     | 0°   | 45°  | 90°  |
|-----|------|------|------|
| 0°  | 7055 | 7055 | 7055 |
| 5°  | 7054 | 6928 | 6977 |
| 10° | 6972 | 6777 | 6741 |
| 15° | 6864 | 6538 | 6381 |
| 20° | 6725 | 6215 | 5942 |
| 25° | 6582 | 5856 | 5519 |
| 30° | 6395 | 5489 | 4986 |
| 35° | 6210 | 5096 | 4518 |
| 40° | 6022 | 4690 | 3983 |
| 45° | 5806 | 4244 | 3499 |
| 50° | 5580 | 3793 | 3026 |
| 55° | 5343 | 3314 | 2573 |
| 60° | 5068 | 2816 | 2108 |
| 65° | 4752 | 2312 | 1886 |
| 70° | 4368 | 1841 | 1693 |
| 75° | 3883 | 1593 | 1521 |
| 80° | 3189 | 1295 | 1289 |
| 85° | 2076 | 803  | 917  |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 5806 cd/sqm

TEST NUMBER: P911759

CATALOG NUMBER: DFN2DIP-SQ2F0-070D050US850-RLLONL

**ZONAL LUMENS:**

| Zone      | Lumens  | % Fixture |
|-----------|---------|-----------|
| 0°-10°    | 300.7   | 2.5       |
| 10°-20°   | 825.5   | 6.8       |
| 20°-30°   | 1158.9  | 9.6       |
| 30°-40°   | 1263.3  | 10.5      |
| 40°-50°   | 1161.1  | 9.6       |
| 50°-60°   | 911.9   | 7.5       |
| 60°-70°   | 593.5   | 4.9       |
| 70°-80°   | 305.5   | 2.5       |
| 80°-90°   | 81.3    | 0.7       |
| 90°-100°  | 61.7    | 0.5       |
| 100°-110° | 230.0   | 1.9       |
| 110°-120° | 610.1   | 5.0       |
| 120°-130° | 1011.9  | 8.4       |
| 130°-140° | 1074.8  | 8.9       |
| 140°-150° | 999.0   | 8.3       |
| 150°-160° | 803.1   | 6.6       |
| 160°-170° | 517.5   | 4.3       |
| 170°-180° | 178.1   | 1.5       |
| 0°-30°    | 2285.1  | 18.9      |
| 0°-40°    | 3548.4  | 29.4      |
| 0°-60°    | 5621.4  | 46.5      |
| 0°-90°    | 6601.8  | 54.6      |
| 90°-120°  | 901.9   | 7.5       |
| 90°-150°  | 3987.5  | 33.0      |
| 90°-180°  | 5486.0  | 45.4      |
| 0°-180°   | 12088.1 | 100.0     |

**CANDELA DISTRIBUTION:**

|      | 0°   | 22.5° | 45°  | 67.5° | 90°  | Flux |
|------|------|-------|------|-------|------|------|
| 0°   | 3208 | 3208  | 3208 | 3208  | 3208 |      |
| 5°   | 3208 | 3194  | 3156 | 3182  | 3174 | 304  |
| 15°  | 3052 | 3020  | 2921 | 2866  | 2837 | 860  |
| 25°  | 2770 | 2677  | 2485 | 2366  | 2323 | 1274 |
| 35°  | 2387 | 2239  | 1983 | 1800  | 1736 | 1494 |
| 45°  | 1951 | 1756  | 1452 | 1246  | 1176 | 1507 |
| 55°  | 1484 | 1257  | 944  | 770   | 714  | 1326 |
| 65°  | 1002 | 766   | 505  | 407   | 398  | 993  |
| 75°  | 534  | 331   | 232  | 212   | 209  | 565  |
| 85°  | 125  | 64    | 55   | 55    | 55   | 143  |
| 90°  | 1    | 16    | 27   | 34    | 36   | 11   |
| 95°  | 88   | 43    | 53   | 60    | 58   | 104  |
| 105° | 412  | 452   | 83   | 98    | 103  | 440  |
| 115° | 779  | 802   | 836  | 209   | 111  | 767  |
| 125° | 1101 | 1118  | 1144 | 1154  | 1158 | 982  |
| 135° | 1362 | 1384  | 1396 | 1410  | 1407 | 1052 |
| 145° | 1580 | 1579  | 1602 | 1611  | 1605 | 988  |
| 155° | 1740 | 1728  | 1744 | 1752  | 1742 | 802  |
| 165° | 1833 | 1825  | 1829 | 1839  | 1829 | 518  |
| 175° | 1875 | 1866  | 1869 | 1878  | 1865 | 178  |
| 180° | 1871 | 1871  | 1871 | 1871  | 1871 |      |

TEST NUMBER: P911759

CATALOG NUMBER: DFN2DIP-SQ2F0-070D050US850-RLLONL

**CANDELA DISTRIBUTION (FULL):**

|        | 0°     | 22.5°  | 45°    | 67.5°  | 90°    |
|--------|--------|--------|--------|--------|--------|
| 0°     | 3208.4 | 3208.4 | 3208.4 | 3208.4 | 3208.4 |
| 2.5°   | 3222.9 | 3208.4 | 3176.4 | 3205.7 | 3199.8 |
| 5°     | 3208.4 | 3193.9 | 3156.1 | 3182.3 | 3173.6 |
| 7.5°   | 3182.3 | 3165.0 | 3124.4 | 3135.7 | 3121.3 |
| 10°    | 3147.5 | 3127.2 | 3069.2 | 3060.3 | 3043.0 |
| 12.5°  | 3104.0 | 3077.8 | 2999.3 | 2982.0 | 2949.9 |
| 15°    | 3051.6 | 3019.6 | 2921.0 | 2865.9 | 2836.9 |
| 17.5°  | 2990.6 | 2944.2 | 2822.2 | 2758.3 | 2711.8 |
| 20°    | 2921.0 | 2862.8 | 2717.7 | 2645.3 | 2581.2 |
| 22.5°  | 2845.6 | 2778.7 | 2610.1 | 2511.6 | 2468.2 |
| 25°    | 2770.1 | 2677.0 | 2485.4 | 2366.5 | 2322.8 |
| 27.5°  | 2680.1 | 2581.2 | 2369.3 | 2232.9 | 2166.0 |
| 30°    | 2584.3 | 2473.7 | 2241.4 | 2093.6 | 2015.1 |
| 32.5°  | 2491.3 | 2357.6 | 2119.7 | 1945.4 | 1872.7 |
| 35°    | 2386.8 | 2238.6 | 1983.3 | 1800.4 | 1736.3 |
| 37.5°  | 2285.2 | 2125.3 | 1855.5 | 1654.8 | 1582.5 |
| 40°    | 2177.6 | 2003.6 | 1721.7 | 1515.7 | 1440.1 |
| 42.5°  | 2067.4 | 1881.6 | 1588.3 | 1373.3 | 1301.0 |
| 45°    | 1951.3 | 1756.5 | 1451.9 | 1245.5 | 1175.9 |
| 47.5°  | 1840.9 | 1634.9 | 1321.3 | 1114.9 | 1051.1 |
| 50°    | 1719.0 | 1512.9 | 1193.4 | 992.9  | 932.2  |
| 52.5°  | 1599.7 | 1381.9 | 1071.4 | 879.8  | 824.7  |
| 55°    | 1483.6 | 1257.2 | 943.5  | 769.5  | 714.4  |
| 57.5°  | 1364.7 | 1132.4 | 830.5  | 667.8  | 621.4  |
| 60°    | 1242.7 | 1010.4 | 711.3  | 563.5  | 516.9  |
| 62.5°  | 1123.7 | 891.5  | 609.6  | 470.4  | 447.3  |
| 65°    | 1001.8 | 766.4  | 505.3  | 406.7  | 397.7  |
| 67.5°  | 885.6  | 650.3  | 406.7  | 357.0  | 348.4  |
| 70°    | 763.7  | 537.2  | 336.7  | 307.7  | 296.0  |
| 72.5°  | 647.5  | 432.5  | 281.6  | 258.5  | 252.6  |
| 75°    | 534.2  | 330.8  | 232.2  | 211.9  | 209.2  |
| 77.5°  | 421.1  | 235.0  | 183.0  | 171.2  | 165.5  |
| 80°    | 316.4  | 168.5  | 139.3  | 127.9  | 127.9  |
| 82.5°  | 220.6  | 113.3  | 95.8   | 89.9   | 89.9   |
| 85°    | 124.8  | 63.8   | 55.1   | 55.1   | 55.1   |
| 87.5°  | 46.5   | 23.1   | 23.1   | 20.3   | 20.3   |
| 90°    | 1.3    | 16.2   | 27.1   | 33.9   | 36.5   |
| 92.5°  | 33.9   | 28.5   | 32.5   | 35.3   | 36.5   |
| 95°    | 87.9   | 43.3   | 52.8   | 59.7   | 58.2   |
| 97.5°  | 158.4  | 47.5   | 69.0   | 73.2   | 74.4   |
| 100°   | 239.8  | 54.2   | 77.2   | 87.9   | 90.7   |
| 102.5° | 329.0  | 326.4  | 80.0   | 94.7   | 98.9   |
| 105°   | 411.7  | 452.4  | 82.6   | 97.5   | 102.9  |
| 107.5° | 507.8  | 541.5  | 85.4   | 100.1  | 105.7  |
| 110°   | 600.0  | 628.2  | 237.0  | 101.6  | 106.9  |

TEST NUMBER: P911759

CATALOG NUMBER: DFN2DIP-SQ2F0-070D050US850-RLLONL

**CANDELA DISTRIBUTION (continued):**

|        | 0°     | 22.5°  | 45°    | 67.5°  | 90°    |
|--------|--------|--------|--------|--------|--------|
| 112.5° | 686.6  | 710.9  | 687.9  | 104.2  | 108.3  |
| 115°   | 778.6  | 801.6  | 835.5  | 208.6  | 111.1  |
| 117.5° | 858.5  | 885.5  | 908.7  | 714.9  | 360.2  |
| 120°   | 947.9  | 968.2  | 992.6  | 1008.9 | 826.0  |
| 122.5° | 1023.6 | 1045.3 | 1072.5 | 1080.6 | 1082.1 |
| 125°   | 1100.8 | 1118.5 | 1144.3 | 1153.7 | 1157.8 |
| 127.5° | 1171.2 | 1190.2 | 1210.7 | 1224.1 | 1225.4 |
| 130°   | 1237.6 | 1259.4 | 1274.1 | 1289.1 | 1287.9 |
| 132.5° | 1305.4 | 1323.0 | 1337.8 | 1350.1 | 1348.8 |
| 135°   | 1362.3 | 1384.0 | 1396.0 | 1409.8 | 1407.0 |
| 137.5° | 1421.7 | 1438.0 | 1451.7 | 1465.2 | 1461.2 |
| 140°   | 1480.0 | 1490.9 | 1505.7 | 1517.9 | 1511.2 |
| 142.5° | 1528.9 | 1538.4 | 1555.9 | 1566.7 | 1559.9 |
| 145°   | 1580.3 | 1578.9 | 1601.8 | 1611.4 | 1604.6 |
| 147.5° | 1624.9 | 1620.8 | 1643.9 | 1650.6 | 1645.3 |
| 150°   | 1668.3 | 1658.8 | 1680.5 | 1688.6 | 1681.8 |
| 152.5° | 1704.8 | 1694.0 | 1714.3 | 1722.5 | 1713.0 |
| 155°   | 1740.0 | 1727.9 | 1744.1 | 1752.2 | 1741.5 |
| 157.5° | 1768.4 | 1757.7 | 1769.9 | 1779.4 | 1768.4 |
| 160°   | 1792.9 | 1784.7 | 1792.9 | 1800.9 | 1791.5 |
| 162.5° | 1814.4 | 1806.5 | 1813.1 | 1822.6 | 1810.4 |
| 165°   | 1833.4 | 1825.4 | 1829.4 | 1838.8 | 1829.4 |
| 167.5° | 1848.4 | 1840.2 | 1844.4 | 1853.8 | 1841.6 |
| 170°   | 1860.6 | 1852.4 | 1855.1 | 1864.6 | 1852.4 |
| 172.5° | 1868.7 | 1860.6 | 1863.3 | 1872.8 | 1860.6 |
| 175°   | 1875.4 | 1865.9 | 1868.7 | 1878.1 | 1864.6 |
| 177.5° | 1878.1 | 1868.7 | 1870.1 | 1879.5 | 1867.3 |
| 180°   | 1871.3 | 1871.3 | 1871.3 | 1871.3 | 1871.3 |

TEST NUMBER: P911759

CATALOG NUMBER: DFN2DIP-SQ2F0-070D050US850-RLONL

**CIE UGR TABLE:**

| Reflectances:   |      |                  |       |       |       |       |                |       |       |       |       |
|-----------------|------|------------------|-------|-------|-------|-------|----------------|-------|-------|-------|-------|
| Ceiling         |      | 0.7              | 0.7   | 0.5   | 0.5   | 0.3   | 0.7            | 0.7   | 0.5   | 0.5   | 0.3   |
| Wall            |      | 0.5              | 0.3   | 0.5   | 0.3   | 0.3   | 0.5            | 0.3   | 0.5   | 0.3   | 0.3   |
| Reference plane |      | 0.2              | 0.2   | 0.2   | 0.2   | 0.2   | 0.2            | 0.2   | 0.2   | 0.2   | 0.2   |
| Room dimensions |      | Viewed crosswise |       |       |       |       | Viewed endwise |       |       |       |       |
| X=2H            | Y=2H | 14.24            | 15.11 | 15.16 | 16.05 | 17.25 | 10.20          | 11.07 | 11.12 | 12.01 | 13.21 |
|                 | 3H   | 15.90            | 16.68 | 16.84 | 17.63 | 18.86 | 11.37          | 12.15 | 12.31 | 13.10 | 14.33 |
|                 | 4H   | 16.50            | 17.23 | 17.45 | 18.18 | 19.42 | 11.81          | 12.55 | 12.76 | 13.50 | 14.74 |
|                 | 6H   | 16.91            | 17.58 | 17.87 | 18.54 | 19.79 | 12.12          | 12.80 | 13.08 | 13.75 | 15.01 |
|                 | 8H   | 17.03            | 17.67 | 17.99 | 18.64 | 19.89 | 12.20          | 12.85 | 13.17 | 13.82 | 15.07 |
|                 | 12H  | 17.08            | 17.69 | 18.05 | 18.66 | 19.93 | 12.24          | 12.85 | 13.21 | 13.82 | 15.09 |
| 4H              | 2H   | 14.26            | 14.99 | 15.21 | 15.94 | 17.18 | 10.79          | 11.53 | 11.75 | 12.48 | 13.72 |
|                 | 3H   | 16.07            | 16.68 | 17.03 | 17.66 | 18.91 | 12.12          | 12.73 | 13.09 | 13.71 | 14.97 |
|                 | 4H   | 16.75            | 17.30 | 17.72 | 18.28 | 19.56 | 12.66          | 13.21 | 13.63 | 14.19 | 15.47 |
|                 | 6H   | 17.25            | 17.72 | 18.23 | 18.72 | 20.00 | 13.06          | 13.54 | 14.05 | 14.54 | 15.81 |
|                 | 8H   | 17.41            | 17.86 | 18.40 | 18.85 | 20.14 | 13.18          | 13.63 | 14.17 | 14.62 | 15.91 |
|                 | 12H  | 17.50            | 17.90 | 18.50 | 18.91 | 20.20 | 13.23          | 13.64 | 14.24 | 14.65 | 15.94 |
| 8H              | 4H   | 16.71            | 17.16 | 17.70 | 18.15 | 19.44 | 12.93          | 13.38 | 13.92 | 14.37 | 15.66 |
|                 | 6H   | 17.26            | 17.63 | 18.27 | 18.66 | 19.95 | 13.42          | 13.79 | 14.44 | 14.83 | 16.12 |
|                 | 8H   | 17.46            | 17.79 | 18.48 | 18.81 | 20.12 | 13.60          | 13.93 | 14.62 | 14.95 | 16.26 |
|                 | 12H  | 17.59            | 17.88 | 18.61 | 18.89 | 20.24 | 13.71          | 13.99 | 14.73 | 15.01 | 16.36 |
| 12H             | 4H   | 16.67            | 17.07 | 17.67 | 18.08 | 19.37 | 12.93          | 13.33 | 13.94 | 14.34 | 15.64 |
|                 | 6H   | 17.23            | 17.56 | 18.25 | 18.58 | 19.89 | 13.47          | 13.79 | 14.49 | 14.81 | 16.12 |
|                 | 8H   | 17.44            | 17.73 | 18.47 | 18.74 | 20.10 | 13.66          | 13.95 | 14.69 | 14.97 | 16.32 |