

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1029369

Luminaire Tested: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

Issue Date: 5/6/2025

Test Information

Test Method: LM-79-2019
Report Number: P1029369
REPORT IS A COMBINATION OF REPORTS P985670 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/6/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K
Description: Define 2 Direct/Indirect Wall Mount with 4000K BioUP LEDs {m-DER=0.865} {m-EER=0.951}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3004.0 lumens
Efficiency: N/A
Efficacy: 114.7 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.09 / 1.23
Luminous Opening: Rectangular w/ Sides (W: 0.17' x L: 4' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 26.2
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1029369

CATALOG NUMBER: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

Luminous Intensity Polar Plot



TEST NUMBER: P1029369

CATALOG NUMBER: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	105	105	105	105	96	96	96	96	79	79	79	63	63	63	49	49	49
1	96	92	89	85	88	84	81	78	70	68	66	56	55	53	44	43	42
2	88	81	75	70	80	74	69	65	62	58	55	50	47	45	39	37	36
3	81	72	65	59	73	66	60	55	55	50	47	44	41	39	35	33	31
4	74	64	56	50	67	58	52	47	49	44	40	40	36	33	31	29	27
5	68	57	49	43	62	52	45	40	44	39	35	36	32	29	29	26	24
6	63	51	43	38	57	47	40	35	40	34	30	33	29	26	26	23	21
7	58	46	38	33	53	43	36	31	36	31	27	30	26	23	24	21	19
8	54	42	34	29	49	39	32	28	33	28	24	27	23	21	22	19	17
9	50	38	31	26	46	36	29	25	30	25	22	25	21	19	20	18	16
10	47	35	28	24	43	33	26	22	28	23	20	23	20	17	19	16	14

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	9054	9054	9054	9054
5°	9075	9654	9110	7680
10°	8971	10539	9027	6332
15°	8753	11116	8875	5334
20°	8617	10438	8617	4636
25°	8342	8967	8380	4146
30°	7890	7049	8041	3755
35°	7490	4874	7616	3435
40°	7029	3680	7110	3181
45°	6462	3025	6567	2906
50°	5971	2654	5983	2661
55°	5412	2262	5446	2394
60°	4816	1890	4882	2089
65°	4284	1537	4362	1784
70°	3750	1205	3846	1438
75°	3149	875	3273	1043
80°	2459	555	2635	620
85°	1610	280	1737	207

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 157.5°

Vertical Angle: 45°

Luminance: 9360 cd/sqm

TEST NUMBER: P1029369

CATALOG NUMBER: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	54.5	1.8
10°-20°	158.6	5.3
20°-30°	230.1	7.7
30°-40°	242.6	8.1
40°-50°	214.7	7.1
50°-60°	171.4	5.7
60°-70°	116.4	3.9
70°-80°	59.6	2.0
80°-90°	15.1	0.5
90°-100°	19.6	0.7
100°-110°	73.0	2.4
110°-120°	193.6	6.4
120°-130°	321.1	10.7
130°-140°	341.1	11.4
140°-150°	317.0	10.6
150°-160°	254.9	8.5
160°-170°	164.2	5.5
170°-180°	56.5	1.9
0°-30°	443.2	14.8
0°-40°	685.8	22.8
0°-60°	1071.9	35.7
0°-90°	1263.1	42.0
90°-120°	286.2	9.5
90°-150°	1265.3	42.1
90°-180°	1741.0	58.0
0°-180°	3004.0	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	572	572	572	572	572	
5°	572	639	575	508	572	54
15°	538	785	545	377	538	152
25°	483	654	485	302	483	221
35°	394	356	401	251	394	247
45°	296	215	301	206	296	230
55°	203	151	204	160	203	181
65°	120	93	123	108	120	120
75°	56	46	58	54	56	60
85°	11	12	12	9	11	13
90°	0	12	0	12	0	2
95°	28	18	28	18	28	33
105°	131	33	131	33	131	140
115°	247	35	247	35	247	243
125°	349	367	349	367	349	312
135°	432	446	432	446	432	334
145°	502	509	502	509	502	314
155°	552	553	552	553	552	254
165°	582	580	582	580	582	164
175°	595	592	595	592	595	57
180°	594	594	594	594	594	

TEST NUMBER: P1029369

CATALOG NUMBER: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	22.5°	25°	30°	35°	40°	45°
0°	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0
2.5°	575.1	576.4	578.6	579.0	583.4	586.9	590.9	590.9	592.2	591.8	588.3
5°	572.4	576.4	582.1	586.9	594.9	598.4	603.7	607.6	611.1	613.8	613.3
7.5°	568.0	575.1	583.4	592.7	603.2	609.4	616.8	623.9	628.7	633.1	636.2
10°	560.6	572.4	583.9	596.2	609.8	618.2	627.0	636.2	643.7	652.0	659.9
12.5°	550.5	567.6	581.7	597.9	614.6	623.9	637.9	645.0	659.5	680.6	686.3
15°	537.7	561.0	574.2	594.9	616.8	624.3	643.7	655.1	685.0	698.2	714.0
17.5°	525.8	551.8	569.4	593.1	614.6	629.2	648.1	671.4	696.4	715.3	732.9
20°	516.2	541.2	562.3	588.7	616.0	634.4	654.2	682.4	709.6	729.0	742.6
22.5°	494.2	526.3	550.9	580.4	613.3	638.8	657.7	688.5	718.0	729.8	741.7
25°	483.2	510.9	539.5	572.9	611.6	641.9	658.2	692.5	718.4	722.8	725.4
27.5°	463.0	494.2	527.6	565.8	611.1	636.6	657.3	688.5	709.2	706.1	698.2
30°	437.9	476.2	513.1	554.4	605.0	632.7	652.0	680.6	691.1	675.3	661.2
32.5°	419.4	455.5	496.4	544.3	597.9	624.3	643.2	665.6	667.8	639.3	615.5
35°	394.4	434.4	480.5	531.1	586.1	609.8	627.4	641.0	630.5	590.5	562.3
37.5°	372.0	411.5	460.8	512.2	569.8	593.1	607.2	609.4	583.4	548.3	506.9
40°	347.3	388.2	439.7	493.7	551.8	572.0	580.8	574.2	536.8	495.9	448.0
42.5°	322.7	363.2	418.6	474.0	528.9	546.1	549.6	531.5	485.8	437.9	382.5
45°	295.9	338.1	393.5	449.3	502.5	512.2	512.6	486.7	432.6	382.5	331.1
47.5°	273.9	313.0	368.0	423.8	468.7	475.3	472.6	442.7	383.8	327.5	282.7
50°	249.7	287.1	341.6	396.6	434.8	436.6	430.0	387.3	329.7	278.3	242.7
52.5°	223.8	261.6	311.7	364.5	398.8	396.1	383.4	337.7	283.6	240.9	213.7
55°	203.1	236.5	283.6	335.0	359.2	351.7	337.7	291.1	248.4	212.4	188.6
57.5°	180.3	209.7	255.9	300.7	314.8	307.8	293.7	250.2	210.6	183.3	167.5
60°	158.7	185.5	226.0	263.4	274.3	266.9	250.6	211.5	182.9	160.0	148.2
62.5°	138.9	162.2	196.1	230.4	234.8	227.3	213.2	181.6	157.0	138.9	130.1
65°	120.5	142.4	169.7	195.6	199.6	191.7	177.2	154.3	133.7	122.2	113.9
67.5°	102.4	120.0	144.2	163.1	165.3	157.8	146.0	127.5	114.8	102.4	96.3
70°	86.6	99.8	118.7	134.1	135.0	127.9	121.8	105.1	95.4	86.6	81.8
72.5°	71.2	80.5	95.0	106.4	106.8	102.4	96.7	86.2	77.8	71.7	66.8
75°	56.3	64.2	73.0	83.1	82.7	79.1	74.7	68.1	61.1	57.2	55.0
77.5°	43.1	47.9	55.0	61.6	61.6	59.8	57.2	52.3	47.9	44.0	41.8
80°	30.8	33.9	39.6	41.8	42.6	42.2	40.0	36.5	34.7	31.7	30.8
82.5°	19.8	22.0	24.6	26.8	28.1	27.3	26.8	25.1	22.4	21.5	20.7
85°	11.4	12.3	13.6	14.9	15.4	14.9	15.8	14.5	13.2	13.2	12.8
87.5°	4.8	5.3	6.2	6.2	6.6	6.6	6.2	6.6	6.6	6.2	5.7
90°	0.4	1.5	2.5	3.6	4.7	5.2	5.6	6.3	7.1	7.8	8.6
92.5°	10.7	10.3	9.9	9.6	9.2	9.0	9.1	9.4	9.7	10.0	10.3
95°	27.9	24.8	21.6	18.5	15.4	13.8	14.1	14.8	15.5	16.1	16.8
97.5°	50.3	42.5	34.6	26.8	18.9	15.0	15.8	17.3	18.8	20.4	21.9
100°	76.1	63.0	49.9	36.8	23.7	17.2	18.0	19.6	21.3	22.9	24.5
102.5°	104.4	104.2	104.0	103.9	103.7	103.6	94.9	77.5	60.2	42.8	25.4
105°	130.6	133.5	136.3	139.2	142.1	143.5	130.5	104.4	78.3	52.3	26.2
107.5°	161.1	163.5	165.9	168.3	170.7	171.9	155.8	123.6	91.5	59.3	27.1
110°	190.4	192.4	194.4	196.4	198.4	199.4	185.6	158.0	130.4	102.8	75.2



TEST NUMBER: P1029369

CATALOG NUMBER: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	22.5°	25°	30°	35°	40°	45°
112.5°	217.9	219.6	221.3	223.0	224.7	225.6	224.8	223.2	221.5	219.9	218.3
115°	247.1	248.7	250.3	252.0	253.6	254.4	255.6	258.0	260.3	262.7	265.1
117.5°	272.4	274.3	276.2	278.1	280.0	281.0	281.8	283.4	285.1	286.7	288.3
120°	300.8	302.2	303.6	305.1	306.5	307.2	308.1	309.8	311.5	313.3	315.0
122.5°	324.9	326.4	327.9	329.4	330.9	331.7	332.7	334.6	336.5	338.4	340.3
125°	349.3	350.5	351.8	353.0	354.3	354.9	355.8	357.6	359.5	361.3	363.1
127.5°	371.7	373.0	374.4	375.7	377.0	377.7	378.4	379.9	381.3	382.8	384.2
130°	392.7	394.2	395.8	397.3	398.8	399.6	400.1	401.2	402.2	403.3	404.3
132.5°	414.2	415.4	416.7	417.9	419.2	419.8	420.3	421.4	422.4	423.5	424.5
135°	432.3	433.8	435.4	436.9	438.4	439.2	439.6	440.5	441.3	442.2	443.0
137.5°	451.2	452.3	453.5	454.6	455.7	456.3	456.8	457.7	458.7	459.6	460.6
140°	469.7	470.5	471.2	472.0	472.7	473.1	473.6	474.7	475.7	476.8	477.8
142.5°	485.1	485.8	486.4	487.1	487.8	488.1	488.7	490.0	491.2	492.5	493.7
145°	501.5	501.4	501.3	501.2	501.1	501.0	501.8	503.4	505.1	506.7	508.3
147.5°	515.6	515.3	515.1	514.8	514.5	514.4	515.2	516.8	518.5	520.1	521.7
150°	529.4	528.7	528.1	527.4	526.7	526.4	527.2	528.7	530.2	531.8	533.3
152.5°	541.0	540.2	539.5	538.7	538.0	537.6	538.3	539.7	541.2	542.6	544.0
155°	552.2	551.3	550.5	549.6	548.7	548.3	548.9	550.0	551.2	552.3	553.5
157.5°	561.2	560.4	559.7	558.9	558.2	557.8	558.2	559.1	559.9	560.8	561.6
160°	568.9	568.3	567.7	567.2	566.6	566.3	566.6	567.2	567.7	568.3	568.9
162.5°	575.8	575.2	574.6	574.1	573.5	573.2	573.4	573.9	574.4	574.9	575.4
165°	581.8	581.2	580.6	580.1	579.5	579.2	579.3	579.6	579.9	580.2	580.5
167.5°	586.5	585.9	585.4	584.8	584.3	584.0	584.1	584.4	584.7	585.0	585.3
170°	590.4	589.8	589.2	588.7	588.1	587.8	587.9	588.1	588.3	588.5	588.7
172.5°	593.0	592.4	591.8	591.3	590.7	590.4	590.5	590.7	590.9	591.1	591.3
175°	595.1	594.4	593.8	593.1	592.4	592.1	592.2	592.4	592.6	592.8	593.0
177.5°	596.0	595.3	594.7	594.0	593.3	593.0	593.0	593.1	593.2	593.3	593.4
180°	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8

TEST NUMBER: P1029369

CATALOG NUMBER: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

CANDELA DISTRIBUTION (continued):

	50°	55°	60°	65°	67.5°	70°	75°	80°	85°	90°	95°
0°	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0
2.5°	594.4	594.9	595.7	600.1	602.3	602.8	601.0	605.0	606.3	605.0	604.1
5°	622.6	625.2	630.5	636.2	635.7	636.2	638.8	641.5	642.3	638.8	640.1
7.5°	647.2	652.5	658.2	667.0	667.0	671.4	673.1	675.3	680.6	678.0	677.1
10°	675.3	682.4	692.9	707.0	707.4	711.8	716.2	723.2	725.4	723.7	724.6
12.5°	710.5	724.1	725.0	740.4	747.4	748.3	755.3	754.0	758.4	758.4	765.9
15°	725.9	747.0	758.9	773.8	778.2	772.9	778.6	784.8	785.2	785.2	784.8
17.5°	753.6	761.9	773.8	781.7	783.5	783.5	783.9	786.6	784.8	781.3	783.9
20°	759.3	762.8	767.2	766.3	767.2	762.8	758.4	754.0	754.5	752.3	758.9
22.5°	748.7	747.9	737.7	731.2	731.2	722.4	714.0	710.1	706.1	707.4	709.6
25°	722.4	708.7	696.4	686.7	684.6	670.5	659.0	655.5	648.9	654.2	655.1
27.5°	680.2	664.8	645.0	636.6	625.2	619.5	611.6	601.0	587.4	595.3	594.0
30°	634.9	612.0	595.7	575.5	557.5	556.2	541.2	523.6	516.6	516.6	520.6
32.5°	584.3	554.0	530.2	501.7	484.1	476.6	458.6	441.0	444.9	431.7	436.6
35°	525.4	485.4	455.5	427.8	414.6	405.8	382.5	372.8	362.3	356.1	367.6
37.5°	469.1	423.0	384.7	354.4	349.5	333.7	317.9	311.7	305.6	308.2	307.8
40°	400.5	359.6	325.3	301.6	293.3	285.8	275.2	267.8	263.8	266.0	266.4
42.5°	338.5	304.2	278.7	262.0	255.0	249.7	244.5	238.3	237.0	237.0	238.7
45°	290.6	262.5	245.3	231.7	227.7	223.8	219.8	217.2	216.3	214.6	215.9
47.5°	252.4	229.9	219.4	209.3	204.9	204.0	200.5	199.2	197.4	197.0	197.4
50°	220.3	206.2	196.5	190.8	187.7	186.4	184.7	182.0	181.1	183.3	182.5
52.5°	197.8	184.7	179.4	173.7	171.9	170.1	167.5	167.9	167.5	166.6	166.6
55°	175.4	167.1	161.8	157.4	157.0	155.2	153.0	152.1	151.7	150.8	152.1
57.5°	157.4	150.8	146.0	142.0	140.3	140.3	138.1	136.3	136.3	135.9	136.3
60°	139.4	132.8	129.7	125.7	124.4	124.0	122.7	121.8	120.5	120.5	120.5
62.5°	122.7	117.4	113.9	110.4	110.8	108.6	106.8	106.0	106.0	106.4	106.4
65°	106.8	103.3	98.9	95.8	95.0	94.5	93.6	93.2	91.9	92.8	92.8
67.5°	92.3	87.5	84.9	83.5	82.2	81.8	80.9	80.0	79.6	79.1	80.0
70°	77.8	73.9	71.7	70.8	69.5	69.0	68.6	67.3	67.7	68.1	68.6
72.5°	64.6	61.1	60.7	58.0	58.0	58.0	56.3	57.2	56.7	55.8	56.7
75°	51.0	49.2	48.4	47.0	47.5	47.0	46.6	45.3	45.3	45.7	46.2
77.5°	40.4	38.7	38.3	36.9	36.1	36.9	36.1	35.6	35.6	36.1	36.1
80°	29.9	29.0	27.7	27.7	27.7	27.3	27.3	27.3	26.8	26.4	26.8
82.5°	19.8	19.8	19.3	18.9	19.3	18.5	18.9	18.9	18.9	18.9	18.9
85°	12.8	12.3	12.3	11.9	11.9	11.9	12.3	11.4	11.4	11.9	11.9
87.5°	5.7	5.7	5.7	6.2	5.7	5.7	5.7	6.2	5.7	5.7	5.7
90°	9.1	9.5	10.0	10.5	10.7	10.8	11.0	11.2	11.4	11.6	11.4
92.5°	10.5	10.7	10.9	11.1	11.2	11.2	11.3	11.4	11.5	11.6	11.5
95°	17.3	17.7	18.2	18.7	18.9	18.9	18.8	18.7	18.6	18.5	18.6
97.5°	22.2	22.5	22.8	23.1	23.2	23.2	23.3	23.4	23.5	23.6	23.5
100°	25.3	26.0	26.8	27.5	27.9	28.0	28.2	28.4	28.6	28.8	28.6
102.5°	26.4	27.5	28.5	29.6	30.1	30.2	30.5	30.8	31.1	31.4	31.1
105°	27.2	28.3	29.3	30.4	30.9	31.1	31.5	31.9	32.3	32.7	32.3
107.5°	28.1	29.2	30.2	31.3	31.8	32.0	32.4	32.7	33.1	33.5	33.1
110°	65.6	56.1	46.5	37.0	32.2	32.4	32.8	33.1	33.5	33.9	33.5

TEST NUMBER: P1029369

CATALOG NUMBER: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

CANDELA DISTRIBUTION (continued):

	50°	55°	60°	65°	67.5°	70°	75°	80°	85°	90°	95°
112.5°	177.1	136.0	94.8	53.7	33.1	33.2	33.5	33.8	34.1	34.4	34.1
115°	220.9	176.7	132.5	88.3	66.2	62.8	55.9	49.0	42.1	35.2	42.1
117.5°	274.7	261.0	247.4	233.7	226.9	214.4	189.4	164.3	139.3	114.3	139.3
120°	316.1	317.3	318.4	319.5	320.1	313.7	300.8	287.9	275.0	262.1	275.0
122.5°	340.9	341.5	342.0	342.6	342.9	342.9	343.0	343.1	343.2	343.3	343.2
125°	363.8	364.4	365.1	365.8	366.1	366.2	366.5	366.8	367.1	367.4	367.1
127.5°	385.2	386.1	387.1	388.0	388.5	388.5	388.6	388.7	388.8	388.9	388.8
130°	405.4	406.4	407.5	408.6	409.1	409.0	408.9	408.8	408.7	408.6	408.7
132.5°	425.4	426.2	427.1	428.0	428.4	428.4	428.3	428.2	428.1	428.0	428.1
135°	444.0	444.9	445.9	446.8	447.3	447.2	447.0	446.9	446.7	446.5	446.7
137.5°	461.6	462.5	463.5	464.4	464.9	464.8	464.5	464.2	463.9	463.6	463.9
140°	478.7	479.5	480.4	481.3	481.7	481.5	481.0	480.5	480.0	479.5	480.0
142.5°	494.5	495.3	496.0	496.8	497.2	497.0	496.5	496.0	495.5	495.0	495.5
145°	509.0	509.6	510.3	511.0	511.3	511.1	510.6	510.1	509.7	509.2	509.7
147.5°	522.2	522.6	523.1	523.6	523.8	523.6	523.2	522.9	522.5	522.1	522.5
150°	533.9	534.4	535.0	535.5	535.8	535.6	535.1	534.6	534.2	533.7	534.2
152.5°	544.6	545.2	545.7	546.3	546.6	546.3	545.6	544.9	544.3	543.6	544.3
155°	554.1	554.6	555.2	555.7	556.0	555.6	554.9	554.1	553.4	552.6	553.4
157.5°	562.3	562.9	563.6	564.3	564.6	564.2	563.5	562.7	562.0	561.2	562.0
160°	569.5	570.1	570.6	571.2	571.5	571.2	570.5	569.8	569.2	568.5	569.2
162.5°	576.1	576.7	577.4	578.1	578.4	578.0	577.1	576.2	575.4	574.5	575.4
165°	581.2	581.8	582.5	583.2	583.5	583.2	582.5	581.8	581.2	580.5	581.2
167.5°	586.0	586.6	587.3	588.0	588.3	587.9	587.0	586.1	585.3	584.4	585.3
170°	589.4	590.0	590.7	591.4	591.7	591.3	590.4	589.5	588.7	587.8	588.7
172.5°	592.0	592.6	593.3	594.0	594.3	593.9	593.0	592.1	591.3	590.4	591.3
175°	593.7	594.3	595.0	595.7	596.0	595.5	594.6	593.6	592.7	591.7	592.7
177.5°	594.1	594.7	595.4	596.1	596.4	596.0	595.1	594.3	593.4	592.6	593.4
180°	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8

TEST NUMBER: P1029369

CATALOG NUMBER: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

CANDELA DISTRIBUTION (continued):

	100°	105°	110°	112.5°	115°	120°	125°	130°	135°	140°	145°
0°	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0
2.5°	606.3	603.2	600.6	601.0	603.2	601.5	597.1	591.3	589.1	586.5	589.1
5°	642.8	640.1	634.9	635.3	634.0	632.2	625.2	616.4	616.4	609.4	608.5
7.5°	678.8	674.9	671.4	670.5	665.6	662.1	656.0	643.7	638.8	630.5	625.6
10°	719.3	716.2	712.2	707.4	704.8	698.6	688.5	670.5	661.7	650.3	641.9
12.5°	760.2	759.7	750.9	741.3	740.8	731.2	724.1	699.9	688.1	672.7	652.9
15°	786.1	783.9	779.1	774.2	775.6	765.0	749.2	720.6	712.7	694.2	673.1
17.5°	785.7	785.7	784.4	783.5	782.2	779.1	770.3	751.4	738.6	715.3	695.5
20°	760.6	766.3	767.6	767.2	771.6	773.8	773.4	761.5	751.4	730.7	710.5
22.5°	710.5	723.7	729.4	732.9	742.1	747.0	758.4	754.0	751.4	736.0	718.8
25°	663.9	668.3	685.4	686.3	699.1	710.9	722.4	729.8	739.5	733.8	719.3
27.5°	603.7	613.8	626.1	635.3	637.9	662.1	681.0	695.1	717.1	718.8	714.0
30°	535.5	540.3	560.6	572.9	586.9	604.5	631.8	656.0	675.8	693.8	699.9
32.5°	452.4	472.2	484.1	499.0	511.3	542.5	576.0	607.2	630.0	660.4	673.6
35°	376.3	391.7	412.0	418.1	440.5	466.9	510.4	550.5	585.2	616.0	642.8
37.5°	313.5	325.8	347.3	357.0	370.2	404.0	440.5	490.2	532.0	569.8	603.2
40°	270.4	279.6	295.9	299.0	310.0	340.7	370.2	416.8	472.2	523.2	559.7
42.5°	240.9	245.3	256.3	260.3	267.3	288.0	314.4	358.3	409.8	462.5	514.0
45°	219.8	222.9	229.5	233.0	241.8	251.0	272.6	307.8	348.2	401.4	456.8
47.5°	200.9	204.9	207.5	209.7	214.6	224.7	238.7	264.7	303.4	352.2	405.8
50°	185.1	186.4	191.3	191.7	194.8	201.4	214.6	230.4	261.2	300.7	352.6
52.5°	169.3	170.6	173.7	176.7	178.1	183.3	192.1	205.3	228.2	259.4	305.6
55°	153.4	155.2	158.3	160.5	161.8	166.2	171.5	184.2	202.2	224.2	262.0
57.5°	137.6	141.6	142.4	143.8	146.0	150.8	155.6	163.1	177.2	197.4	225.1
60°	122.7	124.0	127.1	128.4	130.6	133.2	139.4	145.1	155.2	171.0	196.1
62.5°	107.3	110.4	111.7	113.0	114.8	117.8	121.8	127.9	136.7	149.5	169.3
65°	94.1	94.5	97.2	98.9	100.7	102.9	106.8	112.6	117.8	129.7	144.2
67.5°	81.3	82.2	83.1	84.9	87.1	89.3	92.8	95.8	102.4	110.4	121.8
70°	69.0	69.0	71.2	72.5	72.1	74.7	77.4	80.9	85.7	93.2	102.4
72.5°	58.0	57.6	59.4	59.8	60.7	62.4	64.2	67.7	70.3	76.1	83.1
75°	46.2	47.0	47.9	47.9	49.2	50.6	52.3	54.1	57.2	60.7	65.9
77.5°	36.5	36.5	37.4	37.8	39.1	38.7	40.4	42.2	44.4	47.5	51.4
80°	26.8	27.7	27.7	27.7	28.1	28.6	30.3	31.7	33.0	35.2	36.9
82.5°	18.9	18.9	19.8	19.8	19.8	20.7	20.7	21.1	22.0	23.3	24.6
85°	11.9	11.9	11.9	12.3	11.9	12.3	13.2	12.8	13.2	14.1	14.1
87.5°	5.7	5.7	5.7	5.7	5.7	6.2	5.7	6.2	6.6	6.6	6.6
90°	11.2	11.0	10.8	10.7	10.5	10.0	9.5	9.1	8.6	7.8	7.1
92.5°	11.4	11.3	11.2	11.2	11.1	10.9	10.7	10.5	10.3	10.0	9.7
95°	18.7	18.8	18.9	18.9	18.7	18.2	17.7	17.3	16.8	16.1	15.5
97.5°	23.4	23.3	23.2	23.2	23.1	22.8	22.5	22.2	21.9	20.4	18.8
100°	28.4	28.2	28.0	27.9	27.5	26.8	26.0	25.3	24.5	22.9	21.3
102.5°	30.8	30.5	30.2	30.1	29.6	28.5	27.5	26.4	25.4	42.8	60.2
105°	31.9	31.5	31.1	30.9	30.4	29.3	28.3	27.2	26.2	52.3	78.3
107.5°	32.7	32.4	32.0	31.8	31.3	30.2	29.2	28.1	27.1	59.3	91.5
110°	33.1	32.8	32.4	32.2	37.0	46.5	56.1	65.6	75.2	102.8	130.4

TEST NUMBER: P1029369

CATALOG NUMBER: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

CANDELA DISTRIBUTION (continued):

	100°	105°	110°	112.5°	115°	120°	125°	130°	135°	140°	145°
112.5°	33.8	33.5	33.2	33.1	53.7	94.8	136.0	177.1	218.3	219.9	221.5
115°	49.0	55.9	62.8	66.2	88.3	132.5	176.7	220.9	265.1	262.7	260.3
117.5°	164.3	189.4	214.4	226.9	233.7	247.4	261.0	274.7	288.3	286.7	285.1
120°	287.9	300.8	313.7	320.1	319.5	318.4	317.3	316.1	315.0	313.3	311.5
122.5°	343.1	343.0	342.9	342.9	342.6	342.0	341.5	340.9	340.3	338.4	336.5
125°	366.8	366.5	366.2	366.1	365.8	365.1	364.4	363.8	363.1	361.3	359.5
127.5°	388.7	388.6	388.5	388.5	388.0	387.1	386.1	385.2	384.2	382.8	381.3
130°	408.8	408.9	409.0	409.1	408.6	407.5	406.4	405.4	404.3	403.3	402.2
132.5°	428.2	428.3	428.4	428.4	428.0	427.1	426.2	425.4	424.5	423.5	422.4
135°	446.9	447.0	447.2	447.3	446.8	445.9	444.9	444.0	443.0	442.2	441.3
137.5°	464.2	464.5	464.8	464.9	464.4	463.5	462.5	461.6	460.6	459.6	458.7
140°	480.5	481.0	481.5	481.7	481.3	480.4	479.5	478.7	477.8	476.8	475.7
142.5°	496.0	496.5	497.0	497.2	496.8	496.0	495.3	494.5	493.7	492.5	491.2
145°	510.1	510.6	511.1	511.3	511.0	510.3	509.6	509.0	508.3	506.7	505.1
147.5°	522.9	523.2	523.6	523.8	523.6	523.1	522.6	522.2	521.7	520.1	518.5
150°	534.6	535.1	535.6	535.8	535.5	535.0	534.4	533.9	533.3	531.8	530.2
152.5°	544.9	545.6	546.3	546.6	546.3	545.7	545.2	544.6	544.0	542.6	541.2
155°	554.1	554.9	555.6	556.0	555.7	555.2	554.6	554.1	553.5	552.3	551.2
157.5°	562.7	563.5	564.2	564.6	564.3	563.6	562.9	562.3	561.6	560.8	559.9
160°	569.8	570.5	571.2	571.5	571.2	570.6	570.1	569.5	568.9	568.3	567.7
162.5°	576.2	577.1	578.0	578.4	578.1	577.4	576.7	576.1	575.4	574.9	574.4
165°	581.8	582.5	583.2	583.5	583.2	582.5	581.8	581.2	580.5	580.2	579.9
167.5°	586.1	587.0	587.9	588.3	588.0	587.3	586.6	586.0	585.3	585.0	584.7
170°	589.5	590.4	591.3	591.7	591.4	590.7	590.0	589.4	588.7	588.5	588.3
172.5°	592.1	593.0	593.9	594.3	594.0	593.3	592.6	592.0	591.3	591.1	590.9
175°	593.6	594.6	595.5	596.0	595.7	595.0	594.3	593.7	593.0	592.8	592.6
177.5°	594.3	595.1	596.0	596.4	596.1	595.4	594.7	594.1	593.4	593.3	593.2
180°	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8

TEST NUMBER: P1029369

CATALOG NUMBER: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

CANDELA DISTRIBUTION (continued):

	150°	155°	157.5°	160°	165°	170°	175°	180°	185°	190°	195°
0°	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0
2.5°	586.9	584.7	583.4	584.3	581.7	575.1	575.1	577.3	574.6	572.0	568.0
5°	603.2	598.8	596.2	595.7	589.6	579.0	576.8	574.6	568.9	562.8	556.2
7.5°	619.0	611.1	606.7	603.7	594.9	581.2	575.5	570.7	561.4	552.2	543.9
10°	632.2	620.8	615.5	610.7	599.3	582.1	572.9	564.1	552.2	540.3	529.8
12.5°	642.8	629.6	623.0	616.0	601.9	579.5	568.0	554.0	542.1	526.3	515.7
15°	660.4	633.1	627.0	620.4	605.9	575.1	561.0	545.2	528.9	507.8	496.4
17.5°	674.4	637.9	637.5	623.4	604.5	573.3	551.8	531.1	513.5	492.4	474.4
20°	682.8	645.4	638.4	623.9	600.1	561.4	539.0	516.2	497.3	471.8	453.7
22.5°	689.8	656.0	637.5	619.9	590.9	557.5	524.5	503.0	477.0	449.3	432.2
25°	692.5	658.2	638.8	618.6	584.3	546.1	508.7	485.4	456.4	431.3	408.0
27.5°	692.9	657.7	634.0	612.9	575.1	531.1	492.9	468.2	436.1	407.1	383.8
30°	688.5	652.9	631.4	608.5	566.3	517.5	473.5	446.3	412.0	382.9	358.8
32.5°	675.3	643.2	625.6	600.6	554.9	498.6	455.0	424.7	388.7	360.1	336.8
35°	653.3	631.4	612.0	588.7	539.9	481.0	436.6	401.0	364.5	337.2	315.2
37.5°	626.1	614.2	596.2	573.3	522.8	465.2	415.9	376.3	339.9	313.5	291.9
40°	589.1	592.2	574.6	554.0	502.5	443.6	389.1	351.3	317.0	292.4	271.3
42.5°	549.1	561.9	551.8	532.0	480.1	419.9	369.3	327.5	294.1	268.6	251.0
45°	506.0	528.0	521.9	507.4	456.8	394.8	341.2	300.7	271.3	246.6	231.3
47.5°	459.0	490.2	490.2	479.7	430.9	369.8	317.0	275.7	246.6	229.1	214.1
50°	411.1	446.3	452.0	444.9	401.8	341.2	287.5	250.2	225.1	208.0	197.0
52.5°	361.0	401.8	412.4	408.9	371.1	313.9	263.4	226.9	204.0	189.1	179.4
55°	313.0	360.5	372.0	373.3	338.1	284.0	236.5	204.4	182.5	172.3	164.0
57.5°	267.8	313.5	326.2	328.4	304.7	256.8	211.5	183.3	163.6	155.2	148.6
60°	229.1	267.3	284.0	288.9	268.2	225.1	188.2	160.9	146.0	138.1	131.9
62.5°	197.4	228.2	245.8	247.1	237.9	197.4	164.0	141.1	128.4	121.3	118.3
65°	166.6	194.3	204.9	210.2	202.7	171.0	141.6	122.7	112.6	106.4	103.3
67.5°	142.0	159.6	168.4	175.4	167.9	144.2	120.5	105.1	97.6	91.4	89.7
70°	116.5	131.0	137.6	144.6	138.1	120.0	102.9	88.8	82.2	77.4	75.2
72.5°	93.2	104.6	110.8	115.2	111.2	96.3	82.2	72.5	67.7	64.2	62.9
75°	73.9	81.8	85.3	88.4	86.6	75.2	66.4	58.5	54.1	51.0	50.1
77.5°	56.3	62.0	65.9	66.8	64.6	57.2	49.7	44.8	41.3	39.6	38.7
80°	40.0	43.5	45.7	47.0	44.8	41.8	36.5	33.0	29.9	27.7	27.3
82.5°	26.8	28.6	30.3	29.9	29.0	26.4	23.3	21.5	20.2	18.5	18.5
85°	15.4	15.8	16.7	17.1	16.7	14.9	13.2	12.3	11.4	10.1	10.1
87.5°	6.6	7.0	7.0	7.5	6.6	6.6	5.7	4.8	4.8	4.4	4.0
90°	6.3	5.6	5.2	4.7	3.6	2.5	1.5	0.4	1.5	2.5	3.6
92.5°	9.4	9.1	9.0	9.2	9.6	9.9	10.3	10.7	10.3	9.9	9.6
95°	14.8	14.1	13.8	15.4	18.5	21.6	24.8	27.9	24.8	21.6	18.5
97.5°	17.3	15.8	15.0	18.9	26.8	34.6	42.5	50.3	42.5	34.6	26.8
100°	19.6	18.0	17.2	23.7	36.8	49.9	63.0	76.1	63.0	49.9	36.8
102.5°	77.5	94.9	103.6	103.7	103.9	104.0	104.2	104.4	104.2	104.0	103.9
105°	104.4	130.5	143.5	142.1	139.2	136.3	133.5	130.6	133.5	136.3	139.2
107.5°	123.6	155.8	171.9	170.7	168.3	165.9	163.5	161.1	163.5	165.9	168.3
110°	158.0	185.6	199.4	198.4	196.4	194.4	192.4	190.4	192.4	194.4	196.4

TEST NUMBER: P1029369

CATALOG NUMBER: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

CANDELA DISTRIBUTION (continued):

	150°	155°	157.5°	160°	165°	170°	175°	180°	185°	190°	195°
112.5°	223.2	224.8	225.6	224.7	223.0	221.3	219.6	217.9	219.6	221.3	223.0
115°	258.0	255.6	254.4	253.6	252.0	250.3	248.7	247.1	248.7	250.3	252.0
117.5°	283.4	281.8	281.0	280.0	278.1	276.2	274.3	272.4	274.3	276.2	278.1
120°	309.8	308.1	307.2	306.5	305.1	303.6	302.2	300.8	302.2	303.6	305.1
122.5°	334.6	332.7	331.7	330.9	329.4	327.9	326.4	324.9	326.4	327.9	329.4
125°	357.6	355.8	354.9	354.3	353.0	351.8	350.5	349.3	350.5	351.8	353.0
127.5°	379.9	378.4	377.7	377.0	375.7	374.4	373.0	371.7	373.0	374.4	375.7
130°	401.2	400.1	399.6	398.8	397.3	395.8	394.2	392.7	394.2	395.8	397.3
132.5°	421.4	420.3	419.8	419.2	417.9	416.7	415.4	414.2	415.4	416.7	417.9
135°	440.5	439.6	439.2	438.4	436.9	435.4	433.8	432.3	433.8	435.4	436.9
137.5°	457.7	456.8	456.3	455.7	454.6	453.5	452.3	451.2	452.3	453.5	454.6
140°	474.7	473.6	473.1	472.7	472.0	471.2	470.5	469.7	470.5	471.2	472.0
142.5°	490.0	488.7	488.1	487.8	487.1	486.4	485.8	485.1	485.8	486.4	487.1
145°	503.4	501.8	501.0	501.1	501.2	501.3	501.4	501.5	501.4	501.3	501.2
147.5°	516.8	515.2	514.4	514.5	514.8	515.1	515.3	515.6	515.3	515.1	514.8
150°	528.7	527.2	526.4	526.7	527.4	528.1	528.7	529.4	528.7	528.1	527.4
152.5°	539.7	538.3	537.6	538.0	538.7	539.5	540.2	541.0	540.2	539.5	538.7
155°	550.0	548.9	548.3	548.7	549.6	550.5	551.3	552.2	551.3	550.5	549.6
157.5°	559.1	558.2	557.8	558.2	558.9	559.7	560.4	561.2	560.4	559.7	558.9
160°	567.2	566.6	566.3	566.6	567.2	567.7	568.3	568.9	568.3	567.7	567.2
162.5°	573.9	573.4	573.2	573.5	574.1	574.6	575.2	575.8	575.2	574.6	574.1
165°	579.6	579.3	579.2	579.5	580.1	580.6	581.2	581.8	581.2	580.6	580.1
167.5°	584.4	584.1	584.0	584.3	584.8	585.4	585.9	586.5	585.9	585.4	584.8
170°	588.1	587.9	587.8	588.1	588.7	589.2	589.8	590.4	589.8	589.2	588.7
172.5°	590.7	590.5	590.4	590.7	591.3	591.8	592.4	593.0	592.4	591.8	591.3
175°	592.4	592.2	592.1	592.4	593.1	593.8	594.4	595.1	594.4	593.8	593.1
177.5°	593.1	593.0	593.0	593.3	594.0	594.7	595.3	596.0	595.3	594.7	594.0
180°	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8

TEST NUMBER: P1029369

CATALOG NUMBER: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

CANDELA DISTRIBUTION (continued):

	200°	202.5°	205°	210°	215°	220°	225°	230°	235°	240°	245°
0°	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0
2.5°	565.8	568.0	567.6	563.2	558.4	554.4	546.9	547.8	545.2	545.6	548.3
5°	551.8	551.8	550.0	543.9	535.9	531.5	523.2	521.0	515.7	515.3	514.8
7.5°	536.8	534.6	532.4	523.6	514.0	506.9	495.5	492.9	487.6	484.1	482.3
10°	519.2	516.2	511.8	501.7	489.8	481.0	469.1	465.6	455.5	451.1	448.5
12.5°	499.9	498.1	491.1	482.7	463.4	453.7	436.6	440.1	430.0	421.2	419.9
15°	480.5	474.0	470.0	456.4	433.1	428.7	415.0	408.0	398.8	391.7	391.7
17.5°	461.6	451.5	442.7	428.2	411.1	398.8	388.7	385.1	373.7	366.7	365.4
20°	436.6	425.2	423.0	402.3	390.4	376.8	367.1	358.3	350.0	346.9	344.7
22.5°	412.8	399.7	396.1	378.5	366.7	353.0	343.4	337.2	331.1	328.9	324.9
25°	387.3	379.4	374.2	355.2	342.1	329.3	322.7	318.3	312.6	312.2	309.5
27.5°	362.7	355.2	350.0	331.9	322.3	310.4	305.1	300.3	297.2	295.9	294.6
30°	341.6	333.3	327.1	313.9	302.0	292.4	288.0	284.9	283.1	280.9	280.5
32.5°	318.3	313.5	305.1	295.0	285.8	276.5	273.9	271.7	269.1	268.2	267.8
35°	298.5	291.9	286.7	275.2	271.3	263.4	260.3	258.5	255.0	254.1	253.2
37.5°	279.2	273.0	267.3	260.3	252.8	248.4	246.6	244.0	242.3	242.7	241.8
40°	259.8	255.0	250.6	243.1	238.7	236.5	233.0	230.4	229.5	229.9	229.5
42.5°	240.9	236.5	233.9	228.2	223.8	221.6	219.4	216.8	218.1	218.1	219.4
45°	223.8	219.8	218.1	213.7	211.0	207.5	205.3	204.9	206.6	206.2	206.2
47.5°	206.2	204.9	202.7	198.7	195.2	193.0	192.6	192.6	194.3	195.2	194.8
50°	192.6	189.9	187.3	184.2	181.6	180.7	179.4	180.3	182.0	182.0	182.9
52.5°	175.4	173.7	172.8	170.1	168.4	168.4	168.4	168.8	170.1	171.5	171.0
55°	160.5	159.2	158.3	157.0	154.8	155.2	154.8	155.6	157.0	158.3	159.2
57.5°	144.6	144.2	143.3	141.1	141.1	140.7	142.0	142.4	144.6	145.5	146.8
60°	130.6	129.3	129.3	127.5	127.5	127.5	128.8	130.1	131.9	132.3	133.2
62.5°	115.6	115.6	115.2	113.9	113.9	115.2	115.6	117.4	118.3	118.3	119.6
65°	101.6	101.1	100.7	101.1	101.6	101.6	102.9	103.8	104.6	105.1	105.5
67.5°	87.5	87.1	87.9	87.5	88.4	90.1	89.7	91.0	92.3	92.3	92.8
70°	74.3	75.2	74.7	75.6	75.2	76.1	77.4	77.8	77.8	78.3	79.6
72.5°	62.0	62.0	62.0	61.6	62.0	62.9	63.8	64.2	65.1	65.5	66.8
75°	50.1	50.1	49.2	50.1	50.1	51.0	51.9	51.9	51.9	52.8	54.1
77.5°	37.8	38.3	37.8	38.7	38.7	39.1	40.0	39.6	40.4	40.9	41.3
80°	27.7	27.3	27.3	27.3	27.7	27.7	28.6	29.0	29.0	30.3	29.5
82.5°	17.6	18.0	17.6	18.0	18.0	18.5	18.0	18.5	18.9	19.8	19.3
85°	10.1	9.7	9.7	10.1	9.7	9.7	10.1	9.7	10.1	9.7	10.1
87.5°	4.0	3.5	3.5	3.5	3.5	3.1	3.1	2.6	2.6	2.6	2.2
90°	4.7	5.2	5.6	6.3	7.1	7.8	8.6	9.1	9.5	10.0	10.5
92.5°	9.2	9.0	9.1	9.4	9.7	10.0	10.3	10.5	10.7	10.9	11.1
95°	15.4	13.8	14.1	14.8	15.5	16.1	16.8	17.3	17.7	18.2	18.7
97.5°	18.9	15.0	15.8	17.3	18.8	20.4	21.9	22.2	22.5	22.8	23.1
100°	23.7	17.2	18.0	19.6	21.3	22.9	24.5	25.3	26.0	26.8	27.5
102.5°	103.7	103.6	94.9	77.5	60.2	42.8	25.4	26.4	27.5	28.5	29.6
105°	142.1	143.5	130.5	104.4	78.3	52.3	26.2	27.2	28.3	29.3	30.4
107.5°	170.7	171.9	155.8	123.6	91.5	59.3	27.1	28.1	29.2	30.2	31.3
110°	198.4	199.4	185.6	158.0	130.4	102.8	75.2	65.6	56.1	46.5	37.0

TEST NUMBER: P1029369

CATALOG NUMBER: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

CANDELA DISTRIBUTION (continued):

	200°	202.5°	205°	210°	215°	220°	225°	230°	235°	240°	245°
112.5°	224.7	225.6	224.8	223.2	221.5	219.9	218.3	177.1	136.0	94.8	53.7
115°	253.6	254.4	255.6	258.0	260.3	262.7	265.1	220.9	176.7	132.5	88.3
117.5°	280.0	281.0	281.8	283.4	285.1	286.7	288.3	274.7	261.0	247.4	233.7
120°	306.5	307.2	308.1	309.8	311.5	313.3	315.0	316.1	317.3	318.4	319.5
122.5°	330.9	331.7	332.7	334.6	336.5	338.4	340.3	340.9	341.5	342.0	342.6
125°	354.3	354.9	355.8	357.6	359.5	361.3	363.1	363.8	364.4	365.1	365.8
127.5°	377.0	377.7	378.4	379.9	381.3	382.8	384.2	385.2	386.1	387.1	388.0
130°	398.8	399.6	400.1	401.2	402.2	403.3	404.3	405.4	406.4	407.5	408.6
132.5°	419.2	419.8	420.3	421.4	422.4	423.5	424.5	425.4	426.2	427.1	428.0
135°	438.4	439.2	439.6	440.5	441.3	442.2	443.0	444.0	444.9	445.9	446.8
137.5°	455.7	456.3	456.8	457.7	458.7	459.6	460.6	461.6	462.5	463.5	464.4
140°	472.7	473.1	473.6	474.7	475.7	476.8	477.8	478.7	479.5	480.4	481.3
142.5°	487.8	488.1	488.7	490.0	491.2	492.5	493.7	494.5	495.3	496.0	496.8
145°	501.1	501.0	501.8	503.4	505.1	506.7	508.3	509.0	509.6	510.3	511.0
147.5°	514.5	514.4	515.2	516.8	518.5	520.1	521.7	522.2	522.6	523.1	523.6
150°	526.7	526.4	527.2	528.7	530.2	531.8	533.3	533.9	534.4	535.0	535.5
152.5°	538.0	537.6	538.3	539.7	541.2	542.6	544.0	544.6	545.2	545.7	546.3
155°	548.7	548.3	548.9	550.0	551.2	552.3	553.5	554.1	554.6	555.2	555.7
157.5°	558.2	557.8	558.2	559.1	559.9	560.8	561.6	562.3	562.9	563.6	564.3
160°	566.6	566.3	566.6	567.2	567.7	568.3	568.9	569.5	570.1	570.6	571.2
162.5°	573.5	573.2	573.4	573.9	574.4	574.9	575.4	576.1	576.7	577.4	578.1
165°	579.5	579.2	579.3	579.6	579.9	580.2	580.5	581.2	581.8	582.5	583.2
167.5°	584.3	584.0	584.1	584.4	584.7	585.0	585.3	586.0	586.6	587.3	588.0
170°	588.1	587.8	587.9	588.1	588.3	588.5	588.7	589.4	590.0	590.7	591.4
172.5°	590.7	590.4	590.5	590.7	590.9	591.1	591.3	592.0	592.6	593.3	594.0
175°	592.4	592.1	592.2	592.4	592.6	592.8	593.0	593.7	594.3	595.0	595.7
177.5°	593.3	593.0	593.0	593.1	593.2	593.3	593.4	594.1	594.7	595.4	596.1
180°	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8

TEST NUMBER: P1029369

CATALOG NUMBER: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

CANDELA DISTRIBUTION (continued):

	247.5°	250°	255°	260°	265°	270°	275°	280°	285°	290°	292.5°
0°	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0
2.5°	545.2	546.5	543.4	542.5	543.4	540.3	541.2	542.1	542.1	543.4	544.3
5°	513.5	511.8	508.7	507.8	506.9	508.2	507.4	508.7	509.1	512.2	512.6
7.5°	482.3	479.7	477.0	474.4	473.5	471.3	473.5	473.5	476.6	475.7	477.9
10°	445.4	444.9	441.4	440.1	438.3	434.8	439.7	438.3	440.5	444.5	445.4
12.5°	418.1	413.3	415.5	409.3	411.5	408.0	408.4	408.4	412.0	412.4	411.5
15°	392.2	388.2	382.5	379.9	378.5	376.8	382.5	382.9	380.3	386.5	384.3
17.5°	365.8	365.8	360.5	359.2	355.7	357.4	356.6	357.0	356.1	360.5	362.7
20°	342.9	340.7	339.0	339.4	335.0	334.1	333.3	334.1	337.2	340.3	341.2
22.5°	324.5	323.1	318.8	319.6	316.1	317.4	316.6	318.8	319.2	319.2	322.3
25°	306.9	305.1	305.6	303.8	302.5	302.5	301.2	302.5	304.2	305.1	305.6
27.5°	293.7	292.4	290.2	288.9	289.7	287.5	289.3	290.6	290.6	289.7	290.6
30°	277.9	278.7	278.7	274.3	276.1	275.2	276.5	277.4	277.4	277.9	277.0
32.5°	267.3	264.7	264.2	263.8	263.8	262.0	262.0	263.4	263.8	264.2	265.6
35°	253.2	253.2	251.0	252.4	250.6	251.0	250.6	251.0	251.9	250.6	251.9
37.5°	240.5	240.9	240.1	240.9	241.4	240.5	239.6	241.4	240.5	240.5	239.6
40°	229.5	229.1	229.5	229.5	229.5	229.9	229.1	229.1	229.1	228.2	227.3
42.5°	220.3	217.6	218.5	219.0	217.6	217.6	218.1	217.6	219.0	216.3	216.3
45°	207.1	206.2	206.6	206.6	207.5	206.2	207.1	207.5	206.2	205.8	204.9
47.5°	195.2	196.1	195.2	196.1	196.1	197.0	195.2	195.6	196.1	194.3	193.0
50°	183.3	183.3	184.7	184.2	184.7	183.8	183.8	183.3	183.8	182.9	181.6
52.5°	172.3	171.0	173.2	172.8	172.3	171.9	171.5	171.9	171.0	170.1	170.1
55°	158.7	158.7	160.0	160.5	160.5	159.6	158.7	159.2	158.7	158.3	157.8
57.5°	147.7	146.0	146.8	147.3	147.3	146.0	146.8	146.0	146.0	146.4	145.1
60°	133.7	133.7	132.8	134.1	134.1	133.2	133.2	133.7	132.8	132.3	131.9
62.5°	118.7	119.1	120.5	120.9	121.3	120.5	119.6	120.0	120.0	118.7	119.1
65°	106.0	106.8	108.6	108.2	107.3	107.7	106.8	107.3	106.0	106.4	105.1
67.5°	93.6	93.2	93.6	93.6	94.5	94.1	93.2	93.2	92.8	94.1	92.8
70°	80.5	80.5	80.5	80.5	80.9	81.3	80.5	79.6	80.0	79.1	78.7
72.5°	66.8	67.3	66.8	67.7	66.4	67.3	67.3	66.8	66.4	66.4	66.4
75°	54.1	55.0	53.6	54.1	53.6	54.5	54.1	54.1	53.2	52.8	53.2
77.5°	41.3	41.8	40.9	41.3	40.9	41.3	41.3	40.9	40.9	40.9	40.9
80°	29.5	29.9	29.5	29.0	28.6	29.5	28.6	29.0	29.5	29.0	29.9
82.5°	18.9	18.9	18.5	18.9	18.0	18.0	18.5	18.5	18.0	18.9	18.0
85°	9.2	9.2	10.1	9.2	8.8	8.8	8.8	9.2	8.8	9.7	9.2
87.5°	2.2	1.8	2.2	2.2	1.8	1.8	2.2	1.8	2.2	2.6	1.8
90°	10.7	10.8	11.0	11.2	11.4	11.6	11.4	11.2	11.0	10.8	10.7
92.5°	11.2	11.2	11.3	11.4	11.5	11.6	11.5	11.4	11.3	11.2	11.2
95°	18.9	18.9	18.8	18.7	18.6	18.5	18.6	18.7	18.8	18.9	18.9
97.5°	23.2	23.2	23.3	23.4	23.5	23.6	23.5	23.4	23.3	23.2	23.2
100°	27.9	28.0	28.2	28.4	28.6	28.8	28.6	28.4	28.2	28.0	27.9
102.5°	30.1	30.2	30.5	30.8	31.1	31.4	31.1	30.8	30.5	30.2	30.1
105°	30.9	31.1	31.5	31.9	32.3	32.7	32.3	31.9	31.5	31.1	30.9
107.5°	31.8	32.0	32.4	32.7	33.1	33.5	33.1	32.7	32.4	32.0	31.8
110°	32.2	32.4	32.8	33.1	33.5	33.9	33.5	33.1	32.8	32.4	32.2

TEST NUMBER: P1029369

CATALOG NUMBER: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

CANDELA DISTRIBUTION (continued):

	247.5°	250°	255°	260°	265°	270°	275°	280°	285°	290°	292.5°
112.5°	33.1	33.2	33.5	33.8	34.1	34.4	34.1	33.8	33.5	33.2	33.1
115°	66.2	62.8	55.9	49.0	42.1	35.2	42.1	49.0	55.9	62.8	66.2
117.5°	226.9	214.4	189.4	164.3	139.3	114.3	139.3	164.3	189.4	214.4	226.9
120°	320.1	313.7	300.8	287.9	275.0	262.1	275.0	287.9	300.8	313.7	320.1
122.5°	342.9	342.9	343.0	343.1	343.2	343.3	343.2	343.1	343.0	342.9	342.9
125°	366.1	366.2	366.5	366.8	367.1	367.4	367.1	366.8	366.5	366.2	366.1
127.5°	388.5	388.5	388.6	388.7	388.8	388.9	388.8	388.7	388.6	388.5	388.5
130°	409.1	409.0	408.9	408.8	408.7	408.6	408.7	408.8	408.9	409.0	409.1
132.5°	428.4	428.4	428.3	428.2	428.1	428.0	428.1	428.2	428.3	428.4	428.4
135°	447.3	447.2	447.0	446.9	446.7	446.5	446.7	446.9	447.0	447.2	447.3
137.5°	464.9	464.8	464.5	464.2	463.9	463.6	463.9	464.2	464.5	464.8	464.9
140°	481.7	481.5	481.0	480.5	480.0	479.5	480.0	480.5	481.0	481.5	481.7
142.5°	497.2	497.0	496.5	496.0	495.5	495.0	495.5	496.0	496.5	497.0	497.2
145°	511.3	511.1	510.6	510.1	509.7	509.2	509.7	510.1	510.6	511.1	511.3
147.5°	523.8	523.6	523.2	522.9	522.5	522.1	522.5	522.9	523.2	523.6	523.8
150°	535.8	535.6	535.1	534.6	534.2	533.7	534.2	534.6	535.1	535.6	535.8
152.5°	546.6	546.3	545.6	544.9	544.3	543.6	544.3	544.9	545.6	546.3	546.6
155°	556.0	555.6	554.9	554.1	553.4	552.6	553.4	554.1	554.9	555.6	556.0
157.5°	564.6	564.2	563.5	562.7	562.0	561.2	562.0	562.7	563.5	564.2	564.6
160°	571.5	571.2	570.5	569.8	569.2	568.5	569.2	569.8	570.5	571.2	571.5
162.5°	578.4	578.0	577.1	576.2	575.4	574.5	575.4	576.2	577.1	578.0	578.4
165°	583.5	583.2	582.5	581.8	581.2	580.5	581.2	581.8	582.5	583.2	583.5
167.5°	588.3	587.9	587.0	586.1	585.3	584.4	585.3	586.1	587.0	587.9	588.3
170°	591.7	591.3	590.4	589.5	588.7	587.8	588.7	589.5	590.4	591.3	591.7
172.5°	594.3	593.9	593.0	592.1	591.3	590.4	591.3	592.1	593.0	593.9	594.3
175°	596.0	595.5	594.6	593.6	592.7	591.7	592.7	593.6	594.6	595.5	596.0
177.5°	596.4	596.0	595.1	594.3	593.4	592.6	593.4	594.3	595.1	596.0	596.4
180°	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8

TEST NUMBER: P1029369

CATALOG NUMBER: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

CANDELA DISTRIBUTION (continued):

	295°	300°	305°	310°	315°	320°	325°	330°	335°	337.5°	340°
0°	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0	572.0
2.5°	543.0	546.5	545.2	540.3	546.1	546.1	550.0	550.0	554.9	556.6	559.2
5°	512.2	514.8	517.0	514.8	518.8	525.0	528.5	531.5	538.1	540.8	544.7
7.5°	479.2	484.1	486.3	486.3	492.9	499.9	506.9	511.3	520.6	524.1	528.0
10°	447.1	452.8	457.2	456.8	467.8	472.2	481.0	491.1	500.3	505.6	511.3
12.5°	413.3	416.4	422.5	431.3	433.9	441.9	452.0	464.7	481.4	486.3	494.6
15°	385.1	393.5	398.3	402.3	408.4	415.9	426.9	439.2	455.9	466.5	475.3
17.5°	361.4	372.4	375.5	374.6	382.5	393.9	406.7	415.9	430.9	443.6	452.0
20°	342.1	346.5	351.7	353.9	360.1	372.4	384.7	395.3	407.6	417.7	427.3
22.5°	322.7	326.2	330.6	334.6	339.4	346.5	358.3	371.5	383.4	393.1	404.0
25°	306.9	309.1	313.0	316.1	321.4	326.2	334.6	349.1	363.2	368.9	378.5
27.5°	291.5	293.3	295.9	299.4	302.0	306.9	314.4	326.2	340.7	346.5	359.6
30°	277.9	279.2	281.8	283.6	284.9	290.6	296.3	305.6	316.6	324.5	334.1
32.5°	265.1	266.4	269.1	269.5	271.3	274.3	279.6	288.0	297.6	304.2	312.6
35°	251.0	251.9	254.6	255.4	256.8	259.4	263.4	269.5	278.3	283.1	290.6
37.5°	240.1	239.6	241.4	242.7	244.5	245.8	247.1	253.2	259.8	264.2	270.0
40°	228.2	227.3	227.7	229.5	230.4	232.1	232.1	238.3	242.7	246.2	250.6
42.5°	216.3	215.9	215.0	215.9	216.8	217.2	217.6	222.0	226.4	229.5	234.3
45°	204.4	204.0	203.1	203.6	203.6	204.4	205.8	207.5	210.6	213.2	215.9
47.5°	193.5	192.6	191.3	190.8	191.7	191.7	191.7	193.5	196.5	197.4	200.0
50°	182.0	180.7	178.9	178.1	178.1	177.6	178.5	178.9	181.6	182.5	184.7
52.5°	169.7	168.8	167.1	165.3	165.8	164.9	165.3	165.8	166.6	167.9	169.3
55°	157.4	155.6	154.3	153.9	152.6	152.6	151.2	153.0	152.6	153.0	154.8
57.5°	145.5	143.8	141.6	140.7	139.4	138.9	138.1	137.6	138.1	139.4	140.7
60°	131.5	130.6	129.3	127.9	127.1	125.7	124.9	124.9	124.4	124.4	124.9
62.5°	117.8	117.4	115.6	115.2	114.3	113.4	112.1	111.2	111.2	112.1	112.6
65°	104.6	104.2	102.9	102.4	100.2	99.4	98.9	98.5	97.6	97.6	97.6
67.5°	92.3	91.0	91.0	88.8	87.1	86.2	85.3	84.9	84.9	84.9	85.3
70°	78.7	78.7	77.4	76.1	74.3	74.7	73.4	72.1	72.1	71.2	71.7
72.5°	65.5	65.1	63.8	63.3	62.0	60.7	59.8	60.7	59.4	58.9	59.4
75°	52.8	52.3	51.4	50.6	51.0	49.7	48.4	47.9	47.9	47.0	47.0
77.5°	40.4	41.3	39.6	39.1	38.3	37.4	36.9	36.5	36.5	36.5	37.4
80°	28.1	28.6	28.6	27.7	28.1	26.8	26.8	26.8	25.5	25.9	26.4
82.5°	18.0	18.0	17.6	18.0	17.6	17.6	17.1	17.1	16.7	16.7	17.1
85°	10.1	9.7	9.2	10.1	9.7	9.7	9.2	9.2	9.2	9.2	9.2
87.5°	2.2	2.6	2.6	2.6	2.6	3.1	3.1	3.1	3.5	3.5	3.5
90°	10.5	10.0	9.5	9.1	8.6	7.8	7.1	6.3	5.6	5.2	4.7
92.5°	11.1	10.9	10.7	10.5	10.3	10.0	9.7	9.4	9.1	9.0	9.2
95°	18.7	18.2	17.7	17.3	16.8	16.1	15.5	14.8	14.1	13.8	15.4
97.5°	23.1	22.8	22.5	22.2	21.9	20.4	18.8	17.3	15.8	15.0	18.9
100°	27.5	26.8	26.0	25.3	24.5	22.9	21.3	19.6	18.0	17.2	23.7
102.5°	29.6	28.5	27.5	26.4	25.4	42.8	60.2	77.5	94.9	103.6	103.7
105°	30.4	29.3	28.3	27.2	26.2	52.3	78.3	104.4	130.5	143.5	142.1
107.5°	31.3	30.2	29.2	28.1	27.1	59.3	91.5	123.6	155.8	171.9	170.7
110°	37.0	46.5	56.1	65.6	75.2	102.8	130.4	158.0	185.6	199.4	198.4

TEST NUMBER: P1029369

CATALOG NUMBER: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

CANDELA DISTRIBUTION (continued):

	295°	300°	305°	310°	315°	320°	325°	330°	335°	337.5°	340°
112.5°	53.7	94.8	136.0	177.1	218.3	219.9	221.5	223.2	224.8	225.6	224.7
115°	88.3	132.5	176.7	220.9	265.1	262.7	260.3	258.0	255.6	254.4	253.6
117.5°	233.7	247.4	261.0	274.7	288.3	286.7	285.1	283.4	281.8	281.0	280.0
120°	319.5	318.4	317.3	316.1	315.0	313.3	311.5	309.8	308.1	307.2	306.5
122.5°	342.6	342.0	341.5	340.9	340.3	338.4	336.5	334.6	332.7	331.7	330.9
125°	365.8	365.1	364.4	363.8	363.1	361.3	359.5	357.6	355.8	354.9	354.3
127.5°	388.0	387.1	386.1	385.2	384.2	382.8	381.3	379.9	378.4	377.7	377.0
130°	408.6	407.5	406.4	405.4	404.3	403.3	402.2	401.2	400.1	399.6	398.8
132.5°	428.0	427.1	426.2	425.4	424.5	423.5	422.4	421.4	420.3	419.8	419.2
135°	446.8	445.9	444.9	444.0	443.0	442.2	441.3	440.5	439.6	439.2	438.4
137.5°	464.4	463.5	462.5	461.6	460.6	459.6	458.7	457.7	456.8	456.3	455.7
140°	481.3	480.4	479.5	478.7	477.8	476.8	475.7	474.7	473.6	473.1	472.7
142.5°	496.8	496.0	495.3	494.5	493.7	492.5	491.2	490.0	488.7	488.1	487.8
145°	511.0	510.3	509.6	509.0	508.3	506.7	505.1	503.4	501.8	501.0	501.1
147.5°	523.6	523.1	522.6	522.2	521.7	520.1	518.5	516.8	515.2	514.4	514.5
150°	535.5	535.0	534.4	533.9	533.3	531.8	530.2	528.7	527.2	526.4	526.7
152.5°	546.3	545.7	545.2	544.6	544.0	542.6	541.2	539.7	538.3	537.6	538.0
155°	555.7	555.2	554.6	554.1	553.5	552.3	551.2	550.0	548.9	548.3	548.7
157.5°	564.3	563.6	562.9	562.3	561.6	560.8	559.9	559.1	558.2	557.8	558.2
160°	571.2	570.6	570.1	569.5	568.9	568.3	567.7	567.2	566.6	566.3	566.6
162.5°	578.1	577.4	576.7	576.1	575.4	574.9	574.4	573.9	573.4	573.2	573.5
165°	583.2	582.5	581.8	581.2	580.5	580.2	579.9	579.6	579.3	579.2	579.5
167.5°	588.0	587.3	586.6	586.0	585.3	585.0	584.7	584.4	584.1	584.0	584.3
170°	591.4	590.7	590.0	589.4	588.7	588.5	588.3	588.1	587.9	587.8	588.1
172.5°	594.0	593.3	592.6	592.0	591.3	591.1	590.9	590.7	590.5	590.4	590.7
175°	595.7	595.0	594.3	593.7	593.0	592.8	592.6	592.4	592.2	592.1	592.4
177.5°	596.1	595.4	594.7	594.1	593.4	593.3	593.2	593.1	593.0	593.0	593.3
180°	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8	593.8

TEST NUMBER: P1029369

CATALOG NUMBER: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

CANDELA DISTRIBUTION (continued):

	345°	350°	355°	360°
0°	572.0	572.0	572.0	572.0
2.5°	561.4	561.4	568.0	575.1
5°	549.1	552.2	562.8	572.4
7.5°	537.3	542.5	555.7	568.0
10°	522.8	529.8	546.1	560.6
12.5°	508.7	515.3	534.2	550.5
15°	488.9	497.3	517.5	537.7
17.5°	469.1	477.5	502.1	525.8
20°	445.8	456.8	484.5	516.2
22.5°	424.3	437.9	468.7	494.2
25°	400.5	421.6	450.2	483.2
27.5°	379.4	400.5	429.5	463.0
30°	355.7	377.2	407.1	437.9
32.5°	332.8	352.6	381.6	419.4
35°	309.1	328.0	356.1	394.4
37.5°	287.5	306.0	336.8	372.0
40°	266.4	285.8	312.2	347.3
42.5°	246.6	263.8	287.5	322.7
45°	228.6	240.9	262.9	295.9
47.5°	209.7	220.7	240.9	273.9
50°	192.1	201.4	219.0	249.7
52.5°	175.0	182.9	199.2	223.8
55°	159.6	167.1	178.9	203.1
57.5°	143.8	149.5	160.9	180.3
60°	128.4	133.7	142.9	158.7
62.5°	113.0	117.4	126.2	138.9
65°	99.4	102.9	109.5	120.5
67.5°	86.2	88.4	93.6	102.4
70°	73.4	75.2	79.6	86.6
72.5°	59.8	61.6	66.4	71.2
75°	48.4	48.8	52.3	56.3
77.5°	37.8	37.4	40.0	43.1
80°	25.9	27.3	29.5	30.8
82.5°	17.6	18.0	18.9	19.8
85°	9.7	10.1	10.1	11.4
87.5°	4.0	4.4	4.4	4.8
90°	3.6	2.5	1.5	0.4
92.5°	9.6	9.9	10.3	10.7
95°	18.5	21.6	24.8	27.9
97.5°	26.8	34.6	42.5	50.3
100°	36.8	49.9	63.0	76.1
102.5°	103.9	104.0	104.2	104.4
105°	139.2	136.3	133.5	130.6
107.5°	168.3	165.9	163.5	161.1
110°	196.4	194.4	192.4	190.4

TEST NUMBER: P1029369

CATALOG NUMBER: S122DIW-B290D435UB2750-4F0-XX-W2A-A_4000K

CANDELA DISTRIBUTION (continued):

	345°	350°	355°	360°
112.5°	223.0	221.3	219.6	217.9
115°	252.0	250.3	248.7	247.1
117.5°	278.1	276.2	274.3	272.4
120°	305.1	303.6	302.2	300.8
122.5°	329.4	327.9	326.4	324.9
125°	353.0	351.8	350.5	349.3
127.5°	375.7	374.4	373.0	371.7
130°	397.3	395.8	394.2	392.7
132.5°	417.9	416.7	415.4	414.2
135°	436.9	435.4	433.8	432.3
137.5°	454.6	453.5	452.3	451.2
140°	472.0	471.2	470.5	469.7
142.5°	487.1	486.4	485.8	485.1
145°	501.2	501.3	501.4	501.5
147.5°	514.8	515.1	515.3	515.6
150°	527.4	528.1	528.7	529.4
152.5°	538.7	539.5	540.2	541.0
155°	549.6	550.5	551.3	552.2
157.5°	558.9	559.7	560.4	561.2
160°	567.2	567.7	568.3	568.9
162.5°	574.1	574.6	575.2	575.8
165°	580.1	580.6	581.2	581.8
167.5°	584.8	585.4	585.9	586.5
170°	588.7	589.2	589.8	590.4
172.5°	591.3	591.8	592.4	593.0
175°	593.1	593.8	594.4	595.1
177.5°	594.0	594.7	595.3	596.0
180°	593.8	593.8	593.8	593.8

(END OF REPORT)